

## [edit system services dhcp-local-server] Hierarchy Level

---

```
dhcp-local-server {
  authentication {
    password password-string;
    username-include {
      circuit-type;
      delimiter delimiter-character;
      domain-name domain-name-string;
      logical-system-name;
      mac-address;
      option-60;
      option-82 <circuit-id> <remote-id>;
      routing-instance-name;
      user-prefix user-prefix-string;
    }
  }
  dynamic-profile profile-name (aggregate-clients | use-primary primary-profile-name);
  group group-name {
    authentication {
      password password-string;
      username-include {
        circuit-type;
        delimiter delimiter-character;
        domain-name domain-name-string;
        logical-system-name;
        mac-address;
        option-60;
        option-82 <circuit-id> <remote-id>;
        overrides;
        routing-instance-name;
        user-prefix user-prefix-string;
      }
    }
    dynamic-profile profile-name (aggregate-clients | use-primary
      primary-profile-name);
    interface interface-name [upto upto-interface-name] [exclude];
    overrides {
      interface-client-limit number;
      no-arp;
    }
  }
  overrides {
    interface-client-limit number;
    no-arp;
  }
  pool-match-order {
    ip-address-first;
    option-82;
  }
  traceoptions {
```

```
file filename <files number> <size size> <world-readable | no-world-readable>  
<match regex>;  
flag flag;  
}  
}
```