

## Using Matching Option 60 Strings to Process DHCP Client Traffic

---

Configuring option 60 support helps you manage multivendor networks by enabling the extended DHCP relay agent to compare option 60 vendor-specific strings received in DHCP client packets against a list of ASCII or hexadecimal strings that you configure on the router.

You can configure exact match or partial match criteria for option 60 string-to-DHCP server mapping and specify either the `ascii` statement (to define a nonempty ASCII match string of 1 through 255 alphanumeric characters) or the `hexadecimal` statement (to define a hexadecimal match string of 1 through 255 hexadecimal characters [0 through 9, a through f, A through F]).

When you configure a partial match, the option 60 string can contain a superset of the configured ASCII or hexadecimal string, provided that the leftmost characters of the option 60 string entirely match the characters in the configured match string. For a partial match, the longest match rule applies. For example, the extended DHCP relay agent matches the string “test123” before it matches the string “test”.

If the option 60 string received in the DHCP client packet matches the configured ASCII or hexadecimal string, you can define one of the following actions for the associated DHCP client packets:

- Relay client traffic to a group of specific DHCP relay servers that provide the requested client service.

The DHCP client packet is relayed to all of the servers in the specified group that map to the vendor class identifier information provided in the option 60 string. To configure the named group of DHCP relay servers, which are also referred to as vendor-option servers, include the `server-group` statement at the `[edit forwarding-options dhcp-relay]` hierarchy level, as described in [Configuring Server Groups](#).

The following additional considerations apply when you configure an ASCII or hexadecimal match string:

- You can configure the same ASCII or hexadecimal match string as both an exact (`equals`) match and as a partial (`starts-with`) match. In that case, the exact string match configured with the `equals` statement takes precedence over the partial string match configured with the `starts-with` statement.
- A server group can contain multiple server addresses and can map to more than one match string.
- You can configure an unlimited number of match strings.
- The use of wildcard attributes in match strings is not supported.
- Forward client traffic to a specific extended DHCP local server.
- Drop (discard) the packets. Specifying that certain DHCP client packets be dropped can be useful when DHCP clients request services that are invalid or no longer supported.

1. To configure match criteria:

- To specify an exact, left-to-right match of the configured match string with the option 60 string, use the **vendor-option equals** statement:

- To specify a nonempty ASCII match string.

```
[edit forwarding-options dhcp-relay relay-option-60]
user@host# set vendor-option equals ascii video55
```

- To specify a hexadecimal match string.

```
[edit forwarding-options dhcp-relay relay-option-60]
user@host# set vendor-option equals hexadecimal ff
```

- To specify a partial match of the configured match string with the option 60 string, use the **vendor-option starts-with** statement:

- To specify a partial ASCII match string.

```
[edit forwarding-options dhcp-relay relay-option-60]
user@host# set vendor-option starts-with ascii video
```

- To specify a partial hexadecimal match string.

```
[edit forwarding-options dhcp-relay relay-option-60]
user@host# set vendor-option starts-with hexadecimal ff
```

2. To configure the action to take when the DHCP client packet matches the configured ASCII or hexadecimal string:

- To relay client traffic to a group of specific DHCP relay servers that provide the requested client service.

```
[edit forwarding-options dhcp-relay relay-option-60 vendor-option equals ascii
video55]
user@host# set relay-server-group
```

The DHCP client packet is relayed to all of the servers specified in the **server-group** statement at the [edit forwarding-options dhcp-relay] hierarchy level that map to the vendor class identifier information provided in the option 60 string.

- To forward client traffic to a specific extended DHCP local server.

```
[edit forwarding-options dhcp-relay relay-option-60 vendor-option equals ascii
video55]
user@host# set local-server-group
```

To configure an extended DHCP local server, include the **dhcp-local-server** statement at the [edit system services] hierarchy level. For information about configuring and using the extended DHCP local server, see [Configuring the Extended DHCP Local Server](#) .

- To drop (discard) the packets:

```
[edit forwarding-options dhcp-relay relay-option-60 vendor-option equals ascii
video55]
user@host# set drop
```

For configuration examples that illustrate how to use matching option 60 strings to forward or drop DHCP client traffic, see [Example: Using Option 60 Strings to Forward DHCP Client Traffic](#) and [Example: Using Option 60 Strings to Drop DHCP Client Traffic](#).

