

## [edit ethernet-switching-options] Configuration Statement Hierarchy

---

```
ethernet-switching-options {
  analyzer {
    name {
      loss-priority priority;
      ratio number;
      input {
        ingress {
          interface (all | interface-name);
          vlan (vlan-id | vlan-name);
        }
        egress {
          interface (all | interface-name);
        }
      }
      output {
        interface interface-name;
        vlan (vlan-id | vlan-name);
      }
    }
  }
  bpdu-block {
    interface (all | [interface-name]);
    disable-timeout timeout;
  }
  dot1q-tunneling {
    ether-type (0x8100 | 0x88a8 | 0x9100)
  }
  redundant-trunk-group {
    group-name name {
      interface interface-name <primary>;
    }
  }
  secure-access-port {
    dhcp-snooping-file {
      location local_pathname | remote_URL;
      timeout seconds;
      write-interval seconds;
    }
    interface (all | interface-name) {
      allowed-mac {
        mac-address-list;
      }
      (dhcp-trusted | no-dhcp-trusted );
      mac-limit limit action action;
      no-allowed-mac-log;
      static-ip ip-address {
        vlan vlan-name;
        mac mac-address;
      }
    }
  }
}
```

```

vlan (all | vlan-name) {
  (arp-inspection | no-arp-inspection );
  dhcp-option82 {
    circuit-id {
      prefix hostname;
      use-interface-description;
      use-vlan-id;
    }
    remote-id {
      prefix hostname | mac | none;
      use-interface-description;
      use-string string;
    }
    vendor-id [string];
  }
  (examine-dhcp | no-examine-dhcp );
  (ip-source-guard | no-ip-source-guard);
  mac-move-limit limit action action;
}
}
storm-control {
  interface (all | interface-name) {
    level level;
    no-broadcast;
    no-unknown-unicast;
  }
}
traceoptions {
  file filename <files number> <no-stamp> <replace> <size size> <world-readable
  | no-world-readable>;
  flag flag <disable>;
}
unknown-unicast-forwarding {
  vlan (all | vlan-name) {
    interface interface-name;
  }
}
}
voip {
  interface (all | [interface-name | access-ports]) {
    vlan vlan-name ;
    forwarding-class <assured-forwarding | best-effort | expedited-forwarding |
    network-control>;
  }
}
}
}

```

- Related Topics**
- Port Mirroring on EX-series Switches Overview
  - Port Security for EX-series Switches Overview
  - Understanding 802.1X and VoIP on EX-series Switches
  - Understanding Redundant Trunk Links on EX-series Switches
  - Understanding Storm Control on EX-series Switches

- Understanding 802.1X and VoIP on EX-series Switches
- Understanding Q-in-Q Tunneling on EX-series Switches
- Understanding Unknown Unicast Forwarding on EX-series Switches

