

Chapter 21

Summary of the Interprovider and Carrier-of-Carriers VPNs Configuration Statements

The following section explains the configuration statements that apply specifically to hierarchical and recursive Border Gateway Protocol (BGP) and Multiprotocol Label Switching (MPLS) virtual private networks (VPNs).

labeled-unicast

Syntax	<pre>labeled-unicast { per-group-label; resolve-vpn; traffic-statistics { file <i>file-name</i> <world-readable no-world-readable>; interval <i>seconds</i>; } }</pre>
Hierarchy Level	[edit logical-routers <i>logical-router-name</i> protocols bgp family inet], [edit logical-routers <i>logical-router-name</i> protocols bgp group <i>group-name</i> family inet], [edit protocols bgp family inet], [edit protocols bgp group <i>group-name</i> family inet]
Description	Advertise labeled routes from the inet.0 VPN, and place labeled routes into the inet.0 VPN. When the labeled-unicast statement is used, the local router automatically performs a next hop to self on all routes advertised into the external BGP (EBGP) from the internal BGP (IBGP) and from IBGP to EBGP.
Options	resolve-vpn —(Optional) Store labeled routes in the inet.3 table to resolve routes for a provider edge (PE) router located in a different autonomous system (AS). For a PE router to install a route in the VPN routing and forwarding (VRF) table, the next hop must resolve to a route stored in the inet.3 table. The other statements are explained separately.
Usage Guidelines	See “Configuring Interprovider and Carrier-of-Carriers VPNs” on page 385.
Required Privilege Level	routing—To view this statement in the configuration. routing-control—To add this statement to the configuration.

per-group-label

Syntax	per-group-label;
Hierarchy Level	[edit logical-routers <i>logical-router-name</i> protocols bgp family inet labeled-unicast], [edit logical-routers <i>logical-router-name</i> protocols bgp group <i>group-name</i> family inet labeled-unicast], [edit protocols bgp family inet labeled-unicast], [edit protocols bgp group <i>group-name</i> family inet labeled-unicast]
Description	Account for traffic from each customer separately by advertising separate labels for the same prefix to the peer routers in the BGP groups.
Usage Guidelines	See “Configuring BGP to Gather Interprovider and Carrier-of-Carriers VPNs Statistics” on page 406.
Required Privilege Level	routing—To view this statement in the configuration. routing-control—To add this statement to the configuration.

traffic-statistics

Syntax	traffic-statistics { file <i>file-name</i> <world-readable no-world-readable>; interval <i>seconds</i> ; }
Hierarchy Level	[edit logical-routers <i>logical-router-name</i> protocols bgp family inet labeled-unicast], [edit logical-routers <i>logical-router-name</i> protocols bgp group <i>group-name</i> family inet labeled-unicast], [edit protocols bgp family inet labeled-unicast], [edit protocols bgp group <i>group-name</i> family inet labeled-unicast]
Description	Enable the collection of traffic statistics for interprovider or carrier-of-carriers VPNs.
Options	file <i>file-name</i> —Specify a filename for the BGP labeled-unicast traffic statistics file. If you do not specify a filename, statistics are still collected but can only be viewed by using the show bgp group traffic statistics <i>group-name</i> command. interval <i>seconds</i> —Specify how often BGP labeled-unicast traffic statistics are collected.
Usage Guidelines	See “Configuring BGP to Gather Interprovider and Carrier-of-Carriers VPNs Statistics” on page 406.
Required Privilege Level	routing—To view this statement in the configuration. routing-control—To add this statement to the configuration.