

You can configure STRM to log and correlate events received from external sources such as security equipment (for example, firewalls), and network equipment (for example, switches and routers). Device Support Modules (DSMs) enable you to integrate STRM with these external devices.

To install a DSM:

- Download the file to your STRM console.
- Log in to STRM as root.
- Navigate to the directory that includes the downloaded file.
- Enter the following command:

```
rpm -Uvh <filename>
```

Where <filename> is the name of the downloaded file.

For example:

```
DSM-6.1-NetScreenFirewall-4.0-7.i386.rpm
```

- Log in to the STRM interface.
- <https://<IP Address>>

Where <IP Address> is the IP address of the STRM system. The default username and password are:

Username: admin

Password: [original root password]

- In the main STRM interface, click Config.
- From the menu, select Configurations // Deploy configuration changes.

For more information, please refer to the follow DSM documentation:

[Configuring DSMS](#)

Copyright © 2008, Juniper Networks, Inc. All rights reserved. Juniper Networks, the Juniper Networks logo, NetScreen, and ScreenOS are registered trademarks of Juniper Networks, Inc. in the United States and other countries. JUNOS and JUNOSe are trademarks of Juniper Networks, Inc. All other trademarks, service marks, registered trademarks, or registered service marks are the property of their respective owners. Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.