



ISDN BRI S/T PIM

Product Overview

The Juniper Networks single-port ISDN Basic Rate Interface (BRI) S/T Physical Interface Module (PIM) for the Juniper Networks SSG140 Secure Services Gateway, complements the 10 onboard Ethernet interfaces with expanded WAN connectivity.

Product Description

The Juniper Networks® single-port ISDN BRI S/T PIM provides the physical connection to ISDN network media types receiving incoming packets from the network and transmitting outgoing packets to the network. The single-port ISDN BRI S/T PIM forwards packets for processing while performing framing and line-speed signaling. The ISDN BRI PIM includes a single physical port supporting ISDN BRI S/T interface types. For ISDN U interface support, an external NT-1 is required.

Features and Benefits

- Dial-backup on demand
- Multilink Point-to-Point Protocol (MLPPP) over two ISDN B-channels
- Bandwidth on demand
- Complete configuration and management by command-line interface (CLI), Web user interface, or Juniper Networks Network and Security Manager (NSM)

Specifications

Interface Connector

- 1 x RJ-45

Dimensions (W x H x D) and Weight

- 5.45 x 0.63 x 6.5 in (13.8 x 1.6 x 16.5 cm)

Environmental

- Operating temperature: 32° to 104° F (0° to 40° C)
- Storage temperature: -40° to 158° F (-40° to 70° C)
- Relative humidity: 5% to 90% noncondensing

LEDs

PIM LEDs indicate port status with the following LED states:

- Status
 - Green: Online with no alarms or failures.
 - Red: Active with a local alarm, router has detected a failure
- CH1 - Channel 1: Green - Channel B1 is active
- CH2 - Channel 2: Green - Channel B2 is active

Standards and Compliance

Safety

- CAN/CSA-C22.2 No. 60950-1-03/UL 60950-1 Third Edition, Safety of Information Technology Equipment
- EN 60950-1:2001+A11, Safety of Information Technology Equipment
- IEC 60950-1:2001 First Edition, Safety of Information Technology Equipment

EMC (Emissions)

- FCC Part 15 Class B (USA)
- EN 55022 Class B (Europe)
- AS 3548 Class B (Australia)
- VCCI Class B (Japan)
- BSMI Class B (Taiwan)

Immunity

- EN 55024
- EN-61000-4-2 ESD
- EN-61000-4-3 Radiated Immunity
- EN-61000-4-4 EFT
- EN-61000-4-5 Surge
- EN-61000-4-6 Low Frequency Common Immunity
- EN-61000-4-11 Voltage Dips and Sags

European Telecommunications Standardization Institute (ETSI)

- ETSI EN-300386-2: Telecommunication Network Equipment Electromagnetic Compatibility Requirements

Telecom

- FCC Part 68/TIA-968
- IC CS-03

Standards

ITU Standards: Compliance with ITU Standards

- Layer 1: ITU-T I.430
- Layer 2: ITU-T Q.920, ITU-T Q.921: LAPD
- Layer 3: ITU-T I.450, ITU-T I.451

ISDN Protocols: Support for the Following ISDN Protocols

- att5e – AT&T switch variant
- etsi – European Telecommunications Standards Institute switch variant
- ni1 – National ISDN 1 switch variant
- ntdms-100 – Northern Telecom DMS-100
- ntt – NTT Group switch for Japan

Juniper Networks Services and Support

Juniper Networks is the leader in performance-enabling services that are designed to accelerate, extend, and optimize your high-performance network. Our services allow you to maximize operational efficiency while reducing costs and minimizing risk, achieving a faster time to value for your network. Juniper Networks ensures operational excellence by optimizing the network to maintain required levels of performance, reliability, and availability. For more details, please visit www.juniper.net/us/en/products-services.

Ordering Information

Model Number	Description
JX-1BRI-ST-S	1-port ISDN S/T BRI Physical Interface Module

The ISDN Mini-PIMs are supported in Juniper Networks ScreenOS® Software 5.4 or higher on the SSG140.

About Juniper Networks

Juniper Networks is in the business of network innovation. From devices to data centers, from consumers to cloud providers, Juniper Networks delivers the software, silicon and systems that transform the experience and economics of networking. The company serves customers and partners worldwide. Additional information can be found at www.juniper.net.

Corporate and Sales Headquarters

Juniper Networks, Inc.
1194 North Mathilda Avenue
Sunnyvale, CA 94089 USA
Phone: 888.JUNIPER (888.586.4737)
or 408.745.2000
Fax: 408.745.2100
www.juniper.net

APAC Headquarters

Juniper Networks (Hong Kong)
26/F, Cityplaza One
1111 King's Road
Taikoo Shing, Hong Kong
Phone: 852.2332.3636
Fax: 852.2574.7803

EMEA Headquarters

Juniper Networks Ireland
Airside Business Park
Swords, County Dublin, Ireland
Phone: 35.31.8903.600
EMEA Sales: 00800.4586.4737
Fax: 35.31.8903.601

To purchase Juniper Networks solutions, please contact your Juniper Networks representative at 1-866-298-6428 or authorized reseller.

Copyright 2011 Juniper Networks, Inc. All rights reserved. Juniper Networks, the Juniper Networks logo, Junos, NetScreen, and ScreenOS are registered trademarks of Juniper Networks, Inc. in the United States and other countries. All other trademarks, service marks, registered marks, or registered service marks are the property of their respective owners. Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.