

Release Notes: Juniper Identity Management Service 1.1.4

Release 1.1.4
31 January 2019
Revision 1

Contents	
Introduction	2
Features	2
Specifications	3
System Requirements	4
Supported Identity Sources	5
Changes in Behavior and Syntax	5
Known Behavior	5
Known Issues	5
Resolved Issues	5
Requesting Technical Support	5
Self-Help Online Tools and Resources	6
Creating a Service Request with JTAC	6
Revision History	6

Introduction

This release note accompanies Juniper® Identity Management Service Release 1.1.4. It describes the product and its known behavior, problems, and limitations.

Juniper Identity Management Service (for Windows) is a standalone Windows service application that collects and maintains a large database of user, device, and group information from Active Directory domains, enabling SRX Series firewalls to rapidly identify thousands of users in a large, distributed enterprise. SRX Series Service Gateways can create, manage, and refine firewall rules that are based on user identity rather than IP address, query Juniper Identity Management Service, obtain the proper user identity information, and then enforce the appropriate security policy decisions to permit or deny access to protected corporate resources and the Internet.

Features

The following features are new in Juniper Identity Management Service (JIMS) v1.1:

- **Contrail Service Orchestrator (CSO) Integration**—If your network environment uses Contrail Service Orchestration (CSO), Juniper Identity Management Service supports operation with each CSO to facilitate the handling of firewall security policy decisions between the CSO platform and SRX Series devices by providing domain, group, user, and device identity information from Active Directory domains to each CSO. Juniper Identity Management Service is available as a standalone product or as an integrated identity management service from within Contrail Service Orchestration (CSO)

CSO is deployed in the cloud, and the tenant infrastructure includes the tenant premises behind a firewall and cannot directly access Microsoft Active Directory in the customer's domain. Juniper Identity Management Service acts as the communication layer between identity servers such as Microsoft Active Directory and the CSO platform. Juniper Identity Management Service assists CSO in making policy user firewall decisions to filter traffic on SRX Series devices in a distributed deployment by providing user, device, and group identity information from the Active Directory domains to each CSO.

All communication between Juniper Identity Management Service and CSO is initiated by the JIMS server. Upon startup, or configuring or updating CSO, the JIMS server initiates HTTPS connection to each fully configured CSO. The information exchange between Juniper Identity Management Service and each fully configured CSO is secure, live, and allows for a full resynchronization at any point in the data collection process.

[See [Introduction](#) and [Configuring the Connection to a CSO Client](#).]

- **Templates**—You can develop one or more templates in Juniper Identity Management Service:
 - SRX Series Device Templates—Support the grouping of client configurations to facilitate the configuration of multiple SRX Series devices.
 - Data Source Templates—Support the grouping of event or information source configurations to facilitate the configuration of a specific data source.

A template is a way to share common configuration attributes across items within a homogeneous collection without having to re-enter those attributes for each configuration instance. Templates allow configurations to share common data. A template provides default settings that can be referenced to create an instance.

For example, when using an SRX series device template, you can specify a username and password in a template, and assign that template across all SRX Series devices that require the same login credentials. Utilizing a template allows you to copy the configuration and only re-enter the password for the specific template.

[See [Configuring SRX Series Device Templates](#) and [Configuring Data Source Templates](#).]

- **User/Device Event Filters**—Event filters on the JIMS server enable you to apply a filter in your network to define users or devices to *exclude* from reports the JIMS server sends to SRX Series devices. The User/Device Event filter performs regular expression matching to filter specific users or devices by name. The filter ignores events associated with a particular user or device.

[See [Configuring Event and Group Filters](#).]

- **Support IPv6 Reports**—The JIMS server allows IPv6-related report information to pass from the JIMS server to SRX Series devices.



NOTE: SRX Series devices must be running the Junos OS 18.1R1 release, or a later release, to receive IPv6 reports.

[See [Configuring the Connection to an SRX Series Device](#).]

- **Processing Events**—On startup, the JIMS server now attempts to learn all groups and then all users from the user directories before processing events. If the learn procedure takes more than 90 seconds, the JIMS server will begin to process events for users which have already been learned. For a domain that is still learning, an event may continue to wait up to 4 minutes for a particular user to be read before the JIMS server begins executing parallel queries in an attempt to process the event.

Specifications

Table 1: SRX and JIMS Server Requirements and Specifications

Component	Operating System and Kernel Versions
Supported Junos OS software releases	<ul style="list-style-type: none"> • 15.1X49-D160.2, 17.4R3, or a later release • 12.3X48-D45 or a later release
Supported SRX Series device platforms	<ul style="list-style-type: none"> • vSRX Virtual Firewall, SRX300 line, SRX1500, SRX4100, SRX4200, SRX5000 line (Junos OS Release 15.1X49-D160.2, 17.4R3, or a later release) • SRX650, SRX240H2, SRX3000 line, and SRX5000 line (Junos OS Release 12.3X48-D45 or a later release)

Table 1: SRX and JIMS Server Requirements and Specifications (continued)

Component	Operating System and Kernel Versions
Supported Contrail Service Orchestration (CSO) release	Release 4.0.1 or later NOTE: If your network deployment includes Contrail Service Orchestration (CSO), JIMS 1.1.4 is currently certified for use only with the upcoming CSO 4.0.1 release or later. Please see Contrail Service Orchestration Documentation to determine which SRX releases are used with specific releases of CSO.
Maximum SRX Series devices	100
Maximum CSO platforms	10
Maximum event log sources	150
Maximum Active Directories	100
Maximum domains	25
Maximum user entries	500,000

System Requirements

Juniper Identity Management Service can be installed on the following Microsoft Windows platforms:

- Windows Server 2016
- Windows Server 2012 R2 with Windows Server 2012 R2 Updates (KB2919355 and KB2999226)
- Windows Server 2008 R2 with Service Pack 1 (SP1) and Update for Windows Server 2008 R2 x64 Edition (KB3140245)



NOTE: Windows Server 2008 R2 with SP1 also requires installation of an update that provides support for Transport Layer Security (TLS) 1.1 and TLS 1.2. See [Update to enable TLS 1.1 and TLS 1.2 as a default secure protocols in WinHTTP in Windows](#) for details. After you apply the update, select **Run as administrator** to restart the JIMS Administrative Interface.



BEST PRACTICE: Note the following best practices when installing Juniper Identity Management Service on a Microsoft Windows platform:

- Because Juniper Identity Management Service participates in the security infrastructure protecting your network, we recommend using Windows

Update regularly and judiciously to obtain the latest Security Updates and other Critical Updates from Microsoft.

- Juniper Identity Management Service requires a server with a 4-core, 64-bit compatible 1.4 GHz or higher CPU, a minimum of 16 GB of system memory, and 100 GB of disk space.
- If using Windows Server 2008 R2, avoid installation on a primary domain controller (PDC). Juniper Identity Management Service should be installed in a separate, non-domain controller instance.

Supported Identity Sources

Juniper Identity Management Service supports the following identity sources:

- Microsoft Active Directory on Windows Server 2008 R2 and later
- Microsoft Exchange Server 2010 with Service Pack 3 (SP3)

Changes in Behavior and Syntax

This section lists the changes in behavior of JIMS features and changes from Juniper Identity Management Service (JIMS) v1.1.4.

- Starting in JIMS Release 1.1.4, JIMS blocks the event log reading for up to 900 seconds if there is at least one Info Source in the learning state.

[See [Viewing Event Log Source Status](#).]

Known Behavior

There are no known limitations for Juniper Identity Management Service in JIMS Release 1.1.4.

Known Issues

There are no known issues for Juniper Identity Management Service in JIMS Release 1.1.4.

Resolved Issues

There are no resolved issues for Juniper Identity Management Service in JIMS Release 1.1.4.

Requesting Technical Support

Technical product support is available through the Juniper Networks Technical Assistance Center (JTAC). If you are a customer with an active J-Care or Partner Support Service support contract, or are covered under warranty, and need post-sales technical support, you can access our tools and resources online or open a case with JTAC.

- JTAC policies—For a complete understanding of our JTAC procedures and policies, review the *JTAC User Guide* located at <https://www.juniper.net/us/en/local/pdf/resource-guides/7100059-en.pdf>.
- Product warranties—For product warranty information, visit <http://www.juniper.net/support/warranty/>.
- JTAC hours of operation—The JTAC centers have resources available 24 hours a day, 7 days a week, 365 days a year.

Self-Help Online Tools and Resources

For quick and easy problem resolution, Juniper Networks has designed an online self-service portal called the Customer Support Center (CSC) that provides you with the following features:

- Find CSC offerings: <https://www.juniper.net/customers/support/>
- Search for known bugs: <https://prsearch.juniper.net/>
- Find product documentation: <https://www.juniper.net/documentation/>
- Find solutions and answer questions using our Knowledge Base: <https://kb.juniper.net/>
- Download the latest versions of software and review release notes: <https://www.juniper.net/customers/csc/software/>
- Search technical bulletins for relevant hardware and software notifications: <https://kb.juniper.net/InfoCenter/>
- Join and participate in the Juniper Networks Community Forum: <https://www.juniper.net/company/communities/>
- Create a service request online: <https://myjuniper.juniper.net>

To verify service entitlement by product serial number, use our Serial Number Entitlement (SNE) Tool: <https://entitlementsearch.juniper.net/entitlementsearch/>

Creating a Service Request with JTAC

You can create a service request with JTAC on the Web or by telephone.

- Visit <https://myjuniper.juniper.net>.
- Call 1-888-314-JTAC (1-888-314-5822 toll-free in the USA, Canada, and Mexico).

For international or direct-dial options in countries without toll-free numbers, see <https://support.juniper.net/support/requesting-support/>.

Revision History

31 January 2019—Revision 1—Juniper Identity Management Service Release 1.1.4

Copyright © 2019 Juniper Networks, Inc. All rights reserved.

Juniper Networks, the Juniper Networks logo, Juniper, and Junos are registered trademarks of Juniper Networks, Inc. and/or its affiliates in the United States and other countries. All other trademarks may be property of their respective owners.

Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.