

## always-write-giaddr

---

**Syntax**    always-write-giaddr;

**Hierarchy Level**    [edit forwarding-options dhcp-relay overrides],  
[edit forwarding-options dhcp-relay group *group-name* overrides],  
[edit logical-systems *logical-system-name* forwarding-options dhcp-relay overrides],  
[edit logical-systems *logical-system-name* forwarding-options dhcp-relay group *group-name* overrides],  
[edit logical-systems *logical-system-name* routing-instances *routing-instance-name* forwarding-options dhcp-relay overrides],  
[edit logical-systems *logical-system-name* routing-instances *routing-instance-name* forwarding-options dhcp-relay group *group-name* overrides],  
[edit routing-instances *routing-instance-name* forwarding-options dhcp-relay overrides],  
[edit routing-instances *routing-instance-name* forwarding-options dhcp-relay group *group-name* overrides]

**Release Information**    Statement introduced in JUNOS Release 8.3.

**Description**    Overwrite the gateway IP address (giaddr) of every DHCP packet with the giaddr of the DHCP relay agent before forwarding the packet to the DHCP server.

**Required Privilege Level**    interface—To view this statement in the configuration.  
interface-control—To add this statement to the configuration.

**Related Topics**    ■    Extended DHCP Local Server Overview

