

## default-local-server-group

---

<b>Syntax</b>	default-local-server-group <i>local-server-group-name</i> ;
<b>Hierarchy Level</b>	[edit forwarding-options dhcp-relay relay-option-60 vendor-option], [edit forwarding-options dhcp-relay group <i>group-name</i> relay-option-60 vendor-option], [edit logical-systems <i>logical-system-name</i> forwarding-options dhcp-relay relay-option-60 vendor-option], [edit logical-systems <i>logical-system-name</i> forwarding-options dhcp-relay group <i>group-name</i> relay-option-60 vendor-option], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> forwarding-options dhcp-relay relay-option-60 vendor-option], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> forwarding-options dhcp-relay group <i>group-name</i> relay-option-60 vendor-option], [edit routing-instances <i>routing-instance-name</i> forwarding-options dhcp-relay relay-option-60 vendor-option], [edit routing-instances <i>routing-instance-name</i> forwarding-options dhcp-relay group <i>group-name</i> relay-option-60 vendor-option]
<b>Release Information</b>	Statement introduced in JUNOS Release 9.0.
<b>Description</b>	<p>Forward DHCP client packets to a default extended DHCP local server when you use the DHCP vendor class identifier option (option 60) in DHCP packets to forward client traffic to specific DHCP servers.</p> <p>If the option 60 string received in the DHCP client packet does not match the ASCII or hexadecimal match string and match criteria (exact match or partial match) that you specify, the extended DHCP relay agent forwards the client packets to the specified default DHCP local server group configured with the <code>dhcp-local-server</code> statement at the [edit system services] hierarchy level.</p>
<b>Options</b>	<i>local-server-group-name</i> —Name of the default extended DHCP local server group.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Topics</b>	■ Using Option 60 Information to Forward Client Traffic to Specific DHCP Servers

