

## default-relay-server-group

---

<b>Syntax</b>	default-relay-server-group <i>server-group-name</i> ;
<b>Hierarchy Level</b>	<p>[edit forwarding-options dhcp-relay relay-option-60 vendor-option], [edit forwarding-options dhcp-relay group <i>group-name</i> relay-option-60 vendor-option], [edit logical-systems <i>logical-system-name</i> forwarding-options dhcp-relay relay-option-60 vendor-option], [edit logical-systems <i>logical-system-name</i> forwarding-options dhcp-relay group <i>group-name</i> relay-option-60 vendor-option], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> forwarding-options dhcp-relay relay-option-60 vendor-option], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> forwarding-options dhcp-relay group <i>group-name</i> relay-option-60 vendor-option], [edit routing-instances <i>routing-instance-name</i> forwarding-options dhcp-relay relay-option-60 vendor-option], [edit routing-instances <i>routing-instance-name</i> forwarding-options dhcp-relay group <i>group-name</i> relay-option-60 vendor-option]</p>
<b>Release Information</b>	Statement introduced in JUNOS Release 9.0.
<b>Description</b>	<p>Relay DHCP client packets to a default group of extended DHCP relay servers when you use the DHCP vendor class identifier option (option 60) in DHCP packets to forward client traffic to specific DHCP servers.</p> <p>If the option 60 string received in the DHCP client packet does not match the ASCII or hexadecimal match string and match criteria (exact match or partial match) that you specify, the extended DHCP relay agent relays the client packets to the specified default group of servers configured with the server-group statement at the [edit forwarding-options dhcp-relay] hierarchy level.</p>
<b>Options</b>	<i>server-group-name</i> —Name of the default DHCP relay server group.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Topics</b>	■ Using Option 60 Information to Forward Client Traffic to Specific DHCP Servers

