

## mac-address

---

**Syntax**    mac-address;

**Hierarchy Level**    [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* system services dhcp-local-server authentication username-include],  
[edit logical-systems *logical-system-name* routing-instances *routing-instance-name* system services dhcp-local-server group *group-name* authentication username-include],  
[edit logical-systems *logical-system-name* system services dhcp-local-server authentication username-include],  
[edit logical-systems *logical-system-name* system services dhcp-local-server group *group-name* authentication username-include],  
[edit logical-systems *logical-system-name* routing-instances *routing-instance-name* system services dhcp-local-server authentication username-include],  
[edit logical-systems *logical-system-name* routing-instances *routing-instance-name* system services dhcp-local-server group *group-name* authentication username-include],  
[edit routing-instances *routing-instance-name* system services dhcp-local-server authentication username-include],  
[edit routing-instances *routing-instance-name* system services dhcp-local-server group *group-name* authentication username-include],  
[edit system services dhcp-local-server authentication username-include],  
[edit system services dhcp-local-server group *group-name* authentication username-include]

**Release Information**    Statement introduced in JUNOS Release 9.1.

**Description**    Specify that the MAC address from the client PDU is concatenated with the username during the subscriber authentication process.

**Required Privilege Level**    system—To view this statement in the configuration.  
system-control—To add this statement to the configuration.

**Related Topics**    ■    Using External AAA Authentication Services with DHCP

