

option-82

Syntax option-82 <circuit-id> <remote-id>;

Hierarchy Level [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* system services dhcp-local-server authentication username-include],
[edit logical-systems *logical-system-name* routing-instances *routing-instance-name* system services dhcp-local-server group *group-name* authentication username-include],
[edit logical-systems *logical-system-name* system services dhcp-local-server authentication username-include],
[edit logical-systems *logical-system-name* system services dhcp-local-server group *group-name* authentication username-include],
[edit logical-systems *logical-system-name* routing-instances *routing-instance-name* system services dhcp-local-server authentication username-include],
[edit logical-systems *logical-system-name* routing-instances *routing-instance-name* system services dhcp-local-server group *group-name* authentication username-include],
[edit routing-instances *routing-instance-name* system services dhcp-local-server authentication username-include],
[edit routing-instances *routing-instance-name* system services dhcp-local-server group *group-name* authentication username-include],
[edit system services dhcp-local-server authentication username-include],
[edit system services dhcp-local-server group *group-name* authentication username-include]

Release Information Statement introduced in JUNOS Release 9.1.

Description Specify the type of Option 82 information from the client PDU that is concatenated with the username during the subscriber authentication process. You can specify either, both, or neither of the Agent Circuit ID and Agent Remote ID suboptions. If you specify both, the Agent Circuit ID is supplied first, followed by a delimiter, and then the Agent Remote ID. If you specify that neither suboption is supplied, the raw payload of Option 82 from the PDU is concatenated to the username.

Options circuit-id—The string for the Agent Circuit ID suboption (suboption 1).

remote-id—The string for the Agent Remote ID suboption (suboption 2).

Required Privilege Level system—To view this statement in the configuration.
system-control—To add this statement to the configuration.

Related Topics ■ Using External AAA Authentication Services with DHCP

