

Juniper Networks VSAs Supported by the AAA Service Framework

Table 1 on page 1 describes Juniper Networks VSAs supported by the JUNOS software AAA Service Framework. The AAA Service Framework uses vendor ID 4874, which is assigned to Juniper Networks by the Internet Assigned Numbers Authority (IANA).

Table 1: Supported Juniper Networks VSAs

Attribute Number	Attribute Name	Description	Value
26-4	Primary-DNS	Client DNS address negotiated during IPCP	integer: 4-byte primary-dns-address
26-5	Secondary-DNS	Client DNS address negotiated during IPCP	integer: 4-byte secondary-dns-address
26-6	Primary-WINS	Client WINS (NBNS) address negotiated during IPCP	integer: 4-byte primary-wins-address
26-7	Secondary-WINS	Client WINS (NBNS) address negotiated during IPCP	integer: 4-byte secondary-wins-address
26-10	Ingress-Policy-Name	Input policy name to apply to client interface	string: input-policy-name
26-11	Egress-Policy-Name	Output policy name to apply to client interface	string: output-policy-name
26-12	Ingress-Statistics	Enable or disable input statistics on client interface	integer: ■ 0 = disable ■ 1 = enable
26-13	Egress-Statistics	Enable or disable output statistics on client interface	integer: ■ 0 = disable ■ 1 = enable
26-23	IGMP-Enable	Enable or disable IGMP on a client interface	integer: ■ 0 = disable ■ 1 = enable
26-34	Framed-IP-Route-Tag	Route tag to apply to returned framed-ip-address	integer: 4-octet
26-42	Input-Gigapackets	Number of times input-packets attribute rolls over its 4-octet field	integer

Table 1: Supported Juniper Networks VSAs (continued)

Attribute Number	Attribute Name	Description	Value
26-43	Output-Gigapackets	Number of times output-packets attribute rolls over its 4-octet field	integer
26-56	DHCP-MAC-Address	Client MAC address	string: mac-address
26-57	DHCP-GI-Address	DHCP relay agent IP address	integer: 4-octet
26-58	LI-Action	Traffic mirroring action	0 = stop mirroring 1 = start mirroring 2 = no action
26-59	Med-Dev-Handle	Link to which traffic mirroring is applied	Salt-encrypted string
26-60	MD-Ip-Address	IP address of content destination device to which mirrored traffic is forwarded	Salt-encrypted IP address
26-61	MD-Port-Number	UDP port in the content destination device to which mirrored traffic is forwarded	Salt-encrypted integer
26-63	Interface-Desc	Text string that identifies the subscriber's access interface	string: interface-description
26-65	Activate-Service	Service to activate for the subscriber	string: service-name
26-66	Deactivate-Service	Service to deactivate for the subscriber	string: service-name
26-71	IGMP-Access-Group-Name	Access List to use for the group (G) filter	string: 32-octet
26-72	IGMP-Access-Source-Group-Name	Access List to use for the source-group (S,G) filter	string: 32-octet
26-74	MLD-Access-Group-Name	Access List to use for the group (G) filter	string: 32-octet

Table 1: Supported Juniper Networks VSAs (continued)

Attribute Number	Attribute Name	Description	Value
26-75	MLD-Access-Source-Group-Name	Access List to use for the source-group (S,G) filter	string: 32-octet
26-77	MLD-Version	MLD Protocol Version	integer: 1-octet ■ 1 = MLD version ■ 2 = MLD version
26-78	IGMP-Version	IGMP Protocol Version	integer: 1-octet ■ 1 = IGMP version ■ 2 = IGMP version ■ 3 = IGMP version
26-83	Acct-Service-Session	Name of the service (including parameter values) that is associated with service manager statistics	string: service-name
26-84	Mobile-IP-Algorithm	Authentication algorithm used for Mobile-IP registration	integer: 4-octet
26-85	Mobile-IP-SPI	Security parameter index number for Mobile IP registration	integer: 4-octet
26-86	Mobile-IP-Key	Security association MD5 key for Mobile IP registration	string: key
26-87	Mobile-IP-Replay	Replay timestamp for Mobile IP registration	integer: 4-octet
26-89	Mobile-IP-Lifetime	Registration lifetime for Mobile IP registration	integer: 4-octet
26-97	IGMP-Immediate-Leave	IGMP Immediate Leave	integer: 4-octet ■ 0 = disable ■ 1 = enable
26-100	MLD-Immediate-Leave	MLD Immediate Leave	integer: 4-octet ■ 0 = disable ■ 1 = enable

Table 1: Supported Juniper Networks VSAs (continued)

Attribute Number	Attribute Name	Description	Value
26-108	CoS-Scheduler-Pmt-Type	<p>Tag (parameter type) value and parameter description:</p> <ul style="list-style-type: none"> ■ 1: CoS scheduler map name ■ 2: CoS shaping rate ■ 3: CoS guaranteed rate ■ 4: CoS delay-buffer rate 	<p>2 parts, delimited by white space:</p> <ul style="list-style-type: none"> ■ Parameter type ■ Parameter value
26-146	CoS-Scheduler-Pmt-Type	<p>Tag (parameter type) value and parameter description:</p> <ul style="list-style-type: none"> ■ Null: CoS scheduler name ■ 1: CoS scheduler transmit rate ■ 2: CoS scheduler buffer size ■ 3: CoS scheduler priority ■ 4: CoS scheduler drop-profile low ■ 5: CoS scheduler drop-profile medium-low ■ 6: CoS scheduler drop-profile medium-high ■ 7: CoS scheduler drop-profile high ■ 8: CoS scheduler drop-profile any 	<p>3 parts, delimited by white space:</p> <ul style="list-style-type: none"> ■ Scheduler name ■ Parameter type ■ Parameter value