

## Enabling a Trusted DHCP Server (J-Web Procedure)

---

You can configure any interface on the EX-series switch that connects to a DHCP server as a trusted interface (port). Configuring a DHCP server on a trusted interface protects against rogue DHCP servers sending leases.

You configure a trusted DHCP server on an interface, not on a VLAN. By default, all access interfaces are untrusted and all trunk interfaces are trusted.

To enable a trusted DHCP server on one or more interfaces by using the J-Web interface:

1. Select **Configure>Security>Port Security**.
2. Select one or more interfaces from the Port list.
3. Click the **Edit** button. If a message appears asking if you want to enable port security, click **Yes**.
4. Select the **Trust DHCP** check box and then click **OK**.
5. Click **OK** after the command has been successfully delivered.



**NOTE:** You can enable or disable port security on the switch at any time by clicking the **Activate** or **Deactivate** button on the Port Security Configuration page. If security status is shown as **Disabled** when you try to edit settings for any VLANs or interfaces (ports), the message asking if you want to enable port security appears.

- 
- Related Topics**
- Enabling a Trusted DHCP Server (CLI Procedure)
  - Example: Configuring Port Security, with DHCP Snooping, DAI, MAC Limiting, and MAC Move Limiting, on an EX-series Switch
  - Example: Configuring a DHCP Server Interface as Untrusted to Protect the Switch from Rogue DHCP Server Attacks
  - Verifying That a Trusted DHCP Server Is Working Correctly
  - Monitoring Port Security
  - Understanding Trusted DHCP Servers for Port Security on EX-series Switches

