

Example: Subscriber Secure Policy Dynamic Profile

In this example, subscriber secure policy mirroring is configured for subscriber access using user-defined variables and JUNOS predefined variables. This example is for the flow-tap service configured on a router without a Tunnel Services PIC.

The user-defined variables equate to RADIUS settings as follows:

User-Defined Variable Name	JUNOS Variable	RADIUS VSA Name	RADIUS Attribute Number	Example RADIUS Setting
ssp-intercept-id	\$ssp-intercept-id	Interception Identifier	26-59	subscriber-bg-2350
ssp-destination-addr	\$ssp-destination-addr	MD-IP-Address	26-60	192.163.100.22
ssp-destination-port	\$ssp-destination-port	MD-Port-Number	26-61	2222

```
variables {
    var ssp-intercept-id;
    var ssp-destination-addr;
    var ssp-destination-port;
}
interfaces {
    <*> {
        unit <*> {
            family inet {
                filter {
                    input ssp;
                    output ssp;
                }
            }
        }
    }
}
firewall {
    family inet {
        filter ssp {
            term $ssp-id {
                from {
                    # optional classifiers.
                }
                then {
                    flowtap-destination-address $ssp-destination-addr;
                    flowtap-destination-port $ssp-destination-port;
                    flowtap;
                }
            }
        }
    }
}
```

