

address

Syntax address *address* {
 arp *ip-address* (mac | multicast-mac) *mac-address* <publish>;
 broadcast *address*;
 [Unresolved xref] *address*;
 destination-profile *name*;
 eui-64;
 master-only;
 multipoint-destination *address* dlcidlcid-identifier;
 multipoint-destination *address* {
 [Unresolved xref] *cells*;
 inverse-arp;
 oam-liveness {
 up-count *cells*;
 down-count *cells*;
 }
 oam-period (disable | seconds);
 shaping {
 (cbr *rate* | rtvbr peak *rate* sustained *rate* burst *length* | vbr peak *rate* sustained
 rate burst *length*);
 queue-length *number*;
 }
 vci *vpi-identifier.vci-identifier*;
 }
 [Unresolved xref];
 preferred;
 (vrrp-group | vrrp-inet6-group) *group-number* {
 (accept-data | no-accept-data);
 advertise-interval *seconds*;
 authentication-type *authentication*;
 authentication-key *key*;
 fast-interval *milliseconds*;
 (preempt | no-preempt) {
 hold-time *seconds*;
 }
 priority-number *number*;
 track {
 priority-cost *seconds*;
 priority-hold-time *interface-name* {
 interface *priority*;
 bandwidth-threshold *bits-per-second* {
 priority;
 }
 }
 }
 route *ip-address/mask* routing-instance *instance-name* priority-cost *cost*;
 }
 virtual-address [*addresses*];
}

Hierarchy Level	[edit interfaces <i>interface-name</i> unit <i>logical-unit-number</i> family <i>family</i>], [edit logical-systems <i>logical-system-name</i> interfaces <i>interface-name</i> unit <i>logical-unit-number</i> family <i>family</i>]
Release Information	Statement introduced before JUNOS Release 7.4.
Description	Configure the interface address.
Options	<i>address</i> —Address of the interface. The remaining statements are explained separately.
Usage Guidelines	See Configuring the Protocol Family.
Required Privilege Level	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
Related Topics	negotiate-address, [Unresolved xref] , <i>JUNOS System Basics Configuration Guide</i>