

## destination-profile

---

<b>Syntax</b>	destination-profile <i>name</i> ;
<b>Hierarchy Level</b>	[edit interfaces <i>interface-name</i> unit <i>logical-unit-number</i> family inet address <i>address</i> ], [edit interfaces <i>interface-name</i> unit <i>logical-unit-number</i> family inet <a href="#">[Unresolved xref]</a> <i>interface-name</i> <a href="#">[Unresolved xref]</a> <i>address</i> ], [edit logical-systems <i>logical-system-name</i> interfaces <i>interface-name</i> unit <i>logical-unit-number</i> family inet address <i>address</i> ], [edit logical-systems <i>logical-system-name</i> interfaces <i>interface-name</i> unit <i>logical-unit-number</i> family inet <a href="#">[Unresolved xref]</a> <i>interface-name</i> <a href="#">[Unresolved xref]</a> <i>address</i> ]
<b>Release Information</b>	Statement introduced before JUNOS Release 7.4.
<b>Description</b>	For interfaces with PPP encapsulation, assign PPP properties to the remote end. You define the profile at the [edit access group-profile <i>name</i> ppp] hierarchy level.
<b>Options</b>	<i>name</i> —Profile name defined at the [edit access group-profile <i>name</i> ppp] hierarchy level.
<b>Usage Guidelines</b>	See Configuring IPCP Options.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Topics</b>	<a href="#">[Unresolved xref]</a> , <i>JUNOS System Basics Configuration Guide</i> .

