

group

Syntax `group group-name {`
 `active-server-group server-group-name;`
 `authentication {`
 `password password-string;`
 `username-include {`
 `circuit-type;`
 `delimiter delimiter-character;`
 `domain-name domain-name-string;`
 `logical-system-name;`
 `mac-address;`
 `option-60;`
 `option-82 [circuit-id] [remote-id];`
 `routing-instance-name;`
 `user-prefix user-prefix-string;`
 `}`
 `}`
 `dynamic-profile profile-name <aggregate-clients (merge | replace) |`
 `use-primary primary-profile-name>;`
 `overrides {`
 `always-write-giaddr;`
 `always-write-option-82;`
 `client-discover-match;`
 `interface-client-limit number;`
 `layer2-unicast-replies;`
 `no-arp;`
 `proxy-mode;`
 `trust-option-82;`
 `disable-relay;`
 `}`
 `relay-option-60 {`
 `vendor-option {`
 `(equals | starts-with) (ascii match-string | hexadecimal match-hex) {`
 `(default-relay-server-group server-group-name |`
 `default-local-server-group local-server-group-name |`
 `drop);`
 `}`
 `(default-relay-server-group server-group-name |`
 `default-local-server-group local-server-group-name |`
 `drop);`
 `}`
 `}`
 `relay-option-82 {`
 `circuit-id {`
 `prefix host-name logical-system-name routing-instance-name;`
 `}`
 `}`
 `interface interface-name [upto upto-interface-name] [exclude];`

}

Hierarchy Level	[edit forwarding-options dhcp-relay], [edit logical-systems <i>logical-system-name</i> forwarding-options dhcp-relay], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instance-name</i> forwarding-options dhcp-relay], [edit routing-instances <i>routing-instance-name</i> forwarding-options dhcp-relay]
Release Information	Statement introduced in JUNOS Release 8.3.
Description	<p>Specify the name of a group of interfaces that have a common DHCP relay agent configuration. A group must contain at least one interface.</p> <p>The statements configured at the [edit forwarding-options dhcp-relay group <i>group-name</i>] hierarchy level apply only to the named group of interfaces, and override any global DHCP relay agent settings configured with the same statements at the [edit forwarding-options dhcp-relay] hierarchy level.</p>
Options	<p><i>group-name</i>—Name of a group of interfaces that have a common DHCP relay agent configuration.</p> <p>The remaining statements are explained separately.</p>
Required Privilege Level	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
Related Topics	<ul style="list-style-type: none">■ Extended DHCP Relay Agent Overview■ Using External AAA Authentication Services with DHCP■ Attaching Dynamic Profiles to DHCP Subscriber Interfaces