

## home-agent

---

<b>Syntax</b>	<pre>home-agent {     nai (<i>name@domain</i>   <i>@domain</i>) {         home-agent <i>ip-address</i>;     } }</pre>
<b>Hierarchy Level</b>	[edit logical-systems <i>logical-system-name</i> services mobile-ip dynamic-home-assignment], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instances-name</i> services mobile-ip dynamic-home-assignment], [edit routing-instances <i>routing-instances-name</i> services mobile-ip dynamic-home-assignment], [edit services mobile-ip dynamic-home-assignment]
<b>Release Information</b>	Statement introduced in JUNOS Release 9.3. Support at the [edit logical-systems <i>logical-system-name</i> services mobile-ip dynamic-home-assignment], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instances-name</i> services mobile-ip dynamic-home-assignment], and [edit routing-instances <i>routing-instances-name</i> services mobile-ip dynamic-home-assignment] hierarchy levels added in JUNOS Release 9.5.
<b>Description</b>	Configure the IP address to which registration requests are sent as part of the home agent's dynamic assignment rule.
<b>Options</b>	The remaining statements are explained separately.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Topics</b>	<ul style="list-style-type: none"><li>■ Configuring Mobile IP</li><li>■ Configuring Dynamic Home Assignment for the Mobile Node</li></ul>

