

overrides

Syntax overrides {
 always-write-giaddr;
 always-write-option-82;
 client-discover-match;
 interface-client-limit *number*;
 layer2-unicast-replies;
 no-arp;
 proxy-mode;
 trust-option-82;
 disable-relay;
 }

Hierarchy Level [edit forwarding-options dhcp-relay],
 [edit forwarding-options dhcp-relay group *group-name*],
 [edit logical-systems *logical-system-name* forwarding-options dhcp-relay],
 [edit logical-systems *logical-system-name* forwarding-options dhcp-relay group *group-name*],
 [edit logical-systems *logical-system-name* routing-instances *routing-instance-name*
 forwarding-options dhcp-relay],
 [edit logical-systems *logical-system-name* routing-instances *routing-instance-name*
 forwarding-options dhcp-relay group *group-name*],
 [edit routing-instances *routing-instance-name* forwarding-options dhcp-relay],
 [edit routing-instances *routing-instance-name* forwarding-options dhcp-relay group
 group-name]

Release Information Statement introduced in JUNOS Release 8.3.

Description Override the default configuration settings for the extended DHCP relay agent. Specifying the **overrides** statement with no subordinate statements removes all DHCP relay agent overrides at that hierarchy level.

To override global DHCP relay agent configuration options, include the **overrides** statement and its subordinate statements at the [edit forwarding-options dhcp-relay] hierarchy level. To override DHCP relay agent configuration options for a named group of interfaces, include the statements at the [edit forwarding-options dhcp-relay group *group-name*] hierarchy level.

The statements are explained separately.

Required Privilege Level interface—To view this statement in the configuration.
 interface-control—To add this statement to the configuration.

Related Topics ■ Extended DHCP Relay Agent Overview
 ■ Overriding the Default DHCP Relay Configuration

