

pop-swap

| | |
|---------------------------------|---|
| Syntax | pop-swap; |
| Hierarchy Level | [edit interfaces <i>interface-name</i> unit <i>logical-unit-number</i> [Unresolved xref]], [edit interfaces <i>interface-name</i> unit <i>logical-unit-number</i> [Unresolved xref]], [edit logical-systems <i>logical-system-name</i> interfaces <i>interface-name</i> unit <i>logical-unit-number</i> [Unresolved xref]], [edit logical-systems <i>logical-system-name</i> interfaces <i>interface-name</i> unit <i>logical-unit-number</i> [Unresolved xref]] |
| Release Information | Statement introduced in JUNOS Release 8.1. |
| Description | For Gigabit Ethernet IQ, IQ2 and IQ2-E interfaces, and for aggregated Ethernet interfaces using Gigabit Ethernet IQ2 and IQ2-E or 10-Gigabit Ethernet PICs on MX-series routing platforms, specify the VLAN rewrite operation to remove the outer VLAN tag of the frame, and replace the inner VLAN tag of the frame with a user-specified VLAN tag value. The inner tag becomes the outer tag in the final frame. |
| Usage Guidelines | See Removing the Outer VLAN Tag and Rewriting the Inner VLAN Tag. |
| Required Privilege Level | interface—To view this statement in the configuration. interface-control—To add this statement to the configuration. |

