

redial-delay

Syntax	<code>redial-delay time;</code>
Hierarchy Level	[edit interfaces <i>dl</i> n unit <i>logical-unit-number</i> dialer-options], [edit logical-systems <i>logical-system-name</i> interfaces <i>dl</i> n unit <i>logical-unit-number</i> dialer-options]
Release Information	Statement introduced in JUNOS Release 7.5.
Description	<p>(J-series Services Routers) For interfaces configured for ISDN with dialout, specify the delay (in seconds) between two successive calls made by the dialer. To configure callback mode, include the <code>callback</code> statement at the [edit interfaces <i>dl</i>n unit <i>logical-unit-number</i> dialer-options] hierarchy level.</p> <p>If the <code>callback</code> statement is configured, you cannot use the <code>caller caller-id</code> statement at the [edit interfaces <i>dl</i>n unit <i>logical-unit-number</i> dialer-options] hierarchy level.</p>
Options	<p><i>time</i>—Delay (in seconds) between two successive calls.</p> <p>Range: 2 through 255 seconds</p> <p>Default: 3 seconds</p>
Usage Guidelines	See [Unresolved xref] .
Required Privilege Level	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
Related Topics	<i>J-series Services Router Basic LAN and WAN Access Configuration Guide</i>

