

## swap-push

---

<b>Syntax</b>	swap-push;
<b>Hierarchy Level</b>	[edit interfaces <i>interface-name</i> unit <i>logical-unit-number</i> <a href="#">[Unresolved xref]</a> ], [edit interfaces <i>interface-name</i> unit <i>logical-unit-number</i> <a href="#">[Unresolved xref]</a> ], [edit logical-systems <i>logical-system-name</i> interfaces <i>interface-name</i> unit <i>logical-unit-number</i> <a href="#">[Unresolved xref]</a> ], [edit logical-systems <i>logical-system-name</i> interfaces <i>interface-name</i> unit <i>logical-unit-number</i> <a href="#">[Unresolved xref]</a> ]
<b>Release Information</b>	Statement introduced in JUNOS Release 8.1.
<b>Description</b>	For Gigabit Ethernet IQ, IQ2 and IQ2-E interfaces, and for aggregated Ethernet interfaces using Gigabit Ethernet IQ2 and IQ2-E or 10-Gigabit Ethernet PICs on MX-series routing platforms, specify the VLAN rewrite operation to replace the outer VLAN tag of the frame with a user-specified VLAN tag value. A user-specified outer VLAN tag is pushed in front. The outer tag becomes an inner tag in the final frame.
<b>Usage Guidelines</b>	See Rewriting a VLAN Tag and Adding a New Tag.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.

