

timestamp-tolerance

Syntax	timestamp-tolerance <i>seconds</i> ;
Hierarchy Level	[edit logical-systems <i>logical-system-name</i> services mobile-ip home-agent virtual-network home-agent-address <i>ip-address</i>], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instances-name</i> services mobile-ip home-agent virtual-network home-agent-address <i>ip-address</i>], [edit routing-instances <i>routing-instances-name</i> services mobile-ip home-agent virtual-network home-agent-address <i>ip-address</i>], [edit services mobile-ip home-agent virtual-network home-agent-address <i>ip-address</i>]
Release Information	Statement introduced in JUNOS Release 9.3. Support at the [edit logical-systems <i>logical-system-name</i> services mobile-ip home-agent virtual-network home-agent-address <i>ip-address</i>], [edit logical-systems <i>logical-system-name</i> routing-instances <i>routing-instances-name</i> services mobile-ip home-agent virtual-network home-agent-address <i>ip-address</i>], and [edit routing-instances <i>routing-instances-name</i> services mobile-ip home-agent virtual-network home-agent-address <i>ip-address</i>] hierarchy levels added in JUNOS Release 9.5.
Description	Configure the acceptable difference between a registration request timestamp and the local time of the home agent.
Options	timestamp-tolerance <i>seconds</i> —Acceptable difference in time between a registration request timestamp and the local time of the home agent. Range: 1 through 255 seconds Default: 7 seconds
Required Privilege Level	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
Related Topics	■ Configuring Mobile IP ■ Configuring the Mobile IP Home Agent

