

## Configuring a VLAN Dynamic Profile for Creating Single-Tag VLANs Using Any TPID Values

---

You can configure a VLAN dynamic profile to create single-tag VLANs that accept any TPID values by configuring the `vlan-tags` statement and the `$junos-vlan-id` variable.



**NOTE:** For procedures to configure a VLAN dynamic profile for creating single-tag VLANs that use only standard TPID values (a TPID value of 0x8100), see [Configuring a VLAN Dynamic Profile for Creating Single-Tag VLANs Using Standard TPID Values](#).

---

Before you begin:

- Configure the dynamic profile.

See [Configuring a Basic Dynamic Profile](#).

To configure a dynamic VLAN profile:

1. Ensure that the VLAN dynamic profile uses the `$junos-interface-ifd-name` variable for the dynamic interface and the `$junos-interface-unit` variable for the interface unit.
2. (Optional) To support dynamic demux interfaces, enable them using the `demux-source` statement.

```
[edit dynamic-profiles VLAN-PROF1 interfaces "$junos-interface-ifd-name" unit
"$junos-interface-unit"]
user@host# set demux-source inet
```

3. (Optional) To configure the router to respond to any ARP request, specify the `proxy-arp` statement.

```
[edit dynamic-profiles VLAN-PROF1 interfaces "$junos-interface-ifd-name" unit
"$junos-interface-unit"]
user@host# set proxy-arp
```

4. Specify that you want to use dynamic VLAN IDs in the dynamic profile.

```
[edit dynamic-profiles VLAN-PROF1 interfaces "$junos-interface-ifd-name" unit
"$junos-interface-unit"]
user@host# set vlan-tags outer $junos-vlan-id
```

The variable is dynamically replaced with both the TPID value and a VLAN ID within the VLAN range specified at the `[interfaces]` hierarchy level.

5. Define the unit family.
  - a. Specify the family type.

```
[edit dynamic-profiles VLAN-PROF1 interfaces "$junos-interface-ifd-name" unit
"$junos-interface-unit"]
user@host# set family inet
```

- b. (Optional) Enable IP and MAC address validation for dynamic IP demux interfaces in a dynamic profile.

```
[edit dynamic-profiles VLAN-PROF1 interfaces "$junos-interface-ifd-name" unit
"$junos-interface-unit" family inet]
user@host# set mac-validate strict
```

- c. Specify the unnumbered address.

```
[edit dynamic-profiles VLAN-PROF1 interfaces "$junos-interface-ifd-name" unit
"$junos-interface-unit" family inet]
user@host# set unnumbered-address lo.0
```

- d. Specify the preferred source address.

```
[edit dynamic-profiles VLAN-PROF1 interfaces "$junos-interface-ifd-name" unit
"$junos-interface-unit" family inet]
user@host# set preferred-source-address 192.0.16.1
```

- Related Topics**
- Configuring a Basic Dynamic Profile
  - Dynamic 802.1Q VLAN Overview
  - Dynamic Variables Overview
  - Configuring Frames with Particular TPIDs to Be Processed as Tagged Frames