

## drop-profile-map

---

<b>Syntax</b>	drop-profile-map loss-priority (any   low   medium-low   medium-high   high) protocol (any   non-tcp   tcp) drop-profile ( <i>profile-name</i>   <i>variable</i> );
<b>Hierarchy Level</b>	[edit dynamic-profiles <i>profile-name</i> class-of-service schedulers <i>scheduler-name</i> ]
<b>Release Information</b>	Statement introduced before JUNOS Release 7.4. The [edit dynamic-profiles <i>profile-name</i> ] hierarchy added in JUNOS Release 9.3. The \$junos-cos-scheduler-dropfile-low, \$junos-cos-scheduler-dropfile-medium-low, \$junos-cos-scheduler-dropfile-medium-high, \$junos-cos-scheduler-dropfile-high, and \$junos-cos-scheduler-dropfile-any predefined variable added in JUNOS Release 9.4.
<b>Description</b>	Define loss priority value for drop profile.  The statements are explained separately.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Topics</b>	<ul style="list-style-type: none"><li>■ Dynamic Variables Overview</li><li>■ Configuring Schedulers in a Dynamic Profile</li><li>■ scheduler</li></ul>

---

Published: 2009-07-16