

group

Syntax `group group-name {`
 `active-server-group server-group-name;`
 `authentication {`
 `password password-string;`
 `username-include {`
 `circuit-type;`
 `delimiter delimiter-character;`
 `domain-name domain-name-string;`
 `logical-system-name;`
 `mac-address;`
 `option-60;`
 `option-82 [circuit-id] [remote-id];`
 `routing-instance-name;`
 `user-prefix user-prefix-string;`
 `}`
 `}`
 `dynamic-profile profile-name <aggregate-clients (merge | replace) |`
 `use-primaryprimary-profile-name>;`
 `overrides {`
 `always-write-giaddr;`
 `always-write-option-82;`
 `client-discover-match;`
 `interface-client-limit number;`
 `layer2-unicast-replies;`
 `no-arp;`
 `proxy-mode;`
 `trust-option-82;`
 `disable-relay;`
 `}`
 `relay-option-60 {`
 `vendor-option {`
 `(equals | starts-with) (ascii match-string | hexadecimal match-hex) {`
 `(default-relay-server-group server-group-name |`
 `default-local-server-group local-server-group-name |`
 `drop);`
 `}`
 `(default-relay-server-group server-group-name |`
 `default-local-server-group local-server-group-name |`
 `drop);`
 `}`
 `}`
 `relay-option-82 {`
 `circuit-id {`
 `prefix prefix;`
 `use-interface-description (logical | device);`
 `}`
 `}`
 `interface interface-name [upto upto-interface-name] [exclude];`
}

Hierarchy Level [edit forwarding-options dhcp-relay],

[edit logical-systems *logical-system-name* forwarding-options dhcp-relay],
[edit logical-systems *logical-system-name* routing-instances *routing-instance-name*
forwarding-options dhcp-relay],
[edit routing-instances *routing-instance-name* forwarding-options dhcp-relay]

Release Information Statement introduced in JUNOS Release 8.3.

Description Specify the name of a group of interfaces that have a common DHCP relay agent configuration. A group must contain at least one interface.

The statements configured at the [edit forwarding-options dhcp-relay group *group-name*] hierarchy level apply only to the named group of interfaces, and override any global DHCP relay agent settings configured with the same statements at the [edit forwarding-options dhcp-relay] hierarchy level.

Options *group-name*—Name of a group of interfaces that have a common DHCP relay agent configuration.

The remaining statements are explained separately.

Required Privilege Level interface—To view this statement in the configuration.
interface-control—To add this statement to the configuration.

Related Topics

- Extended DHCP Relay Agent Overview
- Using External AAA Authentication Services with DHCP
- Attaching Dynamic Profiles to DHCP Subscriber Interfaces

Published: 2009-07-16