

layer2-unicast-replies

Syntax layer2-unicast-replies;

Hierarchy Level [edit forwarding-options dhcp-relay overrides],
[edit forwarding-options dhcp-relay group *group-name* overrides],
[edit logical-systems *logical-system-name* forwarding-options dhcp-relay overrides],
[edit logical-systems *logical-system-name* forwarding-options dhcp-relay group *group-name* overrides],
[edit logical-systems *logical-system-name* routing-instances *routing-instance-name* forwarding-options dhcp-relay overrides],
[edit logical-systems *logical-system-name* routing-instances *routing-instance-name* forwarding-options dhcp-relay group *group-name* overrides],
[edit routing-instances *routing-instance-name* forwarding-options dhcp-relay overrides],
[edit routing-instances *routing-instance-name* forwarding-options dhcp-relay group *group-name* overrides]

Release Information Statement introduced in JUNOS Release 8.3.

Description Override the setting of the broadcast bit in DHCP request packets and instead use the Layer 2 unicast transmission method to transmit DHCP Offer reply packets and DHCP ACK reply packets from the DHCP server to DHCP clients during the discovery process.

Required Privilege Level interface—To view this statement in the configuration.
interface-control—To add this statement to the configuration.

Related Topics ■ Extended DHCP Relay Agent Overview

Published: 2009-07-16