

## relay-agent-subscriber-id

---

**Syntax** relay-agent-subscriber-id;

**Hierarchy Level** [edit logical-systems *logical-system-name* routing-instances *routing-instance-name* system services dhcp-local-server dhcpv6 authentication username-include],  
[edit logical-systems *logical-system-name* routing-instances *routing-instance-name* system services dhcp-local-server dhcpv6 group *group-name* authentication username-include],  
[edit logical-systems *logical-system-name* system services dhcp-local-server dhcpv6 authentication username-include],  
[edit logical-systems *logical-system-name* system services dhcp-local-server dhcpv6 group *group-name* authentication username-include],  
[edit logical-systems *logical-system-name* routing-instances *routing-instance-name* system services dhcp-local-server dhcpv6 authentication username-include],  
[edit logical-systems *logical-system-name* routing-instances *routing-instance-name* system services dhcp-local-server dhcpv6 group *group-name* authentication username-include],  
[edit routing-instances *routing-instance-name* system services dhcp-local-server dhcpv6 authentication username-include],  
[edit routing-instances *routing-instance-name* system services dhcp-local-server dhcpv6 group *group-name* authentication username-include],  
[edit system services dhcp-local-server dhcpv6 authentication username-include],  
[edit system services dhcp-local-server dhcpv6 group *group-name* authentication username-include]

**Release Information** Statement introduced in JUNOS Release 9.6.

**Description** Specify that the DHCPv6 Relay Agent Subscriber-ID option (option 38) in the client PDU name is concatenated with the username during the subscriber authentication process.

**Required Privilege Level** system—To view this statement in the configuration.  
system-control—To add this statement to the configuration.

**Related Topics** ■ Creating Unique Usernames for DHCP Clients

---

Published: 2009-07-16