

schedulers

Syntax schedulers {
 (*scheduler-name*) {
 buffer-size (*seconds* | percent *percentage* | remainder | temporal *microseconds*);
 drop-profile-map loss-priority (any | low | medium-low | medium-high | high) protocol
 (any | non-tcp | tcp) drop-profile *profile-name*;
 priority *priority-level*;
 transmit-rate (percent *percentage* | *rate* | remainder) <exact | rate-limit>;
 }
}

Hierarchy Level [edit dynamic-profiles *profile-name* class-of-service]

Release Information Statement introduced before JUNOS Release 7.4.
The [edit dynamic-profiles *profile-name*] hierarchy added in JUNOS Release 9.3.
The \$junos-cos-scheduler predefined variable added in JUNOS Release 9.4.

Description Specify scheduler name and parameter values in a dynamic profile.

Options *scheduler-name*—Name of the scheduler to be configured or the JUNOS predefined variable (\$junos-cos-scheduler). The predefined variable is replaced with the scheduler name obtained from the RADIUS server when a subscriber authenticates over the subscriber interface to which the subscriber access dynamic profile is attached.

The remaining statements are explained separately.

Required Privilege Level interface—To view this statement in the configuration.
interface-control—To add this statement to the configuration.

Related Topics

- Dynamic Variables Overview
- Configuring Schedulers in a Dynamic Profile
- scheduler

Published: 2009-07-16