

server-reject-vlan

Syntax	server-reject-vlan (<i>vlan-id</i> <i>vlan-name</i>);
Hierarchy Level	[edit protocols dot1x authenticator interface (all [<i>interface-names</i>])]
Release Information	Statement introduced in JUNOS Release 9.3 for EX Series switches.
Description	<p>For EX Series switches configured for 802.1X authentication, specify that when the switch receives an Extensible Authentication Protocol Over LAN (EAPOL) Access-Reject message during the authentication process between the switch and the RADIUS authentication server, supplicants attempting access to the LAN are granted access and moved to a specific VLAN. Any VLAN name or VLAN ID sent by a RADIUS server as part of the EAPOL Access-Reject message is ignored.</p> <p>When you specify the VLAN ID or VLAN name, the VLAN must already be configured on the switch.</p>
Default	None
Options	<p><i>vlan-id</i> —Numeric identifier of the VLAN to which the supplicant is moved.</p> <p><i>vlan-name</i>—Name of the VLAN to which the supplicant is moved.</p>
Required Privilege Level	<p>routing—To view this statement in the configuration.</p> <p>routing-control—To add this statement to the configuration.</p>
Related Topics	<ul style="list-style-type: none">■ show dot1x■ Example: Connecting a RADIUS Server for 802.1X to an EX Series Switch■ Configuring Server Fail Fallback (CLI Procedure)■ Understanding Server Fail Fallback and 802.1X Authentication on EX Series Switches

Published: 2009-07-21