



Junos[®] OS

IPSec Feature Guide for Routing Devices

Release

14.1



Published: 2014-05-02

Juniper Networks, Inc.
1194 North Mathilda Avenue
Sunnyvale, California 94089
USA
408-745-2000
www.juniper.net

Juniper Networks, Junos, Steel-Belted Radius, NetScreen, and ScreenOS are registered trademarks of Juniper Networks, Inc. in the United States and other countries. The Juniper Networks Logo, the Junos logo, and JunosE are trademarks of Juniper Networks, Inc. All other trademarks, service marks, registered trademarks, or registered service marks are the property of their respective owners.

Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

Junos[®] OS IPSec Feature Guide for Routing Devices
Release 14.1
Copyright © 2014, Juniper Networks, Inc.
All rights reserved.

The information in this document is current as of the date on the title page.

YEAR 2000 NOTICE

Juniper Networks hardware and software products are Year 2000 compliant. Junos OS has no known time-related limitations through the year 2038. However, the NTP application is known to have some difficulty in the year 2036.

END USER LICENSE AGREEMENT

The Juniper Networks product that is the subject of this technical documentation consists of (or is intended for use with) Juniper Networks software. Use of such software is subject to the terms and conditions of the End User License Agreement ("EULA") posted at <http://www.juniper.net/support/eula.html>. By downloading, installing or using such software, you agree to the terms and conditions of that EULA.

Table of Contents

	About the Documentation	xi
	Documentation and Release Notes	xi
	Supported Platforms	xi
	Using the Examples in This Manual	xi
	Merging a Full Example	xii
	Merging a Snippet	xii
	Documentation Conventions	xiii
	Documentation Feedback	xv
	Requesting Technical Support	xv
	Self-Help Online Tools and Resources	xv
	Opening a Case with JTAC	xvi
Part 1	Overview	
Chapter 1	Product Overview	3
	Overview of IPSec	3
	IPsec-Enabled Line Cards	4
	Authentication Algorithms	5
	Encryption Algorithms	6
	IPsec Protocols	7
	Security Associations	9
	IPSec Modes	9
	Digital Certificates	10
	Service Sets	11
Chapter 2	System Requirements	13
	System Requirements	13
Chapter 3	Glossary	15
	Terms and Acronyms	15
Part 2	Configuration	
Chapter 4	IPSec Configuration	21
	Considering General IPSec Issues	21
	Configuring Security Associations	25
	Configuring Manual SAs	25
	Configuring IKE Dynamic SAs	26
	Using a Filter to Select Traffic to Be Secured	30
	Applying the Filter or Service Set to the Interface Receiving Traffic to Be Secured	31
	Configuring IKE Dynamic SAs	32

	Configuring Manual SAs	35
Chapter 5	Digital Certificates	39
	Configuring a CA Profile	39
	Configuring a Certificate Revocation List	40
	Requesting a CA Digital Certificate	41
	Generating a Private/Public Key Pair	41
	Generating and Enrolling a Local Digital Certificate	41
	Applying the Local Digital Certificate to an IPSec Configuration	41
	Configuring Automatic Reenrollment of Digital Certificates	42
	Monitoring Digital Certificates	42
	Clearing Digital Certificates	43
Chapter 6	Other Options	45
	Option: Using Filter-Based Forwarding to Select Traffic to Be Secured	45
	Option: Using IPSec with a Layer 3 VPN	46
	Option: Securing BGP Sessions with Transport Mode	48
	Option: Securing OSPFv3 Networks with Transport Mode	49
	Option: Securing OSPFv2 Networks with Transport Mode	49
	Option: Monitoring IPSec by Using SNMP	51
	Option: Configuring Multiple Routed Tunnels in a Single Next-Hop Service Set	51
	Option: Using Digital Certificates	53
Chapter 7	IPSec Dynamic Endpoints	55
	Option: Configuring IPSec Dynamic Endpoints	55
	Dynamic Endpoint Tunnel Architecture	56
	Authentication Process	56
	Dynamic Implicit Rules	57
	Reverse Route Insertion	57
	Configuring an IKE Access Profile	58
	Configuring the Service Set	59
	Configuring the Interface Identifier	59
Part 3	Examples	
Chapter 8	IPSec Configuration Examples	63
	Example: ES PIC Manual SA Configuration	63
	Verifying Your Work	69
	Router 1	69
	Router 2	70
	Router 3	71
	Router 4	71
	Example: AS PIC Manual SA Configuration	72
	Verifying Your Work	78
	Router 1	78
	Router 2	78
	Router 3	79

Example: ES PIC IKE Dynamic SA Configuration	80
Verifying Your Work	86
Router 1	87
Router 2	87
Router 3	88
Router 4	90
Example: AS PIC IKE Dynamic SA Configuration	90
Verifying Your Work	96
Router 1	96
Router 2	97
Router 3	98
Router 4	98
Example: IKE Dynamic SA Between an AS PIC and an ES PIC Configuration	99
Verifying Your Work	106
Router 1	106
Router 2	107
Router 3	108
Router 4	109
Example: AS PIC IKE Dynamic SA with Digital Certificates Configuration	110
Verifying Your Work	119
Router 1	120
Router 2	120
Router 3	124
Router 4	127
Example: Dynamic Endpoint Tunneling Configuration	127
Verifying Your Work	129

Part 4

Chapter 9

Administration

IPSec Commands	133
clear security pki ca-certificate	134
clear security pki certificate-request	135
clear security pki crl	136
clear security pki local-certificate	137
request security certificate (signed)	138
request security certificate (unsigned)	140
request security key-pair	141
request security pki ca-certificate enroll	142
request security pki ca-certificate load	143
request security pki generate-certificate-request	144
request security pki generate-key-pair	146
request security pki local-certificate enroll	147
request security pki local-certificate load	149
request system certificate add	150
show ike security-associations	151
show ipsec certificates	155
show security pki ca-certificate	158
show ipsec security-associations	162
show security pki certificate-request	165

show security pki crl	167
show security pki local-certificate	169
show services ipsec-vpn certificates	172
show services ipsec-vpn ike security-associations	175
show services ipsec-vpn ipsec security-associations	179
show system certificate	183

Part 5

Index

Index	187
-----------------	-----

List of Figures

Part 1	Overview	
Chapter 1	Product Overview	3
	Figure 1: AH Protocol	7
	Figure 2: ESP Protocol	8
Part 3	Examples	
Chapter 8	IPSec Configuration Examples	63
	Figure 3: ES PIC Manual SA Topology Diagram	63
	Figure 4: AS PIC Manual SA Topology Diagram	72
	Figure 5: ES PIC IKE Dynamic SA Topology Diagram	80
	Figure 6: AS PIC IKE Dynamic SA Topology Diagram	90
	Figure 7: AS PIC to ES PIC IKE Dynamic SA Topology Diagram	99
	Figure 8: AS PIC IKE Dynamic SA Topology Diagram	110
	Figure 9: IPSec Dynamic Endpoint Tunneling Topology Diagram	127

List of Tables

	About the Documentation	xi
	Table 1: Notice Icons	xiii
	Table 2: Text and Syntax Conventions	xiv
Part 2	Configuration	
Chapter 4	IPSec Configuration	21
	Table 3: Comparison of IPSec Configuration Statements and Operational Mode Commands for the AS and MultiServices PICs and ES PIC	21
	Table 4: Authentication and Encryption Key Lengths	23
	Table 5: Weak and Semiweak Keys	24
	Table 6: IKE and IPSec Proposal and Policy Default Values for the AS and MultiServices PICs	27
	Table 7: IKE and IPSec Proposal and Policy Default Values for the AS and MultiServices PICs	33
Chapter 7	IPSec Dynamic Endpoints	55
	Table 8: Default IKE and IPSec Proposals for Dynamic SA Negotiations	56
Part 4	Administration	
Chapter 9	IPSec Commands	133
	Table 9: show ike security-associations Output Fields	151
	Table 10: show ipsec certificates Output Fields	155
	Table 11: show security pki ca-certificate Output Fields	158
	Table 12: show ipsec security-associations Output Fields	162
	Table 13: show security pki certificate-request Output Fields	165
	Table 14: show security pki crl Output Fields	167
	Table 15: show security pki local-certificate Output Fields	169
	Table 16: show services ipsec-vpn certificates Output Fields	172
	Table 17: show services ipsec-vpn ike security-associations Output Fields	175
	Table 18: show services ipsec-vpn ipsec security-associations Output Fields	179
	Table 19: show system certificate Output Fields	183

About the Documentation

- Documentation and Release Notes on page xi
- Supported Platforms on page xi
- Using the Examples in This Manual on page xi
- Documentation Conventions on page xiii
- Documentation Feedback on page xv
- Requesting Technical Support on page xv

Documentation and Release Notes

To obtain the most current version of all Juniper Networks® technical documentation, see the product documentation page on the Juniper Networks website at <http://www.juniper.net/techpubs/>.

If the information in the latest release notes differs from the information in the documentation, follow the product Release Notes.

Juniper Networks Books publishes books by Juniper Networks engineers and subject matter experts. These books go beyond the technical documentation to explore the nuances of network architecture, deployment, and administration. The current list can be viewed at <http://www.juniper.net/books>.

Supported Platforms

For the features described in this document, the following platforms are supported:

- MX Series
- T Series
- M Series

Using the Examples in This Manual

If you want to use the examples in this manual, you can use the **load merge** or the **load merge relative** command. These commands cause the software to merge the incoming configuration into the current candidate configuration. The example does not become active until you commit the candidate configuration.

If the example configuration contains the top level of the hierarchy (or multiple hierarchies), the example is a *full example*. In this case, use the **load merge** command.

If the example configuration does not start at the top level of the hierarchy, the example is a *snippet*. In this case, use the **load merge relative** command. These procedures are described in the following sections.

Merging a Full Example

To merge a full example, follow these steps:

1. From the HTML or PDF version of the manual, copy a configuration example into a text file, save the file with a name, and copy the file to a directory on your routing platform.

For example, copy the following configuration to a file and name the file **ex-script.conf**. Copy the **ex-script.conf** file to the **/var/tmp** directory on your routing platform.

```
system {
  scripts {
    commit {
      file ex-script.xml;
    }
  }
}
interfaces {
  fxp0 {
    disable;
    unit 0 {
      family inet {
        address 10.0.0.1/24;
      }
    }
  }
}
```

2. Merge the contents of the file into your routing platform configuration by issuing the **load merge** configuration mode command:

```
[edit]
user@host# load merge /var/tmp/ex-script.conf
load complete
```

Merging a Snippet

To merge a snippet, follow these steps:

1. From the HTML or PDF version of the manual, copy a configuration snippet into a text file, save the file with a name, and copy the file to a directory on your routing platform.

For example, copy the following snippet to a file and name the file **ex-script-snippet.conf**. Copy the **ex-script-snippet.conf** file to the **/var/tmp** directory on your routing platform.

```
commit {
  file ex-script-snippet.xml; }
```

2. Move to the hierarchy level that is relevant for this snippet by issuing the following configuration mode command:

```
[edit]
user@host# edit system scripts
[edit system scripts]
```

3. Merge the contents of the file into your routing platform configuration by issuing the **load merge relative** configuration mode command:

```
[edit system scripts]
user@host# load merge relative /var/tmp/ex-script-snippet.conf
load complete
```

For more information about the **load** command, see the *CLI User Guide*.

Documentation Conventions

Table 1 on page xiii defines notice icons used in this guide.

Table 1: Notice Icons







Icon	Meaning	Description
	Informational note	Indicates important features or instructions.
	Caution	Indicates a situation that might result in loss of data or hardware damage.
	Warning	Alerts you to the risk of personal injury or death.
	Laser warning	Alerts you to the risk of personal injury from a laser.
	Tip	Indicates helpful information.
	Best practice	Alerts you to a recommended use or implementation.

Table 2 on page xiv defines the text and syntax conventions used in this guide.

Table 2: Text and Syntax Conventions

Convention	Description	Examples
Bold text like this	Represents text that you type.	To enter configuration mode, type the configure command: user@host> configure
Fixed-width text like this	Represents output that appears on the terminal screen.	user@host> show chassis alarms No alarms currently active
<i>Italic text like this</i>	<ul style="list-style-type: none"> Introduces or emphasizes important new terms. Identifies guide names. Identifies RFC and Internet draft titles. 	<ul style="list-style-type: none"> A policy <i>term</i> is a named structure that defines match conditions and actions. <i>Junos OS CLI User Guide</i> RFC 1997, <i>BGP Communities Attribute</i>
<i>Italic text like this</i>	Represents variables (options for which you substitute a value) in commands or configuration statements.	Configure the machine's domain name: [edit] root@# set system domain-name <i>domain-name</i>
Text like this	Represents names of configuration statements, commands, files, and directories; configuration hierarchy levels; or labels on routing platform components.	<ul style="list-style-type: none"> To configure a stub area, include the stub statement at the [edit protocols ospf area area-id] hierarchy level. The console port is labeled CONSOLE.
< > (angle brackets)	Encloses optional keywords or variables.	stub <default-metric metric>;
(pipe symbol)	Indicates a choice between the mutually exclusive keywords or variables on either side of the symbol. The set of choices is often enclosed in parentheses for clarity.	broadcast multicast (string1 string2 string3)
# (pound sign)	Indicates a comment specified on the same line as the configuration statement to which it applies.	rsvp { # Required for dynamic MPLS only
[] (square brackets)	Encloses a variable for which you can substitute one or more values.	community name members [community-ids]
Indentation and braces ({ })	Identifies a level in the configuration hierarchy.	[edit] routing-options { static { route default { nexthop address; retain; } } }
;(semicolon)	Identifies a leaf statement at a configuration hierarchy level.	

GUI Conventions

Table 2: Text and Syntax Conventions (*continued*)

Convention	Description	Examples
Bold text like this	Represents graphical user interface (GUI) items you click or select.	<ul style="list-style-type: none"> In the Logical Interfaces box, select All Interfaces. To cancel the configuration, click Cancel.
> (bold right angle bracket)	Separates levels in a hierarchy of menu selections.	In the configuration editor hierarchy, select Protocols>Ospf .

Documentation Feedback

We encourage you to provide feedback, comments, and suggestions so that we can improve the documentation. You can send your comments to techpubs-comments@juniper.net, or fill out the documentation feedback form at <https://www.juniper.net/cgi-bin/docbugreport/>. If you are using e-mail, be sure to include the following information with your comments:

- Document or topic name
- URL or page number
- Software release version (if applicable)

Requesting Technical Support

Technical product support is available through the Juniper Networks Technical Assistance Center (JTAC). If you are a customer with an active J-Care or JNASC support contract, or are covered under warranty, and need post-sales technical support, you can access our tools and resources online or open a case with JTAC.

- JTAC policies—For a complete understanding of our JTAC procedures and policies, review the *JTAC User Guide* located at <http://www.juniper.net/us/en/local/pdf/resource-guides/7100059-en.pdf>.
- Product warranties—For product warranty information, visit <http://www.juniper.net/support/warranty/>.
- JTAC hours of operation—The JTAC centers have resources available 24 hours a day, 7 days a week, 365 days a year.

Self-Help Online Tools and Resources

For quick and easy problem resolution, Juniper Networks has designed an online self-service portal called the Customer Support Center (CSC) that provides you with the following features:

- Find CSC offerings: <http://www.juniper.net/customers/support/>
- Search for known bugs: <http://www2.juniper.net/kb/>

- Find product documentation: <http://www.juniper.net/techpubs/>
- Find solutions and answer questions using our Knowledge Base: <http://kb.juniper.net/>
- Download the latest versions of software and review release notes: <http://www.juniper.net/customers/csc/software/>
- Search technical bulletins for relevant hardware and software notifications: <http://kb.juniper.net/InfoCenter/>
- Join and participate in the Juniper Networks Community Forum: <http://www.juniper.net/company/communities/>
- Open a case online in the CSC Case Management tool: <http://www.juniper.net/cm/>

To verify service entitlement by product serial number, use our Serial Number Entitlement (SNE) Tool: <https://tools.juniper.net/SerialNumberEntitlementSearch/>

Opening a Case with JTAC

You can open a case with JTAC on the Web or by telephone.

- Use the Case Management tool in the CSC at <http://www.juniper.net/cm/>.
- Call 1-888-314-JTAC (1-888-314-5822 toll-free in the USA, Canada, and Mexico).

For international or direct-dial options in countries without toll-free numbers, see <http://www.juniper.net/support/requesting-support.html>.

PART 1

Overview

- [Product Overview on page 3](#)
- [System Requirements on page 13](#)
- [Glossary on page 15](#)

CHAPTER 1

Product Overview

- [Overview of IPSec on page 3](#)
- [IPsec-Enabled Line Cards on page 4](#)
- [Authentication Algorithms on page 5](#)
- [Encryption Algorithms on page 6](#)
- [IPsec Protocols on page 7](#)
- [Security Associations on page 9](#)
- [IPsec Modes on page 9](#)
- [Digital Certificates on page 10](#)
- [Service Sets on page 11](#)

Overview of IPSec

IP Security (IPSec) provides a secure way to authenticate senders and encrypt IP version 4 (IPv4) and version 6 (IPv6) traffic between network devices, such as routers and hosts. IPSec offers network administrators and their users the benefits of data confidentiality, data integrity, sender authentication, and anti-replay services. IPSec is increasingly becoming a critical component in today's contemporary IP networks.

IPSec is a framework for ensuring secure private communication over IP networks and is based on standards developed by the International Engineering Task Force (IETF). IPSec provides security services at the network layer of the Open Systems Interconnection (OSI) model by enabling a system to select required security protocols, determine the algorithms to use for the security services, and implement any cryptographic keys required to provide the requested services. You can use IPSec to protect one or more paths between a pair of hosts, between a pair of security gateways (such as routers), or between a security gateway and a host.

The terminology and components of IPSec can be intimidating to first-time users. However, if you learn a few key concepts, you can quickly master and deploy IPSec in your network. The main concepts you need to understand are as follows:

- [IPsec-Enabled Line Cards on page 4](#)
- [Authentication Algorithms on page 5](#)
- [Encryption Algorithms on page 6](#)

- [IPsec Protocols on page 7](#)
- [Security Associations on page 9](#)
- [IPsec Modes on page 9](#)
- [Digital Certificates on page 10](#)
- [Service Sets on page 11](#)

IPsec-Enabled Line Cards

The first choice you need to make when implementing IPsec on a Junos OS-based router is the type of line card you wish to use. The term line card includes Physical Interface Cards (PICs), Modular Interface Cards (MICs), Dense Port Concentrators (DPCs), and Modular Port Concentrators (MPCs). The following line cards support IPsec implementation.



NOTE: See the specific hardware documentation for your router to determine if the line cards on that router support IPsec.

The following line cards support IPsec implementation.

- The Encryption Services (ES) PIC provides encryption services and software support for IPsec.
- The Adaptive Services (AS) PIC and the Adaptive Services (AS) II PIC provide IPsec services and other services, such as Network Address Translation (NAT) and stateful firewall.
- The AS II Federal Information Processing Standards (FIPS) PIC is a special version of the AS PIC that communicates securely with the Routing Engine by using internal IPsec. You must configure IPsec on the AS II FIPS PIC when you enable FIPS mode on the router. For more information about implementing IPsec on an AS II FIPS PIC installed in a router configured in FIPS mode, see the *Secure Configuration Guide for Common Criteria and Junos-FIPS*.
- The Multiservices PICs supply hardware acceleration for an array of packet processing-intensive services. These services include IPsec services and other services, such as stateful firewall, NAT, IPsec, anomaly detection, and tunnel services.
- The Multiservices Dense Port Concentrators (DPCs) provide IPsec services.
- The Multiservices Modular Port Concentrators (MS-MPCs) support IPsec services.
- The Multiservices Modular Interface Cards (MS-MICs) support IPsec services.



NOTE: Junos OS extension-provider packages, including the IPsec service package, come preinstalled and preconfigured on MS-MPCs and MS-MICs.

- Related Documentation**
- [Overview of IPSec on page 3](#)
 - [Considering General IPSec Issues on page 21](#)
 - *IPSec Feature Guide for Routing Devices*
 - *Understanding Services PICs*
 - *Enabling Service Packages*
 - *Introducing Multiservices MIC and Multiservices MPC (MS-MIC and MS-MPC)*

Authentication Algorithms

Authentication is the process of verifying the identity of the sender. Authentication algorithms use a shared key to verify the authenticity of the IPsec devices. The Junos OS uses the following authentication algorithms:

- Message Digest 5 (MD5) uses a one-way hash function to convert a message of arbitrary length to a fixed-length message digest of 128 bits. Because of the conversion process, it is mathematically infeasible to calculate the original message by computing it backwards from the resulting message digest. Likewise, a change to a single character in the message will cause it to generate a very different message digest number.

To verify that the message has not been tampered with, the Junos OS compares the calculated message digest against a message digest that is decrypted with a shared key. The Junos OS uses the MD5 hashed message authentication code (HMAC) variant that provides an additional level of hashing. MD5 can be used with authentication header (AH), Encapsulating Security Payload (ESP), and Internet Key Exchange (IKE).

- Secure Hash Algorithm 1 (SHA-1) uses a stronger algorithm than MD5. SHA-1 takes a message of less than 264 bits in length and produces a 160-bit message digest. The large message digest ensures that the data has not been changed and that it originates from the correct source. The Junos OS uses the SHA-1 HMAC variant that provides an additional level of hashing. SHA-1 can be used with AH, ESP, and IKE.
- SHA-256, SHA-384, and SHA-512 (sometimes grouped under the name SHA-2) are variants of SHA-1 and use longer message digests. The Junos OS supports the SHA-256 version of SHA-2, which can process all versions of Advanced Encryption Standard (AES), Data Encryption Standard (DES), and Triple DES (3DES) encryption.

- Related Documentation**
- *Understanding Junos VPN Site Secure*
 - [Encryption Algorithms on page 6](#)

Encryption Algorithms

Encryption encodes data into a secure format so that it cannot be deciphered by unauthorized users. Like authentication algorithms, a shared key is used with encryption algorithms to verify the authenticity of the IPsec devices. The Junos OS uses the following encryption algorithms:

- Data Encryption Standard cipher-block chaining (DES-CBC) is a symmetric secret-key block algorithm. DES uses a key size of 64 bits, where 8 bits are used for error detection and the remaining 56 bits provide encryption. DES performs a series of simple logical operations on the shared key, including permutations and substitutions. CBC takes the first block of 64 bits of output from DES, combines this block with the second block, feeds this back into the DES algorithm, and repeats this process for all subsequent blocks.
- Triple DES-CBC (3DES-CBC) is an encryption algorithm that is similar to DES-CBC, but provides a much stronger encryption result because it uses three keys for 168-bit (3 x 56-bit) encryption. 3DES works by using the first key to encrypt the blocks, the second key to decrypt the blocks, and the third key to re-encrypt the blocks.
- Advanced Encryption Standard (AES) is a next-generation encryption method based on the Rijndael algorithm developed by Belgian cryptographers Dr. Joan Daemen and Dr. Vincent Rijmen. It uses a 128-bit block and three different key sizes (128, 192, and 256 bits). Depending on the key size, the algorithm performs a series of computations (10, 12, or 14 rounds) that include byte substitution, column mixing, row shifting, and key addition. The use of AES in conjunction with IPsec is defined in RFC 3602, *The AES-CBC Cipher Algorithm and Its Use with IPsec*.

**Related
Documentation**

- *Understanding Junos VPN Site Secure*
- *Configuring IKE Proposals*
- *Configuring IPsec Proposals*
- *encryption*

IPsec Protocols

IPsec protocols determine the type of authentication and encryption applied to packets that are secured by the router. The Junos OS supports the following IPsec protocols:

- AH—Defined in RFC 2402, AH provides connectionless integrity and data origin authentication for IPv4 and IPv6 packets. It also provides protection against replays. AH authenticates as much of the IP header as possible, as well as the upper-level protocol data. However, some IP header fields might change in transit. Because the value of these fields might not be predictable by the sender, they cannot be protected by AH. In an IP header, AH can be identified with a value of **51** in the **Protocol** field of an IPv4 packet and the **Next Header** field of an IPv6 packet. An example of the IPsec protection offered by AH is shown in [Figure 1 on page 7](#).



NOTE: AH is not supported on the T Series, M120, and M320 routers.

Figure 1: AH Protocol

Header format

Byte 0	Byte 1	Byte 2	Byte 3
Next header	Payload length	Reserved	
Security Parameters Index (SPI)			
Sequence number			
Authentication data (variable)			

Original IPv4 packet before AH is applied

Original IP header	TCP header	Data
--------------------	------------	------

IPv4 packet after AH transport mode is applied

Original IP header	AH header	TCP header	Data
Authenticating			

IPv4 packet after AH tunnel mode is applied


New IP header	AH header	Original IP header	TCP header	Data
Authenticating				

g015522


- **ESP**—Defined in RFC 2406, ESP can provide encryption and limited traffic flow confidentiality, or connectionless integrity, data origin authentication, and an anti-replay service. In an IP header, ESP can be identified a value of **50** in the **Protocol** field of an IPv4 packet and the **Next Header** field of an IPv6 packet. An example of the IPsec protection offered by ESP is shown in [Figure 2 on page 8](#).

Figure 2: ESP Protocol


Header format




Original IPv4 packet before ESP is applied



IPv4 packet after ESP transport mode is applied



IPv4 packet after ESP tunnel mode is applied



g015521

- **Bundle**—When you compare AH with ESP, there are some benefits and shortcomings in both protocols. ESP provides a decent level of authentication and encryption, but does so only for part of the IP packet. Conversely, although AH does not provide encryption, it does provide authentication for the entire IP packet. Because of this, the Junos OS offers a third form of IPsec protocol called a protocol bundle. The bundle option offers a hybrid combination of AH authentication with ESP encryption.

Related Documentation

- [Understanding Junos VPN Site Secure](#)
- [Configuring IPsec Proposals](#)
- [Configuring Security Associations](#)
- [protocol](#)

Security Associations

Another IPSec consideration is the type of security association (SA) that you wish to implement. An SA is a set of IPSec specifications that are negotiated between devices that are establishing an IPSec relationship. These specifications include preferences for the type of authentication, encryption, and IPSec protocol that should be used when establishing the IPSec connection. An SA can be either unidirectional or bidirectional, depending on the choices made by the network administrator. An SA is uniquely identified by a Security Parameter Index (SPI), an IPv4 or IPv6 destination address, and a security protocol (AH or ESP) identifier.

You can configure IPSec with a preset, preshared manual SA or use IKE to establish a dynamic SA. Manual SAs require you to specify all the IPSec requirements up front. Conversely, IKE dynamic SAs typically contain configuration defaults for the highest levels of authentication and encryption.

IPSec Modes

When configuring IPSec, the last major consideration is the type of IPSec mode you wish to implement in your network. The Junos OS supports the following IPSec modes:

- Tunnel mode is supported for both AH and ESP in the Junos OS and is the usual choice for a router. In tunnel mode, the SA and associated protocols are applied to tunneled IPv4 or IPv6 packets. For a tunnel mode SA, an outer IP header specifies the IPSec processing destination, and an inner IP header specifies the ultimate destination for the packet. The security protocol header appears after the outer IP header, and before the inner IP header. In addition, there are slight differences for tunnel mode when you implement it with AH and ESP:
 - For AH, portions of the outer IP header are protected, as well as the entire tunneled IP packet.
 - For ESP, only the tunneled packet is protected, not the outer header.

When one side of a security association is a security gateway (such as a router), the SA must use tunnel mode. However, when traffic (for example, SNMP commands or BGP sessions) is destined for a router, the system acts as a host. Transport mode is allowed in this case because the system does not act as a security gateway and does not send or receive transit traffic.

- Transport mode provides a security association between two hosts. In transport mode, the protocols provide protection primarily for upper layer protocols. For IPv4 and IPv6 packets, a transport mode security protocol header appears immediately after the IP header and any options, and before any higher layer protocols (for example, TCP or UDP). There are slight differences for transport mode when you implement it with AH and ESP:
 - For AH, selected portions of the IP header are protected, as well as selected portions of the extension headers and selected options within the IPv4 header.
 - For ESP, only the higher layer protocols are protected, not the IP header or any extension headers preceding the ESP header.



NOTE: Support for IPSec transport mode is primarily limited to routing authentication and to certain configurations only application when Junos FIPs code is used.

**Related
Documentation**

- [Overview of IPSec on page 3](#)
- [Configuring Security Associations on page 25](#)
- [Understanding OSPFv3 Authentication](#)
- [Example: Configuring IPsec Authentication for an OSPF Interface](#)

Digital Certificates

For small networks, the use of preshared keys in an IPSec configuration is often sufficient. However, as a network grows, it can become a challenge to add new preshared keys on the local router and all new and existing IPSec peers. One solution for scaling an IPSec network is to use digital certificates.

A digital certificate implementation uses the public key infrastructure (PKI), which requires you to generate a key pair consisting of a public key and a private key. The keys are created with a random number generator and are used to encrypt and decrypt data. In networks that do not use digital certificates, an IPSec-enabled device encrypts data with the private key and IPSec peers decrypt the data with the public key.

With digital certificates, the key sharing process requires an additional level of complexity. First, you and your IPSec peers request a certificate authority (CA) to send you a CA certificate that contains the public key of the CA. Next, you request the CA to enroll a local digital certificate that contains your public key and some additional information. When the CA processes your request, it signs your local certificate with the private key of the CA. Then you install the CA certificate and the local certificate in your local router and load the CA certificate in the remote devices before you can establish IPSec tunnels with your peers.

When you request a peering relationship with an IPSec peer, the peer receives a copy of your local certificate. Because the peer already has the CA certificate loaded, it can use the CA's public key contained in the CA certificate to decrypt your local certificate that has been signed by the CA's private key. As a result, the peer now has a copy of your public key. The peer encrypts data with your public key before sending it to you. When your local router receives the data, it decrypts the data with your private key.

In the Junos OS, you must implement the following steps to be able to initially use digital certificates:

- Configure a CA profile to request CA and local digital certificates—The profile contains the name and URL of the CA or registration authority (RA), as well as some retry timer settings.
- Configure certificate revocation list support—A certificate revocation list (CRL) contains a list of certificates canceled before their expiration date. When a participating peer

uses a CRL, the CA acquires the most recently issued CRL and checks the signature and validity of a peer's digital certificate. You can request and load CRLs manually, configure an LDAP server to handle CRL processing automatically, or disable CRL processing that is enabled by default.

- Request a digital certificate from the CA—The request can be made either online or manually. Online CA digital certificate requests use the Simple Certificate Enrollment Protocol (SCEP) format. If you request the CA certificate manually, you must also load the certificate manually.
- Generate a private/public key pair—The public key is included in the local digital certificate and the private key is used to decrypt data received from peers.
- Generate and enroll a local digital certificate—The local certificate can be processed online using SCEP or generated manually in the Public-Key Cryptography Standards #10 (PKCS-10) format. If you create the local certificate request manually, you must also load the certificate manually.
- Apply the digital certificate to an IPSec configuration—To activate a local digital certificate, you configure the IKE proposal to use digital certificates instead of preshared keys, reference the local certificate in the IKE policy, and identify the CA in the service set.

Optionally, you can do the following:

- Configure the digital certificate to automatically reenroll—Starting in Junos OS Release 8.5, you can configure automatic reenrollment for digital certificates.
- Monitor digital certificate events and delete certificates and requests—You can issue operational mode commands to monitor IPSec tunnels established using digital certificates and delete certificates or requests.

For more details on managing digital certificates, configuring them in an IPSec service set, and monitoring and clearing them, see [“Option: Using Digital Certificates” on page 53](#) and [“Example: AS PIC IKE Dynamic SA with Digital Certificates Configuration” on page 110](#).

Service Sets

The Adaptive Services PIC supports two types of service sets when you configure IPSec tunnels. Because they are used for different purposes, it is important to know the differences between these service set types.

- Next-hop service set—Supports multicast and multicast-style dynamic routing protocols (such as OSPF) over IPSec. Next-hop service sets allow you to use *inside* and *outside* logical interfaces on the Adaptive Services PIC to connect with multiple routing instances. They also allow the use of Network Address Translation (NAT) and stateful firewall capabilities. However, next-hop service sets do not monitor Routing Engine traffic by default and require configuration of multiple service sets to support traffic from multiple interfaces.
- Interface service set—Applied to a physical interface and similar to a stateless firewall filter. They are easy to configure, can support traffic from multiple interfaces, and can

monitor Routing Engine traffic by default. However, they cannot support dynamic routing protocols or multicast traffic over the IPsec tunnel.

In general, we recommend that you use next-hop service sets because they support routing protocols and multicast over the IPsec tunnel, they are easier to understand, and the routing table makes forwarding decisions without administrative intervention.

**Related
Documentation**

- *Understanding Junos VPN Site Secure*
- *Configuring Junos VPN Site Secure Using Junos OS Extension Provider Package*

CHAPTER 2

System Requirements

- [System Requirements on page 13](#)

System Requirements

To implement IPSec, your system must meet these minimum requirements:

- Junos OS Release 8.5 or later for automatic reenrollment of digital certificates.
- Junos OS Release 8.3 or later for IPSec support on OSPF version 2
- Junos OS Release 8.2 or later for support on M120 routers
- Junos OS Release 8.1 or later for IPSec IKE support in routing instances, and certificate revocation list support on AS and MultiServices PICs installed on M Series and T Series routers
- Junos OS Release 7.6 or later for AES encryption and SHA-256 authentication support on AS PICs installed in M Series routers, and IPv6-based IPSec for AS PICs installed in M Series and T Series routers
- Junos OS Release 7.5 or later for digital certificate support on AS PICs installed in M Series and T Series routers, and support of the IPSec Monitoring Management Information Base (MIB)
- Junos OS Release 7.4 or later for dynamic endpoint tunneling support and configuring multiple routed tunnels in a single next-hop service set
- Junos OS Release 7.2 or later for transport mode IPSec on Routing Engines running OSPF version 3 and support for the AS II FIPS PIC
- Junos OS Release 7.1 or later for IPSec on the ES PIC for T Series and M320 routers
- Junos OS Release 6.4 or later for IPSec on the AS PIC for T Series and M320 routers
- Junos OS Release 6.2 or later for IPSec on the AS PIC for M Series routers
- Junos OS Release 5.7 or later for multicast over IPSec tunnels on M Series routers
- Junos OS Release 5.2 or later for IPSec on the ES PIC for M Series routers
- Two Juniper Networks M Series or T Series routers
- Two ES PICs or AS PICs for M Series and T Series routers

CHAPTER 3

Glossary

- [Terms and Acronyms on page 15](#)

Terms and Acronyms

A

Adaptive Services PIC	A next-generation Physical Interface Card (PIC) that provides IPSec services and other services, such as Network Address Translation (NAT) and stateful firewall, on M Series and T Series platforms.
Advanced Encryption Standard (AES)	A next-generation encryption method that is based on the Rijndael algorithm and uses a 128-bit block, three different key sizes (128, 192, and 256 bits), and multiple rounds of processing to encrypt data.
authentication header (AH)	A component of the IPSec protocol used to verify that the contents of a packet have not changed (data integrity), and to validate the identity of the sender (data source authentication). For more information about AH, see RFC 2402.

C

certificate authority (CA)	A trusted third-party organization that generates, enrolls, validates, and revokes digital certificates. The CA guarantees the identity of a user and issues public and private keys for message encryption and decryption.
certificate revocation list (CRL)	A list of digital certificates that have been invalidated before their expiration date, including the reasons for their revocation and the names of the entities that have issued them. A CRL prevents usage of digital certificates and signatures that have been compromised.
cipher block chaining (CBC)	A cryptographic method that encrypts blocks of ciphertext by using the encryption result of one block to encrypt the next block. Upon decryption, the validity of each block of ciphertext depends on the validity of all the preceding ciphertext blocks. For more information on how to use CBC with DES and ESP to provide confidentiality, see RFC 2405.

D

Data Encryption Standard (DES)	An encryption algorithm that encrypts and decrypts packet data by processing the data with a single shared key. DES operates in increments of 64-bit blocks and provides 56-bit encryption.
---------------------------------------	---

digital certificate Electronic file that uses private and public key technology to verify the identity of a certificate creator and distribute keys to peers.

E

Encapsulating Security Payload (ESP) A component of the IPSec protocol used to encrypt data in an IPv4 or IPv6 packet, provide data integrity, and ensure data source authentication. For more information about ESP, see RFC 2406.

ES PIC A PIC that provides first-generation encryption services and software support for IPSec on M Series and T Series platforms.

H

Hashed Message Authentication Code (HMAC) A mechanism for message authentication using cryptographic hash functions. HMAC can be used with any iterative cryptographic hash function, such as MD5 or SHA-1, in combination with a secret shared key. For more information on HMAC, see RFC 2104.

I

Internet Key Exchange (IKE) Establishes shared security parameters for any hosts or routers using IPSec. IKE establishes the SAs for IPSec. For more information about IKE, see RFC 2407.

M

Message Digest 5 (MD5) An authentication algorithm that takes a data message of arbitrary length and produces a 128-bit message digest. For more information, see RFC 1321.

P

Perfect Forward Secrecy (PFS) Provides additional security by means of a Diffie-Hellman shared secret value. With PFS, if one key is compromised, previous and subsequent keys are secure because they are not derived from previous keys.

public key infrastructure (PKI) A trust hierarchy that enables users of a public network to securely and privately exchange data through the use of public and private cryptographic key pairs that are obtained and shared with peers through a trusted authority.

R

registration authority (RA) A trusted third-party organization that acts on behalf of a CA to guarantee the identity of a user.

Routing Engine A PCI-based architectural portion of a Junos OS-based router that handles the routing protocol process, the interface process, some of the chassis components, system management, and user access.

S

Secure Hash Algorithm 1 (SHA-1) An authentication algorithm that takes a data message of less than 264 bits in length and produces a 160-bit message digest. For more information on SHA-1, see RFC 3174.

Secure Hash Algorithm 2 (SHA-2)	A successor to the SHA-1 authentication algorithm that includes a group of SHA-1 variants (SHA-224, SHA-256, SHA-384, and SHA-512). SHA-2 algorithms use larger hash sizes and are designed to work with enhanced encryption algorithms such as AES.
security association (SA)	Specifications that must be agreed upon between two network devices before IKE or IPSec are allowed to function. SAs primarily specify protocol, authentication, and encryption options.
Security Association Database (SADB)	A database where all SAs are stored, monitored, and processed by IPSec.
Security Parameter Index (SPI)	An identifier that is used to uniquely identify an SA at a network host or router.
Security Policy Database (SPD)	A database that works with the SADB to ensure maximum packet security. For inbound packets, IPSec checks the SPD to verify if the incoming packet matches the security configured for a particular policy. For outbound packets, IPSec checks the SPD to see if the packet needs to be secured.
Simple Certificate Enrollment Protocol (SCEP)	A protocol that supports CA and registration authority (RA) public key distribution, certificate enrollment, certificate revocation, certificate queries, and certificate revocation list (CRL) queries.
T	
Triple Data Encryption Standard (3DES)	An enhanced DES algorithm that provides 168-bit encryption by processing data three times with three different keys.

PART 2

Configuration

- [IPSec Configuration on page 21](#)
- [Digital Certificates on page 39](#)
- [Other Options on page 45](#)
- [IPSec Dynamic Endpoints on page 55](#)

CHAPTER 4

IPSec Configuration

- [Considering General IPSec Issues on page 21](#)
- [Configuring Security Associations on page 25](#)
- [Using a Filter to Select Traffic to Be Secured on page 30](#)
- [Applying the Filter or Service Set to the Interface Receiving Traffic to Be Secured on page 31](#)
- [Configuring IKE Dynamic SAs on page 32](#)
- [Configuring Manual SAs on page 35](#)

Considering General IPSec Issues

Before you configure IPSec, it is helpful to understand some general guidelines.

- IPv4 and IPv6 traffic and tunnels—You can configure IPSec tunnels to carry traffic in the following ways: IPv4 traffic traveling over IPv4 IPSec tunnels, IPv6 traffic traveling over IPv4 IPSec tunnels, IPv4 traffic traveling over IPv6 IPSec tunnels, and IPv6 traffic traveling over IPv6 IPSec tunnels.
- Configuration syntax differences between the AS and MultiServices PICs and the ES PIC—There are slight differences in the configuration statements and operational mode commands that are used with the PICs that support IPSec. As a result, the syntax for the AS and MultiServices PICs cannot be used interchangeably with the syntax for the ES PIC. However, the syntax for one type of PIC can be converted to its equivalent syntax on the other PIC for interoperability. The differences are highlighted in [Table 3 on page 21](#).
- Configuring keys for authentication and encryption—When preshared keys are required for authentication or encryption, you must use the guidelines shown in [Table 4 on page 23](#) to implement the correct key size.
- Rejection of weak and semiweak keys—The DES and 3DES encryption algorithms will reject weak and semiweak keys. As a result, do not create and use keys that contain the patterns listed in [Table 5 on page 24](#).

Table 3: Comparison of IPSec Configuration Statements and

Table 3: Comparison of IPSec Configuration Statements and Operational Mode Commands for the AS and MultiServices PICs and ES PIC *(continued)*

Operational Mode Commands for the AS and MultiServices PICs and ES PIC

AS and MultiServices PICs Statements and Commands	ES PIC Statements and Commands
Configuration Mode Statements	
[edit service-set <i>name</i>]	—
[edit services ipsec-vpn ike] <ul style="list-style-type: none"> • policy {...} • proposal {...} 	[edit security ike] <ul style="list-style-type: none"> • policy {...} • proposal {...}
[edit services ipsec-vpn ipsec] <ul style="list-style-type: none"> • policy {...} • proposal {...} 	[edit security ipsec] <ul style="list-style-type: none"> • policy {...} • proposal {...}
[edit services ipsec-vpn rule <i>rule-name</i>] <ul style="list-style-type: none"> • remote-gateway <i>address</i> 	[edit interface es- <i>fpc</i> / <i>pic</i> / <i>port</i>] <ul style="list-style-type: none"> • tunnel destination <i>address</i>
[edit services ipsec-vpn rule <i>rule-name</i> term <i>term-name</i>] <ul style="list-style-type: none"> • from <i>match-conditions</i> {...} then dynamic {...} • from <i>match-conditions</i> {...} then manual {...} 	[edit security ipsec] <ul style="list-style-type: none"> • security-association <i>name</i> dynamic {...} • security-association <i>name</i> manual {...}
[edit services ipsec-vpn rule-set]	—
[edit services service-set ipsec-vpn] <ul style="list-style-type: none"> • local-gateway <i>address</i> 	[edit interface es- <i>fpc</i> / <i>pic</i> / <i>port</i>] <ul style="list-style-type: none"> • tunnel source <i>address</i>
Operational Mode Commands	
clear security pki ca-certificate	—
clear security pki certificate-request	—
clear security pki local-certificate	—
clear services ipsec-vpn certificates	—
request security pki ca-certificate enroll	request security certificate (unsigned)
request security pki ca-certificate load	request system certificate add

Table 3: Comparison of IPSec Configuration Statements and Operational Mode Commands for the AS and MultiServices PICs and ES PIC *(continued)*

AS and MultiServices PICs Statements and Commands	ES PIC Statements and Commands
<code>request security pki generate-certificate-request</code>	—
<code>request security pki generate-key-pair</code>	<code>request security key-pair</code>
<code>request security pki local-certificate enroll</code>	<code>request security certificate (signed)</code>
<code>request security pki local-certificate load</code>	<code>request system certificate add</code>
<code>show security pki ca-certificate</code>	<code>show system certificate</code>
<code>show security pki certificate-request</code>	—
<code>show security pki crt</code>	—
<code>show security pki local-certificate</code>	<code>show system certificate</code>
<code>show services ipsec-vpn certificates</code>	<code>show ipsec certificates</code>
<code>show services ipsec-vpn ike security-associations</code>	<code>show ike security-associations</code>
<code>show services ipsec-vpn ipsec security-associations</code>	<code>show ipsec security-associations</code>

Table 4: Authentication and Encryption Key Lengths

	Number of Hexadecimal Characters	Number of ASCII Characters
Authentication		
HMAC-MD5-96	32	16
HMAC-SHA1-96	40	20
Encryption		
AES-128-CBC	16	32
AES-192-CBC	24	48
AES-256-CBC	32	64
DES-CBC	16	8
3DES-CBC	48	24

Table 5: Weak and Semiweak Keys

Weak Keys			
0101	0101	0101	0101
1F1F	1F1F	1F1F	1F1F
E0E0	E0E0	E0E0	E0E0
FEFE	FEFE	FEFE	FEFE
Semiweak Keys			
01FE	01FE	01FE	01FE
1FE0	1FE0	0EF1	0EF1
01E0	01E0	01F1	01F1
1FFE	1FFE	0EFE	0EFE
011F	011F	010E	010E
E0FE	E0FE	F1FE	F1FE
FE01	FE01	FE01	FE01
E01F	E01F	F10E	F10E
E001	E001	F101	F101
FEF1	FEF1	FE0E	FE0E
1F01	1F01	0E01	0E01
FEE0	FEE0	FEF1	FEF1

Keep in mind the following limitations of IPSec services on the AS PIC:

- The AS PIC does not transport packets containing IPv4 options across IPSec tunnels. If you try to send packets containing IP options across an IPSec tunnel, the packets are dropped. Also, if you issue a **ping** command with the **record-route** option across an IPSec tunnel, the **ping** command fails.
- The AS PIC does not transport packets containing the following IPv6 options across IPSec tunnels: hop-by-hop, destination (Type 1 and 2), and routing. If you try to send packets containing these IPv6 options across an IPSec tunnel, the packets are dropped.
- Destination class usage is not supported with IPSec services on the AS PIC.

Configuring Security Associations

The first IPSec configuration step is to select a type of security association for your IPSec connection. You must statically configure all specifications for manual SAs, but you can rely on some defaults when you configure an IKE dynamic SA. To configure a security association, see the following sections.

- [Configuring Manual SAs on page 25](#)
- [Configuring IKE Dynamic SAs on page 26](#)

Configuring Manual SAs

On the ES PIC, you configure a manual security association at the **[edit security ipsec security-association *sa-name*]** hierarchy level. Include your choices for authentication, encryption, direction, mode, protocol, and SPI. Be sure that these choices are configured exactly the same way on the remote IPSec gateway.

```
[edit security]
ipsec {
  security-association sa-name {
    description description;
    manual {
      direction (inbound | outbound | bidirectional) {
        authentication {
          algorithm (hmac-md5-96 | hmac-sha1-96);
          key (ascii-text key | hexadecimal key);
        }
        auxiliary-spi auxiliary-spi;
        encryption {
          algorithm (des-cbc | 3des-cbc);
          key (ascii-text key | hexadecimal key);
        }
        protocol (ah | esp | bundle);
        spi spi-value;
      }
    }
    mode (tunnel | transport);
  }
}
```

On the AS and MultiServices PICs, you configure a manual security association at the **[edit services ipsec-vpn rule *rule-name*]** hierarchy level. Include your choices for authentication, encryption, direction, protocol, and SPI. Be sure that these choices are configured exactly the same way on the remote IPSec gateway.

```
[edit services ipsec-vpn]
rule rule-name {
  match-direction (input | output);
  term term-name {
    from {
      destination-address address;
      source-address address;
    }
  }
}
```

```

then {
    backup-remote-gateway address;
    clear-dont-fragment-bit;
    manual {
        direction (inbound | outbound | bidirectional) {
            authentication {
                algorithm (hmac-md5-96 | hmac-sha1-96);
                key (ascii-text key | hexadecimal key);
            }
            auxiliary-spi spi-value;
            encryption {
                algorithm algorithm; # This can be aes-128-cbc, aes-192-cbc,
                # aes-256-cbc, des-cbc, or 3des-cbc.
                key (ascii-text key | hexadecimal key);
            }
            protocol (ah | bundle | esp);
            spi spi-value;
        }
    }
    no-anti-replay;
    remote-gateway address;
    syslog;
}
}
rule-set rule-set-name {
    [ rule rule-names ];
}

```

Configuring IKE Dynamic SAs

On the ES PIC, you configure an IKE dynamic SA at the **[edit security ike]** and **[edit security ipsec]** hierarchy levels. Include your choices for IKE policies and proposals, which include options for authentication algorithms, authentication methods, Diffie-Hellman groups, encryption, IKE modes, and preshared keys. The IKE policy must use the IP address of the remote end of the IPSec tunnel as the policy name. Also, include your choices for IPSec policies and proposals, which include options for authentication, encryption, protocols, Perfect Forward Secrecy (PFS), and IPSec modes. Be sure that these choices are configured exactly the same way on the remote IPSec gateway.

```

[edit security]
ike {
    proposal ike-proposal-name {
        authentication-algorithm (md5 | sha1 | sha-256 | sha-384);
        authentication-method (dsa-signatures | pre-shared-keys | rsa-signatures);
        description description;
        dh-group (group1 | group2);
        encryption-algorithm (3des-cbc | aes-128-cbc | aes-192-cbc | aes-256-cbc | des-cbc);
        lifetime-seconds seconds;
    }
    policy ike-peer-address {
        description description;
        encoding (binary | pem);
        identity identity-name;
        local-certificate certificate-filename;
    }
}

```

```

    local-key-pair private-public-key-file;
    mode (aggressive | main);
    pre-shared-key (ascii-text key | hexadecimal key);
    proposals [ proposal-names ];
  }
}
ipsec {
  proposal ipsec-proposal-name {
    authentication-algorithm (hmac-md5-96 | hmac-sha1-96 | hmac-sha-256-128);
    description description;
    encryption-algorithm (3des-cbc | aes-128-cbc | aes-192-cbc | aes-256-cbc | des-cbc);
    lifetime-seconds seconds;
    protocol (ah | esp | bundle);
  }
  policy ipsec-policy-name {
    description description;
    perfect-forward-secrecy {
      keys (group1 | group2);
    }
    proposals [ proposal-names ];
  }
  security-association sa-name {
    description description;
    dynamic {
      ipsec-policy policy-name;
      replay-window-size (32 | 64);
    }
    mode (tunnel | transport);
  }
}

```

On the AS and MultiServices PICs, you configure an IKE dynamic security association at the `[edit services ipsec-vpn ike]`, `[edit services ipsec-vpn ipsec]`, and `[edit services ipsec-vpn rule rule-name]` hierarchy levels. Include your choices for IKE policies and proposals, which include options for authentication algorithms, authentication methods, Diffie-Hellman groups, encryption, IKE modes, and preshared keys. Also, include your choices for IPSec policies and proposals, which include options for authentication, encryption, protocols, PFS, and IPSec modes. Be sure that these choices are configured exactly the same way on the remote IPSec gateway.

If you choose not to explicitly configure IKE and IPSec policies and proposals on the AS and MultiServices PICs, your configuration can default to some preset values. These default values are shown in [Table 6 on page 27](#).

Table 6: IKE and IPSec Proposal and Policy Default Values for the AS and MultiServices PICs

IKE Policy Statement	Default Value
<code>mode</code>	<code>main</code>
<code>proposals</code>	<code>default</code>
IKE Proposal Statement	Default Value

Table 6: IKE and IPSec Proposal and Policy Default Values for the AS and MultiServices PICs (*continued*)

IKE Policy Statement	Default Value
authentication-algorithm	sha1
authentication-method	pre-shared-keys
dh-group	group2
encryption-algorithm	3des-cbc
lifetime-seconds	3600 (seconds)
IPSec Policy Statement	Default Value
perfect-forward-secrecy keys	group2
proposals	default
IPSec Proposal Statement	Default Value
authentication-algorithm	hmac-sha1-96
encryption-algorithm	3des-cbc
lifetime-seconds	28800 (seconds)
protocol	esp



NOTE: If you use the default IKE and IPSec policy and proposal values preset within the AS and MultiServices PICs, you must explicitly configure an IKE policy and include a preshared key. This is because the pre-shared-keys authentication method is one of the preset values in the default IKE proposal.

If you decide to configure values manually, the following information shows the complete statement hierarchy and options for dynamic IKE SAs on the AS and MultiServices PICs:

```
[edit services ipsec-vpn]
ike {
  proposal proposal-name {
    authentication-algorithm (md5 | sha1 | sha256);
    authentication-method (pre-shared-keys | rsa-signatures);
    description description;
    dh-group (group1 | group2);
    encryption-algorithm algorithm; # This can be aes-128-cbc, aes-192-cbc,
    # aes-256-cbc, des-cbc, or 3des-cbc.
    lifetime-seconds seconds;
  }
}
```

```

policy policy-name {
  description description;
  local-id {
    ipv4_addr [ values ];
    key_id [ values ];
  }
  local-certificate certificate-id-name;
  mode (aggressive | main);
  pre-shared-key (ascii-text key | hexadecimal key);
  proposals [ proposal-names ];
  remote-id {
    ipv4_addr [ values ];
    key_id [ values ];
  }
}
}
ipsec {
  proposal proposal-name {
    authentication-algorithm (hmac-md5-96 | hmac-sha1-96);
    description description;
    encryption-algorithm algorithm; # This can be aes-128-cbc, aes-192-cbc,
    # aes-256-cbc, des-cbc, or 3des-cbc.
    lifetime-seconds seconds;
    protocol (ah | esp | bundle);
  }
  policy policy-name {
    description description;
    perfect-forward-secrecy {
      keys (group1 | group2);
    }
    proposals [ proposal-names ];
  }
}
rule rule-name {
  match-direction (input | output);
  term term-name {
    from {
      destination-address address;
      source-address address;
    }
    then {
      backup-remote-gateway address;
      clear-dont-fragment-bit;
      dynamic {
        ike-policy policy-name;
        ipsec-policy policy-name;
      }
      no-anti-replay;
      remote-gateway address;
      syslog;
    }
  }
}
rule-set rule-set-name {
  [ rule rule-names ];
}

```

Using a Filter to Select Traffic to Be Secured

For the ES PIC, you need to configure a firewall filter to direct traffic into the IPSec tunnel. To apply a security association to traffic that matches a firewall filter, include the **ipsec-sa sa-name** statement at the **[edit firewall filter filter-name term term-name then]** hierarchy level.

```
[edit firewall filter filter-name]
term term-name {
  from {
    source-address {
      ip-address;
    }
    destination-address {
      ip-address;
    }
  }
  then {
    count counter-name;
    ipsec-sa sa-name;
  }
}
term other {
  then accept;
}
```

For the AS and MultiServices PICs, you do not need to configure a separate firewall filter. A filter is already built into the IPSec VPN **rule** statement at the **[edit services ipsec-vpn]** hierarchy level. To apply a security association to traffic that matches the IPSec VPN rule, include the **dynamic** or **manual** statement at the **[edit services rule rule-name term term-name then]** hierarchy level. To specify whether the rule should match input or output traffic, include the **match-direction** statement at the **[edit services rule rule-name]** hierarchy level.

After defining the rules for your IPSec VPNs, you must apply the rules to a service set. To do this, include the **ipsec-vpn-rules rule-name** statement at the **[edit services service-set service-set-name]** hierarchy level. Include an IPv4 or IPv6 IPSec gateway with the **local-gateway local-ip-address** statement at the **[edit services service-set service-set-name]** hierarchy level.

Also, you must select either a single interface or a pair of interfaces that participate in IPSec. To select a single interface, include the interface-service **interface-name** statement at the **[edit services service-set service-set-name]** hierarchy level. To select a pair of interfaces and a next hop, include the **next-hop-service** statement at the **[edit services service-set service-set-name]** hierarchy level and specify an inside interface and an outside interface. Only next-hop service sets support IPSec within Layer 3 VPNs and use of routing protocols over the IPSec tunnel.

```
[edit services]
service-set service-set-name {
  interface-service {
    service-interface interface-name;
```

```

}
next-hop-service {
    inside-service-interface interface-name;
    outside-service-interface interface-name;
}
ipsec-vpn-options {
    local-gateway local-ip-address <routing-instance instance-name>;
    trusted-ca ca-profile-name;
}
ipsec-vpn-rules rule-name;
}
ipsec-vpn {
    rule rule-name {
        term term-name {
            from {
                source-address {
                    ip-address;
                }
                destination-address {
                    ip-address;
                }
            }
            then {
                remote-gateway remote-ip-address;
                (dynamic | manual);
            }
        }
    }
    match-direction output;
}
}

```

Applying the Filter or Service Set to the Interface Receiving Traffic to Be Secured

For the ES PIC, apply your firewall filter on the input interface receiving the traffic that you wish to send to the IPSec tunnel. To do this, include the **filter** statement at the **[edit interfaces *interface-name* unit *unit-number* family inet]** hierarchy level.

```

[edit interfaces interface-name unit unit-number family inet]
filter {
    input filter-name;
}

```

For the AS and MultiServices PICs, apply your IPSec-based interface service set to the input interface receiving the traffic that you wish to send to the IPSec tunnel. To do this, include the **service-set *service-set-name*** statement at the **[edit interfaces *interface-name* unit *unit-number* family inet service (input | output)]** hierarchy level.

```

[edit interfaces interface-name unit unit-number family inet]
service {
    input {
        service-set service-set-name;
    }
    output {
        service-set service-set-name;
    }
}

```

```
}
```

To configure a next-hop-based service set on the AS and MultiServices PICs, include the **service-domain** statement at the **[edit interfaces *interface-name* unit *unit-number*]** hierarchy level and specify one logical interface on the AS PIC as an inside interface and a second logical interface on the AS PIC as an outside interface.

```
[edit interfaces sp-fpc/pic/port]
unit 0 {
  family inet {
    address ip-address;
  }
}
unit 1 {
  family inet;
  service-domain inside;
}
unit 2 {
  family inet;
  service-domain outside;
}
```

Configuring IKE Dynamic SAs

On the ES PIC, you configure an IKE dynamic SA at the **[edit security ike]** and **[edit security ipsec]** hierarchy levels. Include your choices for IKE policies and proposals, which include options for authentication algorithms, authentication methods, Diffie-Hellman groups, encryption, IKE modes, and preshared keys. The IKE policy must use the IP address of the remote end of the IPSec tunnel as the policy name. Also, include your choices for IPSec policies and proposals, which include options for authentication, encryption, protocols, Perfect Forward Secrecy (PFS), and IPSec modes. Be sure that these choices are configured exactly the same way on the remote IPSec gateway.

```
[edit security]
ike {
  proposal ike-proposal-name {
    authentication-algorithm (md5 | sha1 | sha-256 | sha-384);
    authentication-method (dsa-signatures | pre-shared-keys | rsa-signatures);
    description description;
    dh-group (group1 | group2);
    encryption-algorithm (3des-cbc | aes-128-cbc | aes-192-cbc | aes-256-cbc | des-cbc);
    lifetime-seconds seconds;
  }
  policy ike-peer-address {
    description description;
    encoding (binary | pem);
    identity identity-name;
    local-certificate certificate-filename;
    local-key-pair private-public-key-file;
    mode (aggressive | main);
    pre-shared-key (ascii-text key | hexadecimal key);
    proposals [ proposal-names ];
  }
}
```



```

ipsec {
  proposal ipsec-proposal-name {
    authentication-algorithm (hmac-md5-96 | hmac-sha1-96 | hmac-sha-256-128);
    description description;
    encryption-algorithm (3des-cbc | aes-128-cbc | aes-192-cbc | aes-256-cbc | des-cbc);
    lifetime-seconds seconds;
    protocol (ah | esp | bundle);
  }
  policy ipsec-policy-name {
    description description;
    perfect-forward-secrecy {
      keys (group1 | group2);
    }
    proposals [ proposal-names ];
  }
  security-association sa-name {
    description description;
    dynamic {
      ipsec-policy policy-name;
      replay-window-size (32 | 64);
    }
    mode (tunnel | transport);
  }
}

```

On the AS and MultiServices PICs, you configure an IKE dynamic security association at the `[edit services ipsec-vpn ike]`, `[edit services ipsec-vpn ipsec]`, and `[edit services ipsec-vpn rule rule-name]` hierarchy levels. Include your choices for IKE policies and proposals, which include options for authentication algorithms, authentication methods, Diffie-Hellman groups, encryption, IKE modes, and preshared keys. Also, include your choices for IPSec policies and proposals, which include options for authentication, encryption, protocols, PFS, and IPSec modes. Be sure that these choices are configured exactly the same way on the remote IPSec gateway.

If you choose not to explicitly configure IKE and IPSec policies and proposals on the AS and MultiServices PICs, your configuration can default to some preset values. These default values are shown in [Table 6 on page 27](#).

Table 7: IKE and IPSec Proposal and Policy Default Values for the AS and MultiServices PICs

IKE Policy Statement	Default Value
mode	main
proposals	default
IKE Proposal Statement	Default Value
authentication-algorithm	sha1
authentication-method	pre-shared-keys
dh-group	group2

Table 7: IKE and IPSec Proposal and Policy Default Values for the AS and MultiServices PICs (*continued*)

IKE Policy Statement	Default Value
encryption-algorithm	3des-cbc
lifetime-seconds	3600 (seconds)
IPSec Policy Statement	Default Value
perfect-forward-secrecy keys	group2
proposals	default
IPSec Proposal Statement	Default Value
authentication-algorithm	hmac-sha1-96
encryption-algorithm	3des-cbc
lifetime-seconds	28800 (seconds)
protocol	esp



NOTE: If you use the default IKE and IPSec policy and proposal values preset within the AS and MultiServices PICs, you must explicitly configure an IKE policy and include a preshared key. This is because the **pre-shared-keys** authentication method is one of the preset values in the default IKE proposal.

If you decide to configure values manually, the following information shows the complete statement hierarchy and options for dynamic IKE SAs on the AS and MultiServices PICs:

```
[edit services ipsec-vpn]
ike {
  proposal proposal-name {
    authentication-algorithm (md5 | sha1 | sha256);
    authentication-method (pre-shared-keys | rsa-signatures);
    description description;
    dh-group (group1 | group2);
    encryption-algorithm algorithm; # This can be aes-128-cbc, aes-192-cbc,
    # aes-256-cbc, des-cbc, or 3des-cbc.
    lifetime-seconds seconds;
  }
  policy policy-name {
    description description;
    local-id {
      ipv4_addr [ values ];
      key_id [ values ];
    }
  }
}
```

```

local-certificate certificate-id-name;
mode (aggressive | main);
pre-shared-key (ascii-text key | hexadecimal key);
proposals [ proposal-names ];
remote-id {
    ipv4_addr [ values ];
    key_id [ values ];
}
}
}
ipsec {
    proposal proposal-name {
        authentication-algorithm (hmac-md5-96 | hmac-sha1-96);
        description description;
        encryption-algorithm algorithm; # This can be aes-128-cbc, aes-192-cbc,
        # aes-256-cbc, des-cbc, or 3des-cbc.
        lifetime-seconds seconds;
        protocol (ah | esp | bundle);
    }
    policy policy-name {
        description description;
        perfect-forward-secrecy {
            keys (group1 | group2);
        }
        proposals [ proposal-names ];
    }
}
rule rule-name {
    match-direction (input | output);
    term term-name {
        from {
            destination-address address;
            source-address address;
        }
        then {
            backup-remote-gateway address;
            clear-dont-fragment-bit;
            dynamic {
                ike-policy policy-name;
                ipsec-policy policy-name;
            }
            no-anti-replay;
            remote-gateway address;
            syslog;
        }
    }
}
rule-set rule-set-name {
    [ rule rule-names ];
}

```

Configuring Manual SAs

On the ES PIC, you configure a manual security association at the **[edit security ipsec security-association *name*]** hierarchy level. Include your choices for authentication,

encryption, direction, mode, protocol, and SPI. Be sure that these choices are configured exactly the same way on the remote IPSec gateway.

```
[edit security]
ipsec {
  security-association sa-name {
    description description;
    manual {
      direction (inbound | outbound | bidirectional) {
        authentication {
          algorithm (hmac-md5-96 | hmac-sha1-96);
          key (ascii-text key | hexadecimal key);
        }
        auxiliary-spi auxiliary-spi;
        encryption {
          algorithm (des-cbc | 3des-cbc);
          key (ascii-text key | hexadecimal key);
        }
        protocol (ah | esp | bundle);
        spi spi-value;
      }
    }
    mode (tunnel | transport);
  }
}
```

On the AS and MultiServices PICs, you configure a manual security association at the **[edit services ipsec-vpn rule *rule-name*]** hierarchy level. Include your choices for authentication, encryption, direction, protocol, and SPI. Be sure that these choices are configured exactly the same way on the remote IPSec gateway.

```
[edit services ipsec-vpn]
rule rule-name {
  match-direction (input | output);
  term term-name {
    from {
      destination-address address;
      source-address address;
    }
    then {
      backup-remote-gateway address;
      clear-dont-fragment-bit;
      manual {
        direction (inbound | outbound | bidirectional) {
          authentication {
            algorithm (hmac-md5-96 | hmac-sha1-96);
            key (ascii-text key | hexadecimal key);
          }
          auxiliary-spi spi-value;
          encryption {
            algorithm algorithm; # This can be aes-128-cbc, aes-192-cbc,
            # aes-256-cbc, des-cbc, or 3des-cbc.
            key (ascii-text key | hexadecimal key);
          }
          protocol (ah | bundle | esp);
          spi spi-value;
        }
      }
    }
  }
}
```

```
    }  
  }  
  no-anti-replay;  
  remote-gateway address;  
  syslog;  
}  
}  
rule-set rule-set-name {  
  [ rule rule-names ];  
}
```


CHAPTER 5

Digital Certificates

- [Configuring a CA Profile on page 39](#)
- [Configuring a Certificate Revocation List on page 40](#)
- [Requesting a CA Digital Certificate on page 41](#)
- [Generating a Private/Public Key Pair on page 41](#)
- [Generating and Enrolling a Local Digital Certificate on page 41](#)
- [Applying the Local Digital Certificate to an IPSec Configuration on page 41](#)
- [Configuring Automatic Reenrollment of Digital Certificates on page 42](#)
- [Monitoring Digital Certificates on page 42](#)
- [Clearing Digital Certificates on page 43](#)

Configuring a CA Profile

The CA profile contains the name and URL of the CA or RA, as well as some retry timer settings. CA certificates issued by Entrust, VeriSign, and Microsoft are all compatible with M Series, and T Series routers. To configure the domain name of the CA or RA, include the **ca-identity** statement at the **[edit security pki ca-profile *ca-profile-name*]** hierarchy level. To configure the URL of the CA, include the **url** statement at the **[edit security pki ca-profile *ca-profile-name* enrollment]** hierarchy level. To configure the number of enrollment attempts the router should perform, include the **retry** statement at the **[edit security pki ca-profile *ca-profile-name* enrollment]** hierarchy level. To configure the amount of time the router should wait between enrollment attempts, include the **retry-interval** statement at the **[edit security pki ca-profile *ca-profile-name* enrollment]** hierarchy level.

```
[edit security pki]
ca-profile ca-profile-name {
  ca-identity ca-identity;
  enrollment {
    url url-name;
    retry number-of-enrollment-attempts; # The range is 0 though 100 attempts.
    retry-interval seconds; # The range is 0 though 3600 seconds.
  }
}
```

Configuring a Certificate Revocation List

A certificate revocation list (CRL) contains a list of digital certificates that have been canceled before their expiration date. When a participating peer uses a digital certificate, it checks the certificate signature and validity. It also acquires the most recently issued CRL and checks that the certificate serial number is not on that CRL. By default, CRL verification is enabled on any CA profile running on Junos OS Release 8.1 or later. To disable CRL verification, include the **disable** statement at the **[edit security pki ca-profile ca-profile-name revocation-check]** hierarchy level.

To specify the URL for the Lightweight Directory Access Protocol (LDAP) server where your CA stores its current CRL, include the **url** statement at the **[edit security pki ca-profile ca-profile-name revocation-check crl]** hierarchy level. If the LDAP server requires a password to access the CRL, include the **password** statement at the **[edit security pki ca-profile ca-profile-name revocation-check crl url]** hierarchy level.



NOTE: You do not need to specify a URL for the LDAP server if the certificate includes a certificate distribution point (CDP). The CDP is a field within the certificate that contains information about how to retrieve the CRL for the certificate. The router uses this information to download the CRL automatically. Any LDAP URL you configure takes precedence over the CDP included in the certificate.

If you manually downloaded the CRL, you must manually install it on the router. To manually install the CRL, issue the **request security pki crl load ca-profile ca-profile-name filename path/filename** command.

To configure the time interval between CRL updates, include the **refresh-interval** statement at the **[edit security ca-profile ca-profile-name revocation-check crl]** hierarchy level.

To override the default behavior and permit IPSec peer authentication to continue when the CRL fails to download, include the **disable on-download-failure** statement at the **[edit security ca-profile ca-profile-name revocation-check crl]** hierarchy level.

```
[edit security pki ca-profile ca-profile-name]
revocation-check {
  disable;
  crl {
    disable on-download-failure;
    refresh-interval number-of-hours { # The range is 0 through 8784 hours.
      url {
        url-name;
        password;
      }
    }
  }
}
```


Requesting a CA Digital Certificate

You can request a CA digital certificate either online or manually. To request a digital certificate from a CA or RA online by using SCEP, issue the **request security pki ca-certificate enroll ca-profile *ca-profile-name*** command.

If you obtained the CA digital certificate manually through e-mail or other out-of-band mechanism, you must load it manually. To manually install a certificate in your router, issue the **request security pki local-certificate load** command.

Generating a Private/Public Key Pair

A key pair is a critical element of a digital certificate implementation. The public key is included in the local digital certificate and the private key is used to decrypt data received from peers. To generate a private/public key pair, issue the **request security pki generate-key-pair certificate-id *certificate-id-name*** command.

Generating and Enrolling a Local Digital Certificate

You can generate and enroll a local digital certificate either online or manually. To generate and enroll a local certificate online by using SCEP, issue the **request security pki local-certificate enroll** command. To generate a local certificate request manually in the PKCS-10 format, issue the **request security pki generate-certificate-request** command.

If you create the local certificate request manually, you must also load the certificate manually. To manually install a certificate in your router, issue the **request security pki local-certificate load** command.

Applying the Local Digital Certificate to an IPSec Configuration

To activate a local digital certificate, you configure the IKE proposal to use digital certificates instead of preshared keys, reference the local certificate in the IKE policy, and identify the CA or RA in the service set. To enable the IKE proposal for digital certificates, include the **rsa-signatures** statement at the **[edit services ipsec-vpn ike proposal *proposal-name* authentication-method]** hierarchy level. To reference the local certificate in the IKE policy, include the **local-certificate** statement at the **[edit services ipsec-vpn ike policy *policy-name*]** hierarchy level. To identify the CA or RA in the service set, include the **trusted-ca** statement at the **[edit services service-set *service-set-name* ipsec-vpn-options]** hierarchy level.

```
[edit services]
service-set service-set-name {
  .....
  ipsec-vpn-options {
    trusted-ca ca-profile-name;
  }
}
ipsec-vpn {
  ike {
    proposal proposal-name {
```

```

.....
    authentication-method [pre-shared-keys | rsa-signatures];
  }
  policy policy-name {
    .....
    local-certificate certificate-id-name;
  }
}
}

```

Configuring Automatic Reenrollment of Digital Certificates

You can configure automatic reenrollment for digital certificates. This feature is by default not enabled. To configure automatic reenrollment for digital certificates, include the **auto-re-enrollment** statement at the [edit security pki] hierarchy level:

```

[edit]
security {
  pki {
    auto-re-enrollment {
      certificate-id certificate-name {
        ca-profile ca-profile-name;
        challenge-password password;
        re-enroll-trigger-time-percentage percentage; # Percentage of validity-period
          # (specified in certificate) when automatic
          # reenrollment should be initiated.
        re-generate-keypair;
        validity-period number-of-days;
      }
    }
  }
}

```

Monitoring Digital Certificates

- | | |
|----------------|--|
| Purpose | You can issue various forms of the show security pki command to view digital certificates and certificate requests and certificate revocation lists: |
| Action | <ul style="list-style-type: none"> • To display the CA digital certificate, issue the show security pki ca-certificate ca-profile <i>ca-profile-name</i> command. • To display the local digital certificate and the public key used to enroll the certificate, issue the show security pki local-certificate certificate-id <i>certificate-id-name</i> command. • To display the local certificate request in PKCS-10 format, issue the show security pki certificate-request certificate-id <i>certificate-id-name</i> command. • You can also view which digital certificates are used in IKE negotiations to establish IPSec tunnels by issuing the show services ipsec-vpn certificates command. • To display the certificate revocation list, issue the show security pki crl ca-profile <i>ca-profile-name</i> command. • To determine if a certificate is enabled for automatic-reenrollment, issue the show security pki command. |

Clearing Digital Certificates

Purpose	Variations of the clear security pki command enable you to delete certificates or requests and certificate revocation lists:
Action	<ul style="list-style-type: none">• To delete the CA digital certificate, issue the clear security pki ca-certificate ca-profile <i>ca-profile-name</i> command.• To delete the local digital certificate and the associated private/public key pair, issue the clear security pki local-certificate certificate-id <i>certificate-id-name</i> command.• To delete the local certificate request, issue the clear security pki certificate-request certificate-id <i>certificate-id-name</i> command.• To clear the digital certificates that were used in IKE negotiations to establish IPsec tunnels, issue the clear services ipsec-vpn certificates command.• To delete the certificate revocation list, issue the clear security pki crl ca-profile <i>ca-profile-name</i> command.
Related Documentation	<ul style="list-style-type: none">• Example: AS PIC IKE Dynamic SA with Digital Certificates Configuration on page 110• <i>Security Services Administration Guide for Routing Devices</i>• <i>Junos VPN Site Secure</i>

CHAPTER 6

Other Options

- [Option: Using Filter-Based Forwarding to Select Traffic to Be Secured on page 45](#)
- [Option: Using IPSec with a Layer 3 VPN on page 46](#)
- [Option: Securing BGP Sessions with Transport Mode on page 48](#)
- [Option: Securing OSPFv3 Networks with Transport Mode on page 49](#)
- [Option: Securing OSPFv2 Networks with Transport Mode on page 49](#)
- [Option: Monitoring IPSec by Using SNMP on page 51](#)
- [Option: Configuring Multiple Routed Tunnels in a Single Next-Hop Service Set on page 51](#)
- [Option: Using Digital Certificates on page 53](#)

Option: Using Filter-Based Forwarding to Select Traffic to Be Secured

Instead of using a firewall filter, you can also forward traffic into an IPSec security association by using a filter-based forwarding instance. First, configure the filter-based forwarding instance. Then, configure a routing table group to advertise the routes from the filter-based forwarding instance. Next, create a firewall filter for the ES PIC and reference the filter-based forwarding instance. Lastly, apply the filter and IPSec security association to the ES PIC.

```
[edit]
routing-instances {
  forwarding {
    instance-type forwarding;
    routing-options {
      static {
        route 10.10.10.0/24 next-hop 192.168.0.5;
      }
    }
  }
}
routing-options {
  rib-groups {
    group-name {
      import-rib [ inet.0 forwarding.inet.0 ];
    }
  }
}
```

```

firewall {
  family inet {
    filter filter-name {
      term term-name {
        then routing-instance instance-name;
      }
    }
  }
}
[edit]
interfaces {
  es-0/0/0 {
    unit 0 {
      tunnel {
        source source-ip-address;
        destination destination-ip-address;
      }
      family inet {
        ipsec-sa sa-name;
        filter {
          input filter-name;
        }
        address ip-address;
      }
    }
  }
}

```

Option: Using IPSec with a Layer 3 VPN

Some key concepts to keep in mind when configuring IPSec within a VPN include the following:

- Add the outside services interface for a next-hop style service set into the routing instance by including the **interface *sp-fpc/pic/port*** statement at the **[edit routing-instances *instance-name*]** hierarchy level.
- For interface style service sets, add the interface on which you apply the service set and the services interface by including both interfaces at the **[edit routing-instances *instance-name*]** hierarchy level.
- To define a routing instance for the local gateway within the service set, include the **routing-instance *instance-name*** option at the **[edit services service-set *service-set-name* ipsec-vpn-options local-gateway *address*]** hierarchy level.

The following configuration for an AS PIC on a provider edge (PE) router demonstrates the use of next-hop service sets with an IKE dynamic SA in a VPN routing and forwarding (VRF) routing instance.

```

[edit]
interfaces {
  so-0/0/0 {
    description "Interface connected to the customer edge (CE) router";
    unit 0 {
      family inet {

```

```

        address 10.6.6.6/32;
    }
}
so-2/2/0 {
    description "Source IPSec tunnel interface to the network core";
    unit 0 {
        family inet {
            address 10.10.1.1/30;
        }
    }
}
sp-3/1/0 {
    description "AS PIC interface";
    unit 0 {
        family inet {
            address 10.7.7.7/32;
        }
    }
    unit 1 {
        family inet;
        service-domain inside;
    }
    unit 2 {
        family inet;
        service-domain outside;
    }
}
}
policy-options {
    policy-statement vpn-export-policy {
        then {
            community add community-name;
            accept;
        }
    }
    policy-statement vpn-import-policy {
        term term-name {
            from community community-name;
            then accept;
        }
    }
    community community-name members target:100:20;
}
routing-instances {
    vrf {
        instance-type vrf;
        interface sp-3/1/0.1; # Inside sp interface.
        interface so-0/0/0.0; # Interface that connects to the CE router.
        route-distinguisher route-distinguisher;
        vrf-import vpn-import-policy;
        vrf-export vpn-export-policy;
        routing-options {
            static {
                route ip-address/prefix next-hop so-0/0/0.0; # Routes for the CE router.
                route ip-address/prefix next-hop sp-3/1/0.1; # Routes for IPSec.
            }
        }
    }
}

```

```

    }
  }
}
services {
  service-set service-set-name {
    next-hop-service {
      inside-service-interface sp-3/1/0.1;
      outside-service-interface sp-3/1/0.2;
    }
    ipsec-vpn-options {
      local-gateway 10.10.1.1;
    }
    ipsec-vpn-rules rule-name;
  }
  ipsec-vpn {
    rule rule-name {
      term term-name {
        from {
          source-address {
            source-ip-address;
          }
        }
        then {
          remote-gateway 10.10.1.2;
          dynamic {
            ike-policy ike-policy-name;
          }
        }
      }
    }
    match-direction direction;
  }
  ike {
    policy ike-policy-name {
      pre-shared-key ascii-text preshared-key;
    }
  }
}
}

```

For more information on VRF routing instances, see the *Junos VPNs Configuration Guide*.
 For more information on next-hop service sets, see the *Junos Services Interfaces Configuration Guide*.

Option: Securing BGP Sessions with Transport Mode

For the ES PIC, you can use IPSec to secure BGP sessions between Routing Engines in M Series and T Series platforms. To configure, create a transport mode security association and apply the SA to the BGP configuration by including the **ipsec-sa** statement at the **[edit protocols bgp group group-name]** hierarchy level.

```

[edit]
protocols {
  bgp {
    group group-name {

```



```

    local-address ip-address;
    export export-policy;
    peer-as as-number;
    ipsec-sa sa-name;
    neighbor peer-ip-address;
  }
}

```

Option: Securing OSPFv3 Networks with Transport Mode

OSPF version 3 (OSPFv3), unlike OSPF version 2, does not have a built-in authentication method and relies on IPsec to provide this functionality. Using the ES PIC syntax, you can use IPsec to secure OSPFv3 between Routing Engines in M Series and T Series platforms. You can secure specific OSPFv3 interfaces and protect OSPFv3 virtual links. To configure, create a transport mode security association and apply the SA to the OSPFv3 configuration by including the **ipsec-sa** statement at the **[edit protocols ospf3 area *area-number* interface *interface-name*]** or **[edit protocols ospf3 area *area-number* virtual-link neighbor-id *neighbor-ip-address* transit-area *area-number*]** hierarchy level.

```

[edit]
protocols {
  ospf3 {
    area area-number {
      interface interface-name {
        ipsec-sa sa-name;
      }
      virtual-link neighbor-id neighbor-ip-address transit-area area-number {
        ipsec-sa sa-name;
      }
    }
  }
}

```

Option: Securing OSPFv2 Networks with Transport Mode

By default, you can configure MD5 or simple text password-based authentication over OSPFv2 links. In addition to these basic authentications, the Junos OS supports OSPFv2 with a security authentication header (AH), Encapsulating Security Payload (ESP), or an IPsec protocol bundle that supports both AH and ESP. You can configure IPsec over OSPFv2 using transport mode security associations on physical, sham, or virtual links.

Because the Junos OS supports only bidirectional security associations over OSPFv2, OSPFv2 peers must be configured with the same IPsec security association. Configuring OSPFv2 peers with different security associations or with dynamic IKE will prevent adjacencies from being established. In addition, you must configure identical security associations for sham links with the same remote endpoint address, for virtual links with the same remote endpoint address, for all neighbors on OSPF nonbroadcast multiaccess (NBMA) or point-to-multipoint links, and for every subnet that is part of a broadcast link.

To create a manual bidirectional security association, include the **security-association** ***security-association-name*** statement at the **[edit security ipsec]** hierarchy level:

```
[edit]
security {
  ipsec {
    security-association security-association name {
      mode transport;
      manual {
        direction bidirectional {
          protocol (ah | esp | bundle);
          spi spi--value;
          authentication {
            algorithm (hmac-md5-96 | hmac-sha1-96);
            key (ascii-text key | hexadecimal key);
          }
        }
      }
    }
  }
}
```

To configure IPSec on an OSPFv2 interface, create a transport mode security association and include the **ipsec-sa name** statement at the **[edit protocols ospf area *area-id*]** hierarchy level:

```
[edit]
protocols {
  ospf {
    area area-id {
      interface interface-name {
        ipsec-sa sa-name;
      }
      virtual-link neighbor-id a.b.c.d transit-area x.x.x.x {
        ipsec-sa sa-name;
      }
      sham-link-remote {
        ipsec-sa sa-name;
      }
    }
  }
}
```

To verify your configuration, enter the **show ospf interface detail** command. This command gives detailed information about the **ospfv2** interface and displays the interface's security association at the bottom of the output. In the example below, the security association configured on this router is **sa1**.

```
user@router> show ospf interface detail
Interface          State      Area      DR ID      BDR ID Nbrs
fe-0/0/1.0         BDR       0.0.0.0    192.168.37.12  10.255.245.215 1
Type LAN, address 192.168.37.11, Mask 255.255.255.248, MTU 4460, Cost 40
DR addr 192.168.37.12, BDR addr 192.168.37.11, Adj count 1, Priority 128
Hello 10, Dead 40, ReXmit 5, Not Stub
t1-0/2/1.0         PtToPt    0.0.0.0    0.0.0.0      0.0.0.0 0
Type P2P, Address 0.0.0.0, Mask 0.0.0.0, MTU 1500, Cost 2604
Adj count 0
Hello 10, Dead 40, ReXmit 5, Not Stub
```

Auth type: MD5, Active key ID 3, Start time 2002 Nov 19 10:00:00 PST
IPsec SA Name: sa1

Option: Monitoring IPsec by Using SNMP

In Junos OS Release 7.5 and later, the IPsec Monitoring MIB provides a way to monitor IPsec information on AS PICs installed in M Series and T Series routers by using the Simple Network Management Protocol (SNMP). The MIB provides an IKE tunnel table to monitor IKE security associations and view related statistics, an IPsec tunnel table to view IPsec tunnel statistics, and an IPsec security associations table to view all IPsec SAs. For more information, see the *Junos Network Management Configuration Guide*.

Option: Configuring Multiple Routed Tunnels in a Single Next-Hop Service Set

To save you time and simplify your configurations, an enhancement to the Junos OS enables you to configure several routed IPsec tunnels within a single next-hop service set. To configure, establish multiple services interfaces as inside interfaces by including the **service-domain inside** statement at the **[edit interfaces sp-fpc/pic/port unit logical-unit-number]** hierarchy level. Then, include the **ipsec-inside-interface** statement at the **[edit services ipsec-vpn rule rule-name term term-name from]** hierarchy level.



NOTE: The full IPsec and IKE proposals and policies are not shown in the following example for the sake of brevity. For more information on proposals and policies, see “Configuring IKE Dynamic SAs” on page 26.

```
[edit]
interfaces {
  sp-3/3/0 {
    unit 3 {
      family inet;
      service-domain inside;
    }
    unit 4 {
      family inet;
      service-domain outside;
    }
    unit 5 {
      family inet;
      service-domain inside;
    }
  }
}
services {
  service-set link_type_ss_1 {
    next-hop-service {
      inside-service-interface sp-3/3/0.3;
      outside-service-interface sp-3/3/0.4;
    }
    ipsec-vpn-options {
      local-gateway 10.8.7.2;
    }
  }
}
```

```

    ipsec-vpn-rules link_rule_1;
  }
  ipsec-vpn {
    rule link_rule_1 {
      term 1 {
        from {
          ipsec-inside-interface sp-3/3/0.3;
        }
        then {
          remote-gateway 10.10.7.3;
          backup-remote-gateway 10.8.7.1;
          dynamic {
            ike-policy main_mode_ike_policy;
            ipsec-policy dynamic_ipsec_policy;
          }
        }
      }
    }
    term 2 {
      from {
        ipsec-inside-interface sp-3/3/0.5;
      }
      then {
        remote-gateway 10.12.7.5;
        dynamic {
          ike-policy main_mode_ike_policy;
          ipsec-policy dynamic_ipsec_policy;
        }
      }
    }
  }
  match-direction input;
}
}

```

To confirm that your configuration is working, issue the **show services ipsec-vpn ipsec security-associations** command. Notice that each IPSec inside interface that you assigned to each IPSec tunnel is included in the output of this command.

```

user@router> show services ipsec-vpn ipsec security-associations
Service set: link_type_ss_1

```

```

Rule: link_rule_1, Term: 1, Tunnel index: 1
Local gateway: 10.8.7.2, Remote gateway: 10.8.7.1
IPSec inside interface: sp-3/3/0.3

```

Direction	SPI	AUX-SPI	Mode	Type	Protocol
inbound	3216392497	0	tunnel	dynamic	ESP
outbound	398917249	0	tunnel	dynamic	ESP

```

Rule: link_rule_1, Term: 2, Tunnel index: 2
Local gateway: 10.8.7.2, Remote gateway: 10.12.7.5
IPSec inside interface: sp-3/3/0.5

```

Direction	SPI	AUX-SPI	Mode	Type	Protocol
inbound	762146783	0	tunnel	dynamic	ESP
outbound	319191515	0	tunnel	dynamic	ESP

Option: Using Digital Certificates

A popular way for network administrators to scale an IPSec network is to use digital certificates instead of preshared keys. To enable digital certificates in your network, you need to use a combination of operational mode commands and configuration statements. The following steps enable you to implement digital certificates on AS and MultiServices PICs installed in M Series and T Series routers:

- [Configuring a CA Profile on page 39](#)
- [Configuring a Certificate Revocation List on page 40](#)
- [Requesting a CA Digital Certificate on page 41](#)
- [Generating a Private/Public Key Pair on page 41](#)
- [Generating and Enrolling a Local Digital Certificate on page 41](#)
- [Applying the Local Digital Certificate to an IPSec Configuration on page 41](#)
- [Configuring Automatic Reenrollment of Digital Certificates on page 42](#)
- [Monitoring Digital Certificates on page 42](#)
- [Clearing Digital Certificates on page 43](#)

CHAPTER 7

IPSec Dynamic Endpoints

- [Option: Configuring IPSec Dynamic Endpoints on page 55](#)
- [Dynamic Endpoint Tunnel Architecture on page 56](#)
- [Authentication Process on page 56](#)
- [Dynamic Implicit Rules on page 57](#)
- [Reverse Route Insertion on page 57](#)
- [Configuring an IKE Access Profile on page 58](#)
- [Configuring the Service Set on page 59](#)
- [Configuring the Interface Identifier on page 59](#)

Option: Configuring IPSec Dynamic Endpoints

IPSec tunnels can also be established using *dynamic peer* security gateways, in which the remote end of the tunnels do not have a statically assigned IPv4 or IPv6 address. Since the remote address is not known and is assigned from an address pool each time the remote host reboots, establishment of the tunnel relies on using IKE main mode with preshared global keys. Both policy-based and link-type tunnels are supported as follows:

- Policy-based tunnels used shared mode.
- Link-type or routed tunnels use dedicated mode. Each tunnel allocates a service interface from a pool of interfaces configured for the dynamic peers. Routing protocols can be configured to run on these service interfaces to learn routes over the IPSec tunnel that is used as a link.

This section includes the following topics:

- [Dynamic Endpoint Tunnel Architecture on page 56](#)
- [Configuring an IKE Access Profile on page 58](#)
- [Configuring the Service Set on page 59](#)
- [Configuring the Interface Identifier on page 59](#)

Dynamic Endpoint Tunnel Architecture

When you configure dynamic endpoint tunnels, the following components are used:

- [Authentication Process on page 56](#)
- [Dynamic Implicit Rules on page 57](#)
- [Reverse Route Insertion on page 57](#)

Authentication Process

The remote dynamic peer initiates IKE and IPSec negotiations with the local (Juniper Networks) router. The local router uses a default set of authentication and encryption values to match the IPSec and IKE proposals sent by the remote peer to establish the SA. If any of the values match, the tunnel establishment process continues. The default values are shown in [Table 8 on page 56](#).

Table 8: Default IKE and IPSec Proposals for Dynamic SA Negotiations

Statement Name	Values
Implicit IKE Proposal	
authentication-method	preshared keys
dh-group	group1, group2
authentication-algorithm	sha1, md5
encryption-algorithm	3des-cbc, des-cbc
lifetime-seconds	3600 seconds
Implicit IPSec Proposal	
protocol	esp, ah, bundle
authentication-algorithm	hmac-sha1-96, hmac-md5-96
encryption-algorithm	3des-cbc, des-cbc
lifetime-seconds	28,800 seconds (8 hours)

Phase 2 of the authentication process matches the *proxy identities* of the protected hosts and networks sent by the peer against a list of configured proxy identities. The accepted proxy identity is used to create the dynamic rules for encrypting the traffic. You can configure proxy identities by including the **allowed-proxy-pair** statement in an IKE access profile at the **[edit access profile *profile-name* client * ike]** hierarchy level. If no configured entry matches, the negotiation is rejected.

However, if you do not configure the **allowed-proxy-pair** statement, the default value **ANY(0.0.0.0/0)-ANY** is applied, and the local router accepts any proxy identities sent by the peer.

Once the phase 2 negotiation has been successfully completed, the router builds dynamic rules and inserts the reverse route into the routing table using the accepted proxy identity.

Dynamic Implicit Rules

After successful negotiation with the dynamic peer, the key management process (kmd) creates a dynamic rule for the accepted phase 2 proxy and applies it on the local AS or MultiServices PIC. The source and destination addresses are specified by the accepted proxy. This rule is used to encrypt traffic directed to one of the end hosts in the phase 2 proxy identity.



NOTE: You do not configure this rule; it is created by the key management process (kmd).

The **ipsec-inside-interface** value is the interface name assigned to the dynamic tunnel. The **source-address** and **destination-address** values are accepted from the proxy ID. The **match-direction** value is **input** for next-hop-style service sets.

Rule lookup for static tunnels is unaffected by the presence of a dynamic rule; it is performed in the order configured. When a packet is received for a service-set, static rules are always matched first. Dynamic rules are matched only after the rule match for static rules has failed.

Reverse Route Insertion

Static routes are automatically inserted into the route table for those networks and hosts protected by a remote tunnel endpoint. These protected hosts and networks are known as remote proxy identities.

Each route is created based on the remote proxy network and prefix length sent by the peer and is inserted in the relevant route table after successful phase 1 and phase 2 negotiations.

The route preference for each of these static reverse routes is 1. This value is necessary to avoid conflict with similar routes that might be added by the routing protocol process (rpd).

No routes are added if the accepted remote proxy address is the default (**0.0.0.0/0**). In this case, you can run routing protocols over the IPSec tunnel to learn routes and add static routes for the traffic you want to be protected over this tunnel.

For next-hop style service sets, the reverse routes include next hops pointing to the locations specified by the **inside-service-interface** statements.

The selection of the routing table in which these routes are inserted depends on where you configure the **inside-service-interface** statement. If these interfaces are present in a

VRF routing instance, then routes are added to the corresponding VRF routing table; otherwise, the routes are added to **inet.0**.



NOTE: Reverse route insertion takes place only for tunnels to dynamic peers. These routes are added only for next-hop style service sets.

Configuring an IKE Access Profile

You can configure only one tunnel profile per service set for all dynamic peers. The configured preshared key in the profile is used for IKE authentication of all dynamic peers terminating in that service set.

The IKE tunnel profile specifies all the information needed to complete the IKE negotiation. For more information on access profiles, see the *Junos System Basics Configuration Guide*.

```
[edit access]
profile profile-name {
  client * {
    ike {
      allowed-proxy-pair {
        remote remote-proxy-address local local-proxy-address;
      }
      pre-shared-key ([ ascii-text key-string ] | [ hexadecimal key-string ]);
      interface-id string-value;
      ipsec-policy ipsec-policy;
    }
  }
}
```



NOTE: For dynamic peers, the Junos OS supports only IKE main mode with the preshared key method of authentication. In this mode, an IPv4 or IPv6 address is used to identify a tunnel peer to get the preshared key information. The client value * (wildcard) means that the configuration within this profile is valid for all dynamic peers terminating within the service set accessing this profile.

The following statements are the parts of the IKE profile:

- **allowed-proxy-pair**—During phase 2 IKE negotiation, the remote peer supplies its network address (**remote**) and its peer's network address (**local**). Since multiple dynamic tunnels are authenticated through the same mechanism, this statement must include the list of possible combinations. If the dynamic peer does not present a valid combination, the phase 2 IKE negotiation fails.

By default, remote 0.0.0.0/0 local 0.0.0.0/0 is used if no values are configured.

- **pre-shared-key**—Mandatory key used to authenticate the dynamic peer during IKE phase 1 negotiation. This key must be configured on both ends of the tunnel and

distributed through an out-of-band secure mechanism. You can configure the key value either in **hexadecimal** or **ascii-text** format.

- **interface-id**—Interface identifier, a mandatory attribute used to derive the logical service interface information for the session.
- **ipsec-policy**—Name of the IPsec policy that defines the IPsec policy information for the session. You define the IPsec policy at the **[edit services ipsec-vpn ipsec policy policy-name]** hierarchy level. If no policy is set, any policy proposed by the dynamic peer is accepted.

Configuring the Service Set

To complete a dynamic endpoint tunnel configuration, you need to reference the IKE access profile configured at the **[edit access]** hierarchy level in the service set. To do this, include the **ike-access-profile** statement at the **[edit services service-set name ipsec-vpn-options]** hierarchy level:

```
[edit services]
service-set name {
  next-hop-service {
    inside-service-interface interface-name;
    outside-service-interface interface-name;
  }
  ipsec-vpn-options {
    local-gateway address;
    ike-access-profile profile-name;
  }
}
```

You can reference only one access profile in each service set. This profile is used to negotiate IKE and IPSec security associations with dynamic peers only.



NOTE: If you configure an IKE access profile in a service set, no other service set can share the same **local-gateway** address.

Configuring the Interface Identifier

You can configure an interface identifier for a group of dynamic peers, which specifies which adaptive services logical interface(s) take part in the dynamic IPSec negotiation. By assigning the same interface identifier to multiple logical interfaces, you can create a pool of interfaces for this purpose. To configure, include the **ipsec-interface-id** statement at the **[edit interfaces interface-name]** hierarchy level:

```
[edit interfaces sp-fpc/pic/port]
unit logical-unit-number {
  dial-options {
    ipsec-interface-id identifier;
    (shared | dedicated);
  }
}
```

Specifying the interface identifier in the **dial-options** statement makes this logical interface part of the pool identified by the IPSec interface identifier.



NOTE: Only one interface identifier can be specified at a time. You can include the **ipsec-interface-id** statement or the **l2tp-interface-id** statement, but not both simultaneously.

The **shared** statement enables one logical interface to be shared across multiple tunnels. The **dedicated** statement specifies that the logical interface is associated with a single tunnel, which is necessary when you are configuring an IPSec link-type tunnel. You must include the **dedicated** statement when you specify an **ipsec-interface-id** value.

PART 3

Examples

- [IPSec Configuration Examples on page 63](#)

CHAPTER 8

IPSec Configuration Examples

- [Example: ES PIC Manual SA Configuration on page 63](#)
- [Example: AS PIC Manual SA Configuration on page 72](#)
- [Example: ES PIC IKE Dynamic SA Configuration on page 80](#)
- [Example: AS PIC IKE Dynamic SA Configuration on page 90](#)
- [Example: IKE Dynamic SA Between an AS PIC and an ES PIC Configuration on page 99](#)
- [Example: AS PIC IKE Dynamic SA with Digital Certificates Configuration on page 110](#)
- [Example: Dynamic Endpoint Tunneling Configuration on page 127](#)

Example: ES PIC Manual SA Configuration

Figure 3: ES PIC Manual SA Topology Diagram




Figure 3 on page 63 shows an IPSec topology containing a group of four routers. Routers 2 and 3 establish an IPSec tunnel using an ES PIC and manual SA settings. Routers 1 and 4 provide basic connectivity and are used to verify that the IPSec tunnel is operational.

On Router 1, provide basic OSPF connectivity to Router 2.

```
Router 1 [edit]
interfaces {
  so-0/0/0 {
    description "To R2 so-0/0/0";
    unit 0 {
      family inet {
        address 10.1.12.2/30;
      }
    }
  }
  lo0 {
    unit 0 {
```

```

        family inet {
            address 10.0.0.1/32;
        }
    }
}
routing-options {
    router-id 10.0.0.1;
}
protocols {
    ospf {
        area 0.0.0.0 {
            interface so-0/0/0.0;
            interface lo0.0;
        }
    }
}

```

On Router 2, enable OSPF as the underlying routing protocol to connect to Routers 1 and 3. Configure a bidirectional manual SA called **sa-manual** at the **[edit security ipsec security-association]** hierarchy level. Use AH for the protocol, **400** for the SPI, HMAC-MD5-96 for authentication, and a 32-bit hexadecimal authentication key for the MD5 authentication key. (For more information about key length, see [Table 4 on page 23](#).) Because you are using AH, there is no need to configure encryption.

To direct traffic into the ES PIC and the IPSec tunnel, create two firewall filters. The **es-traffic** filter matches inbound traffic from Router 1 destined for Router 4, whereas the **es-return** filter matches the return path from Router 4 to Router 1. Apply the **es-traffic** filter to the **so-0/0/0** interface; then apply both the **es-return** filter and the **sa-manual** SA to the **es-0/3/0** interface.

```

Router 2 [edit]
interfaces {
    so-0/0/0 {
        description "To R1 so-0/0/0";
        unit 0 {
            family inet {
                filter {
                    input es-traffic; # Apply a filter that sends traffic to the IPSec tunnel here.
                }
                address 10.1.12.1/30;
            }
        }
    }
    so-0/0/1 {
        description "To R3 so-0/0/1";
        unit 0 {
            family inet {
                address 10.1.15.1/30;
            }
        }
    }
    es-0/3/0 {
        unit 0 {
            tunnel { # Specify the IPSec tunnel endpoints here.

```



```

        source 10.1.15.1;
        destination 10.1.15.2;
    }
    family inet {
        ipsec-sa sa-manual; # Apply the manual SA here.
        filter {
            input es-return; # Apply the filter that matches return IPSec traffic here.
        }
    }
}
}
lo0 {
    unit 0 {
        family inet {
            address 10.0.0.2/32;
        }
    }
}
}
routing-options {
    router-id 10.0.0.2;
}
protocols {
    ospf {
        area 0.0.0.0 {
            interface so-0/0/0.0;
            interface so-0/0/1.0;
            interface lo0.0;
        }
    }
}
}
security {
    ipsec {
        security-association sa-manual { # Define the manual SA specifications here.
            mode tunnel;
            manual {
                direction bidirectional {
                    protocol ah;
                    spi 400;
                    authentication {
                        algorithm hmac-md5-96;
                        key hexadecimal "$9$ro/eK8x7VY2ahSvL7-2gfTQF9Apu1EhrmfF/Ctl
                        RlKMw7-VwYg4ZhSeW8XbwJGjHmP5QF69wY4Zjif5369ApBSyKv8XRE";
                    }
                }
            }
        }
    }
}
}

# The 32-bit unencrypted hexadecimal key is abcdef01abcdef01abcdef01abcdef01.
firewall {
    filter es-traffic { # Define a filter that sends traffic to the IPSec tunnel here.
        term to-es {
            from {
                source-address {

```

```

        10.1.12.0/24;
    }
    destination-address {
        10.1.56.0/24;
    }
}
then {
    count ipsec-tunnel;
    ipsec-sa sa-manual;
}
}
term other {
    then accept;
}
}
filter es-return { # Define a filter that matches return IPSec traffic here.
    term return {
        from {
            source-address {
                10.1.56.0/24;
            }
            destination-address {
                10.1.12.0/24;
            }
        }
        then accept;
    }
}
}

```

On Router 3, enable OSPF as the underlying routing protocol to connect to Routers 2 and 4. Configure a bidirectional manual SA called **sa-manual** at the **[edit security ipsec security-association]** hierarchy level. Use the exact same specifications that you used for the SA on Router 2: AH for the protocol, **400** for the SPI, HMAC-MD5-96 for authentication, and a 32-bit hexadecimal authentication key of **abcdef01abcdef01abcdef01abcdef01** for the MD5 authentication key. (For more information about authentication key length, see [Table 4 on page 23](#).) Because you are using AH, there is no need to configure an encryption algorithm.

To direct traffic into the ES PIC and the IPSec tunnel, create two firewall filters. The **es-traffic** filter matches inbound traffic from Router 4 destined for Router 1, whereas the **es-return** filter matches the return path from Router 1 to Router 4. Apply the **es-traffic** filter to the **so-0/0/0** interface; then apply both the **es-return** filter and the **sa-manual** SA to the **es-0/3/0** interface.

```

Router 3 [edit]
interfaces {
    so-0/0/0 {
        description "To R4 so-0/0/0";
        unit 0 {
            family inet {
                filter {
                    input es-traffic; # Apply a filter that sends traffic to the IPSec tunnel here.
                }
            }
            address 10.1.56.1/30;
        }
    }
}

```

```

    }
  }
}
so-0/0/1 {
  description "To R2 so-0/0/1";
  unit 0 {
    family inet {
      address 10.1.15.2/30;
    }
  }
}
es-0/3/0 {
  unit 0 {
    tunnel { # Specify the IPSec tunnel endpoints here.
      source 10.1.15.2;
      destination 10.1.15.1;
    }
    family inet {
      ipsec-sa sa-manual; # Apply the manual SA here.
      filter {
        input es-return; # Apply the filter that matches return IPSec traffic here.
      }
    }
  }
}
lo0 {
  unit 0 {
    family inet {
      address 10.0.0.3/32;
    }
  }
}
}
routing-options {
  router-id 10.0.0.3;
}
protocols {
  ospf {
    area 0.0.0.0 {
      interface so-0/0/0.0;
      interface so-0/0/1.0;
      interface lo0.0;
    }
  }
}
}
security {
  ipsec {
    security-association sa-manual { # Define the manual SA specifications here.
      mode tunnel;
      manual {
        direction bidirectional {
          protocol ah;
          spi 400;
          authentication {
            algorithm hmac-md5-96;
            key hexadecimal "$9$KMfMWx-ds4oGyl87dboaQF36tuOBESyK5Q6

```

```

        ApOhcvWLXdbS24aJDylMXxNY2ZUjk.5Tz36Ct24JDkqQz/CtuORleW8xNcS";
    }
}
}
}
}
}
}

```

The 32-bit unencrypted hexadecimal key is abcdef01abcdef01abcdef01abcdef01.

```

firewall {
  filter es-traffic { # Define a filter that sends traffic to the IPSec tunnel here.
    term to-es {
      from {
        source-address {
          10.1.56.0/24;
        }
        destination-address {
          10.1.12.0/24;
        }
      }
      then {
        count ipsec-tunnel;
        ipsec-sa sa-manual;
      }
    }
    term other {
      then accept;
    }
  }
  filter es-return { # Define a filter that matches return IPSec traffic here.
    term return {
      from {
        source-address {
          10.1.12.0/24;
        }
        destination-address {
          10.1.56.0/24;
        }
      }
      then accept;
    }
  }
}

```

On Router 4, provide basic OSPF connectivity to Router 3.

```

Router 4 [edit]
interfaces {
  so-0/0/0 {
    description "To R3 so-0/0/0";
    unit 0 {
      family inet {
        address 10.1.56.2/30;
      }
    }
  }
}

```

```

    }
    lo0 {
        unit 0 {
            family inet {
                address 10.0.0.4/32;
            }
        }
    }
}
routing-options {
    router-id 10.0.0.4;
}
protocols {
    ospf {
        area 0.0.0.0 {
            interface so-0/0/0.0;
            interface lo0.ping
        }
    }
}
}

```

Verifying Your Work

To verify proper operation of a manual IPSec SA on the ES PIC, use the following commands:

- **ping**
- **show ipsec security-associations (detail)**
- **traceroute**

The following sections show the output of these commands used with the configuration example:

- [Router 1 on page 69](#)
- [Router 2 on page 70](#)
- [Router 3 on page 71](#)
- [Router 4 on page 71](#)

Router 1

On Router 1, issue a **ping** command to the **so-0/0/0** interface of Router 4 to send traffic across the IPSec tunnel.

```

user@R1> ping 10.1.56.2
PING 10.1.56.2 (10.1.56.2): 56 data bytes
64 bytes from 10.1.56.2: icmp_seq=0 ttl=253 time=0.939 ms
64 bytes from 10.1.56.2: icmp_seq=1 ttl=253 time=0.886 ms
64 bytes from 10.1.56.2: icmp_seq=2 ttl=253 time=0.826 ms
^C
--- 10.1.56.2 ping statistics ---
3 packets transmitted, 3 packets received, 0% packet loss
round-trip min/avg/max/stddev = 0.826/0.884/0.939/0.046 ms

```

You can also issue the **tracert** command to verify that traffic to 10.1.56.2 travels over the IPSec tunnel between Router 2 and Router 3. Notice that the second hop does not reference 10.1.15.2—the physical interface on Router 3. Instead, the loopback address of 10.0.0.3 on Router 3 appears as the second hop. This indicates that the IPSec tunnel is operating correctly.

```
user@R1> tracert 10.1.56.2
tracert to 10.1.56.2 (10.1.56.2), 30 hops max, 40 byte packets
 1 10.1.12.1 (10.1.12.1) 0.655 ms 0.549 ms 0.508 ms
 2 10.0.0.3 (10.0.0.3) 0.833 ms 0.786 ms 0.757 ms
 3 10.1.56.2 (10.1.56.2) 0.808 ms 0.741 ms 0.716 ms
```

Router 2

Another way to verify that matched traffic is being diverted to the bidirectional IPSec tunnel is to view the firewall filter counter. After you issue the **ping** command from Router 1 (three packets), the **es-traffic** firewall filter counter looks like this:

```
user@R2> show firewall filter es-traffic
Filter: es-traffic
Counters:
Name                               Bytes      Packets
ipsec-tunnel                        252         3
```

After you issue the **ping** command from both Router 1 (three packets) and Router 4 (two packets), the **es-traffic** firewall filter counter looks like this:

```
user@R2> show firewall filter es-traffic
Filter: es-traffic
Counters:
Name                               Bytes      Packets
ipsec-tunnel                        420         5
```

To verify that the IPSec security association is active, issue the **show ipsec security-associations detail** command. Notice that the SA contains the settings you specified, such as AH for the protocol and HMAC-MD5-96 for the authentication algorithm.

```
user@R2> show ipsec security-associations detail
Security association: sa-manual, Interface family: Up

Local gateway: 10.1.15.1, Remote gateway: 10.1.15.2
Local identity: ipv4_subnet(any:0,[0..7]=0.0.0.0/0)
Remote identity: ipv4_subnet(any:0,[0..7]=0.0.0.0/0)

Direction: inbound, SPI: 400, AUX-SPI: 0
Mode: tunnel, Type: manual, State: Installed
Protocol: AH, Authentication: hmac-md5-96, Encryption: None
Anti-replay service: Disabled

Direction: outbound, SPI: 400, AUX-SPI: 0
Mode: tunnel, Type: manual, State: Installed
Protocol: AH, Authentication: hmac-md5-96, Encryption: None
Anti-replay service: Disabled
```

Router 3

View the firewall filter counter to continue verifying that matched traffic is being diverted to the bidirectional IPSec tunnel. After you issue the **ping** command from Router 1 (three packets), the **es-traffic** firewall filter counter looks like this:

```
user@R3> show firewall filter es-traffic
Filter: es-traffic
Counters:
Name                               Bytes      Packets
ipsec-tunnel                       252        3
```

After you issue the **ping** command from both Router 1 (three packets) and Router 4 (two packets), the **es-traffic** firewall filter counter looks like this:

```
user@R3> show firewall filter es-traffic
Filter: es-traffic
Counters:
Name                               Bytes      Packets
ipsec-tunnel                       420        5
```

To verify that the IPSec security association is active, issue the **show ipsec security-associations detail** command. Notice that the SA on Router 3 contains the same settings you specified on Router 2.

```
user@R3> show ipsec security-associations detail
Security association: sa-manual, Interface family: Up

Local gateway: 10.1.15.2, Remote gateway: 10.1.15.1
Local identity: ipv4_subnet(any:0,[0..7]=0.0.0.0/0)
Remote identity: ipv4_subnet(any:0,[0..7]=0.0.0.0/0)

Direction: inbound, SPI: 400, AUX-SPI: 0
Mode: tunnel, Type: manual, State: Installed
Protocol: AH, Authentication: hmac-md5-96, Encryption: None
Anti-replay service: Disabled

Direction: outbound, SPI: 400, AUX-SPI: 0
Mode: tunnel, Type: manual, State: Installed
Protocol: AH, Authentication: hmac-md5-96, Encryption: None
Anti-replay service: Disabled
```

Router 4

On Router 4, issue a **ping** command to the **so-0/0/0** interface of Router 1 to send traffic across the IPSec tunnel.

```
user@R4> ping 10.1.12.2
PING 10.1.12.2 (10.1.12.2): 56 data bytes
64 bytes from 10.1.12.2: icmp_seq=0 ttl=253 time=0.937 ms
64 bytes from 10.1.12.2: icmp_seq=1 ttl=253 time=0.872 ms
^C
--- 10.1.12.2 ping statistics ---
2 packets transmitted, 2 packets received, 0% packet loss
round-trip min/avg/max/stddev = 0.872/0.905/0.937/0.032 ms
```

You can also issue the **traceroute** command to verify that traffic to **10.1.12.2** travels over the IPSec tunnel between Router 3 and Router 2. Notice that the second hop does not reference **10.1.15.1**—the physical interface on Router 2. Instead, the loopback address of

10.0.0.2 on Router 2 appears as the second hop. This indicates that the IPSec tunnel is operating correctly.

```
user@R4> traceroute 10.1.12.2
traceroute to 10.1.12.2 (10.1.12.2), 30 hops max, 40 byte packets
 1  10.1.56.1 (10.1.56.1)  0.670 ms  0.589 ms  0.548 ms
 2  10.0.0.2 (10.0.0.2)  0.815 ms  0.791 ms  0.763 ms
 3  10.1.12.2 (10.1.12.2)  0.798 ms  0.741 ms  0.714 ms
```

Example: AS PIC Manual SA Configuration

Figure 4: AS PIC Manual SA Topology Diagram




Figure 4 on page 72 shows a similar IPSec topology to the one used in the ES PIC manual SA example. The difference is that Routers 2 and 3 establish an IPSec tunnel using an AS PIC and use slightly modified manual SA settings. Routers 1 and 4 again provide basic connectivity and are used to verify that the IPSec tunnel is operational.

On Router 1, provide basic OSPF connectivity to Router 2.

```
Router 1 [edit]
interfaces {
  so-0/0/0 {
    description "To R2 so-0/0/0";
    unit 0 {
      family inet {
        address 10.1.12.2/30;
      }
    }
  }
  lo0 {
    unit 0 {
      family inet {
        address 10.0.0.1/32;
      }
    }
  }
}
routing-options {
  router-id 10.0.0.1;
}
protocols {
  ospf {
    area 0.0.0.0 {
      interface so-0/0/0.0;
      interface lo0.0;
    }
  }
}
```



```

    }
  }

```

On Router 2, enable OSPF as the underlying routing protocol to connect to Routers 1 and 3. Configure a bidirectional manual SA in a rule called rule-manual-SA-BiEspshades at the **[edit ipsec-vpn rule]** hierarchy level. Reference this rule in a service set called service-set-manual-BiEspshades at the **[edit services service-set]** hierarchy level.

Configure all specifications for your manual SA. Use ESP for the protocol, **261** for the SPI, HMAC-SHA1-96 for authentication, DES-CBC for encryption, a 20-bit ASCII authentication key for the SHA-1 authentication key, and an 8-bit ASCII encryption key for the DES-CBC authentication key. (For more information about key lengths, see [Table 4 on page 23](#).)

To direct traffic into the AS PIC and the IPSec tunnel, configure a next-hop style service set and add the adaptive services logical interface used as the IPSec inside interface into the OSPF configuration.

```

Router 2 [edit]
          interfaces {
            so-0/0/0 {
              description "To R1 so-0/0/0";
              unit 0 {
                family inet {
                  address 10.1.12.1/30;
                }
              }
            }
            so-0/0/1 {
              description "To R3 so-0/0/1";
              unit 0 {
                family inet {
                  address 10.1.15.1/30;
                }
              }
            }
            sp-1/2/0 {
              services-options {
                syslog {
                  host local {
                    services info;
                  }
                }
              }
              unit 0 {
                family inet {
                }
              }
              unit 1 { # sp-1/2/0.1 is the IPSec inside interface.
                family inet;
                service-domain inside;
              }
              unit 2 { # sp-1/2/0.2 is the IPSec outside interface.
                family inet;
                service-domain outside;
              }
            }
          }

```

```

lo0 {
  unit 0 {
    family inet {
      address 10.0.0.2/32;
    }
  }
}
routing-options {
  router-id 10.0.0.2;
}
protocols {
  ospf {
    area 0.0.0.0 {
      interface so-0/0/0.0;
      interface lo0.0;
      interface sp-1/2/0.1; # This sends OSPF traffic over the IPSec tunnel.
    }
  }
}
services {
  service-set service-set-manual-BiEspshades { # Define your service set here.
    next-hop-service { # Required for dynamic routing protocols such as OSPF.
      inside-service-interface sp-1/2/0.1;
      outside-service-interface sp-1/2/0.2;
    }
    ipsec-vpn-options {
      local-gateway 10.1.15.1; # Specify the local IP address of the IPSec tunnel.
    }
    ipsec-vpn-rules rule-manual-SA-BiEspshades; # Reference the IPSec rule here.
  }
  ipsec-vpn {
    rule rule-manual-SA-BiEspshades { # Define your IPSec VPN rule here.
      term term-manual-SA-BiEspshades {
        then {
          remote-gateway 10.1.15.2; # The remote IP address of the IPSec tunnel.
          manual { # Define the manual SA specifications here.
            direction bidirectional {
              protocol esp;
              spi 261;
              authentication {
                algorithm hmac-sha1-96;
                key ascii-text "$9$v.s8xd24Zk.5bs.5QFAtM8XNVYJGifT3goT369
                  OBxNdW2ajHmFnCZUnCtuEh";
                ## The unencrypted key is juniperjuniperjunipe (20 characters for
                  HMAC-SHA-1-96).
              }
              encryption {
                algorithm des-cbc;
                key ascii-text "$9$3LJW/A0EclLxdBlxdbSJZn/CpOR";
                ## The unencrypted key is juniperj (8 characters for DES-CBC).
              }
            }
          }
        }
      }
    }
  }
}

```

```

        match-direction input; # Correct match direction for next-hop service sets.
    }
}
}
}
security {
    pki {
        auto-re-enrollment {
            certificate-id certificate-name {
                ca-profile ca-profile-name;
                challenge-password password;
                re-enroll-trigger-time-percentage percentage; #Percentage of validity-period
                    # (specified in certificate) when automatic
                    # reenrollment should be initiated.
                re-generate-keypair;
                validity-period number-of-days;
            }
        }
    }
}

```

On Router 3, enable OSPF as the underlying routing protocol to connect to Routers 2 and 4. Configure a bidirectional manual SA in a rule called rule-manual-SA-BiEspshades at the **[edit ipsec-vpn rule]** hierarchy level. Reference this rule in a service set called service-set-manual-BiEspshades at the **[edit services service-set]** hierarchy level.

Configure the same specifications for your manual SA that you specified on Router 2. Use ESP for the protocol, **261** for the SPI, HMAC-SHA1-96 for authentication, DES-CBC for encryption, a 20-bit ASCII authentication key for the SHA-1 authentication key, and an 8-bit ASCII encryption key for the DES-CBC authentication key. (For more information about key lengths, see [Table 4 on page 23.](#))

To direct traffic into the AS PIC and the IPSec tunnel, configure a next-hop style service set and add the adaptive services logical interface used as the IPSec inside interface into the OSPF configuration.

```

Router 3 [edit]
interfaces {
    so-0/0/0 {
        description "To R4 so-0/0/0";
        unit 0 {
            family inet {
                address 10.1.56.1/30;
            }
        }
    }
    so-0/0/1 {
        description "To R2 so-0/0/1";
        unit 0 {
            family inet {
                address 10.1.15.2/30;
            }
        }
    }
    sp-1/2/0 {
        services-options {

```

```

syslog {
  host local {
    services info;
  }
}
unit 0 {
  family inet {
  }
  unit 1 { # sp-1/2/0.1 is the IPSec inside interface.
    family inet;
    service-domain inside;
  }
  unit 2 { # sp-1/2/0.2 is the IPSec outside interface.
    family inet;
    service-domain outside;
  }
}
lo0 {
  unit 0 {
    family inet {
      address 10.0.0.3/32;
    }
  }
}
routing-options {
  router-id 10.0.0.3;
}
protocols {
  ospf {
    area 0.0.0.0 {
      interface so-0/0/0.0;
      interface lo0.0;
      interface sp-1/2/0.1; # This sends OSPF traffic over the IPSec tunnel.
    }
  }
}
services {
  service-set service-set-manual-BiEspshades { # Define your service set here.
    next-hop-service { # Required for dynamic routing protocols such as OSPF.
      inside-service-interface sp-1/2/0.1;
      outside-service-interface sp-1/2/0.2;
    }
    ipsec-vpn-options {
      local-gateway 10.1.15.2; # Specify the local IP address of the IPSec tunnel.
    }
    ipsec-vpn-rules rule-manual-SA-BiEspshades; # Reference the IPSec rule here.
  }
  ipsec-vpn {
    rule rule-manual-SA-BiEspshades { # Define your IPSec VPN rule here.
      term term-manual-SA-BiEspshades {
        then {
          remote-gateway 10.1.15.1; # The remote IP address of the IPSec tunnel.
          manual { # Define the manual SA specifications here.
            direction bidirectional {

```

```

protocol esp;
spi 261;
authentication {
    algorithm hmac-sha1-96;
    key ascii-text "$9$v.s8xd24Zk.5bs.5QFAtM8XNVYJGifT3goT369
    OBxNdw2ajHmFnCZUnCtuEH";
    ## The unencrypted key is juniperjuniperjunipe (20 characters for
    HMAC-SHA-1-96).
}
encryption {
    algorithm des-cbc;
    key ascii-text "$9$3LJW/A0EcLLxdBlxdsJZn/CpOR";
    ## The unencrypted key is juniperj (8 characters for DES-CBC).
}
}
}
}
}
}
match-direction input; # Specify in which direction the rule should match.
}
}
}
}
}

```

On Router 4, provide basic OSPF connectivity to Router 3.

```

Router 4 [edit]
interfaces {
    so-0/0/0 {
        description "To R3 so-0/0/0";
        unit 0 {
            family inet {
                address 10.1.56.2/30;
            }
        }
    }
    lo0 {
        unit 0 {
            family inet {
                address 10.0.0.4/32;
            }
        }
    }
}
routing-options {
    router-id 10.0.0.4;
}
protocols {
    ospf {
        area 0.0.0.0 {
            interface so-0/0/0.0;
            interface lo0.0;
        }
    }
}
}

```

Verifying Your Work

To verify proper operation of a manual IPSec SA on the AS PIC, use the following commands:

- **ping**
- **show services ipsec-vpn ipsec security-associations (detail)**
- **show services ipsec-vpn ipsec statistics**

The following sections show the output of these commands used with the configuration example:

- [Router 1 on page 78](#)
- [Router 2 on page 78](#)
- [Router 3 on page 79](#)

Router 1

On Router 1, issue a **ping** command to the **lo0** interface on Router 4 to send traffic across the IPSec tunnel.

```
user@R1> ping 10.0.0.4
PING 10.0.0.4 (10.0.0.4): 56 data bytes
64 bytes from 10.0.0.4: icmp_seq=0 ttl=254 time=1.375 ms
64 bytes from 10.0.0.4: icmp_seq=1 ttl=254 time=18.375 ms
64 bytes from 10.0.0.4: icmp_seq=2 ttl=254 time=1.120 ms
^C
--- 10.0.0.4 ping statistics ---
3 packets transmitted, 3 packets received, 0% packet loss
round-trip min/avg/max/stddev = 1.120/6.957/18.375/8.075 ms
```

Router 2

To verify that the IPSec security association is active, issue the **show services ipsec-vpn ipsec security-associations detail** command. Notice that the SA contains the settings you specified, such as ESP for the protocol and HMAC-SHA1-96 for the authentication algorithm.

```
user@R2> show services ipsec-vpn ipsec security-associations detail
Service set: service-set-manual-BiEspshades
Rule: rule-manual-SA-BiEspshades, Term: term-manual-SA-BiEspshades,
Tunnel index: 1
Local gateway: 10.1.15.1, Remote gateway: 10.1.15.2
Local identity: ipv4_subnet(any:0,[0..7]=10.0.0.0/8)
Remote identity: ipv4_subnet(any:0,[0..7]=0.0.0.0/0)

Direction: inbound, SPI: 261, AUX-SPI: 0
Mode: tunnel, Type: manual, State: Installed
Protocol: ESP, Authentication: hmac-sha1-96, Encryption: des-cbc
Anti-replay service: Disabled

Direction: outbound, SPI: 261, AUX-SPI: 0
Mode: tunnel, Type: manual, State: Installed
Protocol: ESP, Authentication: hmac-sha1-96, Encryption: des-cbc
Anti-replay service: Disabled
```

To verify that traffic is traveling over the bidirectional IPSec tunnel, issue the **show services ipsec-vpn statistics** command:

```
user@R2> show services ipsec-vpn ipsec statistics
```

```
PIC: sp-1/2/0, Service set: service-set-manual-BiEspshades
```

ESP Statistics:

```
Encrypted bytes:      1616
Decrypted bytes:      1560
Encrypted packets:    20
Decrypted packets:    19
```

AH Statistics:

```
Input bytes:          0
Output bytes:         0
Input packets:        0
Output packets:       0
```

Errors:

```
AH authentication failures: 0, Replay errors: 0
ESP authentication failures: 0, ESP decryption failures: 0
Bad headers: 0, Bad trailers: 0
```

Router 3

To verify that the IPSec security association is active, issue the **show services ipsec-vpn ipsec security-associations detail** command. To be successful, the SA on Router 3 must contain the same settings you specified on Router 2.

```
user@R3> show services ipsec-vpn ipsec security-associations detail
```

```
Service set: service-set-manual-BiEspshades
```

```
Rule: rule-manual-SA-BiEspshades, Term: term-manual-SA-BiEspshades,
Tunnel index: 1
```

```
Local gateway: 10.1.15.2, Remote gateway: 10.1.15.1
```

```
Local identity: ipv4_subnet(any:0,[0..7]=10.0.0.0/8)
```

```
Remote identity: ipv4_subnet(any:0,[0..7]=0.0.0.0/0)
```

```
Direction: inbound, SPI: 261, AUX-SPI: 0
```

```
Mode: tunnel, Type: manual, State: Installed
```

```
Protocol: ESP, Authentication: hmac-sha1-96, Encryption: des-cbc
```

```
Anti-replay service: Disabled
```

```
Direction: outbound, SPI: 261, AUX-SPI: 0
```

```
Mode: tunnel, Type: manual, State: Installed
```

```
Protocol: ESP, Authentication: hmac-sha1-96, Encryption: des-cbc
```

```
Anti-replay service: Disabled
```

To verify that traffic is traveling over the bidirectional IPSec tunnel, issue the **show services ipsec-vpn statistics** command:

```
user@R3> show services ipsec-vpn ipsec statistics
```

```
PIC: sp-1/2/0, Service set: service-set-manual-BiEspshades
```

ESP Statistics:

```
Encrypted bytes:      1560
Decrypted bytes:      1616
Encrypted packets:    19
Decrypted packets:    20
```

AH Statistics:

```
Input bytes:          0
Output bytes:         0
Input packets:        0
```

```

Output packets:          0
Errors:
  AH authentication failures: 0, Replay errors: 0
  ESP authentication failures: 0, ESP decryption failures: 0
  Bad headers: 0, Bad trailers: 0

```

Example: ES PIC IKE Dynamic SA Configuration

Figure 5: ES PIC IKE Dynamic SA Topology Diagram




Figure 5 on page 80 shows the same IPSec topology as seen in the ES PIC manual SA example. However, this time the configuration requires Routers 2 and 3 to establish an IPSec tunnel using an IKE dynamic SA, enhanced authentication, and stronger encryption. Routers 1 and 4 continue to provide basic connectivity and are used to verify that the IPSec tunnel is operational.

On Router 1, provide basic OSPF connectivity to Router 2.

```

Router 1 [edit]
interfaces {
  so-0/0/0 {
    description "To R2 so-0/0/0";
    unit 0 {
      family inet {
        address 10.1.12.2/30;
      }
    }
  }
  lo0 {
    unit 0 {
      family inet {
        address 10.0.0.1/32;
      }
    }
  }
}
routing-options {
  router-id 10.0.0.1;
}
protocols {
  ospf {
    area 0.0.0.0 {
      interface so-0/0/0.0;
      interface lo0.0;
    }
  }
}

```


On Router 2, enable OSPF as the underlying routing protocol to connect to Routers 1 and 3. Configure a bidirectional IKE dynamic SA called **sa-dynamic** at the **[edit security ipsec security-association]** hierarchy level. For your IKE policy and proposal, use preshared keys for the authentication method, SHA-1 for the authentication algorithm, 3DES-CBC for encryption, group 2 for the Diffie-Hellman group, main mode, 3600 seconds for the lifetime, and a preshared key of **juniper** for the initial IKE negotiation. For your IPSec policy and proposal, use ESP for the protocol, HMAC-SHA1-96 for authentication, 3DES-CBC for encryption, 28800 seconds for the lifetime, and group 2 for the PFS group.

To direct traffic into the ES PIC and the IPSec tunnel, create two firewall filters. The **es-traffic** filter matches inbound traffic from Router 1 destined for Router 4, whereas the **es-return** filter matches the return path from Router 4 to Router 1. Apply the **es-traffic** filter to the **so-0/0/0** interface, and then apply both the **es-return** filter and the **sa-dynamic** SA to the **es-0/3/0** interface.

```
Router 2 [edit]
interfaces {
  so-0/0/0 {
    description "To R1 so-0/0/0";
    unit 0 {
      family inet {
        filter {
          input es-traffic; # Apply a filter that sends traffic to the IPSec tunnel here.
        }
        address 10.1.12.1/30;
      }
    }
  }
  so-0/0/1 {
    description "To R3 so-0/0/1";
    unit 0 {
      family inet {
        address 10.1.15.1/30;
      }
    }
  }
}
es-0/3/0 {
  unit 0 {
    tunnel { # Specify the IPSec tunnel endpoints here.
      source 10.1.15.1;
      destination 10.1.15.2;
    }
    family inet {
      ipsec-sa sa-dynamic; # Apply the dynamic SA here.
      filter {
        input es-return; # Apply the filter that matches return IPSec traffic here.
      }
    }
  }
}
lo0 {
  unit 0 {
    family inet {
      address 10.0.0.2/32;
    }
  }
}
```

```

    }
  }
}
routing-options {
  router-id 10.0.0.2;
}
protocols {
  ospf {
    area 0.0.0.0 {
      interface so-0/0/0.0;
      interface so-0/0/1.0;
      interface lo0.0;
    }
  }
}
security {
  ipsec {
    proposal es-ipsec-proposal { # Define your IPSec proposal specifications here.
      protocol esp;
      authentication-algorithm hmac-sha1-96;
      encryption-algorithm 3des-cbc;
      lifetime-seconds 28800;
    }
    policy es-ipsec-policy { # Define your IPSec policy specifications here.
      perfect-forward-secrecy {
        keys group2;
      }
      proposals es-ipsec-proposal; # Reference the IPSec proposal here.
    }
    security-association sa-dynamic { # Define your dynamic SA here.
      mode tunnel;
      dynamic {
        ipsec-policy es-ipsec-policy; # Reference the IPSec policy here.
      }
    }
  }
}
ike {
  proposal es-ike-proposal { # Define your IKE proposal specifications here.
    authentication-method pre-shared-keys;
    dh-group group2;
    authentication-algorithm sha1;
    encryption-algorithm 3des-cbc;
    lifetime-seconds 3600;
  }
  policy 10.1.15.2 { # Define your IKE policy specifications here.
    mode main;
    proposals es-ike-proposal; # Reference the IKE proposal here.
    pre-shared-key ascii-text "$9$TF6ABlcvWxpOWxNdG4QFn";
    ## The unencrypted preshared key for this example is juniper.
  }
}
}
firewall {
  filter es-traffic { # Define a filter that sends traffic to the IPSec tunnel here.
    term to-es {

```

```

    from {
        source-address {
            10.1.12.0/24;
        }
        destination-address {
            10.1.56.0/24;
        }
    }
    then {
        count ipsec-tunnel;
        ipsec-sa sa-dynamic;
    }
}
term other {
    then accept;
}
}
filter es-return { # Define a filter that matches return IPSec traffic here.
    term return {
        from {
            source-address {
                10.1.56.0/24;
            }
            destination-address {
                10.1.12.0/24;
            }
        }
        then accept;
    }
}
}

```

On Router 3, enable OSPF as the underlying routing protocol to connect to Routers 2 and 4. Configure a bidirectional IKE dynamic SA called **sa-dynamic** at the **[edit security ipsec security-association]** hierarchy level. Use the same policies and proposals that you used on Router 2.

For your IKE policy and proposal, use preshared keys for the authentication method, SHA-1 for the authentication algorithm, 3DES-CBC for encryption, group 2 for the Diffie-Hellman group, main mode, 3600 seconds for the lifetime, and a preshared key of **juniper** for the initial IKE negotiation. For your IPSec policy and proposal, use ESP for the protocol, HMAC-SHA1-96 for authentication, 3DES-CBC for encryption, 28800 seconds for the lifetime, and group 2 for the PFS group.

To direct traffic into the ES PIC and the IPSec tunnel, create two firewall filters. The **es-traffic** filter matches inbound traffic from Router 4 destined for Router 1, whereas the **es-return** filter matches the return path from Router 1 to Router 4. Apply the **es-traffic** filter to the **so-0/0/0** interface; then apply both the **es-return** filter and the **sa-dynamic** SA to the **es-0/3/0** interface.

```

Router 3 [edit]
interfaces {
    so-0/0/0 {
        description "To R4 so-0/0/0";
        unit 0 {

```

```

        family inet {
            filter {
                input es-traffic; # Apply a filter that sends traffic to the IPSec tunnel here.
            }
            address 10.1.56.1/30;
        }
    }
}
so-0/0/1 {
    description "To R2 so-0/0/1";
    unit 0 {
        family inet {
            address 10.1.15.2/30;
        }
    }
}
es-0/3/0 {
    unit 0 {
        tunnel { # Specify the IPSec tunnel endpoints here.
            source 10.1.15.2;
            destination 10.1.15.1;
        }
        family inet {
            ipsec-sa sa-dynamic; # Apply the dynamic SA here.
            filter {
                input es-return; # Apply the filter that matches return IPSec traffic here.
            }
        }
    }
}
lo0 {
    unit 0 {
        family inet {
            address 10.0.0.3/32;
        }
    }
}
routing-options {
    router-id 10.0.0.3;
}
protocols {
    ospf {
        area 0.0.0.0 {
            interface so-0/0/0.0;
            interface so-0/0/1.0;
            interface lo0.0;
        }
    }
}
security {
    ipsec {
        proposal es-ipsec-proposal { # Define your IPSec proposal specifications here.
            protocol esp;
            authentication-algorithm hmac-sha1-96;
            encryption-algorithm 3des-cbc;
        }
    }
}

```

```

        lifetime-seconds 28800;
    }
    policy es-ipsec-policy { # Define your IPSec policy specifications here.
        perfect-forward-secrecy {
            keys group2;
        }
        proposals es-ipsec-proposal; # Reference the IPSec proposal here.
    }
    security-association sa-dynamic { # Define your dynamic SA here.
        mode tunnel;
        dynamic {
            ipsec-policy es-ipsec-policy; # Reference the IPSec policy here.
        }
    }
}
ike {
    proposal es-ike-proposal { # Define your IKE proposal specifications here.
        authentication-method pre-shared-keys;
        dh-group group2;
        authentication-algorithm sha1;
        encryption-algorithm 3des-cbc;
        lifetime-seconds 3600;
    }
    policy 10.1.15.1 { # Define your IKE policy specifications here.
        mode main;
        proposals es-ike-proposal; # Reference the IKE proposal here.
        pre-shared-key ascii-text "$9$TF6ABlcvWxpOWxNdG4QFn";
        ## The unencrypted preshared key for this example is juniper.
    }
}
}
firewall {
    filter es-traffic { # Define a filter that sends traffic to the IPSec tunnel here.
        term to-es {
            from {
                source-address {
                    10.1.56.0/24;
                }
                destination-address {
                    10.1.12.0/24;
                }
            }
            then {
                count ipsec-tunnel;
                ipsec-sa sa-dynamic;
            }
        }
        term other {
            then accept;
        }
    }
}
filter es-return { # Define a filter that matches return IPSec traffic here.
    term return {
        from {
            source-address {
                10.1.12.0/24;
            }

```

```
    }
    destination-address {
        10.1.56.0/24;
    }
}
then accept;
}
}
```

On Router 4, provide basic OSPF connectivity to Router 3.

```
Router 4 [edit]
interfaces {
    so-0/0/0 {
        description "To R3 so-0/0/0";
        unit 0 {
            family inet {
                address 10.1.56.2/30;
            }
        }
    }
    lo0 {
        unit 0 {
            family inet {
                address 10.0.0.4/32;
            }
        }
    }
}
routing-options {
    router-id 10.0.0.4;
}
protocols {
    ospf {
        area 0.0.0.0 {
            interface so-0/0/0.0;
            interface lo0.0;
        }
    }
}
```

Verifying Your Work

To verify proper operation of an IKE-based dynamic SA on the ES PIC, use the following commands:

- **ping**
- **show ike security-associations (detail)**
- **show ipsec security-associations (detail)**
- **traceroute**

The following sections show the output of these commands used with the configuration example:

- [Router 1 on page 87](#)
- [Router 2 on page 87](#)
- [Router 3 on page 88](#)
- [Router 4 on page 90](#)

Router 1

On Router 1, issue a **ping** command to the **so-0/0/0** interface of Router 4 to send traffic across the IPSec tunnel.

```
user@R1> ping 10.1.56.2
PING 10.1.56.2 (10.1.56.2): 56 data bytes
64 bytes from 10.1.56.2: icmp_seq=0 ttl=253 time=0.917 ms
64 bytes from 10.1.56.2: icmp_seq=1 ttl=253 time=0.881 ms
64 bytes from 10.1.56.2: icmp_seq=2 ttl=253 time=0.897 ms
64 bytes from 10.1.56.2: icmp_seq=3 ttl=253 time=0.871 ms
64 bytes from 10.1.56.2: icmp_seq=4 ttl=253 time=0.890 ms
64 bytes from 10.1.56.2: icmp_seq=5 ttl=253 time=0.858 ms
64 bytes from 10.1.56.2: icmp_seq=6 ttl=253 time=0.904 ms
^C
--- 10.1.56.2 ping statistics ---
7 packets transmitted, 7 packets received, 0% packet loss
round-trip min/avg/max/stddev = 0.858/0.888/0.917/0.019 ms
```

You can also issue the **traceroute** command to verify that traffic to **10.1.56.2** travels over the IPSec tunnel between Router 2 and Router 3. Notice that the second hop does not reference **10.1.15.2**—the physical interface on Router 3. Instead, the loopback address of **10.0.0.3** on Router 3 appears as the second hop. This indicates that the IPSec tunnel is operating correctly.

```
user@R1> traceroute 10.1.56.2
traceroute to 10.1.56.2 (10.1.56.2), 30 hops max, 40 byte packets
 1 10.1.12.1 (10.1.12.1) 0.655 ms 0.549 ms 0.508 ms
 2 10.0.0.3 (10.0.0.3) 0.833 ms 0.786 ms 0.757 ms

3 10.1.56.2 (10.1.56.2) 0.808 ms 0.741 ms 0.716 ms
```

Router 2

Another way to verify that matched traffic is being diverted to the bidirectional IPSec tunnel is to view the firewall filter counter. After you issue the **ping** command from Router 1 (seven packets), the **es-traffic** firewall filter counter looks like this:

```
user@R2> show firewall filter es-traffic
Filter: es-traffic
Counters:
Name                               Bytes          Packets
ipsec-tunnel                        588             7
```

After you issue the **ping** command from both Router 1 (seven packets) and Router 4 (five packets), the **es-traffic** firewall filter counter looks like this:

```
user@R2> show firewall filter es-traffic
Filter: es-traffic
Counters:
```

Name	Bytes	Packets
ipsec-tunnel	1008	12

To verify that the IKE SA negotiation between Routers 2 and 3 is successful, issue the **show ike security-associations detail** command. Notice that the SA contains the settings you specified, such as SHA-1 for the authentication algorithm and 3DES-CBC for the encryption algorithm.

```
user@R2> show ike security-associations detail
IKE peer 10.1.15.2
  Role: Initiator, State: Matured
  Initiator cookie: b5dbdfe2f9000000, Responder cookie: a24c868410000041
  Exchange type: Main, Authentication method: Pre-shared-keys
  Local: 10.1.15.1:500, Remote: 10.1.15.2:500
  Lifetime: Expires in 401 seconds
  Algorithms:
    Authentication      : sha1
    Encryption          : 3des-cbc
    Pseudo random function: hmac-sha1
  Traffic statistics:
    Input bytes  :          1736
    Output bytes :          2652
    Input packets:           9
    Output packets:         15
  Flags: Caller notification sent
  IPsec security associations: 3 created, 0 deleted
  Phase 2 negotiations in progress: 0
```

To verify that the IPsec security association is active, issue the **show ipsec security-associations detail** command. Notice that the SA contains the settings you specified, such as ESP for the protocol, HMAC-SHA1-96 for the authentication algorithm, and 3DES-CBC for the encryption algorithm.

```
user@R2> show ipsec security-associations detail
Security association: sa-dynamic, Interface family: Up
  Local gateway: 10.1.15.1, Remote gateway: 10.1.15.2
  Local identity: ipv4_subnet(any:0,[0..7]=10.1.12.0/24)
  Remote identity: ipv4_subnet(any:0,[0..7]=10.1.16.0/24)
  Direction: inbound, SPI: 2133029543, AUX-SPI: 0
  Mode: tunnel, Type: dynamic, State: Installed
  Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc
  Soft lifetime: Expires in 26212 seconds
  Hard lifetime: Expires in 26347 seconds
  Anti-replay service: Disabled
  Direction: outbound, SPI: 1759450863, AUX-SPI: 0
  Mode: tunnel, Type: dynamic, State: Installed
  Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc
  Soft lifetime: Expires in 26212 seconds
  Hard lifetime: Expires in 26347 seconds
  Anti-replay service: Disabled
```

Router 3

View the firewall filter counter to continue verifying that matched traffic is being diverted to the bidirectional IPsec tunnel. After you issue the **ping** command from Router 1 (seven packets), the **es-traffic** firewall filter counter looks like this:

```
user@R3> show firewall filter es-traffic
```



```
Filter: es-traffic
```

```
Counters:
```

Name	Bytes	Packets
ipsec-tunnel	588	7

After you issue the **ping** command from both Router 1 (seven packets) and Router 4 (five packets), the **es-traffic** firewall filter counter looks like this:

```
user@R3> show firewall filter es-traffic
```

```
Filter: es-traffic
```

```
Counters:
```

Name	Bytes	Packets
ipsec-tunnel	1008	12

To verify the success of the IKE security association, issue the **show ike security-associations detail** command. Notice that the SA on Router 3 contains the same settings you specified on Router 2.

```
user@R3> show ike security-associations detail
```

```
IKE peer 10.1.15.1
```

```
Role: Responder, State: Matured
```

```
Initiator cookie: b5dbdfe2f9000000, Responder cookie: a24c868410000041
```

```
Exchange type: Main, Authentication method: Pre-shared-keys
```

```
Local: 10.1.15.2:500, Remote: 10.1.15.1:500
```

```
Lifetime: Expires in 564 seconds
```

```
Algorithms:
```

```
Authentication : sha1
```

```
Encryption : 3des-cbc
```

```
Pseudo random function: hmac-sha1
```

```
Traffic statistics:
```

```
Input bytes : 2652
```

```
Output bytes : 1856
```

```
Input packets: 15
```

```
Output packets: 10
```

```
Flags: Caller notification sent
```

```
IPSec security associations: 3 created, 4 deleted
```

```
Phase 2 negotiations in progress: 0
```

To verify that the IPSec security association is active, issue the **show ipsec security-associations detail** command. Notice that the SA on Router 3 contains the same settings you specified on Router 2.

```
user@R3> show ipsec security-associations detail
```

```
Security association: sa-dynamic, Interface family: Up
```

```
Local gateway: 10.1.15.2, Remote gateway: 10.1.15.1
```

```
Local identity: ipv4_subnet(any:0,[0..7]=10.1.56.0/24)
```

```
Remote identity: ipv4_subnet(any:0,[0..7]=10.1.12.0/24)
```

```
Direction: inbound, SPI: 1759450863, AUX-SPI: 0
```

```
Mode: tunnel, Type: dynamic, State: Installed
```

```
Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc
```

```
Soft lifetime: Expires in 26427 seconds
```

```
Hard lifetime: Expires in 26517 seconds
```

```
Anti-replay service: Disabled
```

```
Direction: outbound, SPI: 2133029543, AUX-SPI: 0
```

```
Mode: tunnel, Type: dynamic, State: Installed
```

```
Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc
```

```
Soft lifetime: Expires in 26427 seconds
```

```
Hard lifetime: Expires in 26517 seconds
```

```
Anti-replay service: Disabled
```

Router 4

On Router 4, issue a **ping** command to the **so-0/0/0** interface of Router 1 to send traffic across the IPSec tunnel.

```
user@R4> ping 10.1.12.2
user@R4> ping 10.1.12.2
PING 10.1.12.2 (10.1.12.2): 56 data bytes
64 bytes from 10.1.12.2: icmp_seq=0 ttl=253 time=13.528 ms
64 bytes from 10.1.12.2: icmp_seq=1 ttl=253 time=0.873 ms
64 bytes from 10.1.12.2: icmp_seq=2 ttl=253 time=32.145 ms
64 bytes from 10.1.12.2: icmp_seq=3 ttl=253 time=0.921 ms
64 bytes from 10.1.12.2: icmp_seq=4 ttl=253 time=0.899 ms
^C
--- 10.1.12.2 ping statistics ---
5 packets transmitted, 5 packets received, 0% packet loss
round-trip min/avg/max/stddev = 0.873/9.673/32.145/12.255 ms
```

You can also issue the **traceroute** command to verify that traffic to **10.1.12.2** travels over the IPSec tunnel between Router 3 and Router 2. Notice that the second hop does not reference **10.1.15.1**—the physical interface on Router 2. Instead, the loopback address of **10.0.0.2** on Router 2 appears as the second hop. This indicates that the IPSec tunnel is operating correctly.

```
user@R4> traceroute 10.1.12.2
traceroute to 10.1.12.2 (10.1.12.2), 30 hops max, 40 byte packets
 1 10.1.56.1 (10.1.56.1) 0.681 ms 0.624 ms 0.547 ms
 2 10.0.0.2 (10.0.0.2) 0.800 ms 0.770 ms 0.737 ms
 3 10.1.12.2 (10.1.12.2) 0.793 ms 0.742 ms 0.716 ms
```

Example: AS PIC IKE Dynamic SA Configuration

Figure 6: AS PIC IKE Dynamic SA Topology Diagram




Figure 6 on page 90 shows the same IPSec topology as seen in the AS PIC manual SA example. However, this configuration requires Routers 2 and 3 to establish an IPSec tunnel using an IKE dynamic SA, enhanced authentication, and stronger encryption. Routers 1 and 4 continue to provide basic connectivity and are used to verify that the IPSec tunnel is operational.



NOTE: When you do not specify an IKE proposal, an IPSec proposal, and an IPSec policy on an AS PIC, the Junos OS defaults to the highest level of encryption and authentication. As a result, the default authentication protocol is ESP, the default authentication mode is HMAC-SHA1-96, and the default encryption mode is 3DES-CBC. For more information about default IKE and IPSec policies and proposals on the AS PIC, see [“IKE and IPSec Proposal and Policy Default Values for the AS and MultiServices PICs”](#) on page 26.

On Router 1, provide basic OSPF connectivity to Router 2.

```
Router 1 [edit]
interfaces {
  so-0/0/0 {
    description "To R2 so-0/0/0";
    unit 0 {
      family inet {
        address 10.1.12.2/30;
      }
    }
  }
  lo0 {
    unit 0 {
      family inet {
        address 10.0.0.1/32;
      }
    }
  }
}
routing-options {
  router-id 10.0.0.1;
}
protocols {
  ospf {
    area 0.0.0.0 {
      interface so-0/0/0.0;
      interface lo0.0;
    }
  }
}
```

On Router 2, enable OSPF as the underlying routing protocol to connect to Routers 1 and 3. Configure a bidirectional IKE dynamic SA in a rule called **rule-ike** at the **[edit ipsec-vpn rule]** hierarchy level. Reference this rule in a service set called **service-set-dynamic-BiEspsha3des** at the **[edit services service-set]** hierarchy level.

Using default values in the AS PIC, you do not need to specify an IPSec proposal, IPSec policy, or IKE proposal. However, you do need to configure a preshared key in an IKE policy with the **pre-shared-key** statement at the **[edit services ipsec-vpn ike policy *policy-name*]** hierarchy level. (For more information about default IKE and IPSec policies and proposals on the AS PIC, see [“IKE and IPSec Proposal and Policy Default Values for the AS and MultiServices PICs”](#) on page 26.)

To direct traffic into the AS PIC and the IPSec tunnel, configure a next-hop style service set and add the adaptive services logical interface used as the IPSec inside interface into the OSPF configuration.

```
Router 2 [edit]
interfaces {
  so-0/0/0 {
    description "To R1 so-0/0/0";
    unit 0 {
      family inet {
        address 10.1.12.1/30;
      }
    }
  }
  so-0/0/1 {
    description "To R3 so-0/0/1";
    unit 0 {
      family inet {
        address 10.1.15.1/30;
      }
    }
  }
  sp-1/2/0 {
    services-options {
      syslog {
        host local {
          services info;
        }
      }
    }
    unit 0 {
      family inet {
      }
    }
    unit 1 { # sp-1/2/0.1 is the IPSec inside interface.
      family inet;
      service-domain inside;
    }
    unit 2 { # sp-1/2/0.2 is the IPSec outside interface.
      family inet;
      service-domain outside;
    }
  }
  lo0 {
    unit 0 {
      family inet {
        address 10.0.0.2/32;
      }
    }
  }
}
routing-options {
  router-id 10.0.0.2;
}
protocols {
  ospf {
    area 0.0.0.0 {
```

```

        interface so-0/0/0.0;
        interface lo0.0;
        interface sp-1/2/0.1; # This sends OSPF traffic over the IPSec tunnel.
    }
}
}
services {
    service-set service-set-dynamic-BiEspsha3des { # Define your service set here.
        next-hop-service { # Required for dynamic routing protocols such as OSPF.
            inside-service-interface sp-1/2/0.1;
            outside-service-interface sp-1/2/0.2;
        }
        ipsec-vpn-options {
            local-gateway 10.1.15.1; # Specify the local IP address of the IPSec tunnel.
        }
        ipsec-vpn-rules rule-ike; # Reference your IPSec VPN rule here.
    }
    ipsec-vpn {
        rule rule-ike { # Define your IPSec VPN rule here.
            term term-ike {
                then {
                    remote-gateway 10.1.15.2; # The remote IP address of the IPSec tunnel.
                    dynamic { # This creates a dynamic SA.
                        ike-policy ike-policy-preshared; # Reference your IKE policy here.
                    }
                }
            }
            match-direction input; # Specify in which direction the rule should match.
        }
        ike {
            policy ike-policy-preshared { # Define your IKE policy specifications here.
                pre-shared-key ascii-text "$9$KtKWX-YgJHqfVwqfTzCAvWL";
                ## The unencrypted preshared key for this example is juniper.
            }
        }
    }
}
}

```

On Router 3, enable OSPF as the underlying routing protocol to connect to Routers 2 and 4. Configure a bidirectional IKE dynamic SA in a rule called **rule-ike** at the **[edit ipsec-vpn rule]** hierarchy level. Reference this rule in a service set called **service-set-dynamic-BiEspsha3des** at the **[edit services service-set]** hierarchy level.

Again, use the same default policies and proposals that you used on Router 2. However, remember to configure a preshared key in an IKE policy with the **pre-shared-key** statement at the **[edit services ipsec-vpn ike policy *policy-name*]** hierarchy level. The key must match the one you specified on Router 2. (For more information about default IKE and IPSec policies and proposals on the AS PIC, see [“IKE and IPSec Proposal and Policy Default Values for the AS and MultiServices PICs”](#) on page 26.)

To direct traffic into the AS PIC and the IPSec tunnel, configure a next-hop style service set and add the adaptive services logical interface used as the IPSec inside interface into the OSPF configuration.

```

Router 3 [edit]
interfaces {
  so-0/0/0 {
    description "To R4 so-0/0/0";
    unit 0 {
      family inet {
        address 10.1.56.1/30;
      }
    }
  }
  so-0/0/1 {
    description "To R2 so-0/0/1";
    unit 0 {
      family inet {
        address 10.1.15.2/30;
      }
    }
  }
  sp-1/2/0 {
    services-options {
      syslog {
        host local {
          services info;
        }
      }
    }
    unit 0 {
      family inet {
      }
    }
    unit 1 { # sp-1/2/0.1 is the IPSec inside interface.
      family inet;
      service-domain inside;
    }
    unit 2 { # sp-1/2/0.2 is the IPSec outside interface.
      family inet;
      service-domain outside;
    }
  }
  lo0 {
    unit 0 {
      family inet {
        address 10.0.0.3/32;
      }
    }
  }
}
routing-options {
  router-id 10.0.0.3;
}
protocols {
  ospf {
    area 0.0.0.0 {
      interface so-0/0/0.0;
      interface lo0.0;
      interface sp-1/2/0.1; # This sends OSPF traffic over the IPSec tunnel.
    }
  }
}

```

```

    }
  }
  services {
    service-set service-set-dynamic-BiEspsha3des { # Define your service set here.
      next-hop-service { # Required for dynamic routing protocols such as OSPF.
        inside-service-interface sp-1/2/0.1;
        outside-service-interface sp-1/2/0.2;
      }
      ipsec-vpn-options {
        local-gateway 10.1.15.2; # Specify the local IP address of the IPSec tunnel.
      }
      ipsec-vpn-rules rule-ike; # Reference your IPSec VPN rule here.
    }
    ipsec-vpn {
      rule rule-ike { # Define your IPSec VPN rule here.
        term term-ike {
          then {
            remote-gateway 10.1.15.1; # The remote IP address of the IPSec tunnel.
            dynamic { # This creates a dynamic SA.
              ike-policy ike-policy-preshared; # Reference your IKE policy here.
            }
          }
        }
        match-direction input; # Specify in which direction the rule should match.
      }
      ike {
        policy ike-policy-preshared { # Define your IKE policy specifications here.
          pre-shared-key ascii-text "$9$KtKWX-YgJHqfVwqfTzCAvWL";
          ## The unencrypted preshared key for this example is juniper.
        }
      }
    }
  }
}

```

On Router 4, provide basic OSPF connectivity to Router 3.

```

Router 4 [edit]
interfaces {
  so-0/0/0 {
    description "To R3 so-0/0/0";
    unit 0 {
      family inet {
        address 10.1.56.2/30;
      }
    }
  }
  lo0 {
    unit 0 {
      family inet {
        address 10.0.0.4/32;
      }
    }
  }
}
routing-options {

```

```
    router-id 10.0.0.4;
  }
  protocols {
    ospf {
      area 0.0.0.0 {
        interface so-0/0/0.0;
        interface lo0.0;
      }
    }
  }
}
```

Verifying Your Work

To verify proper operation of an IKE-based dynamic SA on the AS PIC, use the following commands:

- **ping**
- **show services ipsec-vpn ike security-associations (detail)**
- **show services ipsec-vpn ipsec security-associations (detail)**
- **show services ipsec-vpn ipsec statistics**
- **traceroute**

The following sections show the output of these commands used with the configuration example:

- [Router 1 on page 96](#)
- [Router 2 on page 97](#)
- [Router 3 on page 98](#)
- [Router 4 on page 98](#)

Router 1

On Router 1, issue a **ping** command to the **so-0/0/0** interface on Router 4 to send traffic across the IPSec tunnel.

```
user@R1> ping 10.1.56.2
PING 10.1.56.2 (10.1.56.2): 56 data bytes
64 bytes from 10.1.56.2: icmp_seq=0 ttl=254 time=1.351 ms
64 bytes from 10.1.56.2: icmp_seq=1 ttl=254 time=1.187 ms
64 bytes from 10.1.56.2: icmp_seq=2 ttl=254 time=1.172 ms
64 bytes from 10.1.56.2: icmp_seq=3 ttl=254 time=1.154 ms
64 bytes from 10.1.56.2: icmp_seq=4 ttl=254 time=1.156 ms
^C
--- 10.1.56.2 ping statistics ---
5 packets transmitted, 5 packets received, 0% packet loss
round-trip min/avg/max/stddev = 1.154/1.204/1.351/0.074 ms
```


Router 2

To verify that the IKE SA negotiation is successful, issue the **show services ipsec-vpn ike security-associations** command.

```
user@R2> show services ipsec-vpn ike security-associations
Remote Address  State      Initiator cookie  Responder cookie  Exchange type
10.1.15.2       Matured    03075bd3a0000003  4bfff26a5c7000003  Main
```

To verify that the IPSec security association is active, issue the **show services ipsec-vpn ipsec security-associations detail** command. Notice that the SA contains the default settings inherent in the AS PIC, such as ESP for the protocol and HMAC-SHA1-96 for the authentication algorithm.

```
user@R2> show services ipsec-vpn ipsec security-associations detail
Service set: service-set-dynamic-BiEspsha3des
Rule: rule-ike, Term: term-ike, Tunnel index: 1
Local gateway: 10.1.15.1, Remote gateway: 10.1.15.2
Local identity: ipv4_subnet(any:0,[0..7]=10.1.12.0/24)
Remote identity: ipv4_subnet(any:0,[0..7]=10.1.56.0/24)
Direction: inbound, SPI: 2666326758, AUX-SPI: 0
Mode: tunnel, Type: dynamic, State: Installed
Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc
Soft lifetime: Expires in 26863 seconds
Hard lifetime: Expires in 26998 seconds
Anti-replay service: Enabled, Replay window size: 64
Direction: outbound, SPI: 684772754, AUX-SPI: 0
Mode: tunnel, Type: dynamic, State: Installed
Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc
Soft lifetime: Expires in 26863 seconds
Hard lifetime: Expires in 26998 seconds
Anti-replay service: Enabled, Replay window size: 64
```

To verify that traffic is traveling over the bidirectional IPSec tunnel, issue the **show services ipsec-vpn statistics** command:

```
user@R2> show services ipsec-vpn ipsec statistics
PIC: sp-1/2/0, Service set: service-set-dynamic-BiEspsha3des
ESP Statistics:
  Encrypted bytes:      2248
  Decrypted bytes:      2120
  Encrypted packets:    27
  Decrypted packets:    25
AH Statistics:
  Input bytes:          0
  Output bytes:         0
  Input packets:        0
  Output packets:       0
Errors:
  AH authentication failures: 0, Replay errors: 0
  ESP authentication failures: 0, ESP decryption failures: 0
Bad headers: 0, Bad trailers: 0
```

Router 3

To verify that the IKE SA negotiation is successful, issue the **show services ipsec-vpn ike security-associations** command. To be successful, the SA on Router 3 must contain the same settings you specified on Router 2.

```
user@R3> show services ipsec-vpn ike security-associations
Remote Address  State      Initiator cookie  Responder cookie  Exchange type
10.1.15.1       Matured           03075bd3a0000003  4bffa26a5c7000003  Main
```

To verify that the IPsec SA is active, issue the **show services ipsec-vpn ipsec security-associations detail** command. To be successful, the SA on Router 3 must contain the same settings you specified on Router 2.

```
user@R3> show services ipsec-vpn ipsec security-associations detail
Service set: service-set-dynamic-BiEspsha3des
Rule: rule-ike, Term: term-ike, Tunnel index: 1
Local gateway: 10.1.15.2, Remote gateway: 10.1.15.1
Local identity: ipv4_subnet(any:0,[0..7]=10.1.56.0/24)
Remote identity: ipv4_subnet(any:0,[0..7]=10.1.12.0/24)
Direction: inbound, SPI: 684772754, AUX-SPI: 0
Mode: tunnel, Type: dynamic, State: Installed
Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc
Soft lifetime: Expires in 26598 seconds
Hard lifetime: Expires in 26688 seconds
Anti-replay service: Enabled, Replay window size: 64
Direction: outbound, SPI: 2666326758, AUX-SPI: 0
Mode: tunnel, Type: dynamic, State: Installed
Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc
Soft lifetime: Expires in 26598 seconds
Hard lifetime: Expires in 26688 seconds
Anti-replay service: Enabled, Replay window size: 64
```

To verify that traffic is traveling over the bidirectional IPsec tunnel, issue the **show services ipsec-vpn statistics** command:

```
user@R3> show services ipsec-vpn ipsec statistics
PIC: sp-1/2/0, Service set: service-set-dynamic-BiEspsha3des
ESP Statistics:
  Encrypted bytes:          2120
  Decrypted bytes:         2248
  Encrypted packets:        25
  Decrypted packets:        27
AH Statistics:
  Input bytes:              0
  Output bytes:             0
  Input packets:            0
  Output packets:           0
Errors:
  AH authentication failures: 0, Replay errors: 0
  ESP authentication failures: 0, ESP decryption failures: 0
```

Bad headers: 0, Bad trailers: 0

Router 4

On Router 4, issue a **ping** command to the **so-0/0/0** interface on Router 1 to send traffic across the IPsec tunnel.

```
user@R4> ping 10.1.12.2
```

```

PING 10.1.12.2 (10.1.12.2): 56 data bytes
64 bytes from 10.1.12.2: icmp_seq=0 ttl=254 time=1.350 ms
64 bytes from 10.1.12.2: icmp_seq=1 ttl=254 time=1.161 ms
64 bytes from 10.1.12.2: icmp_seq=2 ttl=254 time=1.124 ms
64 bytes from 10.1.12.2: icmp_seq=3 ttl=254 time=1.142 ms
64 bytes from 10.1.12.2: icmp_seq=4 ttl=254 time=1.139 ms
64 bytes from 10.1.12.2: icmp_seq=5 ttl=254 time=1.116 ms
^C
--- 10.1.12.2 ping statistics ---
6 packets transmitted, 6 packets received, 0% packet loss
round-trip min/avg/max/stddev = 1.116/1.172/1.350/0.081 ms

```

The final way you can confirm that traffic travels over the IPSec tunnel is by issuing the **traceroute** command to the **so-0/0/0** interface on Router 1. Notice that the physical interface between Routers 2 and 3 is not referenced in the path; traffic enters the IPSec tunnel through the adaptive services IPSec inside interface on Router 3, passes through the loopback interface on Router 2, and ends at the **so-0/0/0** interface on Router 1.

```

user@R4> traceroute 10.1.12.2
traceroute to 10.1.12.2 (10.1.12.2), 30 hops max, 40 byte packets
 1  10.1.15.2 (10.1.15.2)  0.987 ms  0.630 ms  0.563 ms
 2  10.0.0.2 (10.0.0.2)  1.194 ms  1.058 ms  1.033 ms
 3  10.1.12.2 (10.1.12.2)  1.073 ms  0.949 ms  0.932 ms

```

Example: IKE Dynamic SA Between an AS PIC and an ES PIC Configuration

Figure 7: AS PIC to ES PIC IKE Dynamic SA Topology Diagram




Figure 7 on page 99 shows a hybrid configuration that allows you to create an IPSec tunnel between the AS PIC and the ES PIC. Router 2 contains an AS PIC at **sp-1/2/0** and Router 3 has an ES PIC at **es-0/3/0**. To establish an IPSec tunnel using an IKE dynamic SA, the key is to learn the default IKE SA and IPSec SA settings built into the AS PIC and configure them explicitly on the ES PIC. Routers 1 and 4 again provide basic connectivity and are used to verify that the IPSec tunnel is operational.

On Router 1, provide basic OSPF connectivity to Router 2.

```

Router 1 [edit]
interfaces {
  so-0/0/0 {
    description "To R2 so-0/0/0";
    unit 0 {
      family inet {
        address 10.1.12.2/30;
      }
    }
  }
}

```

```

lo0 {
  unit 0 {
    family inet {
      address 10.0.0.1/32;
    }
  }
}
routing-options {
  router-id 10.0.0.1;
}
protocols {
  ospf {
    area 0.0.0.0 {
      interface so-0/0/0.0;
      interface lo0.0;
    }
  }
}

```

On Router 2, enable OSPF as the underlying routing protocol to connect to Routers 1 and 3. Configure a bidirectional IKE dynamic SA in a rule called **rule-ike** at the **[edit ipsec-vpn rule]** hierarchy level. Reference this rule in a service set called **service-set-dynamic-BiEspsha3des** at the **[edit services service-set]** hierarchy level.

Using default values in the AS PIC, you do not need to specify an IPSec proposal, IPSec policy, or IKE proposal. However, you do need to configure a preshared key in an IKE policy with the **pre-shared-key** statement at the **[edit services ipsec-vpn ike policy *policy-name*]** hierarchy level. (For more information about default IKE and IPSec policies and proposals on the AS PIC, see [“IKE and IPSec Proposal and Policy Default Values for the AS and MultiServices PICs”](#) on page 26.)

To direct traffic into the AS PIC and the IPSec tunnel, include match conditions in the **rule-ike** IPSec VPN rule to match inbound traffic from Router 1 that is destined for Router 4. Because the rule is already referenced by the service set, apply the service set to the **so-0/0/1** interface. To count the amount of traffic that enters the IPSec tunnel, configure a firewall filter called **ipsec-tunnel** and apply it to the **sp-1/2/0** interface.

```

Router 2 [edit]
interfaces {
  so-0/0/0 {
    description "To R1 so-0/0/0";
    unit 0 {
      family inet {
        address 10.1.12.1/30;
      }
    }
  }
  so-0/0/1 {
    description "To R3 so-0/0/1";
    unit 0 {
      family inet {
        service { # Apply the service set here.
          input {
            service-set service-set-dynamic-BiEspsha3des;

```

```

    }
    output {
        service-set service-set-dynamic-BIEspsha3des;
    }
}
address 10.1.15.1/30;
}
}
sp-1/2/0 {
    services-options {
        syslog {
            host local {
                services info;
            }
        }
    }
    unit 0 {
        family inet {
            filter {
                input ipsec-tunnel; # Apply the firewall filter with the counter here.
            }
        }
    }
}
lo0 {
    unit 0 {
        family inet {
            address 10.0.0.2/32;
        }
    }
}
}
routing-options {
    router-id 10.0.0.2;
}
protocols {
    ospf {
        area 0.0.0.0 {
            interface so-0/0/0.0;
            interface so-0/0/1.0;
            interface lo0.0;
        }
    }
}
}
firewall {
    filter ipsec-tunnel { # Configure a firewall filter to count IPSec traffic here.
        term 1 {
            then {
                count ipsec-tunnel;
                accept;
            }
        }
    }
}
}
services {

```

```

service-set service-set-dynamic-BiEspsha3des { # Define your service set here.
  interface-service {
    service-interface sp-1/2/0; # Specify an interface to process IPSec.
  }
  ipsec-vpn-options {
    local-gateway 10.1.15.1; # Specify the local IP address of the IPSec tunnel.
  }
  ipsec-vpn-rules rule-ike; # Reference your IPSec VPN rule here.
}
ipsec-vpn {
  rule rule-ike { # Define your IPSec VPN rule here.
    term term-ike {
      from {
        source-address {
          10.1.12.0/24;
        }
        destination-address {
          10.1.56.0/24;
        }
      }
      then {
        remote-gateway 10.1.15.2; # The remote IP address of the IPSec tunnel.
        dynamic { # This creates a dynamic SA.
          ike-policy ike-policy-preshared; # Reference your IKE proposal here.
        }
      }
    }
  }
  match-direction output; # Specify in which direction the rule should match.
}
ike {
  policy ike-policy-preshared { # Define your IKE policy specifications here.
    pre-shared-key ascii-text "$9$KtKWx-YgJHqfVwqfTzCAvWL";
    ## The unencrypted preshared key for this example is juniper.
  }
}
}
}

```

On Router 3, enable OSPF as the underlying routing protocol to connect to Routers 2 and 4. Configure a bidirectional IKE dynamic SA called **sa-dynamic** at the **[edit security ipsec security-association]** hierarchy level. To allow the ES PIC to communicate with the IKE dynamic SA established on Router 2, you must explicitly configure the same policies and proposals on the ES PIC that are available by default on the AS PIC. (For more information about default IKE and IPSec policies and proposals on the AS PIC, see [“IKE and IPSec Proposal and Policy Default Values for the AS and MultiServices PICs”](#) on page 26.)

For your IKE policy and proposal, use preshared keys for the authentication method, SHA-1 for the authentication algorithm, 3DES-CBC for encryption, group 2 for the Diffie-Hellman group, main mode, 3600 seconds for the lifetime, and a preshared key of **juniper** for the initial IKE negotiation. For your IPSec policy and proposal, use ESP for the protocol, HMAC-SHA1-96 for authentication, 3DES-CBC for encryption, 28800 seconds for the lifetime, and group 2 for the PFS group.

To direct traffic into the ES PIC and the IPSec tunnel, create two firewall filters. The **es-traffic** filter matches inbound traffic from Router 4 destined for Router 1, whereas the **es-return** filter matches the return path from Router 1 to Router 4. Apply the **es-traffic** filter to the **so-0/0/0** interface; then apply both the **es-return** filter and the **sa-dynamic** SA to the **es-0/3/0** interface.

```
Router 3 [edit]
interfaces {
  so-0/0/0 {
    description "To R4 so-0/0/0";
    unit 0 {
      family inet {
        filter {
          input es-traffic; # Apply a filter that sends traffic to the IPSec tunnel here.
        }
        address 10.1.56.1/30;
      }
    }
  }
  so-0/0/1 {
    description "To R2 so-0/0/1";
    unit 0 {
      family inet {
        address 10.1.15.2/30;
      }
    }
  }
  es-0/3/0 {
    unit 0 {
      tunnel { # Specify the IPSec tunnel endpoints here.
        source 10.1.15.2;
        destination 10.1.15.1;
      }
      family inet {
        ipsec-sa sa-dynamic; # Apply the dynamic SA here.
        filter {
          input es-return; # Apply the filter that matches return IPSec traffic here.
        }
      }
    }
  }
  lo0 {
    unit 0 {
      family inet {
        address 10.0.0.3/32;
      }
    }
  }
}
routing-options {
  router-id 10.0.0.3;
}
protocols {
  ospf {
```

```

    area 0.0.0.0 {
        interface so-0/0/0.0;
        interface so-0/0/1.0;
        interface lo0.0;
    }
}
security {
    ipsec {
        proposal es-ipsec-proposal { # Define your IPSec proposal specifications here.
            protocol esp;
            authentication-algorithm hmac-sha1-96;
            encryption-algorithm 3des-cbc;
            lifetime-seconds 28800;
        }
        policy es-ipsec-policy { # Define your IPSec policy specifications here.
            perfect-forward-secrecy {
                keys group2;
            }
            proposals es-ipsec-proposal; # Reference the IPSec proposal here.
        }
        security-association sa-dynamic { # Define your dynamic SA here.
            mode tunnel;
            dynamic {
                ipsec-policy es-ipsec-policy; # Reference the IPSec policy here.
            }
        }
    }
}
ike {
    proposal es-ike-proposal { # Define your IKE proposal specifications here.
        authentication-method pre-shared-keys;
        dh-group group2;
        authentication-algorithm sha1;
        encryption-algorithm 3des-cbc;
        lifetime-seconds 3600;
    }
    policy 10.1.15.1 { # Define your IKE policy specifications here.
        mode main;
        proposals es-ike-proposal; # Reference the IKE proposal here.
        pre-shared-key ascii-text "$9$TF6ABlcvWxpOWxNdG4QFn";
        ## The unencrypted preshared key for this example is juniper.
    }
}
}
firewall {
    filter es-traffic { # Define a filter that sends traffic to the IPSec tunnel here.
        term to-es {
            from {
                source-address {
                    10.1.56.0/24;
                }
                destination-address {
                    10.1.12.0/24;
                }
            }
        }
        then {

```



```

        count ipsec-tunnel;
        ipsec-sa sa-dynamic;
    }
}
term other {
    then accept;
}
}
filter es-return { # Define a filter that matches return IPSec traffic here.
    term return {
        from {
            source-address {
                10.1.12.0/24;
            }
            destination-address {
                10.1.56.0/24;
            }
        }
        then accept;
    }
}
}

```

On Router 4, provide basic OSPF connectivity to Router 3.

```

Router 4 [edit]
interfaces {
    so-0/0/0 {
        description "To R3 so-0/0/0";
        unit 0 {
            family inet {
                address 10.1.56.2/30;
            }
        }
    }
    lo0 {
        unit 0 {
            family inet {
                address 10.0.0.4/32;
            }
        }
    }
}
routing-options {
    router-id 10.0.0.4;
}
protocols {
    ospf {
        area 0.0.0.0 {
            interface so-0/0/0.0;
            interface lo0.0;
        }
    }
}
}

```

Verifying Your Work

To verify proper operation of an IKE-based dynamic SA on the AS PIC, use the following commands:

- **ping**
- **show services ipsec-vpn ike security-associations (detail)**
- **show services ipsec-vpn ipsec security-associations (detail)**
- **traceroute**

To verify proper operation of an IKE-based dynamic SA on the ES PIC, use the following commands:

- **ping**
- **show ike security-associations (detail)**
- **show ipsec security-associations (detail)**
- **traceroute**

The following sections show the output of these commands used with the configuration example:

- [Router 1 on page 106](#)
- [Router 2 on page 107](#)
- [Router 3 on page 108](#)
- [Router 4 on page 109](#)

Router 1

On Router 1, issue a **ping** command to the **so-0/0/0** interface of Router 4 to send traffic across the IPSec tunnel.

```
user@R1> ping 10.1.56.2
PING 10.1.56.2 (10.1.56.2): 56 data bytes
64 bytes from 10.1.56.2: icmp_seq=0 ttl=253 time=1.172 ms
64 bytes from 10.1.56.2: icmp_seq=1 ttl=253 time=1.020 ms
64 bytes from 10.1.56.2: icmp_seq=2 ttl=253 time=0.998 ms
64 bytes from 10.1.56.2: icmp_seq=3 ttl=253 time=1.037 ms
^C
--- 10.1.56.2 ping statistics ---
4 packets transmitted, 4 packets received, 0% packet loss
round-trip min/avg/max/stddev = 0.998/1.057/1.172/0.068 ms
```

You can also issue the **traceroute** command to verify that traffic to **10.1.56.2** travels over the IPSec tunnel between Router 2 and Router 3. Notice that the traced path does not reference **10.1.15.2**—the physical interface on Router 3. Instead, traffic arriving at Router 2 is immediately filtered into the IPSec tunnel and the path is listed as unknown with the ******* notation. This indicates that the IPSec tunnel is operating correctly.

```
user@R1> traceroute 10.1.56.2
```

```

traceroute to 10.1.56.2 (10.1.56.2), 30 hops max, 40 byte packets
 1 * * *
 2 10.1.56.2 (10.1.56.2) 1.045 ms 0.915 ms 0.850 ms

```

Router 2

One way to verify that matched traffic is being diverted to the bidirectional IPSec tunnel is to view the firewall filter counter. Before any traffic flows, the **ipsec-tunnel** firewall filter counter looks like this:

```

user@R2> show firewall filter ipsec-tunnel
Filter: ipsec-tunnel
Counters:
Name                               Bytes          Packets
ipsec-tunnel                        0              0

```

After you issue the **ping** command from Router 1 (four packets) to 10.1.56.2, the **ipsec-tunnel** firewall filter counter looks like this:

```

user@R2> show firewall filter ipsec-tunnel
Filter: ipsec-tunnel
Counters:
Name                               Bytes          Packets
ipsec-tunnel                        336            4

```

After you issue the **ping** command from both Router 1 to 10.1.56.2 (four packets) and from Router 4 to 10.1.12.2 (six packets), the **ipsec-tunnel** firewall filter counter looks like this:

```

user@R2> show firewall filter ipsec-tunnel
Filter: es-traffic
Counters:
Name                               Bytes          Packets
ipsec-tunnel                        840            10

```

To verify that the IKE SA negotiation is successful, issue the **show services ipsec-vpn ike security-associations detail** command. Notice that the SA contains the default IKE settings inherent in the AS PIC, such as SHA-1 for the authentication algorithm and 3DES-CBC for the encryption algorithm.

```

user@R2> show services ipsec-vpn ike security-associations detail
IKE peer 10.1.15.2
  Role: Responder, State: Matured
  Initiator cookie: c8e1e4c0da000040, Responder cookie: 4fbaa5184e000044
  Exchange type: Main, Authentication method: Pre-shared-keys
  Local: 10.1.15.1:500, Remote: 10.1.15.2:500
  Lifetime: Expires in 3535 seconds
  Algorithms:
    Authentication      : sha1
    Encryption          : 3des-cbc
    Pseudo random function: hmac-sha1
  Traffic statistics:
    Input bytes :      840
    Output bytes :     756
    Input packets:       5
    Output packets:      4
  Flags: Caller notification sent
  IPSec security associations: 1 created, 0 deleted
  Phase 2 negotiations in progress: 0

```

To verify that the IPSec security association is active, issue the **show services ipsec-vpn ipsec security-associations detail** command. Notice that the SA contains the default settings inherent in the AS PIC, such as ESP for the protocol and HMAC-SHA1-96 for the authentication algorithm.

```
user@R2> show services ipsec-vpn ipsec security-associations detail
Service set: service-set-dynamic-BiEspsha3des
Rule: rule-ike, Term: term-ike, Tunnel index: 1
Local gateway: 10.1.15.1, Remote gateway: 10.1.15.2
Local identity: ipv4_subnet(any:0,[0..7]=10.1.12.0/24)
Remote identity: ipv4_subnet(any:0,[0..7]=10.1.56.0/24)
Direction: inbound, SPI: 407204513, AUX-SPI: 0
Mode: tunnel, Type: dynamic, State: Installed
Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc
Soft lifetime: Expires in 24546 seconds
Hard lifetime: Expires in 24636 seconds
Anti-replay service: Disabled
Direction: outbound, SPI: 2957235894, AUX-SPI: 0
Mode: tunnel, Type: dynamic, State: Installed
Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc
Soft lifetime: Expires in 24546 seconds
Hard lifetime: Expires in 24636 seconds
Anti-replay service: Disabled
```

Router 3

View the firewall filter counter to continue verifying that matched traffic is being diverted to the bidirectional IPSec tunnel. After you issue the **ping** command from Router 1 (four packets), the **es-traffic** firewall filter counter looks like this:

```
user@R3> show firewall filter es-traffic
Filter: es-traffic
Counters:
Name                               Bytes      Packets
ipsec-tunnel                        336         4
```

After you issue the **ping** command from both Router 1 (four packets) and Router 4 (six packets), the **es-traffic** firewall filter counter looks like this:

```
user@R3> show firewall filter es-traffic
Filter: es-traffic
Counters:
Name                               Bytes      Packets
ipsec-tunnel                        840        10
```

To verify the success of the IKE security association on the ES PIC, issue the **show ike security-associations detail** command. Notice that the IKE SA on Router 3 contains the same settings you specified on Router 2.

```
user@R3> show ike security-associations detail
IKE peer 10.1.15.1
Role: Initiator, State: Matured
Initiator cookie: c8e1e4c0da000040, Responder cookie: 4fbaa5184e000044
Exchange type: Main, Authentication method: Pre-shared-keys
Local: 10.1.15.2:500, Remote: 10.1.15.1:500
Lifetime: Expires in 3441 seconds
Algorithms:
Authentication      : sha1
Encryption          : 3des-cbc
```

```

Pseudo random function: hmac-sha1
Traffic statistics:
Input bytes :          756
Output bytes :          840
Input packets:          4
Output packets:         5
Flags: Caller notification sent
IPSec security associations: 1 created, 0 deleted
Phase 2 negotiations in progress: 0

```

To verify that the IPSec security association is active, issue the **show ipsec security-associations detail** command. Notice that the IPSec SA on Router 3 contains the same settings you specified on Router 2.

```

user@R3> show ipsec security-associations detail
Security association: sa-dynamic, Interface family: Up
Local gateway: 10.1.15.2, Remote gateway: 10.1.15.1
Local identity: ipv4_subnet(any:0,[0..7]=10.1.56.0/24)
Remote identity: ipv4_subnet(any:0,[0..7]=10.1.12.0/24)
Direction: inbound, SPI: 2957235894, AUX-SPI: 0
Mode: tunnel, Type: dynamic, State: Installed
Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc
Soft lifetime: Expires in 28555 seconds
Hard lifetime: Expires in 28690 seconds
Anti-replay service: Disabled
Direction: outbound, SPI: 407204513, AUX-SPI: 0
Mode: tunnel, Type: dynamic, State: Installed
Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc
Soft lifetime: Expires in 28555 seconds
Hard lifetime: Expires in 28690 seconds
Anti-replay service: Disabled

```

Router 4

On Router 4, issue a **ping** command to the **so-0/0/0** interface on Router 1 to send traffic across the IPSec tunnel.

```

user@R4> ping 10.1.12.2
PING 10.1.12.2 (10.1.12.2): 56 data bytes
64 bytes from 10.1.12.2: icmp_seq=0 ttl=254 time=1.350 ms
64 bytes from 10.1.12.2: icmp_seq=1 ttl=254 time=1.161 ms
64 bytes from 10.1.12.2: icmp_seq=2 ttl=254 time=1.124 ms
64 bytes from 10.1.12.2: icmp_seq=3 ttl=254 time=1.142 ms
64 bytes from 10.1.12.2: icmp_seq=4 ttl=254 time=1.139 ms
64 bytes from 10.1.12.2: icmp_seq=5 ttl=254 time=1.116 ms
^C
--- 10.1.12.2 ping statistics ---
6 packets transmitted, 6 packets received, 0% packet loss
round-trip min/avg/max/stddev = 1.116/1.172/1.350/0.081 ms

```

Again, the **traceroute** command verifies that traffic to **10.1.12.2** travels over the IPSec tunnel between Router 3 and Router 2. Notice that the second hop does not reference **10.1.15.1**—the physical interface on Router 2. Instead, the second hop is listed as unknown with the ******* notation. This indicates that the IPSec tunnel is operating correctly.

```

user@R4> traceroute 10.1.12.2
traceroute to 10.1.12.2 (10.1.12.2), 30 hops max, 40 byte packets
 1  10.1.56.1 (10.1.56.1)  3.561 ms  0.613 ms  0.558 ms
 2  * * *
 3  10.1.12.2 (10.1.12.2)  1.073 ms  0.862 ms  0.818 ms

```

Example: AS PIC IKE Dynamic SA with Digital Certificates Configuration

Figure 8: AS PIC IKE Dynamic SA Topology Diagram




Figure 8 on page 110 shows the same IPSec topology as the AS PIC dynamic SA example on “Example: AS PIC IKE Dynamic SA Configuration” on page 90. However, this configuration requires Routers 2 and 3 to establish an IKE-based IPSec tunnel by using digital certificates in place of preshared keys. Routers 1 and 4 continue to provide basic connectivity and are used to verify that the IPSec tunnel is operational.

On Router 1, provide basic OSPF connectivity to Router 2.

```
Router 1 [edit]
interfaces {
  so-0/0/0 {
    description "To R2 so-0/0/0";
    unit 0 {
      family inet {
        address 10.1.12.2/30;
      }
    }
  }
  lo0 {
    unit 0 {
      family inet {
        address 10.0.0.1/32;
      }
    }
  }
}
routing-options {
  router-id 10.0.0.1;
}
protocols {
  ospf {
    area 0.0.0.0 {
      interface so-0/0/0;
      interface lo0.0;
    }
  }
}
```

On Router 2, you must request a CA certificate, create a local certificate, and load these digital certificates into the router before you can reference them in your IPSec

configuration. To begin, configure an IPSec profile by specifying the trusted CA and URL of the CA server that handles CA certificate processing:

```
[edit]
security {
  pki {
    ca-profile entrust {
      ca-identity entrust;
      enrollment {
        url http://ca-1.jnpr.net/cgi-bin/pkiclient.exe;
      }
    }
  }
}
```

Certificate revocation list (CRL) verification is enabled by default. You can optionally specify the Lightweight Access Directory (LDAP) server where the CA stores the CRL. The certificate typically includes a certificate distribution point (CDP), which contains information about how to retrieve the CRL for the certificate. The router uses this information to download the CRL automatically. In this example, the LDAP URL is specified, which overrides the location provided in the certificate:

```
[edit]
security pki ca-profile entrust {
  revocation-check {
    crl {
      url ldap://10.157.90.185/o=juniper,c=uscertificateRevocationListbase;
    }
  }
}
```

After you configure the CA profile, you can request a CA certificate from the trusted CA. In this example, the certificate is enrolled online and installed into the router automatically.

```
user@R2> request security pki ca-certificate enroll ca-profile entrust
Received following certificates:
Certificate: C=us, O=juniper
Fingerprint: 00:8e:6f:58:dd:68:bf:25:0a:e3:f9:17:70:d6:61:f3:53:a7:79:10
Certificate: C=us, O=juniper, CN=First Officer
Fingerprint: bc:78:87:9b:a7:91:13:20:71:db:ac:b5:56:71:42:ad:1a:b6:46:17
Certificate: C=us, O=juniper, CN=First Officer
Fingerprint: 46:71:15:34:f0:a6:41:76:65:81:33:4f:68:47:c4:df:78:b8:e3:3f
Do you want to load the above CA certificate ? [yes,no] (no) yes
```



NOTE: If you obtain the CA certificate directly from the CA (for example, as an e-mail attachment or website download), you can install it with the **request security pki ca-certificate load** command.

Next, you must generate a private/public key pair before you can create a local certificate.

```
user@R2> request security pki generate-key-pair certificate-id local-entrust2
Generated key pair local-entrust2, key size 1024 bits
```

When the key pair is available, generate a local certificate request and send it to the CA for processing.

```
user@R2> request security pki generate-certificate-request
certificate-id local-entrust2 domain-name router2.juniper.net
filename entrust-req2 subject cn=router2.juniper.net
Generated certificate request
-----BEGIN CERTIFICATE REQUEST-----
MIIBoTCCAQoCAQAwGjEYMBYGA1UEAxMPdHxLmp1bm1wZXIubmV0MIGfMA0GCSqG
SIb3DQEBAQUAA4GNADCBiQKBgQCiUFk1Qws1Ud+AqN5DDxRs2kVyKEhh9qoVFnz+
Hz4c9vSy3B8E1wTJ1kmIt2cB3yi fB6zePd+6WYpf57Crwre7YqPkixM31F6z3YjX
H+1BPNbCxNWYvyrnSyVYDbFj8o0Xyqog8ACDfVL2JBWrPNBYy7imq/K9soDBbAs6
5hZqqwIDAQABoEcwRQYJKoZIhvcNAQkOMTgwNjA0BgNVHQ8BAf8EBAMCB4AwJAYD
VR0RAQH/BBowGIIWdHxLmVuZ2xhYi5qdW5pcGVyLm51dDANBgkqhkiG9w0BAQQF
AA0BgQBc2rq1v5SOQXH7LCb/FdqAL8ZM6GoaNs5d6cGwq4bB6a7UQFgtH406gQ3G
3iH0Zfz4xMIBpJYuGd1dkqgvcDoH3AgTsLkfn7Wi3x5H2qeQVs9bvL4P5nvEZLND
EIMUHwteo1ZCiZ70f09Fer9cXWHSQs1UtXtgPqQJy2xIeImLgw==
-----END CERTIFICATE REQUEST-----
Fingerprint:
0d:90:b8:d2:56:74:fc:84:59:62:b9:78:71:9c:e4:9c:54:ba:16:97 (sha1)
1b:08:d4:f7:90:f1:c4:39:08:c9:de:76:00:86:62:b8 (md5)
```



NOTE: You can request the creation and installation of a local certificate online with the `request security pki local-certificate enroll` command. For more information, see [“Generating and Enrolling a Local Digital Certificate” on page 41](#) or the *Junos System Basics and Services Command Reference*.

The trusted CA digitally signs the local certificate and returns it to you. Copy the certificate file into the router and load the certificate.

```
user@R2> request security pki local-certificate load filename /tmp/router2-cert certificate-id
local-entrust2
Local certificate local-entrust2 loaded successfully
```



NOTE: The name of the file sent to you by the CA might not match the name of the certificate identifier. However, the certificate-id name must always match the name of the key pair you generated for the router.

After the local and CA certificates have been loaded, you can reference them in your IPSec configuration.

Using default values in the AS PIC, you do not need to configure an IPSec proposal or IPSec policy. However, you must configure an IKE proposal that specifies the use of digital certificates, reference the IKE proposal and local certificate in an IKE policy, and apply the CA profile to the service set. To enable an IKE proposal for digital certificates, include the `rsa-signatures` statement at the `[edit services ipsec-vpn ike proposal proposal-name authentication-method]` hierarchy level. To reference the local certificate in the IKE policy, include the `local-certificate` statement at the `[edit services ipsec-vpn ike policy policy-name]` hierarchy level. To identify the CA or RA in the service set, include the `trusted-ca` statement at the `[edit services service-set service-set-name ipsec-vpn-options]` hierarchy level.



NOTE: For more information about default IKE and IPSec policies and proposals on the AS PIC, see [“IKE and IPSec Proposal and Policy Default Values for the AS and MultiServices PICs” on page 26.](#)

Optionally, you can configure automatic reenrollment of the certificate with the **auto-re-enrollment** statement at the **[edit security pki]** hierarchy level.

The remaining configuration components of your IKE-based IPSec tunnel are the same as when you use preshared keys. Enable OSPF as the underlying routing protocol to connect to Routers 1 and 3. Configure a bidirectional IKE dynamic SA in a rule called **rule-ike** at the **[edit ipsec-vpn rule]** hierarchy level. Reference this rule in a service set called **service-set-dynamic-BiEspsha3des** at the **[edit services service-set]** hierarchy level.

To direct traffic into the AS PIC and the IPSec tunnel, configure a next-hop style service set and add the adaptive services logical interface used as the IPSec inside interface into the OSPF configuration.

```
Router 2 [edit]
interfaces {
  so-0/0/0 {
    description "To R1 so-0/0/0";
    unit 0 {
      family inet {
        address 10.1.12.1/30;
      }
    }
  }
  so-0/0/1 {
    description "To R3 so-0/0/1";
    unit 0 {
      family inet {
        address 10.1.15.1/30;
      }
    }
  }
  sp-1/2/0 {
    unit 0 {
      family inet;
    }
    unit 1 { # sp-1/2/0.1 is the IPSec inside interface.
      family inet;
      service-domain inside;
    }
    unit 2 { # sp-1/2/0.2 is the IPSec outside interface.
      family inet;
      service-domain outside;
    }
  }
  lo0 {
    unit 0 {
      family inet {
        address 10.0.0.2/32;
      }
    }
  }
}
```

```

    }
  }
}
routing-options {
  router-id 10.0.0.2;
}
protocols {
  ospf {
    area 0.0.0.0 {
      interface so-0/0/0.0;
      interface sp-1/2/0.1; # This sends OSPF traffic over the IPSec tunnel.
      interface lo0.0;
    }
  }
}
}
security { # Configure CA profiles here, including the URLs used to reach the CAs.
  pki {
    ca-profile entrust {
      ca-identity entrust;
      enrollment {
        url http://ca-1.jnpr.net/cgi-bin/pkiclient.exe;
      }
      revocation-check {
        crl {
          url ldap://10.157.90.185/o=juniper,c=uscertificateRevocationListbase;
          # Specify the URL of the LDAP server where the CA stores the CRL.
        }
      }
    }
    ca-profile microsoft {
      ca-identity microsoft;
      enrollment {
        url http://192.168.11.78:80/certsrv/mscep/mscep.dll;
      }
    }
    ca-profile verisign {
      ca-identity verisign;
      enrollment {
        url http://pilotonsiteipsec.verisign.com/cgi-bin/pkiclient.exe;
      }
    }
  }
}
services {
  service-set service-set-dynamic-BiEspsha3des { # Define your service set here.
    next-hop-service { # Required for dynamic routing protocols such as OSPF.
      inside-service-interface sp-1/2/0.1;
      outside-service-interface sp-1/2/0.2;
    }
    ipsec-vpn-options {
      trusted-ca entrust; # Reference the CA profile here.
      local-gateway 10.1.15.1; # Specify the local IP address of the IPSec tunnel.
    }
    ipsec-vpn-rules rule-ike; # Reference your IPSec VPN rule here.
  }
  ipsec-vpn {

```

```

rule rule-ike { # Define your IPSec VPN rule here.
  term term-ike {
    then {
      remote-gateway 10.1.15.2; # The remote IP address of the IPSec tunnel.
      dynamic { # This creates a dynamic SA.
        ike-policy ike-digital-certificates; # Reference your IKE policy here.
      }
    }
  }
  match-direction input; # Specify in which direction the rule should match.
}
ike {
  proposal ike-proposal {
    authentication-method rsa-signatures; # Uses digital certificates
  }
  policy ike-digital-certificates {
    proposals ike-proposal; # Apply the IKE proposal here.
    local-id fqdn router2.juniper.net; # Provide an identifier for the local router.
    local-certificate local-entrust2; # Reference the local certificate here.
    remote-id fqdn router3.juniper.net; # Provide an ID for the remote router.
  }
}
establish-tunnels immediately;
}
}

```

On Router 3, you must repeat the digital certificate procedures you performed on Router 2. If the IPSec peers do not have a symmetrical configuration containing all the necessary components, they cannot establish a peering relationship.

You need to request a CA certificate, create a local certificate, load these digital certificates into the router, and reference them in your IPSec configuration. Begin by configuring an IPSec CA profile. Include the **ca-profile** statement at the **[edit security pki]** hierarchy level and specify the trusted CA and URL of the CA server that handles CA certificate processing. Include the CRL statements found on Router 2 to complete your CA profile on Router 3.

After you configure the CA profile, request a CA certificate from the trusted CA. In this example, the certificate is enrolled online and installed into the router automatically.

```
user@R3> request security pki ca-certificate enroll ca-profile entrust
```

Received following certificates:

Certificate: C=us, O=juniper

Fingerprint: 00:8e:6f:58:dd:68:bf:25:0a:e3:f9:17:70:d6:61:f3:53:a7:79:10

Certificate: C=us, O=juniper, CN=First Officer

Fingerprint: bc:78:87:9b:a7:91:13:20:71:db:ac:b5:56:71:42:ad:1a:b6:46:17

Certificate: C=us, O=juniper, CN=First Officer

Fingerprint: 46:71:15:34:f0:a6:41:76:65:81:33:4f:68:47:c4:df:78:b8:e3:3f

Do you want to load the above CA certificate ? [yes,no] (no) yes



NOTE: If you obtain the CA certificate directly from the CA (for example, as an e-mail attachment or website download), you can install it with the **request security pki ca-certificate load** command.

Next, generate a private/public key pair.

```
user@R3> request security pki generate-key-pair certificate-id local-entrust3
Generated key pair local-entrust3, key size 1024 bits
```

When the key pair is available, you can generate a local certificate request and send it to the CA for processing.

```
user@R3> request security pki generate-certificate-request
certificate-id local-entrust3 domain-name router3.juniper.net
filename entrust-req3 subject cn=router3.juniper.net
Generated certificate request
-----BEGIN CERTIFICATE REQUEST-----
MIIB8jCCAVsCAQAwZTEYMBYGA1UEAxMPdHA1Lmp1bm1wZXIubmV0MRQwEgYDVQQL
EwtFbmdpbmVlcm1uZzEQMA4GA1UEChMHSnVuaXB1cjETMBEGA1UECBMKQ2FsaWZv
cm5pYTEMMAoGA1UEBhMDVVBmIGfMA0GCSqGSIb3DQEBAQUAA4GNADCBiQKBgQCg
Wjo50w8jrnphs0sRFvqQMwC6P1Ya65thrJ8nHZ2qgYgRbSr08hd0DhvU6/5VuD2/
zBtgV5ZSA01yV6DXq1bVj/2XirQAJMRCr1eYu6DhYRBMNq/UaQv4Z8Sse1EJv+uR
HTNbD7x1wpw2zwz1tRuGFtFr/FrGB0hF7IE+Xm5e2wIDAQABoE0wSwYJKoZIhvcN
AQkOMT4wPDA0BgNVHQ8BAf8EBAMCB4AwKgYDVRORAQH/BCAwHocEwKhGk4IwDHA1
LmVuZ2xhYi5qdW5pcGVyLm51dDANBgkqhkiG9w0BAQQFAA0BgQBbiJ+ZCeQ59/eY
4Rd6awIpJFTz0svRZLxxjFWogusVTmaD2dsqFBqftS1eJBdeiuRcYMF9v0n0GKm
FNfouegwei5+vzdNmNo55eIb3rs4pP62q0W5CUgmbHrjtp3lyJsvu0xTTcPNY8zw
b6GyM2Hdkk3Vh2ReX11tQUSqYujTjw==
-----END CERTIFICATE REQUEST-----
Fingerprint:
7c:e8:f9:45:93:8d:a3:92:7f:18:29:02:f1:c8:e2:85:3d:ad:df:1f (sha1)
00:4e:df:a0:6b:ad:8c:50:da:7c:a1:cf:5d:37:b0:ea (md5)
```

The trusted CA digitally signs the local certificate and returns it to you. Copy the certificate file into the router and load the certificate.

```
user@R3> request security pki local-certificate load filename /tmp/router3-cert certificate-id
local-entrust3
Local certificate local-entrust3 loaded successfully
```

After the local and CA certificates have been loaded, you can reference them in your IPSec configuration. Using default values in the AS PIC, you do not need to configure an IPSec proposal or IPSec policy. However, you must configure an IKE proposal that uses digital certificates, reference the IKE proposal and local certificate in an IKE policy, and apply the CA profile to the service set. To enable the IKE proposal for digital certificates, include the **rsa-signatures** statement at the **[edit services ipsec-vpn ike proposal proposal-name authentication-method]** hierarchy level. To reference the local certificate in the IKE policy, include the **local-certificate** statement at the **[edit services ipsec-vpn ike policy policy-name]** hierarchy level. To identify the CA or RA in the service set, include the **trusted-ca** statement at the **[edit services service-set service-set-name ipsec-vpn-options]** hierarchy level.

The remaining configuration components of your IKE-based IPSec tunnel are the same as when you use preshared keys. Enable OSPF as the underlying routing protocol to connect to Routers 2 and 4. Configure a bidirectional IKE dynamic SA in a rule called **rule-ike** at the **[edit ipsec-vpn rule]** hierarchy level. Reference this rule in a service set called **service-set-dynamic-BiEspsha3des** at the **[edit services service-set]** hierarchy level.

To direct traffic into the AS PIC and the IPSec tunnel, configure a next-hop style service set and add the adaptive services logical interface used as the IPSec inside interface into the OSPF configuration.

```

Router 3 [edit]
interfaces {
  so-0/0/0 {
    description "To R4 so-0/0/0";
    unit 0 {
      family inet {
        address 10.1.56.1/30;
      }
    }
  }
  so-0/0/1 {
    description "To R2 so-0/0/1";
    unit 0 {
      family inet {
        address 10.1.15.2/30;
      }
    }
  }
  sp-1/2/0 {
    unit 0 {
      family inet;
    }
    unit 1 { # sp-1/2/0.1 is the IPSec inside interface.
      family inet;
      service-domain inside;
    }
    unit 2 { # sp-1/2/0.2 is the IPSec outside interface.
      family inet;
      service-domain outside;
    }
  }
  lo0 {
    unit 0 {
      family inet {
        address 10.0.0.3/32;
      }
    }
  }
}
routing-options {
  router-id 10.0.0.3;
}
protocols {
  ospf {
    area 0.0.0.0 {
      interface so-0/0/0.0;
      interface sp-1/2/0.1; # This sends OSPF traffic over the IPSec tunnel.
      interface lo0.0;
    }
  }
}
security { # Configure CA profiles here, including the URLs used to reach the CAs.
  pki {
    ca-profile entrust {
      ca-identity entrust;
      enrollment {

```

```

        url http://ca-1.jnpr.net/cgi-bin/pkiclient.exe;
    }
    revocation-check {
        crl {
            url ldap://10.157.90.185/o=juniper,c=uscertificateRevocationListbase;
            # Specify the URL of the LDAP server where the CA stores the CRL.
        }
    }
}
ca-profile microsoft {
    ca-identity microsoft;
    enrollment {
        url http://192.168.11.78:80/certsrv/mscep/mscep.dll;
    }
}
ca-profile verisign {
    ca-identity verisign;
    enrollment {
        url http://pilotonsiteipsec.verisign.com/cgi-bin/pkiclient.exe;
    }
}
}
}
services {
    service-set service-set-dynamic-BiEspsha3des { # Define your service set here.
        next-hop-service { # Required for dynamic routing protocols such as OSPF.
            inside-service-interface sp-1/2/0.1;
            outside-service-interface sp-1/2/0.2;
        }
        ipsec-vpn-options {
            trusted-ca entrust; # Reference the CA profile here.
            local-gateway 10.1.15.2; # Specify the local IP address of the IPSec tunnel.
        }
        ipsec-vpn-rules rule-ike; # Reference your IPSec VPN rule here.
    }
    ipsec-vpn {
        rule rule-ike { # Define your IPSec VPN rule here.
            term term-ike {
                then {
                    remote-gateway 10.1.15.1; # The remote IP address of the IPSec tunnel.
                    dynamic { # This creates a dynamic SA.
                        ike-policy ike-digital-certificates; # Reference your IKE policy here.
                    }
                }
            }
            match-direction input; # Specify in which direction the rule should match.
        }
        ike {
            proposal ike-proposal {
                authentication-method rsa-signatures; # Uses digital certificates
            }
            policy ike-digital-certificates {
                proposals ike-proposal; # Apply the IKE proposal here.
                local-id fqdn router3.juniper.net; # Provide an identifier for the local router.
                local-certificate local-entrust3; # Reference the local certificate here.
                remote-id fqdn router2.juniper.net; # Provide an ID for the remote router.
            }
        }
    }
}

```

```

    }
  }
  establish-tunnels immediately;
}
}

```

On Router 4, provide basic OSPF connectivity to Router 3.

```

Router 4 [edit]
interfaces {
  so-0/0/0 {
    description "To R3 so-0/0/0";
    unit 0 {
      family inet {
        address 10.1.56.2/30;
      }
    }
  }
  lo0 {
    unit 0 {
      family inet {
        address 10.0.0.4/32;
      }
    }
  }
}
routing-options {
  router-id 10.0.0.4;
}
protocols {
  ospf {
    area 0.0.0.0 {
      interface so-0/0/0.0;
      interface lo0.0;
    }
  }
}

```

Verifying Your Work

To verify proper operation of an IKE-based dynamic SA on the AS PIC, use the following commands:

- **ping**
- **show services ipsec-vpn certificates (detail)**
- **show services ipsec-vpn ike security-associations (detail)**
- **show services ipsec-vpn ipsec security-associations (detail)**
- **show services ipsec-vpn ipsec statistics**
- **traceroute**

To verify and manage digital certificates in your router, use the following commands:

- **show security pki ca-certificate (detail)**
- **show security pki certificate-request (detail)**
- **show security pki local-certificate (detail)**

The following sections show the output of these commands used with the configuration example:

- [Router 1 on page 120](#)
- [Router 2 on page 120](#)
- [Router 3 on page 124](#)
- [Router 4 on page 127](#)

Router 1

On Router 1, issue a **ping** command to the **so-0/0/0** interface on Router 4 to send traffic across the IPSec tunnel.

```
user@R1> ping 10.1.56.2
PING 10.1.56.2 (10.1.56.2): 56 data bytes
64 bytes from 10.1.56.2: icmp_seq=0 ttl=254 time=1.351 ms
64 bytes from 10.1.56.2: icmp_seq=1 ttl=254 time=1.187 ms
64 bytes from 10.1.56.2: icmp_seq=2 ttl=254 time=1.172 ms
64 bytes from 10.1.56.2: icmp_seq=3 ttl=254 time=1.154 ms
64 bytes from 10.1.56.2: icmp_seq=4 ttl=254 time=1.156 ms
^C
--- 10.1.56.2 ping statistics ---
5 packets transmitted, 5 packets received, 0% packet loss
round-trip min/avg/max/stddev = 1.154/1.204/1.351/0.074 ms
```

If you ping the loopback address of Router 4, the operation succeeds because the address is part of the OSPF network configured on Router 4.

```
user@R1> ping 10.0.0.4
PING 10.0.0.4 (10.0.0.4): 56 data bytes
64 bytes from 10.0.0.4: icmp_seq=0 ttl=62 time=1.318 ms
64 bytes from 10.0.0.4: icmp_seq=1 ttl=62 time=1.084 ms
64 bytes from 10.0.0.4: icmp_seq=2 ttl=62 time=3.260 ms
^C
--- 10.0.0.4 ping statistics ---
3 packets transmitted, 3 packets received, 0% packet loss
round-trip min/avg/max/stddev = 1.084/1.887/3.260/0.975 ms
```

Router 2

To verify that matched traffic is being diverted to the bidirectional IPSec tunnel, view the IPSec statistics:

```
user@R2> show services ipsec-vpn ipsec statistics
```

```
PIC: sp-1/2/0, Service set: service-set-dynamic-BiEspsha3des
```

```
ESP Statistics:
  Encrypted bytes:      162056
  Decrypted bytes:      161896
```



```

Encrypted packets:      2215
Decrypted packets:      2216
AH Statistics:
Input bytes:            0
Output bytes:           0
Input packets:          0
Output packets:         0
Errors:
AH authentication failures: 0, Replay errors: 0
ESP authentication failures: 0, ESP decryption failures: 0
Bad headers: 0, Bad trailers: 0

```

To verify that the IKE SA negotiation is successful, issue the **show services ipsec-vpn ike security-associations** command:

```

user@R2> show services ipsec-vpn ike security-associations
Remote Address  State      Initiator cookie  Responder cookie  Exchange type
10.1.15.2       Matured    d82610c59114fd37 ec4391f76783ef28  Main

```

To verify that the IPSec security association is active, issue the **show services ipsec-vpn ipsec security-associations detail** command. Notice that the SA contains the default settings inherent in the AS PIC, such as ESP for the protocol and HMAC-SHA1-96 for the authentication algorithm.

```

user@R2> show services ipsec-vpn ipsec security-associations detail
Service set: service-set-dynamic-BiEspsha3des

Rule: rule-ike, Term: term-ike, Tunnel index: 1
Local gateway: 10.1.15.1, Remote gateway: 10.1.15.2
IPSec inside interface: sp-1/2/0.1
Local identity: ipv4_subnet(any:0,[0..7]=0.0.0.0/0)
Remote identity: ipv4_subnet(any:0,[0..7]=0.0.0.0/0)

Direction: inbound, SPI: 857451461, AUX-SPI: 0
Mode: tunnel, Type: dynamic, State: Installed
Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc
Soft lifetime: Expires in 9052 seconds
Hard lifetime: Expires in 9187 seconds
Anti-replay service: Enabled, Replay window size: 64

Direction: outbound, SPI: 1272330309, AUX-SPI: 0
Mode: tunnel, Type: dynamic, State: Installed
Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc
Soft lifetime: Expires in 9052 seconds
Hard lifetime: Expires in 9187 seconds
Anti-replay service: Enabled, Replay window size: 64

```

To display the digital certificates that are used to establish the IPSec tunnel, issue the **show services ipsec-vpn certificates** command:

```

user@R2> show services ipsec-vpn certificates
Service set: service-set-dynamic-BiEspsha3des, Total entries: 3
Certificate cache entry: 3
Flags: Non-root Trusted
Issued to: router3.juniper.net, Issued by: juniper
Alternate subject: router3.juniper.net
Validity:
Not before: 2005 Nov 21st, 23:33:58 GMT
Not after: 2008 Nov 22nd, 00:03:58 GMT

```

```

Certificate cache entry: 2

```

```

Flags: Non-root Trusted
Issued to: router2.juniper.net, Issued by: juniper
Alternate subject: router2.juniper.net
Validity:
  Not before: 2005 Nov 21st, 23:28:22 GMT
  Not after: 2008 Nov 21st, 23:58:22 GMT

```

```

Certificate cache entry: 1
Flags: Root Trusted
Issued to: juniper, Issued by: juniper
Validity:
  Not before: 2005 Oct 18th, 23:54:22 GMT
  Not after: 2025 Oct 19th, 00:24:22 GMT

```

To display the CA certificate, issue the **show security pki ca-certificate detail** command. Notice that there are three separate certificates: one for certificate signing, one for key encipherment, and one for the CA's digital signature.

```

user@R2> show security pki ca-certificate detail
Certificate identifier: entrust
Certificate version: 3
Serial number: 4355 9235
Issuer:
  Organization: juniper, Country: us
Subject:
  Organization: juniper, Country: us
Validity:
  Not before: 2005 Oct 18th, 23:54:22 GMT
  Not after: 2025 Oct 19th, 00:24:22 GMT
Public key algorithm: rsaEncryption(1024 bits)
cb:9e:2d:c0:70:f8:ea:3c:f2:b5:f0:02:48:87:dc:68:99:a3:57:4f
0e:b9:98:0b:95:47:0d:1f:97:7c:53:17:dd:1a:f8:da:e5:08:d1:1c
78:68:1f:2f:72:9f:a2:cf:81:e3:ce:c5:56:89:ce:f0:97:93:fa:36
19:3e:18:7d:8c:9d:21:fe:1f:c3:87:8d:b3:5d:f3:03:66:9d:16:a7
bf:18:3f:f0:7a:80:f0:62:50:43:83:4f:0e:d7:c6:42:48:c0:8a:b2
c7:46:30:38:df:9b:dc:bc:b5:08:7a:f3:cd:64:db:2b:71:67:fe:d8
04:47:08:07:de:17:23:13
Signature algorithm: sha1WithRSAEncryption
Fingerprint:
  00:8e:6f:58:dd:68:bf:25:0a:e3:f9:17:70:d6:61:f3:53:a7:79:10 (sha1)
  71:6f:6a:76:17:9b:d6:2a:e7:5a:72:97:82:6d:26:86 (md5)
Distribution CRL:
  C=us, O=juniper, CN=CRL1
  http://CA-1/CRL/juniper_us_crlfile.crl
Use for key: CRL signing, Certificate signing

```

```

Certificate identifier: entrust
Certificate version: 3
Serial number: 4355 925c
Issuer:
  Organization: juniper, Country: us
Subject:
  Organization: juniper, Country: us, Common name: First Officer
Validity:
  Not before: 2005 Oct 18th, 23:55:59 GMT
  Not after: 2008 Oct 19th, 00:25:59 GMT
Public key algorithm: rsaEncryption(1024 bits)
c0:a4:21:32:95:0a:cd:ec:12:03:d1:a2:89:71:8e:ce:4e:a6:f9:2f
1a:9a:13:8c:f6:a0:3d:c9:bd:9d:c2:a0:41:77:99:1b:1e:ed:5b:80
34:46:f8:5b:28:34:38:2e:91:7d:4e:ad:14:86:78:67:e7:02:1d:2e
19:11:b7:fa:0d:ba:64:20:e1:28:4e:3e:bb:6e:64:dc:cd:b1:b4:7a

```

```

ca:8f:47:dd:40:69:c2:35:95:ce:b8:85:56:d7:0f:2d:04:4d:5d:d8
42:e1:4f:6b:bf:38:c0:45:1e:9e:f0:b4:7f:74:6f:e9:70:fd:4a:78
da:eb:10:27:bd:46:34:33
Signature algorithm: sha1WithRSAEncryption
Fingerprint:
  bc:78:87:9b:a7:91:13:20:71:db:ac:b5:56:71:42:ad:1a:b6:46:17 (sha1)
  23:79:40:c9:6d:a6:f0:ca:e0:13:30:d4:29:6f:86:79 (md5)
Distribution CRL:
  C=us, O=juniper, CN=CRL1
  http://CA-1/CRL/juniper_us_crlfile.crl
Use for key: Key encipherment
Certificate identifier: entrust
Certificate version: 3
Serial number: 4355 925b
Issuer:
  Organization: juniper, Country: us
Subject:
  Organization: juniper, Country: us, Common name: First Officer
Validity:
  Not before: 2005 Oct 18th, 23:55:59 GMT
  Not after: 2008 Oct 19th, 00:25:59 GMT
Public key algorithm: rsaEncryption(1024 bits)
  ea:75:c4:f3:58:08:ea:65:5c:7e:b3:de:63:0a:cf:cf:ec:9a:82:e2
  d7:e8:b9:2f:bd:4b:cd:86:2f:f1:dd:d8:a2:95:af:ab:51:a5:49:4e
  00:10:c6:25:ff:b5:49:6a:99:64:74:69:e5:8c:23:5b:b4:70:62:8e
  e4:f9:a2:28:d4:54:e2:0b:1f:50:a2:92:cf:6c:8f:ae:10:d4:69:3c
  90:e2:1f:04:ea:ac:05:9b:3a:93:74:d0:59:24:e9:d2:9d:c2:ef:22
  b9:32:c7:2c:29:4f:91:cb:5a:26:fe:1d:c0:36:dc:f4:9c:8b:f5:26
  af:44:bf:53:aa:d4:5f:67
Signature algorithm: sha1WithRSAEncryption
Fingerprint:
  46:71:15:34:f0:a6:41:76:65:81:33:4f:68:47:c4:df:78:b8:e3:3f (sha1)
  ee:cc:c7:f4:5d:ac:65:33:0a:55:db:59:72:2c:dd:16 (md5)
Distribution CRL:
  C=us, O=juniper, CN=CRL1
  http://CA-1/CRL/juniper_us_crlfile.crl
Use for key: Digital signature

```

To display the local certificate request, issue the **show security pki certificate-request** command:

```

user@R2> show security pki certificate-request
Certificate identifier: local-entrust2
Issued to: router2.juniper.net
Public key algorithm: rsaEncryption(1024 bits)
Public key verification status: Passed

```

To display the local certificate, issue the **show security pki local-certificate** command:

```

user@R2> show security pki local-certificate
Certificate identifier: local-entrust2
Issued to: router2.juniper.net, Issued by: juniper
Validity:
  Not before: 2005 Nov 21st, 23:28:22 GMT
  Not after: 2008 Nov 21st, 23:58:22 GMT
Public key algorithm: rsaEncryption(1024 bits)
Public key verification status: Passed

```

Router 3

To verify that matched traffic is being diverted to the bidirectional IPSec tunnel, view the IPSec statistics:

```
user@R3> show services ipsec-vpn ipsec statistics
```

```
PIC: sp-1/2/0, Service set: service-set-dynamic-BiEspsha3des
```

```
ESP Statistics:
```

```
  Encrypted bytes:      161896
  Decrypted bytes:      162056
  Encrypted packets:    2216
  Decrypted packets:    2215
```

```
AH Statistics:
```

```
  Input bytes:          0
  Output bytes:         0
  Input packets:        0
  Output packets:       0
```

```
Errors:
```

```
  AH authentication failures: 0, Replay errors: 0
  ESP authentication failures: 0, ESP decryption failures: 0
  Bad headers: 0, Bad trailers: 0
```

To verify that the IKE SA negotiation is successful, issue the **show services ipsec-vpn ike security-associations** command. To be successful, the SA on Router 3 must contain the same settings you specified on Router 2.

```
user@R3> show services ipsec-vpn ike security-associations
```

```
Remote Address  State      Initiator cookie  Responder cookie  Exchange type
10.1.15.1       Matured           d82610c59114fd37 ec4391f76783ef28  Main
```

To verify that the IPSec SA is active, issue the **show services ipsec-vpn ipsec security-associations detail** command. To be successful, the SA on Router 3 must contain the same settings you specified on Router 2.

```
user@R3> show services ipsec-vpn ipsec security-associations detail
```

```
Service set: service-set-dynamic-BiEspsha3des
```

```
Rule: rule-ike, Term: term-ike, Tunnel index: 1
Local gateway: 10.1.15.2, Remote gateway: 10.1.15.1
IPSec inside interface: sp-1/2/0.1
Local identity: ipv4_subnet(any:0,[0..7]=0.0.0.0/0)
Remote identity: ipv4_subnet(any:0,[0..7]=0.0.0.0/0)
```

```
Direction: inbound, SPI: 1272330309, AUX-SPI: 0
Mode: tunnel, Type: dynamic, State: Installed
Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc
Soft lifetime: Expires in 7219 seconds
Hard lifetime: Expires in 7309 seconds
Anti-replay service: Enabled, Replay window size: 64
```

```
Direction: outbound, SPI: 857451461, AUX-SPI: 0
Mode: tunnel, Type: dynamic, State: Installed
Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc
Soft lifetime: Expires in 7219 seconds
Hard lifetime: Expires in 7309 seconds
Anti-replay service: Enabled, Replay window size: 64
```

To display the digital certificates that are used to establish the IPSec tunnel, issue the **show services ipsec-vpn certificates** command:

```
user@R3> show services ipsec-vpn certificates
Service set: service-set-dynamic-BiEspsha3des, Total entries: 3
Certificate cache entry: 3
  Flags: Non-root Trusted
  Issued to: router3.juniper.net, Issued by: juniper
  Alternate subject: router3.juniper.net
  Validity:
    Not before: 2005 Nov 21st, 23:33:58 GMT
    Not after: 2008 Nov 22nd, 00:03:58 GMT

Certificate cache entry: 2
  Flags: Non-root Trusted
  Issued to: router2.juniper.net, Issued by: juniper
  Alternate subject: router2.juniper.net
  Validity:
    Not before: 2005 Nov 21st, 23:28:22 GMT
    Not after: 2008 Nov 21st, 23:58:22 GMT

Certificate cache entry: 1
  Flags: Root Trusted
  Issued to: juniper, Issued by: juniper
  Validity:
    Not before: 2005 Oct 18th, 23:54:22 GMT
    Not after: 2025 Oct 19th, 00:24:22 GMT
```

To display the CA certificate, issue the **show security pki ca-certificate detail** command. Notice that there are three separate certificates: one for certificate signing, one for key encipherment, and one for the CA's digital signature.

```
user@R3> show security pki ca-certificate detail
Certificate identifier: entrust
Certificate version: 3
Serial number: 4355 9235
Issuer:
  Organization: juniper, Country: us
Subject:
  Organization: juniper, Country: us
Validity:
  Not before: 2005 Oct 18th, 23:54:22 GMT
  Not after: 2025 Oct 19th, 00:24:22 GMT
Public key algorithm: rsaEncryption(1024 bits)
cb:9e:2d:c0:70:f8:ea:3c:f2:b5:f0:02:48:87:dc:68:99:a3:57:4f
0e:b9:98:0b:95:47:0d:1f:97:7c:53:17:dd:1a:f8:da:e5:08:d1:1c
78:68:1f:2f:72:9f:a2:cf:81:e3:ce:c5:56:89:ce:f0:97:93:fa:36
19:3e:18:7d:8c:9d:21:fe:1f:c3:87:8d:b3:5d:f3:03:66:9d:16:a7
bf:18:3f:f0:7a:80:f0:62:50:43:83:4f:0e:d7:c6:42:48:c0:8a:b2
c7:46:30:38:df:9b:dc:bc:b5:08:7a:f3:cd:64:db:2b:71:67:fe:d8
04:47:08:07:de:17:23:13
Signature algorithm: sha1WithRSAEncryption
Fingerprint:
  00:8e:6f:58:dd:68:bf:25:0a:e3:f9:17:70:d6:61:f3:53:a7:79:10 (sha1)
  71:6f:6a:76:17:9b:d6:2a:e7:5a:72:97:82:6d:26:86 (md5)
Distribution CRL:
  C=us, O=juniper, CN=CRL1
  http://CA-1/CRL/juniper_us_crlfile.crl
Use for key: CRL signing, Certificate signing
Certificate identifier: entrust
Certificate version: 3
```

```

Serial number: 4355 925c
Issuer:
  Organization: juniper, Country: us
Subject:
  Organization: juniper, Country: us, Common name: First Officer
Validity:
  Not before: 2005 Oct 18th, 23:55:59 GMT
  Not after: 2008 Oct 19th, 00:25:59 GMT
Public key algorithm: rsaEncryption(1024 bits)
c0:a4:21:32:95:0a:cd:ec:12:03:d1:a2:89:71:8e:ce:4e:a6:f9:2f
1a:9a:13:8c:f6:a0:3d:c9:bd:9d:c2:a0:41:77:99:1b:1e:ed:5b:80
34:46:f8:5b:28:34:38:2e:91:7d:4e:ad:14:86:78:67:e7:02:1d:2e
19:11:b7:fa:0d:ba:64:20:e1:28:4e:3e:bb:6e:64:dc:cd:b1:b4:7a
ca:8f:47:dd:40:69:c2:35:95:ce:b8:85:56:d7:0f:2d:04:4d:5d:d8
42:e1:4f:6b:bf:38:c0:45:1e:9e:f0:b4:7f:74:6f:e9:70:fd:4a:78
da:eb:10:27:bd:46:34:33
Signature algorithm: sha1WithRSAEncryption
Fingerprint:
  bc:78:87:9b:a7:91:13:20:71:db:ac:b5:56:71:42:ad:1a:b6:46:17 (sha1)
  23:79:40:c9:6d:a6:f0:ca:e0:13:30:d4:29:6f:86:79 (md5)
Distribution CRL:
  C=us, O=juniper, CN=CRL1
  http://CA-1/CRL/juniper_us_crlfile.crl
Use for key: Key encipherment
Certificate identifier: entrust
Certificate version: 3
Serial number: 4355 925b
Issuer:
  Organization: juniper, Country: us
Subject:
  Organization: juniper, Country: us, Common name: First Officer
Validity:
  Not before: 2005 Oct 18th, 23:55:59 GMT
  Not after: 2008 Oct 19th, 00:25:59 GMT
Public key algorithm: rsaEncryption(1024 bits)
ea:75:c4:f3:58:08:ea:65:5c:7e:b3:de:63:0a:cf:cf:ec:9a:82:e2
d7:e8:b9:2f:bd:4b:cd:86:2f:f1:dd:d8:a2:95:af:ab:51:a5:49:4e
00:10:c6:25:ff:b5:49:6a:99:64:74:69:e5:8c:23:5b:b4:70:62:8e
e4:f9:a2:28:d4:54:e2:0b:1f:50:a2:92:cf:6c:8f:ae:10:d4:69:3c
90:e2:1f:04:ea:ac:05:9b:3a:93:74:d0:59:24:e9:d2:9d:c2:ef:22
b9:32:c7:2c:29:4f:91:cb:5a:26:fe:1d:c0:36:dc:f4:9c:8b:f5:26
af:44:bf:53:aa:d4:5f:67
Signature algorithm: sha1WithRSAEncryption
Fingerprint:
  46:71:15:34:f0:a6:41:76:65:81:33:4f:68:47:c4:df:78:b8:e3:3f (sha1)
  ee:cc:c7:f4:5d:ac:65:33:0a:55:db:59:72:2c:dd:16 (md5)
Distribution CRL:
  C=us, O=juniper, CN=CRL1
  http://CA-1/CRL/juniper_us_crlfile.crl
Use for key: Digital signature

```

To display the local certificate request, issue the **show security pki certificate-request** command:

```

user@R3> show security pki certificate-request
Certificate identifier: local-entrust3
Issued to: router3.juniper.net
Public key algorithm: rsaEncryption(1024 bits)
Public key verification status: Passed

```

To display the local certificate, issue the **show security pki local-certificate** command:

```
user@R3> show security pki local-certificate
Certificate identifier: local-entrust3
Issued to: router3.juniper.net, Issued by: juniper
Validity:
  Not before: 2005 Nov 21st, 23:33:58 GMT
  Not after: 2008 Nov 22nd, 00:03:58 GMT
Public key algorithm: rsaEncryption(1024 bits)
Public key verification status: Passed
```

Router 4

On Router 4, issue a **ping** command to the **so-0/0/0** interface on Router 1 to send traffic across the IPSec tunnel.

```
user@R4> ping 10.1.12.2
PING 10.1.12.2 (10.1.12.2): 56 data bytes
64 bytes from 10.1.12.2: icmp_seq=0 ttl=254 time=1.350 ms
64 bytes from 10.1.12.2: icmp_seq=1 ttl=254 time=1.161 ms
64 bytes from 10.1.12.2: icmp_seq=2 ttl=254 time=1.124 ms
64 bytes from 10.1.12.2: icmp_seq=5 ttl=254 time=1.116 ms
^C
--- 10.1.12.2 ping statistics ---
4 packets transmitted, 4 packets received, 0% packet loss
round-trip min/avg/max/stddev = 1.116/1.172/1.350/0.081 ms
```

The final way you can confirm that traffic travels over the IPSec tunnel is by issuing the **traceroute** command to the **so-0/0/0** interface on Router 1. Notice that the physical interface between Routers 2 and 3 is not referenced in the path; traffic enters the IPSec tunnel through the adaptive services IPSec inside interface on Router 3, passes through the loopback interface on Router 2, and ends at the **so-0/0/0** interface on Router 1.

```
user@R4> traceroute 10.1.12.2
traceroute to 10.1.12.2 (10.1.12.2), 30 hops max, 40 byte packets
 1  10.1.15.2 (10.1.15.2)  0.987 ms  0.630 ms  0.563 ms
 2  10.0.0.2 (10.0.0.2)  1.194 ms  1.058 ms  1.033 ms
 3  10.1.12.2 (10.1.12.2)  1.073 ms  0.949 ms  0.932 ms
```

For additional information on using digital certificates, see the *Junos Services Interfaces Configuration Guide* and the *Junos System Basics and Services Command Reference*.

Example: Dynamic Endpoint Tunneling Configuration

Figure 9: IPSec Dynamic Endpoint Tunneling Topology Diagram




Figure 9 on page 127 shows a local network N-1 located behind security gateway SG-1. SG-1 is a Juniper Networks router terminating dynamic peer endpoints. The tunnel termination address on SG-1 is 10.7.7.2 and the local network address is 172.16.1.0/24.

A remote peer router obtains addresses from an ISP pool and runs RFC-compliant IKE. Remote network N-2 has address 172.16.2.0/24 and is located behind security gateway SG-2 with tunnel termination address 10.7.7.1.

On Router SG-1, configure an IKE access profile to accept proposals from SG-2. Apply the interface identifier from the access profile to the inside services interface and apply the IKE access profile itself to the IPSec next-hop style service set.

```
Router SG-1 [edit]
access {
  profile ike_access {
    client * { # Accepts proposals from specified peers that use the preshared key.
      ike {
        allowed-proxy-pair local 10.255.14.63/32 remote 10.255.14.64/32;
        pre-shared-key ascii-text "$9$1hoESeLxdgoGvWoGDif5IEc"; # SECRET-DATA
        interface-id test_id; # Apply this ID to the inside services interfaces.
      }
    }
  }
}
interfaces {
  fe-0/0/0 {
    description "Connection to the local network";
    unit 0 {
      family inet {
        address 172.16.1.1/24;
      }
    }
  }
  so-1/0/0 {
    description "Connection to SG-2";
    no-keepalives;
    encapsulation cisco-hdlc;
    unit 0 {
      family inet {
        address 10.7.7.2/30;
      }
    }
  }
  sp-3/3/0 {
    unit 0 {
      family inet;
    }
    unit 3 {
      dial-options {
        ipsec-interface-id test_id; # Accepts dynamic endpoint tunnels.
        shared;
      }
      service-domain inside;
    }
    unit 4 {
```



```

        family inet;
        service-domain outside;
    }
}
services {
    service-set dynamic_nh_ss { # Create a next-hop service set
        next-hop-service { # for the dynamic endpoint tunnels.
            inside-service-interface sp-3/3/0.3;
            outside-service-interface sp-3/3/0.4;
        }
        ipsec-vpn-options {
            local-gateway 10.7.7.2;
            ike-access-profile ike_access; # Apply the IKE access profile here.
        }
    }
}
}

```

Verifying Your Work

To verify proper operation of a dynamic endpoint tunnel configured on the AS PIC, use the following command:

```
show services ipsec-vpn ipsec security-associations (detail)
```

The following section shows output from this command used with the configuration example. The dynamically created rule `_junos_` appears in the output, as well as the establishment of the inbound and outbound dynamically created tunnels.

```
user@router> show services ipsec-vpn ipsec security-associations detail
Service set: dynamic_nh_ss
```

```

Rule: _junos_ , Term: tunnel4, Tunnel index: 4
Local gateway: 10.7.7.2, Remote gateway: 10.7.7.1
Local identity: ipv4(any:0,[0..3]=10.255.14.63)
Remote identity: ipv4(any:0,[0..3]=10.255.14.64)

```

```

Direction: inbound , SPI: 428111023, AUX-SPI: 0
  Mode: tunnel, Type: dynamic, State: Installed
  Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc
  Soft lifetime: Expires in 27660 seconds
  Hard lifetime: Expires in 27750 seconds
  Anti-replay service: Enabled, Replay window size: 64

```

```

Direction: outbound , SPI: 4035429231, AUX-SPI: 0
  Mode: tunnel, Type: dynamic, State: Installed
  Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc
  Soft lifetime: Expires in 27660 seconds
  Hard lifetime: Expires in 27750 seconds
  Anti-replay service: Enabled, Replay window size: 64

```


PART 4

Administration

- [IPSec Commands on page 133](#)

CHAPTER 9

IPSec Commands

- clear security pki ca-certificate
- clear security pki certificate-request
- clear security pki crl
- clear security pki local-certificate
- request security certificate (signed)
- request security certificate (unsigned)
- request security key-pair
- request security pki ca-certificate enroll
- request security pki ca-certificate load
- request security pki generate-certificate-request
- request security pki generate-key-pair
- request security pki local-certificate enroll
- request security pki local-certificate load
- request system certificate add
- show ike security-associations
- show ipsec certificates
- show security pki ca-certificate
- show ipsec security-associations
- show security pki certificate-request
- show security pki crl
- show security pki local-certificate
- show services ipsec-vpn certificates
- show services ipsec-vpn ike security-associations
- show services ipsec-vpn ipsec security-associations
- show system certificate

clear security pki ca-certificate

Syntax	clear security pki ca-certificate (all ca-profile <i>ca-profile-name</i>)
Release Information	Command introduced in Junos OS Release 7.5.
Description	Delete certificate authority (CA) digital certificates from the router.
Options	all —Delete all CA digital certificates from the router. ca-profile <i>ca-profile-name</i> —Delete the specified CA profile.
Required Privilege Level	clear
Related Documentation	<ul style="list-style-type: none">• request security pki ca-certificate enroll on page 142• request security pki ca-certificate load on page 143• show security pki ca-certificate on page 158
List of Sample Output	clear security pki ca-certificate all on page 134
Output Fields	When you enter this command, you are provided feedback on the status of your request.

Sample Output

clear security pki ca-certificate all

```
user@host> clear security pki ca-certificate all
```

clear security pki certificate-request

Syntax	clear security pki certificate-request (all certificate-id <i>certificate-id-name</i>)
Release Information	Command introduced in Junos OS Release 7.5.
Description	Delete manually generated local digital certificate requests from the router.
Options	<p>all—Delete all local digital certificate requests from the router.</p> <p>certificate-id <i>certificate-id-name</i>—Delete the specified local digital certificate and corresponding public/private key pair.</p>
Required Privilege Level	clear
Related Documentation	<ul style="list-style-type: none">• show security pki certificate-request on page 165
List of Sample Output	clear security pki certificate-request all on page 135
Output Fields	When you enter this command, you are provided feedback on the status of your request.

Sample Output

clear security pki certificate-request all

```
user@host> clear security pki certificate-request all
```

clear security pki crt

Syntax	clear security pki crt (all ca-profile <i>ca-profile-name</i>)
Release Information	Command introduced in Junos 8.1
Description	Delete certificate revocation lists (CRLs) from the router.
Options	all —Delete all CRLs from the router. ca-profile <i>ca-profile-name</i> —Delete CRLs associated with the specified CA profile.
Required Privilege Level	clear
List of Sample Output	clear security pki crt ca-profile all on page 136
Output Fields	When you enter this command, you are provided feedback on the status of your request.

Sample Output

clear security pki crt ca-profile all

```
user@host> clear security pki crt ca-profile all
```


clear security pki local-certificate

Syntax	clear security pki local-certificate <all certificate-id <i>certificate-id-name</i> system-generated>
Release Information	Command introduced in Junos OS Release 7.5.
Description	Delete local digital certificates, certificate requests, and the corresponding public/private key pairs from the router.
Options	<p>all—(Optional) Delete all local digital certificates, certificate requests, and the corresponding public and private key pairs from the router.</p> <p>certificate-id <i>certificate-id-name</i>—(Optional) Delete the specified local digital certificate and corresponding public and private key pair.</p> <p>system-generated—(Optional) Auto-generated self-signed certificate.</p>
Required Privilege Level	clear
Related Documentation	<ul style="list-style-type: none"> • request security pki local-certificate enroll on page 147 • show security pki local-certificate on page 169
List of Sample Output	clear security pki local-certificate all on page 137
Output Fields	This command produces no output.

Sample Output

clear security pki local-certificate all

```
user@host> clear security pki local-certificate all
```

request security certificate (signed)

Syntax	<code>request security certificate enroll filename <i>filename</i> subject <i>subject</i> alternative-subject <i>alternative-subject</i> certification-authority <i>certification-authority</i> encoding (binary pem) key-file <i>key-file</i> domain-name <i>domain-name</i></code>
Release Information	Command introduced before Junos OS Release 7.4. Command introduced in Junos OS Release 9.0 for EX Series switches.
Description	(Encryption interface on M Series and T Series routers and EX Series switches only) Obtain a signed certificate from a certificate authority (CA). The signed certificate validates the CA and the owner of the certificate. The results are saved in a specified file to the <code>/var/etc/ikecert</code> directory.
Options	<p>filename <i>filename</i>—File that stores the certificate.</p> <p>subject <i>subject</i>—Distinguished name (dn), which consists of a set of components—for example, an organization (o), an organization unit (ou), a country (c), and a locality (l).</p> <p>alternative-subject <i>alternative-subject</i>—Tunnel source address.</p> <p>certification-authority <i>certification-authority</i>—Name of the certificate authority profile in the configuration.</p> <p>encoding (binary pem)—File format used for the certificate. The format can be a binary file or privacy-enhanced mail (PEM), an ASCII base64-encoded format. The default format is binary.</p> <p>key-file <i>key-file</i>—File containing a local private key.</p> <p>domain-name <i>domain-name</i>—Fully qualified domain name.</p>
Required Privilege Level	maintenance
List of Sample Output	request security certificate (signed) on page 138
Output Fields	When you enter this command, you are provided feedback on the status of your request.

Sample Output

request security certificate (signed)

```

user@host> request security certificate enroll filename host.crt subject c=uk,o=london
alternative-subject 10.50.1.4 certification-authority verisign key-file host-1.prv domain-name
host.juniper.net
CA name: juniper.net CA file: ca_verisign
local pub/private key pair: host.prv
subject: c=uk,o=london domain name: host.juniper.net
alternative subject: 10.50.1.4
Encoding: binary
Certificate enrollment has started. To view the status of your enrollment, check
the key management process (kmd) log file at /var/log/kmd. <-----

```


request security certificate (unsigned)

Syntax	<code>request security certificate enroll filename <i>filename</i> ca-file <i>ca-file</i> ca-name <i>ca-name</i> encoding (binary perm) url <i>url</i></code>
Release Information	Command introduced before Junos OS Release 7.4. Command introduced in Junos OS Release 9.0 for EX Series switches.
Description	(Encryption interface on M Series and T Series routers and EX Series switches only) Obtain a certificate from a certificate authority (CA). The results are saved in a specified file to the <code>/var/etc/ikecert</code> directory.
Options	<p>filename <i>filename</i>—File that stores the public key certificate.</p> <p>ca-file <i>ca-file</i>—Name of the certificate authority profile in the configuration.</p> <p>ca-name <i>ca-name</i>—Name of the certificate authority.</p> <p>encoding (binary pem)—File format used for the certificate. The format can be a binary file or privacy-enhanced mail (PEM), an ASCII base64-encoded format. The default value is binary.</p> <p>url <i>url</i>—Certificate authority URL.</p>
Required Privilege Level	maintenance
List of Sample Output	request security certificate (unsigned) on page 140
Output Fields	When you enter this command, you are provided feedback on the status of your request.

Sample Output

request security certificate (unsigned)

```
user@host> request security certificate enroll filename ca_verisign ca-file verisign ca-name
juniper.net urlxyzcompany URL
http://<verisign ca-name xyzcompany url>/cgi-bin/pkiclient.exe CA name: juniper.net
CA file: verisign Encoding: binary
Certificate enrollment has started. To view the status of your enrollment, check
the key management process (kmd) log file at /var/log/kmd. <-----
```

request security key-pair

Syntax	<code>request security key-pair <i>filename</i></code> <code><size <i>key-size</i>></code> <code><type (rsa dsa)></code>
Release Information	Command introduced before Junos OS Release 7.4. Command introduced in Junos OS Release 9.0 for EX Series switches.
Description	(Encryption interface on M Series and T Series routers and EX Series switches only) Generate a public and private key pair for a digital certificate.
Options	<i>filename</i> —Name of a file in which to store the key pair. <i>size key-size</i> —(Optional) Key size, in bits. The key size can be 512 , 1024 , or 2048 . The default value is 1024 . <i>type</i> —(Optional) Algorithm used to encrypt the key: <ul style="list-style-type: none"> • rsa—RSA algorithm. This is the default. • dsa—Digital signature algorithm with Secure Hash Algorithm (SHA).
Required Privilege Level	maintenance
List of Sample Output	request security key-pair on page 141
Output Fields	When you enter this command, you are provided feedback on the status of your request.

Sample Output

request security key-pair

```
user@host> request security key-pair security-key-file
```

request security pki ca-certificate enroll

Syntax	<code>request security pki ca-certificate enroll ca-profile <i>ca-profile-name</i></code>
Release Information	Command introduced in Junos OS Release 7.5.
Description	Request a digital certificate from a certificate authority (CA) online by using the Simple Certificate Enrollment Protocol (SCEP).
Options	<code>ca-profile <i>ca-profile-name</i></code> —CA profile name.
Required Privilege Level	maintenance
Related Documentation	<ul style="list-style-type: none">• clear security pki ca-certificate on page 134• show security pki ca-certificate on page 158
List of Sample Output	request security pki ca-certificate enroll on page 142
Output Fields	When you enter this command, you are provided feedback on the status of your request.

Sample Output

request security pki ca-certificate enroll

```
user@host> request security pki ca-certificate enroll ca-profile entrust
Received following certificates:
Certificate: C=us, O=juniper, CN=First Officer
Fingerprint: 46:71:15:34:f0:a6:41:76:65:81:33:4f:68:47:c4:df:78:b8:e3:3f
Certificate: C=us, O=juniper, CN=First Officer
Fingerprint: bc:78:87:9b:a7:91:13:20:71:db:ac:b5:56:71:42:ad:1a:b6:46:17
Certificate: C=us, O=juniper
Fingerprint: 00:8e:6f:58:dd:68:bf:25:0a:e3:f9:17:70:d6:61:f3:53:a7:79:10
Do you want to load the above CA certificate ? [yes,no] (no) yes
```

request security pki ca-certificate load

Syntax	<code>request security pki ca-certificate load ca-profile <i>ca-profile-name</i> filename <i>path/filename</i></code>
Release Information	Command introduced in Junos OS Release 7.5.
Description	Manually load a certificate authority (CA) digital certificate from a specified location.
Options	<p>ca-profile <i>ca-profile-name</i>—Load the specified CA profile.</p> <p>filename <i>path/filename</i>—Directory location and filename of the CA digital certificate.</p>
Required Privilege Level	maintenance
Related Documentation	<ul style="list-style-type: none"> • clear security pki ca-certificate on page 134 • show security pki ca-certificate on page 158
List of Sample Output	request security pki ca-certificate load on page 143
Output Fields	When you enter this command, you are provided feedback on the status of your request.

Sample Output

request security pki ca-certificate load

```
user@host> request security pki ca-certificate load ca-profile ca-private filename pki-file
```

request security pki generate-certificate-request

Syntax	<code>request security pki generate-certificate-request certificate-id <i>certificate-id-name</i> domain-name <i>domain-name</i> subject <i>subject-distinguished-name</i> <email <i>email-address</i>> <filename (<i>path</i> <i>terminal</i>)> <ip-address <i>ip-address</i>></code>
Release Information	Command introduced in Junos OS Release 7.5.
Description	Manually generate a local digital certificate request in the Public-Key Cryptography Standards #10 (PKCS-10) format.
Options	<p>certificate-id <i>certificate-id-name</i>—Name of the local digital certificate and the public/private key pair.</p> <p>domain-name <i>domain-name</i>—Fully qualified domain name (FQDN). The FQDN provides the identity of the certificate owner for Internet Key Exchange (IKE) negotiations and provides an alternative to the subject name.</p> <p>subject <i>subject-distinguished-name</i>—Distinguished name format that contains the common name, department, company name, state, and country:</p> <ul style="list-style-type: none">• CN—Common name• OU—Organizational unit name• O—Organization name• ST—State• C—Country <p>email <i>email-address</i>—(Optional) E-mail address of the certificate holder.</p> <p>filename (<i>path</i> <i>terminal</i>)—(Optional) Location where the local digital certificate request should be placed or the login terminal.</p> <p>ip-address <i>ip-address</i>—(Optional) IP address of the router.</p>
Required Privilege Level	maintenance
Related Documentation	<ul style="list-style-type: none">• clear security pki certificate-request on page 135• show security pki certificate-request on page 165
List of Sample Output	request security pki generate-certificate-request on page 145
Output Fields	When you enter this command, you are provided feedback on the status of your request.

Sample Output

request security pki generate-certificate-request

```
user@host> request security pki generate-certificate-request certificate-id local-entrust2
domain-name router2.juniper.net filename entrust-req2 subject cn=router2.juniper.net
```

Generated certificate request

-----BEGIN CERTIFICATE REQUEST-----

```
MIIBOTCCAQoCAQAwGjEYMBYGA1UEAxMPdHxLmp1bm1wZXIubmV0MIGfMA0GCSqG
SIb3DQEBAQUAA4GNADCBiQKBgQCiuFk1Qws1Ud+AqN5DDxRs2kVyKEhh9qoVFnz+
Hz4c9vsy3B8E1wTJ1kmIt2cB3yi fB6zePd+6WYpf57Crwre7YqPkiXM31F6z3YjX
H+1BPNbCxNWYvyrnSyVYDbFj8o0Xyqog8ACDFVL2JBWrPNBYy7imq/K9soDBbAs6
5hZqqwIDAQABoEcwRQYJKoZIhvcNAQkOMTgwNjA0BGNVHQ8BAf8EBAMCB4AwJAYD
VR0RAQH/BBowGIIWdHxLmVuZ2xhYi5qdW5pcGVyLm5ldDANBgkqhkiG9w0BAQQF
AAOBgQBc2rq1v5S0QXH7LCb/FdqAL8ZM6GoaN5d6cGwq4bB6a7UQFgtH406gQ3G
3iH0Zfz4xMIBpJYuGd1dkqgvcDoH3AgTsLkfn7Wi3x5H2qeQVs9bvL4P5nvEZLND
EIMUHwteo1ZCiZ70f09Fer9cXWHSQs1UtXtgPqQJy2xIeImLgw==
```

-----END CERTIFICATE REQUEST-----

Fingerprint:

```
0d:90:b8:d2:56:74:fc:84:59:62:b9:78:71:9c:e4:9c:54:ba:16:97 (sha1)
1b:08:d4:f7:90:f1:c4:39:08:c9:de:76:00:86:62:b8 (md5)
```

request security pki generate-key-pair

Syntax	<code>request security pki generate-key-pair certificate-id <i>certificate-id-name</i> <size (512 1024 2048)></code>
Release Information	Command introduced in Junos OS Release 7.5.
Description	Generate a Public Key Infrastructure (PKI) public and private key pair for a local digital certificate.
Options	certificate-id <i>certificate-id-name</i> —Name of the local digital certificate and the public/private key pair. size —(Optional) Key pair size. The key pair size can be 512 , 1024 , or 2048 bits.
Required Privilege Level	maintenance
List of Sample Output	request security pki generate-key-pair on page 146
Output Fields	When you enter this command, you are provided feedback on the status of your request.

Sample Output

request security pki generate-key-pair

```
user@host> request security pki generate-key-pair certificate-id billy size 2048
Generated key pair billy, key size 2048 bits
```

request security pki local-certificate enroll

Syntax	request security pki local-certificate enroll <i>ca-profile ca-profile-name</i> <i>certificate-id certificate-id-name</i> challenge-password <i>password</i> domain-name <i>domain-name</i> subject <i>subject-distinguished-name</i> <email <i>email-address</i> > <ip-address <i>ip-address</i> >
Release Information	Command introduced in Junos OS Release 7.5.
Description	Request that a certificate authority (CA) enroll and install a local digital certificate online by using the Simple Certificate Enrollment Protocol (SCEP).
Options	<p>ca-profile <i>ca-profile-name</i>—CA profile name.</p> <p>certificate-id <i>certificate-id-name</i>—Name of the local digital certificate and the public/private key pair.</p> <p>challenge-password <i>password</i>—Password set by the administrator and normally obtained from the SCEP enrollment webpage of the CA. The password is 16 characters in length.</p> <p>domain-name <i>domain-name</i>—Fully qualified domain name (FQDN). The FQDN provides the identity of the certificate owner for Internet Key Exchange (IKE) negotiations and provides an alternative to the subject name.</p> <p>subject <i>subject-distinguished-name</i>—Distinguished name format that contains the common name, department, company name, state, and country:</p> <ul style="list-style-type: none"> • CN—Common name • OU—Organizational unit name • O—Organization name • ST—State • C—Country <p>email <i>email-address</i>—(Optional) E-mail address of the certificate holder.</p> <p>ip-address <i>ip-address</i>—(Optional) IP address of the router.</p>
Required Privilege Level	maintenance
Related Documentation	<ul style="list-style-type: none"> • show security pki local-certificate on page 169
Output Fields	When you enter this command, you are provided feedback on the status of your request.

Sample Output

```
user@host> request security pki local-certificate enroll certificate-id r3-entrust-scep ca-profile  
entrust domain-name router3.juniper.net subject "CN=router3,OU=Engineering,O=juniper,C=US"  
challenge-password 123
```

Certificate enrollment has started. To view the status of your enrollment, check the public key infrastructure log (pkid) log file at /var/log/pkid. Please save the challenge-password for revoking this certificate in future. Note that this password is not stored on the router.

request security pki local-certificate load

Syntax	<code>request security pki local-certificate load certificate-id <i>certificate-id-name</i> filename <i>path</i></code>
Release Information	Command introduced in Junos OS Release 7.5.
Description	Manually load a local digital certificate from a specified location.
Options	<p>certificate-id <i>certificate-id-name</i>—Name of the public/private key pair mapped to the local digital certificate.</p> <p>filename <i>path/filename</i>—Directory location and filename of the local digital certificate provided by the CA.</p>
Required Privilege Level	maintenance
List of Sample Output	request security pki local-certificate load on page 149
Output Fields	When you enter this command, you are provided feedback on the status of your request.

Sample Output

request security pki local-certificate load

```
user@host> request security pki local-certificate load filename /tmp/router2-cert certificate-id
local-entrust2
Local certificate local-entrust2 loaded successfully
```

request system certificate add

Syntax	<code>request system certificate add (<i>filename</i> terminal)</code>
Release Information	Command introduced before Junos OS Release 7.4. Command introduced in Junos OS Release 11.1 for the QFX Series.
Description	(Encryption interface on M Series and T Series routers, PTX Series, and QFX Series switches only) Add a certificate provided by the Juniper Networks certificate authority (CA).
Options	<i>filename</i> —Filename (URL, local, or remote). <i>terminal</i> —Use login terminal.
Required Privilege Level	maintenance
List of Sample Output	request system certificate add on page 150
Output Fields	When you enter this command, you are provided feedback on the status of your request.

Sample Output

request system certificate add

```
user@host> request system certificate add terminal
```

show ike security-associations

Syntax	show ike security-associations <brief detail> <peer-address>
Release Information	Command introduced before Junos OS Release 7.4.
Description	(Encryption interface on M Series and T Series routers only) Display information about Internet Key Exchange (IKE) security associations.
Options	<p>none—Display standard information about all IKE security associations.</p> <p>brief detail—(Optional) Display the specified level of output.</p> <p>peer-address—(Optional) Display IKE security associations for the specified peer address.</p>
Required Privilege Level	view
Related Documentation	<ul style="list-style-type: none"> • clear ike security-associations
List of Sample Output	show ike security-associations on page 154 show ike security-associations detail on page 154
Output Fields	<p>Table 9 on page 151 lists the output fields for the show ike security-associations command. Output fields are listed in the approximate order in which they appear.</p>

Table 9: show ike security-associations Output Fields

Field Name	Field Description	Level of Output
IKE peer	Remote end of the IKE negotiation.	detail
Role	Part played in the IKE session. The router triggering the IKE negotiation is the initiator, and the router accepting the first IKE exchange packets is the responder.	detail
Remote Address	Responder's address.	none specified
State	State of the IKE security association: <ul style="list-style-type: none"> • Matured—The IKE security association is established. • Not matured—The IKE security association is in the process of negotiation. 	none specified
Initiator cookie	When the IKE negotiation is triggered, a random number is sent to the remote node.	All levels

Table 9: show ike security-associations Output Fields (*continued*)

Field Name	Field Description	Level of Output
Responder cookie	<p>The remote node generates its own random number and sends it back to the initiator as a verification that the packets were received.</p> <p>Of the numerous security services available, protection against denial of service (DoS) is one of the most difficult to address. A “cookie” or anticlogging token (ACT) is aimed at protecting the computing resources from attack without spending excessive CPU resources to determine the cookie's authenticity. An exchange prior to CPU-intensive public key operations can thwart some DoS attempts (such as simple flooding with invalid IP source addresses).</p>	All levels
Exchange type	<p>Specifies the number of messages in an IKE exchange, and the payload types that are contained in each message. Each exchange type provides a particular set of security services, such as anonymity of the participants, perfect forward secrecy of the keying material, and authentication of the participants. Junos OS supports two types of exchanges:</p> <ul style="list-style-type: none"> • Main—The exchange is done with six messages. Main encrypts the payload, protecting the identity of the neighbor. • Aggressive—The exchange is done with three messages. Aggressive does not encrypt the payload, leaving the identity of the neighbor unprotected. 	All Levels
Authentication method	Type of authentication determines which payloads are exchanged and when they are exchanged. The Junos OS supports only pre-shared keys .	detail
Local	Prefix and port number of the local end.	detail
Remote	Prefix and port number of the remote end.	detail
Lifetime	Number of seconds remaining until the IKE security association expires.	detail
Algorithms	<p>Header for the IKE algorithms output.</p> <ul style="list-style-type: none"> • Authentication—Type of authentication algorithm used: md5 or sha1. • Encryption—Type of encryption algorithm used: des-cbc, 3des-cbc, or None. • Pseudo random function—Function that generates highly unpredictable random numbers: hmac-md5 or hmac-sha1. 	detail
Traffic statistics	<p>Number of bytes and packets received and transmitted on the IKE security association.</p> <ul style="list-style-type: none"> • Input bytes, Output bytes—Number of bytes received and transmitted on the IKE security association. • Input packets, Output packets—Number of packets received and transmitted on the IKE security association. 	detail

Table 9: show ike security-associations Output Fields (*continued*)

Field Name	Field Description	Level of Output
Flags	Notification to the key management process of the status of the IKE negotiation: <ul style="list-style-type: none"> • caller notification sent—Caller program notified about the completion of the IKE negotiation. • waiting for done—Negotiation is done. The library is waiting for the remote end retransmission timers to expire. • waiting for remove—Negotiation has failed. The library is waiting for the remote end retransmission timers to expire before removing this negotiation. • waiting for policy manager—Negotiation is waiting for a response from the policy manager. 	detail
IPsec security associates	Number of IPsec security associations created and deleted with this IKE security association.	detail
Phase 2 negotiations in progress	Number of phase 2 IKE negotiations in progress and status information: <ul style="list-style-type: none"> • Negotiation type—Type of phase 2 negotiation. The Junos OS currently supports quick mode. • Message ID—Unique identifier for a phase 2 negotiation. • Local identity—Identity of the local phase 2 negotiation. The format is <i>id-type-name (proto-name:port-number,[O..id-data-len] = iddata-presentation)</i> • Remote identity—Identity of the remote phase 2 negotiation. The format is <i>id-type-name (proto-name:port-number,[O..id-data-len] = iddata-presentation)</i> • Flags—Notification to the key management process of the status of the IKE negotiation: <ul style="list-style-type: none"> • caller notification sent—Caller program notified about the completion of the IKE negotiation. • waiting for done—Negotiation is done. The library is waiting for the remote end retransmission timers to expire. • waiting for remove—Negotiation has failed. The library is waiting for the remote end retransmission timers to expire before removing this negotiation. • waiting for policy manager—Negotiation is waiting for a response from the policy manager. 	detail

Sample Output

show ike security-associations

```
user@host> show ike security-associations
Remote Address  State           Initiator cookie  Responder cookie  Exchange type
4.4.4.4         Matured           93870456fa000011 723a20713700003e Main
```

show ike security-associations detail

```
user@host> show ike security-associations detail
IKE peer 4.4.4.4
  Role: Initiator, State: Matured
  Initiator cookie: cf22bd81a7000001, Responder cookie: fe83795c2800002e
  Exchange type: Main, Authentication method: Pre-shared-keys
  Local: 4.4.4.5:500, Remote: 4.4.4.4:500
  Lifetime: Expires in 187 seconds
  Algorithms:
    Authentication      : md5
    Encryption          : 3des-cbc
    Pseudo random function: hmac-md5
  Traffic statistics:
    Input bytes  :          1000
    Output bytes :          1280
    Input packets:           5
    Output packets:          9
  Flags: Caller notification sent
  IPsec security associations: 2 created, 0 deleted
  Phase 2 negotiations in progress: 1

Negotiation type: Quick mode, Role: Initiator, Message ID: 3582889153
  Local: 4.4.4.5:500, Remote: 4.4.4.4:500
  Local identity: ipv4_subnet(tcp:80,[0..7]=10.1.1.0/24)
  Remote identity: ipv4_subnet(tcp:100,[0..7]=10.1.2.0/24)
  Flags: Caller notification sent, Waiting for done
```

show ipsec certificates

Syntax	show ipsec certificates <brief detail> <crl <i>crl-name</i> <i>serial-number</i> >
Release Information	Command introduced before Junos OS Release 7.4.
Description	(Encryption interface on M Series and T Series routers only) Display information about the IPsec certificate database.
Options	<p>none—Display standard information about all of the entries in the IPsec certificate database.</p> <p>brief detail—(Optional) Display the specified level of output.</p> <p>crl <i>crl-name</i> <i>serial-number</i>—(Optional) Display information about the entries on the certificate revocation list (CRL) or for the specified serial number. A CRL is a timestamped list identifying revoked certificates. The CRL is signed by a certificate authority (CA) or CRL issuer and made freely available in a public repository. Each revoked certificate is identified in a CRL by its certificate serial number.</p>
Required Privilege Level	view
Related Documentation	<ul style="list-style-type: none"> • <i>clear ipsec security-associations</i>
List of Sample Output	show ipsec certificates detail on page 156
Output Fields	Table 10 on page 155 lists the output fields for the show ipsec certificates command. Output fields are listed in the approximate order in which they appear.

Table 10: show ipsec certificates Output Fields

Field Name	Field Description	Level of Output
Database	Display information about the IPsec certificate database. <ul style="list-style-type: none"> • Total entries—Number of database entries, including entries that are not trusted or that are in the process of being deleted. • Active entries—Number of database entries, excluding entries that are marked as deleted. • Locked entries—Number of statically configured database entries that cannot expire, such as CA certificates that are root or trusted. 	All levels
Subject	Distinguished name for the certificate for C, O, CN , as described in RFC 3280, <i>Internet x.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile</i> .	All levels
ID	Identification number of the database entry. ID is generated by the internal certificate database.	All levels

Table 10: show ipsec certificates Output Fields (*continued*)

Field Name	Field Description	Level of Output
References	Reference number the certificate manager has for the particular entry.	detail
Serial	Unique serial number assigned to each certificate by the CA.	All levels
Flags	State of the certificate. <ul style="list-style-type: none"> • Trusted—Passed validity checks. • Not trusted—Failed validity checks. • Root—Entry is locked and may have been learned through IKE or a locally configured CA certificate. • Non-root—Entry is not locked. • Crl-issuer—Entity issues CRLs. • Non-crl-issuer—Entity does not issue CRLs. 	detail
Validity period starts	Start time that the certificate is valid, in the format <i>yyyy mon dd, hh:mm:ss GMT</i> .	detail
Validity period ends	End time that the certificate is valid, in the format <i>yyyy mon dd, hh:mm:ss GMT</i> .	detail
Alternative name information	Auxiliary identity for the certificate: <i>dns-name</i> , <i>email-address</i> , <i>ip-address</i> , or <i>uri</i> (uniform resource identifier).	detail
Issuer	Information about the entity that has signed and issued the CRL as described in RFC 2459, <i>Internet X.509 Public Key Infrastructure Certificate and CRL Profile</i> .	detail

Sample Output

show ipsec certificates detail

```

user@host> show ipsec certificates detail
Database: Total entries: 3 Active entries: 4 Locked entries: 1
Subject: C=us, O=x
  ID: 5, References: 0, Serial: 22314868
  Flags: Trusted Non-root Crl-issuer
  Validity period starts: 2003 Mar 1st, 01:20:42 GMT
  Validity period ends: 2003 Mar 31st, 01:50:42 GMT
  Alternative name information:
    IP address: 10.20.210.1
  Issuer: C=FI, O=Company-ABC, CN=Company ABC class 2

Subject: C=us, O=x
  ID: 4, References: 0, Serial: 22315496
  Flags: Trusted Non-root Crl-issuer
  Validity period starts: 2003 Mar 1st, 01:21:45 GMT
  Validity period ends: 2003 Mar 31st, 01:51:45 GMT
  Alternative name information:
    IP address: 10.20.210.20
  Issuer: C=FI, O=Company-ABC, CN=Company ABC class 2

Subject: C=FI, O=SSH Company-ABC, CN=Company ABC class 2
  ID: 1, References: 1, Serial: 1538512
  Flags: Trusted Root Non-crl-issuer

```

Validity period starts: 2001 Aug 1st, 07:08:32 GMT
Validity period ends: 2004 Aug 1st, 07:08:32 GMT
Alternative name information:
Email address: certifier-support@ssh.com
Issuer: C=FI, O=Company-ABC, CN=Company ABC class 2

show security pki ca-certificate

Syntax	show security pki ca-certificate <brief detail> <ca-profile <i>ca-profile-name</i> >
Release Information	Command introduced in Junos OS Release 7.5.
Description	Display information about certificate authority (CA) digital certificates installed in the router.
Options	<p>none—(Same as brief) Display information about all CA digital certificates.</p> <p>brief detail—(Optional) Display the specified level of output.</p> <p>ca-profile <i>ca-profile-name</i>—(Optional) Display information about only the specified CA profile.</p>
Required Privilege Level	view
List of Sample Output	show security pki ca-certificate on page 159 show security pki ca-certificate detail on page 160
Output Fields	Table 11 on page 158 lists the output fields for the show security pki ca-certificate command. Output fields are listed in the approximate order in which they appear.

Table 11: show security pki ca-certificate Output Fields

Field Name	Field Description	Level of Output
Certificate identifier	Name of the digital certificate.	All levels
Certificate version	Revision number of the digital certificate.	detail
Serial number	Unique serial number of the digital certificate.	detail
Issued by	Authority that issued the digital certificate.	none brief
Issued to	Device that was issued the digital certificate.	none brief
Issuer	<p>Authority that issued the digital certificate, including details of the authority organized using the distinguished name format. Possible subfields are:</p> <ul style="list-style-type: none"> • Common name—Name of the authority. • Organization—Organization of origin. • Organizational unit—Department within an organization. • State—State of origin. • Country—Country of origin. 	detail

Table 11: show security pki ca-certificate Output Fields (*continued*)

Field Name	Field Description	Level of Output
Subject	Details of the digital certificate holder organized using the distinguished name format. Possible subfields are: <ul style="list-style-type: none"> • Common name—Name of the requestor. • Organization—Organization of origin. • Organizational unit—Department within an organization. • State—State of origin. • Country—Country of origin. 	detail
Validity	Time period when the digital certificate is valid. Values are: <ul style="list-style-type: none"> • Not before—Start time when the digital certificate becomes valid. • Not after—End time when the digital certificate becomes invalid. 	All levels
Public key algorithm	Encryption algorithm used with the private key, such as rsaEncryption(1024 bits) .	All levels
Signature algorithm	Encryption algorithm that the CA used to sign the digital certificate, such as sha1WithRSAEncryption .	detail
Fingerprint	Secure Hash Algorithm (SHA1) and Message Digest 5 (MD5) hashes used to identify the digital certificate.	detail
Distribution CRL	Distinguished name information and the URL for the certificate revocation list (CRL) server.	detail
Use for key	Use of the public key, such as Certificate signing , CRL signing , Digital signature , or Key encipherment .	detail

Sample Output

show security pki ca-certificate

```

user@host> show security pki ca-certificate
Certificate identifier: entrust
  Issued to: juniper, Issued by: juniper
  Validity:
    Not before: 2005 Oct 18th, 23:54:22 GMT
    Not after: 2025 Oct 19th, 00:24:22 GMT
  Public key algorithm: rsaEncryption(1024 bits)

Certificate identifier: entrust
  Issued to: First Officer, Issued by: juniper
  Validity:
    Not before: 2005 Oct 18th, 23:55:59 GMT
    Not after: 2008 Oct 19th, 00:25:59 GMT
  Public key algorithm: rsaEncryption(1024 bits)

Certificate identifier: entrust
  Issued to: First Officer, Issued by: juniper
  Validity:
    Not before: 2005 Oct 18th, 23:55:59 GMT

```

Not after: 2008 Oct 19th, 00:25:59 GMT
Public key algorithm: rsaEncryption(1024 bits)

show security pki ca-certificate detail

```

user@host> show security pki ca-certificate detail
Certificate identifier: entrust
Certificate version: 3
Serial number: 4355 9235
Issuer:
  Organization: juniper, Country: us
Subject:
  Organization: juniper, Country: us
Validity:
  Not before: 2005 Oct 18th, 23:54:22 GMT
  Not after: 2025 Oct 19th, 00:24:22 GMT
Public key algorithm: rsaEncryption(1024 bits)
cb:9e:2d:c0:70:f8:ea:3c:f2:b5:f0:02:48:87:dc:68:99:a3:57:4f
0e:b9:98:0b:95:47:0d:1f:97:7c:53:17:dd:1a:f8:da:e5:08:d1:1c
78:68:1f:2f:72:9f:a2:cf:81:e3:ce:c5:56:89:ce:f0:97:93:fa:36
19:3e:18:7d:8c:9d:21:fe:1f:c3:87:8d:b3:5d:f3:03:66:9d:16:a7
bf:18:3f:f0:7a:80:f0:62:50:43:83:4f:0e:d7:c6:42:48:c0:8a:b2
c7:46:30:38:df:9b:dc:bc:b5:08:7a:f3:cd:64:db:2b:71:67:fe:d8
04:47:08:07:de:17:23:13
Signature algorithm: sha1WithRSAEncryption
Fingerprint:
  00:8e:6f:58:dd:68:bf:25:0a:e3:f9:17:70:d6:61:f3:53:a7:79:10 (sha1)
  71:6f:6a:76:17:9b:d6:2a:e7:5a:72:97:82:6d:26:86 (md5)
Distribution CRL:
  C=us, O=juniper, CN=CRL1
  http://CA-1/CRL/juniper_us_crlfile.crl
Use for key: CRL signing, Certificate signing
Certificate identifier: entrust
Certificate version: 3
Serial number: 4355 925c
Issuer:
  Organization: juniper, Country: us
Subject:
  Organization: juniper, Country: us, Common name: First Officer
Validity:
  Not before: 2005 Oct 18th, 23:55:59 GMT
  Not after: 2008 Oct 19th, 00:25:59 GMT
Public key algorithm: rsaEncryption(1024 bits)
c0:a4:21:32:95:0a:cd:ec:12:03:d1:a2:89:71:8e:ce:4e:a6:f9:2f
1a:9a:13:8c:f6:a0:3d:c9:bd:9d:c2:a0:41:77:99:1b:1e:ed:5b:80
34:46:f8:5b:28:34:38:2e:91:7d:4e:ad:14:86:78:67:e7:02:1d:2e
19:11:b7:fa:0d:ba:64:20:e1:28:4e:3e:bb:6e:64:dc:cd:b1:b4:7a
ca:8f:47:dd:40:69:c2:35:95:ce:b8:85:56:d7:0f:2d:04:4d:5d:d8
42:e1:4f:6b:bf:38:c0:45:1e:9e:f0:b4:7f:74:6f:e9:70:fd:4a:78
da:eb:10:27:bd:46:34:33
Signature algorithm: sha1WithRSAEncryption
Fingerprint:
  bc:78:87:9b:a7:91:13:20:71:db:ac:b5:56:71:42:ad:1a:b6:46:17 (sha1)
  23:79:40:c9:6d:a6:f0:ca:e0:13:30:d4:29:6f:86:79 (md5)
Distribution CRL:
  C=us, O=juniper, CN=CRL1
  http://CA-1/CRL/juniper_us_crlfile.crl
Use for key: Key encipherment
Certificate identifier: entrust
Certificate version: 3
Serial number: 4355 925b

```



```
Issuer:
  Organization: juniper, Country: us
Subject:
  Organization: juniper, Country: us, Common name: First Officer
Validity:
  Not before: 2005 Oct 18th, 23:55:59 GMT
  Not after: 2008 Oct 19th, 00:25:59 GMT
Public key algorithm: rsaEncryption(1024 bits)
  ea:75:c4:f3:58:08:ea:65:5c:7e:b3:de:63:0a:cf:cf:ec:9a:82:e2
  d7:e8:b9:2f:bd:4b:cd:86:2f:f1:dd:d8:a2:95:af:ab:51:a5:49:4e
  00:10:c6:25:ff:b5:49:6a:99:64:74:69:e5:8c:23:5b:b4:70:62:8e
  e4:f9:a2:28:d4:54:e2:0b:1f:50:a2:92:cf:6c:8f:ae:10:d4:69:3c
  90:e2:1f:04:ea:ac:05:9b:3a:93:74:d0:59:24:e9:d2:9d:c2:ef:22
  b9:32:c7:2c:29:4f:91:cb:5a:26:fe:1d:c0:36:dc:f4:9c:8b:f5:26
  af:44:bf:53:aa:d4:5f:67
Signature algorithm: sha1WithRSAEncryption
Fingerprint:
  46:71:15:34:f0:a6:41:76:65:81:33:4f:68:47:c4:df:78:b8:e3:3f (sha1)
  ee:cc:c7:f4:5d:ac:65:33:0a:55:db:59:72:2c:dd:16 (md5)
Distribution CRL:
  C=us, O=juniper, CN=CRL1
  http://CA-1/CRL/juniper_us_crlfile.crl
Use for key: Digital signature
```

show ipsec security-associations

Syntax	show ipsec security-associations <brief detail> <sa-name>
Release Information	Command introduced before Junos OS Release 7.4.
Description	Display information about the IPsec security associations applied to the local or transit traffic stream.
Options	<p>none—Display standard information about all IPsec security associations.</p> <p>brief detail—(Optional) Display the specified level of output.</p> <p>sa-name—(Optional) Display the specified IPsec security association.</p>
Required Privilege Level	view
List of Sample Output	show ipsec security-associations sa-name on page 164 show ipsec security-associations sa-name detail on page 164
Output Fields	Table 12 on page 162 lists the output fields for the show ipsec security-associations command. Output fields are listed in the approximate order in which they appear.

Table 12: show ipsec security-associations Output Fields

Field Name	Field Description	Level of Output
Security association	Name of the security association.	All levels
Interface family	<p>Status of the interface family of the security association. If the interface family field is absent, it is a transport mode security association. The interface family can have one of three options:</p> <ul style="list-style-type: none"> • Up—The security association is referenced in the interface family and the interface family is up. • Down—The security association is referenced in the interface family and the interface family is down. • No reference—The security association is not referenced in the interface family. 	All levels
Local gateway	Gateway address of the local system.	All levels
Remote gateway	Gateway address of the remote system.	All levels
Local identity	Prefix and port number of the local end	All levels
Remote identity	Prefix and port number of the remote end.	All levels
Direction	Direction of the security association: inbound or outbound .	All levels
SPI	Value of the security parameter index.	All levels

Table 12: show ipsec security-associations Output Fields (*continued*)

Field Name	Field Description	Level of Output
AUX-SPI	Value of the auxiliary security parameter index. <ul style="list-style-type: none"> When the value is AH or ESP, AUX-SPI is always 0. When the value is AH+ESP, AUX-SPI is always a positive integer. 	All levels
State	Status of the security association: <ul style="list-style-type: none"> Installed—The security association is installed in the security association database. (For transport mode security associations, the value of State must always be Installed.) Not installed—The security association is not installed in the security association database. 	detail
Mode	Mode of the security association: <ul style="list-style-type: none"> transport—Protects single host-to-host protections. tunnel—Protects connections between security gateways. 	All levels
Type	Type of security association: <ul style="list-style-type: none"> manual—Security parameters require no negotiation. They are static, and are configured by the user. dynamic—Security parameters are negotiated by the IKE protocol. Dynamic security associations are not supported in transport mode. 	All levels
Protocol	Protocol supported: <ul style="list-style-type: none"> transport mode—Supports Encapsulation Security Protocol (ESP) or Authentication Header (AH). tunnel mode—Supports ESP or AH+ESP. 	All levels
Authentication	Type of authentication used: hmac-md5-96 , hmac-sha1-96 , or None .	detail
Encryption	Type of encryption used: des-cbc , 3des-csc , or None .	detail
Soft lifetime Hard lifetime	(dynamic output only) Each lifetime of a security association has two display options, hard and soft, one of which must be present for a dynamic security association. The hard lifetime specifies the lifetime of the SA. The soft lifetime , which is derived from the hard lifetime, informs the IPsec key management system that the SA is about to expire. This allows the key management system to negotiate a new SA before the hard lifetime expires. <ul style="list-style-type: none"> Expires in seconds seconds—Number of seconds left until the security association expires. Expires in kilobytes kilobytes—Number of kilobytes left until the security association expires. 	detail
Anti-replay service	State of the service that prevents packets from being replayed: Enabled or Disabled .	detail

Table 12: show ipsec security-associations Output Fields (*continued*)

Field Name	Field Description	Level of Output
Replay window size	Configured size, in packets, of the antireplay service window: 32 or 64. The antireplay window size protects the receiver against replay attacks by rejecting old or duplicate packets. If the replay window size is 0, the antireplay service is disabled.	detail

Sample Output

show ipsec security-associations sa-name

```

user@host> show ipsec security-associations sa-cosmic brief
Security association: sa-cosmic, Interface family: Up
Local gateway: 21.21.1.1, Remote gateway: 21.21.2.1
Local identity: ipv4_subnet(any:0,[0..7]=0.0.0.0/0)
Remote identity: ipv4_subnet(any:0,[0..7]=0.0.0.0/0)
Direction SPI      AUX-SPI    Mode      Type      Protocol
inbound  2908734119  0          tunnel    dynamic   AH
outbound 3494029335  0          tunnel    dynamic   AH

```

show ipsec security-associations sa-name detail

```

user@host> show ipsec security-associations sa-cosmic detail
Security association: sa-cosmic, Interface family: Up

Local gateway: 21.21.1.1, Remote gateway: 21.21.2.1
Local identity: ipv4_subnet(any:0,[0..7]=0.0.0.0/0)
Remote identity: ipv4_subnet(any:0,[0..7]=0.0.0.0/0)
Direction: inbound, SPI: 2908734119, AUX-SPI: 0, State: Installed
Mode: tunnel, Type: dynamic
Protocol: AH, Authentication: hmac-md5-96, Encryption: None
Soft lifetime: Expired
Hard lifetime: Expires in 120 seconds
Anti-replay service: Disabled

Direction: outbound, SPI: 3494029335, AUX-SPI: 0, State: Installed
Mode: tunnel, Type: dynamic
Protocol: AH, Authentication: hmac-md5-96, Encryption: None
Soft lifetime: Expired
Hard lifetime: Expires in 120 seconds
Anti-replay service: Disabled

```

show security pki certificate-request

Syntax	show security pki certificate-request <brief detail> <certificate-id <i>certificate-id-name</i> >
Release Information	Command introduced in Junos OS Release 7.5.
Description	Display information about manually generated local digital certificate requests that are stored in the router.
Options	<p>none—(same as brief) Display information about all local digital certificate requests.</p> <p>brief detail—(Optional) Display the specified level of output.</p> <p>certificate-id <i>certificate-id-name</i>—(Optional) Display information about only the specified local digital certificate request</p>
Required Privilege Level	view
Related Documentation	<ul style="list-style-type: none"> • clear security pki certificate-request on page 135
List of Sample Output	show security pki certificate-request on page 166 show security pki certificate-request detail on page 166
Output Fields	Table 13 on page 165 lists the output fields for the show security pki certificate-request command. Output fields are listed in the approximate order in which they appear.

Table 13: show security pki certificate-request Output Fields

Field Name	Field Description	Level of Output
Certificate identifier	Name of the digital certificate.	All levels
Certificate version	Revision number of the digital certificate.	detail
Issued to	Device that was issued the digital certificate.	none brief
Subject	<p>Details of the digital certificate holder organized using the distinguished name format. Possible subfields are:</p> <ul style="list-style-type: none"> • Common name—Name of the authority. • Organization—Organization of origin. • Organizational unit—Department within an organization. • State—State of origin. • Country—Country of origin. 	detail
Alternate subject	Domain name or IP address of the device related to the digital certificate.	detail

Table 13: show security pki certificate-request Output Fields (*continued*)

Field Name	Field Description	Level of Output
Validity	Time period when the digital certificate is valid. Values are: <ul style="list-style-type: none"> Not before—Time when the digital certificate becomes valid. Not after—End time when the digital certificate becomes invalid. 	All levels
Public key algorithm	Encryption algorithm used with the private key, such as rsaEncryption(1024 bits) .	All levels
Public key verification status	Public key verification status: Failed or Passed . The detail output also provides the verification hash.	All levels
Fingerprint	Secure Hash Algorithm (SHA1) and Message Digest 5 (MD5) hashes used to identify the digital certificate.	detail
Use for key	Use of the public key, such as Certificate signing , CRL signing , Digital signature , or Key encipherment .	detail

Sample Output

show security pki certificate-request

```

user@host> show security pki certificate-request
Certificate identifier: local-microsoft-2
Issued to: router2.juniper.net
Public key algorithm: rsaEncryption(1024 bits)
Public key verification status: Passed

```

show security pki certificate-request detail

```

user@host> show security pki certificate-request detail
Certificate identifier: local-entrust3
Certificate version: 3
Subject:
  Common name: router3.juniper.net
Alternate subject: router3.juniper.net
Public key algorithm: rsaEncryption(1024 bits)
Public key verification status: Passed
  fb:79:df:d4:a9:03:0f:d3:69:7e:c1:e4:27:35:9c:d9:b1:a2:47:78
  d2:6d:f3:e5:f4:68:4f:b3:04:45:88:57:99:82:39:a6:51:9e:5f:42
  23:3f:d7:6e:3d:a5:54:a9:b1:2d:6e:90:dd:12:8a:bf:ef:2b:20:50
  ba:f0:da:d9:0c:ad:5e:d6:c6:98:3a:ae:3f:90:dd:94:78:c1:ea:2e
  7c:f0:2d:d4:79:d4:cd:f0:52:df:5e:72:f2:e7:ae:66:f7:61:f4:bc
  72:57:3e:6c:6d:d3:24:58:8b:f4:ef:da:2a:6a:fa:eb:98:f8:34:84
  79:54:da:4f:d3:6f:52:1f
Fingerprint:
  7c:e8:f9:45:93:8d:a3:92:7f:18:29:02:f1:c8:e2:85:3d:ad:df:1f (sha1)
  00:4e:df:a0:6b:ad:8c:50:da:7c:a1:cf:5d:37:b0:ea (md5)
Use for key: Digital signature

```

show security pki crt

Syntax	show security pki crt <brief detail> <ca-profile <i>ca-profile-name</i> >
Release Information	Command introduced in Junos OS Release 8.1.
Description	Display information about the certificate revocation lists (CRLs) that are stored in the router.
Options	<p>none—(same as brief) Display information about all CRLs.</p> <p>brief detail—(Optional) Display the specified level of output.</p> <p>ca-profile <i>ca-profile-name</i>—(Optional) Display CRL information about only the specified CA profile.</p>
Required Privilege Level	view
Related Documentation	<ul style="list-style-type: none"> • clear security pki crt on page 136
List of Sample Output	show security pki crt on page 168 show security pki crt detail on page 168
Output Fields	Table 14 on page 167 shows the output fields for the show security pki crt command. Output fields are listed in the approximate order in which they appear.

Table 14: show security pki crt Output Fields

Field Name	Field Description	Level of Output
CA profile	Name of the configured CA profile.	All levels
CRL version	Revision number of the certificate revocation list.	All levels
CRL number	Number of the certificate revocation list	All levels
CRL issuer	Device that was issued the certificate revocation list.	All levels
Issuer	<p>Details of the digital certificate holder organized using the distinguished name format. Possible subfields are:</p> <ul style="list-style-type: none"> • Common name—Name of the authority. • Organization—Organization of origin. • Organizational unit—Department within an organization. • State—State of origin. • Country—Country of origin. 	detail
Effective date	Date and time the certificate revocation list becomes valid.	All levels

Table 14: show security pki crl Output Fields (*continued*)

Field Name	Field Description	Level of Output
Next update	Date and time the router will download the latest version of the certificate revocation list.	All levels
Revocation List	<p>List of digital certificates that have been revoked before their expiration date. Values are:</p> <ul style="list-style-type: none"> • Serial number—Unique serial number of the digital certificate • Revocation date—Date and time that the digital certificate was revoked. 	detail

Sample Output

show security pki crl

```
CA profile entrust
CRL version: V2
CRL number: 24
CRL issuer: C=CA, O=juniper
Effective date: 2006 May 31st, 05:35:25 GMT
Next update: 2006 Jun 1st, 06:35:25 GMT
```

show security pki crl detail

```
CA profile: entrust
CRL version: V2
CRL number: 24
Issuer:
  Organization: juniper, Country: ca
Validity:
  Effective date: 2006 May 31st, 05:35:25 GMT
  Next update: 2006 Jun 1st, 06:35:25 GMT
Revocation List:
  Serial number      Revocation date
  4451aca3 2006      May 25th, 09:13:38 GMT
  4451aca4 2006      May 25th, 10:11:33 GMT
  4451acb4 2006      May 29th, 11:28:54 GMT
  4451aceb 2006      May 29th, 11:29:01 GMT
  4451acfe 2006      May 29th, 11:29:17 GMT
  4451acff 2006      May 31st, 05:29:55 GMT
```


show security pki local-certificate

Syntax	show security pki local-certificate <brief detail> <certificate-id <i>certificate-id-name</i> > <system-generated>
Release Information	Command introduced in Junos OS Release 7.5.
Description	Display information about the local digital certificates and the corresponding public keys installed in the router.
Options	<p>none—(same as brief) Display information about all local digital certificates and corresponding public keys.</p> <p>brief detail—(Optional) Display the specified level of output.</p> <p>certificate-id <i>certificate-id-name</i>—(Optional) Display information about only the specified the local digital certificate and corresponding public keys.</p> <p>system-generated—(Optional) Auto-generated self-signed certificate.</p>
Required Privilege Level	view
Related Documentation	<ul style="list-style-type: none"> • clear security pki local-certificate on page 137
List of Sample Output	show security pki local-certificate on page 170 show security pki local-certificate detail on page 171
Output Fields	Table 15 on page 169 lists the output fields for the show security pki local-certificate command. Output fields are listed in the approximate order in which they appear.

Table 15: show security pki local-certificate Output Fields

Field Name	Field Description	Level of Output
Certificate identifier	Name of the digital certificate.	All levels
Certificate version	Revision number of the digital certificate.	detail
Serial number	Unique serial number of the digital certificate.	detail
Issued by	Authority that issued the digital certificate.	none brief
Issued to	Device that was issued the digital certificate.	none brief

Table 15: show security pki local-certificate Output Fields (*continued*)

Field Name	Field Description	Level of Output
Issuer	Authority that issued the digital certificate, including details of the authority organized using the distinguished name format. Possible subfields are: <ul style="list-style-type: none"> • Common name—Name of the authority. • Organization—Organization of origin. • Organizational unit—Department within an organization. • State—State of origin. • Country—Country of origin. 	detail
Subject	Details of the digital certificate holder organized using the distinguished name format. Possible subfields are: <ul style="list-style-type: none"> • Common name—Name of the authority. • Organization—Organization of origin. • Organizational unit—Department within an organization. • State—State of origin. • Country—Country of origin. 	detail
Alternate subject	Domain name or IP address of the device related to the digital certificate.	detail
Validity	Time period when the digital certificate is valid. Values are: <ul style="list-style-type: none"> • Not before—Start time when the digital certificate becomes valid. • Not after—End time when the digital certificate becomes invalid. 	All levels
Public key algorithm	Encryption algorithm used with the private key, such as rsaEncryption (1024 bits) .	All levels
Public key verification status	Public key verification status: Failed or Passed . The detail output also provides the verification hash.	All levels
Signature algorithm	Encryption algorithm that the CA used to sign the digital certificate, such as sha1WithRSAEncryption .	detail
Fingerprint	Secure Hash Algorithm (SHA1) and Message Digest 5 (MD5) hashes used to identify the digital certificate.	detail
Distribution CRL	Distinguished name information and URL for the certificate revocation list (CRL) server.	detail
Use for key	Use of the public key, such as Certificate signing , CRL signing , Digital signature , or Key encipherment .	detail

Sample Output

show security pki local-certificate

```

user@host> show security pki local-certificate
Certificate identifier: local-entrust2
  Issued to: router2.juniper.net, Issued by: juniper

```

```

Validity:
  Not before: 2005 Nov 21st, 23:28:22 GMT
  Not after: 2008 Nov 21st, 23:58:22 GMT
Public key algorithm: rsaEncryption(1024 bits)
Public key verification status: Passed

```

show security pki local-certificate detail

```

user@host> show security pki local-certificate detail
Certificate identifier: local-entrust3
Certificate version: 3
Serial number: 4355 94f9
Issuer:
  Organization: juniper, Country: us
Subject:
  Organization: juniper, Country: us, Common name: router3.juniper.net
Alternate subject: router3.juniper.net
Validity:
  Not before: 2005 Nov 21st, 23:33:58 GMT
  Not after: 2008 Nov 22nd, 00:03:58 GMT
Public key algorithm: rsaEncryption(1024 bits)
Public key verification status: Passed
fb:79:df:d4:a9:03:0f:d3:69:7e:c1:e4:27:35:9c:d9:b1:a2:47:78
d2:6d:f3:e5:f4:68:4f:b3:04:45:88:57:99:82:39:a6:51:9e:5f:42
23:3f:d7:6e:3d:a5:54:a9:b1:2d:6e:90:dd:12:8a:bf:ef:2b:20:50
ba:f0:da:d9:0c:ad:5e:d6:c6:98:3a:ae:3f:90:dd:94:78:c1:ea:2e
7c:f0:2d:d4:79:d4:cd:f0:52:df:5e:72:f2:e7:ae:66:f7:61:f4:bc
72:57:3e:6c:6d:d3:24:58:8b:f4:ef:da:2a:6a:fa:eb:98:f8:34:84
79:54:da:4f:d3:6f:52:1f
Signature algorithm: sha1WithRSAEncryption
Fingerprint:
  61:3a:d0:b4:7a:16:9b:39:ba:81:3f:9d:ab:34:e5:c8:be:3b:a1:6d (sha1)
  60:a0:ff:58:05:4a:65:73:9d:74:3a:e1:83:6f:1b:c8 (md5)
Distribution CRL:
  C=us, O=juniper, CN=CRL1
  http://CA-1/CRL/juniper_us_crlfile.crl
Use for key: Digital signature

```

show services ipsec-vpn certificates

Syntax	show services ipsec-vpn certificates <brief detail> <service-set <i>service-set</i> >
Release Information	Command introduced in Junos OS Release 7.5.
Description	(Adaptive services interfaces only) Display local and remote certificates installed in the IPsec configuration memory cache that are used for the IKE negotiation.
Options	<p>none—(same as brief) Display information about local and remote certificates associated with all service sets.</p> <p>brief detail—(Optional) Display the specified level of output.</p> <p>service-set <i>service-set</i>—(Optional) Display information about local and remote certificates associated with only the specified service set.</p>
Required Privilege Level	view
List of Sample Output	show security ipsec-vpn certificates on page 173 show security ipsec-vpn certificates detail on page 173
Output Fields	Table 16 on page 172 lists the output fields for the show services ipsec-vpn certificates command. Output fields are listed in the approximate order in which they appear.

Table 16: show services ipsec-vpn certificates Output Fields

Field Name	Field Description	Level of Output
Service set	Name of the IPsec service set.	All levels
Total entries	Number of certificate cache entries.	All levels
Certificate cache entry	Identification number of the certificate cache entry.	All levels
Flags	Information about the digital certificate, including whether the certificate is a root certificate and trusted.	none brief
Issued to	Device that was issued the digital certificate.	none brief
Issued by	Authority that issued the digital certificate.	none brief
Certificate version	Revision number of the digital certificate.	detail
Serial number	Unique serial number of the digital certificate.	detail
Alternate subject	Domain name or IP address of the device related to the digital certificate.	All levels

Table 16: show services ipsec-vpn certificates Output Fields (*continued*)

Field Name	Field Description	Level of Output
Validity	Time period when the digital certificate is valid. Values are: <ul style="list-style-type: none"> • Not before—Start time when the digital certificate becomes valid. • Not after—End time when the digital certificate becomes invalid. 	none brief
Public key algorithm	Specifies the encryption algorithm used with the private key, such as rsaEncryption (1024 bits) .	detail
Signature algorithm	Encryption algorithm that the CA used to sign the digital certificate, such as sha1WithRSAEncryption .	detail
Fingerprint	Secure Hash Algorithm (SHA1) and Message Digest 5 (MD5) hashes used to identify the digital certificate.	detail
Distribution CRL	Distinguished name information and the URL for the certificate revocation list (CRL) server.	detail
Use for key	Use of the public key, such as Certificate signing , CRL signing , Digital signature , or Key encipherment .	detail

Sample Output

show security ipsec-vpn certificates

```

user@host> show services ipsec-vpn certificates
Service set: serviceset-dynamic-BiEspsha3des, Total entries: 3
Certificate cache entry: 3
  Flags: Non-root Trusted
  Issued to: router3.juniper.net, Issued by: juniper
  Alternate subject: router3.juniper.net
  Validity:
    Not before: 2005 Nov 21st, 23:33:58 GMT
    Not after: 2008 Nov 22nd, 00:03:58 GMT

Certificate cache entry: 2
  Flags: Non-root Trusted
  Issued to: router2.juniper.net, Issued by: juniper
  Alternate subject: router2.juniper.net
  Validity:
    Not before: 2005 Nov 21st, 23:28:22 GMT
    Not after: 2008 Nov 21st, 23:58:22 GMT

Certificate cache entry: 1
  Flags: Root Trusted
  Issued to: juniper, Issued by: juniper
  Validity:
    Not before: 2005 Oct 18th, 23:54:22 GMT
    Not after: 2025 Oct 19th, 00:24:22 GMT

```

show security ipsec-vpn certificates detail

```

user@host> show services ipsec-vpn certificates detail

```

```
Service set: serviceset-dynamic-BiEspsha3des, Total entries: 3
Certificate cache entry: 3
  Certificate version: 3
  Serial number: 4355 94f9
  Alternate subject: router3.juniper.net
  Public key algorithm: rsaEncryption
  Signature algorithm: sha1WithRSAEncryption
  Fingerprint:
    61:3a:d0:b4:7a:16:9b:39:ba:81:3f:9d:ab:34:e5:c8:be:3b:a1:6d (sha1)
    60:a0:ff:58:05:4a:65:73:9d:74:3a:e1:83:6f:1b:c8 (md5)
  Distribution CRL:
    C=us, O=juniper, CN=CRL1
    http://CA-1/CRL/juniper_us_crlfile.crl
  Use for key: Digital signature

Certificate cache entry: 2
  Certificate version: 3
  Serial number: 4355 94f8
  Alternate subject: router2.juniper.net
  Public key algorithm: rsaEncryption
  Signature algorithm: sha1WithRSAEncryption
  Fingerprint:
    30:c3:a4:04:da:33:9d:60:23:5a:48:75:48:2c:f0:c6:96:6c:31:fa (sha1)
    9a:a2:ce:ef:7e:10:80:a0:c8:4d:2f:e7:e1:d3:69:9d (md5)
  Distribution CRL:
    C=us, O=juniper, CN=CRL1
    http://CA-1/CRL/juniper_us_crlfile.crl
  Use for key: Digital signature

Certificate cache entry: 1
  Certificate version: 3
  Flags: Root
  Serial number: 4355 9235
  Public key algorithm: rsaEncryption
  Signature algorithm: sha1WithRSAEncryption
  Fingerprint:
    00:8e:6f:58:dd:68:bf:25:0a:e3:f9:17:70:d6:61:f3:53:a7:79:10 (sha1)
    71:6f:6a:76:17:9b:d6:2a:e7:5a:72:97:82:6d:26:86 (md5)
  Distribution CRL:
    C=us, O=juniper, CN=CRL1
    http://CA-1/CRL/juniper_us_crlfile.crl
  Use for key: CRL signing, Certificate signing
```

show services ipsec-vpn ike security-associations

Syntax	show services ipsec-vpn ike security-associations <brief detail> <peer-address>
Release Information	Command introduced before Junos OS Release 7.4. Statistics for Internet Key Exchange (IKE) security associations for each services PIC introduced in Junos OS Release 12.1.
Description	(Adaptive services interface only) Display information for Internet Key Exchange (IKE) security associations. If no security association is specified, the information for all security associations is displayed.
Options	none —(same as brief) Display standard information for all IPsec security associations. brief detail —(Optional) Display the specified level of output. peer-address —(Optional) Display information about a particular security association address.
Required Privilege Level	view
List of Sample Output	show services ipsec-vpn ike security-associations on page 177 show services ipsec-vpn ike security-associations detail on page 178
Output Fields	Table 17 on page 175 lists the output fields for the show services ipsec-vpn ike security-associations command. Output fields are listed in the approximate order in which they appear.

Table 17: show services ipsec-vpn ike security-associations Output Fields

Field Name	Field Description	Level of Output
IKE peer	Remote end of the IKE negotiation.	detail
Role	Part played in the IKE session. The router triggering the IKE negotiation is the initiator, and the router accepting the first IKE exchange packets is the responder.	detail
Remote Address	Responder's address.	none specified
State	State of the IKE security association: <ul style="list-style-type: none"> • Matured—IKE security association is established. • Not matured—The IKE security association is in the process of negotiation. 	none specified
Initiator cookie	When the IKE negotiation is triggered, a random number is sent to the remote node.	All levels

Table 17: show services ipsec-vpn ike security-associations Output Fields (*continued*)

Field Name	Field Description	Level of Output
Responder cookie	<p>The remote node generates its own random number and sends it back to the initiator as a verification that the packets were received.</p> <p>Of the numerous security services available, protection against denial of service (DoS) is one of the most difficult to address. A “cookie” or anticlogging token (ACT) is aimed at protecting the computing resources from attack without spending excessive CPU resources to determine the cookie's authenticity. An exchange prior to CPU-intensive public key operations can thwart some DoS attempts (such as simple flooding with invalid IP source addresses).</p>	All levels
Exchange type	<p>Specifies the number of messages in an IKE exchange, and the payload types that are contained in each message. Each exchange type provides a particular set of security services, such as anonymity of the participants, perfect forward secrecy of the keying material, and authentication of the participants. Junos OS supports two types of exchanges:</p> <ul style="list-style-type: none"> • Main—The exchange is done with six messages. Main encrypts the payload, protecting the identity of the neighbor. • Aggressive—The exchange is done with three messages. Aggressive does not encrypt the payload, leaving the identity of the neighbor unprotected. • IKEv2—The exchange is negotiated using IKE version 2. 	All levels
PIC	The services PIC for which the IKE security associations are displayed.	All levels
Authentication method	Type of authentication determines which payloads are exchanged and when they are exchanged. The Junos OS supports only pre-shared keys .	detail
Local	Prefix and port number of the local end.	detail
Remote	Prefix and port number of the remote end.	detail
Lifetime	Number of seconds remaining until the IKE security association expires.	detail
Algorithms	<p>Header for the IKE algorithms output.</p> <ul style="list-style-type: none"> • Authentication—(detail output only) Type of authentication algorithm used: md5 or sha1 • Encryption—(detail output only) Type of encryption algorithm used: des-cbc, 3des-cbc, or None. • Pseudo random function—Function that generates highly unpredictable random numbers: hmac-md5 or hmac-sha1. 	detail
Traffic statistics	<p>Number of bytes and packets received and transmitted on the IKE security association.</p> <ul style="list-style-type: none"> • Input bytes, Output bytes—Number of bytes received and transmitted on the IKE security association. • Input packets, Output packets—Number of packets received and transmitted on the IKE security association. 	detail

Table 17: show services ipsec-vpn ike security-associations Output Fields (*continued*)

Field Name	Field Description	Level of Output
Flags	Notification to the key management process of the status of the IKE negotiation: <ul style="list-style-type: none"> caller notification sent—Caller program notified about the completion of the IKE negotiation. waiting for done—Negotiation is done. The library is waiting for the remote end retransmission timers to expire. waiting for remove—Negotiation has failed. The library is waiting for the remote end retransmission timers to expire before removing this negotiation. waiting for policy manager—Negotiation is waiting for a response from the policy manager. 	detail
IPsec security associates	Number of IPsec security associations created and deleted with this IKE security association.	detail
Phase 2 negotiations in progress	Number of phase 2 negotiations in progress and status information: <ul style="list-style-type: none"> Negotiation type—Type of phase 2 negotiation. The Junos OS currently supports quick mode. Message ID—Unique identifier for a phase 2 negotiation. Local identity—Identity of the local phase 2 negotiation. The format is <i>id-type-name (proto-name:port-number,[0..id-data-len] = iddata-presentation)</i>. Remote identity—Identity of the remote phase 2 negotiation. The format is <i>id-type-name (proto-name:port-number,[0..id-data-len] = iddata-presentation)</i>. Flags—Notification to the key management process of the status of the IKE negotiation: <ul style="list-style-type: none"> caller notification sent—Caller program notified about the completion of the IKE negotiation. waiting for done—Negotiation is done. The library is waiting for the remote end retransmission timers to expire. waiting for remove—Negotiation has failed. The library is waiting for the remote end retransmission timers to expire before removing this negotiation. waiting for policy manager—Negotiation is waiting for a response from the policy manager. 	detail

Sample Output

show services ipsec-vpn ike security-associations

```

user@host> show services ipsec-vpn ike security-associations
Remote Address  State      Initiator cookie  Responder cookie  Exchange type
-----
6.6.6.1         Matured    062d291d21275fc7  82ef00e3d1f1c981  Main
6.6.6.2         Matured    cd6d581d7bb1664d  88a707779f3ad8d1  Main
6.6.6.3         Matured    86621051e3e78360  6bc5cc83fd67baa4  IKEv2
PIC: sp-0/3/0
6.6.6.7         Matured    565e2813075e6fdb  67886757a74edcd6  IKEv2

```

show services ipsec-vpn ike security-associations detail

```
user@host> show services ipsec-vpn ike security-associations detail
IKE peer 3.1.0.2
  Role: Responder, State: Matured
  Initiator cookie: d91c9f20f78e1d4e, Responder cookie: 727a04ed8d5021a1
  Exchange type: IKEv2, Authentication method: Pre-shared-keys
  Local: 4.1.0.2:500, Remote: 3.1.0.2:500
  Lifetime: Expires in 1357 seconds
  Algorithms:
    Authentication      : sha1
    Encryption          : 3des-cbc
    Pseudo random function: hmac-sha1
  Traffic statistics:
    Input bytes  :          22244
    Output bytes :          22236
    Input packets:           263
    Output packets:          263
  Flags: Caller notification sent
  IPsec security associations: 0 created, 0 deleted
  Phase 2 negotiations in progress: 0

IKE peer 4.4.4.4
  Role: Initiator, State: Matured
  Initiator cookie: cf22bd81a7000001, Responder cookie: fe83795c2800002e
  Exchange type: Main, Authentication method: Pre-shared-keys
  Local: 4.4.4.5:500, Remote: 4.4.4.4:500
  Lifetime: Expires in 187 seconds
  Algorithms:
    Authentication      : md5
    Encryption          : 3des-cbc
    Pseudo random function: hmac-md5
  Traffic statistics:
    Input bytes  :          1000
    Output bytes :          1280
    Input packets:           5
    Output packets:           9
  Flags: Caller notification sent
  IPsec security associations: 2 created, 0 deleted
  Phase 2 negotiations in progress: 1

Negotiation type: Quick mode, Role: Initiator, Message ID: 3582889153
  Local: 4.4.4.5:500, Remote: 4.4.4.4:500
  Local identity: ipv4_subnet(tcp:80,[0..7]=10.1.1.0/24)
  Remote identity: ipv4_subnet(tcp:100,[0..7]=10.1.2.0/24)
  Flags: Caller notification sent, Waiting for done
```

show services ipsec-vpn ipsec security-associations

Syntax	show services ipsec-vpn ipsec security-associations <brief detail extensive> <service-set <i>service-set-name</i> >
Release Information	Command introduced before Junos OS Release 7.4.
Description	(Adaptive services interface only) Display IPsec security associations for the specified service set. If no service set is specified, the security associations for all service sets are displayed.
Options	<p>none—Display standard information about IPsec security associations for all service sets.</p> <p>brief detail extensive—(Optional) Display the specified level of output.</p> <p>service-set <i>service-set-name</i>—(Optional) Display information about a particular service set.</p>
Required Privilege Level	view
List of Sample Output	show services ipsec-vpn ipsec security associations extensive on page 182
Output Fields	Table 18 on page 179 lists the output fields for the show services ipsec-vpn ipsec security-associations command. Output fields are listed in the approximate order in which they appear.

Table 18: show services ipsec-vpn ipsec security-associations Output Fields

Field Name	Field Description	Level of Output
Service set	Name of the service set for which the IPsec security associations are defined. If appropriate, includes the outside service interface VRF name.	All levels
Rule	Name of the rule set applied to the security association.	detail extensive
Term	Name of the IPsec term applied to the security association.	detail extensive
Tunnel index	Numeric identifier of the specific IPsec tunnel for the security association.	detail extensive
Local gateway	Gateway address of the local system.	All levels
Remote gateway	Gateway address of the remote system.	All levels
IPsec inside interface	Name of the logical interface hosting the IPsec tunnels.	All levels
Tunnel MTU	MTU of the IPsec tunnel.	All levels

Table 18: show services ipsec-vpn ipsec security-associations Output Fields (*continued*)

Field Name	Field Description	Level of Output
Local identity	<p>Protocol, address or prefix, and port number of the local entity of the IPsec association. The format is id-type-name (proto-name:port-number,[0..id-data-len] = iddata-presentation). The protocol is always displayed as any because it is not user-configurable in the IPsec rule. Similarly, the port number field in the output is always displayed as 0 because it is not user-configurable in the IPsec rule. The value of the id-data-len parameter can be one of the following, depending on the address configured in the IPsec rule:</p> <ul style="list-style-type: none"> For an IPv4 address, the length is 4 and the value displayed is 3. For a subnet mask of an IPv4 address, the length is 8 and the value displayed is 7. For a range of IPv4 addresses, the length is 8 and the value displayed is 7. For an IPv6 address prefix, the length is 16 and the value displayed is 15. For a subnet mask of an IPv6 address prefix, the length is 32 and the value displayed is 31. For a range of IPv6 address prefixes, the length is 32 and the value displayed is 31. <p>The value of the id-data-presentation field denotes the IPv4 address or IPv6 prefix details. If the fully qualified domain name (FQDN) is specified instead of the address for the local peer of the IPsec association, it is displayed instead of the address details.</p>	All levels
Remote identity	<p>Protocol, address or prefix, and port number of the remote entity of the IPsec association. The format is id-type-name (proto-name:port-number,[0..id-data-len] = iddata-presentation). The protocol is always displayed as any because it is not user-configurable in the IPsec rule. Similarly, the port number field in the output is always displayed as 0 because it is not user-configurable in the IPsec rule. The value of the id-data-len parameter can be one of the following, depending on the address configured in the IPsec rule:</p> <ul style="list-style-type: none"> For an IPv4 address, the length is 4 and the value displayed is 3. For a subnet mask of an IPv4 address, the length is 8 and the value displayed is 7. For a range of IPv4 addresses, the length is 8 and the value displayed is 7. For an IPv6 address prefix, the length is 16 and the value displayed is 15. For a subnet mask of an IPv6 address prefix, the length is 32 and the value displayed is 31. For a range of IPv6 address prefixes, the length is 32 and the value displayed is 31. <p>The value of the id-data-presentation field denotes the IPv4 address or IPv6 prefix details. If the fully qualified domain name (FQDN) is specified instead of the address for the remote peer of the IPsec association, it is displayed instead of the address details.</p>	All levels
Primary remote gateway	IP address of the configured primary remote peer.	All levels
Backup remote gateway	IP address of the configured backup remote peer.	All levels

Table 18: show services ipsec-vpn ipsec security-associations Output Fields (*continued*)

Field Name	Field Description	Level of Output
State	State of the primary or backup interface: Active , Offline , or Standby . Both ES PICs are initialized to Offline . For primary and backup peers, State can be Active or Standby . If both peers are in a state of Standby , no connection exists yet between the two peers.	All levels
Failover counter	Number of times a PIC switched between primary and backup interfaces, or the number of times the tunnel switched between the primary and remote peers since the software has been activated.	All levels
Direction	Direction of the security association: inbound or outbound .	All levels
SPI	Value of the security parameter index.	All levels
AUX-SPI	Value of the auxiliary security parameter index. <ul style="list-style-type: none"> When the value of Protocol is AH or ESP, AUX-SPI is always 0. When the value of Protocol is AH+ESP, AUX-SPI is always a positive integer. 	All levels
Mode	Mode of the security association: <ul style="list-style-type: none"> transport—Protects single host-to-host protections. tunnel—Protects connections between security gateways. 	detail extensive
Type	Type of security association: <ul style="list-style-type: none"> manual—Security parameters require no negotiation. They are static, and are configured by the user. dynamic—Security parameters are negotiated by the IKE protocol. Dynamic security associations are not supported in transport mode. 	detail extensive
State	Status of the security association: <ul style="list-style-type: none"> Installed—The security association is installed in the security association database. (For transport mode security associations, the value of State must always be Installed.) Not installed—The security association is not installed in the security association database. 	detail extensive
Protocol	Protocol supported: <ul style="list-style-type: none"> transport mode supports Encapsulation Security Protocol (ESP) or Authentication Header (AH). tunnel mode supports ESP or AH+ESP. 	All levels
Authentication	Type of authentication used: hmac-md5-96 , hmac-sha1-96 , or none .	detail extensive
Encryption	Type of encryption algorithm used: aes-cbc (128 bits) , aes-cbc (192 bits) , aes-cbc (256 bits) , des-cbc , 3des-cbc , or None .	detail

Table 18: show services ipsec-vpn ipsec security-associations Output Fields (*continued*)

Field Name	Field Description	Level of Output
Soft lifetime Hard lifetime	<p>Each lifetime of a security association has two display options, hard and soft, one of which must be present for a dynamic security association. The hard lifetime specifies the lifetime of the SA. The soft lifetime, which is derived from the hard lifetime, informs the IPsec key management system that the SA is about to expire. This information allows the key management system to negotiate a new SA before the hard lifetime expires.</p> <ul style="list-style-type: none"> Expires in <i>seconds</i> seconds—Number of seconds left until the security association expires. Expires in <i>kilobytes</i> kilobytes—Number of kilobytes left until the security association expires. 	detail extensive
Anti-replay service	State of the service that prevents packets from being replayed: Enabled or Disabled .	detail extensive
Replay window size	Configured size, in packets, of the antireplay service window: 32 or 64 . The antireplay window size protects the receiver against replay attacks by rejecting old or duplicate packets. If the replay window size is 0 , antireplay service is disabled.	detail

Sample Output

show services ipsec-vpn ipsec security associations extensive

```

user@host> show services ipsec-vpn ipsec security-associations extensive
Service set: service-set-1
  Rule: _junos_, Term: term-1, Tunnel index: 1
  Local gateway: 101.101.101.2, Remote gateway: 14.14.14.4
  IPsec inside interface: sp-2/0/0.1 Local identity:
  ipv4_subnet(any:0,[0..7]=0.0.0.0/0)
  Remote identity: ipv4_subnet(any:0,[0..7]=0.0.0.0/0)
  Primary remote gateway: 101.101.101.1, State: Standby
  Backup remote gateway: 14.14.14.4, State: Active
  Failover counter: 1

  Direction: inbound, SPI: 3743521590, AUX-SPI: 0
  Mode: tunnel, Type: dynamic, State: Installed
  Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc
  Soft lifetime: Expires in 23043 seconds
  Hard lifetime: Expires in 23178 seconds
  Anti-replay service: Enabled, Replay window size: 64

  Direction: outbound, SPI: 2551045240, AUX-SPI: 0
  Mode: tunnel, Type: dynamic, State: Installed
  Protocol: ESP, Authentication: hmac-sha1-96, Encryption: 3des-cbc
  Soft lifetime: Expires in 23043 seconds
  Hard lifetime: Expires in 23178 seconds
  Anti-replay service: Enabled, Replay window size: 64

```

show system certificate

Syntax	<code>show system certificate</code> <code><certificate-id></code>
Release Information	Command introduced before Junos OS Release 7.4. Command introduced in Junos OS Release 11.1 for the QFX Series.
Description	(Encryption interface on M Series, T Series routers, and QFX Series switches only) Display installed certificates signed by the Juniper Networks certificate authority.
Options	none —Display all installed certificates signed by the Juniper Networks certificate authority. certificate-id —(Optional) Display the details of a particular certificate.
Required Privilege Level	maintenance
List of Sample Output	show system certificate on page 184 show system certificate (QFX Series) on page 184
Output Fields	Table 19 on page 183 lists the output fields for the show system certificate command. Output fields are listed in the approximate order in which they appear.

Table 19: show system certificate Output Fields

Field Name	Field Description
Certificate identifier	Unique identifier associated with a certificate. The certificate identifier is the common name of the subject.
Issuer Subject	Information about the certificate issuer and the distinguished name (DN) of the issuer, respectively: <ul style="list-style-type: none"> • Organization—Name of the owner's organization. • Organizational unit—Name of the owner's department. • Country—Two-character country code in which the owner's system is located. • State—State in the USA in which the owner is using the certificate. • Locality—City in which the owner's system is located. • Common name—Name of the owner of the certificate. • E-mail address—E-mail address of the owner of the certificate.
Validity	When a certificate is valid.
Signature algorithm	Encryption algorithm applied to the installed certificate.
Public key algorithm	Encryption algorithm applied to the public key.

Sample Output

show system certificate

```
user@host> show system certificate
Certificate identifier: Dallas-v3
Issuer:
Organization: Juniper Networks, Organizational unit: Juniper CA,
Country: US, State: CA, Locality: Sunnyvale, Common name: Dallas CA,
E-mail address:ca@juniper.net
Subject:
Organization: Juniper Networks, Organizational unit: Juniper CA,
Country: US, State: CA, Locality: Sunnyvale, Common name: Dallas-v3,
E-mail address:ca@juniper.net
Validity:
Not before: Mar 13 03:23:25 2004 GMT
Not after: Mar 24 03:23:25 2014 GMT
Signature algorithm: sha1WithRSAEncryption
Public key algorithm: dsaEncryption
```

show system certificate (QFX Series)

```
user@host> show system certificate
Certificate identifier: Dallas-v3
Issuer:
Organization: Juniper Networks, Organizational unit: Juniper CA,
Country: US, State: CA, Locality: Sunnyvale, Common name: Dallas CA,
E-mail address:ca@juniper.net
Subject:
Organization: Juniper Networks, Organizational unit: Juniper CA,
Country: US, State: CA, Locality: Sunnyvale, Common name: Dallas-v3,
E-mail address:ca@juniper.net
Validity:
Not before: Mar 13 03:23:25 2004 GMT
Not after: Mar 24 03:23:25 2014 GMT
Signature algorithm: sha1WithRSAEncryption
Public key algorithm: dsaEncryption
```


PART 5

Index

- [Index on page 187](#)

Index

Symbols

#, comments in configuration statements.....	xiv
(), in syntax descriptions.....	xiv
< >, in syntax descriptions.....	xiv
[], in configuration statements.....	xiv
{ }, in configuration statements.....	xiv
(pipe), in syntax descriptions.....	xiv

B

braces, in configuration statements.....	xiv
brackets	
angle, in syntax descriptions.....	xiv
square, in configuration statements.....	xiv

C

certificate revocation list See CRL	
certificates	
for IKE negotiation, displaying.....	172
installed, displaying.....	183
key pairs, generating.....	141
PKI	
CA certificates, clearing.....	134
CA certificates, displaying.....	158
CA certificates, loading manually.....	143
certificate revocation lists, clearing.....	136
certificate revocation lists, displaying.....	167
key pair, generating.....	146
local certificates, clearing.....	137
local certificates, displaying.....	169
local certificates, loading manually.....	149
local certificates, requesting	
manually.....	144
local certificates, requesting online.....	142
local certificates, requesting that CA	
install.....	147
local certificates, requests, clearing.....	135
local certificates, requests,	
displaying.....	165
provided by Juniper Networks, adding.....	150
signed certificate, obtaining.....	138
unsigned certificate, obtaining.....	140

clear security pki ca-certificate command.....	134
clear security pki certificate-request	
command.....	135
clear security pki crl command.....	136
clear security pki local-certificate command.....	137
comments, in configuration statements.....	xiv
conventions	
text and syntax.....	xiii
CRL.....	40
curly braces, in configuration statements.....	xiv
customer support.....	xv
contacting JTAC.....	xv

D

DEP	
configuration procedure.....	55
example configuration.....	127
operational mode commands.....	129
overview.....	55
digital certificates See certificates	
IPSec.....	53
documentation	
comments on.....	xv
dynamic endpoint tunneling See DEP	

F

font conventions.....	xiii
-----------------------	------

I

IKE	
adaptive services interfaces	
security associations, displaying.....	175
encryption services interfaces	
security associations, displaying.....	151
IPSec	
example configuration	
AS PIC IKE SAs	90
AS PIC IKE SAs with digital	
certificates.....	110
AS PIC manual SAs	72
AS PIC to ES PIC IKE SAs	99
DEP	127
ES PIC IKE SAs	80
ES PIC manual SAs	63
operational mode commands	
AS PIC IKE SAs.....	96
AS PIC IKE SAs with digital	
certificates.....	119
AS PIC manual SAs.....	78

AS PIC to ES PIC IKE SAs.....	106	request security key-pair command.....	141
DEP.....	129	request security pki ca-certificate enroll	
ES PIC IKE SAs.....	86	command.....	142
ES PIC manual SAs.....	69	request security pki ca-certificate load	
options		command.....	143
configuring multiple routed tunnels in a		request security pki generate-certificate-request	
single next-hop service set.....	51	command.....	144
CRL.....	40	request security pki generate-key-pair	
DEP.....	55	command.....	146
digital certificates.....	53	request security pki local-certificate enroll	
filter-based forwarding.....	45	command.....	147
Layer 3 VPNs.....	46	request security pki local-certificate load	
monitoring with SNMP.....	51	command.....	149
securing BGP sessions.....	48	request system certificate add command.....	150
securing OSPFv2 networks.....	49		
securing OSPFv3 networks.....	49		
overview.....	3	S	
system requirements.....	13	security certificate See certificates	
IPsec services		show ike security-associations command.....	151
adaptive services interfaces		show ipsec certificates command.....	155
IKE security associations, displaying.....	175	show ipsec security-associations command.....	162
IPSec security associations,		show security pki ca-certificate command.....	158
displaying.....	179	show security pki certificate-request	
encryption services interfaces		command.....	165
certificate database, displaying.....	155	show security pki crl command.....	167
IKE security associations, displaying.....	151	show security pki local-certificate command.....	169
IPSec security associations,		show services ipsec-vpn certificates	
displaying.....	162	command.....	172
K		show services ipsec-vpn ike security-associations	
key pair for digital certificate, generating.....	141	command.....	175
L		show services ipsec-vpn ipsec security-associations	
Layer 3 VPNs		command.....	179
IPSec.....	46	show system certificate command.....	183
M		show system statistics command.....	150
manuals		support, technical See technical support	
comments on.....	xv	syntax conventions.....	xiii
P		system requirements	
parentheses, in syntax descriptions.....	xiv	IPSec.....	13
PKI See certificates, PKI		T	
R		technical support	
request security certificate (signed)		contacting JTAC.....	xv
command.....	138		
request security certificate (unsigned)			
command.....	140		