



---

Junos<sup>®</sup> OS

## Services Interfaces Overview for Routing Devices

Release  
15.1



---

Modified: 2015-05-12

Juniper Networks, Inc.  
1133 Innovation Way  
Sunnyvale, California 94089  
USA  
408-745-2000  
[www.juniper.net](http://www.juniper.net)

Juniper Networks, Junos, Steel-Belted Radius, NetScreen, and ScreenOS are registered trademarks of Juniper Networks, Inc. in the United States and other countries. The Juniper Networks Logo, the Junos logo, and JunosE are trademarks of Juniper Networks, Inc. All other trademarks, service marks, registered trademarks, or registered service marks are the property of their respective owners.

Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

*Junos<sup>®</sup> OS Services Interfaces Overview for Routing Devices*

15.1

Copyright © 2015, Juniper Networks, Inc.  
All rights reserved.

The information in this document is current as of the date on the title page.

#### YEAR 2000 NOTICE

Juniper Networks hardware and software products are Year 2000 compliant. Junos OS has no known time-related limitations through the year 2038. However, the NTP application is known to have some difficulty in the year 2036.

#### END USER LICENSE AGREEMENT

The Juniper Networks product that is the subject of this technical documentation consists of (or is intended for use with) Juniper Networks software. Use of such software is subject to the terms and conditions of the End User License Agreement ("EULA") posted at <http://www.juniper.net/support/eula.html>. By downloading, installing or using such software, you agree to the terms and conditions of that EULA.

# Table of Contents

	About the Documentation . . . . .	vii
	Documentation and Release Notes . . . . .	vii
	Supported Platforms . . . . .	vii
	Using the Examples in This Manual . . . . .	vii
	Merging a Full Example . . . . .	viii
	Merging a Snippet . . . . .	viii
	Documentation Conventions . . . . .	ix
	Documentation Feedback . . . . .	xi
	Requesting Technical Support . . . . .	xi
	Self-Help Online Tools and Resources . . . . .	xi
	Opening a Case with JTAC . . . . .	xii
<b>Chapter 1</b>	<b>Overview . . . . .</b>	<b>13</b>
	Understanding Services PICs . . . . .	13
	Adaptive Services and Multiservices PICs . . . . .	13
	Encryption Services (ES) PIC . . . . .	14
	Multilink Services and Link Services PICs . . . . .	14
	Monitoring Services PICs . . . . .	14
	Tunnel Services PIC . . . . .	15
	Multiservices MIC and Multiservices MPC . . . . .	15
	Multiservices MIC and Multiservices MPC (MS-MIC and MS-MPC) Overview . . . . .	15
	Supported Platforms . . . . .	17
<b>Chapter 2</b>	<b>Configuration Overview . . . . .</b>	<b>19</b>
	Services Interface Naming Overview . . . . .	19
	Enabling Service Packages . . . . .	21
	Layer 2 Service Package Capabilities and Interfaces . . . . .	24
	Services Configuration Procedure . . . . .	25
	Example: Service Interfaces Configuration . . . . .	26
	Configuring Default Timeout Settings for Services Interfaces . . . . .	29
	Configuring System Logging for Services Interfaces . . . . .	30
<b>Chapter 3</b>	<b>Configuration Statements . . . . .</b>	<b>33</b>
	address (Interfaces) . . . . .	34
	applications (Services ALGs) . . . . .	35
	applications (Services CoS) . . . . .	35
	applications (Services IDS) . . . . .	36
	applications (Services NAT) . . . . .	36
	applications (Services Stateful Firewall) . . . . .	37
	close-timeout . . . . .	37
	cpu-load-threshold . . . . .	38
	facility-override . . . . .	39

	host (Interfaces) .....	40
	inactivity-timeout .....	40
	interfaces .....	41
	log-prefix (Interfaces) .....	41
	next-hop-service .....	42
	open-timeout .....	43
	port (System Log Messages) .....	43
	rule-set (Services Stateful Firewall) .....	44
	service-set (Interfaces) .....	44
	service-set (Services) .....	45
	services (CoS) .....	47
	services (IDS) .....	47
	services (IPsec VPN) .....	48
	services (Hierarchy) .....	48
	services (Interfaces) .....	49
	services (NAT) .....	49
	services (L2TP) .....	50
	services (L2TP System Logging) .....	50
	services (Stateful Firewall) .....	51
	services (System Logging) .....	52
	services-options .....	53
	session-limit .....	54
	syslog (Interfaces) .....	54
	tcp-tickles .....	55
<b>Chapter 4</b>	<b>Index .....</b>	<b>57</b>
	Index .....	59

# List of Tables

	<b>About the Documentation</b> .....	<b>vii</b>
	Table 1: Notice Icons .....	ix
	Table 2: Text and Syntax Conventions .....	x
<b>Chapter 1</b>	<b>Overview</b> .....	<b>13</b>
	Table 3: MX Series Routers that Support MS-MIC and MS-MPC .....	16
<b>Chapter 2</b>	<b>Configuration Overview</b> .....	<b>19</b>
	Table 4: AS and Multiservices PIC Services by Service Package, PIC, and Platform .....	22
	Table 5: System Log Message Severity Levels .....	31



# About the Documentation

- Documentation and Release Notes on page vii
- Supported Platforms on page vii
- Using the Examples in This Manual on page vii
- Documentation Conventions on page ix
- Documentation Feedback on page xi
- Requesting Technical Support on page xi

## Documentation and Release Notes

---

To obtain the most current version of all Juniper Networks® technical documentation, see the product documentation page on the Juniper Networks website at <http://www.juniper.net/techpubs/>.

If the information in the latest release notes differs from the information in the documentation, follow the product Release Notes.

Juniper Networks Books publishes books by Juniper Networks engineers and subject matter experts. These books go beyond the technical documentation to explore the nuances of network architecture, deployment, and administration. The current list can be viewed at <http://www.juniper.net/books>.

## Supported Platforms

---

For the features described in this document, the following platforms are supported:

- M Series
- MX Series
- T Series

## Using the Examples in This Manual

---

If you want to use the examples in this manual, you can use the **load merge** or the **load merge relative** command. These commands cause the software to merge the incoming configuration into the current candidate configuration. The example does not become active until you commit the candidate configuration.

If the example configuration contains the top level of the hierarchy (or multiple hierarchies), the example is a *full example*. In this case, use the **load merge** command.

If the example configuration does not start at the top level of the hierarchy, the example is a *snippet*. In this case, use the **load merge relative** command. These procedures are described in the following sections.

## Merging a Full Example

To merge a full example, follow these steps:

1. From the HTML or PDF version of the manual, copy a configuration example into a text file, save the file with a name, and copy the file to a directory on your routing platform.

For example, copy the following configuration to a file and name the file **ex-script.conf**. Copy the **ex-script.conf** file to the **/var/tmp** directory on your routing platform.

```
system {
  scripts {
    commit {
      file ex-script.xml;
    }
  }
}
interfaces {
  fxp0 {
    disable;
    unit 0 {
      family inet {
        address 10.0.0.1/24;
      }
    }
  }
}
```

2. Merge the contents of the file into your routing platform configuration by issuing the **load merge** configuration mode command:

```
[edit]
user@host# load merge /var/tmp/ex-script.conf
load complete
```

## Merging a Snippet

To merge a snippet, follow these steps:

1. From the HTML or PDF version of the manual, copy a configuration snippet into a text file, save the file with a name, and copy the file to a directory on your routing platform.

For example, copy the following snippet to a file and name the file **ex-script-snippet.conf**. Copy the **ex-script-snippet.conf** file to the **/var/tmp** directory on your routing platform.

```
commit {
  file ex-script-snippet.xml; }
```



2. Move to the hierarchy level that is relevant for this snippet by issuing the following configuration mode command:

```
[edit]
user@host# edit system scripts
[edit system scripts]
```

3. Merge the contents of the file into your routing platform configuration by issuing the **load merge relative** configuration mode command:

```
[edit system scripts]
user@host# load merge relative /var/tmp/ex-script-snippet.conf
load complete
```

For more information about the **load** command, see the *CLI User Guide*.

## Documentation Conventions

Table 1 on page ix defines notice icons used in this guide.

Table 1: Notice Icons

Icon	Meaning	Description
	Informational note	Indicates important features or instructions.
	Caution	Indicates a situation that might result in loss of data or hardware damage.
	Warning	Alerts you to the risk of personal injury or death.
	Laser warning	Alerts you to the risk of personal injury from a laser.
	Tip	Indicates helpful information.
	Best practice	Alerts you to a recommended use or implementation.

Table 2 on page x defines the text and syntax conventions used in this guide.

Table 2: Text and Syntax Conventions

Convention	Description	Examples
<b>Bold text like this</b>	Represents text that you type.	To enter configuration mode, type the <b>configure</b> command:  user@host> <b>configure</b>
Fixed-width text like this	Represents output that appears on the terminal screen.	user@host> <b>show chassis alarms</b>  No alarms currently active
<i>Italic text like this</i>	<ul style="list-style-type: none"> <li>Introduces or emphasizes important new terms.</li> <li>Identifies guide names.</li> <li>Identifies RFC and Internet draft titles.</li> </ul>	<ul style="list-style-type: none"> <li>A policy <i>term</i> is a named structure that defines match conditions and actions.</li> <li><i>Junos OS CLI User Guide</i></li> <li>RFC 1997, <i>BGP Communities Attribute</i></li> </ul>
<i>Italic text like this</i>	Represents variables (options for which you substitute a value) in commands or configuration statements.	Configure the machine's domain name:  [edit] root@# <b>set system domain-name</b> <i>domain-name</i>
Text like this	Represents names of configuration statements, commands, files, and directories; configuration hierarchy levels; or labels on routing platform components.	<ul style="list-style-type: none"> <li>To configure a stub area, include the <b>stub</b> statement at the [edit protocols ospf area area-id] hierarchy level.</li> <li>The console port is labeled <b>CONSOLE</b>.</li> </ul>
< > (angle brackets)	Encloses optional keywords or variables.	<b>stub &lt;default-metric metric&gt;;</b>
(pipe symbol)	Indicates a choice between the mutually exclusive keywords or variables on either side of the symbol. The set of choices is often enclosed in parentheses for clarity.	<b>broadcast   multicast</b>  <b>(string1   string2   string3)</b>
# (pound sign)	Indicates a comment specified on the same line as the configuration statement to which it applies.	<b>rsvp { # Required for dynamic MPLS only</b>
[ ] (square brackets)	Encloses a variable for which you can substitute one or more values.	<b>community name members [ community-ids ]</b>
Indentation and braces ( { } )	Identifies a level in the configuration hierarchy.	[edit] routing-options { static { route default { nexthop address; retain; } } }
;(semicolon)	Identifies a leaf statement at a configuration hierarchy level.	

---

#### GUI Conventions

---

Table 2: Text and Syntax Conventions (*continued*)

Convention	Description	Examples
<b>Bold text like this</b>	Represents graphical user interface (GUI) items you click or select.	<ul style="list-style-type: none"> <li>In the Logical Interfaces box, select <b>All Interfaces</b>.</li> <li>To cancel the configuration, click <b>Cancel</b>.</li> </ul>
<b>&gt;</b> (bold right angle bracket)	Separates levels in a hierarchy of menu selections.	In the configuration editor hierarchy, select <b>Protocols&gt;Ospf</b> .

## Documentation Feedback

We encourage you to provide feedback, comments, and suggestions so that we can improve the documentation. You can provide feedback by using either of the following methods:

- Online feedback rating system—On any page at the Juniper Networks Technical Documentation site at <http://www.juniper.net/techpubs/index.html>, simply click the stars to rate the content, and use the pop-up form to provide us with information about your experience. Alternately, you can use the online feedback form at <https://www.juniper.net/cgi-bin/docbugreport/>.
- E-mail—Send your comments to [techpubs-comments@juniper.net](mailto:techpubs-comments@juniper.net). Include the document or topic name, URL or page number, and software version (if applicable).

## Requesting Technical Support

Technical product support is available through the Juniper Networks Technical Assistance Center (JTAC). If you are a customer with an active J-Care or JNASC support contract, or are covered under warranty, and need post-sales technical support, you can access our tools and resources online or open a case with JTAC.

- JTAC policies—For a complete understanding of our JTAC procedures and policies, review the *JTAC User Guide* located at <http://www.juniper.net/us/en/local/pdf/resource-guides/7100059-en.pdf>.
- Product warranties—For product warranty information, visit <http://www.juniper.net/support/warranty/>.
- JTAC hours of operation—The JTAC centers have resources available 24 hours a day, 7 days a week, 365 days a year.

## Self-Help Online Tools and Resources

For quick and easy problem resolution, Juniper Networks has designed an online self-service portal called the Customer Support Center (CSC) that provides you with the following features:

- Find CSC offerings: <http://www.juniper.net/customers/support/>
- Search for known bugs: <http://www2.juniper.net/kb/>
- Find product documentation: <http://www.juniper.net/techpubs/>
- Find solutions and answer questions using our Knowledge Base: <http://kb.juniper.net/>
- Download the latest versions of software and review release notes:  
<http://www.juniper.net/customers/csc/software/>
- Search technical bulletins for relevant hardware and software notifications:  
<http://kb.juniper.net/InfoCenter/>
- Join and participate in the Juniper Networks Community Forum:  
<http://www.juniper.net/company/communities/>
- Open a case online in the CSC Case Management tool: <http://www.juniper.net/cm/>

To verify service entitlement by product serial number, use our Serial Number Entitlement (SNE) Tool: <https://tools.juniper.net/SerialNumberEntitlementSearch/>

## Opening a Case with JTAC

You can open a case with JTAC on the Web or by telephone.

- Use the Case Management tool in the CSC at <http://www.juniper.net/cm/>.
- Call 1-888-314-JTAC (1-888-314-5822 toll-free in the USA, Canada, and Mexico).

For international or direct-dial options in countries without toll-free numbers, see <http://www.juniper.net/support/requesting-support.html>.

## CHAPTER 1

# Overview

- [Understanding Services PICs on page 13](#)
- [Multiservices MIC and Multiservices MPC \(MS-MIC and MS-MPC\) Overview on page 15](#)
- [Supported Platforms on page 17](#)

### Understanding Services PICs

---

Interfaces used in router networks can be broadly classified into two:

- Networking interfaces, such as Ethernet and SONET interfaces, that primarily provide traffic connectivity. For more information on these interfaces, see the Junos<sup>®</sup> OS Network Interfaces.
- Services interfaces, such as Adaptive Services interfaces and Multiservices interfaces, that provide specific capabilities for manipulating traffic before it is delivered to its destination.

Services interfaces enable you to add services to your network incrementally. Junos OS supports the following services interfaces:

- [Adaptive Services and Multiservices PICs on page 13](#)
- [Encryption Services \(ES\) PIC on page 14](#)
- [Multilink Services and Link Services PICs on page 14](#)
- [Monitoring Services PICs on page 14](#)
- [Tunnel Services PIC on page 15](#)
- [Multiservices MIC and Multiservices MPC on page 15](#)

### Adaptive Services and Multiservices PICs

Adaptive Services [AS] PICs and Multiservices PICs enable you to perform multiple services on the same PIC by configuring a set of services and applications. The AS and Multiservices PICs offer a range of services that you can configure in one or more service sets. The following are some of the services you can configure on Adaptive services or multiservices interfaces:

- Class-of-service
- Intrusion detection service (IDS)

- IP Security (IPsec)
- Layer 2 tunneling protocols
- Monitoring services
- Network Address Translation (NAT)
- Stateful firewalls
- Voice services

For more information about these services, see *Adaptive Services Overview*.



**NOTE:** On Juniper Networks MX Series 3D Universal Edge Routers, the Multiservices DPC provides essentially the same capabilities as the Multiservices PIC. The interfaces on both platforms are configured in the same way.

## Encryption Services (ES) PIC

ES PIC provides a security suite for the IP version 4 (IPv4) and IP version 6 (IPv6) network layers. The suite provides functionality such as authentication of origin, data integrity, confidentiality, replay protection, and nonrepudiation of source. It also defines mechanisms for key generation and exchange, management of security associations, and support for digital certificates. For more information about encryption interfaces, see *Configuring Encryption Interfaces*.

## Multilink Services and Link Services PICs

Multilink Services and Link Services PICs enable you to split, recombine, and sequence datagrams across multiple logical data links. The goal of multilink operation is to coordinate multiple independent links between a fixed pair of systems, providing a virtual link with greater bandwidth than any of the members. The Junos OS supports two services PICs based on the Multilink Protocol: the Multilink Services PIC and the Link Services PIC.

For more information about multilink and link services interfaces, see *Link and Multilink Services Interfaces Feature Guide for Routing Devices*.

## Monitoring Services PICs

Monitoring Services PICs enable you to monitor traffic flow and export the monitored traffic. Monitoring traffic allows you to perform the following tasks:

- Gather and export detailed information about IPv4 traffic flows between source and destination nodes in your network.
- Sample all incoming IPv4 traffic on the monitoring interface and present the data in cflowd record format.
- Perform discard accounting on an incoming traffic flow.

- Encrypt or tunnel outgoing cflowd records, intercepted IPv4 traffic, or both.
- Direct filtered traffic to different packet analyzers and present the data in its original format.

For more information about flow monitoring interfaces, see *Monitoring, Sampling, and Collection Services Interfaces Feature Guide for Routing Devices*.

## Tunnel Services PIC

Tunnel Services PIC provides a private, secure path through an otherwise public network by encapsulating arbitrary packets inside a transport protocol. Tunnels connect discontinuous subnetworks and enable encryption interfaces, virtual private networks (VPNs), and MPLS.

For more information about tunnel interfaces, see *Tunnel Properties*.

## Multiservices MIC and Multiservices MPC

The Multiservices Modular Interfaces Card (MS-MIC) and the Multiservices Modular PIC Concentrator (MS-MPC), introduced in Junos OS Release 13.2, provide improved scaling and high performance. The MS-MIC and MS-MPC have enhanced memory (16 GB for MS-MIC, 32 GB per NPU of MS-MPC) and processing capabilities.

The services interfaces on MS-MPC and MS-MIC are identified in the configuration with an **ms-** prefix (for example, **ms-1/2/1**).

The following services packages come preinstalled and preconfigured on MS-MICs and MS-MPCs in Junos OS Release 13.2:

- Junos Traffic Vision (formerly referred to as Jflow/Flow Monitoring)
- Junos Address Aware (formerly referred to as NAT features)
- Junos VPN Site Secure (formerly referred to as IPsec features)
- Junos Network Secure (formerly referred to as the Stateful Firewall feature)

For information about MS-MIC and MS-MPC, see “[Multiservices MIC and Multiservices MPC \(MS-MIC and MS-MPC\) Overview](#)” on page 15.

### Related Documentation

- [Supported Platforms on page 17](#)
- [Packet Flow Through the Adaptive Services or Multiservices PIC](#)
- [Enabling Service Packages on page 21](#)
- [Services Configuration Procedure on page 25](#)
- [Services Interface Naming Overview on page 19](#)

## Multiservices MIC and Multiservices MPC (MS-MIC and MS-MPC) Overview

Juniper Networks supports the Multiservices Modular Interfaces Card (MS-MIC) and the Multiservices Modular PIC Concentrator (MS-MPC) that provide improved scaling and

high performance. The MS-MIC and MS-MPC have enhanced memory (16 GB for MS-MIC, 32 GB per NPU of MS-MPC) and processing capabilities.

The services interfaces on MS-MPC and MS-MIC are identified in the configuration with an **ms-** prefix (for example, **ms-1/2/1**). The following services packages come preinstalled and preconfigured on MS-MICs and MS-MPCs:

- Junos Traffic Vision (formerly referred to as Jflow)
- Junos Address Aware (formerly referred to as NAT features)
- Junos VPN Site Secure (formerly referred to as IPsec features)
- Junos Network Secure (formerly referred to as the Stateful Firewall feature)
- Junos Services Crypto Base PIC Package
- Junos Services Application Level Gateways



**NOTE:** You can check the default packages on an MS-MIC or MS-MPC by executing the **show extension-provider system packages interface ms-interace** operational mode command.

The MS-MIC and MS-MPC also support the captive portal content delivery (HTTP redirect) service package when configured for installation using the **set chassis** operational mode command.

Table 3 on page 16 lists the platforms on which the MS-MIC and MS-MPC are supported.

**Table 3: MX Series Routers that Support MS-MIC and MS-MPC**

	MX5	MX10	MX40	MX80	MX240	MX480	MX960	MX2010	MX2020
<b>MS-MIC</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>NOTE:</b> Only Junos Traffic Vision is supported.									
<b>MS-MPC</b>	No	No	No	No	Yes	Yes	Yes	No	No

You can install an MS-MIC on one of the following line cards:

- MPC-Type1
- MPC-Type2

#### Related Documentation

- [Understanding Services PICs on page 13](#)
- [Example: Configuring Junos VPN Site Secure on MS MIC and MS-MPC](#)
- [Example: Configuring Flow Monitoring on MS-MIC and MS-MPC](#)



## Supported Platforms

---

For information about which platforms support Adaptive Services and MultiServices PICs and their features, see [“Enabling Service Packages” on page 21](#).

For information about PIC support on a specific Juniper Networks M Series Multiservice Edge Router or T Series Core Router, see the appropriate *PIC Guide* for the platform.

For information about MS-DPC support on a specific MX Series router, see the appropriate *DPC Guide* for the platform.

For information about services supported on Juniper Networks SRX Series Services Gateways, see [Feature Explorer](#).

- Related Documentation**
- [Understanding Services PICs on page 13](#)
  - [Multiservices MIC and Multiservices MPC \(MS-MIC and MS-MPC\) Overview on page 15](#)



## CHAPTER 2

# Configuration Overview

- [Services Interface Naming Overview on page 19](#)
- [Enabling Service Packages on page 21](#)
- [Services Configuration Procedure on page 25](#)
- [Example: Service Interfaces Configuration on page 26](#)
- [Configuring Default Timeout Settings for Services Interfaces on page 29](#)
- [Configuring System Logging for Services Interfaces on page 30](#)

## Services Interface Naming Overview

---

Each interface has an interface name, which specifies the media type, the slot the FPC is located in, the location on the FPC that the PIC is installed in, and the PIC port. The interface name uniquely identifies an individual network connector in the system. You use the interface name when configuring interfaces and when enabling various functions and properties, such as routing protocols, on individual interfaces. The system uses the interface name when displaying information about the interface, for example, in the **show interfaces** command.

The interface name is represented by a physical part, a logical part, and a channel part in the following format:

**physical**<:channel>.logical

The channel part of the name is optional for all interfaces except channelized DS3, E1, OC12, and STM1 interfaces.

The physical part of an interface name identifies the physical device, which corresponds to a single physical network connector. This part of the interface name has the following format:

*type-fpc/pic/port*

**type** is the media type, which identifies the network device. For service interfaces, it can be one of the following:

- **ams**—Aggregated multiservices (AMS) interface. An AMS interface is a bundle of services interfaces that can function as a single interface. An AMS interface is denoted as **amsN** in the configuration, where **N** is a unique number that identifies an AMS interface (for example, **ams0**). The member interfaces in an AMS interface are identified in the configuration with an **mams-** prefix (for example, **mams-1/2/0**).
- **cp**—Flow collector interface.
- **es**—Encryption interface.
- **gr**—Generic routing encapsulation tunnel interface.
- **gre**—This interface is internally generated and not configurable.
- **ip**—IP-over-IP encapsulation tunnel interface.
- **ipip**—This interface is internally generated and not configurable.
- **ls**—Link services interface.
- **lsq**—Link services intelligent queuing (IQ) interface; also used for voice services.
- **mams**—Member interface in an AMS interface.
- **ml**—Multilink interface.
- **mo**—Monitoring services interface. The logical interface **mo-fpc/pic/port.16383** is an internally generated, nonconfigurable interface for router control traffic.
- **ms**—Multiservices interfaces on multiservices modular interfaces card (MS-MIC) and multiservices modular port concentrators (MS-MPC).
- **mt**—Multicast tunnel interface. This interface is automatically generated, but you can configure properties on it if needed.
- **mtun**—This interface is internally generated and not configurable.
- **rlsq**—Redundancy LSQ interface.
- **rsp**—Redundancy adaptive services interface.
- **si**—Services inline interface, configured on MX3D Series routers only.
- **sp**—Adaptive services interface. The logical interface **sp-fpc/pic/port.16383** is an internally generated, nonconfigurable interface for router control traffic.
- **tap**—This interface is internally generated and not configurable.
- **vt**—Virtual loopback tunnel interface.

**Related  
Documentation**

- [Understanding Services PICs on page 13](#)
- [Understanding Aggregated Multiservices Interfaces](#)
- [Examples: Configuring Services Interfaces](#)

## Enabling Service Packages

For AS PICs, Multiservices PICs, Multiservices DPCs, and the internal Adaptive Services Module (ASM) in the M7i router, there are two service packages: Layer 2 and Layer 3. Both service packages are supported on all adaptive services interfaces, but you can enable only one service package per PIC, with the exception of a combined package supported on the ASM. On a single router, you can enable both service packages by installing two or more PICs on the platform.



**NOTE:** Graceful Routing Engine switchover (GRES) is automatically enabled on all services PICs and DPCs except the ES PIC. It is supported on all M Series, MX Series, and T Series routers except for TX Matrix routers. Layer 3 services should retain state after switchover, but Layer 2 services will restart. For IPsec services, Internet Key Exchange (IKE) negotiations are not stored and must be restarted after switchover. For more information about GRES, see the *Junos OS High Availability Library for Routing Devices*.

You enable service packages per PIC, not per port. For example, if you configure the Layer 2 service package, the entire PIC uses the configured package. To enable a service package, include the service-package statement at the `[edit chassis fpc slot-number pic pic-number adaptive-services]` hierarchy level, and specify `layer-2` or `layer-3`:

```
[edit chassis fpc slot-number pic pic-number adaptive-services]
service-package (layer-2 | layer-3);
```

To determine which package an AS PIC supports, issue the `show chassis hardware` command: if the PIC supports the Layer 2 package, it is listed as **Link Services II**, and if it supports the Layer 3 package, it is listed as **Adaptive Services II**. To determine which package a Multiservices PIC supports, issue the `show chassis pic fpc-slot slot-number pic-slot slot-number` command. The **Package** field displays the value **Layer-2** or **Layer-3**.



**NOTE:** The ASM has a default option (`layer-2-3`) that combines the features available in the Layer 2 and Layer 3 service packages.

After you commit a change in the service package, the PIC is taken offline and then brought back online immediately. You do not need to manually take the PIC offline and online.



**NOTE:** Changing the service package causes all state information associated with the previous service package to be lost. You should change the service package only when there is no active traffic going to the PIC.

The services supported in each package differ by PIC and platform type. [Table 4 on page 22](#) lists the services supported within each service package for each PIC and platform.

On the AS and Multiservices PICs, *link services* support includes Junos OS CoS components, LFI (FRF.12), MLFR end-to-end (FRF.15), MLFR UNI NNI (FRF.16), MLPPP (RFC 1990), and multiclass MLPPP. For more information, see “[Layer 2 Service Package Capabilities and Interfaces](#)” on page 24 and *Layer 2 Service Package Capabilities and Interfaces*.



**NOTE:** The AS PIC II for Layer 2 Service is dedicated to supporting the Layer 2 service package only.

For additional information about Layer 3 services, see the *Junos OS, Release 15.1*.

**Table 4: AS and Multiservices PIC Services by Service Package, PIC, and Platform**

Services	ASM	AS/AS2 PICs and Multiservices PICs	AS/AS2 and Multiservices PICs	AS2 and Multiservices PICs	AS2 and Multiservices PICs
Layer 2 Service Package (Only)	M7i	M7i, M10i, and M20	M40e and M120	M320, T320, and T640	TX Matrix
Link Services:					
• Link services	Yes	Yes	Yes	Yes	No
• Multiclass MLPPP	Yes	Yes	Yes	Yes	No
Voice Services:					
• CRTP and LFI	Yes	Yes	Yes	Yes	No
• CRTP and MLPPP	Yes	Yes	Yes	Yes	No
• CRTP over PPP (without MLPPP)	Yes	Yes	Yes	Yes	No
Layer 3 Service Package (Only)	M7i	M7i, M10i, and M20	M40e and M120	M320, T320, and T640	TX Matrix
Security Services:					
• CoS	Yes	Yes	Yes	Yes	No
• Intrusion detection system (IDS)	Yes	Yes	Yes	Yes	No
• IPsec	Yes	Yes	Yes	Yes	No
• NAT	Yes	Yes	Yes	Yes	No
• Stateful firewall	Yes	Yes	Yes	Yes	No
Accounting Services:					

Table 4: AS and Multiservices PIC Services by Service Package, PIC, and Platform (*continued*)

Services	ASM	AS/AS2 PICs and Multiservices PICs	AS/AS2 and Multiservices PICs	AS2 and Multiservices PICs	AS2 and Multiservices PICs
• Active monitoring	Yes	Yes	Yes	Yes	Yes
• Dynamic flow capture (Multiservices 400 PIC only)	No	No	No	Yes	No
• Flow-tap	Yes	Yes	Yes (M40e only)	Yes	No
• Passive monitoring (Multiservices 400 PIC only)	No	Yes	Yes (M40e only)	Yes	No
• Port mirroring	Yes	Yes	Yes	Yes	Yes
LNS Services:					
• L2TP LNS	Yes	Yes (M7i and M10i only)	Yes (M120 only)	No	No
Voice Services:					
• BGF	Yes	Yes	Yes	Yes	No
Layer 2 and Layer 3 Service Package (Common Features)	M7i	M7i, M10i, and M20	M40e and M120	M320, T320, and T640	TX Matrix
RPM Services:					
• RPM probe timestamping	Yes	Yes	Yes	Yes	No
Tunnel Services:					
• GRE ( <i>gr-fpc/pic/port</i> )	Yes	Yes	Yes	Yes	Yes
• GRE fragmentation ( <i>clear-dont-fragment-bit</i> )	Yes	Yes	Yes	No	No
• GRE key	Yes	Yes	Yes	Yes	No
• IP-IP tunnels ( <i>ip-fpc/pic/port</i> )	Yes	Yes	Yes	Yes	Yes
• Logical tunnels ( <i>lt-fpc/pic/port</i> )	No	No	No	No	No
• Multicast tunnels ( <i>mt-fpc/pic/port</i> )	Yes	Yes	Yes	Yes	Yes
• PIM de-encapsulation ( <i>pd-fpc/pic/port</i> )	Yes	Yes	Yes	Yes	Yes

Table 4: AS and Multiservices PIC Services by Service Package, PIC, and Platform (*continued*)

Services	ASM	AS/AS2 PICs and Multiservices PICs	AS/AS2 and Multiservices PICs	AS2 and Multiservices PICs	AS2 and Multiservices PICs
• PIM encapsulation ( <b>pe-fpc/pic/port</b> )	Yes	Yes	Yes	Yes	Yes
• Virtual tunnels ( <b>vt-fpc/pic/port</b> )	Yes	Yes	Yes	Yes	Yes

## Layer 2 Service Package Capabilities and Interfaces

When you enable the Layer 2 service package, you can configure link services. On the AS and Multiservices PICs and the ASM, link services include support for the following:

- Junos CoS components—*Layer 2 Service Package Capabilities and Interfaces* describes how the Junos CoS components work on link services IQ (**lsq**) interfaces. For detailed information about Junos CoS components, see the *Class of Service Feature Guide for Routing Devices*.
- LFI on Frame Relay links using FRF.12 end-to-end fragmentation—The standard for FRF.12 is defined in the specification FRF.12, *Frame Relay Fragmentation Implementation Agreement*.
- LFI on MLPPP links.
- MLFR UNI NNI (FRF.16)—The standard for FRF.16 is defined in the specification FRF.16.1, *Multilink Frame Relay UNI/NNI Implementation Agreement*.
- MLPPP (RFC 1990)
- MLFR end-to-end (FRF.15)

For the LSQ interface on the AS and Multiservices PICs, the configuration syntax is almost the same as for Multilink and Link Services PICs. The primary difference is the use of the interface-type descriptor **lsq** instead of **ml** or **ls**. When you enable the Layer 2 service package, the following interfaces are automatically created:

```

gr-fpc/pic/port
ip-fpc/pic/port
lsq-fpc/pic/port
lsq-fpc/pic/port:0
...
lsq-fpc/pic/port:N
mt-fpc/pic/port
pd-fpc/pic/port
pe-fpc/pic/port
sp-fpc/pic/port
vt-fpc/pic/port

```

Interface types **gr**, **ip**, **mt**, **pd**, **pe**, and **vt** are standard tunnel interfaces that are available on the AS and Multiservices PICs whether you enable the Layer 2 or the Layer 3 service package. These tunnel interfaces function the same way for both service packages,



except that the Layer 2 service package does not support some tunnel functions, as shown in [Table 4 on page 22](#).

Interface type `lsq-fpc/pic/port` is the physical link services IQ (`lsq`) interface. Interface types `lsq-fpc/pic/port:0` through `lsq-fpc/pic/port:N` represent FRF.16 bundles. These interface types are created when you include the `mlfr-uni-nni-bundles` statement at the `[edit chassis fpc slot-number pic pic-number]` option. For more information, see *Layer 2 Service Package Capabilities and Interfaces* and *Link and Multilink Services Interfaces Feature Guide for Routing Devices*.



**NOTE:** Interface type `sp` is created because it is needed by the Junos OS. For the Layer 2 service package, the `sp` interface is not configurable, but you should not disable it.

#### Related Documentation

- [Understanding Services PICs on page 13](#)
- [Adaptive Services Overview](#)
- [Supported Platforms on page 17](#)
- [Packet Flow Through the Adaptive Services or Multiservices PIC](#)
- [Services Configuration Procedure on page 25](#)

## Services Configuration Procedure

You follow these general steps to configure services:

1. Define application objects by configuring statements at the `[edit applications]` hierarchy level.
2. Define service rules by configuring statements at the `[edit services (ids | ipsec-vpn | nat | stateful-firewall) rule]` hierarchy level.
3. Group the service rules by configuring the `rule-set` statement at the `[edit services (ids | ipsec-vpn | nat | stateful-firewall)]` hierarchy level.
4. Group service rule sets under a service-set definition by configuring the `service-set` statement at the `[edit services]` hierarchy level.
5. Apply the service set on an interface by including the `service-set` statement at the `[edit interfaces interface-name unit logical-unit-number family inet service (input | output)]` hierarchy level. Alternatively, you can configure logical interfaces as a next-hop destination by including the `next-hop-service` statement at the `[edit services service-set service-set-name]` hierarchy level.



**NOTE:** You can configure IDS, NAT, and stateful firewall service rules within the same service set. You must configure IPsec services in a separate service set, although you can apply both service sets to the same PIC.

- Related Documentation**
- [Understanding Services PICs on page 13](#)
  - [Enabling Service Packages on page 21](#)
  - [Supported Platforms on page 17](#)

---

## Example: Service Interfaces Configuration

The following configuration includes all the items necessary to configure services on an interface.

```
[edit]
interfaces {
  fe-0/1/0 {
    unit 0 {
      family inet {
        service {
          input {
            service-set Firewall-Set;
          }
          output {
            service-set Firewall-Set;
          }
        }
        address 10.1.3.2/24;
      }
    }
  }
  fe-0/1/1 {
    unit 0 {
      family inet {
        filter {
          input Sample;
        }
        address 172.16.1.2/24;
      }
    }
  }
  sp-1/0/0 {
    unit 0 {
      family inet {
        address 172.16.1.3/24 {
        }
      }
    }
  }
}
forwarding-options {
  sampling {
    input {
      family inet {
        rate 1;
      }
    }
  }
}
```

```
output {
  cflowd 10.1.3.1 {
    port 2055;
    version 5;
  }
  flow-inactive-timeout 15;
  flow-active-timeout 60;
  interface sp-1/0/0 {
    engine-id 1;
    engine-type 136;
    source-address 10.1.3.2;
  }
}
}
}
firewall {
  filter Sample {
    term Sample {
      then {
        count Sample;
        sample;
        accept;
      }
    }
  }
}
}
services {
  stateful-firewall {
    rule Rule1 {
      match-direction input;
      term 1 {
        from {
          application-sets Applications;
        }
        then {
          accept;
        }
      }
      term accept {
        then {
          accept;
        }
      }
    }
    rule Rule2 {
      match-direction output;
      term Local {
        from {
          source-address {
            10.1.3.2/32;
          }
        }
        then {
          accept;
        }
      }
    }
  }
}
```

```
    }
  }
  ids {
    rule Attacks {
      match-direction output;
      term Match {
        from {
          application-sets Applications;
        }
        then {
          logging {
            syslog;
          }
        }
      }
    }
  }
}
nat {
  pool public {
    address-range low 172.16.2.1 high 172.16.2.32;
    port automatic;
  }
  rule Private-Public {
    match-direction input;
    term Translate {
      then {
        translated {
          source-pool public;
          translation-type source napt-44;
        }
      }
    }
  }
}
service-set Firewall-Set {
  stateful-firewall-rules Rule1;
  stateful-firewall-rules Rule2;
  nat-rules Private-Public;
  ids-rules Attacks;
  interface-service {
    service-interface sp-1/0/0;
  }
}
applications {
  application ICMP {
    application-protocol icmp;
  }
  application FTP {
    application-protocol ftp;
    destination-port ftp;
  }
  application-set Applications {
    application ICMP;
    application FTP;
  }
}
```

```
}
```

## Configuring Default Timeout Settings for Services Interfaces

You can specify global default settings for certain timers that apply for the entire interface. There are three statements of this type:

- **inactivity-timeout**—Sets the inactivity timeout period for established flows, after which they are no longer valid.
- **open-timeout**—Sets the timeout period for Transmission Control Protocol (TCP) session establishment, for use with SYN-cookie defenses against network intrusion.
- **close-timeout**—Sets the timeout period for Transmission Control Protocol (TCP) session tear-down.

To configure a setting for the inactivity timeout period, include the **inactivity-timeout** statement at the **[edit interfaces *interface-name* services-options]** hierarchy level:

```
[edit interfaces interface-name services-options]
  inactivity-timeout seconds;
```

The default value is 30 seconds. The range of possible values is from 4 through 86,400 seconds. Any value you configure in the application protocol definition overrides the value specified here; for more information, see *Configuring Application Protocol Properties*.

To configure a setting for the TCP session establishment timeout period, include the **open-timeout** statement at the **[edit interfaces *interface-name* services-options]** hierarchy level:

```
[edit interfaces interface-name services-options]
  open-timeout seconds;
```

The default value is 5 seconds. The range of possible values is from 4 through 224 seconds. Any value you configure in the intrusion detection service (IDS) definition overrides the value specified here; for more information, see *Intrusion Detection Properties*.

To configure a setting for the TCP session teardown timeout period, include the **close-timeout** statement at the **[edit interfaces *interface-name* services-options]** hierarchy level:

```
[edit interfaces interface-name services-options]
  close-timeout seconds;
```

The default value is 1 second. The range of possible values is from 2 through 300 seconds.

### Use of Keep-Alive Messages for Greater Control of TCP Inactivity Timeouts

Keep-alive messages are generated automatically to prevent TCP inactivity timeouts. The default number of keep-alive messages is 4. However, you can configure the number of keep-alive messages by entering the **tcp-tickles** statement at the **[edit interfaces *interface-name* service-options]** hierarchy level.

When timeout is generated for a bidirectional TCP flow, keep-alive packets are sent to reset the timer. If number of consecutive keep-alive packets sent in a flow reaches the default or configured limit, the conversation is deleted. There are several possible scenarios, depending on the setting of the **inactivity-timer** and the default or configured maximum number of keep-alive messages.

- If the configured value of keep-alive messages is zero and **inactivity-timeout** is NOT configured (in which case the default timeout value of 30 is used), no keep-alive packets are sent. The conversation is deleted when any flow in the conversation is idle for more than 30 seconds.
- If the configured value of keep-alive messages is zero and the **inactivity-timeout** is configured, no keep-alive packets are sent, and the conversation is deleted when any flow in the conversation is idle for more than the configured timeout value.
- If the default or configured maximum number of keep-alive messages is some positive integer, and any of the flows in a conversation is idle for more than the default or configured value for **inactivity-timeout** keep-alive packets are sent. If hosts do not respond to the configured number of consecutive keep-alive packets, the conversation is deleted. The interval between keep-alive packets will be 1 second. However, if the host sends back an ACK packet, the corresponding flow becomes active, and keep-alive packets are not sent until the flow becomes idle again.

**Related  
Documentation**

- [Understanding Services PICs on page 13](#)
- [Configuring the Address and Domain for Services Interfaces](#)
- [Configuring System Logging for Services Interfaces on page 30](#)
- [Applying Filters and Services to Interfaces](#)
- [Examples: Configuring Services Interfaces](#)

---

## Configuring System Logging for Services Interfaces

You specify properties that control how system log messages are generated for the interface as a whole. If you configure different values for the same properties at the **[edit services service-set service-set-name]** hierarchy level, the service-set values override the values configured for the interface. For more information on configuring service-set properties, see *Configuring System Logging for Service Sets*.

To configure interface-wide default system logging values, include the **syslog** statement at the **[edit interfaces interface-name services-options]** hierarchy level:

```
[edit interfaces interface-name services-options]
syslog {
  host hostname {
    services severity-level;
    facility-override facility-name;
    log-prefix prefix-value;
    port port-number;
  }
}
```

Configure the **host** statement with a hostname or an IP address that specifies the system log target server. The hostname **local** directs system log messages to the Routing Engine. For external system log servers, the hostname must be reachable from the same routing instance to which the initial data packet (that triggered session establishment) is delivered. You can specify only one system logging hostname.

Table 5 on page 31 lists the severity levels that you can specify in configuration statements at the **[edit interfaces *interface-name* services-options syslog host *hostname*]** hierarchy level. The levels from **emergency** through **info** are in order from highest severity (greatest effect on functioning) to lowest.

**Table 5: System Log Message Severity Levels**

Severity Level	Description
<b>any</b>	Includes all severity levels
<b>emergency</b>	System panic or other condition that causes the router to stop functioning
<b>alert</b>	Conditions that require immediate correction, such as a corrupted system database
<b>critical</b>	Critical conditions, such as hard drive errors
<b>error</b>	Error conditions that generally have less serious consequences than errors in the emergency, alert, and critical levels
<b>warning</b>	Conditions that warrant monitoring
<b>notice</b>	Conditions that are not errors but might warrant special handling
<b>info</b>	Events or nonerror conditions of interest

We recommend setting the system logging severity level to **error** during normal operation. To monitor PIC resource usage, set the level to **warning**. To gather information about an intrusion attack when an intrusion detection system error is detected, set the level to **notice** for a specific interface. To debug a configuration or log Network Address Translation (NAT) functionality, set the level to **info**.

For more information about system log messages, see the *Junos OS System Log Messages Reference*.

To use one particular facility code for all logging to the specified system log host, include the **facility-override** statement at the **[edit interfaces *interface-name* services-options syslog host *hostname*]** hierarchy level:

```
[edit interfaces interface-name services-options]
  facility-override facility-name;
```

The supported facilities include **authorization**, **daemon**, **ftp**, **kernel**, **user**, and **local0** through **local7**.

To specify a text prefix for all logging to this system log host, include the **log-prefix** statement at the **[edit interfaces *interface-name* services-options syslog host *hostname*]** hierarchy level:

```
[edit interfaces interface-name services-options]  
log-prefix prefix-value;
```

**Related  
Documentation**

- [Understanding Services PICs on page 13](#)
- [Configuring the Address and Domain for Services Interfaces](#)
- [Configuring Default Timeout Settings for Services Interfaces on page 29](#)
- [Applying Filters and Services to Interfaces](#)
- [Examples: Configuring Services Interfaces](#)



## CHAPTER 3

# Configuration Statements

- [address \(Interfaces\) on page 34](#)
- [applications \(Services ALGs\) on page 35](#)
- [applications \(Services CoS\) on page 35](#)
- [applications \(Services IDS\) on page 36](#)
- [applications \(Services NAT\) on page 36](#)
- [applications \(Services Stateful Firewall\) on page 37](#)
- [close-timeout on page 37](#)
- [cpu-load-threshold on page 38](#)
- [facility-override on page 39](#)
- [host \(Interfaces\) on page 40](#)
- [inactivity-timeout on page 40](#)
- [interfaces on page 41](#)
- [log-prefix \(Interfaces\) on page 41](#)
- [next-hop-service on page 42](#)
- [open-timeout on page 43](#)
- [port \(System Log Messages\) on page 43](#)
- [rule-set \(Services Stateful Firewall\) on page 44](#)
- [service-set \(Interfaces\) on page 44](#)
- [service-set \(Services\) on page 45](#)
- [services \(CoS\) on page 47](#)
- [services \(IDS\) on page 47](#)
- [services \(IPsec VPN\) on page 48](#)
- [services \(Hierarchy\) on page 48](#)
- [services \(Interfaces\) on page 49](#)
- [services \(NAT\) on page 49](#)
- [services \(L2TP\) on page 50](#)
- [services \(L2TP System Logging\) on page 50](#)
- [services \(Stateful Firewall\) on page 51](#)

- [services \(System Logging\) on page 52](#)
- [services-options on page 53](#)
- [session-limit on page 54](#)
- [syslog \(Interfaces\) on page 54](#)
- [tcp-tickles on page 55](#)

---

## address (Interfaces)

---

<b>Syntax</b>	<code>address <i>address</i> {     ... }</code>
<b>Hierarchy Level</b>	[edit interfaces <i>interface-name</i> unit (Interfaces) <i>logical-unit-number</i> family (Interfaces) <i>family</i> ], [edit logical-systems <i>logical-system-name</i> interfaces <i>interface-name</i> unit (Interfaces) <i>logical-unit-number</i> family (Interfaces) <i>family</i> ]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4.
<b>Description</b>	Configure the interface address.
<b>Options</b>	<i>address</i> —Address of the interface.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <i>Junos OS Network Interfaces Library for Routing Devices</i> for other statements that do not affect services interfaces.</li><li>• <i>Configuring the Address and Domain for Services Interfaces</i></li><li>• <i>Junos OS Network Interfaces Library for Routing Devices</i></li></ul>

## applications (Services ALGs)

---

<b>Syntax</b>	<code>applications { ... }</code>
<b>Hierarchy Level</b>	[edit]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4.
<b>Description</b>	Define the applications used in services.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <i>ALG Descriptions</i></li> <li>• <i>Configuring Application Sets</i></li> <li>• <i>Configuring Application Protocol Properties</i></li> <li>• <i>Examples: Configuring Application Protocols</i></li> <li>• <i>Verifying the Output of ALG Sessions</i></li> </ul>

## applications (Services CoS)

---

<b>Syntax</b>	<code>applications [ <i>application-name</i> ];</code>
<b>Hierarchy Level</b>	[edit <a href="#">services</a> cos rule <i>rule-name</i> term <i>term-name</i> from]
<b>Release Information</b>	Statement introduced in Junos OS Release 8.1.
<b>Description</b>	Define one or more applications to which the CoS services apply.
<b>Options</b>	<i>application-name</i> —Name of the target application.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <i>Configuring Match Conditions in a CoS Rule</i></li> <li>• <i>Configuring CoS Rules</i></li> </ul>

## applications (Services IDS)

---

<b>Syntax</b>	<code>applications [ <i>application-name</i> ];</code>
<b>Hierarchy Level</b>	[edit <a href="#">services</a> ids rule <i>rule-name</i> term <i>term-name</i> from]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4.
<b>Description</b>	Define one or more applications to which IDS applies.
<b>Options</b>	<i>application-name</i> —Name of the target application.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <i>Configuring IDS Rules</i></li></ul>

## applications (Services NAT)

---

<b>Syntax</b>	<code>applications [ <i>application-name</i> ];</code>
<b>Hierarchy Level</b>	[edit <a href="#">services</a> nat rule <i>rule-name</i> term <i>term-name</i> from]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4.
<b>Description</b>	Define one or more application protocols to which the NAT services apply.
<b>Options</b>	<i>application-name</i> —Name of the target application.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <i>Network Address Translation Rules Overview</i></li></ul>

## applications (Services Stateful Firewall)

---

<b>Syntax</b>	<code>applications [ <i>application-name</i> ];</code>
<b>Hierarchy Level</b>	[edit <a href="#">services</a> stateful-firewall rule <i>rule-name</i> term <i>term-name</i> from]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4.
<b>Description</b>	Define one or more applications to which the stateful firewall services apply.
<b>Options</b>	<i>application-name</i> —Name of the target application.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring Stateful Firewall Rules</a></li> </ul>

## close-timeout

---

<b>Syntax</b>	<code>close-timeout <i>seconds</i>;</code>
<b>Hierarchy Level</b>	[edit interfaces <i>interface-name</i> <a href="#">services-options</a> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 12.3.
<b>Description</b>	Configure the timeout period for Transmission Control Protocol (TCP) session tear-down.
<b>Options</b>	<i>seconds</i> —Timeout period. <b>Default:</b> 1 second <b>Range:</b> 2 through 300 seconds
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring Default Timeout Settings for Services Interfaces on page 29</a></li> </ul>

## cpu-load-threshold

---

Syntax	cpu-load-threshold <i>percentage</i> ;
Hierarchy Level	[edit interfaces <i>interface-name</i> <b>services-options</b> session-limit]
Release Information	Statement introduced in Release 13.2.
Description	Regulate the usage of CPU resources. When the CPU usage exceeds the value (percentage of the total available CPU resources) configured for <b>cpu-load-threshold</b> , the system reduces the rate of new sessions so that the existing sessions are not affected by low CPU availability. The CPU utilization is constantly monitored, and if the CPU usage remains in overload state—that is, above the <b>cpu-load-threshold</b> value configured—for a continuous period of 5 seconds, Junos OS reduces the session rate value configured at <b>edit interfaces <i>interface-name</i> services-options session-limit rate</b> by 10%. This is repeated until the CPU utilization comes down to the configured limit.
Required Privilege Level	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
Related Documentation	<ul style="list-style-type: none"><li>• <a href="#">services-options on page 53</a></li></ul>

---

## facility-override

---

<b>Syntax</b>	<code>facility-override <i>facility-name</i>;</code>
<b>Hierarchy Level</b>	[edit <a href="#">interfaces</a> <i>interface-name</i> <a href="#">services-options</a> <a href="#">syslog</a> <a href="#">host</a> <i>hostname</i> ]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4.
<b>Description</b>	Override the default facility for system log reporting.
<b>Options</b>	<p><i>facility-name</i>—Name of the facility that overrides the default assignment. Valid entries include:</p> <ul style="list-style-type: none"><li><code>authorization</code></li><li><code>daemon</code></li><li><code>ftp</code></li><li><code>kernel</code></li><li><code>local0</code> through <code>local7</code></li><li><code>user</code></li></ul>
<b>Required Privilege Level</b>	<p>interface—To view this statement in the configuration.</p> <p>interface-control—To add this statement to the configuration.</p>
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring System Logging for Services Interfaces on page 30</a></li></ul>

## host (Interfaces)

---

<b>Syntax</b>	<pre>host <i>hostname</i> {     <i>services severity-level</i>;     <i>facility-override facility-name</i>;     <i>log-prefix prefix-value</i>;     <i>port port-number</i>; }</pre>
<b>Hierarchy Level</b>	[edit <a href="#">interfaces interface-name services-options syslog</a> ]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4.
<b>Description</b>	Specify the hostname for the system logging utility.
<b>Options</b>	<p><i>hostname</i>—Name of the system logging utility host machine. This can be the local Routing Engine or an external server address.</p> <p>The remaining statements are explained separately.</p>
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Applying Filters and Services to Interfaces</a></li></ul>

## inactivity-timeout

---

<b>Syntax</b>	<pre>inactivity-timeout <i>seconds</i>;</pre>
<b>Hierarchy Level</b>	[edit <a href="#">interfaces interface-name services-options</a> ]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4.
<b>Description</b>	Configure the inactivity timeout period for established flows. The timeout value configured in the application protocol definition overrides this value.
<b>Options</b>	<p><i>seconds</i>—Timeout period.</p> <p><b>Default:</b> 30 seconds</p> <p><b>Range:</b> 4 through 86,400 seconds</p>
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring Default Timeout Settings for Services Interfaces on page 29</a></li></ul>



## interfaces

---


<b>Syntax</b>	<code>interfaces { ... }</code>
<b>Hierarchy Level</b>	[edit]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4.
<b>Description</b>	Configure interfaces on the router.
<b>Default</b>	The management and internal Ethernet interfaces are automatically configured. You must configure all other interfaces.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <i>Junos OS Network Interfaces Library for Routing Devices</i></li> </ul>

## log-prefix (Interfaces)

---

<b>Syntax</b>	<code>log-prefix <i>prefix-value</i>;</code>
<b>Hierarchy Level</b>	[edit <a href="#">interfaces</a> <i>interface-name</i> <a href="#">services-options</a> <code>syslog</code> <i>host</i> <i>hostname</i> ]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4.
<b>Description</b>	Set the system logging prefix value.
<b>Options</b>	<i>prefix-value</i> —System logging prefix value.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <i>Junos OS Services Interfaces Library for Routing Devices</i></li> <li>• <a href="#">Configuring System Logging for Services Interfaces on page 30</a></li> </ul>

## next-hop-service

<b>Syntax</b>	<pre> next-hop-service {   inside-service-interface <i>interface-name.unit-number</i>;   outside-service-interface <i>interface-name.unit-number</i>;   outside-service-interface-type <i>interface-type</i>;   service-interface-pool <i>name</i>; } </pre>
<b>Hierarchy Level</b>	[edit <a href="#">services service-set service-set-name</a> ]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4. <b>service-interface-pool</b> option added in Junos OS Release 9.3.
<b>Description</b>	Specify interface names or a service interface pool for the forwarding next-hop service set. You cannot specify both a service interface pool and an inside or outside interface.
<b>Options</b>	<p><b>inside-service-interface <i>interface-name.unit-number</i></b>—Name and logical unit number of the service interface associated with the service set applied inside the network.</p> <p><b>outside-service-interface <i>interface-name.unit-number</i></b>—Name and logical unit number of the service interface associated with the service set applied outside the network.</p> <p><b>outside-service-interface-type <i>interface-type</i></b>—Identifies the interface type of the service interface associated with the service set applied outside the network. For inline IP reassembly, set the interface type to local.</p> <p><b>service-interface-pool <i>name</i></b>—Name of the pool of logical interfaces configured at the [edit <a href="#">services service-interface-pools pool pool-name</a>] hierarchy level. You can configure a service interface pool only if the service set has a PGCP rule configured. The service set cannot contain any other type of rule.</p>
<div>  <p><b>NOTE:</b> <b>service-interface-pool</b> is not applicable for IP reassembly configuration on L2TP.</p> </div>	
<b>Required Privilege Level</b>	<p>interface—To view this statement in the configuration.</p> <p>interface-control—To add this statement to the configuration.</p>
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li><i>Configuring Service Sets to be Applied to Services Interfaces</i></li> </ul>

## open-timeout

---

<b>Syntax</b>	<code>open-timeout <i>seconds</i>;</code>
<b>Hierarchy Level</b>	[edit interfaces <i>interface-name</i> <a href="#">services-options</a> ]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4.
<b>Description</b>	Configure a timeout period for Transmission Control Protocol (TCP) session establishment.
<b>Options</b>	<p><b><i>seconds</i></b>—Timeout period.</p> <p><b>Default:</b> 5 seconds</p> <p><b>Range:</b> 4 through 224 seconds</p>
<b>Required Privilege Level</b>	<p>interface—To view this statement in the configuration.</p> <p>interface-control—To add this statement to the configuration.</p>
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring Default Timeout Settings for Services Interfaces on page 29</a></li> </ul>

## port (System Log Messages)

---

<b>Syntax</b>	<code>port <i>port-number</i>;</code>
<b>Hierarchy Level</b>	[edit <a href="#">interfaces</a> <i>interface-name</i> <a href="#">services-options</a> <a href="#">syslog host</a> <i>hostname</i> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 11.1.
<b>Description</b>	UDP port for system log messages on the host. The default port is 514.
<b>Options</b>	<b><i>port-number</i></b> —Port number for system log messages.
<b>Required Privilege Level</b>	<p>interface—To view this statement in the configuration.</p> <p>interface-control—To add this statement to the configuration.</p>
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring System Logging for Services Interfaces on page 30</a></li> </ul>

## rule-set (Services Stateful Firewall)

---

<b>Syntax</b>	<code>rule-set <i>rule-set-name</i> {     [ rule <i>rule-names</i> ; }</code>
<b>Hierarchy Level</b>	[edit <a href="#">services</a> stateful-firewall]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4.
<b>Description</b>	Specify the rule set the router uses when applying this service.
<b>Options</b>	<i>rule-set-name</i> —Identifier for the collection of rules that constitute this rule set.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <i>Configuring Stateful Firewall Rule Sets</i></li></ul>

## service-set (Interfaces)

---

<b>Syntax</b>	<code>service-set <i>service-set-name</i>;</code>
<b>Hierarchy Level</b>	[edit interfaces <i>interface-name</i> unit <i>logical-unit-number</i> family inet service (input   output)], [edit logical-systems <i>logical-system-name</i> interfaces <i>interface-name</i> unit <i>logical-unit-number</i> family inet service (input   output)]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4.
<b>Description</b>	Define one or more service sets to be applied to an interface. If you define multiple service sets, the router software evaluates the filters in the order in which they appear in the configuration.
<b>Options</b>	<i>service-set-name</i> —Identifies the service set.
<b>Required Privilege Level</b>	System—To view this statement in the configuration. System-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <i>Applying Filters and Services to Interfaces</i></li></ul>

## service-set (Services)

```
Syntax  service-set service-set-name {
    allow-multicast;
    extension-service service-name {
        provider-specific-rules-configuration;
    }
    (ids-rules rule-name | ids-rule-sets rule-set-name);
    interface-service {
        service-interface interface-name;
    }
    ipsec-vpn-options {
        anti-replay-window-size bits;
        clear-dont-fragment-bit;
        ike-access-profile profile-name;
        local-gateway address;
        no-anti-replay;
        passive-mode-tunneling;
        trusted-ca [ ca-profile-names ];
        tunnel-mtu bytes;
    }
    ip-reassembly-rules rule-name;
    (ipsec-vpn-rules rule-name | ipsec-vpn-rule-sets rule-set-name);
    max-flows number;
    max-drop-flows {
        ingress ingress-flows;
        egress egress-flows;
    }
    nat-options {
        land-attack-check (ip-only | ip-port);
        max-sessions-per-subscriber session-number;
        stateful-nat64 {
            clear-dont-fragment-bit;
        }
    }
    (nat-rules rule-name | nat-rule-sets rule-set-name);
    next-hop-service {
        inside-service-interface interface-name.unit-number;
        outside-service-interface interface-name.unit-number;
        outside-service-interface-type local;
        service-interface-pool name;
    }
    (pgcp-rules rule-name | pgcp-rule-sets rule-set-name);
    (ptsp-rules rule-name | ptsp-rule-sets rule-set-name);
    service-set-options {
        bypass-traffic-on-exceeding-flow-limits;
        bypass-traffic-on-pic-failure;
        enable-asymmetric-traffic-processing;
        routing-engine-services;
        support-uni-directional-traffic;
    }
    snmp-trap-thresholds {
        flows high high-threshold | low low-threshold;
        nat-address-port high-threshold | low low-threshold;
    }
}
```

```

    }
  }
  software-options {
    dslite-ipv6-prefix-length dslite-ipv6-prefix-length;
  }
  (software-rules rule-name | software-rule-sets rule-set-name);
  (stateful-firewall-rules rule-name | stateful-firewall-rule-sets rule-set-name);
  syslog {
    host hostname {
      class {
        alg-logs;
        ids-logs;
        nat-logs;
        packet-logs;
        pcp-logs;
        session-logs <open | close>;
        stateful-firewall-logs ;
      }
      services severity-level;
      facility-override facility-name;
      interface-service prefix-value;
    }
  }
}

```

**Hierarchy Level** [edit services]

**Release Information** Statement introduced before Junos OS Release 7.4.  
**pgcp-rules** and **pgcp-rule-sets** options added in Junos OS Release 8.4.  
**server-set-options** option added in Junos OS Release 10.1.  
**ptsp-rules** and **ptsp-rule-sets** options added in Junos OS Release 10.2.  
**software-rules** and **clear-rule-sets** options added in Junos OS Release 10.4.  
**software-options** option added in Junos OS Release 14.1.

**Description** Define the service set.

**Options** ***service-set-name***—Name of the service set. You can include special characters, such as a forward slash (/), colon (:), or a period (.).

**Range:** Up to 64 alphanumeric characters.

The remaining statements are explained separately.

**Required Privilege Level** interface—To view this statement in the configuration.  
 interface-control—To add this statement to the configuration.

**Related Documentation**

- *Service Set Properties*

---

## services (CoS)

---

<b>Syntax</b>	<code>services cos { ... }</code>
<b>Hierarchy Level</b>	[edit]
<b>Release Information</b>	Statement introduced in Junos OS Release 8.1.
<b>Description</b>	Define the service rules to be applied to traffic.
<b>Options</b>	<code>cos</code> —Identifier for the class-of-service set of rules statements.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <i>Configuring CoS Rules</i></li></ul>

---

## services (IDS)

---

<b>Syntax</b>	<code>services ids { ... }</code>
<b>Hierarchy Level</b>	[edit]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4.
<b>Description</b>	Define the service rules to be applied to traffic.
<b>Options</b>	<code>ids</code> —Identifies the IDS set of rules statements.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <i>Configuring IDS Rules</i></li></ul>

## services (IPsec VPN)

---

<b>Syntax</b>	<code>services ipsec-vpn { ... }</code>
<b>Hierarchy Level</b>	[edit]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4.
<b>Description</b>	Define the service rules to be applied to traffic.
<b>Options</b>	<code>ipsec-vpn</code> —IPsec set of rules statements.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <i>Configuring Security Associations</i></li></ul>

## services (Hierarchy)

---

<b>Syntax</b>	<code>services { ... }</code>
<b>Hierarchy Level</b>	[edit]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4.
<b>Description</b>	Define the service rules to be applied to traffic.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <i>Service Set Properties</i></li></ul>



## services (Interfaces)

<b>Syntax</b>	<code>services severity-level;</code>
<b>Hierarchy Level</b>	[edit <a href="#">interfaces interface-name services-options syslog host hostname</a> ]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4.
<b>Description</b>	Specify the system logging severity level.
<b>Options</b>	<p><b>severity-level</b>—Assigns a severity level to the facility. Valid entries include:</p> <ul style="list-style-type: none"> <li>• <b>alert</b>—Conditions that should be corrected immediately.</li> <li>• <b>any</b>—Matches any level.</li> <li>• <b>critical</b>—Critical conditions.</li> <li>• <b>emergency</b>—Panic conditions.</li> <li>• <b>error</b>—Error conditions.</li> <li>• <b>info</b>—Informational messages.</li> <li>• <b>notice</b>—Conditions that require special handling.</li> <li>• <b>warning</b>—Warning messages.</li> </ul>
<b>Required Privilege Level</b>	<p>interface—To view this statement in the configuration.</p> <p>interface-control—To add this statement to the configuration.</p>
<b>Related Documentation</b>	<ul style="list-style-type: none"> <li>• <a href="#">Configuring System Logging for Services Interfaces on page 30</a></li> </ul>

## services (NAT)

<b>Syntax</b>	<code>services nat { ... }</code>
<b>Hierarchy Level</b>	[edit]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4.
<b>Description</b>	Define the service rules to be applied to traffic.
<b>Options</b>	<b>nat</b> —Identifies the NAT set of rules statements.
<b>Required Privilege Level</b>	<p>interface—To view this statement in the configuration.</p> <p>interface-control—To add this statement to the configuration.</p>

## services (L2TP)

---

<b>Syntax</b>	<code>services l2tp { ... }</code>
<b>Hierarchy Level</b>	[edit]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4.
<b>Description</b>	Define the service properties to be applied to traffic.
<b>Options</b>	<b>l2tp</b> —Identifies the L2TP set of services statements.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <i>L2TP Services Configuration Overview</i></li></ul>

## services (L2TP System Logging)

---

<b>Syntax</b>	<code>services severity-level;</code>
<b>Hierarchy Level</b>	[edit services l2tp tunnel-group <i>group-name</i> syslog host <i>hostname</i> ]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4.
<b>Description</b>	Specify the system logging severity level.
<b>Options</b>	<b>severity-level</b> —Assigns a severity level to the facility. Valid entries include: <ul style="list-style-type: none"><li>• <b>alert</b>—Conditions that should be corrected immediately.</li><li>• <b>any</b>—Matches any level.</li><li>• <b>critical</b>—Critical conditions.</li><li>• <b>emergency</b>—Panic conditions.</li><li>• <b>error</b>—Error conditions.</li><li>• <b>info</b>—Informational messages.</li><li>• <b>notice</b>—Conditions that require special handling.</li><li>• <b>warning</b>—Warning messages.</li></ul>
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <i>Configuring System Logging of L2TP Tunnel Activity</i></li></ul>

## services (Stateful Firewall)

---

<b>Syntax</b>	<code>services stateful-firewall { ... }</code>
<b>Hierarchy Level</b>	[edit]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4. Statement introduced in Junos OS Release 10.4.
<b>Description</b>	Define the service rules to be applied to traffic.
<b>Options</b>	<b>stateful-firewall</b> —Identifies the stateful firewall set of rules statements.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <i>Junos Network Secure</i>.</li></ul>

## services (System Logging)

---

<b>Syntax</b>	<code>services severity-level;</code>
<b>Hierarchy Level</b>	[edit <a href="#">services service-set service-set-name</a> syslog host <i>hostname</i> ]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4.
<b>Description</b>	Specify the severity level for system logging messages.
<b>Options</b>	<p><b>severity-level</b>—Assigns a severity level to the facility. Valid entries are:</p> <ul style="list-style-type: none"><li>• <b>alert</b>—Conditions that should be corrected immediately.</li><li>• <b>any</b>—Matches any level.</li><li>• <b>critical</b>—Critical conditions.</li><li>• <b>emergency</b>—Panic conditions.</li><li>• <b>error</b>—Error conditions.</li><li>• <b>info</b>—Informational messages.</li><li>• <b>notice</b>—Conditions that require special handling.</li><li>• <b>warning</b>—Warning messages.</li></ul>
<b>Required Privilege Level</b>	<p>interface—To view this statement in the configuration.</p> <p>interface-control—To add this statement to the configuration.</p>
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <i>Configuring System Logging for Service Sets</i></li></ul>

## services-options

**Syntax**

```

services-options {
  cgn-pic;
  close-timeout
  fragment-limit
  disable-global-timeout-override;
  ignore-errors <alg> <tcp>;
  inactivity-non-tcp-timeout seconds;
  inactivity-tcp-timeout seconds;
  inactivity-timeout seconds
  open-timeout seconds;
  pba-interim-logging-interval seconds;
  reassembly-timeout
  session-limit {
    maximum number;
    rate new-sessions-per-second;
    cpu-load-threshold percentage;
  }
  session-timeout seconds;
  jflow-log {
    message-rate-limit messages-per-second;
  }
  syslog {
    host hostname {
      facility-override facility-name;
      log-prefix prefix-value;
      port port-number;
      services severity-level;
    }
    message-rate-limit messages-per-second;
  }
  tcp-tickles tcp-tickles;
  trio-flow-offload minimum-bytes minimum-bytes;
}

```

**Hierarchy Level** [edit interfaces *interface-name*]

**Release Information** Statement introduced before Junos OS Release 7.4.

**Description** Define the service options to be applied on an interface.

**Options** The remaining statements are explained separately.

**Required Privilege Level** interface—To view this statement in the configuration.  
interface-control—To add this statement to the configuration.

**Related Documentation**

- *Interface Properties*.

## session-limit

---

<b>Syntax</b>	<pre>session-limit {     maximum <i>number</i>;     rate <i>new-sessions-per-second</i>;     <b>cpu-load-threshold</b> <i>percentage</i>; }</pre>
<b>Hierarchy Level</b>	[edit interfaces <i>interface-name</i> <b>services-options</b> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 9.6.
<b>Description</b>	Restrict the maximum number of sessions and the session rate on Multiservices PICs.
<b>Options</b>	<b>session-limit</b> —Restricts the maximum number of sessions and the session rate for Multiservices PICs.  The remaining statements are explained separately.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.

## syslog (Interfaces)

---

<b>Syntax</b>	<pre>syslog {     <b>host</b> <i>hostname</i> {         <b>services</b> <i>severity-level</i>;         <b>facility-override</b> <i>facility-name</i>;         <b>log-prefix</b> <i>prefix-value</i>;         <b>port</b> <i>port-number</i>;     }     message-rate-limit <i>messages-per-second</i>; }</pre>
<b>Hierarchy Level</b>	[edit interfaces <i>interface-name</i> <b>services-options</b> ]
<b>Release Information</b>	Statement introduced before Junos OS Release 7.4.
<b>Description</b>	Configure generation of system log messages for the service set. System log information is passed to the kernel for logging in the <b>/var/log</b> directory. Any values configured in the service set definition override these values.
<b>Options</b>	The remaining statements are described separately.
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring System Logging for Services Interfaces on page 30</a></li></ul>

---

## tcp-tickles

---

<b>Syntax</b>	<code>tcp-tickles <i>tcp-tickles</i>;</code>
<b>Hierarchy Level</b>	[edit interfaces <i>interface-name</i> <a href="#">services-options</a> ]
<b>Release Information</b>	Statement introduced in Junos OS Release 11.4.
<b>Description</b>	Define the maximum number of keep-alive messages sent before a TCP session is allowed to timeout.
<b>Options</b>	<b><i>tcp-tickles</i></b> —Number of keep-alive messages. <b>Range:</b> 0 through 30 <b>Default:</b> 4
<b>Required Privilege Level</b>	interface—To view this statement in the configuration. interface-control—To add this statement to the configuration.
<b>Related Documentation</b>	<ul style="list-style-type: none"><li>• <a href="#">Configuring Default Timeout Settings for Services Interfaces on page 29</a></li></ul>





## CHAPTER 4

# Index

- [Index on page 59](#)



# Index

## Symbols

#, comments in configuration statements.....	x
( ), in syntax descriptions.....	x
< >, in syntax descriptions.....	x
[ ], in configuration statements.....	x
{ }, in configuration statements.....	x
(pipe), in syntax descriptions.....	x

## A

address statement	
interfaces.....	34
alert (system logging severity level).....	31
any (system logging severity level).....	31
applications statement	
application-level gateways.....	37
applications hierarchy.....	35
CoS.....	35
IDS.....	36
NAT.....	36
stateful firewall.....	37

## B

braces, in configuration statements.....	x
brackets	
angle, in syntax descriptions.....	x
square, in configuration statements.....	x

## C

close-timeout statement.....	37
comments, in configuration statements.....	x
conventions	
text and syntax.....	ix
critical (system logging severity level).....	31
curly braces, in configuration statements.....	x
customer support.....	xi
contacting JTAC.....	xi

## D

destination-port statement	
applications.....	35

documentation	
comments on.....	xi

## E

emergency (system logging severity level).....	31
error (system logging severity level).....	31

## F

facility-override statement.....	39
font conventions.....	ix

## H

hardware requirements.....	13
host statement.....	40
usage guidelines.....	30

## I

inactivity-timeout statement	
flow monitoring.....	40
usage guidelines.....	29
info (system logging severity level).....	31
interfaces	
naming.....	19
interfaces statement	
interfaces hierarchy.....	41

## L

log-prefix statement.....	41
usage guidelines.....	30

## M

manuals	
comments on.....	xi

## N

next-hop-service statement.....	42
notice (system logging severity level).....	31

## O

open-timeout statement.....	43
usage guidelines.....	29

## P

parentheses, in syntax descriptions.....	x
PIC types for services.....	13
platforms, supported.....	17
procedural overview.....	25

**R**

rule-set statement	
stateful firewall.....	44

**S**

service packages.....	21
service-set statement.....	44, 45
services configuration overview.....	25
services PICs.....	13
services statement	
CoS.....	47
IDS.....	47
interfaces.....	49
usage guidelines.....	30
IPsec.....	48
NAT.....	49
stateful firewall.....	51
services-options statement.....	53
usage guidelines.....	29, 30
session-limit statement.....	54
support, technical See technical support	
syntax conventions.....	ix
syslog statement	
interfaces.....	54
usage guidelines.....	30

**T**

tcp-tickles statement.....	55
technical support	
contacting JTAC.....	xi

**W**

warning (system logging severity level).....	31
--	----