



Junos[®] OS

System Log Messages Reference

Release

15.1



Modified: 2015-05-26

Juniper Networks, Inc.
1133 Innovation Way
Sunnyvale, California 94089
USA
408-745-2000
www.juniper.net

Juniper Networks, Junos, Steel-Belted Radius, NetScreen, and ScreenOS are registered trademarks of Juniper Networks, Inc. in the United States and other countries. The Juniper Networks Logo, the Junos logo, and JunosE are trademarks of Juniper Networks, Inc. All other trademarks, service marks, registered trademarks, or registered service marks are the property of their respective owners.

Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

Junos[®] OS System Log Messages Reference
Release 15.1
Copyright © 2015, Juniper Networks, Inc.
All rights reserved.

Revision History
May 2015—R1 Junos OS 15.1

The information in this document is current as of the date on the title page.

YEAR 2000 NOTICE

Juniper Networks hardware and software products are Year 2000 compliant. Junos OS has no known time-related limitations through the year 2038. However, the NTP application is known to have some difficulty in the year 2036.

END USER LICENSE AGREEMENT

The Juniper Networks product that is the subject of this technical documentation consists of (or is intended for use with) Juniper Networks software. Use of such software is subject to the terms and conditions of the End User License Agreement ("EULA") posted at <http://www.juniper.net/support/eula.html>. By downloading, installing or using such software, you agree to the terms and conditions of that EULA.

Abbreviated Table of Contents

	About This Guide	lxv
Part 1	Overview	
Chapter 1	Configuring System Log Messages	3
Part 2	System Log Messages	
Chapter 2	AAA System Log Messages	69
Chapter 3	ACCT System Log Messages	71
Chapter 4	ALARMD System Log Messages	75
Chapter 5	AMD System Log Messages	81
Chapter 6	ANALYZER System Log Messages	83
Chapter 7	ANTISPAM System Log Messages	85
Chapter 8	APPID System Log Messages	87
Chapter 9	APPIDD System Log Messages	89
Chapter 10	APPPXY System Log Messages	91
Chapter 11	APPTRACK System Log Messages	93
Chapter 12	ASP System Log Messages	97
Chapter 13	AUDITD System Log Messages	129
Chapter 14	AUTHD System Log Messages	133
Chapter 15	AUTOCONFD System Log Messages	137
Chapter 16	AUTOD System Log Messages	139
Chapter 17	AV System Log Messages	141
Chapter 18	BBE System Log Messages	145
Chapter 19	BFDD System Log Messages	147
Chapter 20	BGP System Log Messages	151
Chapter 21	BOOTPD System Log Messages	165
Chapter 22	CFMD System Log Messages	171
Chapter 23	CHASSISD System Log Messages	175
Chapter 24	CHASSISM System Log Messages	275
Chapter 25	CLKSYNCD System Log Messages	277
Chapter 26	COSD System Log Messages	287
Chapter 27	DCBX System Log Messages	303
Chapter 28	DCD System Log Messages	305

Chapter 29	DDOS System Log Messages	313
Chapter 30	DFCD System Log Messages	317
Chapter 31	DFWD System Log Messages	321
Chapter 32	DHCPD System Log Messages	323
Chapter 33	DIAM System Log Messages	329
Chapter 34	DOTIXD System Log Messages	331
Chapter 35	DYNAMIC System Log Messages	335
Chapter 36	ESWD System Log Messages	341
Chapter 37	EVENTD System Log Messages	351
Chapter 38	FABOAMD System Log Messages	361
Chapter 39	FC System Log Messages	363
Chapter 40	FCOE System Log Messages	369
Chapter 41	FIP System Log Messages	371
Chapter 42	FIPS System Log Messages	375
Chapter 43	FLOW System Log Messages	377
Chapter 44	FPCLOGIN System Log Messages	381
Chapter 45	FSAD System Log Messages	383
Chapter 46	FUD System Log Messages	393
Chapter 47	FWAUTH System Log Messages	399
Chapter 48	GPRSD System Log Messages	405
Chapter 49	HNCACHED System Log Messages	407
Chapter 50	ICCPD System Log Messages	409
Chapter 51	IDP System Log Messages	411
Chapter 52	JADE System Log Messages	419
Chapter 53	JCS System Log Messages	423
Chapter 54	JDIAMETERD System Log Messages	429
Chapter 55	JIVED System Log Messages	431
Chapter 56	JNUD System Log Messages	435
Chapter 57	JPTSPD System Log Messages	437
Chapter 58	JSERVICES System Log Messages	441
Chapter 59	JSRPD System Log Messages	445
Chapter 60	JTASK System Log Messages	455
Chapter 61	JTRACE System Log Messages	469
Chapter 62	KMD System Log Messages	471
Chapter 63	L2ALD System Log Messages	487
Chapter 64	L2CPD System Log Messages	503
Chapter 65	L2TPD System Log Messages	507
Chapter 66	LACP System Log Messages	537

Chapter 67	LACPD System Log Messages	539
Chapter 68	LFMD System Log Messages	541
Chapter 69	LIBJNX System Log Messages	543
Chapter 70	LIBJSNMP System Log Messages	553
Chapter 71	LIBMSRPC System Log Messages	559
Chapter 72	LICENSE System Log Messages	563
Chapter 73	LLDP System Log Messages	571
Chapter 74	LOGIN System Log Messages	573
Chapter 75	LPDFD System Log Messages	579
Chapter 76	LRMUX System Log Messages	581
Chapter 77	LSYSD System Log Messages	583
Chapter 78	MBG System Log Messages	585
Chapter 79	MCSN System Log Messages	601
Chapter 80	MIB2D System Log Messages	603
Chapter 81	MPLS System Log Messages	611
Chapter 82	NEXTHOP System Log Messages	615
Chapter 83	NSD System Log Messages	617
Chapter 84	NSTRACED System Log Messages	619
Chapter 85	NTPDATE System Log Messages	621
Chapter 86	NTPD System Log Messages	623
Chapter 87	PARSE System Log Messages	625
Chapter 88	PFE System Log Messages	627
Chapter 89	PFED System Log Messages	635
Chapter 90	PGCPD System Log Messages	637
Chapter 91	PING System Log Messages	639
Chapter 92	PKID System Log Messages	643
Chapter 93	PPMD System Log Messages	653
Chapter 94	PPPD System Log Messages	655
Chapter 95	PROFILER System Log Messages	663
Chapter 96	RDD System Log Messages	665
Chapter 97	RMOPD System Log Messages	669
Chapter 98	RPD System Log Messages	673
Chapter 99	RT System Log Messages	747
Chapter 100	RTLOG System Log Messages	761
Chapter 101	RTLOGD System Log Messages	763
Chapter 102	RTPERF System Log Messages	765
Chapter 103	SAVAL System Log Messages	767
Chapter 104	SDK System Log Messages	769

Chapter 105	SDXD System Log Messages	771
Chapter 106	SM System Log Messages	775
Chapter 107	SMTPD System Log Messages	777
Chapter 108	SNMP System Log Messages	779
Chapter 109	SNMPD System Log Messages	783
Chapter 110	SPD System Log Messages	797
Chapter 111	SSH System Log Messages	805
Chapter 112	SSHD System Log Messages	807
Chapter 113	SSL System Log Messages	809
Chapter 114	SYSTEM System Log Messages	813
Chapter 115	TFTPD System Log Messages	815
Chapter 116	TRANSPORTD System Log Messages	819
Chapter 117	UFDD System Log Messages	823
Chapter 118	UI System Log Messages	825
Chapter 119	UTMD System Log Messages	855
Chapter 120	VCCPD System Log Messages	857
Chapter 121	VM System Log Messages	863
Chapter 122	VRRPD System Log Messages	865
Chapter 123	WEB System Log Messages	869
Chapter 124	WEBFILTER System Log Messages	875
Part 3	Index	
	Index	881

Table of Contents

	About This Guide	lxv
	Junos OS Documentation and Release Notes	lxv
	Objectives	lxvi
	Audience	lxvi
	Supported Platforms	lxvi
	Using the Examples in This Manual	lxvii
	Merging a Full Example	lxvii
	Merging a Snippet	lxviii
	Documentation Conventions	lxviii
	Documentation Feedback	lxx
	Requesting Technical Support	lxxi
	Self-Help Online Tools and Resources	lxxi
	Opening a Case with JTAC	lxxi
Part 1	Overview	
Chapter 1	Configuring System Log Messages	3
	Junos OS System Log Configuration Hierarchy	3
	Minimum and Default System Logging Configuration	4
	Junos OS Minimum System Logging Configuration	4
	Junos OS Default System Log Settings	5
	Junos OS Platform-Specific Default System Log Messages	6
	Configuring System Logging for a Single-Chassis System	7
	Specifying the Facility and Severity of Messages to Include in the Log	9
	Directing System Log Messages to a Log File	11
	Logging Messages in Structured-Data Format	12
	Directing System Log Messages to a User Terminal	13
	Directing System Log Messages to the Console	13
	Directing Messages to a Remote Machine or the Other Routing Engine	13
	Specifying an Alternative Source Address for System Log Messages	
	Directed to a Remote Destination	15
	Changing the Alternative Facility Name for System Log Messages	
	Directed to a Remote Destination	15
	Default Facilities for System Log Messages Directed to a Remote	
	Destination	17
	Alternate Facilities for System Log Messages Directed to a Remote	
	Destination	17
	Examples: Assigning an Alternative Facility to System Log Messages	
	Directed to a Remote Destination	18

Adding a Text String to System Log Messages Directed to a Remote Destination	19
Adding a String	20
Specifying Log File Size, Number, and Archiving Properties	20
Including Priority Information in System Log Messages	22
System Log Facility Codes and Numerical Codes Reported in Priority Information	23
Including the Year or Millisecond in Timestamps	25
Using Regular Expressions to Refine the Set of Logged Messages	25
Junos System Log Regular Expression Operators for the match Statement	27
Disabling the System Logging of a Facility	28
Examples: Configuring System Logging	29
Configuring System Logging for a TX Matrix Router	31
Configuring Message Forwarding in the Routing Matrix	33
Impact of Different Local and Forwarded Severity Levels on System Log Messages on a TX Matrix Router	34
Configuring Optional Features for Forwarded Messages	36
Including Priority Information in Forwarded Messages	36
Adding a Text String to Forwarded Messages	37
Using Regular Expressions to Refine the Set of Forwarded Messages	37
Directing Messages to a Remote Destination from the Routing Matrix Based on the TX Matrix Router	37
Configuring System Logging Differently on Each T640 Router in a Routing Matrix	38
Configuring System Logging for a TX Matrix Plus Router	40
Configuring Message Forwarding to the TX Matrix Plus Router	42
Impact of Different Local and Forwarded Severity Levels on System Log Messages on a TX Matrix Plus Router	43
Messages Logged When the Local and Forwarded Severity Levels Are the Same	43
Messages Logged When the Local Severity Level Is Lower	43
Messages Logged When the Local Severity Level Is Higher	44
Configuring Optional Features for Forwarded Messages on a TX Matrix Plus Router	45
Including Priority Information in Forwarded Messages	45
Adding a Text String to Forwarded Messages	46
Using Regular Expressions to Refine the Set of Forwarded Messages	46
Directing Messages to a Remote Destination from the Routing Matrix Based on a TX Matrix Plus Router	46
Configuring System Logging Differently on Each T1600 or T4000 Router in a Routing Matrix	47

	Displaying and Interpreting System Log Messages	49
	Displaying a Log File from a Single-Chassis System	49
	Displaying a Log File from a Routing Matrix	50
	Interpreting System Log Messages	50
	Interpreting Messages Generated in Structured-Data Format	51
	Interpreting Messages Generated in Standard Format by a Junos OS Process or Library	55
	Interpreting Messages Generated in Standard Format by Services on a PIC	56
	Format of the message-source Field	57
	The message-source Field on a Single-Chassis System	57
	The message-source Field on a TX Matrix Platform	58
	Examples: Displaying a Log File	59
	Getting Help About System Log Messages	60
	Displaying and Interpreting System Log Message Descriptions	60
	Examples: Displaying System Log Message Descriptions	62
Part 2	System Log Messages	
Chapter 2	AAA System Log Messages	69
	AAA_RADIUS_SERVER_STATE_CHANGE	69
Chapter 3	ACCT System Log Messages	71
	ACCT_ACCOUNTING_FERROR	71
	ACCT_ACCOUNTING_FOPEN_ERROR	71
	ACCT_ACCOUNTING_SMALL_FILE_SIZE	71
	ACCT_BAD_RECORD_FORMAT	71
	ACCT_CU_RTSLIB_ERROR	72
	ACCT_FORK_ERR	72
	ACCT_FORK_LIMIT_EXCEEDED	72
	ACCT_GETHOSTNAME_ERROR	72
	ACCT_MALLOC_FAILURE	73
	ACCT_THREAD_CREATE_FAILURE	73
	ACCT_UNDEFINED_COUNTER_NAME	73
	ACCT_XFER_FAILED	73
	ACCT_XFER_POPEN_FAIL	74
	ACCT_XFER_TIMEOUT	74
Chapter 4	ALARMD System Log Messages	75
	ALARMD_CONFIG_ACCESS_ERROR	75
	ALARMD_CONFIG_CLOSE_ERROR	75
	ALARMD_CONFIG_PARSE_ERROR	75
	ALARMD_CONFIG_RECONFIG_ERROR	76
	ALARMD_CONNECTION_FAILURE	76
	ALARMD_DECODE_ALARM_OBJECT_ERROR	76
	ALARMD_EXISTS	76
	ALARMD_EXISTS_TERM_OTHER	77
	ALARMD_IFDALARM_TYPE_ERROR	77
	ALARMD_IFDEV_RTSLIB_FAILURE	77
	ALARMD_IPC_MSG_ERROR	77

	ALARM_IPC_MSG_WRITE_ERROR	78
	ALARM_IPC_UNEXPECTED_MSG	78
	ALARM_MEM_ALLOC_FAILURE	78
	ALARM_MGR_CONNECT	78
	ALARM_MULTIPLE_ALARM_BIT_ERROR	79
	ALARM_PIDFILE_OPEN	79
	ALARM_PIPE_WRITE_ERROR	79
	ALARM_SOCKET_CREATE	79
	ALARM_UNEXPECTED_EXIT	80
Chapter 5	AMD System Log Messages	81
	AMD_CONFIG_CHECK_FAILED	81
	AMD_FILE_OPEN_FAILURE	81
Chapter 6	ANALYZER System Log Messages	83
	ANALYZER_INPUT_INTERFACES_LIMIT	83
Chapter 7	ANTISPAM System Log Messages	85
	ANTISPAM_SPAM_DETECTED_MT	85
Chapter 8	APPID System Log Messages	87
	APPID_SIGNATURE_LICENSE_EXPIRED	87
Chapter 9	APPIDD System Log Messages	89
	APPIDD_APPPACK_DOWNLOAD_RESULT	89
	APPIDD_APPPACK_INSTALL_RESULT	89
	APPIDD_APPPACK_UNINSTALL_RESULT	89
	APPIDD_DAEMON_INIT_FAILED	89
	APPIDD_INTERNAL_ERROR	90
	APPIDD_SCHEDULED_UPDATE_FAILED	90
Chapter 10	APPPXY System Log Messages	91
	APPPXY_SESSION_ABORT_MT	91
Chapter 11	APPTRACK System Log Messages	93
	APPTRACK_SESSION_APP_UPDATE	93
	APPTRACK_SESSION_APP_UPDATE_LS	93
	APPTRACK_SESSION_CLOSE	94
	APPTRACK_SESSION_CLOSE_LS	94
	APPTRACK_SESSION_CREATE	94
	APPTRACK_SESSION_CREATE_LS	95
	APPTRACK_SESSION_VOL_UPDATE	95
	APPTRACK_SESSION_VOL_UPDATE_LS	95
Chapter 12	ASP System Log Messages	97
	ASP_COS_RULE_MATCH	97
	ASP_IDS_HOST_RATE	97
	ASP_IDS_HOST_RATE_APP	98
	ASP_IDS_INV_CLEAR_QUERY	98
	ASP_IDS_INV_CLEAR_QUERY_VER	98
	ASP_IDS_INV_SHOW_QUERY	98
	ASP_IDS_INV_SHOW_QUERY_VER	99

ASP_IDS_LIMIT_FLOW_RATE_BY_DEST	99
ASP_IDS_LIMIT_FLOW_RATE_BY_PAIR	99
ASP_IDS_LIMIT_FLOW_RATE_BY_SRC	100
ASP_IDS_LIMIT_OPEN_FLOWS_BY_DEST	100
ASP_IDS_LIMIT_OPEN_FLOWS_BY_PAIR	101
ASP_IDS_LIMIT_OPEN_FLOWS_BY_SRC	101
ASP_IDS_LIMIT_PKT_RATE_BY_DEST	101
ASP_IDS_LIMIT_PKT_RATE_BY_PAIR	102
ASP_IDS_LIMIT_PKT_RATE_BY_SRC	102
ASP_IDS_NO_MEM_SHOW_CMD	102
ASP_IDS_NULL_CLEAR_QUERY	103
ASP_IDS_NULL_SHOW_QUERY	103
ASP_IDS_RULE_MATCH	103
ASP_IDS_SYN_COOKIE_OFF	103
ASP_IDS_SYN_COOKIE_ON	104
ASP_IDS_TCP_SYN_ATTACK	104
ASP_L2TP_MESSAGE_INCOMPLETE	105
ASP_L2TP_NO_MEM	105
ASP_L2TP_OBJ_CAC_FAIL	105
ASP_L2TP_STATS_BULK_QUERY_FAILED	105
ASP_L2TP_STATS_VERSION_INVALID	106
ASP_L2TP_TUN_GRP_ADD_FAIL_ALLOC	106
ASP_L2TP_TUN_GRP_ADD_FAIL_EXISTS	106
ASP_L2TP_TUN_GRP_CHG_FAIL_ALLOC	106
ASP_L2TP_TUN_GRP_CHG_FAIL_INVLD	106
ASP_L2TP_TUN_GRP_DEL_FAIL_INVLD	107
ASP_NAT_OUTOF_ADDRESSES	107
ASP_NAT_OUTOF_PORTS	107
ASP_NAT_POOL_RELEASE	107
ASP_NAT_PORT_BLOCK_ACTIVE	108
ASP_NAT_PORT_BLOCK_ALLOC	108
ASP_NAT_PORT_BLOCK_RELEASE	108
ASP_NAT_RULE_MATCH	108
ASP_PCP_NAT_MAP_CREATE	109
ASP_PCP_NAT_MAP_DELETE	109
ASP_PCP_TPC_ALLOC_ERR	109
ASP_PCP_TPC_NOT_FOUND	109
ASP_PGCP_IPC_MSG_WRITE_FAILED	110
ASP_PGCP_IPC_PIPE_WRITE_FAILED	110
ASP_SFW_ALG_LEVEL_ADJUSTED	110
ASP_SFW_ALG_PROMOTION_FAILED	111
ASP_SFW_APP_MSG_TOO_LONG	111
ASP_SFW_CHANGE_INACTIVITY_TIMER	111
ASP_SFW_CREATE_ACCEPT_FLOW	112
ASP_SFW_CREATE_DISCARD_FLOW	112
ASP_SFW_CREATE_REJECT_FLOW	112
ASP_SFW_DELETE_FLOW	113
ASP_SFW_DROP_FLOW_DELETE	113
ASP_SFW_FTP_ACTIVE_ACCEPT	113

	ASP_SFW_FTP_PASSIVE_ACCEPT	114
	ASP_SFW_ICMP_ERROR_DROP	114
	ASP_SFW_ICMP_HEADER_LEN_ERROR	114
	ASP_SFW_ICMP_PACKET_ERROR_LENGTH	115
	ASP_SFW_IP_FRAG_ASSEMBLY_TIMEOUT	115
	ASP_SFW_IP_FRAG_OVERLAP	115
	ASP_SFW_IP_OPTION_DROP_PACKET	116
	ASP_SFW_IP_PACKET_CHECKSUM_ERROR	116
	ASP_SFW_IP_PACKET_DST_BAD	116
	ASP_SFW_IP_PACKET_FRAG_LEN_INV	117
	ASP_SFW_IP_PACKET_INCORRECT_LEN	117
	ASP_SFW_IP_PACKET_LAND_ATTACK	117
	ASP_SFW_IP_PACKET_NOT_VERSION_4	118
	ASP_SFW_IP_PACKET_PROTOCOL_ERROR	118
	ASP_SFW_IP_PACKET_SRC_BAD	118
	ASP_SFW_IP_PACKET_TOO_LONG	119
	ASP_SFW_IP_PACKET_TOO_SHORT	119
	ASP_SFW_IP_PACKET_TTL_ERROR	119
	ASP_SFW_NEW_POLICY	120
	ASP_SFW_NO_IP_PACKET	120
	ASP_SFW_NO_POLICY	120
	ASP_SFW_NO_RULE_DROP	120
	ASP_SFW_PING_DUPLICATED_SEQNO	121
	ASP_SFW_PING_MISMATCHED_SEQNO	121
	ASP_SFW_PING_OUTOF_SEQNO_CACHE	121
	ASP_SFW_POLICY_REJECT	122
	ASP_SFW_RULE_ACCEPT	122
	ASP_SFW_RULE_DISCARD	122
	ASP_SFW_RULE_REJECT	123
	ASP_SFW_SYN_DEFENSE	123
	ASP_SFW_TCP_BAD_SYN_COOKIE_RESP	124
	ASP_SFW_TCP_FLAGS_ERROR	124
	ASP_SFW_TCP_HEADER_LEN_ERROR	124
	ASP_SFW_TCP_NON_SYN_FIRST_PACKET	125
	ASP_SFW_TCP_PORT_ZERO	125
	ASP_SFW_TCP_RECONSTRUCT_DROP	125
	ASP_SFW_TCP_SCAN	126
	ASP_SFW_TCP_SEQNO_AND_FLAGS_ZERO	126
	ASP_SFW_TCP_SEQNO_ZERO_FLAGS_SET	126
	ASP_SFW_UDP_HEADER_LEN_ERROR	127
	ASP_SFW_UDP_PORT_ZERO	127
	ASP_SFW_UDP_SCAN	127
	ASP_SFW_VERY_BAD_PACKET	128
	ASP_SVC_SET_MAX_FLOWS_EXCEEDED	128
Chapter 13	AUDITD System Log Messages	129
	AUDITD_RADIUS_AV_AUTH_TYPE_ERROR	129
	AUDITD_RADIUS_AV_ERROR	129
	AUDITD_RADIUS_AV_PORT_ERROR	129

	AUDITD_RADIUS_OPEN_FAILED	130
	AUDITD_RADIUS_REQ_CREATE_FAILED	130
	AUDITD_RADIUS_REQ_DROPPED	130
	AUDITD_RADIUS_REQ_SEND_ERROR	130
	AUDITD_RADIUS_REQ_TIMED_OUT	131
	AUDITD_RADIUS_SERVER_ADD_ERROR	131
	AUDITD_SOCKET_FAILURE	131
	AUDITD_TACPLUS_SHM_CREATE_FAILED	132
Chapter 14	AUTHD System Log Messages	133
	AUTHD_ACCOUNTING_STATE_CHANGE	133
	AUTHD_ACCT_ON_ACK_NOT_RECEIVED	133
	AUTHD_AUTH_CREATE_FAILED	133
	AUTHD_AUTH_SERVER_STATUS_CHANGE	134
	AUTHD_RADIUS_GETHOSTNAME_FAILED	134
	AUTHD_SERVER_INIT_BIND_FAIL	134
	AUTHD_SERVER_INIT_LISTEN_FAIL	134
Chapter 15	AUTOCONFD System Log Messages	137
	AUTOCONFD_AUTHENTICATE_LICENSE	137
Chapter 16	AUTOD System Log Messages	139
	AUTOD_BIND_FAILURE	139
	AUTOD_HOSTNAME_EXPANSION_FAILURE	139
	AUTOD_RECV_FAILURE	139
	AUTOD_RES_MKQUERY_FAILURE	140
	AUTOD_SEND_FAILURE	140
	AUTOD_SOCKET_CREATE_FAILURE	140
Chapter 17	AV System Log Messages	141
	AV_PATTERN_GET_FAILED	141
	AV_PATTERN_KEY_EXPIRED	141
	AV_PATTERN_KL_CHECK_FAILED	141
	AV_PATTERN_TOO_BIG	142
	AV_PATTERN_UPDATED	142
	AV_PATTERN_WRITE_FS_FAILED	142
	AV_SCANNER_READY	143
	AV_VIRUS_DETECTED_MT	143
Chapter 18	BBE System Log Messages	145
	BBE_MIBD_TRAP_HEADER_FAILURE	145
	BBE_MIBD_TRAP_SEND_FAILURE	145
Chapter 19	BFDD System Log Messages	147
	BFDD_MIRROR_ERROR	147
	BFDD_MIRROR_VERSION_MISMATCH	147
	BFDD_READ_ERROR	148
	BFDD_TRAP_MHOP_STATE_DOWN	148
	BFDD_TRAP_MHOP_STATE_UP	148
	BFDD_TRAP_SHOP_STATE_DOWN	148
	BFDD_TRAP_SHOP_STATE_UP	149

Chapter 20

BFDD_TRAP_STATE_DOWN	149
BFDD_TRAP_STATE_UP	149
BFDD_WRITE_ERROR	149
BGP System Log Messages	151
BGP_ADDR_NOT_FOUND	151
BGP_ALLOC_BUFFER_ALREADY_EXISTS	151
BGP_BIND_FAILED_ADDR_UNAVAILABLE	151
BGP_Cease_PREFIX_LIMIT_EXCEEDED	152
BGP_CFG_PATH_ATTRIBUTE_WARNING	152
BGP_CONNECT_FAILED	152
BGP_CONNECT_GET_SOCKET_ERROR	152
BGP_CONNECT_SOCKET_SHUTDOWN	153
BGP_COPY_BUFFER_ALREADY_EXISTS	153
BGP_ERROR_SENDING_KEEPALIVE	153
BGP_ERROR_UNEXPECTED_LOCAL_PREF	154
BGP_FLUSH_FAILED_AFTER_RETRYING	154
BGP_FREE_NONEXISTENT_BUFFER	154
BGP_GATHER_FLUSH_FAILED	154
BGP_IGNORE_INVALID_PREFIX	155
BGP_NLRI_MISMATCH	155
BGP_NO_ADDRESS_BOUND_TO_SOCKET	155
BGP_NO_INCOMING_INTERFACE_FOUND	156
BGP_OPEN_INTERNAL_VERSION_ERROR	156
BGP_ORF_BAD_MSG_HEADER	156
BGP_ORF_LEN_EXCEEDS_MAX_PFXLEN	156
BGP_ORF_MAXLEN_EXCEEDS_MAX_PFXLEN	157
BGP_ORF_MAXLEN_LESS_THAN_MINLEN	157
BGP_ORF_MAX_PFXLEN_LESS_THAN_LEN	157
BGP_ORF_MINLEN_EXCEEDS_MAX_PFXLEN	158
BGP_ORF_MINLEN_LESS_THAN_LEN	158
BGP_ORF_PREFIX_BAD_LENGTH	158
BGP_ORF_PREFIX_INVALID_LENGTH	158
BGP_ORF_PREFIX_LESS_THAN_MINLEN	159
BGP_ORF_PREFIX_LIMIT_EXCEEDED	159
BGP_PREFIX_LIMIT_EXCEEDED	159
BGP_PREFIX_THRESH_EXCEEDED	160
BGP_REFRESH_FOR_UNNEGOTIATED_NLRI	160
BGP_RESET_PENDING_CONNECTION	160
BGP_SET_INTERFACE_FAILED	160
BGP_SOCKET_ADDR_NOT_FOUND	161
BGP_SPOOL_FLUSH_CONNECTION_CLOSED	161
BGP_SPOOL_FLUSH_FAILED	161
BGP_UNEXPECTED_MESSAGE_TYPE	162
BGP_UNUSABLE_AS_PATH	162
BGP_UNUSABLE_NEXTHOP	162
BGP_UPDATE_CONTAINS_GARBAGE	162
BGP_UPDATE_MISSING_PREFIXES	163
BGP_WRITE_CONNECTION_CLOSED	163

	BGP_WRITE_FAILED	163
	BGP_WRITE_FAILED_AFTER_RETRYING	163
	BGP_WRITE_WOULD_BLOCK	164
Chapter 21	BOOTPD System Log Messages	165
	BOOTPD_ARG_ERR	165
	BOOTPD_BAD_ID	165
	BOOTPD_BOOTSTRING	165
	BOOTPD_CONFIG_ERR	166
	BOOTPD_CONF_OPEN	166
	BOOTPD_DUP_PIC_SLOT	166
	BOOTPD_DUP_REV	166
	BOOTPD_DUP_SLOT	167
	BOOTPD_HWDB_ERROR	167
	BOOTPD_MODEL_CHK	167
	BOOTPD_NEW_CONF	168
	BOOTPD_NO_BOOTSTRING	168
	BOOTPD_NO_CONFIG	168
	BOOTPD_PARSE_ERR	168
	BOOTPD_REPARSE	169
	BOOTPD_SELECT_ERR	169
	BOOTPD_TIMEOUT	169
Chapter 22	CFMD System Log Messages	171
	CFMD_CCM_DEFECT_AIS	171
	CFMD_CCM_DEFECT_CROSS_CONNECT	171
	CFMD_CCM_DEFECT_ERROR	172
	CFMD_CCM_DEFECT_MAC_STATUS	172
	CFMD_CCM_DEFECT_NONE	172
	CFMD_CCM_DEFECT_RDI	172
	CFMD_CCM_DEFECT_RMEP	173
	CFMD_CCM_DEFECT_UNKNOWN	173
	CFMD_PPM_READ_ERROR	173
	CFMD_PPM_WRITE_ERROR	173
Chapter 23	CHASSISD System Log Messages	175
	CHASSISD_ACQUIRE_MASTERSHIP	175
	CHASSISD_ANTICF_PIM_CHECK_FAILED	175
	CHASSISD_ANTICF_RE_CHECK_FAILED	175
	CHASSISD_ANTICF_RE_ROM_READ_FAIL	176
	CHASSISD_ANTICF_RE_SHA_READ_FAIL	176
	CHASSISD_ANTICF_ROM_READ_FAILED	176
	CHASSISD_ANTICF_SHA_READ_FAILED	176
	CHASSISD_ARGUMENT_ERROR	177
	CHASSISD_BLOWERS_SPEED	177
	CHASSISD_BLOWERS_SPEED_FULL	177
	CHASSISD_BLOWERS_SPEED_MEDIUM	177
	CHASSISD_BUS_DEVICE_OPEN_FAILURE	178
	CHASSISD_CB_CLOCK_CHECKSUM	178
	CHASSISD_CB_MASTER_BP_IGNORED	178

CHASSISD_CB_READ	178
CHASSISD_CB_RE_ONLINE_BP_IGNORED	179
CHASSISD_CFEB_POWER_FAILURE	179
CHASSISD_CLEAR_CONFIG_ERROR	179
CHASSISD_CLOCK_FAILURE	180
CHASSISD_CLOCK_NOTICE	180
CHASSISD_CLOCK_RESET_FAIL	180
CHASSISD_CMB_READBACK_ERROR	180
CHASSISD_COMMAND_ACK_ERROR	181
CHASSISD_COMMAND_ACK_SFM_ERROR	181
CHASSISD_CONCAT_MODE_ERROR	181
CHASSISD_CONFIG_ACCESS_ERROR	182
CHASSISD_CONFIG_CHANGE_IFDEV_DEL	182
CHASSISD_CONFIG_INIT_ERROR	182
CHASSISD_CONFIG_WARNING	182
CHASSISD_DEVICE_OPEN_ERROR	183
CHASSISD_EXEC_ERROR	183
CHASSISD_EXISTS	183
CHASSISD_EXISTS_TERM_OTHER	183
CHASSISD_FAN_FAILURE	184
CHASSISD_FASIC_CONFIG_COMPLETE	184
CHASSISD_FASIC_FTOKEN_ERROR	184
CHASSISD_FASIC_FTOKEN_INIT_ERROR	184
CHASSISD_FASIC_HSL_CONFIG_ERROR	185
CHASSISD_FASIC_HSL_LINK_ERROR	185
CHASSISD_FASIC_INIT_ERROR	185
CHASSISD_FASIC_INPUT_DROP	186
CHASSISD_FASIC_OUTPUT_DROP	186
CHASSISD_FASIC_PIO_READ_ERROR	186
CHASSISD_FASIC_PIO_WRITE_ERROR	187
CHASSISD_FASIC_PLL_ERROR	187
CHASSISD_FASIC_RESET_ERROR	187
CHASSISD_FASIC_SRAM_ERROR	188
CHASSISD_FASIC_VERSION_ERROR	188
CHASSISD_FCHIP_CONFIG_COMPLETE	188
CHASSISD_FCHIP_CONFIG_MD_ERROR	188
CHASSISD_FCHIP_CONFIG_RATE_ERROR	189
CHASSISD_FCHIP_CONFIG_READ_ERROR	189
CHASSISD_FCHIP_FTOKEN_ERROR	189
CHASSISD_FCHIP_FTOKEN_INIT_ERROR	189
CHASSISD_FCHIP_HSR_ERROR	190
CHASSISD_FCHIP_HSR_INIT_ERROR	190
CHASSISD_FCHIP_HSR_INIT_LINK_ERR	190
CHASSISD_FCHIP_HSR_RESET_ERROR	190
CHASSISD_FCHIP_HST_ERROR	191
CHASSISD_FCHIP_HST_INIT_ERROR	191
CHASSISD_FCHIP_HST_INIT_LINK_ERR	191
CHASSISD_FCHIP_HST_RESET_ERROR	191
CHASSISD_FCHIP_INIT_ERROR	192

CHASSISD_FCHIP_LINK_ERROR	192
CHASSISD_FCHIP_MONITOR_ERROR	192
CHASSISD_FCHIP_PIO_READ_ERROR	192
CHASSISD_FCHIP_PIO_WRITE_ERROR	193
CHASSISD_FCHIP_POLL_ERROR	193
CHASSISD_FCHIP_RATE_ERROR	193
CHASSISD_FCHIP_SIB_NOT_STARTED	194
CHASSISD_FCHIP_VERSION_ERROR	194
CHASSISD_FEB_REVERSION	194
CHASSISD_FEB_SWITCHOVER	194
CHASSISD_FHSR_READ_REG_ERROR	194
CHASSISD_FHSR_WRITE_REG_ERROR	195
CHASSISD_FHST_READ_REG_ERROR	195
CHASSISD_FHST_WRITE_REG_ERROR	195
CHASSISD_FILE_OPEN	196
CHASSISD_FILE_STAT	196
CHASSISD_FM_ACTION_FPC_OFFLINE	196
CHASSISD_FM_ACTION_FPC_ONLINE	196
CHASSISD_FM_ACTION_FPC_POWER_OFF	197
CHASSISD_FM_ACTION_FPC_RECOVERY	197
CHASSISD_FM_ACTION_FPC_RESTART	197
CHASSISD_FM_ACTION_PLANE_OFFLINE	198
CHASSISD_FM_ACTION_PLANE_ONLINE	198
CHASSISD_FM_BAD_STATE	198
CHASSISD_FM_DETECT_FPC_FABRIC_DEGRADED	198
CHASSISD_FM_DETECT_PLANES_DOWN	199
CHASSISD_FM_DETECT_UNREACHABLE	199
CHASSISD_FM_ERROR	199
CHASSISD_FM_ERROR_CLOS_F13_HSR	200
CHASSISD_FM_ERROR_CLOS_F13_HST	200
CHASSISD_FM_ERROR_CLOS_F2_HSR	200
CHASSISD_FM_ERROR_CLOS_F2_HST	201
CHASSISD_FM_ERROR_F13_FB_HSR_TXP	201
CHASSISD_FM_ERROR_F13_FB_RX_VC	202
CHASSISD_FM_ERROR_F13_FB_TXP	202
CHASSISD_FM_ERROR_F13_FB_TX_VC	202
CHASSISD_FM_ERROR_F13_VC_PWR	203
CHASSISD_FM_ERROR_LCC_SIB_CBL	203
CHASSISD_FM_ERROR_LCC_SIB_HSR_PFE	203
CHASSISD_FM_ERROR_LCC_SIB_HSR_XC	204
CHASSISD_FM_ERROR_LCC_SIB_OPTICS_FAULT	204
CHASSISD_FM_ERROR_LCC_SIB_RX_OPTICS	204
CHASSISD_FM_ERROR_LCC_SIB_TX_OPTICS	205
CHASSISD_FM_ERROR_SC_CLOS_F13_HSR	205
CHASSISD_FM_ERROR_SC_CLOS_F13_HST	205
CHASSISD_FM_ERROR_SC_CLOS_F2_HSR	206
CHASSISD_FM_ERROR_SC_CLOS_F2_HST	206
CHASSISD_FM_ERROR_SC_SIB_CBL	207
CHASSISD_FM_ERROR_SC_SIB_HSR_XC	207

CHASSISD_FM_ERROR_SC_SIB_OPTICS_FAULT	207
CHASSISD_FM_ERROR_SC_SIB_RX_OPTICS	208
CHASSISD_FM_ERROR_SC_SIB_TX_OPTICS	208
CHASSISD_FM_ERROR_SIB_L_FB_HSR	208
CHASSISD_FM_ERROR_SIB_L_FB_RX_VC	209
CHASSISD_FM_ERROR_SIB_L_FB_SMF	209
CHASSISD_FM_ERROR_SIB_L_FB_TXP	209
CHASSISD_FM_ERROR_SIB_L_FB_TX_VC	210
CHASSISD_FM_ERROR_SIB_L_HSR_PFE	210
CHASSISD_FM_ERROR_SIB_L_HSR_TXP	210
CHASSISD_FM_ERROR_SIB_L_MISMATCH	211
CHASSISD_FM_ERROR_SIB_L_VC_PWR	211
CHASSISD_FM_ERROR_SIB_S_FB_HSR	212
CHASSISD_FM_ERROR_SIB_S_FB_SMF	212
CHASSISD_FM_FABRIC_DEGRADED	212
CHASSISD_FM_FPC_FABRIC_DEGRADED	213
CHASSISD_FM_MEMORY_ERROR	213
CHASSISD_FM_SIB_ERROR	213
CHASSISD_FM_SIB_FPC_TYPE_ERROR	213
CHASSISD_FPC_JAM_HSL2_PARAMS_TIMEOUT	214
CHASSISD_FPC_NOT_FOUND	214
CHASSISD_FPC_OPTICS_HOT_NOTICE	214
CHASSISD_FPC_PIC_DETECT_TIMEOUT	214
CHASSISD_FPC_TYPE_SIB_TYPE_ERROR	215
CHASSISD_FRU_ALREADY_OFFLINE	215
CHASSISD_FRU_ALREADY_ONLINE	215
CHASSISD_FRU_EVENT	216
CHASSISD_FRU_FIRE_TEMP_CONDITION	216
CHASSISD_FRU_HIGH_TEMP_CONDITION	216
CHASSISD_FRU_INVALID_SLOT	216
CHASSISD_FRU_IO_ERROR	217
CHASSISD_FRU_IO_OFFSET_ERROR	217
CHASSISD_FRU_IPC_WRITE_ERROR	217
CHASSISD_FRU_OFFLINE_FAILED	218
CHASSISD_FRU_OFFLINE_NOTICE	218
CHASSISD_FRU_OFFLINE_TIMEOUT	218
CHASSISD_FRU_ONLINE_TIMEOUT	218
CHASSISD_FRU_OVER_TEMP_CONDITION	219
CHASSISD_FRU_STEP_ERROR	219
CHASSISD_FRU_UNRESPONSIVE	219
CHASSISD_FRU_UNRESPONSIVE_RETRY	219
CHASSISD_FRU_UNSUPPORTED	220
CHASSISD_FRU_VERSION_MISMATCH	220
CHASSISD_GASIC_ID_ERROR	220
CHASSISD_GBUS_NOT_READY	221
CHASSISD_GBUS_READBACK_ERROR	221
CHASSISD_GBUS_RESET_EVENT	221
CHASSISD_GBUS_SANITY_ERROR	221
CHASSISD_GENERIC_ERROR	222

CHASSISD_GENERIC_WARNING	222
CHASSISD_GETTIMEOFDAY	222
CHASSISD_GRES_UNSUPP_PIC	222
CHASSISD_HIGH_TEMP_CONDITION	223
CHASSISD_HOST_TEMP_READ	223
CHASSISD_HSR_CONFIG_READ_ERROR	223
CHASSISD_HSR_CONFIG_WRITE_ERROR	223
CHASSISD_HSR_ELEMENTS_ERROR	224
CHASSISD_HSR_FIFO_ERROR	224
CHASSISD_I2CS_READBACK_ERROR	224
CHASSISD_I2C_BAD_IDEEPROM_FORMAT	224
CHASSISD_I2C_FIC_PRESENCE_READ	225
CHASSISD_I2C_GENERIC_ERROR	225
CHASSISD_I2C_INVALID_ASSEMBLY_ID	225
CHASSISD_I2C_IOCTL_FAILURE	226
CHASSISD_I2C_IO_FAILURE	226
CHASSISD_I2C_MIDPLANE_CORRUPT	226
CHASSISD_I2C_RANGE_ERROR	226
CHASSISD_I2C_READ_ERROR	227
CHASSISD_I2C_WRITE_ERROR	227
CHASSISD_IDEEPROM_READ_ERROR	227
CHASSISD_IFDEV_CREATE_FAILURE	227
CHASSISD_IFDEV_CREATE_NOTICE	228
CHASSISD_IFDEV_DETACH_ALL_PSEUDO	228
CHASSISD_IFDEV_DETACH_FPC	228
CHASSISD_IFDEV_DETACH_PIC	229
CHASSISD_IFDEV_DETACH_PSEUDO	229
CHASSISD_IFDEV_DETACH_TLV_ERROR	229
CHASSISD_IFDEV_GETBYNAME_NOTICE	229
CHASSISD_IFDEV_GET_BY_INDEX_FAIL	230
CHASSISD_IFDEV_GET_BY_NAME_FAIL	230
CHASSISD_IFDEV_NO_MEMORY	230
CHASSISD_IFDEV_RETRY_NOTICE	230
CHASSISD_IFDEV_RTSLIB_FAILURE	231
CHASSISD_IFILTER_INSTALL_ERROR	231
CHASSISD_IOCTL_FAILURE	231
CHASSISD_IPC_ANNOUNCE_TIMEOUT	231
CHASSISD_IPC_CONNECTION_DROPPED	232
CHASSISD_IPC_DAEMON_WRITE_ERROR	232
CHASSISD_IPC_ERROR	232
CHASSISD_IPC_FLUSH_ERROR	233
CHASSISD_IPC_MSG_DROPPED	233
CHASSISD_IPC_MSG_ERROR	233
CHASSISD_IPC_MSG_FRU_NOT_FOUND	234
CHASSISD_IPC_MSG_QFULL_ERROR	234
CHASSISD_IPC_MSG_UNHANDLED	234
CHASSISD_IPC_UNEXPECTED_MSG	234
CHASSISD_IPC_UNEXPECTED_RECV	235
CHASSISD_IPC_WRITE_ERROR	235

CHASSISD_IPC_WRITE_ERR_NO_PIPE	235
CHASSISD_IPC_WRITE_ERR_NULL_ARGS	235
CHASSISD_ISSU_BLOB_ERROR	236
CHASSISD_ISSU_DAEMON_ERROR	236
CHASSISD_ISSU_ERROR	236
CHASSISD_ISSU_FRU_ERROR	236
CHASSISD_ISSU_FRU_IPC_ERROR	237
CHASSISD_JTREE_ERROR	237
CHASSISD_LCC_RELEASE_MASTERSHIP	237
CHASSISD_LOST_MASTERSHIP	237
CHASSISD_MAC_ADDRESS_AE_ERROR	238
CHASSISD_MAC_ADDRESS_ATS_ERROR	238
CHASSISD_MAC_ADDRESS_CBP_ERROR	238
CHASSISD_MAC_ADDRESS_ERROR	238
CHASSISD_MAC_ADDRESS_FABRIC_ERR	239
CHASSISD_MAC_ADDRESS_IRB_ERROR	239
CHASSISD_MAC_ADDRESS_PIP_ERROR	239
CHASSISD_MAC_ADDRESS_PLT_ERROR	239
CHASSISD_MAC_ADDRESS_SWFAB_ERR	240
CHASSISD_MAC_ADDRESS_VIRB_ERROR	240
CHASSISD_MAC_ADDRESS_VLAN_ERROR	240
CHASSISD_MAC_ADDRESS_VTEP_ERROR	240
CHASSISD_MAC_DEFAULT	241
CHASSISD_MAIN_THREAD_STALLED	241
CHASSISD_MALLOC_FAILURE	241
CHASSISD_MASTER_CG_REMOVED	241
CHASSISD_MASTER_PCG_REMOVED	242
CHASSISD_MASTER_SCG_REMOVED	242
CHASSISD_MBUS_ERROR	242
CHASSISD_MCHASSIS_SWITCH_WARNING	242
CHASSISD_MCS_INTR_ERROR	243
CHASSISD_MGR_CONNECT	243
CHASSISD_MIC_OFFLINE_NOTICE	243
CHASSISD_MULTILINK_BUNDLES_ERROR	244
CHASSISD_MXC_LINK	244
CHASSISD_NO_CGS	244
CHASSISD_NO_PCGS	244
CHASSISD_NO_SCGS	245
CHASSISD_OFFLINE_NOTICE	245
CHASSISD_OID_GEN_FAILED	245
CHASSISD_OVER_TEMP_CONDITION	245
CHASSISD_OVER_TEMP_SHUTDOWN_TIME	246
CHASSISD_PARSE_COMPLETE	246
CHASSISD_PCI_ERROR	246
CHASSISD_PDU_BREAKER_TRIP	247
CHASSISD_PDU_NOT_OK	247
CHASSISD_PEER_UNCONNECTED	247
CHASSISD_PEM_BREAKER_TRIP	247
CHASSISD_PEM_IMPROPER	248

CHASSISD_PEM_INPUT_BAD	248
CHASSISD_PEM_NOT_SUFFICIENT	248
CHASSISD_PEM_OVERLOAD	249
CHASSISD_PEM_TEMPERATURE	249
CHASSISD_PEM_VOLTAGE	249
CHASSISD_PFE_LAUNCH_ERROR	249
CHASSISD_PIC_CMD_GIVEUP	250
CHASSISD_PIC_CMD_TIMEOUT	250
CHASSISD_PIC_CONFIG_CONFLICT	250
CHASSISD_PIC_CONFIG_ERROR	250
CHASSISD_PIC_HWERROR	251
CHASSISD_PIC_OFFLINE_NOTICE	251
CHASSISD_PIC_OID_GEN_FAILED	251
CHASSISD_PIC_OID_UNKNOWN	252
CHASSISD_PIC_PORT_ERROR	252
CHASSISD_PIC_RESET_ON_SWITCHOVER	252
CHASSISD_PIC_SPEED_INVALID	252
CHASSISD_PIC_VERSION_ERROR	253
CHASSISD_PIDFILE_OPEN	253
CHASSISD_POWER_CHECK	253
CHASSISD_POWER_EVENT	254
CHASSISD_POWER_ON_CHECK_FAILURE	254
CHASSISD_POWER_RATINGS_EXCEEDED	254
CHASSISD_PSD_RELEASE_MASTERSHIP	254
CHASSISD_PSM_NOT_OK	255
CHASSISD_PSM_NOT_OK_1	255
CHASSISD_PSM_TRIP	255
CHASSISD_PSU_ERROR	255
CHASSISD_PSU_FAN_FAIL	256
CHASSISD_PSU_INPUT_BAD	256
CHASSISD_PSU_OVERLOAD	256
CHASSISD_PSU_TEMPERATURE	257
CHASSISD_PSU_VOLTAGE	257
CHASSISD_RANGE_CHECK	257
CHASSISD_RECONNECT_SUCCESSFUL	258
CHASSISD_RELEASE_MASTERSHIP	258
CHASSISD_RE_CONSOLE_FE_STORM	258
CHASSISD_RE_CONSOLE_ME_STORM	258
CHASSISD_RE_INIT_INVALID_RE_SLOT	259
CHASSISD_RE_OVER_TEMP_CONDITION	259
CHASSISD_RE_OVER_TEMP_SHUTDOWN	259
CHASSISD_RE_OVER_TEMP_WARNING	259
CHASSISD_RE_WARM_TEMP_CONDITION	260
CHASSISD_ROOT_MOUNT_ERROR	260
CHASSISD_RTS_SEQ_ERROR	260
CHASSISD_SBOARD_VERSION_MISMATCH	261
CHASSISD_SENSOR_RANGE_NOTICE	261
CHASSISD_SERIAL_ID	261
CHASSISD_SFC_FPM_CHCFG_WARNING	261

CHASSISD_SFM_MODE_ERROR	262
CHASSISD_SFM_NOT_ONLINE	262
CHASSISD_SHUTDOWN_NOTICE	262
CHASSISD_SIB_INVALID_SLOT	263
CHASSISD_SIGPIPE	263
CHASSISD_SMB_ERROR	263
CHASSISD_SMB_INVALID_PS	263
CHASSISD_SMB_IOCTL_FAILURE	264
CHASSISD_SMB_READ_FAILURE	264
CHASSISD_SNMP_TRAP1	264
CHASSISD_SNMP_TRAP10	265
CHASSISD_SNMP_TRAP3	265
CHASSISD_SNMP_TRAP6	265
CHASSISD_SNMP_TRAP7	265
CHASSISD_SPI_IOCTL_FAILURE	266
CHASSISD_SPMB_RESTART	266
CHASSISD_SPMB_RESTART_TIMEOUT	266
CHASSISD_SSB_FAILOVERS	266
CHASSISD_STANDALONE_FPC_NOTICE	267
CHASSISD_SYSCTL_ERROR	267
CHASSISD_TEMP_HOT_NOTICE	267
CHASSISD_TEMP_SENSOR_FAILURE	267
CHASSISD_TERM_SIGNAL	268
CHASSISD_TIMER_CLR_ERR	268
CHASSISD_TIMER_ERR	268
CHASSISD_TIMER_VAL_ERR	268
CHASSISD_UNEXPECTED_EXIT	269
CHASSISD_UNEXPECTED_VALUE	269
CHASSISD_UNSUPPORTED_FPC	269
CHASSISD_UNSUPPORTED_MODEL	270
CHASSISD_UNSUPPORTED_PIC	270
CHASSISD_UNSUPPORTED_PIC_MODE	270
CHASSISD_UNSUPPORTED_SIB	270
CHASSISD_VCHASSIS_CONVERT_ERROR	271
CHASSISD_VCHASSIS_LICENSE_ERROR	271
CHASSISD_VCHASSIS_MEMBER_LIST_NOTICE	271
CHASSISD_VCHASSIS_MEMBER_OP_NOTICE	271
CHASSISD_VCHASSIS_MEMBER_UPDATE_NOTICE	272
CHASSISD_VERSION_MISMATCH	272
CHASSISD_VOLTAGE_READ_FAILED	272
CHASSISD_VOLTAGE_SENSOR_INIT	273
CHASSISD_VSERIES_LICENSE_ERROR	273
CHASSISD_ZONE_BLOWERS_SPEED	273
CHASSISD_ZONE_BLOWERS_SPEED_FULL	273
CHASSISD_ZONE_BLOWERS_SPEED_OFF	273
Chapter 24 CHASSISM System Log Messages	275
CHASSISM_SYSTEM	275

Chapter 25	CLKSYNCD System Log Messages	277
	CLKSYNCD_EVENT_BITS_DPLL_STATUS	277
	CLKSYNCD_EVENT_DPLL_STATUS	277
	CLKSYNCD_EVENT_LED_STATE_CHANGED	277
	CLKSYNCD_EVENT_PRI_REF_CHANGED	278
	CLKSYNCD_EVENT_PRI_SRC_RECOVERED	278
	CLKSYNCD_EVENT_PTP_CLOCK_ACCU_CHG	278
	CLKSYNCD_EVENT_PTP_CLOCK_CLASS_CHG	278
	CLKSYNCD_EVENT_PTP_GM_CHG	279
	CLKSYNCD_EVENT_PTP_HYBRID_STATUS	279
	CLKSYNCD_EVENT_PTP_SERVO_STATUS	279
	CLKSYNCD_EVENT_RX_QL_CHANGED	279
	CLKSYNCD_EVENT_SEC_REF_CHANGED	280
	CLKSYNCD_EVENT_SEC_SRC_RECOVERED	280
	CLKSYNCD_EVENT_SQUELCH_CLEAR	280
	CLKSYNCD_EVENT_SQUELCH_SET	280
	CLKSYNCD_EVENT_SYNCE_DPLL_STATUS	281
	CLKSYNCD_EVENT_TX_QL_CHANGED	281
	CLKSYNCD_FAULT_ACBC_NOT_COMPATIBLE	281
	CLKSYNCD_FAULT_CPLD_NOT_COMPATIBLE	281
	CLKSYNCD_FAULT_EFD_CLEAR	282
	CLKSYNCD_FAULT_EFD_SET	282
	CLKSYNCD_FAULT_LOS_CLEAR	282
	CLKSYNCD_FAULT_LOS_SET	282
	CLKSYNCD_FAULT_LO_ESMC_CLEAR	283
	CLKSYNCD_FAULT_LO_ESMC_SET	283
	CLKSYNCD_FAULT_LTI_CLEAR	283
	CLKSYNCD_FAULT_LTI_SET	283
	CLKSYNCD_FAULT_PRI_SRC_FAILED	284
	CLKSYNCD_FAULT_PTP_UNI_NEG_RATE_REJ_CLEAR	284
	CLKSYNCD_FAULT_PTP_UNI_NEG_RATE_REJ_SET	284
	CLKSYNCD_FAULT_QL_FAIL_CLEAR	284
	CLKSYNCD_FAULT_QL_FAIL_SET	285
	CLKSYNCD_FAULT_SEC_SRC_FAILED	285
Chapter 26	COSD System Log Messages	287
	COSD_AGGR_CONFIG_INVALID	287
	COSD_CHASSIS_SCHED_MAP_INVALID	287
	COSD_CLASSIFIER_NO_SUPPORT_LSI	288
	COSD_CLASS_8021P_UNSUPPORTED	288
	COSD_CLASS_NO_SUPPORT_IFD	288
	COSD_CLASS_NO_SUPPORT_L3_IFL	289
	COSD_CONF_OPEN_FAILURE	289
	COSD_DB_OPEN_FAILED	289
	COSD_EXACT_RATE_UNSUPP_INTERFACE	290
	COSD_EXACT_RATE_UNSUPP_SESSION	290
	COSD_EXP_RW_L2_IFL_NOT_SUPPORTED	290
	COSD_FABRIC_QUEUE_OVERFLOW	291
	COSD_FRAGMENTATION_MAP_CONFLICT	291

	COSD_HIGH_PRIO_QUEUES_INTERFACE	291
	COSD_HIGH_PRIO_QUEUES_SESSION	292
	COSD_IFD_OUTPUT_SHAPING_RATE_ERR	292
	COSD_IFD_SHAPER_ERR	293
	COSD_INTERFACE_NO_MEDIA	293
	COSD_L2TP_COS_NOT_CONFIGURED	293
	COSD_L2TP_COS_NOT_SUPPORTED	294
	COSD_L2TP_SHAPING_NOT_CONFIGURED	294
	COSD_LARGE_DELAY_BUFFER_INVALID	294
	COSD_MALLOC_FAILED	295
	COSD_MAX_FORWARDING_CLASSES_ABC	295
	COSD_MPLS_DSCP_CLASS_NO_SUPPORT	295
	COSD_MULTILINK_CLASS_CONFLICT	296
	COSD_NULL_INPUT_ARGUMENT	296
	COSD_OUT_OF_DEDICATED_QUEUES	296
	COSD_RATE_LIMIT_INVALID	296
	COSD_RATE_LIMIT_NOT_SUPPORTED	297
	COSD_REWRITE_RULE_LIMIT_EXCEEDED	297
	COSD_RL_IFL_NEEDS_SHAPING	298
	COSD_SCHEDULER_MAP_CONFLICT	298
	COSD_SCHED_AVG_CONST_UNSUPPORTED	298
	COSD_SCHED_MAP_GROUP_CONFLICT	299
	COSD_SHAPER_GROUP_CONFLICT	299
	COSD_STREAM_IFD_CREATE_FAILURE	299
	COSD_TIMER_ERROR	299
	COSD_TRICOLOR_ALWAYS_ON	300
	COSD_TRICOLOR_NOT_SUPPORTED	300
	COSD_TX_QUEUE_RATES_TOO_HIGH	301
	COSD_UNKNOWN_CLASSIFIER	301
	COSD_UNKNOWN_REWRITE	301
	COSD_UNKNOWN_TRAFFIC_CLASS_MAP	302
	COSD_UNKNOWN_TRANSLATION_TABLE	302
	COSD_WAN_QUEUE_OVERFLOW	302
Chapter 27	DCBX System Log Messages	303
	DCBX_PFC_DISABLED	303
	DCBX_PFC_ENABLED	303
	DCBX_VERSION	303
Chapter 28	DCD System Log Messages	305
	DCD_AE_CONFIG_WARNING	305
	DCD_FWD_CLASS_ACC_NOT_SUPPORTED	305
	DCD_FWD_CLASS_ACC_NOT_SUPPORTED_IFL	305
	DCD_GRE_CONFIG_INVALID	306
	DCD_GRE_CONFIG_NOT_SUPPORTED	306
	DCD_MALLOC_FAILED_INIT	306
	DCD_PARSE_CFG_WARNING	306
	DCD_PARSE_EMERGENCY	307
	DCD_PARSE_ERROR_CLOCK	307
	DCD_PARSE_ERROR_HIER_SCHEDULER	307

	DCD_PARSE_ERROR_IFLSET	308
	DCD_PARSE_ERROR_MAX_HIER_LEVELS	308
	DCD_PARSE_ERROR_MAX_HIER_LEVELS_2	308
	DCD_PARSE_ERROR_SCHEDULER	309
	DCD_PARSE_ERROR_SCHEDULER_LIMIT	309
	DCD_PARSE_ERROR_VLAN_TAGGING	309
	DCD_PARSE_MINI_EMERGENCY	309
	DCD_PARSE_STATE_EMERGENCY	310
	DCD_PARSE_WARN_INCOMPATIBLE_CFG	310
	DCD_RLT_CONFIG_UNSUPPORTED	310
Chapter 29	DDOS System Log Messages	313
	DDOS_PROTOCOL_VIOLATION_CLEAR	313
	DDOS_PROTOCOL_VIOLATION_SET	313
	DDOS_RTsock_FAILURE	313
	DDOS_SCFD_FLOW_AGGREGATED	314
	DDOS_SCFD_FLOW_CLEARED	314
	DDOS_SCFD_FLOW_DEAGGREGATED	314
	DDOS_SCFD_FLOW_FOUND	315
	DDOS_SCFD_FLOW_RETURN_NORMAL	315
	DDOS_SCFD_FLOW_TIMEOUT	315
Chapter 30	DFCD System Log Messages	317
	DFCD_FTAP_PIC_UNSUPPORTED	317
	DFCD_GENCFG_MALLOC_FAILED	317
	DFCD_GENCFG_WRITE_FAILED	317
	DFCD_LINH_MALLOC_FAILED	318
	DFCD_LI_NEXT_HOP_ADD_FAILED	318
	DFCD_NEXT_HOP_ADD_FAILED	318
	DFCD_NEXT_HOP_DELETE_FAILED	318
	DFCD_SAMPLE_CLASS_ADD_FAILED	319
	DFCD_SAMPLE_CLASS_DELETE_FAILED	319
Chapter 31	DFWD System Log Messages	321
	DFWD_MALLOC_FAILED_INIT	321
	DFWD_PARSE_FILTER_EMERGENCY	321
	DFWD_PARSE_STATE_EMERGENCY	321
	DFWD_POLICER_LIMIT_EXCEEDED	322
Chapter 32	DHCPD System Log Messages	323
	DHCPD_BIND_FAILURE	323
	DHCPD_DEGRADED_MODE	323
	DHCPD_MEMORY_ALLOCATION_FAILURE	323
	DHCPD_OPTION_HOST_NAME	324
	DHCPD_OPTION_LOG_SERVER	324
	DHCPD_OPTION_NTP_SERVER	324
	DHCPD_OVERLAY_CONFIG_FAILURE	324
	DHCPD_OVERLAY_PARSE_FAILURE	325
	DHCPD_RECVMSG_FAILURE	325
	DHCPD_RTsock_FAILURE	325

	DHCPD_SENDMSG_FAILURE	326
	DHCPD_SENDMSG_NOINT_FAILURE	326
	DHCPD_SETSOCKOPT_FAILURE	326
	DHCPD_SOCKET_FAILURE	326
Chapter 33	DIAM System Log Messages	329
	DIAM_PEER_CONN_STATE_CHANGE	329
	DIAM_PEER_OUTQ_HIGH_WATERMARK	329
	DIAM_PEER_OUTQ_LOW_WATERMARK	329
	DIAM_PROFILE_STATE_CHANGE	330
	DIAM_SPIC_UNAVAILABLE	330
	DIAM_TARGET_STATE_CHANGE	330
Chapter 34	DOT1XD System Log Messages	331
	DOT1XD_AUTH_SESSION_DELETED	331
	DOT1XD_MKA_FAIL_ACTION_USER_ALLOWED	331
	DOT1XD_MKA_FAIL_ACTION_USER_PROHIBITED	331
	DOT1XD_MKA_SECURE_CHANNEL_CREATED	332
	DOT1XD_MKA_SECURE_CHANNEL_DELETED	332
	DOT1XD_RCVD_EAPLOGOF_ATHNTCTNG	332
	DOT1XD_RCVD_EAPLOGOF_ATHNTICTD	332
	DOT1XD_RCVD_EAPLOGOF_CONNECTNG	332
	DOT1XD_USR_ACCESS_DENIED	333
	DOT1XD_USR_ATHNTICTD_GST_VLAN	333
	DOT1XD_USR_AUTHENTICATED	333
	DOT1XD_USR_ON_SRVR_FAIL_VLAN	333
	DOT1XD_USR_ON_SRVR_REJECT_VLAN	334
	DOT1XD_USR_SESSION_DISCONNECTED	334
	DOT1XD_USR_SESSION_HELD	334
	DOT1XD_USR_UNATHNTCTD_CLI_CLRD	334
Chapter 35	DYNAMIC System Log Messages	335
	DYNAMIC_VPN_AUTH_CONNECT_FAIL	335
	DYNAMIC_VPN_AUTH_FAIL	335
	DYNAMIC_VPN_AUTH_INVALID	335
	DYNAMIC_VPN_AUTH_MUL_CONN	336
	DYNAMIC_VPN_AUTH_NO_CONFIG	336
	DYNAMIC_VPN_AUTH_NO_LICENSE	336
	DYNAMIC_VPN_AUTH_OK	336
	DYNAMIC_VPN_CLIENT_CONFIG_WRITE	336
	DYNAMIC_VPN_CONN_DEL_NOTIFY	337
	DYNAMIC_VPN_CONN_DEL_REQUEST	337
	DYNAMIC_VPN_CONN_EST_NOTIFY	337
	DYNAMIC_VPN_INIT_SUCCESSFUL	337
	DYNAMIC_VPN_LICENSE_ASSIGNED	338
	DYNAMIC_VPN_LICENSE_CHECK_FAILED	338
	DYNAMIC_VPN_LICENSE_CHECK_OK	338
	DYNAMIC_VPN_LICENSE_EXHAUSTED	338
	DYNAMIC_VPN_LICENSE_FREED	338
	DYNAMIC_VPN_LICENSE_FREE_FAILED	339

	DYNAMIC_VPN_LICENSE_FREE_OK	339
	DYNAMIC_VPN_LICENSE_GET_FAILED	339
	DYNAMIC_VPN_LICENSE_GET_OK	339
	DYNAMIC_VPN_LICENSE_INSTALLED	339
	DYNAMIC_VPN_LICENSE_REQUIRED	340
	DYNAMIC_VPN_LICENSE_UNINSTALLED	340
Chapter 36	ESWD System Log Messages	341
	ESWD_BPDU_BLOCK_ERROR_DISABLED	341
	ESWD_BPDU_BLOCK_ERROR_ENABLED	341
	ESWD_DAI_FAILED	341
	ESWD_DHCP_UNTRUSTED	342
	ESWD_GLOBAL_MAC_LIMIT_ERROR	342
	ESWD_INVALID_MAC_ADDRESS	342
	ESWD_LEARNT_FDB_MEMORY_ERROR	342
	ESWD_MAC_LIMIT_ALERT	343
	ESWD_MAC_LIMIT_BLOCK	343
	ESWD_MAC_LIMIT_DROP	343
	ESWD_MAC_LIMIT_EXCEEDED	343
	ESWD_MAC_MOVE_LIMIT_BLOCK	344
	ESWD_MAC_MOVE_LIMIT_DROP	344
	ESWD_MAC_MOVE_LIMIT_EXCEEDED	344
	ESWD_MAC_SMAC_BRIDGE_MAC_IDENTICAL	345
	ESWD_MIRROR_ERROR	345
	ESWD_MIRROR_VERSION_MISMATCH	345
	ESWD_MODULE_SHUTDOWN_FAILURE	346
	ESWD_NDI_FAILED	346
	ESWD_OUT_OF_LOW_MEMORY	346
	ESWD_PPM_READ_ERROR	346
	ESWD_PPM_WRITE_ERROR	347
	ESWD_STATIC_FDB_MEMORY_WARNING	347
	ESWD_STP_BASE_MAC_ERROR	347
	ESWD_STP_LOOP_PROTECT_CLEARED	347
	ESWD_STP_LOOP_PROTECT_IN_EFFECT	348
	ESWD_STP_ROOT_PROTECT_CLEARED	348
	ESWD_STP_ROOT_PROTECT_IN_EFFECT	348
	ESWD_STP_STATE_CHANGE_INFO	348
	ESWD_ST_CTL_BW_INFO	349
	ESWD_ST_CTL_ERROR_DISABLED	349
	ESWD_ST_CTL_ERROR_ENABLED	349
	ESWD_ST_CTL_ERROR_IN_EFFECT	349
	ESWD_ST_CTL_INFO	349
	ESWD_VLAN_MAC_LIMIT_EXCEEDED	350
	ESWD_VMEMBER_MAC_LIMIT_DROP	350
Chapter 37	EVENTD System Log Messages	351
	EVENTD_ACK_FAILED	351
	EVENTD_ALARM_CLEAR	351
	EVENTD_ALARM_FILE	351
	EVENTD_AUDIT_DISABLED	352

	EVENTD_AUDIT_ENABLED	352
	EVENTD_AUDIT_SHOW	352
	EVENTD_COMMAND_SUBSTITUTE_ERROR	352
	EVENTD_CONFIG_CHANGE_FAILED	353
	EVENTD_CONFIG_CHANGE_SUCCESS	353
	EVENTD_ESCRIPT_EXECUTION	353
	EVENTD_ESCRIPT_NOT_CONFIGURED	353
	EVENTD_EVENT_SEND_FAILED	353
	EVENTD_FORK_ERR	354
	EVENTD_JAIL_SOCKET_FAILURE	354
	EVENTD_PARSE_CONTROL_INFO_FAILED	354
	EVENTD_PIPE_CREATION_FAILED	354
	EVENTD_POLICY_ACTION_FAILED	355
	EVENTD_POLICY_LIMIT_EXCEEDED	355
	EVENTD_POLICY_UPLOAD_FAILED	355
	EVENTD_POOPEN_FAIL	355
	EVENTD_READ_ERROR	356
	EVENTD_REGEX_INVALID	356
	EVENTD_REG_VERSION_MISMATCH	356
	EVENTD_ROTATE_COMMAND_FAILED	356
	EVENTD_ROTATE_FORK_EXCEEDED	357
	EVENTD_ROTATE_FORK_FAILED	357
	EVENTD_SCRIPT_CHECKSUM_MISMATCH	357
	EVENTD_SECURITY_LOG_CLEAR	357
	EVENTD_SET_PROCESS_PRIV_FAILED	357
	EVENTD_SET_TIMER_FAILED	358
	EVENTD_SYSLOG_FWD_FAILED	358
	EVENTD_TEST_ALARM	358
	EVENTD_TRANSFER_COMMAND_FAILED	358
	EVENTD_TRANSFER_FORK_EXCEEDED	359
	EVENTD_TRANSFER_FORK_FAILED	359
	EVENTD_VERSION_MISMATCH	359
	EVENTD_XML_FILENAME_INVALID	359
Chapter 38	FABOAMD System Log Messages	361
	FABOAMD_DEBUGGING	361
Chapter 39	FC System Log Messages	363
	FC_FABRIC_CREATED	363
	FC_FABRIC_DELETED	363
	FC_FABRIC_WWN_ASSIGNED	363
	FC_FABRIC_WWN_CLEARED	363
	FC_FLOGI_VN_PORT_LOGIN_FAILED	364
	FC_LOGICAL_INTERFACE_CREATED	364
	FC_LOGICAL_INTERFACE_DELETED	364
	FC_LOGICAL_INTERFACE_ISOLATED	364
	FC_PROXY_NP_PORT_AVAILABLE	365
	FC_PROXY_NP_PORT_LB_ADDED	365
	FC_PROXY_NP_PORT_LB_REMOVED	365
	FC_PROXY_NP_PORT_LOGIN_ABORTED	365

	FC_PROXY_NP_PORT_LOGIN_FAILED	365
	FC_PROXY_NP_PORT_LOGOUT	366
	FC_PROXY_NP_PORT_NPIV_FAILED	366
	FC_PROXY_NP_PORT_OFFLINE	366
	FC_PROXY_NP_PORT_ONLINE	366
	FC_PROXY_NP_PORT_RESTORE_FAILED	367
	FC_PROXY_NP_PORT_UNAVAILABLE	367
	FC_PROXY_VN_PORT_LOGIN_ABORTED	367
	FC_PROXY_VN_PORT_LOGIN_FAILED	367
Chapter 40	FCOE System Log Messages	369
	FCOE_LOGICAL_INTERFACE_CREATED	369
	FCOE_LOGICAL_INTERFACE_DELETED	369
	FCOE_LOGICAL_INTERFACE_ISOLATED	369
Chapter 41	FIP System Log Messages	371
	FIP_ENODE_CLEARED	371
	FIP_ENODE_FKA_TIMER_EXPIRED	371
	FIP_ENODE_LEARNED	371
	FIP_ENODE_TIMER_EXPIRED	371
	FIP_FCF_TIMER_EXPIRED	372
	FIP_MAX_FCOE_FILTERS_REACHED	372
	FIP_MAX_SESSIONS_REACHED	372
	FIP_PROTOCOL_STARTED	372
	FIP_PROTOCOL_STOPPED	373
	FIP_VN_PORT_FKA_TIMER_EXPIRED	373
	FIP_VN_PORT_LOGIN_FAILED	373
	FIP_VN_PORT_SESSION_CLEARED	373
	FIP_VN_PORT_SESSION_CREATED	374
	FIP_VN_PORT_TIMER_EXPIRED	374
Chapter 42	FIPS System Log Messages	375
	FIPS_KNOWN_ANSWER_TEST	375
Chapter 43	FLOW System Log Messages	377
	FLOW_APP_POLICY_VIOLATION	377
	FLOW_DSTIP_POLICY_VIOLATION	377
	FLOW_HIGH_WATERMARK_TRIGGERED	377
	FLOW_HIGH_WATERMARK_TRIGGERED_LS	378
	FLOW_IP_ACTION	378
	FLOW_IP_ACTION_LS	378
	FLOW_LOW_WATERMARK_TRIGGERED	378
	FLOW_LOW_WATERMARK_TRIGGERED_LS	379
	FLOW_POLICY_VIOLATION	379
	FLOW_REASSEMBLE_FAIL	379
	FLOW_REASSEMBLE_SUCCEED	380
	FLOW_SRCIP_POLICY_VIOLATION	380
Chapter 44	FPCLOGIN System Log Messages	381
	FPCLOGIN_ADDRESS_GET_FAILED	381
	FPCLOGIN_IPC_RECEIVE_FAILED	381

	FPCLOGIN_IPC_SEND_FAILED	381
	FPCLOGIN_LOGIN_FAILED	382
	FPCLOGIN_MESSAGE_INVALID	382
	FPCLOGIN_SOCKET_OPERATION_FAILED	382
Chapter 45	FSAD System Log Messages	383
	FSAD_CONFIG_ERROR	383
	FSAD_CONNTIMEDOUT	383
	FSAD_DIR_CREATE	383
	FSAD_DIR_STAT	384
	FSAD_FAILED	384
	FSAD_FILE_FAILED	384
	FSAD_FILE_REMOVE	384
	FSAD_FILE_RENAME	385
	FSAD_FILE_STAT	385
	FSAD_FILE_SYNC	385
	FSAD_FLOWC_IPC_PAYLOAD_SIZE	386
	FSAD_FLOWC_IPC_SUBTYPE	386
	FSAD_FLOWC_IPC_TYPE	386
	FSAD_FLOWC_IPC_VERSION	386
	FSAD_FLOWC_SERVICE_INACTIVE	387
	FSAD_FREE_SPACE_LOG	387
	FSAD_FREE_SPACE_TMP	387
	FSAD_FS_STAT	387
	FSAD_GEN_IPC_PAYLOAD_SIZE	388
	FSAD_GEN_IPC_SUBTYPE	388
	FSAD_GEN_IPC_TYPE	388
	FSAD_GEN_IPC_VERSION	388
	FSAD_GEN_SERVICE_INACTIVE	389
	FSAD_GEN_SERVICE_INIT_FAILED	389
	FSAD_MAXCONN	389
	FSAD_MEMORYALLOC_FAILED	389
	FSAD_NOT_ROOT	390
	FSAD_PARENT_DIRECTORY	390
	FSAD_PATH_IS_DIRECTORY	390
	FSAD_PATH_IS_NOT_DIRECTORY	390
	FSAD_PATH_IS_SPECIAL	391
	FSAD_RECVERROR	391
	FSAD_RENAME	391
	FSAD_TERMINATED_CONNECTION	391
	FSAD_TRACEOPEN_FAILED	392
	FSAD_USAGE	392
Chapter 46	FUD System Log Messages	393
	FUD_ARGUMENT_FAILURE	393
	FUD_BAD_SERVER_ADDR_FAILURE	393
	FUD_BIND_FAILURE	393
	FUD_DAEMON_FAILURE	394
	FUD_MEMORY_ALLOCATION_FAILURE	394
	FUD_PERMISSION_FAILURE	394

	FUD_PIDLOCK_FAILURE	394
	FUD_PIDUPDATE_FAILURE	395
	FUD_RECVMSG_FAILURE	395
	FUD_RTsock_WRITE_FAILURE	395
	FUD_SENDMSG_FAILURE	396
	FUD_SENDMSG_NOINT_FAILURE	396
	FUD_SETSOCKOPT_FAILURE	396
	FUD_SOCKET_FAILURE	397
Chapter 47	FWAUTH System Log Messages	399
	FWAUTH_FTP_LONG_PASSWORD	399
	FWAUTH_FTP_LONG_PASSWORD_LS	399
	FWAUTH_FTP_LONG_USERNAME	399
	FWAUTH_FTP_LONG_USERNAME_LS	399
	FWAUTH_FTP_USER_AUTH_ACCEPTED	400
	FWAUTH_FTP_USER_AUTH_ACCEPTED_LS	400
	FWAUTH_FTP_USER_AUTH_FAIL	400
	FWAUTH_FTP_USER_AUTH_FAIL_LS	400
	FWAUTH_HTTP_USER_AUTH_ACCEPTED	401
	FWAUTH_HTTP_USER_AUTH_FAIL	401
	FWAUTH_HTTP_USER_AUTH_FAIL_LS	401
	FWAUTH_HTTP_USER_AUTH_OK_LS	401
	FWAUTH_TELNET_LONG_PASSWORD	401
	FWAUTH_TELNET_LONG_PASSWORD_LS	402
	FWAUTH_TELNET_LONG_USERNAME	402
	FWAUTH_TELNET_LONG_USERNAME_LS	402
	FWAUTH_TELNET_USER_AUTH_ACCEPTED	402
	FWAUTH_TELNET_USER_AUTH_FAIL	402
	FWAUTH_TELNET_USER_AUTH_FAIL_LS	403
	FWAUTH_TELNET_USER_AUTH_OK_LS	403
	FWAUTH_WEBAUTH_FAIL	403
	FWAUTH_WEBAUTH_FAIL_LS	403
	FWAUTH_WEBAUTH_SUCCESS	403
	FWAUTH_WEBAUTH_SUCCESS_LS	404
Chapter 48	GPRSD System Log Messages	405
	GPRSD_MEMORY_ALLOC_FAILED	405
	GPRSD_RESTART_CCFG_READ_FAILED	405
Chapter 49	HNCACHED System Log Messages	407
	HNCACHED_HOST_ADDRESS_CHANGED	407
	HNCACHED_NAME_RESOLUTION_FAILURE	407
Chapter 50	ICCPD System Log Messages	409
	ICCPD_ASSERT_SOFT	409
	ICCPD_OPEN_ERROR	409
	ICCPD_READ_ERROR	410
	ICCPD_WRITE_ERROR	410

Chapter 51	IDP System Log Messages	411
	IDP_APPDDOS_APP_ATTACK_EVENT	411
	IDP_APPDDOS_APP_ATTACK_EVENT_LS	411
	IDP_APPDDOS_APP_STATE_EVENT	412
	IDP_APPDDOS_APP_STATE_EVENT_LS	412
	IDP_ATTACK_LOG_EVENT	412
	IDP_ATTACK_LOG_EVENT_LS	413
	IDP_COMMIT_COMPLETED	413
	IDP_COMMIT_FAILED	413
	IDP_DAEMON_INIT_FAILED	414
	IDP_IGNORED_IPV6_ADDRESSES	414
	IDP_INTERNAL_ERROR	414
	IDP_POLICY_COMPILATION_FAILED	414
	IDP_POLICY_LOAD_FAILED	415
	IDP_POLICY_LOAD_SUCCEEDED	415
	IDP_POLICY_UNLOAD_FAILED	415
	IDP_POLICY_UNLOAD_SUCCEEDED	415
	IDP_SCHEDULEDUPDATE_START_FAILED	415
	IDP_SCHEDULED_UPDATE_STARTED	416
	IDP_SECURITY_INSTALL_RESULT	416
	IDP_SESSION_LOG_EVENT	416
	IDP_SESSION_LOG_EVENT_LS	416
	IDP_SIGNATURE_LICENSE_EXPIRED	416
Chapter 52	JADE System Log Messages	419
	JADE_ATTRIBUTES_TOO_LONG	419
	JADE_AUTH_FAILURE	419
	JADE_AUTH_SUCCESS	419
	JADE_EXEC_ERROR	419
	JADE_IRI_AUTH_SUCCESS	420
	JADE_PAM_ERROR	420
	JADE_PAM_NO_LOCAL_USER	420
	JADE_SOCKET_ERROR	420
Chapter 53	JCS System Log Messages	423
	JCS_BBD_LOAD_FAILURE	423
	JCS_BBD_LOCAL_MISMATCH	423
	JCS_BBD_NOT_FOUND	423
	JCS_BBD_NOT_VALID	424
	JCS_BBD_PARSE_ERROR	424
	JCS_BBD_PEER_MISMATCH	424
	JCS_BBD_SYSTEM_CONFLICT	424
	JCS_INVALID_BANDWIDTH_ERROR	425
	JCS_KERNEL_RSD_LINK_DOWN	425
	JCS_KERNEL_RSD_LINK_ENABLED	425
	JCS_MM_COMMUNICATION_ERROR	425
	JCS_MM_COMMUNICATION_OK	426
	JCS_PEER_BLADE_STATE	426
	JCS_READ_BANDWIDTH_ERROR	426

	JCS_READ_BBD_ERROR	426
	JCS_SWITCH_BANDWIDTH_CONFIG	427
	JCS_SWITCH_COMMUNICATION_ERROR	427
Chapter 54	JDAMETERD System Log Messages	429
	JDAMETERD_FUNC_HSHAKE_FAIL	429
	JDAMETERD_FUNC_LOCACCEPT_NFOUND	429
	JDAMETERD_FUNC_NSCK_LISTEN_FAIL	429
	JDAMETERD_FUNC_OUT_OF_SYNC	430
	JDAMETERD_FUNC_PICACCEPT_NFOUND	430
	JDAMETERD_FUNC_TOO_MANY_BADEZES	430
	JDAMETERD_FUNC_USCK_LISTEN_FAIL	430
Chapter 55	JIVED System Log Messages	431
	JIVED_ALREADY_RUNNING	431
	JIVED_EVLIB_FUNC_FAILED	431
	JIVED_INITIATE_CONN_FAILED	431
	JIVED_INIT_FAILED	432
	JIVED_NOT_ROOT	432
	JIVED_PIDFILE_LOCK_FAILED	432
	JIVED_PIDFILE_UPDATE_FAILED	432
	JIVED_SNMP_SEND_TRAP_FAILED	433
Chapter 56	JNUD System Log Messages	435
	JNUD_CONFIG_ERROR	435
	JNUD_INIT_FAILED	435
Chapter 57	JPTSPD System Log Messages	437
	JPTSPD_INIT_FAILURE	437
	JPTSPD_OUT_OF_MEMORY	437
	JPTSPD_PIC_CONNECTED	438
	JPTSPD_PIC_DISCONNECTED	438
	JPTSPD_SRC_FAST_SYNC_ABORT	438
	JPTSPD_SRC_FAST_SYNC_DONE	438
	JPTSPD_SRC_FAST_SYNC_START	438
	JPTSPD_SRC_FULL_SYNC_ABORT	439
	JPTSPD_SRC_FULL_SYNC_DONE	439
	JPTSPD_SRC_FULL_SYNC_START	439
Chapter 58	JSERVICES System Log Messages	441
	JSERVICES_NAT_OUTOF_ADDRESSES	441
	JSERVICES_NAT_OUTOF_PORTS	441
	JSERVICES_NAT_POOL_RELEASE	441
	JSERVICES_NAT_PORT_BLOCK_ACTIVE	442
	JSERVICES_NAT_PORT_BLOCK_ALLOC	442
	JSERVICES_NAT_PORT_BLOCK_RELEASE	442
	JSERVICES_NAT_RULE_MATCH	442
	JSERVICES_SESSION_CLOSE	443
	JSERVICES_SESSION_OPEN	443
	JSERVICES_SFW_RULE_ACCEPT	443
	JSERVICES_SFW_RULE_DISCARD	444

Chapter 59

JSERVICES_SFW_RULE_REJECT	444
JSRPD System Log Messages	445
JSRPD_DAEMONIZE_FAILED	445
JSRPD_DUPLICATE	445
JSRPD_NODE_STATE_CHANGE	445
JSRPD_NOT_ROOT	446
JSRPD_PID_FILE_LOCK	446
JSRPD_PID_FILE_UPDATE	446
JSRPD_REDUNDANCY_MODE_CHANGE	446
JSRPD_REDUNDANCY_MODE_MISMATCH	447
JSRPD_RG_STATE_CHANGE	447
JSRPD_SET_CS_MON_FAILURE	447
JSRPD_SET_HW_MON_FAILURE	447
JSRPD_SET_INTF_MON_FAILURE	448
JSRPD_SET_IP_MON_FAILURE	448
JSRPD_SET_LOOPBACK_MON_FAILURE	448
JSRPD_SET_MBUF_MON_FAILURE	448
JSRPD_SET_NEXTHOP_MON_FAILURE	449
JSRPD_SET_NPC_MON_FAILURE	449
JSRPD_SET_OTHER_INTF_MON_FAIL	449
JSRPD_SET_SPU_MON_FAILURE	449
JSRPD_SOCKET_CREATION_FAILURE	449
JSRPD_SOCKET_LISTEN_FAILURE	450
JSRPD_SOCKET_RECV_HB_FAILURE	450
JSRPD_UNSET_CS_MON_FAILURE	450
JSRPD_UNSET_HW_MON_FAILURE	450
JSRPD_UNSET_INTF_MON_FAILURE	451
JSRPD_UNSET_IP_MON_FAILURE	451
JSRPD_UNSET_LOOPBACK_MON_FAILURE	451
JSRPD_UNSET_MBUF_MON_FAILURE	451
JSRPD_UNSET_NEXTHOP_MON_FAILURE	452
JSRPD_UNSET_NPC_MON_FAILURE	452
JSRPD_UNSET_OTHER_INTF_MON_FAIL	452
JSRPD_UNSET_SPU_MON_FAILURE	452
JSRPD_USAGE	453

Chapter 60

JTASK System Log Messages	455
JTASK_ABORT	455
JTASK_ACTIVE_TERMINATE	455
JTASK_ASSERT	455
JTASK_ASSERT_SOFT	456
JTASK_BFD_READ_ERROR	456
JTASK_BFD_WRITE_ERROR	456
JTASK_CFG_CALLBACK_LONGRUNTIME	457
JTASK_CFG_SCHED_CUMU_LONGRUNTIME	457
JTASK_EXIT	457
JTASK_LOCK_FLOCKED	458
JTASK_LOCK_LOCKED	458
JTASK_MGMT_TIMEOUT	458

	JTASK_MODE_SWITCH	459
	JTASK_MODE_SWITCH_FAIL	459
	JTASK_OS_MEMHIGH	459
	JTASK_PARSE_BAD_COMMAND	459
	JTASK_PARSE_BAD_FILE	460
	JTASK_PARSE_BAD_LR_NAME	460
	JTASK_PARSE_BAD_OPTION	460
	JTASK_PARSE_CMD_ARG	460
	JTASK_PARSE_CMD_DUPLICATE	461
	JTASK_PARSE_CMD_EXTRA	461
	JTASK_PTHREAD_CREATE	461
	JTASK_SCHED_CUMU_LONGRUNTIME	462
	JTASK_SCHED_MODULE_LONGRUNTIME	462
	JTASK_SCHED_TASK_LONGRUNTIME	462
	JTASK_SIGNAL_TERMINATE	462
	JTASK_SNMP_CONN_EINPROGRESS	463
	JTASK_SNMP_CONN_QUIT	463
	JTASK_SNMP_CONN_RETRY	463
	JTASK_SNMP_INVALID_SOCKET	463
	JTASK_SNMP_SOCKOPT_BLOCK	464
	JTASK_SNMP_SOCKOPT_RECVBUF	464
	JTASK_SNMP_SOCKOPT_SENDBUF	464
	JTASK_START	464
	JTASK_SYSTEM	465
	JTASK_TASK_BEGIN	465
	JTASK_TASK_CHILDKILLED	465
	JTASK_TASK_CHILDSTOPPED	465
	JTASK_TASK_DYN_REINIT	466
	JTASK_TASK_FORK	466
	JTASK_TASK_GETWD	466
	JTASK_TASK_MASTERSHIP	466
	JTASK_TASK_NOREINIT	467
	JTASK_TASK_PIDCLOSED	467
	JTASK_TASK_PIDFLOCK	467
	JTASK_TASK_PIDWRITE	467
	JTASK_TASK_REINIT	467
	JTASK_TASK_SIGNALIGNORE	468
	JTASK_TERMINATE_DISK_SPACE	468
Chapter 61	JTRACE System Log Messages	469
	JTRACE_FAILED	469
Chapter 62	KMD System Log Messages	471
	KMD_CFG_IF_ID_POOL_NOT_FOUND	471
	KMD_CFG_IF_ID_POOL_NO_ENTRY	471
	KMD_CFG_IF_ID_POOL_NO_INTERFACE	471
	KMD_CFG_IF_ID_POOL_RETURN_FAILED	472
	KMD_DPD_FAILOVER_MANUAL_TUNNEL	472
	KMD_DPD_FAILOVER_MAX_ATTEMPTS	472
	KMD_DPD_FAILOVER_NO_ACTIVE_PEER	472

KMD_DPD_FAILOVER_NO_BACKUP_PEER	473
KMD_DPD_FAILOVER_NO_TUNNEL_CFG	473
KMD_DPD_REMOTE_ADDRESS_CHANGED	473
KMD_PM_DUPLICATE_LIFE_DURATION	473
KMD_PM_IKE_SERVER_LOOKUP_FAILED	474
KMD_PM_IKE_SERVER_NOT_FOUND	474
KMD_PM_IKE_SRV_NOT_FOUND_DELETE	474
KMD_PM_ILLEGAL_REMOTE_GW_ID	474
KMD_PM_INCONSISTENT_P2_IDS	475
KMD_PM_INVALID_LIFE_TYPE	475
KMD_PM_LIFETIME_TO_SHORT	475
KMD_PM_NO_LIFETIME	475
KMD_PM_NO_LIFE_TYPE	476
KMD_PM_NO_PROPOSAL_FOR_PHASE1	476
KMD_PM_NO_SPD_PHASE1_FUNC_PTR	476
KMD_PM_P1_POLICY_LOOKUP_FAILURE	476
KMD_PM_P2_POLICY_LOOKUP_FAILURE	477
KMD_PM_PHASE1_GROUP_UNSPECIFIED	477
KMD_PM_PHASE1_POLICY_SEARCH_FAIL	477
KMD_PM_PHASE2_POLICY_LOOKUP_FAIL	477
KMD_PM_PROTO_INVALID	478
KMD_PM_PROTO_IPCOMP_UNSUPPORTED	478
KMD_PM_PROTO_ISAKMP_RESV_UNSUPP	478
KMD_PM_SA_CFG_NOT_FOUND	478
KMD_PM_SA_ESTABLISHED	479
KMD_PM_SA_INDEX_GEN_FAILED	479
KMD_PM_SA_PEER_ABSENT	479
KMD_PM_SA_PEER_NOT_FOUND	479
KMD_PM_SPI_DELETE_REJECT	480
KMD_PM_UNEQUAL_PAYLOAD_LENGTH	480
KMD_PM_UNINITIALISE_ERROR	480
KMD_PM_UNINITIALIZE_FAILED	480
KMD_PM_UNKNOWN_P1_IDENTITIES	481
KMD_PM_UNKNOWN_PHASE2_ENTITIES	481
KMD_PM_UNKNOWN_QM_NOTIFICATION	481
KMD_PM_UNSUPPORTED_KEY	481
KMD_PM_UNSUPPORTED_MODE	482
KMD_SNMP_EXTRA_RESPONSE	482
KMD_SNMP_FATAL_ERROR	482
KMD_SNMP_MALLOC_FAILED	482
KMD_SNMP_PIC_CONNECTION_FAILED	483
KMD_SNMP_PIC_NO_RESPONSE	483
KMD_SNMP_PIC_SLOT_NOT_FOUND	483
KMD_VPN_DFBIT_STATUS_MSG	483
KMD_VPN_DOWN_ALARM_USER	484
KMD_VPN_PV_LIFETIME_CHANGED	484
KMD_VPN_PV_PHASE1	484
KMD_VPN_PV_PHASE2	484
KMD_VPN_PV_PSK_CHANGED	484

Chapter 63

KMD_VPN_UP_ALARM_USER	485
L2ALD System Log Messages	487
L2ALD_BD_CREATE_FAILURE	487
L2ALD_BD_CREATE_RETRY_SUCCESS	487
L2ALD_BD_NAME_RESTRICTION	488
L2ALD_DEFAULT_VLAN_DISABLED	488
L2ALD_DUPLICATE_RBEB_MAC	488
L2ALD_FREE_MAC_FAILED	488
L2ALD_GENCFG_OP_FAILED	489
L2ALD_IFBD_COUNT_EXCEED	489
L2ALD_IPC_MESSAGE_ERROR	489
L2ALD_IPC_MESSAGE_INVALID	489
L2ALD_IPC_MESSAGE_SEND_FAILED	490
L2ALD_IPC_PIPE_WRITE_ERROR	490
L2ALD_MAC_LIMIT_EXCEEDED_BD	490
L2ALD_MAC_LIMIT_EXCEEDED_BLOCK	491
L2ALD_MAC_LIMIT_EXCEEDED_IF	491
L2ALD_MAC_LIMIT_EXCEEDED_IFBD	492
L2ALD_MAC_LIMIT_REACHED_BD	492
L2ALD_MAC_LIMIT_REACHED_GLOBAL	492
L2ALD_MAC_LIMIT_REACHED_IF	493
L2ALD_MAC_LIMIT_REACHED_IFBD	493
L2ALD_MAC_LIMIT_REACHED_RTT	493
L2ALD_MAC_LIMIT_RESET_BD	494
L2ALD_MAC_LIMIT_RESET_GLOBAL	494
L2ALD_MAC_LIMIT_RESET_IF	494
L2ALD_MAC_LIMIT_RESET_RTT	495
L2ALD_MAC_MOVE_EXCEEDED_BD	495
L2ALD_MAC_MOVE_EXCEEDED_BD_ACTION_NONE	496
L2ALD_MAC_MOVE_NOTIFICATION	496
L2ALD_MAC_MOVE_NOTIF_ACTION	496
L2ALD_MAC_MOVE_NOTIF_EXTENSIVE	497
L2ALD_MAC_MOVE_SHUTDOWN	497
L2ALD_MALLOC_FAILED	497
L2ALD_MANAGER_CONNECT	498
L2ALD_NAME_LENGTH_IF_DEVICE	498
L2ALD_NAME_LENGTH_IF_FAMILY	498
L2ALD_NAME_LENGTH_IF_LOGICAL	498
L2ALD_PBBN_IFL_REVA	499
L2ALD_PBBN_REINSTATE_IFBDS	499
L2ALD_PBBN_RETRACT_IFBDS	499
L2ALD_PIP_IFD_READ_RETRY	500
L2ALD_RPD_LR_ALLOC_FAILED	500
L2ALD_RPD_SESS_CREATE_FAILED	500
L2ALD_RPD_SESS_HANDLE_ALLOC_FAIL	501
L2ALD_RPD_SOCKET_ALLOC_FAILED	501
L2ALD_RPD_STATE_ALLOC_FAILED	501
L2ALD_RPD_VERSION_MISMATCH	501

	L2ALD_ST_CTL_DISABLED	501
	L2ALD_ST_CTL_ENABLED	502
	L2ALD_ST_CTL_IN_EFFECT	502
Chapter 64	L2CPD System Log Messages	503
	L2CPD_KERNEL_VERSION	503
	L2CPD_KERNEL_VERSION_OLD	503
	L2CPD_KERNEL_VERSION_UNSUPP	503
	L2CPD_MIRROR_ERROR	504
	L2CPD_MIRROR_VERSION_MISMATCH	504
	L2CPD_PPM_READ_ERROR	504
	L2CPD_PPM_WRITE_ERROR	505
	L2CPD_XSTP_SHUTDOWN_FAILED	505
Chapter 65	L2TPD System Log Messages	507
	L2TPD_COS_PROFILE_ADD	507
	L2TPD_COS_PROFILE_DELETE	507
	L2TPD_DB_ADD_FAILED	508
	L2TPD_DB_DELETE_FAILED	508
	L2TPD_DB_INIT_FAILED	508
	L2TPD_DB_TUN_GRP_ALLOC_FAILED	508
	L2TPD_DEFAULT_PROTO_CREATE_FAIL	509
	L2TPD_EVLIB_CREATE_FAILED	509
	L2TPD_EVLIB_FD_DEREGISTER_FAILED	509
	L2TPD_EVLIB_FD_DESELECT_FAILED	509
	L2TPD_EVLIB_FD_NOT_REGISTERED	509
	L2TPD_EVLIB_FD_SELECT_FAILED	510
	L2TPD_EVLIB_TIMER_CLEAR_FAILED	510
	L2TPD_EVLIB_TIMER_SET_FAILED	510
	L2TPD_FILTER_FILE_OPEN_FAILED	510
	L2TPD_GLOBAL_CFG_ADD_FAILED	511
	L2TPD_GLOBAL_CFG_CHANGE_FAILED	511
	L2TPD_GLOBAL_CFG_DELETE_FAILED	511
	L2TPD_IFD_ADD_FAILED	511
	L2TPD_IFD_DELETE_FAILED	511
	L2TPD_IFD_MSG_REGISTER_FAILED	512
	L2TPD_IFD_ROOT_ALLOC_FAILED	512
	L2TPD_IFL_ADD_FAILED	512
	L2TPD_IFL_DELETE_FAILED	512
	L2TPD_IFL_MSG_REGISTER_FAILED	513
	L2TPD_IFL_NOT_FOUND	513
	L2TPD_IFL_ROOT_ALLOC_FAILED	513
	L2TPD_INSTANCE_CREATE_FAILED	513
	L2TPD_INSTANCE_RESTART_FAILED	514
	L2TPD_INTERFACE_ID_NOT_FOUND	514
	L2TPD_MESSAGE_REGISTER_FAILED	514
	L2TPD_MLPPP_BUNDLE_ALLOC_FAILED	514
	L2TPD_MLPPP_BUNDLE_CREATE_FAILED	515
	L2TPD_MLPPP_BUNDLE_INVALID_ID	515
	L2TPD_MLPPP_COPY_CFG_FAILED	515

L2TPD_MLPPP_ID_ALLOC_FAILED	515
L2TPD_MLPPP_ID_BITMAP_ALLOC_FAIL	515
L2TPD_MLPPP_ID_NODE_ADD_FAILED	516
L2TPD_MLPPP_ID_ROOT_ALLOC_FAILED	516
L2TPD_MLPPP_LINK_CREATE_FAILED	516
L2TPD_MLPPP_LINK_MAX_EXCEEDED	516
L2TPD_MLPPP_POOL_ADDRESS_FAILED	517
L2TPD_MLPPP_SESSION_CREATE_FAIL	517
L2TPD_MLPPP_SESSION_DELETE_FAIL	517
L2TPD_MLPPP_SPEED_MISMATCH	517
L2TPD_NH_DELETE_FAILED	518
L2TPD_POLICER_ADD_FAILED	518
L2TPD_POLICER_PROFILE_DEL_FAILED	518
L2TPD_POOL_ADDRESS_FAILED	518
L2TPD_POOL_ASSIGN_ADDRESS_FAILED	519
L2TPD_PPP_ROUTE_ADD_FAILED	519
L2TPD_PPP_ROUTE_DELETE_FAILED	519
L2TPD_PROFILE_NOT_FOUND	519
L2TPD_PROFILE_NO_RADIUS_SERVERS	520
L2TPD_RADIUS_ACCT_PORT_ZERO	520
L2TPD_RADIUS_GETHOSTNAME_FAILED	520
L2TPD_RADIUS_RT_INST_ENOENT	520
L2TPD_RADIUS_RT_INST_NOT_FOUND	520
L2TPD_RADIUS_SERVER_NOT_FOUND	521
L2TPD_RADIUS_SRC_ADDR_BIND_FAIL	521
L2TPD_RADIUS_SRC_ADDR_ENOENT	521
L2TPD_RPD_ASYNC_UNREG_FAILED	521
L2TPD_RPD_ROUTE_ADD_CB_FAILED	522
L2TPD_RPD_ROUTE_ADD_FAILED	522
L2TPD_RPD_ROUTE_DELETE_CB_FAILED	522
L2TPD_RPD_ROUTE_DELETE_FAILED	522
L2TPD_RPD_ROUTE_PREFIX_TOO_LONG	523
L2TPD_RPD_SESS_CREATE_FAILED	523
L2TPD_RPD_SESS_HANDLE_ALLOC_FAIL	523
L2TPD_RPD_SOCKET_ALLOC_FAILED	523
L2TPD_RPD_TBL_LOCATE_BY_NAME	523
L2TPD_RPD_TBL_LOCATE_FAILED	524
L2TPD_RPD_VERSION_MISMATCH	524
L2TPD_RTSLIB_ASYNC_OPEN_FAILED	524
L2TPD_RTSLIB_OPEN_FAILED	524
L2TPD_SERVER_START_FAILED	525
L2TPD_SERVICE_NH_ADD_FAILED	525
L2TPD_SERVICE_NH_DELETE_FAILED	525
L2TPD_SESSION_CFG_ADD_ERROR	525
L2TPD_SESSION_CFG_ADD_FAILED	526
L2TPD_SESSION_CFG_DELETE_FAILED	526
L2TPD_SESSION_DELETE_FAILED	526
L2TPD_SESSION_IFF_NOT_FOUND	526
L2TPD_SESSION_IFL_ADD_FAILED	527

	L2TPD_SESSION_IFL_ALLOC_FAILED	527
	L2TPD_SESSION_IFL_CLI_TREE_ALLOC	527
	L2TPD_SESSION_IFL_DELETED	527
	L2TPD_SESSION_IFL_DELETE_FAILED	527
	L2TPD_SESSION_IFL_GET_FAILED	528
	L2TPD_SESSION_IFL_NOT_EQUAL	528
	L2TPD_SESSION_IFL_NOT_FOUND	528
	L2TPD_SESSION_IFL_OCCUPIED	528
	L2TPD_SESSION_IFL_REMOVE_FAILED	529
	L2TPD_SESSION_INVALID_PEER_IP	529
	L2TPD_SESSION_IP_DUPLICATE	529
	L2TPD_SESSION_ROUTE_ADD_FAILED	529
	L2TPD_SESSION_RT_TBL_NOT_FOUND	530
	L2TPD_SESSION_TUNNEL_ID_MISMATCH	530
	L2TPD_SETSOCKOPT_FAILED	530
	L2TPD_SET_ASYNC_CONTEXT	530
	L2TPD_SHOW_MULTILINK	531
	L2TPD_SHOW_SESSION	531
	L2TPD_SHOW_TUNNEL	531
	L2TPD_SOCKET_FAILED	531
	L2TPD_SUBUNIT_ROUTE_ALLOC_FAILED	532
	L2TPD_TRACE_FILE_OPEN_FAILED	532
	L2TPD_TUNNEL_CFG_ADD_FAILED	532
	L2TPD_TUNNEL_CFG_ADD_INV_ADDR	532
	L2TPD_TUNNEL_CFG_DELETE_FAILED	532
	L2TPD_TUNNEL_DELETE_FAILED	533
	L2TPD_TUNNEL_DEST_IF_LOOKUP_FAIL	533
	L2TPD_TUNNEL_GROUP_ADD_FAILED	533
	L2TPD_TUNNEL_GROUP_CFG_ADD_FAIL	533
	L2TPD_TUNNEL_GROUP_CFG_DEL_FAIL	534
	L2TPD_TUNNEL_GROUP_CREATE_FAILED	534
	L2TPD_TUNNEL_GROUP_DELETE_FAILED	534
	L2TPD_TUNNEL_GROUP_IDX_MISMATCH	534
	L2TPD_TUNNEL_GROUP_RESTART_FAIL	535
	L2TPD_USER_AUTHN_NOT_FOUND	535
	L2TPD_USER_AUTHN_ORDER_UNKNOWN	535
	L2TPD_USER_AUTHN_PWD_NOT_FOUND	535
Chapter 66	LACP System Log Messages	537
	LACP_INTF_DOWN	537
Chapter 67	LACPD System Log Messages	539
	LACPD_ISSU_ACK_TIMEOUT	539
	LACPD_MEMORY_ALLOCATION_FAILED	539
	LACPD_TIMEOUT	539
Chapter 68	LFMD System Log Messages	541
	LFMD_3AH_LINKDOWN	541
	LFMD_3AH_LINKUP	541
	LFMD_3AH_LOCAL_LB_CHANGED	541

	LFMD_3AH_LT_LOOP_CLEARED	541
	LFMD_3AH_LT_LOOP_DETECTED	542
	LFMD_3AH_REQ_REMOTE_LB_CHANGE	542
	LFMD_RTsock_OPEN_FAILED	542
Chapter 69	LIBJNX System Log Messages	543
	LIBJNX_AUDIT_ERROR	543
	LIBJNX_AUDIT_TACPLUS_ERROR	543
	LIBJNX_COMPRESS_EXEC_FAILED	544
	LIBJNX_DEFAULT_IP_ADDR_NOT_SET	544
	LIBJNX_EVLIB_FAILURE	544
	LIBJNX_EXEC_EXITED	545
	LIBJNX_EXEC_FAILED	545
	LIBJNX_EXEC_PIPE	545
	LIBJNX_EXEC_SINGALED	546
	LIBJNX_EXEC_WEXIT	546
	LIBJNX_FILE_COPY_FAILED	546
	LIBJNX_FILE_SYSTEM_FAIL	546
	LIBJNX_FILE_SYSTEM_SPACE	547
	LIBJNX_INVALID_XML_DATA	547
	LIBJNX_LOGIN_ACCOUNTS_NOT_LOCKED	547
	LIBJNX_LOGIN_ACCOUNT_LOCKED	547
	LIBJNX_LOGIN_ACCOUNT_NOT_LOCKED	547
	LIBJNX_LOGIN_ACCOUNT_UNLOCKED	548
	LIBJNX_LOGIN_ACCT_NOT_UNLOCKED	548
	LIBJNX_PRIV_LOWER_FAILED	548
	LIBJNX_PRIV_RAISE_FAILED	548
	LIBJNX_REPLICATE_RCP_ERROR	549
	LIBJNX_REPLICATE_RCP_EXEC_FAILED	549
	LIBJNX_SNMP_ENGINE_FILE_FAILURE	549
	LIBJNX_SNMP_ENGINE_SCAN_FAILURE	550
	LIBJNX_SOCKET_BUFF_ERROR	550
	LIBJNX_SOCKET_FAILURE	550
	LIBJNX_SOCKET_FLUSH_TIMEOUT	551
	LIBJNX_XML_DECODE_FAILED	551
Chapter 70	LIBJSNMP System Log Messages	553
	LIBJSNMP_CTX_FAILURE	553
	LIBJSNMP_IPC_ERROR	553
	LIBJSNMP_IPC_READ_ERROR	553
	LIBJSNMP_MTHD_API_UNKNOWN_TYPE	554
	LIBJSNMP_NS_LOG_CRIT	554
	LIBJSNMP_NS_LOG_EMERG	554
	LIBJSNMP_NS_LOG_ERR	555
	LIBJSNMP_OID_GEN_FAILED	555
	LIBJSNMP_READ_LEN_ERR	555
	LIBJSNMP_RTMSIZE_MISMATCH_ERR	555
	LIBJSNMP_SMS_HDR_ERR	556
	LIBJSNMP_SMS_MSG_ERR	556
	LIBJSNMP_SNMP_PH_INIT_ERR	556

	LIBJSNMP_SOCKET_OPEN_ERR	557
	LIBJSNMP_SOCKET_VER_MISMATCH	557
	LIBJSNMP_TRAP_API_FAILURE	557
	LIBJSNMP_TRAP_UTILS_ERR	558
Chapter 71	LIBMSRPC System Log Messages	559
	LIBMSRPC_CLIENT_INIT_FAILED	559
	LIBMSRPC_CLIENT_KCOM_FAILED	559
	LIBMSRPC_CLIENT_KCOM_NO_IF	559
	LIBMSRPC_CLIENT_NO_CONNECTION	560
	LIBMSRPC_CLIENT_NO_REPLY	560
	LIBMSRPC_CLIENT_PIC_DOWN	561
	LIBMSRPC_CLIENT_WRONG_OUTPUT	561
Chapter 72	LICENSE System Log Messages	563
	LICENSE_CONNECT_FAILURE	563
	LICENSE_CONN_TO_LI_CHECK_FAILURE	563
	LICENSE_CONN_TO_LI_CHECK_SUCCESS	563
	LICENSE_EXPIRED	564
	LICENSE_EXPIRED_KEY_DELETED	564
	LICENSE_GRACE_PERIOD_APPROACHING	564
	LICENSE_GRACE_PERIOD_EXCEEDED	564
	LICENSE_GRACE_PERIOD_EXPIRED	565
	LICENSE_INCORRECT_USAGE_API	565
	LICENSE_INVALIDATE_FEATURE_ID	565
	LICENSE_JVERSION_READ_ERROR	565
	LICENSE_LIST_MANAGEMENT	566
	LICENSE_NEARING_EXPIRY	566
	LICENSE_READ_ERROR	566
	LICENSE_REG_ERROR	566
	LICENSE_REVOKE_DB_CREATE_FAILURE	567
	LICENSE_REVOKE_DB_OPEN_FAILURE	567
	LICENSE_SHM_ATTACH_FAILURE	567
	LICENSE_SHM_CREATE_FAILURE	567
	LICENSE_SHM_DETACH_FAILURE	567
	LICENSE_SHM_DIR_OPEN_FAILURE	568
	LICENSE_SHM_FILE_OPEN_FAILURE	568
	LICENSE_SHM_KEY_CREATE_FAILURE	568
	LICENSE_SHM_SCALE_READ_FAILURE	568
	LICENSE_SHM_SCALE_UPDATE_FAILURE	568
	LICENSE_SHM_USAGE_READ_FAILURE	569
	LICENSE_SHM_USAGE_WRITE_FAILURE	569
	LICENSE_SIGNATURE_VERIFY_FAILED	569
	LICENSE_UNKNOWN_RESPONSE_TYPE	569
	LICENSE_VERIFICATION_FILE_ERROR	569
Chapter 73	LLDP System Log Messages	571
	LLDP_NEIGHBOR_DOWN	571
	LLDP_NEIGHBOR_UP	571

Chapter 74	LOGIN System Log Messages	573
	LOGIN_ABORTED	573
	LOGIN_ATTEMPTS_THRESHOLD	573
	LOGIN_FAILED	573
	LOGIN_FAILED_LIMIT	573
	LOGIN_FAILED_SET_CONTEXT	574
	LOGIN_FAILED_SET_LOGIN	574
	LOGIN_HOSTNAME_UNRESOLVED	574
	LOGIN_INFORMATION	574
	LOGIN_MALFORMED_USER	575
	LOGIN_PAM_AUTHENTICATION_ERROR	575
	LOGIN_PAM_ERROR	575
	LOGIN_PAM_MAX_RETRIES	575
	LOGIN_PAM_STOP	575
	LOGIN_PAM_USER_UNKNOWN	576
	LOGIN_PASSWORD_EXPIRED	576
	LOGIN_REFUSED	576
	LOGIN_ROOT	576
	LOGIN_TIMED_OUT	577
Chapter 75	LPDFD System Log Messages	579
	LPDFD_DYN_PDB_OPEN_FAILED	579
	LPDFD_DYN_REGISTER_FAILED	579
	LPDFD_PCONN_SERVER	579
Chapter 76	LRMUX System Log Messages	581
	LRMUX_FAILED_EXEC	581
	LRMUX_LRPD_PID_LOCK	581
	LRMUX_LRPD_PID_OPEN	581
	LRMUX_LRPD_SEND_HUP	582
Chapter 77	LSYSD System Log Messages	583
	LRMUX_FAILED_EXEC	583
	LRMUX_LRPD_PID_LOCK	583
	LRMUX_LRPD_PID_OPEN	583
	LRMUX_LRPD_SEND_HUP	584
Chapter 78	MBG System Log Messages	585
	MBG_ADDR_ALLOC_ALLOCATED	585
	MBG_ADDR_ALLOC_MM	585
	MBG_ADDR_ALLOC_NO_ADDR	585
	MBG_ADDR_ALLOC_NO_POOL	586
	MBG_ADDR_ALLOC_NO_VRF	586
	MBG_ADDR_ALLOC_UNDEFINED	586
	MBG_ADDR_APFE_DN	586
	MBG_ADDR_APFE_UP	586
	MBG_ADDR_INIT_OK	587
	MBG_ADDR_MM_ACK	587
	MBG_ADDR_MM_ENABLE	587
	MBG_ADDR_NO_MEMORY_HEAP	587

MBG_ADDR_NO_MEMORY_OC	587
MBG_ADDR_PRIMARY	588
MBG_ADDR_SECONDARY	588
MBG_ADDR_STANDALONE	588
MBG_CFG_COMMIT_FAIL	588
MBG_CFG_DB_OPEN_FAIL	589
MBG_CG_CONF_SERVER_REGIST_FAIL	589
MBG_CG_CP_MM_STATE_CHANGE	589
MBG_CG_EVENT_SERVER_REGIST_FAIL	589
MBG_CG_TSP_MM_STATE_CHANGE	589
MBG_CG_UI_SERVER_REGIST_FAIL	590
MBG_CMD_ATTACH_FAIL	590
MBG_CMD_CDR_DEST	590
MBG_CMD_CDR_ENCODING_FAIL	590
MBG_CMD_CONF_CLIENT_INIT_FAIL	591
MBG_CMD_EVE_CLIENT_INIT_FAIL	591
MBG_CMD_GTPP_DOWN	591
MBG_CMD_GTPP_UP	591
MBG_CMD_GTPP_VER_MIS_MATCH	591
MBG_CMD_GW_SER_UP	592
MBG_CMD_HA_CHARGED_CONNEC_FAIL	592
MBG_CMD_HMEM_THRES	592
MBG_CMD_IRI_EXTRACT_FAIL	592
MBG_CMD_LMEM_THRES	593
MBG_CMD_MMEM_THRES	593
MBG_CMD_PMNGR_IPC_REGISTER_FAIL	593
MBG_CMD_PMNGR_SERVER_CONNEC_FAIL	593
MBG_CMD_RE_DISK_FULL	593
MBG_CMD_RE_DISK_FULL_RESOLVED	594
MBG_CMD_RE_DISK_OFFLINE	594
MBG_CMD_RE_DISK_ONLINE	594
MBG_CMD_TIMER_START_FAIL	594
MBG_CMD_TIMER_STOP_FAIL	595
MBG_CMD_TSP_LOOK_UP_FAIL	595
MBG_CMD_UI_CLIENT_INIT_FAIL	595
MBG_CMD_WFA_FULL	595
MBG_CONF_SERVER_INIT_FAIL	595
MBG_EVENT_SERVER_INIT_FAIL	596
MBG_GW_TASK_CREATION_FAILURE	596
MBG_IF_TASK_CREATION_FAILURE	596
MBG_INIT_FAIL	597
MBG_MM_TASK_CREATE_FAIL	597
MBG_PKG_NOT_FOUND	597
MBG_PLATFORM_NOT_SUPPORTED	598
MBG_ROUTING_SOCKET_INIT_FAIL	598
MBG_TIMER_CREATE_FAIL	598
MBG_UI_SERVER_INIT_FAIL	599

Chapter 79	MCSN System Log Messages	601
	MCSN_SYSTEM	601
Chapter 80	MIB2D System Log Messages	603
	MIB2D_ATM_ERROR	603
	MIB2D_CONFIG_CHECK_FAILED	603
	MIB2D_COUNTER_DECREASING	604
	MIB2D_FILE_OPEN_FAILURE	604
	MIB2D_IFD_IFDINDEX_FAILURE	604
	MIB2D_IFD_IFINDEX_FAILURE	604
	MIB2D_IFL_IFINDEX_FAILURE	605
	MIB2D_IF_FLAPPING_MISSING	605
	MIB2D_KVM_FAILURE	605
	MIB2D_MASTERSHIP_UPDATE	606
	MIB2D_PMON_OVERLOAD_CLEARED_TRAP	606
	MIB2D_PMON_OVERLOAD_SET_TRAP	606
	MIB2D_RTSLIB_READ_FAILURE	606
	MIB2D_RTSLIB_SEQ_MISMATCH	607
	MIB2D_SNMP_INDEX_ASSIGN	607
	MIB2D_SNMP_INDEX_DUPLICATE	607
	MIB2D_SNMP_INDEX_UPDATE_STAT	607
	MIB2D_SNMP_INDEX_WRITE	608
	MIB2D_SYSCTL_FAILURE	608
	MIB2D_TRAP_HEADER_FAILURE	608
	MIB2D_TRAP_SEND_FAILURE	609
Chapter 81	MPLS System Log Messages	611
	MPLS_OAM_FANOUT_LIMIT_REACHED	611
	MPLS_OAM_INVALID_SOURCE_ADDRESS	611
	MPLS_OAM_PATH_LIMIT_REACHED	611
	MPLS_OAM_SEND_FAILED	612
	MPLS_OAM_SOCKET_OPEN_FAILED	612
	MPLS_OAM_SOCKET_SELECT_FAILED	612
	MPLS_OAM_TRACEROUTE_INTERRUPTED	612
	MPLS_OAM_TTL_EXPIRED	613
	MPLS_OAM_UNREACHABLE	613
Chapter 82	NEXTHOP System Log Messages	615
	NEXTHOP_COMPONENTS_LIMIT_REACHED	615
Chapter 83	NSD System Log Messages	617
	NSD_MEMORY_ALLOC_FAILED	617
	NSD_RESTART_COMP_CFG_READ_FAILED	617
	NSD_SEC_NODE_COMP_SYNC_FAILED	617
Chapter 84	NSTRACED System Log Messages	619
	NSTRACED_MEMORY_ALLOC_FAILED	619
	NSTRACED_RESTART_CFG_READ_FAILED	619
Chapter 85	NTPDATE System Log Messages	621
	NTPDATE_TIME_CHANGED	621

Chapter 86	NTPD System Log Messages	623
	NTPD_CHANGED_TIME	623
Chapter 87	PARSE System Log Messages	625
	PARSE_WARN_DUPLICATE_ROUTER_AD	625
	PARSE_WARN_NO_LS_ROUTER_AD_CFG	625
	PARSE_WARN_NO_ROUTER_AD_CFG	625
	PARSE_WARN_PROXY_ARP_CFG_ERR	626
Chapter 88	PFE System Log Messages	627
	PFE_ANALYZER_CFG_FAILED	627
	PFE_ANALYZER_SHIM_CFG_FAILED	627
	PFE_ANALYZER_TABLE_WRITE_FAILED	627
	PFE_ANALYZER_TASK_FAILED	627
	PFE_CBF_UNSUPPORTED	628
	PFE_COS_B2_ONE_CLASS	628
	PFE_COS_B2_UNSUPPORTED	628
	PFE_FW_DELETE_MISMATCH_ERR	628
	PFE_FW_IF_DIALER_ERR	629
	PFE_FW_IF_INPUT_ERR	629
	PFE_FW_IF_OUTPUT_ERR	629
	PFE_FW_PSF_DELETE_MISMATCH_ERR	629
	PFE_FW_SYSLOG_ETH	630
	PFE_FW_SYSLOG_IP	630
	PFE_FW_SYSLOG_IP6_GEN	630
	PFE_FW_SYSLOG_IP6_ICMP	630
	PFE_FW_SYSLOG_IP6_TCP_UDP	631
	PFE_MGCP_MEM_INIT_FAILED	631
	PFE_MGCP_REG_HDL_FAIL	631
	PFE_NH_RESOLVE_THROTTLED	631
	PFE_SCCP_ADD_PORT_FAIL	632
	PFE_SCCP_DEL_PORT_FAIL	632
	PFE_SCCP_REG_NAT_VEC_FAIL	632
	PFE_SCCP_REG_RM_FAIL	632
	PFE_SCCP_REG_VSIP_FAIL	632
	PFE_SCCP_RM_CLIENTID_FAIL	633
	PFE_SCREEN_MT_CFG_ERROR	633
	PFE_SCREEN_MT_CFG_EVENT	633
	PFE_SCREEN_MT_ZONE_BINDING_ERROR	633
	PFE_SIP_MEM_INIT_FAILED	633
	PFE_SIP_REG_HDL_FAIL	634
Chapter 89	PFED System Log Messages	635
	PFED_NOTIFICATION_STATS_FAILED	635
Chapter 90	PGCPD System Log Messages	637
	PGCPD_SHUTDOWN	637
	PGCPD_STARTUP	637
	PGCPD_SWITCH_OVER	637

Chapter 91	PING System Log Messages	639
	PING_EGRESS_JITTER_THRESH_EXCEED	639
	PING_EGRESS_STDDEV_THRESH_EXCEED	639
	PING_EGRESS_THRESHOLD_EXCEEDED	639
	PING_INGRESS_JTR_THRESH_EXCEED	640
	PING_INGRESS_STDDV_THRESH_EXCEED	640
	PING_INGRESS_THRESHOLD_EXCEEDED	640
	PING_PROBE_FAILED	640
	PING_RTT_JTR_THRESH_EXCEED	640
	PING_RTT_STDDV_THRESH_EXCEED	641
	PING_RTT_THRESHOLD_EXCEEDED	641
	PING_TEST_COMPLETED	641
	PING_TEST_FAILED	641
	PING_UNKNOWN_THRESH_TYPE_EXCEED	642
Chapter 92	PKID System Log Messages	643
	PKID_AFTER_KEY_GEN_SELF_TEST	643
	PKID_CERT_BASIC_CNSTRS_INV_CA	643
	PKID_CERT_BASIC_CNSTRS_MISSING	643
	PKID_CERT_ID_LOOKUP_FAIL	643
	PKID_CERT_NOT_AFTER_FAIL	644
	PKID_CERT_NOT_BEFORE_FAIL	644
	PKID_CERT_SIGN_VERIFY_FAIL	644
	PKID_CORRUPT_CERT	644
	PKID_CRL_CERTIFICATE_REVOKED	645
	PKID_CRL_CHECK_SKIPPED	645
	PKID_CRL_DOWNLOAD_FAIL_LF	645
	PKID_CRL_DOWNLOAD_SUCCESS	645
	PKID_CRL_LOCAL_CERT_REVOKED	645
	PKID_CRL_SIGNATURE_FAIL	646
	PKID_FIPS_DSA_NOT_ALLOWED	646
	PKID_FIPS_KAT_SUCCESS	646
	PKID_FIPS_RSA_TOO_WEAK	646
	PKID_NO_CA_CERT	646
	PKID_NO_KEYPAIR	647
	PKID_NO_LOCAL_CERT	647
	PKID_OCSP_CA_CERT_MISSING	647
	PKID_OCSP_CONNECTION_FAILOVER	647
	PKID_OCSP_FALLBACK_TO_CRL	648
	PKID_OCSP_NONCE_CHECK_FAIL	648
	PKID_OCSP_RESPONSE_INT_ERROR	648
	PKID_OCSP_RESPONSE_MALFORMED	648
	PKID_OCSP_RESPONSE_SIGN_REQUIRED	648
	PKID_OCSP_RESPONSE_TRY_LATER	649
	PKID_OCSP_RESPONSE_UNAUTHORIZED	649
	PKID_OCSP_RESP_CA_CERT_MISSING	649
	PKID_OCSP_RESP_CERT_REVOKED	649
	PKID_OCSP_RESP_CERT_VERIFY_FAIL	649
	PKID_OCSP_SIGN_VERIFY_FAIL	650

	PKID_OCSP_SKIP_REVOCATION_CHECK	650
	PKID_PV_ASYM_KEYGEN	650
	PKID_PV_CERT_DEL	650
	PKID_PV_CERT_LOAD	650
	PKID_PV_KEYPAIR_DEL	651
	PKID_PV_KEYPAIR_GEN	651
	PKID_PV_OBJECT_READ	651
	PKID_SCEP_INV_DIGEST_ALG	651
	PKID_SCEP_INV_ENCRYPT_ALG	651
	PKID_UNABLE_TO_GET_CRL	652
Chapter 93	PPMD System Log Messages	653
	PPMD_ASSERT_SOFT	653
	PPMD_MIRROR_ERROR	653
	PPMD_OPEN_ERROR	654
	PPMD_READ_ERROR	654
	PPMD_WRITE_ERROR	654
Chapter 94	PPPD System Log Messages	655
	PPPD_AUTH_CREATE_FAILED	655
	PPPD_CHAP_AUTH_IN_PROGRESS	655
	PPPD_CHAP_GETHOSTNAME_FAILED	655
	PPPD_CHAP_INVALID_IDENTIFIER	656
	PPPD_CHAP_INVALID_OPCODE	656
	PPPD_CHAP_LOCAL_NAME_UNAVAILABLE	656
	PPPD_CHAP_OPERATION_UNEXPECTED	656
	PPPD_CHAP_REPLAY_ATTACK_DETECTED	657
	PPPD_EVLIB_CREATE_FAILURE	657
	PPPD_LOCAL_CREATE_FAILED	657
	PPPD_MEMORY_ALLOCATION_FAILURE	657
	PPPD_PAP_GETHOSTNAME_FAILED	658
	PPPD_PAP_INVALID_IDENTIFIER	658
	PPPD_PAP_INVALID_OPCODE	658
	PPPD_PAP_LOCAL_PASSWORD_UNAVAIL	658
	PPPD_PAP_OPERATION_UNEXPECTED	659
	PPPD_POOL_ADDRESSES_EXHAUSTED	659
	PPPD_RADIUS_ADD_SERVER_FAILED	659
	PPPD_RADIUS_ALLOC_PASSWD_FAILED	659
	PPPD_RADIUS_CREATE_FAILED	660
	PPPD_RADIUS_CREATE_REQ_FAILED	660
	PPPD_RADIUS_GETADDRINFO_FAILED	660
	PPPD_RADIUS_GETHOSTNAME_FAILED	660
	PPPD_RADIUS_MESSAGE_UNEXPECTED	661
	PPPD_RADIUS_NO_VALID_SERVERS	661
	PPPD_RADIUS_OPEN_FAILED	661
	PPPD_RADIUS_ROUTE_INST_ENOENT	661
Chapter 95	PROFILER System Log Messages	663
	PROFILER_RECONFIGURE_SIGHUP	663

Chapter 96	RDD System Log Messages	665
	RDD_EVLIB_CREATE_FAILURE	665
	RDD_IFDEV_ADD_FAILURE	665
	RDD_IFDEV_DELETE_FAILURE	665
	RDD_IFDEV_GET_FAILURE	666
	RDD_IFDEV_INCOMPATIBLE_REVERT	666
	RDD_IFDEV_INCOMPATIBLE_SWITCH	666
	RDD_IFDEV_RETRY_NOTICE	667
	RDD_NEW_INTERFACE_STATE	667
Chapter 97	RMOPD System Log Messages	669
	RMOPD_ADDRESS_MULTICAST_INVALID	669
	RMOPD_ADDRESS_SOURCE_INVALID	669
	RMOPD_ADDRESS_STRING_FAILURE	669
	RMOPD_ADDRESS_TARGET_INVALID	670
	RMOPD_ICMP_ADDR_TYPE_UNSUPPORTED	670
	RMOPD_IFINDEX_NOT_ACTIVE	670
	RMOPD_IFINDEX_NO_INFO	670
	RMOPD_IFNAME_NOT_ACTIVE	671
	RMOPD_IFNAME_NO_INFO	671
	RMOPD_ROUTING_INSTANCE_NO_INFO	671
	RMOPD_TRACEROUTE_ERROR	671
Chapter 98	RPD System Log Messages	673
	RPD_AMT_CFG_ADDR_FMLY_INVALID	673
	RPD_AMT_CFG_ANYCAST_INVALID	673
	RPD_AMT_CFG_ANYCAST_MCAST	674
	RPD_AMT_CFG_LOC_ADDR_INVALID	674
	RPD_AMT_CFG_LOC_ADDR_MCAST	674
	RPD_AMT_CFG_PREFIX_LEN_SHORT	674
	RPD_AMT_CFG_RELAY_INVALID	675
	RPD_AMT_RELAY_DISCOVERY	675
	RPD_AMT_TUNNEL_CREATE	675
	RPD_AMT_TUNNEL_DELETE	675
	RPD_AMT_UCAST_STRM_LMT_EXCEEDED	676
	RPD_BGP_CFG_ADDR_INVALID	676
	RPD_BGP_CFG_LOCAL_ASNUM_WARN	676
	RPD_BGP_NEIGHBOR_LLST_EXPIRED	676
	RPD_BGP_NEIGHBOR_STATE_CHANGED	677
	RPD_DYN_CFG_BUSY_SIGNAL_FAILED	677
	RPD_DYN_CFG_GET_PROFILE_FAILED	677
	RPD_DYN_CFG_GET_PROF_NAME_FAILED	677
	RPD_DYN_CFG_GET_SES_STATE_FAILED	678
	RPD_DYN_CFG_GET_SES_TYPE_FAILED	678
	RPD_DYN_CFG_GET_SNAPSHOT_FAILED	678
	RPD_DYN_CFG_PDB_CLOSE_FAILED	678
	RPD_DYN_CFG_PDB_OPEN_FAILED	679
	RPD_DYN_CFG_REGISTER_FAILED	679
	RPD_DYN_CFG_REQUEST_ACK_FAILED	679

RPD_DYN_CFG_RESPONSE_SLOW	680
RPD_DYN_CFG_SCHEMA_OPEN_FAILED	680
RPD_DYN_CFG_SES_RECOVERY_FAILED	680
RPD_DYN_CFG_SET_CONTEXT_FAILED	680
RPD_DYN_CFG_SMID_RECOVERY_FAILED	681
RPD_DYN_CFG_SMID_REG_FAILED	681
RPD_DYN_CFG_SMID_UNREG_FAILED	681
RPD_ESIS_ADJDOWN	681
RPD_ESIS_ADJUP	682
RPD_FEC129_AII_COLLISION	682
RPD_FEC129_AII_COLLISION_CLEARED	682
RPD_FEC129_REMOTE_AII_COLLISION	682
RPD_IFD_INDEXCOLLISION	683
RPD_IFD_NAMECOLLISION	683
RPD_IFL_INDEXCOLLISION	683
RPD_IFL_NAMECOLLISION	684
RPD_IGMP_ACCOUNTING_OFF	684
RPD_IGMP_ACCOUNTING_ON	684
RPD_IGMP_ALL_SUBSCRIBERS_DELETED	684
RPD_IGMP_CFG_CREATE_ENTRY_FAILED	685
RPD_IGMP_CFG_GROUP_OUT_OF_RANGE	685
RPD_IGMP_CFG_INVALID_VALUE	685
RPD_IGMP_CFG_SOURCE_OUT_OF_RANGE	685
RPD_IGMP_DYN_CFG_ALREADY_BOUND	686
RPD_IGMP_DYN_CFG_INVALID_STMT	686
RPD_IGMP_DYN_CFG_SES_ID_ADD_FAIL	686
RPD_IGMP_DYN_CFG_SES_ID_MISMATCH	687
RPD_IGMP_GROUP_LIMIT_EXCEED	687
RPD_IGMP_GROUP_THRESHOLD_EXCEED	687
RPD_IGMP_GRP_THRESH_LIMIT_BELOW	687
RPD_IGMP_JOIN	688
RPD_IGMP_LEAVE	688
RPD_IGMP_MEMBERSHIP_TIMEOUT	688
RPD_IGMP_ROUTER_VERSION_MISMATCH	688
RPD_ISIS_ADJDOWN	689
RPD_ISIS_ADJUP	689
RPD_ISIS_ADJUPNOIP	689
RPD_ISIS_LDP_SYNC	689
RPD_ISIS_LSPCKSUM	690
RPD_ISIS_NO_ROUTERID	690
RPD_ISIS_OVERLOAD	691
RPD_KRT_CCC_IFL_MODIFY	691
RPD_KRT_DELETED_RTT	691
RPD_KRT_IFA_GENERATION	692
RPD_KRT_IFDCHANGE	692
RPD_KRT_IFDEST_GET	692
RPD_KRT_IFDGET	692
RPD_KRT_IFD_CELL_RELAY_INV_MODE	693
RPD_KRT_IFD_CELL_RELAY_NO_MODE	693

RPD_KRT_IFD_GENERATION	693
RPD_KRT_IFL_CELL_RELAY_INV_MODE	694
RPD_KRT_IFL_CELL_RELAY_NO_MODE	694
RPD_KRT_IFL_GENERATION	694
RPD_KRT_KERNEL_BAD_ROUTE	694
RPD_KRT_NEXTHOP_OVERFLOW	695
RPD_KRT_NOIFD	695
RPD_KRT_VERSION	696
RPD_KRT_VERSIONNONE	696
RPD_KRT_VERSIONOLD	696
RPD_KRT_VPLS_IFL_MODIFY	697
RPD_L2VPN_INSTANCE_NOT_FOUND	697
RPD_L2VPN_LABEL_ALLOC_FAILED	697
RPD_L2VPN_REMOTE_SITE_COLLISION	697
RPD_L2VPN_SITE_COLLISION	698
RPD_LAYER2_VC_BFD_DOWN	698
RPD_LAYER2_VC_BFD_UP	698
RPD_LAYER2_VC_DOWN	698
RPD_LAYER2_VC_PING_DOWN	699
RPD_LAYER2_VC_UP	699
RPD_LDP_BFD_DOWN	699
RPD_LDP_BFD_DOWN_TRACEROUTE_FAIL	699
RPD_LDP_BFD_UP	700
RPD_LDP_GR_CFG_IGNORED	700
RPD_LDP_INTF_BLOCKED	700
RPD_LDP_INTF_UNBLOCKED	700
RPD_LDP_NBRDOWN	701
RPD_LDP_NBRUP	701
RPD_LDP_PING_DOWN	701
RPD_LDP_SESSIONDOWN	701
RPD_LDP_SESSIONUP	702
RPD_LMP_ALLOC_ACK	702
RPD_LMP_ALLOC_REQUEST_TIMEOUT	702
RPD_LMP_CONTROL_CHANNEL	702
RPD_LMP_NO_CALLBACK	702
RPD_LMP_NO_MEMORY	703
RPD_LMP_NO_PEER	703
RPD_LMP_PEER	703
RPD_LMP_PEER_IFL	703
RPD_LMP_PEER_INDEX	704
RPD_LMP_RESOURCE	704
RPD_LMP_RESOURCE_NO_LINK	704
RPD_LMP_SEND	704
RPD_LMP_SEND_ALLOCATION_MESSAGE	704
RPD_LMP_SYSFAIL	705
RPD_LMP_TE_LINK	705
RPD_LMP_TE_LINK_INDEX	705
RPD_LMP_UNEXPECTED_OPCODE	705
RPD_MC_CFG_CREATE_ENTRY_FAILED	706

RPD_MC_CFG_FWD_CACHE_CONFLICT	706
RPD_MC_CFG_PREFIX_LEN_SHORT	706
RPD_MC_COSD_WRITE_ERROR	706
RPD_MC_DESIGNATED_PE_CHANGE	707
RPD_MC_DYN_CFG_ALREADY_BOUND	707
RPD_MC_DYN_CFG_SES_ID_ADD_FAIL	707
RPD_MC_DYN_CFG_SES_ID_MISMATCH	708
RPD_MC_FWD_CACHE_SUPPRESSED	708
RPD_MC_FWD_CACHE_THRESH_BELOW	708
RPD_MC_FWD_CACHE_THRESH_EXCEED	708
RPD_MC_FWD_CACHE_UNSUPPRESSED	709
RPD_MC_LOCAL_DESIGNATED_PE	709
RPD_MC_OIF_REJECT	709
RPD_MC_OIF_RE_ADMIT	709
RPD_MIRROR_ERROR	710
RPD_MIRROR_VERSION_MISMATCH	710
RPD_MLD_ACCOUNTING_OFF	710
RPD_MLD_ACCOUNTING_ON	711
RPD_MLD_ALL_SUBSCRIBERS_DELETED	711
RPD_MLD_CFG_CREATE_ENTRY_FAILED	711
RPD_MLD_CFG_GROUP_OUT_OF_RANGE	711
RPD_MLD_CFG_INVALID_VALUE	712
RPD_MLD_CFG_SOURCE_OUT_OF_RANGE	712
RPD_MLD_DYN_CFG_ALREADY_BOUND	712
RPD_MLD_DYN_CFG_INVALID_STMT	712
RPD_MLD_DYN_CFG_SES_ID_ADD_FAIL	713
RPD_MLD_DYN_CFG_SES_ID_MISMATCH	713
RPD_MLD_GROUP_LIMIT_EXCEED	713
RPD_MLD_GROUP_THRESHOLD_EXCEED	713
RPD_MLD_GRP_THRESH_LIMIT_BELOW	714
RPD_MLD_JOIN	714
RPD_MLD_LEAVE	714
RPD_MLD_MEMBERSHIP_TIMEOUT	714
RPD_MLD_ROUTER_VERSION_MISMATCH	715
RPD_MPLS_DYNAMIC_POOL_EXHAUSTED	715
RPD_MPLS_INTERFACE_ROUTE_ERROR	715
RPD_MPLS_INTF_MAX_LABELS_ERROR	715
RPD_MPLS_LABEL_LIMIT_EXCEEDED	716
RPD_MPLS_LABEL_THRESHOLD_LIMIT_EXCEEDED	716
RPD_MPLS_LOSS_DELAY_NOTICE	716
RPD_MPLS_LSP_AUTOBW_NOTICE	716
RPD_MPLS_LSP_BANDWIDTH_CHANGE	716
RPD_MPLS_LSP_CHANGE	717
RPD_MPLS_LSP_DOWN	717
RPD_MPLS_LSP_SWITCH	717
RPD_MPLS_LSP_UP	717
RPD_MPLS_OAM_LSP_PING_REPLY_ERR	718
RPD_MPLS_OAM_PING_REPLY_TIMEOUT	718
RPD_MPLS_OAM_READ_ERROR	718

RPD_MPLS_OAM_WRITE_ERROR	718
RPD_MPLS_PATH_BANDWIDTH_CHANGE	719
RPD_MPLS_PATH_BFD_DOWN	719
RPD_MPLS_PATH_BFD_UP	719
RPD_MPLS_PATH_BW_NOT_AVAILABLE	719
RPD_MPLS_PATH_DOWN	720
RPD_MPLS_PATH_PING_DOWN	720
RPD_MPLS_PATH_UP	720
RPD_MPLS_REQ_BW_NOT_AVAILABLE	720
RPD_MPLS_TABLE_ROUTE_ERROR	721
RPD_MSDP_CFG_SA_LIMITS_CONFLICT	721
RPD_MSDP_CFG_SRC_INVALID	721
RPD_MSDP_PEER_DOWN	721
RPD_MSDP_PEER_UP	722
RPD_MSDP_SRC_ACTIVE_OVER_LIMIT	722
RPD_MSDP_SRC_ACTIVE_OVER_LOGWARN	722
RPD_MSDP_SRC_ACTIVE_OVER_THRESH	722
RPD_MSDP_SRC_ACTIVE_UNDER_LIMIT	723
RPD_MSDP_SRC_ACTIVE_UNDER_LOGWAR	723
RPD_MSDP_SRC_ACTIVE_UNDER_THRESH	723
RPD_MVPN_CFG_PREFIX_LEN_SHORT	724
RPD_MVPN_HOT_ROOT_STANDBY_STATUS	724
RPD_MVPN_SENDER_BASED_RPF_STATUS	724
RPD_OSPF_CFGNBR_P2P	724
RPD_OSPF_IF_COST_CHANGE	725
RPD_OSPF_LDP_SYNC	725
RPD_OSPF_LSA_MAXIMUM_EXCEEDED	725
RPD_OSPF_LSA_WARNING_EXCEEDED	725
RPD_OSPF_NBRDOWN	726
RPD_OSPF_NBRUP	726
RPD_OSPF_OVERLOAD	726
RPD_OSPF_TOPO_IF_COST_CHANGE	726
RPD_PIM_BSR_DROP_PKT	727
RPD_PIM_BSR_SEND_Q_THRESHOLD	727
RPD_PIM_FOUND_NON_BIDIR_NBR	727
RPD_PIM_GRP_RP_MAP_LIMIT_BELOW	727
RPD_PIM_GRP_RP_MAP_LIMIT_EXCEED	728
RPD_PIM_GRP_RP_MAP_THRES_EXCEED	728
RPD_PIM_JP_INFINITE_HOLDTIME	728
RPD_PIM_NBRDOWN	728
RPD_PIM_NBRUP	729
RPD_PIM_NON_BIDIR_RPF	729
RPD_PIM_REGISTER_LIMIT_BELOW	729
RPD_PIM_REGISTER_LIMIT_EXCEED	729
RPD_PIM_REG_THRESH_EXCEED	730
RPD_PIM_SG_LIMIT_BELOW	730
RPD_PIM_SG_LIMIT_EXCEED	730
RPD_PIM_SG_THRESHOLD_EXCEED	730
RPD_PLCY_CFG_COMMUNITY_FAIL	731

RPD_PLCY_CFG_FWDCLASS_OVERRIDDEN	731
RPD_PLCY_CFG_IFALL_NOMATCH	731
RPD_PLCY_CFG_PARSE_GEN_FAIL	731
RPD_PLCY_CFG_PREFIX_LEN_SHORT	731
RPD_PPM_READ_ERROR	732
RPD_PPM_WRITE_ERROR	732
RPD_RA_CFG_CREATE_ENTRY_FAILED	732
RPD_RA_CFG_INVALID_VALUE	732
RPD_RA_DYN_CFG_ALREADY_BOUND	733
RPD_RA_DYN_CFG_INVALID_STMT	733
RPD_RA_DYN_CFG_SES_ID_ADD_FAIL	733
RPD_RA_DYN_CFG_SES_ID_MISMATCH	734
RPD_RDISC_CKSUM	734
RPD_RDISC_NOMULTI	734
RPD_RDISC_NORECVIF	734
RPD_RDISC_SOLICITADDR	735
RPD_RDISC_SOLICITCMP	735
RPD_RDISC_SOLICITLEN	736
RPD_RIP_AUTH_ACK	736
RPD_RIP_AUTH_REQUEST	736
RPD_RIP_AUTH_UPDATE	736
RPD_RIP_JOIN_BROADCAST	737
RPD_RIP_JOIN_MULTICAST	737
RPD_RSVP_BACKUP_DOWN	737
RPD_RSVP_BYPASS_DOWN	737
RPD_RSVP_BYPASS_UP	738
RPD_RSVP_COS_CFG_WARN	738
RPD_RSVP_INCORRECT_FLOWSPEC	738
RPD_RSVP_LSP_SWITCH	738
RPD_RSVP_MAXIMUM_SESSIONS	739
RPD_RSVP_NBRDOWN	739
RPD_RSVP_NBRUP	739
RPD_RT_CFG_BR_CONFLICT	739
RPD_RT_CFG_CREATE_ENTRY_FAILED	740
RPD_RT_CFG_INVALID_VALUE	740
RPD_RT_CFG_TABLE_NON_MATCHING	740
RPD_RT_DUPLICATE_RD	740
RPD_RT_DYN_CFG_INST_NOT_FOUND	741
RPD_RT_DYN_CFG_TABLE_NOT_FOUND	741
RPD_RT_ERROR	741
RPD_RT_IFUP	741
RPD_RT_INST_CFG_RESERVED_NAME	742
RPD_RT_INST_IMPORT_PLCY_WARNING	742
RPD_RT_PATH_LIMIT_BELOW	742
RPD_RT_PATH_LIMIT_REACHED	742
RPD_RT_PATH_LIMIT_WARNING	743
RPD_RT_PREFIX_LIMIT_BELOW	743
RPD_RT_PREFIX_LIMIT_REACHED	743
RPD_RT_PREFIX_LIMIT_WARNING	743

	RPD_RT_SHOWMODE	744
	RPD_RT_TAG_ID_ALLOC_FAILED	744
	RPD_RV_SESSIONDOWN	744
	RPD_START	744
	RPD_SYSTEM	745
	RPD_VPLS_CW_NOT_SUPPORTED	745
	RPD_VPLS_INTF_NOT_IN_SITE	745
Chapter 99	RT System Log Messages	747
	RT_ALG_ERR_GATE	747
	RT_ALG_ERR_INIT	747
	RT_ALG_ERR_MEM_ALLOC	747
	RT_ALG_ERR_NAT	747
	RT_ALG_ERR_RES_ALLOC	748
	RT_ALG_NTC_FSM_DROP	748
	RT_ALG_NTC_PARSE_ERR	748
	RT_ALG_NTC_PKT_MALFORMED	748
	RT_ALG_WRN_CAPACITY_LMT	748
	RT_ALG_WRN_CFG_NEED	749
	RT_FLOW_SESSION_CLOSE	749
	RT_FLOW_SESSION_CLOSE_LS	749
	RT_FLOW_SESSION_CREATE	750
	RT_FLOW_SESSION_CREATE_LS	750
	RT_FLOW_SESSION_DENY	750
	RT_FLOW_SESSION_DENY_LS	750
	RT_H323_NAT_COOKIE_NOT_FOUND	751
	RT_IPSEC_AUTH_FAIL	751
	RT_IPSEC_BAD_SPI	751
	RT_IPSEC_DECRYPT_BAD_PAD	751
	RT_IPSEC_PV_DECRYPTION	752
	RT_IPSEC_PV_ENCRYPTION	752
	RT_IPSEC_PV_REPLAY	752
	RT_IPSEC_PV_SYM_KEYGEN	752
	RT_IPSEC_REPLAY	752
	RT_MGCP_CALL_LIMIT_EXCEED	753
	RT_MGCP_DECODE_FAIL	753
	RT_MGCP_MEM_ALLOC_FAILED	753
	RT_MGCP_REM_NAT_VEC_FAIL	753
	RT_MGCP_RM_CLIENTID_FAIL	753
	RT_MGCP_UNREG_BY_RM	754
	RT_SCCP_CALL_LIMIT_EXCEED	754
	RT_SCCP_CALL_RATE_EXCEED	754
	RT_SCCP_DECODE_FAIL	754
	RT_SCCP_NAT_COOKIE_NOT_FOUND	754
	RT_SCCP_REM_NAT_VEC_FAIL	755
	RT_SCCP_UNREG_RM_FAIL	755
	RT_SCREEN_ICMP	755
	RT_SCREEN_ICMP_LS	755
	RT_SCREEN_IP	756

	RT_SCREEN_IP_LS	756
	RT_SCREEN_SESSION_LIMIT	756
	RT_SCREEN_SESSION_LIMIT_LS	756
	RT_SCREEN_TCP	757
	RT_SCREEN_TCP_DST_IP	757
	RT_SCREEN_TCP_DST_IP_LS	757
	RT_SCREEN_TCP_LS	757
	RT_SCREEN_TCP_SRC_IP	758
	RT_SCREEN_TCP_SRC_IP_LS	758
	RT_SCREEN_UDP	758
	RT_SCREEN_UDP_LS	758
	RT_SCREEN_WHITE_LIST	759
	RT_SCREEN_WHITE_LIST_LS	759
	RT_SCTP_LOG_INFO	759
	RT_SCTP_PKT_INFO	759
Chapter 100	RTLOG System Log Messages	761
	RTLOG_JLOG_TEST	761
	RTLOG_UTP_TCP_SYN_FLOOD	761
	RTLOG_UTP_TCP_SYN_FLOOD_LS	761
Chapter 101	RTLOGD System Log Messages	763
	RTLOGD_LOG_BIND_ERROR	763
	RTLOGD_LOG_READ_ERROR	763
Chapter 102	RTPERF System Log Messages	765
	RTPERF_CPU_THRESHOLD_EXCEEDED	765
	RTPERF_CPU_USAGE_OK	765
Chapter 103	SAVAL System Log Messages	767
	SAVAL_RTsock_FAILURE	767
Chapter 104	SDK System Log Messages	769
	SDK_VMMD_COMMAND_OPTIONS	769
	SDK_VMMD_MOD_LAG	769
Chapter 105	SDXD System Log Messages	771
	SDXD_BEEP_FIN_FAIL	771
	SDXD_BEEP_INIT_FAIL	771
	SDXD_CHANNEL_START_FAIL	771
	SDXD_CONNECT_FAIL	772
	SDXD_DAEMONIZE_FAIL	772
	SDXD_EVLIB_FAILURE	772
	SDXD_KEEPAIVES_MISSED	773
	SDXD_KEEPAIVE_SEND_FAIL	773
	SDXD_MGMT_SOCKET_IO	773
	SDXD_OUT_OF_MEMORY	773
	SDXD_PID_FILE_UPDATE	774
	SDXD_SOCKET_FAILURE	774

Chapter 106	SM System Log Messages	775
	SM_IPPOOL_MM_STATE_CHANGE	775
	SM_IPPOOL_POOL_THRESH_EXCEEDED	775
Chapter 107	SMTPD System Log Messages	777
	SMTPD_DROP_MAIL_PAYLOAD	777
	SMTPD_NO_CONFIGURED_SERVER	777
Chapter 108	SNMP System Log Messages	779
	SNMP_GET_ERROR1	779
	SNMP_GET_ERROR2	779
	SNMP_GET_ERROR3	780
	SNMP_GET_ERROR4	780
	SNMP_RTSLIB_FAILURE	780
	SNMP_TRAP_LINK_DOWN	781
	SNMP_TRAP_LINK_UP	781
	SNMP_TRAP_TRACERT_PATH_CHANGE	781
	SNMP_TRAP_TRACERT_TEST_COMPLETED	781
	SNMP_TRAP_TRACERT_TEST_FAILED	782
Chapter 109	SNMPD System Log Messages	783
	SNMPD_AUTH_FAILURE	783
	SNMPD_AUTH_PRIVILEGES_EXCEEDED	783
	SNMPD_AUTH_RESTRICTED_ADDRESS	784
	SNMPD_AUTH_WRONG_PDU_TYPE	784
	SNMPD_BIND_INFO	784
	SNMPD_CONFIG_ERROR	785
	SNMPD_CONTEXT_ERROR	785
	SNMPD_ENGINE_ID_CHANGED	785
	SNMPD_FILE_FAILURE	785
	SNMPD_GROUP_ERROR	786
	SNMPD_HEALTH_MON_THRESH_CROSS	786
	SNMPD_INIT_FAILED	786
	SNMPD_LIBJUNIPER_FAILURE	787
	SNMPD_MISSING_REGISTRATION	787
	SNMPD_RADIX_FAILURE	787
	SNMPD_RECEIVE_FAILURE	787
	SNMPD_RMONFILE_FAILURE	788
	SNMPD_RMON_COOKIE	788
	SNMPD_RMON_EVENTLOG	788
	SNMPD_RMON_MIBERROR	789
	SNMPD_RTSLIB_ASYNC_EVENT	789
	SNMPD_SCRIPT_OID_ERROR	789
	SNMPD_SCRIPT_REGISTERED	789
	SNMPD_SEND_FAILURE	790
	SNMPD_SET_FAILED	790
	SNMPD_SMOID_GEN_FAILURE	790
	SNMPD_SOCKET_FAILURE	791
	SNMPD_SOCKET_FATAL_FAILURE	791
	SNMPD_SYSLIB_FAILURE	791

	SNMPD_SYSOID_FAILURE	792
	SNMPD_SYSOID_GEN_FAILURE	792
	SNMPD_THROTTLE_QUEUE_DRAINED	792
	SNMPD_TRAP_COLD_START	792
	SNMPD_TRAP_GEN_FAILURE	793
	SNMPD_TRAP_INVALID_DATA	793
	SNMPD_TRAP_QUEUED	793
	SNMPD_TRAP_QUEUE_DRAINED	794
	SNMPD_TRAP_QUEUE_MAX_ATTEMPTS	794
	SNMPD_TRAP_QUEUE_MAX_SIZE	794
	SNMPD_TRAP_TARGET_ADD_NOTICE	794
	SNMPD_TRAP_TARGET_DELETE_NOTICE	794
	SNMPD_TRAP_THROTTLED	795
	SNMPD_TRAP_WARM_START	795
	SNMPD_USER_ERROR	795
Chapter 110	SPD System Log Messages	797
	SPD_CONFIGURATION_COMPILE	797
	SPD_CONN_FAILURE	797
	SPD_CONN_NO_REPLY	797
	SPD_CONN_OPEN_FAILURE	798
	SPD_CONN_SEND_FAILURE	798
	SPD_CONN_UNEXPECTED_MSG	798
	SPD_DAEMONIZE_FAILED	798
	SPD_DB_IF_ADD_FAILURE	799
	SPD_DB_IF_ALLOC_FAILURE	799
	SPD_DB_SVC_SET_ADD_FAILURE	799
	SPD_DB_SVC_SET_ALLOC_FAILURE	799
	SPD_DUPLICATE	800
	SPD_EVLIB_CREATE_FAILURE	800
	SPD_EVLIB_EXIT_FAILURE	800
	SPD_GEN_NUM_FAIL	800
	SPD_NOT_ROOT	801
	SPD_OUT_OF_MEMORY	801
	SPD_PID_FILE_LOCK	801
	SPD_PID_FILE_UPDATE	801
	SPD_SERVICE_NEXT_HOP_ADD_FAILED	802
	SPD_SERVICE_NEXT_HOP_DEL_FAILED	802
	SPD_TRAP_OID_GEN_FAILED	802
	SPD_TRAP_REQUEST_FAILURE	802
	SPD_USAGE	803
Chapter 111	SSH System Log Messages	805
	SSH_MSG_REPLAY_DETECT	805
	SSH_MSG_REPLAY_LIMIT	805
	SSH_RELAY_CONNECT_ERROR	805
	SSH_RELAY_SERVER_ERROR	806
	SSH_RELAY_USAGE	806

Chapter 112	SSHD System Log Messages	807
	SSHD_LOGIN_ATTEMPTS_THRESHOLD	807
	SSHD_LOGIN_FAILED	807
	SSHD_LOGIN_FAILED_LIMIT	807
Chapter 113	SSL System Log Messages	809
	SSL_PROXY_ERROR	809
	SSL_PROXY_INFO	809
	SSL_PROXY_SESSION_IGNORE	810
	SSL_PROXY_SESSION_WHITELIST	810
	SSL_PROXY_SSL_SESSION_ALLOW	810
	SSL_PROXY_SSL_SESSION_DROP	811
	SSL_PROXY_WARNING	811
Chapter 114	SYSTEM System Log Messages	813
	SYSTEM_ABNORMAL_SHUTDOWN	813
	SYSTEM_OPERATIONAL	813
	SYSTEM_SHUTDOWN	813
Chapter 115	TFTPD System Log Messages	815
	TFTPD_AF_ERR	815
	TFTPD_BIND_ERR	815
	TFTPD_CONNECT_ERR	815
	TFTPD_CONNECT_INFO	816
	TFTPD_CREATE_ERR	816
	TFTPD_FIO_ERR	816
	TFTPD_FORK_ERR	816
	TFTPD_NAK_ERR	817
	TFTPD_OPEN_ERR	817
	TFTPD_RECVCOMPLETE_INFO	817
	TFTPD_RECVFROM_ERR	817
	TFTPD_RECV_ERR	817
	TFTPD_SENDCOMPLETE_INFO	818
	TFTPD_SEND_ERR	818
	TFTPD_SOCKET_ERR	818
	TFTPD_STATFS_ERR	818
Chapter 116	TRANSPORTD System Log Messages	819
	TRANSPORTD_IPC_MSG_ERROR	819
	TRANSPORTD_IPC_MSG_UNHANDLED	819
	TRANSPORTD_IPC_UNEXPECTED_MSG	819
	TRANSPORTD_IPC_WRITE_ERROR	820
	TRANSPORTD_IPC_WRITE_ERR_NO_PIPE	820
	TRANSPORTD_MGR_CONNECT	820
	TRANSPORTD_PIPE_WRITE_ERROR	820
	TRANSPORTD_SYSCALL_ERROR	820
Chapter 117	UFDD System Log Messages	823
	UFDD_GROUP_ACTION_COMPLETE	823
	UFDD_LINK_CHANGE	823

Chapter 118	UI System Log Messages	825
	UI_AUTH_BAD_LOCATION	825
	UI_AUTH_EVENT	825
	UI_AUTH_INVALID_CHALLENGE	825
	UI_BOOTTIME_FAILED	826
	UI_CFG_AUDIT_NEW	826
	UI_CFG_AUDIT_OTHER	826
	UI_CFG_AUDIT_SET	826
	UI_CFG_AUDIT_SET_SECRET	827
	UI_CHILD_ARGS_EXCEEDED	827
	UI_CHILD_CHANGE_USER	827
	UI_CHILD_EXEC	827
	UI_CHILD_EXITED	828
	UI_CHILD_FOPEN	828
	UI_CHILD_OUTPUT	828
	UI_CHILD_PIPE_FAILED	829
	UI_CHILD_STOPPED	829
	UI_CHILD_WAITPID	829
	UI_CLASS_MODIFIED_USERS	830
	UI_CLI_IDLE_TIMEOUT	830
	UI_CMDLINE_READ_LINE	830
	UI_CMD_AUTH_REGEX_INVALID	830
	UI_COMMIT	831
	UI_COMMIT_AT_ABORT	831
	UI_COMMIT_AT_COMPLETED	831
	UI_COMMIT_AT_FAILED	831
	UI_COMMIT_COMPLETED	831
	UI_COMMIT_COMPRESS_FAILED	832
	UI_COMMIT_CONFIRMED_REMINDER	832
	UI_COMMIT_EMPTY_CONTAINER	832
	UI_COMMIT_NOT_CONFIRMED	833
	UI_COMMIT_PREV_CNF_SAVED	833
	UI_COMMIT_PROGRESS	833
	UI_COMMIT_ROLLBACK_FAILED	834
	UI_COMMIT_SYNC_FORCE	834
	UI_COND_GROUPS	834
	UI_COND_GROUPS_COMMIT	834
	UI_COND_GROUPS_COMMIT_ABORT	835
	UI_CONFIGURATION_ERROR	835
	UI_CONFIGURATION_WARNING	835
	UI_CONNECT_COMMITD_FAILED	835
	UI_DAEMON_ACCEPT_FAILED	835
	UI_DAEMON_FORK_FAILED	836
	UI_DAEMON_SELECT_FAILED	836
	UI_DAEMON_SOCKET_FAILED	836
	UI_DBASE_ACCESS_FAILED	837
	UI_DBASE_CHECKOUT_FAILED	837
	UI_DBASE_EXTEND_FAILED	837
	UI_DBASE_LOGIN_EVENT	838

UI_DBASE_LOGOUT_EVENT	838
UI_DBASE_MISMATCH_EXTENT	838
UI_DBASE_MISMATCH_MAJOR	839
UI_DBASE_MISMATCH_MINOR	839
UI_DBASE_MISMATCH_SEQUENCE	840
UI_DBASE_MISMATCH_SIZE	840
UI_DBASE_OPEN_FAILED	840
UI_DBASE_REBUILD_FAILED	841
UI_DBASE_REBUILD_SCHEMA_FAILED	841
UI_DBASE_REBUILD_STARTED	841
UI_DBASE_RECREATE	842
UI_DBASE_REOPEN_FAILED	842
UI_DELTA_CONSTRAINT_CHECK_FAILED	842
UI_DELTA_CONSTRAINT_CHECK_FORK_FAILED	843
UI_DELTA_CONSTRAINT_CHECK_NOT_RUNNING	843
UI_DELTA_CONSTRAINT_CHECK_VERSION_MISMATCH	843
UI_DELTA_EXPORTER_FAILURE	843
UI_DELTA_EXPORTER_INIT_FAIL	844
UI_DUPLICATE_UID	844
UI_EPHEMERAL_COMMIT	844
UI_EPHEMERAL_COMMIT_COMPLETED	844
UI_EPHEMERAL_DB_EVENT	844
UI_FACTORY_OPERATION	845
UI_INITIALSETUP_OPERATION	845
UI_INVALID_REMOTE_PERMISSION	845
UI_JUNOSCRIP_CMD	845
UI_JUNOSCRIP_ERROR	846
UI_LCC_NO_MASTER	846
UI_LOAD_EVENT	846
UI_LOAD_JUNOS_DEFAULT_FILE_EVENT	846
UI_LOCK_AUTHENTICATION_FAILED	847
UI_LOCK_AUTHENTICATION_SUCCESS	847
UI_LOGIN_EVENT	847
UI_LOGOUT_EVENT	847
UI_LOST_CONN	848
UI_MASTERSHIP_EVENT	848
UI_MOTD_PROPAGATE_ERROR	848
UI_NETCONF_CMD	848
UI_NETCONF_ERROR	849
UI_PARSE_JUNOSCRIP_ATTRIBUTES	849
UI_READ_FAILED	849
UI_READ_TIMEOUT	849
UI_REBOOT_EVENT	850
UI_RESCUE_OPERATION	850
UI_RESTART_EVENT	850
UI_RESTART_FAILED_EVENT	850
UI_SCHEMA_CHECKOUT_FAILED	850
UI_SCHEMA_MISMATCH_MAJOR	851
UI_SCHEMA_MISMATCH_SEQUENCE	851

	UI_SCHEMA_SEQUENCE_ERROR	852
	UI_SCRIPTS_COPY_FAILED	852
	UI SOCK_WARNING	852
	UI_VERSION_FAILED	853
	UI_WRITE_RECONNECT	853
	UI_XPATH_CONSTRAINT_CHECK_FAILED	853
	UI_XPATH_CONSTRAINT_DA_INIT_FAILED	853
	UI_XPATH_CONSTRAINT_DOC_FAILED	853
Chapter 119	UTMD System Log Messages	855
	UTMD_MAILNOTIFIER_FAILURE	855
	UTMD_MALLOC_FAILURE	855
	UTMD_SSAMLIB_FAILURE	855
Chapter 120	VCCPD System Log Messages	857
	VCCPD_FABRIC_LSDB_LOOKUP_FAILED	857
	VCCPD_FABRIC_MALLOC_FAILURE	857
	VCCPD_FABRIC_PROCESS_OIR_MSG	858
	VCCPD_FABRIC_SYSCTL_ERROR	858
	VCCPD_FABRIC_SYSTEM	858
	VCCPD_FABRIC_UNSUPPORTED_RE_TYPE	858
	VCCPD_FABRIC_UNSUPPORTED_SKU_TYPE	859
	VCCPD_KNL_VERSION	859
	VCCPD_KNL_VERSIONNONE	859
	VCCPD_KNL_VERSIONOLD	860
	VCCPD_PROTOCOL_ADJDOWN	860
	VCCPD_PROTOCOL_ADJUP	860
	VCCPD_PROTOCOL_LSPCKSUM	860
	VCCPD_PROTOCOL_OVERLOAD	861
	VCCPD_SYSTEM	861
Chapter 121	VM System Log Messages	863
	VM_DCF_PB_COMMUNICATION_FAILED	863
	VM_DCF_PB_INVALID_IMAGE	863
	VM_DCF_PB_INVALID_UUID	864
	VM_DCF_PB_RESOURCE_FAILURE	864
Chapter 122	VRRPD System Log Messages	865
	VRRPD_ADVERT_TIME_MISMATCH	865
	VRRPD_AUTH_INFO_INVALID	865
	VRRPD_GET_TRAP_HEADER_FAILED	866
	VRRPD_LINK_LOCAL_ADD_MISMATCH	866
	VRRPD_MISSING_VIP	866
	VRRPD_NEW_BACKUP	867
	VRRPD_NEW_MASTER	867
	VRRPD_V3_PROTO_ERROR	867
	VRRPD_VIP_COUNT_MISMATCH	867
Chapter 123	WEB System Log Messages	869
	WEB_AUTH_FAIL	869
	WEB_AUTH_SUCCESS	869

	WEB_AUTH_TIME_EXCEEDED	869
	WEB_CERT_FILE_NOT_FOUND	869
	WEB_CERT_FILE_NOT_FOUND_RETRY	870
	WEB_CHILD_STATE	870
	WEB_CONFIG_OPEN_ERROR	870
	WEB_CONFIG_WRITE_ERROR	870
	WEB_COULDNT_START_HTTPD	871
	WEB_EVENTLIB_INIT	871
	WEB_KEYPAIR_FILE_NOT_FOUND	871
	WEB_MGD_BIND_ERROR	871
	WEB_MGD_CHMOD_ERROR	871
	WEB_MGD_CONNECT_ERROR	872
	WEB_MGD_FCNTL_ERROR	872
	WEB_MGD_LISTEN_ERROR	872
	WEB_MGD_RECVMSG_PEEK_ERROR	872
	WEB_MGD_SOCKET_ERROR	873
	WEB_PIDFILE_LOCK	873
	WEB_PIDFILE_UPDATE	873
	WEB_UNAME_FAILED	873
	WEB_WEBAUTH_AUTH_FAIL	874
	WEB_WEBAUTH_AUTH_OK	874
	WEB_WEBAUTH_CONNECT_FAIL	874
Chapter 124	WEBFILTER System Log Messages	875
	WEBFILTER_CACHE_NOT_ENABLED	875
	WEBFILTER_INTERNAL_ERROR	875
	WEBFILTER_REQUEST_NOT_CHECKED	875
	WEBFILTER_SERVER_CONNECTED	876
	WEBFILTER_SERVER_DISCONNECTED	876
	WEBFILTER_SERVER_ERROR	876
Part 3	Index	
	Index	881

About This Guide

This preface provides the following guidelines for using the *Junos[®] OS System Log Messages Reference*:

- [Junos OS Documentation and Release Notes on page lxv](#)
- [Objectives on page lxvi](#)
- [Audience on page lxvi](#)
- [Supported Platforms on page lxvi](#)
- [Using the Examples in This Manual on page lxvii](#)
- [Documentation Conventions on page lxviii](#)
- [Documentation Feedback on page lxx](#)
- [Requesting Technical Support on page lxxi](#)

Junos OS Documentation and Release Notes

For a list of related Junos OS documentation, see <http://www.juniper.net/techpubs/software/junos/>.

If the information in the latest release notes differs from the information in the documentation, follow the *Junos OS Release Notes*.

To obtain the most current version of all Juniper Networks[®] technical documentation, see the product documentation page on the Juniper Networks website at <http://www.juniper.net/techpubs/>.

Juniper Networks supports a technical book program to publish books by Juniper Networks engineers and subject matter experts with book publishers around the world. These books go beyond the technical documentation to explore the nuances of network architecture, deployment, and administration using the Junos operating system (Junos OS) and Juniper Networks devices. In addition, the Juniper Networks Technical Library, published in conjunction with O'Reilly Media, explores improving network security, reliability, and availability using Junos OS configuration techniques. All the books are for sale at technical bookstores and book outlets around the world. The current list can be viewed at <http://www.juniper.net/books>.

Objectives

This reference describes system log messages generated by the Junos OS. Use the information to interpret system log messages and determine the appropriate corrective action for error conditions



NOTE: For additional information about the Junos OS—either corrections to or information that might have been omitted from this guide—see the software release notes at <http://www.juniper.net/>.

Audience

This guide is designed for network administrators who are configuring and monitoring a Juniper Networks M Series, MX Series, T Series, EX Series, or J Series router or switch.

To use this reference, you need a broad understanding of networks in general, the Internet in particular, networking principles, and network configuration. You must also be familiar with one or more of the following Internet routing protocols:

- Border Gateway Protocol (BGP)
- Distance Vector Multicast Routing Protocol (DVMRP)
- Intermediate System-to-Intermediate System (IS-IS)
- Internet Control Message Protocol (ICMP) router discovery
- Internet Group Management Protocol (IGMP)
- Multiprotocol Label Switching (MPLS)
- Open Shortest Path First (OSPF)
- Protocol-Independent Multicast (PIM)
- Resource Reservation Protocol (RSVP)
- Routing Information Protocol (RIP)
- Simple Network Management Protocol (SNMP)

Personnel operating the equipment must be trained and competent; must not conduct themselves in a careless, willfully negligent, or hostile manner; and must abide by the instructions provided by the documentation.

Supported Platforms

For the features described in this manual, the Junos OS currently supports the following platforms:

- M Series
- MX Series

- QFabric
- QFX Series
- SRX Series
- T Series
- EX Series

Using the Examples in This Manual

If you want to use the examples in this manual, you can use the **load merge** or the **load merge relative** command. These commands cause the software to merge the incoming configuration into the current candidate configuration. If the example configuration contains the top level of the hierarchy (or multiple hierarchies), the example is a *full example*. In this case, use the **load merge** command.

If the example configuration does not start at the top level of the hierarchy, the example is a *snippet*. In this case, use the **load merge relative** command. These procedures are described in the following sections.

Merging a Full Example

To merge a full example, follow these steps:

1. From the HTML or PDF version of the manual, copy a configuration example into a text file, save the file with a name, and copy the file to a directory on your routing platform.

For example, copy the following configuration to a file and name the file **ex-script.conf**. Copy the **ex-script.conf** file to the **/var/tmp** directory on your routing platform.

```
system {
  scripts {
    commit {
      file ex-script.xml;
    }
  }
}
interfaces {
  fxp0 {
    disable;
    unit 0 {
      family inet {
        address 10.0.0.1/24;
      }
    }
  }
}
```

2. Merge the contents of the file into your routing platform configuration by issuing the **load merge** configuration mode command:

```
[edit]
user@host# load merge /var/tmp/ex-script.conf
load complete
```

Merging a Snippet

To merge a snippet, follow these steps:

1. From the HTML or PDF version of the manual, copy a configuration snippet into a text file, save the file with a name, and copy the file to a directory on your routing platform.

For example, copy the following snippet to a file and name the file **ex-script-snippet.conf**. Copy the **ex-script-snippet.conf** file to the **/var/tmp** directory on your routing platform.

```
commit {
file ex-script-snippet.xsl;
}
```

2. Move to the hierarchy level that is relevant for this snippet by issuing the following configuration mode command:

```
[edit]
user@host# edit system scripts[edit system scripts]
```

3. Merge the contents of the file into your routing platform configuration by issuing the load merge relative configuration mode command:

```
[edit system scripts]
user@host# load merge relative /var/tmp/ex-script-snippet.confload complete
```

For more information about the load command, see the *Junos OS CLI User Guide*

Documentation Conventions

Table 1 on page [lxix](#) defines notice icons used in this guide.

Table 1: Notice Icons







Icon	Meaning	Description
	Informational note	Indicates important features or instructions.
	Caution	Indicates a situation that might result in loss of data or hardware damage.
	Warning	Alerts you to the risk of personal injury or death.
	Laser warning	Alerts you to the risk of personal injury from a laser.
	Tip	Indicates helpful information.
	Best practice	Alerts you to a recommended use or implementation.

Table 2 on page [lxix](#) defines the text and syntax conventions used in this guide.

Table 2: Text and Syntax Conventions

Convention	Description	Examples
Bold text like this	Represents text that you type.	To enter configuration mode, type the configure command: user@host> configure
Fixed-width text like this	Represents output that appears on the terminal screen.	user@host> show chassis alarms No alarms currently active
<i>Italic text like this</i>	<ul style="list-style-type: none"> Introduces or emphasizes important new terms. Identifies guide names. Identifies RFC and Internet draft titles. 	<ul style="list-style-type: none"> A policy <i>term</i> is a named structure that defines match conditions and actions. <i>Junos OS CLI User Guide</i> RFC 1997, <i>BGP Communities Attribute</i>
<i>Italic text like this</i>	Represents variables (options for which you substitute a value) in commands or configuration statements.	Configure the machine's domain name: [edit] root@# set system domain-name <i>domain-name</i>

Table 2: Text and Syntax Conventions (*continued*)

Convention	Description	Examples
Text like this	Represents names of configuration statements, commands, files, and directories; configuration hierarchy levels; or labels on routing platform components.	<ul style="list-style-type: none">To configure a stub area, include the stub statement at the [edit protocols ospf area area-id] hierarchy level.The console port is labeled CONSOLE.
< > (angle brackets)	Encloses optional keywords or variables.	stub <default-metric <i>metric</i>>;
(pipe symbol)	Indicates a choice between the mutually exclusive keywords or variables on either side of the symbol. The set of choices is often enclosed in parentheses for clarity.	broadcast multicast (<i>string1</i> <i>string2</i> <i>string3</i>)
# (pound sign)	Indicates a comment specified on the same line as the configuration statement to which it applies.	rsvp { # Required for dynamic MPLS only
[] (square brackets)	Encloses a variable for which you can substitute one or more values.	community name members [<i>community-ids</i>]
Indentation and braces ({ })	Identifies a level in the configuration hierarchy.	<pre>[edit] routing-options { static { route default { nexthop <i>address</i>; retain; } } }</pre>
;(semicolon)	Identifies a leaf statement at a configuration hierarchy level.	
GUI Conventions		
Bold text like this	Represents graphical user interface (GUI) items you click or select.	<ul style="list-style-type: none">In the Logical Interfaces box, select All Interfaces.To cancel the configuration, click Cancel.
> (bold right angle bracket)	Separates levels in a hierarchy of menu selections.	In the configuration editor hierarchy, select Protocols>Ospf .

Documentation Feedback

We encourage you to provide feedback, comments, and suggestions so that we can improve the documentation. You can provide feedback by using either of the following methods:

- Online feedback rating system—On any page at the Juniper Networks Technical Documentation site at <http://www.juniper.net/techpubs/index.html>, simply click the stars to rate the content, and use the pop-up form to provide us with information about your experience. Alternately, you can use the online feedback form at <https://www.juniper.net/cgi-bin/docbugreport/>.

- E-mail—Send your comments to techpubs-comments@juniper.net. Include the document or topic name, URL or page number, and software version (if applicable).

Requesting Technical Support

Technical product support is available through the Juniper Networks Technical Assistance Center (JTAC). If you are a customer with an active J-Care or JNASC support contract, or are covered under warranty, and need postsales technical support, you can access our tools and resources online or open a case with JTAC.

- JTAC policies—For a complete understanding of our JTAC procedures and policies, review the *JTAC User Guide* located at <http://www.juniper.net/us/en/local/pdf/resource-guides/7100059-en.pdf>.
- Product warranties—For product warranty information, visit <http://www.juniper.net/support/warranty/>.
- JTAC Hours of Operation —The JTAC centers have resources available 24 hours a day, 7 days a week, 365 days a year.

Self-Help Online Tools and Resources

For quick and easy problem resolution, Juniper Networks has designed an online self-service portal called the Customer Support Center (CSC) that provides you with the following features:

- Find CSC offerings: <http://www.juniper.net/customers/support/>
- Find product documentation: <http://www.juniper.net/techpubs/>
- Find solutions and answer questions using our Knowledge Base: <http://kb.juniper.net/>
- Download the latest versions of software and review release notes: <http://www.juniper.net/customers/csc/software/>
- Search technical bulletins for relevant hardware and software notifications: <http://kb.juniper.net/InfoCenter/>
- Join and participate in the Juniper Networks Community Forum: <http://www.juniper.net/company/communities/>
- Open a case online in the CSC Case Management tool: <http://www.juniper.net/cm/>

To verify service entitlement by product serial number, use our Serial Number Entitlement (SNE) Tool: <https://tools.juniper.net/SerialNumberEntitlementSearch/>

Opening a Case with JTAC

You can open a case with JTAC on the Web or by telephone.

- Use the Case Management tool in the CSC at <http://www.juniper.net/cm/>.
- Call 1-888-314-JTAC (1-888-314-5822 toll-free in the USA, Canada, and Mexico).

For international or direct-dial options in countries without toll-free numbers, visit us at <http://www.juniper.net/support/requesting-support.html>

PART 1

Overview

- [Configuring System Log Messages on page 3](#)

CHAPTER 1

Configuring System Log Messages

Junos OS generates system log messages (also called *syslog messages*) to record events that occur on the router, including the following:

- Routine operations, such as creation of an OSPF protocol adjacency or a user login into the configuration database
- Failure and error conditions, such as failure to access a configuration file or unexpected closure of a connection to a peer process
- Emergency or critical conditions, such as router power-down due to excessive temperature

Each system log message identifies the Junos OS process that generated the message and briefly describes the operation or error that occurred.



NOTE: This topic describes system log messages for Junos OS processes and libraries and not the system logging services on a PIC such as the Adaptive Services PIC. For information about configuring system logging for PIC services, see *Junos OS Services Interfaces Library for Routing Devices*.

This chapter discusses the following topics:

- [Junos OS System Log Configuration Hierarchy on page 3](#)
- [Minimum and Default System Logging Configuration on page 4](#)
- [Configuring System Logging for a Single-Chassis System on page 7](#)
- [Configuring System Logging for a TX Matrix Router on page 31](#)
- [Displaying and Interpreting System Log Messages on page 49](#)
- [Getting Help About System Log Messages on page 60](#)

Junos OS System Log Configuration Hierarchy

To configure the router to log system messages, include the **syslog** statement at the **[edit system]** hierarchy level:

```
[edit system]
syslog {
```

```

archive <files number> <size size <world-readable | no-world-readable>;
console {
    facility severity;
}
file filename {
    facility severity;
    archive <archive-sites {ftp-url <password password>}> <files number> <size size>
        <start-time "YYYY-MM-DD.hh:mm"> <transfer-interval minutes> <world-readable |
        no-world-readable>;
    explicit-priority;
    match "regular-expression";
    structured-data {
        brief;
    }
}
host (hostname | other-routing-engine | scc-master) {
    facility severity;
    explicit-priority;
    facility-override facility;
    log-prefix string
    match "regular-expression";
    source-address source-address;
    structured-data {
        brief;
    }
}
source-address source-address;
time-format (year | millisecond | year millisecond);
user (username | *) {
    facility severity;
    match "regular-expression";
}
}

```

**Related
Documentation**

- [Junos OS System Log Overview](#)

Minimum and Default System Logging Configuration

For information about the minimum and default system log settings on routing platforms that run Junos OS, see the following sections:

- [Junos OS Minimum System Logging Configuration on page 4](#)
- [Junos OS Default System Log Settings on page 5](#)
- [Junos OS Platform-Specific Default System Log Messages on page 6](#)

Junos OS Minimum System Logging Configuration

To record or view system log messages, you must include the **syslog** statement at the **[edit system]** hierarchy level. Specify at least one destination for the messages, as described in [Table 3 on page 5](#). For more information about the configuration statements, see *Single-Chassis System Logging Configuration Overview*.

Table 3: Minimum Configuration Statements for System Logging

Destination	Minimum Configuration Statements
File	<code>[edit system syslog] file <i>filename</i> { <i>facility severity</i>; }</code>
Terminal session of one, several, or all users	<code>[edit system syslog] user (<i>username</i> *) { <i>facility severity</i>; }</code>
Router or switch console	<code>[edit system syslog] console { <i>facility severity</i>; }</code>
Remote machine or the other Routing Engine on the router or switch	<code>[edit system syslog] host (<i>hostname</i> other-routing-engine) { <i>facility severity</i>; }</code>

Related Documentation • [Junos OS System Log Overview](#)

Junos OS Default System Log Settings

[Table 4 on page 5](#) summarizes the default system log settings that apply to all routers that run Junos OS, and specifies which statement to include in the configuration to override the default value.

Table 4: Default System Logging Settings

Setting	Default	Overriding Statement	Instructions
Alternative facility for message forwarded to a remote machine	For change-log : local6 For conflict-log : local5 For dfc : local1 For firewall : local3 For interactive-commands : local7 For pfe : local4	<code>[edit system syslog] host <i>hostname</i> { facility-override <i>facility</i>; }</code>	“Changing the Alternative Facility Name for System Log Messages Directed to a Remote Destination” on page 15
Format of messages logged to a file	Standard Junos format, based on UNIX format	<code>[edit system syslog] file <i>filename</i> { structured-data; }</code>	“Logging Messages in Structured-Data Format” on page 12

Table 4: Default System Logging Settings (*continued*)

Setting	Default	Overriding Statement	Instructions
Maximum number of files in the archived set	10	<pre>[edit system syslog] archive { files <i>number</i>; } file <i>filename</i> { archive { files <i>number</i>; } }</pre>	“Specifying Log File Size, Number, and Archiving Properties” on page 20
Maximum size of the log file	M Series, MX Series, and T Series: 1 megabyte (MB) TX Matrix: 10 MB	<pre>[edit system syslog] archive { size <i>size</i>; } file <i>filename</i> { archive { size <i>size</i>; } }</pre>	“Specifying Log File Size, Number, and Archiving Properties” on page 20
Timestamp format	Month, date, hour, minute, second For example: Aug 21 12:36:30	<pre>[edit system syslog] time-format <i>format</i>;</pre>	“Including the Year or Millisecond in Timestamps” on page 25
Users who can read log files	root user and users with the Junos maintenance permission	<pre>[edit system syslog] archive { world-readable; } file <i>filename</i> { archive { world-readable; } }</pre>	“Specifying Log File Size, Number, and Archiving Properties” on page 20

- [Junos OS System Log Overview](#)
- [Junos OS Platform-Specific Default System Log Messages on page 6](#)

Junos OS Platform-Specific Default System Log Messages

The following messages are generated by default on specific routers. To view any of these types of messages, you must configure at least one destination for messages as described in [“Junos OS Minimum System Logging Configuration” on page 4](#).

- To log the kernel process message on an M Series, MX Series, or T Series router, include the **kernel info** statement at the appropriate hierarchy level:

```
[edit system syslog]
(console | file filename | host destination | user username) {
  kernel info;
}
```

- On a routing matrix composed of a TX Matrix router and T640 routers, the master Routing Engine on each T640 router forwards all messages with a severity of **info** and higher to the master Routing Engine on the TX Matrix router. This is equivalent to the following configuration statement included on the TX Matrix router:

```
[edit system syslog]
host scc-master {
  any info;
}
```

- Likewise, on a routing matrix composed of a TX Matrix Plus router with connected T1600 or T4000 routers, the master Routing Engine on each T1600 or T4000 LCC forwards to the master Routing Engine on the TX Matrix Plus router all messages with a severity of **info** and higher. This is equivalent to the following configuration statement included on the TX Matrix Plus router:



NOTE: From the perspective of the user interface, the routing matrix appears as a single router. The TX Matrix Plus router controls all the T1600 or T4000 routers connected to it in the routing matrix.

```
[edit system syslog]
host sfc0-master {
  any info;
}
```

Related Documentation

- [Junos OS System Log Overview](#)
- [Junos OS Default System Log Settings on page 5](#)
- [Routing Matrix with a TX Matrix Plus Router Solutions Page](#)

Configuring System Logging for a Single-Chassis System

The Junos OS system logging utility is similar to the UNIX **syslogd** utility. This section describes how to configure system logging for a single-chassis system that runs Junos OS.

System logging configuration for Junos-FIPS software and for Juniper Networks routing platforms in a Common Criteria environment is the same as for Junos OS. For more information, see the *Secure Configuration Guide for Common Criteria and Junos-FIPS*.

Each system log message belongs to a facility, which groups together related messages. Each message is also preassigned a *severity level*, which indicates how seriously the triggering event affects routing platform functions. You always specify the facility and severity of the messages to include in the log. For more information, see [“Specifying the Facility and Severity of Messages to Include in the Log” on page 9](#).

You direct messages to one or more destinations by including the appropriate statement at the `[edit system syslog]` hierarchy level:

- To a named file in a local file system, by including the **file** statement. See [“Logging Messages in Structured-Data Format” on page 12](#).
- To the terminal session of one or more specific users (or all users) when they are logged in to the routing platform, by including the **user** statement. See [“Directing System Log Messages to a User Terminal” on page 13](#).
- To the routing platform console, by including the **console** statement. See [“Directing System Log Messages to the Console” on page 13](#).
- To a remote machine that is running the **syslogd** utility or to the other Routing Engine on the routing platform, by including the **host** statement. See [“Directing Messages to a Remote Destination from the Routing Matrix Based on the TX Matrix Router” on page 37](#).

By default, messages are logged in a standard format, which is based on a UNIX system log format; for detailed information, see [“Interpreting Messages Generated in Standard Format by a Junos OS Process or Library” on page 55](#), [“Interpreting Messages Generated in Standard Format by Services on a PIC” on page 56](#), and [“Interpreting Messages Generated in Structured-Data Format” on page 51](#). You can alter the content and format of logged messages in the following ways:

- In Junos 8.3 and later, you can log messages to a file in structured-data format instead of the standard Junos format. Structured-data format provides more information without adding significant length, and makes it easier for automated applications to extract information from the message. For more information, see [“Logging Messages in Structured-Data Format” on page 12](#).
- A message’s facility and severity level are together referred to as its priority. By default, the standard Junos format for messages does not include priority information. (Structured-data format includes a priority code by default.) To include priority information in standard-format messages directed to a file or a remote destination, include the **explicit-priority** statement. For more information, see [“Including Priority Information in System Log Messages” on page 22](#).
- By default, the standard Junos format for messages specifies the month, date, hour, minute, and second when the message was logged. You can modify the timestamp on standard-format messages to include the year, the millisecond, or both. (Structured-data format specifies the year and millisecond by default.) For more information, see [“Including the Year or Millisecond in Timestamps” on page 25](#).
- When directing messages to a remote machine, you can specify the IP address that is reported in messages as their source. You can also configure features that make it easier to separate Junos-specific messages or messages generated on particular routing platforms. For more information, see [“Directing Messages to a Remote Destination from the Routing Matrix Based on the TX Matrix Router” on page 37](#).
- The predefined facilities group together related messages, but you can also use regular expressions to specify more exactly which messages from a facility are logged to a

file, a user terminal, or a remote destination. For more information, see [“Using Regular Expressions to Refine the Set of Logged Messages” on page 25](#).

For a statement summary for the statements discussed in this chapter, see the *Junos System Basics Configuration Guide*.

- [Specifying the Facility and Severity of Messages to Include in the Log on page 9](#)
- [Directing System Log Messages to a Log File on page 11](#)
- [Logging Messages in Structured-Data Format on page 12](#)
- [Directing System Log Messages to a User Terminal on page 13](#)
- [Directing System Log Messages to the Console on page 13](#)
- [Directing Messages to a Remote Machine or the Other Routing Engine on page 13](#)
- [Specifying Log File Size, Number, and Archiving Properties on page 20](#)
- [Including Priority Information in System Log Messages on page 22](#)
- [System Log Facility Codes and Numerical Codes Reported in Priority Information on page 23](#)
- [Including the Year or Millisecond in Timestamps on page 25](#)
- [Using Regular Expressions to Refine the Set of Logged Messages on page 25](#)
- [Junos System Log Regular Expression Operators for the match Statement on page 27](#)
- [Disabling the System Logging of a Facility on page 28](#)
- [Examples: Configuring System Logging on page 29](#)

Specifying the Facility and Severity of Messages to Include in the Log

Each system log message belongs to a facility, which groups together messages that either are generated by the same source (such as a software process) or concern a similar condition or activity (such as authentication attempts). Each message is also preassigned a *severity level*, which indicates how seriously the triggering event affects routing platform functions.

When you configure logging for a facility and destination, you specify a severity level for each facility. Messages from the facility that are rated at that level and higher are logged to the following destination:

```
[edit system syslog]
(console | file filename | host destination | user username) {
  facility severity ;
}
```

For more information about the destinations, see [“Directing System Log Messages to a User Terminal” on page 13](#), and, [“Directing System Log Messages to the Console” on page 13](#).

To log messages belonging to more than one facility to a particular destination, specify each facility and associated severity as a separate statement within the set of statements for the destination.

Table 5 on page 10 lists the Junos OS system logging facilities that you can specify in configuration statements at the **[edit system syslog]** hierarchy level.

Table 5: Junos OS System Logging Facilities

Facility	Type of Event or Error
any	All (messages from all facilities)
authorization	Authentication and authorization attempts
change-log	Changes to the Junos OS configuration
conflict-log	Specified configuration is invalid on the router type
daemon	Actions performed or errors encountered by system processes
dfc	Events related to dynamic flow capture
firewall	Packet filtering actions performed by a firewall filter
ftp	Actions performed or errors encountered by the FTP process
interactive-commands	Commands issued at the Junos OS command-line interface (CLI) prompt or by a client application such as a Junos XML protocol or NETCONF XML client
kernel	Actions performed or errors encountered by the Junos OS kernel
pfe	Actions performed or errors encountered by the Packet Forwarding Engine
user	Actions performed or errors encountered by user-space processes

Table 6 on page 10 lists the severity levels that you can specify in configuration statements at the **[edit system syslog]** hierarchy level. The levels from **emergency** through **info** are in order from highest severity (greatest effect on functioning) to lowest.

Unlike the other severity levels, the **none** level disables logging of a facility instead of indicating how seriously a triggering event affects routing functions. For more information, see “Disabling the System Logging of a Facility” on page 28.

Table 6: System Log Message Severity Levels

Severity Level	Description
any	Includes all severity levels
none	Disables logging of the associated facility to a destination
emergency	System panic or other condition that causes the router to stop functioning

Table 6: System Log Message Severity Levels (*continued*)

Severity Level	Description
alert	Conditions that require immediate correction, such as a corrupted system database
critical	Critical conditions, such as hard errors
error	Error conditions that generally have less serious consequences than errors at the emergency, alert, and critical levels
warning	Conditions that warrant monitoring
notice	Conditions that are not errors but might warrant special handling
info	Events or nonerror conditions of interest

Related Documentation

- [Junos OS System Logging Facilities and Message Severity Levels](#)
- [Single-Chassis System Logging Configuration Overview](#)
- [Examples: Configuring System Logging on page 29](#)

Directing System Log Messages to a Log File

To direct system log messages to a file in the `/var/log` directory of the local Routing Engine, include the **file** statement at the `[edit system syslog]` hierarchy level:

```
[edit system syslog]
file filename {
    facility severity;
    archive <archive-sites (ftp-url <password password>)> <files number> <size size>
        <start-time "YYYY-MM-DD.hh:mm"> <transfer-interval minutes> <world-readable |
        no-world-readable>;
    explicit-priority;
    match "regular-expression";
    structured-data {
        brief;
    }
}
```

For the list of facilities and severity levels, see [“Specifying the Facility and Severity of Messages to Include in the Log” on page 9](#).

To prevent log files from growing too large, the Junos OS system logging utility by default writes messages to a sequence of files of a defined size. By including the **archive** statement, you can configure the number of files, their maximum size, and who can read them, either for all log files or for a certain log file. For more information, see [“Specifying Log File Size, Number, and Archiving Properties” on page 20](#).

For information about the following statements, see the indicated sections:

- **explicit-priority**—See “Including Priority Information in System Log Messages” on page 22
- **match**—See “Using Regular Expressions to Refine the Set of Logged Messages” on page 25
- **structured-data**—See “Logging Messages in Structured-Data Format” on page 12

**Related
Documentation**

- *Single-Chassis System Logging Configuration Overview*
- [Examples: Configuring System Logging on page 29](#)

Logging Messages in Structured-Data Format

You can log messages to a file in structured-data format instead of the standard Junos OS format. Structured-data format provides more information without adding significant length, and makes it easier for automated applications to extract information from a message.

The structured-data format complies with Internet draft draft-ietf-syslog-protocol-23, *The syslog Protocol*, which is at <http://tools.ietf.org/html/draft-ietf-syslog-protocol-23>. The draft establishes a standard message format regardless of the source or transport protocol for logged messages.

To output messages to a file in structured-data format, include the **structured-data** statement at the **[edit system syslog file *filename*]** hierarchy level:

```
[edit system syslog file filename]  
  facility severity;  
  structured-data {  
    brief;  
  }
```

The optional **brief** statement suppresses the English-language text that appears by default at the end of a message to describe the error or event.

The structured format is used for all messages logged to the file that are generated by a Junos process or software library.



NOTE: If you include either or both of the **explicit-priority** and **time-format** statements along with the **structured-data** statement, they are ignored. These statements apply to the standard Junos OS system log format, not to structured-data format.

**Related
Documentation**

- *Single-Chassis System Logging Configuration Overview*
- [Examples: Configuring System Logging on page 29](#)

Directing System Log Messages to a User Terminal

To direct system log messages to the terminal session of one or more specific users (or all users) when they are logged in to the local Routing Engine, include the **user** statement at the **[edit system syslog]** hierarchy level:

```
[edit system syslog]
user (username | *) {
    facility severity;
    match "regular-expression";
}
```

Specify one or more Junos OS usernames, separating multiple values with spaces, or use the asterisk (*) to indicate all users who are logged in to the local Routing Engine.

For the list of logging facilities and severity levels, see “[Specifying the Facility and Severity of Messages to Include in the Log](#)” on page 9. For information about the **match** statement, see “[Using Regular Expressions to Refine the Set of Logged Messages](#)” on page 25.

Related Documentation

- [Single-Chassis System Logging Configuration Overview](#)
- [Examples: Configuring System Logging on page 29](#)

Directing System Log Messages to the Console

To direct system log messages to the console of the local Routing Engine, include the **console** statement at the **[edit system syslog]** hierarchy level:

```
[edit system syslog]
console {
    facility severity;
}
```

For the list of logging facilities and severity levels, see “[Specifying the Facility and Severity of Messages to Include in the Log](#)” on page 9.

Related Documentation

- [Single-Chassis System Logging Configuration Overview](#)
- [Examples: Configuring System Logging on page 29](#)

Directing Messages to a Remote Machine or the Other Routing Engine

To direct system log messages to a remote machine or to the other Routing Engine on the routing platform, include the **host** statement at the **[edit system syslog]** hierarchy level:

```
[edit system syslog]
host (hostname | other-routing-engine) {
    facility severity;
    explicit-priority;
    facility-override facility;
    log-prefix string;
    match "regular-expression";
}
```

```
}  
source-address source-address;
```

To direct system log messages to a remote machine, include the **host** *hostname* statement to specify the remote machine's IPv4 address, IPv6 address, or fully qualified hostname. The remote machine must be running the standard **syslogd** utility. We do not recommend directing messages to another Juniper Networks routing platform. In each system log message directed to the remote machine, the hostname of the local Routing Engine appears after the timestamp to indicate that it is the source for the message.

To direct system log messages to the other Routing Engine on a routing platform with two Routing Engines installed and operational, include the **host other-routing-engine** statement. The statement is not automatically reciprocal, so you must include it in each Routing Engine's configuration if you want them to direct messages to each other. In each message directed to the other Routing Engine, the string **re0** or **re1** appears after the timestamp to indicate the source for the message.

For the list of facilities and severity levels to configure under the host statement, see [“Specifying the Facility and Severity of Messages to Include in the Log” on page 9](#).

To record facility and severity level information in each message, include the **explicit-priority** statement. For more information, see [“Including Priority Information in System Log Messages” on page 22](#).

For information about the **match** statement, see [“Using Regular Expressions to Refine the Set of Logged Messages” on page 25](#).

When directing messages to remote machines, you can include the **source-address** statement to specify the IP address of the routing platform that is reported in the messages as their source. In each host statement, you can also include the **facility-override** statement to assign an alternative facility and the **log-prefix** statement to add a string to each message. For more information, see the following sections:

- [Specifying an Alternative Source Address for System Log Messages Directed to a Remote Destination on page 15](#)
- [Changing the Alternative Facility Name for System Log Messages Directed to a Remote Destination on page 15](#)
- [Default Facilities for System Log Messages Directed to a Remote Destination on page 17](#)
- [Alternate Facilities for System Log Messages Directed to a Remote Destination on page 17](#)
- [Examples: Assigning an Alternative Facility to System Log Messages Directed to a Remote Destination on page 18](#)
- [Adding a Text String to System Log Messages Directed to a Remote Destination on page 19](#)
- [Adding a String on page 20](#)

Specifying an Alternative Source Address for System Log Messages Directed to a Remote Destination

To specify the source router to be reported in system log messages when the messages are directed to a remote machine, include the **source-address** statement at the **[edit system syslog]** hierarchy level:

```
[edit system syslog]
source-address source-address;
```

source-address is a valid IPv4 or IPv6 address configured on one of the router interfaces. The address is reported in the messages directed to all remote machines specified in **host hostname** statements at the **[edit system syslog]** hierarchy level, but not in messages directed to the other Routing Engine.

Related Documentation

- [Single-Chassis System Logging Configuration Overview](#)
- [Examples: Assigning an Alternative Facility to System Log Messages Directed to a Remote Destination on page 18](#)

Changing the Alternative Facility Name for System Log Messages Directed to a Remote Destination

Some facilities assigned to messages logged on the local router or switch have Junos OS-specific names (see *Junos OS System Logging Facilities and Message Severity Levels*). In the recommended configuration, a remote machine designated at the **[edit system syslog host hostname]** hierarchy level is not a Juniper Networks router or switch, so its syslogd utility cannot interpret the Junos OS-specific names. To enable the standard syslogd utility to handle messages from these facilities when messages are directed to a remote machine, a standard **localX** facility name is used instead of the Junos OS-specific facility name.

[Table 7 on page 17](#) lists the default alternative facility name next to the Junos OS-specific facility name it is used for.

The syslogd utility on a remote machine handles all messages that belong to a facility in the same way, regardless of the source of the message (the Juniper Networks router or switch or the remote machine itself). For example, the following statements in the configuration of the router called **local-router** direct messages from the **authorization** facility to the remote machine *monitor.mycompany.com*:

```
[edit system syslog]
host monitor.mycompany.com {
    authorization info;
}
```

The default alternative facility for the local **authorization** facility is also **authorization**. If the syslogd utility on **monitor** is configured to write messages belonging to the **authorization** facility to the file **/var/log/auth-attempts**, then the file contains the messages generated when users log in to **local-router** and the messages generated when users log in to **monitor**. Although the name of the source machine appears in each system log

message, the mixing of messages from multiple machines can make it more difficult to analyze the contents of the **auth-attempts** file.

To make it easier to separate the messages from each source, you can assign an alternative facility to all messages generated on **local-router** when they are directed to **monitor**. You can then configure the syslogd utility on **monitor** to write messages with the alternative facility to a different file from messages generated on **monitor** itself.

To change the facility used for all messages directed to a remote machine, include the **facility-override** statement at the **[edit system syslog host *hostname*]** hierarchy level:

```
[edit system syslog host hostname]  
  facility severity;  
  facility-override facility;
```

In general, it makes sense to specify an alternative facility that is not already in use on the remote machine, such as one of the **localX** facilities. On the remote machine, you must also configure the syslogd utility to handle the messages in the desired manner.

[Table 8 on page 17](#) lists the facilities that you can specify in the **facility-override** statement.

We do not recommend including the **facility-override** statement at the **[edit system syslog host *other-routing-engine*]** hierarchy level. It is not necessary to use alternative facility names when directing messages to the other Routing Engine, because its Junos OS system logging utility can interpret the Junos OS-specific names.

The following example shows how to log all messages generated on the local router at the error level or higher to the local0 facility on the remote machine called **monitor.mycompany.com**:

```
[edit system syslog]  
host monitor.mycompany.com {  
  any error;  
  facility-override local0;  
}
```

The following example shows how to configure routers located in California and routers located in New York to send messages to a single remote machine called **central-logger.mycompany.com**. The messages from California are assigned to alternative facility **local0** and the messages from New York are assigned to alternative facility **local2**.

- Configure California routers to aggregate messages in the local0 facility:

```
[edit system syslog]  
host central-logger.mycompany.com {  
  change-log info;  
  facility-override local0;  
}
```

- Configure New York routers to aggregate messages in the local2 facility:

```
[edit system syslog]  
host central-logger.mycompany.com {  
  change-log info;  
  facility-override local2;  
}
```

On central-logger, you can then configure the system logging utility to write messages from the local0 facility to the file **change-log** and the messages from the local2 facility to the file **new-york-config**.

Related Documentation

- [Table 7 on page 17](#)
- [Alternate Facilities for System Log Messages Directed to a Remote Destination on page 17](#)
- [Examples: Assigning an Alternative Facility to System Log Messages Directed to a Remote Destination on page 18](#)

Default Facilities for System Log Messages Directed to a Remote Destination

[Table 7 on page 17](#) lists the default alternative facility name next to the Junos OS-specific facility name for which it is used. For facilities that are not listed, the default alternative name is the same as the local facility name.

Table 7: Default Facilities for Messages Directed to a Remote Destination

Junos OS–Specific Local Facility	Default Facility When Directed to Remote Destination
change-log	local6
conflict-log	local5
dfc	local1
firewall	local3
interactive-commands	local7
pfe	local4

Related Documentation

- [Single-Chassis System Logging Configuration Overview](#)

Alternate Facilities for System Log Messages Directed to a Remote Destination

[Table 8 on page 17](#) lists the facilities that you can specify in the **facility-override** statement.

Table 8: Facilities for the facility-override Statement

Facility	Description
authorization	Authentication and authorization attempts
daemon	Actions performed or errors encountered by system processes
ftp	Actions performed or errors encountered by the FTP process

Table 8: Facilities for the facility-override Statement (*continued*)

Facility	Description
kernel	Actions performed or errors encountered by the Junos OS kernel
local0	Local facility number 0
local1	Local facility number 1
local2	Local facility number 2
local3	Local facility number 3
local4	Local facility number 4
local5	Local facility number 5
local6	Local facility number 6
local7	Local facility number 7
user	Actions performed or errors encountered by user-space processes

We do not recommend including the **facility-override** statement at the **[edit system syslog host other-routing-engine]** hierarchy level. It is not necessary to use alternative facility names when directing messages to the other Routing Engine, because its Junos OS system logging utility can interpret the Junos OS-specific names.

Related Documentation

- [Examples: Assigning an Alternative Facility to System Log Messages Directed to a Remote Destination on page 18](#)
- [Single-Chassis System Logging Configuration Overview](#)

Examples: Assigning an Alternative Facility to System Log Messages Directed to a Remote Destination

Log all messages generated on the local routing platform at the error level or higher to the **local0** facility on the remote machine called **monitor.mycompany.com**:

```
[edit system syslog]
host monitor.mycompany.com {
  any error;
  facility-override local0;
}
```

Configure routing platforms located in California and routing platforms located in New York to send messages to a single remote machine called **central-logger.mycompany.com**. The messages from California are assigned alternative facility **local0** and the messages from New York are assigned to alternative facility **local2**.

- Configure California routing platforms to aggregate messages in the **local0** facility:

```
[edit system syslog]
host central-logger.mycompany.com {
  change-log info;
  facility-override local0;
}
```

- Configure New York routing platforms to aggregate messages in the **local2** facility:

```
[edit system syslog]
host central-logger.mycompany.com {
  change-log info;
  facility-override local2;
}
```

On **central-logger**, you can then configure the system logging utility to write messages from the **local0** facility to the file **california-config** and the messages from the **local2** facility to the file **new-york-config**.

Related Documentation

- [Alternate Facilities for System Log Messages Directed to a Remote Destination on page 17](#)

Adding a Text String to System Log Messages Directed to a Remote Destination

To add a text string to every system log message directed to a remote machine or to the other Routing Engine, include the **log-prefix** statement at the **[edit system syslog host]** hierarchy level:

```
[edit system syslog host (hostname | other-routing-engine)]
  facility severity;
  log-prefix string;
```

The string can contain any alphanumeric or special character except the equal sign (=) and the colon (:). It also cannot include the space character; do not enclose the string in quotation marks (" ") in an attempt to include spaces in it.

The Junos OS system logging utility automatically appends a colon and a space to the specified string when the system log messages are written to the log. The string is inserted after the identifier for the Routing Engine that generated the message.

The following example shows how to add the string M120 to all messages to indicate that the router is an M120 router, and direct the messages to the remote machine hardware-logger.mycompany.com:

```
[edit system syslog]
host hardware-logger.mycompany.com {
  any info;
  log-prefix M120;
}
```

When these configuration statements are included on an M120 router called origin1, a message in the system log on hardware-logger.mycompany.com looks like the following:

```
Mar 9 17:33:23 origin1 M120: mgd[477]: UI_CMDLINE_READ_LINE: user 'root', command 'run
show version'
```

Related Documentation

- [Single-Chassis System Logging Configuration Overview](#)
- [Specifying Log File Size, Number, and Archiving Properties on page 20](#)

Adding a String

Add the string M120 to all messages to indicate that the router is an M120 router, and direct the messages to the remote machine `hardware-logger.mycompany.com`:

```
[edit system syslog]
host hardware-logger.mycompany.com {
  any info;
  log-prefix M120;
}
```

When these configuration statements are included on an M120 router called `origin1`, a message in the system log on `hardware-logger.mycompany.com` looks like the following:

```
Mar 9 17:33:23 origin1 M120: mgd[477]: UI_CMDLINE_READ_LINE: user 'root', command 'run show version'
```

Specifying Log File Size, Number, and Archiving Properties

To prevent log files from growing too large, by default the Junos OS system logging utility writes messages to a sequence of files of a defined size. The files in the sequence are referred to as *archive* files to distinguish them from the *active* file to which messages are currently being written. The default maximum size depends on the platform type:

- 128 kilobytes (KB) for EX Series switches
- 1 megabyte (MB) for M Series, MX Series, and T Series routers
- 10 MB for TX Matrix or TX Matrix Plus routers
- 1 MB for the QFX Series

When an active log file called *logfile* reaches the maximum size, the logging utility closes the file, compresses it, and names the compressed archive file *logfile.0.gz*. The logging utility then opens and writes to a new active file called *logfile*. This process is also known as file rotation. When the new *logfile* reaches the configured maximum size, *logfile.0.gz* is renamed *logfile.1.gz*, and the new *logfile* is closed, compressed, and renamed *logfile.0.gz*. By default, the logging utility creates up to 10 archive files in this manner. When the maximum number of archive files is reached and when the size of the active file reaches the configured maximum size, the contents of the last archived file are overwritten by the current active file. The logging utility by default also limits the users who can read log files to the **root** user and users who have Junos OS **maintenance** permission.

Junos OS provides a configuration statement **log-rotate-frequency** that configures the system log file rotation frequency by configuring the time interval for checking the log file size. The frequency can be set to a value of 1 minute through 59 minutes. The default frequency is 15 minutes.

To configure the log rotation frequency, include the **log-rotate-frequency** statement at the **[edit system syslog]** hierarchy level.

You can include the **archive** statement to change the maximum size of each file, how many archive files are created, and who can read log files.

To configure values that apply to all log files, include the **archive** statement at the **[edit system syslog]** hierarchy level:

```
archive <files number> <size size> <world-readable | no-world-readable>;
```

To configure values that apply to a specific log file, include the **archive** statement at the **[edit system syslog file *filename*]** hierarchy level:

```
archive <archive-sites (ftp-url <password password>)> <files number> <size size>
  <start-time "YYYY-MM-DD.hh:mm"> <transfer-interval minutes> <world-readable |
  no-world-readable>;
```

archive-sites *site-name* specifies a list of archive sites that you want to use for storing files. The ***site-name*** value is any valid FTP URL to a destination. If more than one site name is configured, a list of archive sites for the system log files is created. When a file is archived, the router or switch attempts to transfer the file to the first URL in the list, moving to the next site only if the transfer does not succeed. The log file is stored at the archive site with the specified log filename. For information about how to specify valid FTP URLs, see [Format for Specifying Filenames and URLs in Junos OS CLI Commands](#).

binary-data Mark file as containing binary data. This allows proper archiving of binary files, such as WTMP files (login records for UNIX based systems). To restore the default setting, include the **no-binary-data** statement.

files *number* specifies the number of files to create before the oldest file is overwritten. The value can be from 1 through 1000.

size *size* specifies the maximum size of each file. The value can be from 64 KB (64k) through 1 gigabyte (1g); to represent megabytes, use the letter **m** after the integer. There is no space between the digits and the **k**, **m**, or **g** units letter.

start-time "YYYY-MM-DD.hh:mm" defines the date and time in the local time zone for a one-time transfer of the active log file to the first reachable site in the list of sites specified by the **archive-sites** statement.

transfer-interval *interval* defines the amount of time the current log file remains open (even if it has not reached the maximum possible size) and receives new statistics before it is closed and transferred to an archive site. This interval value can be from 5 through 2880 minutes.

world-readable enables all users to read log files. To restore the default permissions, include the **no-world-readable** statement.

Related Documentation

- [Single-Chassis System Logging Configuration Overview](#)
- [Examples: Configuring System Logging on page 29](#)
- [Routing Matrix with a TX Matrix Plus Router Solutions Page](#)

Including Priority Information in System Log Messages

The facility and severity level of a message are together referred to as its *priority*. By default, messages logged in the standard Junos OS format do not include information about priority. To include priority information in standard-format messages directed to a file, include the **explicit-priority** statement at the **[edit system syslog file *filename*]** hierarchy level:

```
[edit system syslog file filename]  
  facility severity;  
  explicit-priority;
```



NOTE: Messages logged in structured-data format include priority information by default. If you include the **structured-data** statement at the **[edit system syslog file *filename*]** hierarchy level along with the **explicit-priority** statement, the **explicit-priority** statement is ignored and messages are logged in structured-data format.

For information about the **structured-data** statement, see [“Logging Messages in Structured-Data Format” on page 12](#).

To include priority information in messages directed to a remote machine or the other Routing Engine, include the **explicit-priority** statement at the **[edit system syslog host (*hostname* | other-routing-engine)]** hierarchy level:

```
[edit system syslog host (hostname | other-routing-engine)]  
  facility severity;  
  explicit-priority;
```



NOTE: The **other-routing-engine** option does not apply to the QFX Series.

The priority recorded in a message always indicates the original, local facility name. If the **facility-override** statement is included for messages directed to a remote destination, the Junos OS system logging utility still uses the alternative facility name for the messages themselves when directing them to the remote destination. For more information, see [“Changing the Alternative Facility Name for System Log Messages Directed to a Remote Destination” on page 15](#).

When the **explicit-priority** statement is included, the Junos OS logging utility prepends codes for the facility name and severity level to the message tag name, if the message has one:

```
FACILITY-severity[-TAG]
```

(The tag is a unique identifier assigned to some Junos OS system log messages.)

In the following example, the **CHASSISD_PARSE_COMPLETE** message belongs to the **daemon** facility and is assigned severity **info** (6):

```
Aug 21 12:36:30 router1 chassisd[522]: %DAEMON-6-CHASSISD_PARSE_COMPLETE:
Using new configuration
```

When the **explicit-priority** statement is not included, the priority does not appear in the message:

```
Aug 21 12:36:30 router1 chassisd[522]: CHASSISD_PARSE_COMPLETE: Using new
configuration
```

- Related Documentation**
- [Single-Chassis System Logging Configuration Overview](#)
 - [Examples: Configuring System Logging on page 29](#)

System Log Facility Codes and Numerical Codes Reported in Priority Information

Table 9 on page 23 lists the facility codes that can appear in system log messages and maps them to facility names.



NOTE: If the second column in Table 9 on page 23 does not include the Junos OS facility name for a code, the facility cannot be included in a statement at the [edit system syslog] hierarchy level. Junos OS might use the facilities in Table 9 on page 23—and others that are not listed—when reporting on internal operations.

Table 9: Facility Codes Reported in Priority Information

Code	Junos Facility Name	Type of Event or Error
AUTH	authorization	Authentication and authorization attempts
AUTHPRIV		Authentication and authorization attempts that can be viewed by superusers only
CHANGE	change-log	Changes to Junos OS configuration
CONFLICT	conflict-log	Specified configuration is invalid on the router type
CONSOLE		Messages written to /dev/console by the kernel console output r
CRON		Actions performed or errors encountered by the cron process
DAEMON	daemon	Actions performed or errors encountered by system processes
DFC	dfc	Actions performed or errors encountered by the dynamic flow capture process
FIREWALL	firewall	Packet filtering actions performed by a firewall filter
FTP	ftp	Actions performed or errors encountered by the FTP process

Table 9: Facility Codes Reported in Priority Information (*continued*)

Code	Junos Facility Name	Type of Event or Error
INTERACT	interactive-commands	Commands issued at the Junos OS CLI prompt or invoked by a client application such as a Junos XML protocol or NETCONF client
KERN	kernel	Actions performed or errors encountered by the Junos kernel
NTP		Actions performed or errors encountered by the Network Time Protocol (NTP)
PFE	pfe	Actions performed or errors encountered by the Packet Forwarding Engine
SYSLOG		Actions performed or errors encountered by the Junos system logging utility
USER	user	Actions performed or errors encountered by user-space processes

Table 10 on page 24 lists the numerical severity codes that can appear in system log messages and maps them to severity levels.

Table 10: Numerical Codes for Severity Levels Reported in Priority Information

Numerical Code	Severity Level	Description
0	emergency	System panic or other condition that causes the router to stop functioning
1	alert	Conditions that require immediate correction, such as a corrupted system database
2	critical	Critical conditions, such as hard errors
3	error	Error conditions that generally have less serious consequences than errors in the emergency, alert, and critical levels
4	warning	Conditions that warrant monitoring
5	notice	Conditions that are not errors but might warrant special handling
6	info	Events or nonerror conditions of interest
7	debug	Software debugging messages (these appear only if a technical support representative has instructed you to configure this severity level)

- Related Documentation**
- [Single-Chassis System Logging Configuration Overview](#)
 - [Examples: Configuring System Logging on page 29](#)

Including the Year or Millisecond in Timestamps

By default, the timestamp recorded in a standard-format system log message specifies the month, date, hour, minute, and second when the message was logged, as in the following example:

```
Aug 21 12:36:30
```

To include the year, the millisecond, or both in the timestamp, include the **time-format** statement at the **[edit system syslog]** hierarchy level:

```
[edit system syslog]
time-format (year | millisecond | year millisecond);
```

However, the timestamp for traceoption messages is specified in milliseconds by default, and is independent of the **[edit system syslog time-format]** statement.

The modified timestamp is used in messages directed to each destination configured by a **file**, **console**, or **user** statement at the **[edit system syslog]** hierarchy level, but not to destinations configured by a **host** statement.

The following example illustrates the format for a timestamp that includes both the millisecond (401) and the year (2006):

```
Aug 21 12:36:30.401 2006
```



NOTE: Messages logged in structured-data format include the year and millisecond by default. If you include the structured-data statement at the **[edit system syslog file filename]** hierarchy level along with the **time-format** statement, the **time-format** statement is ignored and messages are logged in structured-data format.

For information about the structured-data statement, see “[Logging Messages in Structured-Data Format](#)” on page 12. For information about the contents of a structured-data message, see the *Junos OS System Log Messages Reference*.

- Related Documentation**
- [Single-Chassis System Logging Configuration Overview](#)
 - [Examples: Configuring System Logging on page 29](#)

Using Regular Expressions to Refine the Set of Logged Messages

The predefined facilities group together related messages, but you can also use regular expression matching to specify more exactly which messages from a facility are logged to a file, a user terminal, or a remote destination.

To specify the text string that must (or must not) appear in a message for the message to be logged to a destination, include the **match** statement and specify the regular expression which the text string must match:

```
match "regular-expression";
```

You can include this statement at the following hierarchy levels:

- **[edit system syslog file *filename*]** (for a file)
- **[edit system syslog user (*username* | *)]** (for a specific user session or for all user sessions on a terminal)
- **[edit system syslog host (*hostname* | other-routing-engine)]** (for a remote destination)

In specifying the regular expression, use the notation defined in POSIX Standard 1003.2 for extended (modern) UNIX regular expressions. Explaining regular expression syntax is beyond the scope of this document, but POSIX standards are available from the Institute of Electrical and Electronics Engineers (IEEE, <http://www.ieee.org>).

Table 11 on page 26 specifies which character or characters are matched by some of the regular expression operators that you can use in the match statement. In the descriptions, the term *term* refers to either a single alphanumeric character or a set of characters enclosed in square brackets, parentheses, or braces.



NOTE: The match statement is not case-sensitive.

Table 11: Regular Expression Operators for the match Statement

Operator	Matches
. (period)	One instance of any character except the space.
* (asterisk)	Zero or more instances of the immediately preceding term.
+ (plus sign)	One or more instances of the immediately preceding term.
? (question mark)	Zero or one instance of the immediately preceding term.
(pipe)	One of the terms that appears on either side of the pipe operator.
! (exclamation point)	Any string except the one specified by the expression, when the exclamation point appears at the start of the expression. Use of the exclamation point is Junos OS-specific.
^ (caret)	Start of a line, when the caret appears outside square brackets. One instance of any character that does not follow it within square brackets, when the caret is the first character inside square brackets.
\$ (dollar sign)	End of a line.

Table 11: Regular Expression Operators for the match Statement (*continued*)

Operator	Matches
[] (paired square brackets)	One instance of one of the enclosed alphanumeric characters. To indicate a range of characters, use a hyphen (-) to separate the beginning and ending characters of the range. For example, [a-z0-9] matches any letter or number.
() (paired parentheses)	One instance of the evaluated value of the enclosed term. Parentheses are used to indicate the order of evaluation in the regular expression.

Using Regular Expressions Filter messages that belong to the **interactive-commands** facility, directing those that include the string **configure** to the terminal of the root user:

```
[edit system syslog]
user root {
  interactive-commands any;
  match ".*configure.*";
}
```

Messages like the following appear on the **root** user's terminal when a user issues a **configure** command to enter configuration mode:

```
timestamp router-name mgd[PID]: UI_CMDLINE_READ_LINE: User 'user', command
'configure private'
```

Filter messages that belong to the **daemon** facility and have a severity of **error** or higher, directing them to the file **/var/log/process-errors**. Omit messages generated by the SNMP process (snmpd), instead directing them to the file **/var/log/snmpd-errors**:

```
[edit system syslog]
file process-errors {
  daemon error;
  match "!(.*snmpd.*)";
}
file snmpd-errors {
  daemon error;
  match ".*snmpd.*";
}
```

Related Documentation

- [Single-Chassis System Logging Configuration Overview](#)
- [Examples: Configuring System Logging on page 29](#)

Junos System Log Regular Expression Operators for the match Statement

Table 12: Regular Expression Operators for the match Statement

Operator	Matches
. (period)	One instance of any character except the space.
* (asterisk)	Zero or more instances of the immediately preceding term.

Table 12: Regular Expression Operators for the match Statement (*continued*)

Operator	Matches
+ (plus sign)	One or more instances of the immediately preceding term.
? (question mark)	Zero or one instance of the immediately preceding term.
(pipe)	One of the terms that appear on either side of the pipe operator.
! (exclamation point)	Any string except the one specified by the expression, when the exclamation point appears at the start of the expression. Use of the exclamation point is Junos OS–specific.
^ (caret)	The start of a line, when the caret appears outside square brackets. One instance of any character that does not follow it within square brackets, when the caret is the first character inside square brackets.
\$ (dollar sign)	The end of a line.
[] (paired square brackets)	One instance of one of the enclosed alphanumeric characters. To indicate a range of characters, use a hyphen (-) to separate the beginning and ending characters of the range. For example, [a-z0-9] matches any letter or number.
() (paired parentheses)	One instance of the evaluated value of the enclosed term. Parentheses are used to indicate the order of evaluation in the regular expression.

- Related Documentation**
- [Single-Chassis System Logging Configuration Overview](#)
 - [Examples: Configuring System Logging on page 29](#)

Disabling the System Logging of a Facility

To disable the logging of messages that belong to a particular facility, include the **facility none** statement in the configuration. This statement is useful when, for example, you want to log messages that have the same severity level and belong to all but a few facilities. Instead of including a statement for each facility you want to log, you can include the **any severity** statement and then a **facility none** statement for each facility that you do not want to log. For example, the following logs all messages at the **error** level or higher to the console, except for messages from the **daemon** and **kernel** facilities. Messages from those facilities are logged to the file **>/var/log/internals** instead:

```
[edit system syslog]
console {
  any error;
  daemon none;
  kernel none;
}
file internals {
  daemon info;
```



```

    kernel info;
}

```

Related Documentation

- *Single-Chassis System Logging Configuration Overview*

Examples: Configuring System Logging

The following example shows how to configure the logging of messages about all commands entered by users at the CLI prompt or invoked by client applications such as Junos OS XML protocol or NETCONF client applications, and all authentication or authorization attempts, both to the file **cli-commands** and to the terminal of any user who is logged in:

```

[edit system]
syslog {
  file cli-commands {
    interactive-commands info;
    authorization info;
  }
  user * {
    interactive-commands info;
    authorization info;
  }
}

```

The following example shows how to configure the logging of all changes in the state of alarms to the file **/var/log/alarms**:

```

[edit system]
syslog {
  file alarms {
    kernel warning;
  }
}

```

The following example shows how to configure the handling of messages of various types, as described in the comments. Information is logged to two files, to the terminal of user **alex**, to a remote machine, and to the console:

```

[edit system]
syslog {
  /* write all security-related messages to file /var/log/security */
  file security {
    authorization info;
    interactive-commands info;
  }
  /* write messages about potential problems to file /var/log/messages: */
  /* messages from "authorization" facility at level "notice" and above, */
  /* messages from all other facilities at level "warning" and above */
  file messages {
    authorization notice;
    any warning;
  }
  /* write all messages at level "critical" and above to terminal of user "alex" if */
  /* that user is logged in */
}

```

```
user alex {
  any critical;
}
/* write all messages from the "daemon" facility at level "info" and above, and */
/* messages from all other facilities at level "warning" and above, to the */
/* machine monitor.mycompany.com */
host monitor.mycompany.com {
  daemon info;
  any warning;
}
/* write all messages at level "error" and above to the system console */
console {
  any error;
}
}
```

The following example shows how to configure the handling of messages generated when users issue Junos OS CLI commands, by specifying the **interactive-commands** facility at the following severity levels:

- **info**—Logs a message when users issue any command at the CLI operational or configuration mode prompt. The example writes the messages to the file `/var/log/user-actions`.
- **notice**—Logs a message when users issue the configuration mode commands **rollback** and **commit**. The example writes the messages to the terminal of user **philip**.
- **warning**—Logs a message when users issue a command that restarts a software process. The example writes the messages to the console.

```
[edit system]
syslog {
  file user-actions {
    interactive-commands info;
  }
  user philip {
    interactive-commands notice;
  }
  console {
    interactive-commands warning;
  }
}
```

**Related
Documentation**

- *Single-Chassis System Logging Configuration Overview*

Configuring System Logging for a TX Matrix Router

To configure system logging for all routers in a routing matrix composed of a TX Matrix router and T640 routers, include the **syslog** statement at the **[edit system]** hierarchy level on the TX Matrix router. The **syslog** statement applies to every router in the routing matrix.

```
[edit system]
syslog {
  archive <files number> <size size <world-readable | no-world-readable>;
  console {
    facility severity;
  }
  file filename {
    facility severity;
    archive <archive-sites {ftp-url <password password>}> <files number> <size size>
      <start-time "YYYY-MM-DD.hh:mm"> <transfer-interval minutes> <world-readable |
      no-world-readable>;
    explicit-priority;
    match "regular-expression";
    structured-data {
      brief;
    }
  }
}
host (hostname | other-routing-engine | scc-master) {
  facility severity;
  explicit-priority;
  facility-override facility;
  log-prefix string;
  match "regular-expression";
  source-address source-address;
  port port number;
}
source-address source-address;
time-format (year | millisecond | year millisecond);
(username | *) {
  facility severity;
  match "regular-expression";
}
}
```

When included in the configuration on the TX Matrix router, the following configuration statements have the same effect as on a single-chassis system, except that they apply to every router in the routing matrix:

- **archive**—Sets the size and number of log files on each platform in the routing matrix. See [“Specifying Log File Size, Number, and Archiving Properties” on page 20](#).
- **console**—Directs the specified messages to the console of each platform in the routing matrix. See [“Directing System Log Messages to the Console” on page 13](#).
- **file**—Directs the specified messages to a file of the same name on each platform in the routing matrix. See [“Directing System Log Messages to a Log File” on page 11](#).

- **match**—Limits the set of messages logged to a destination to those that contain (or do not contain) a text string matching a regular expression. See [“Using Regular Expressions to Refine the Set of Logged Messages”](#) on page 25.

The separate **match** statement at the **[edit system syslog host scc-master]** hierarchy level applies to messages forwarded from the T640 routers to the TX Matrix router. See [Configuring Optional Features for Forwarded Messages on a TX Matrix Plus Router](#).

- **port**—Specifies the port number of the remote syslog server.
- **source-address**—Sets the IP address of the router to report in system log messages as the message source, when the messages are directed to the remote machines specified in all **host *hostname*** statements at the **[edit system syslog]** hierarchy level, for each platform in the routing matrix. On a routing matrix composed of a TX Matrix router and T640 routers, the address is not reported by the T640 routers in messages directed to the other Routing Engine on each router or to the TX Matrix router. See [“Specifying an Alternative Source Address for System Log Messages Directed to a Remote Destination”](#) on page 15.
- **structured-data**—Writes messages to a file in structured-data format. See [“Logging Messages in Structured-Data Format”](#) on page 12.
- **time-format**—Adds the millisecond, year, or both to the timestamp in each standard-format message. See [“Including the Year or Millisecond in Timestamps”](#) on page 25.
- **user**—Directs the specified messages to the terminal session of one or more specified users on each platform in the routing matrix that they are logged in to. See [“Directing System Log Messages to a User Terminal”](#) on page 13.

The effect of the other statements differs somewhat for a routing matrix than for a single-chassis system. For more information, see the following sections:

- [Configuring Message Forwarding in the Routing Matrix](#) on page 33
- [Configuring Optional Features for Forwarded Messages](#) on page 36
- [Directing Messages to a Remote Destination from the Routing Matrix Based on the TX Matrix Router](#) on page 37
- [Configuring System Logging Differently on Each T640 Router in a Routing Matrix](#) on page 38
- [Configuring System Logging for a TX Matrix Plus Router](#) on page 40
- [Configuring Message Forwarding to the TX Matrix Plus Router](#) on page 42
- [Impact of Different Local and Forwarded Severity Levels on System Log Messages on a TX Matrix Plus Router](#) on page 43
- [Configuring Optional Features for Forwarded Messages on a TX Matrix Plus Router](#) on page 45
- [Directing Messages to a Remote Destination from the Routing Matrix Based on a TX Matrix Plus Router](#) on page 46
- [Configuring System Logging Differently on Each T1600 or T4000 Router in a Routing Matrix](#) on page 47

Configuring Message Forwarding in the Routing Matrix

By default, the master Routing Engine on each T640 routing node forwards to the master Routing Engine on the TX Matrix platform all messages from all facilities with severity **info** and higher. To change the facility, the severity level, or both, include the **host scc-master** statement at the **[edit system syslog]** hierarchy level on the TX Matrix platform:

```
[edit system syslog]
host scc-master {
  facility severity;
}
```

To disable message forwarding, set the facility to **any** and the severity level to **none**:

```
[edit system syslog]
host scc-master {
  any none;
}
```

In either case, the setting applies to all T640 routing nodes in the routing matrix.

To capture the messages forwarded by the T640 routing nodes (as well as messages generated on the TX Matrix platform itself), you must also configure system logging on the TX Matrix platform. Direct the messages to one or more destinations by including the appropriate statements at the **[edit system syslog]** hierarchy level on the TX Matrix platform:

- To a file, as described in [Directing Messages to a Log File](#).
- To the terminal session of one or more specific users (or all users), as described in [“Directing System Log Messages to a User Terminal” on page 13](#).
- To the console, as described in [“Directing System Log Messages to the Console” on page 13](#).
- To a remote machine that is running the **syslogd** utility or to the other Routing Engine. For more information, see [“Directing Messages to a Remote Destination from the Routing Matrix Based on the TX Matrix Router” on page 37](#).

As previously noted, the configuration statements included on the TX Matrix platform also configure the same destinations on each T640 routing node.

When specifying the severity level for local messages (at the **[edit system syslog (file | host | console | user)]** hierarchy level) and forwarded messages (at the **[edit system syslog host scc-master]** hierarchy level), you can set the same severity level for both, set a lower severity level for local messages, or set a higher severity level for local messages. The following examples describe the consequence of each configuration. (For simplicity, the examples use the **any** facility in every case. You can also specify different severities for different facilities, with more complex consequences.)

- [Impact of Different Local and Forwarded Severity Levels on System Log Messages on a TX Matrix Router on page 34](#)

Impact of Different Local and Forwarded Severity Levels on System Log Messages on a TX Matrix Router

This topic describes the impact of different local and forwarded severity levels configured for system log messages on a TX Matrix router:

- [Messages Logged When the Local and Forwarded Severity Levels Are the Same on page 34](#)
- [Messages Logged When the Local Severity Level Is Lower on page 34](#)
- [Messages Logged When the Local Severity Level Is Higher on page 35](#)

Messages Logged When the Local and Forwarded Severity Levels Are the Same

When the severity level is the same for local and forwarded messages, the log on the TX Matrix router contains all messages from the logs on the T640 routers. For example, you can specify severity **info** for the `/var/log/messages` file, which is the default severity level for messages forwarded by T640 routers:

```
[edit system syslog]
file messages {
  any info;
}
```

[Table 13 on page 34](#) specifies which messages are included in the logs on the T640 routers and the TX Matrix router.

Table 13: Example: Local and Forwarded Severity Level Are Both info

Log Location	Source of Messages	Lowest Severity Included
T640 router	Local	info
TX Matrix router	Local	info
	Forwarded from T640 routers	info

Messages Logged When the Local Severity Level Is Lower

When the severity level is lower for local messages than for forwarded messages, the log on the TX Matrix router includes fewer forwarded messages than when the severities are the same. Locally generated messages are still logged at the lower severity level, so their number in each log is the same as when the severities are the same.

For example, on a TX Matrix router, you can specify severity **notice** for the `/var/log/messages` file and severity **critical** for forwarded messages:

```
[edit system syslog]
file messages {
  any notice;
}
host scc-master {
  any critical;
}
```

Table 14 on page 35 specifies which messages in a routing matrix are included in the logs on the T640 routers and the TX Matrix router. The T640 routers forward only those messages with severity **critical** and higher, so the log on the TX Matrix router does not include the messages with severity **error**, **warning**, or **notice** that the T640 routers log locally.

Table 14: Example: Local Severity Is notice, Forwarded Severity Is critical

Log Location	Source of Messages	Lowest Severity Included
T640 router	Local	notice
TX Matrix router	Local	notice
	Forwarded from T640 routers	critical

Messages Logged When the Local Severity Level Is Higher

When the severity level is higher for local messages than for forwarded messages, the log on the TX Matrix router includes fewer forwarded messages than when the severities are the same, and all local logs contain fewer messages overall.

For example, you can specify severity **critical** for the `/var/log/messages` file and severity **notice** for forwarded messages:

```
[edit system syslog]
file messages {
    any critical;
}
host scc-master {
    any notice;
}
```

Table 15 on page 35 specifies which messages are included in the logs on the T640 routers and the TX Matrix router. Although the T640 routers forward messages with severity **notice** and higher, the TX Matrix router discards any of those messages with severity lower than **critical** (does not log forwarded messages with severity **error**, **warning**, or **notice**). None of the logs include messages with severity **error** or lower.

Table 15: Example: Local Severity Is critical, Forwarded Severity Is notice

Log Location	Source of Messages	Lowest Severity Included
T640 router	Local	critical
TX Matrix router	Local	critical
	Forwarded from T640 routers	critical

Related Documentation

- *Configuring System Logging for a TX Matrix Router*

Configuring Optional Features for Forwarded Messages

To configure additional optional features when specifying how the T640 routing nodes forward messages to the TX Matrix platform, include statements at the `[edit system syslog host scc-master]` hierarchy level. To include priority information (facility and severity level) in each forwarded message, include the **explicit-priority** statement. To insert a text string in each forwarded message, include the **log-prefix** statement. To use regular expression matching to specify more exactly which messages from a facility are forwarded, include the **match** statement.

```
[edit system syslog host scc-master]
  facility severity;
  explicit-priority;
  log-prefix string;
  match "regular-expression";
}
```



NOTE: You can also include the **facility-override** statement at the `[edit system syslog host scc-master]` hierarchy level, but we do not recommend doing so. It is not necessary to use alternative facilities for messages forwarded to the TX Matrix platform, because it runs the Junos system logging utility and can interpret the Junos-specific facilities. For more information about alternative facilities, see [“Changing the Alternative Facility Name for System Log Messages Directed to a Remote Destination”](#) on page 15.

1. [Including Priority Information in Forwarded Messages on page 36](#)
2. [Adding a Text String to Forwarded Messages on page 37](#)
3. [Using Regular Expressions to Refine the Set of Forwarded Messages on page 37](#)

Including Priority Information in Forwarded Messages

When you include the **explicit-priority** statement at the `[edit system syslog host scc-master]` hierarchy level, messages forwarded to the TX Matrix platform include priority information. For the information to appear in a log file on the TX Matrix platform, you must also include the **explicit-priority** statement at the `[edit system syslog file filename]` hierarchy level for the file on the TX Matrix platform. As a consequence, the log file with the same name on each platform in the routing matrix also includes priority information for locally generated messages.

To include priority information in messages directed to a remote machine from all platforms in the routing matrix, also include the **explicit-priority** statement at the `[edit system syslog host hostname]` hierarchy level for the remote machine. For more information, see [Directing Messages to a Remote Destination from the Routing Matrix Based on a TX Matrix Plus Router](#).

In the following example, the `/var/log/messages` file on all platforms includes priority information for messages with severity **notice** and higher from all facilities. The log on the TX Matrix platform also includes messages with those characteristics forwarded from the T640 routing nodes.


```
[edit system syslog]
host scc-master {
  any notice;
  explicit-priority;
}
file messages {
  any notice;
  explicit-priority;
}
```

Adding a Text String to Forwarded Messages

When you include the **log-prefix** statement at the `[edit system syslog host scc-master]` hierarchy level, the string that you define appears in every message forwarded to the TX Matrix platform. For more information, see [“Adding a Text String to System Log Messages Directed to a Remote Destination”](#) on page 19.

Using Regular Expressions to Refine the Set of Forwarded Messages

When you include the **match** statement at the `[edit system syslog host scc-master]` hierarchy level, the regular expression that you specify controls which messages from the T640 routing nodes are forwarded to the TX Matrix platform. The regular expression is not applied to messages from the T640 routing nodes that are directed to destinations other than the TX Matrix platform. For more information about regular expression matching, see [“Using Regular Expressions to Refine the Set of Logged Messages”](#) on page 25.

Directing Messages to a Remote Destination from the Routing Matrix Based on the TX Matrix Router

You can configure a routing matrix composed of a TX Matrix router and T640 routers to direct system logging messages to a remote machine or the other Routing Engine on each router, just as on a single-chassis system. Include the **host** statement at the `[edit system syslog]` hierarchy level on the TX Matrix router:

```
[edit system syslog]
host (hostname | other-routing-engine) {
  facility severity;
  explicit-priority;
  facility-override facility;
  log-prefix string;
  match "regular-expression";
}
source-address source-address;
```

The TX Matrix router directs messages to a remote machine or the other Routing Engine in the same way as a single-chassis system, and the optional statements (**explicit-priority**, **facility-override**, **log-prefix**, **match**, and **source-address**) also have the same effect as on a single-chassis system. For more information, see *Directing System Log Messages to a Remote Machine or the Other Routing Engine*.

For the TX Matrix router to include priority information when it directs messages that originated on a T640 router to the remote destination, you must also include the **explicit-priority** statement at the `[edit system syslog host scc-master]` hierarchy level.

The **other-routing-engine** statement does not interact with message forwarding from the T640 routers to the TX Matrix router. For example, if you include the statement in the configuration for the Routing Engine in slot 0 (**re0**), the **re0** Routing Engine on each T640 router sends messages to the **re1** Routing Engine on its platform only. It does not also send messages directly to the **re1** Routing Engine on the TX Matrix router.

Because the configuration on the TX Matrix router applies to the T640 routers, any T640 router that has interfaces for direct access to the Internet also directs messages to the remote machine. The consequences include the following:

- If the T640 routers are configured to forward messages to the TX Matrix router (as in the default configuration), the remote machine receives two copies of some messages: one directly from the T640 router and the other from the TX Matrix router. Which messages are duplicated depends on whether the severities are the same for local logging and for forwarded messages. For more information, see *Configuring Message Forwarding to the TX Matrix Router*.
- If the **source-address** statement is configured at the **[edit system syslog]** hierarchy level, all routers in the routing matrix report the same source address in messages directed to the remote machine. This is appropriate, because the routing matrix functions as a single router.
- If the **log-prefix** statement is included, the messages from all routers in the routing matrix include the same text string. You cannot use the string to distinguish between the routers in the routing matrix.

**Related
Documentation**

- *Configuring System Logging for a TX Matrix Router*

Configuring System Logging Differently on Each T640 Router in a Routing Matrix

We recommend that all routers in a routing matrix composed of a TX Matrix router and T640 routers use the same configuration, which implies that you include system logging configuration statements on the TX Matrix router only. In rare circumstances, however, you might choose to log different messages on different routers. For example, if one router in the routing matrix is experiencing problems with authentication, a Juniper Networks support representative might instruct you to log messages from the **authorization** facility with severity **debug** on that router.

To configure routers separately, include configuration statements in the appropriate groups at the **[edit groups]** hierarchy level on the TX Matrix router:

- To configure settings that apply to the TX Matrix router but not the T640 routers, include them in the **re0** and **re1** configuration groups.
- To configure settings that apply to particular T640 routers, include them in the **lccn-re0** and **lccn-re1** configuration groups, where **n** is the line-card chassis (LCC) index number of the router.

When you use configuration groups, do not issue CLI configuration-mode commands to change statements at the **[edit system syslog]** hierarchy level on the TX Matrix router. If you do, the resulting statements overwrite the statements defined in configuration groups

and apply to the T640 routers also. (We further recommend that you do not issue CLI configuration-mode commands on the T640 routers at any time.)

The following example shows how to configure the `/var/log/messages` files on three routers to include different sets of messages:

- On the TX Matrix router, local messages with severity **info** and higher from all facilities. The file does not include messages from the T640 routers, because the **host scc-master** statement disables message forwarding.
- On the T640 router designated **LCC0**, messages from the **authorization** facility with severity **info** and higher.
- On the T640 router designated **LCC1**, messages with severity **notice** from all facilities.

```
[edit groups]
re0 {
  system {
    syslog {
      file messages {
        any info;
      }
      host scc-master {
        any none;
      }
    }
  }
}
re1 {
  ... same statements as for re0 ...
}
lcc0-re0 {
  system {
    syslog {
      file messages {
        authorization info;
      }
    }
  }
}
lcc0-re1 {
  ... same statements as for lcc0-re0 ...
}
lcc1-re0 {
  system {
    syslog {
      file messages {
        any notice;
      }
    }
  }
}
lcc1-re1 {
  ... same statements as for lcc1-re0 ...
}
```

- Related Documentation**
- [Configuring System Logging for a TX Matrix Router](#)

Configuring System Logging for a TX Matrix Plus Router

From the perspective of the user interface, the routing matrix appears as a single router. The TX Matrix Plus router (also called the switch-fabric chassis SFC) controls all the T1600 or T4000 routers (also called the line-card chassis LCC) in the routing matrix.

To configure system logging for all routers in a routing matrix composed of a TX Matrix Plus router with connected T1600 or T4000 LCCs, include the **syslog** statement at the **[edit system]** hierarchy level on the SFC. The **syslog** statement applies to every router in the routing matrix.

```
[edit system]
syslog {
  archive <files number> <size size> <world-readable | no-world-readable>;
  console {
    facility severity;
  }
  file filename {
    facility severity;
    archive <archive-sites {ftp-url <password password>}> <files number> <size size>
      <start-time "YYYY-MM-DD.hh:mm"> <transfer-interval minutes> <world-readable |
        no-world-readable>;
    explicit-priority;
    match "regular-expression";
    structured-data {
      brief;
    }
  }
  host (hostname | other-routing-engine | sfc0-master) {
    facility severity;
    explicit-priority;
    facility-override facility;
    log-prefix string;
    match "regular-expression";
  }
  source-address source-address;
  time-format (year | millisecond | year millisecond);
  (username | *) {
    facility severity;
    match "regular-expression";
  }
}
```

When included in the configuration on the TX Matrix Plus router, the following configuration statements have the same effect as on a single-chassis system, except that they apply to every router in the routing matrix.

- **archive**—Sets the size and number of log files on each router in the routing matrix. See [“Specifying Log File Size, Number, and Archiving Properties” on page 20](#).
- **console**—Directs the specified messages to the console of each router in the routing matrix. See [“Directing System Log Messages to the Console” on page 13](#).

- **file**—Directs the specified messages to a file of the same name on each router in the routing matrix. See [“Directing System Log Messages to a Log File” on page 11](#).
- **match**—Limits the set of messages logged to a destination to those that contain (or do not contain) a text string matching a regular expression. See [“Using Regular Expressions to Refine the Set of Logged Messages” on page 25](#).

The separate **match** statement at the **[edit system syslog host sfc0-master]** hierarchy level applies to messages forwarded from the T1600 or T4000 LCCs to the SFC. See [“Configuring Optional Features for Forwarded Messages on a TX Matrix Plus Router” on page 45](#).

- **source-address**—Sets the IP address of the router as the message source in system log messages when the messages are directed to the remote machines specified in all **host hostname** statements at the **[edit system syslog]** hierarchy level, for each router in the routing matrix. On a routing matrix composed of a TX Matrix Plus router with connected T1600 or T4000 LCCs, the address is not reported by the T1600 or T4000 routers in messages directed to the other Routing Engine on each router or to the TX Matrix Plus router. See [“Specifying an Alternative Source Address for System Log Messages Directed to a Remote Destination” on page 15](#).
- **structured-data**—Writes messages to a file in structured-data format. See [“Logging Messages in Structured-Data Format” on page 12](#).
- **time-format**—Adds the millisecond, year, or both to the timestamp in each standard-format message. See [“Including the Year or Millisecond in Timestamps” on page 25](#).
- **user**—Directs the specified messages to the terminal session of one or more specified users on each router in the routing matrix that they are logged in to. See [“Directing System Log Messages to a User Terminal” on page 13](#).

The effect of the other statements differs somewhat for a routing matrix than for a single-chassis system.

Related Documentation

- [Configuring Message Forwarding to the TX Matrix Plus Router on page 42](#)
- [Impact of Different Local and Forwarded Severity Levels on System Log Messages on a TX Matrix Plus Router on page 43](#)
- [Configuring Optional Features for Forwarded Messages on a TX Matrix Plus Router on page 45](#)
- [Directing Messages to a Remote Destination from the Routing Matrix Based on a TX Matrix Plus Router on page 46](#)
- [Configuring System Logging Differently on Each T1600 or T4000 Router in a Routing Matrix on page 47](#)
- [Routing Matrix with a TX Matrix Plus Router Solutions Page](#)

Configuring Message Forwarding to the TX Matrix Plus Router

From the perspective of the user interface, the routing matrix appears as a single router. The TX Matrix Plus router (also called the switch-fabric chassis SFC) controls all the T1600 or T4000 routers (also called the line-card chassis LCC) in the routing matrix.

By default, the master Routing Engine on each connected T1600 or T4000 LCC forwards to the master Routing Engine on the SFC all messages from all facilities with severity level of **info** and higher. To change the facility, the severity level, or both, include the **host sfc0-master** statement at the **[edit system syslog]** hierarchy level on the SFC:

```
[edit system syslog]
host sfc0-master {
  facility severity;
}
```

To disable message forwarding, set the facility to **any** and the severity level to **none**:

```
[edit system syslog]
host sfc0-master {
  any none;
}
```

In either case, the setting applies to all connected LCCs in the routing matrix.

To capture the messages forwarded by the T1600 or T4000 LCCs (as well as messages generated on the SFC itself), you must also configure system logging on the SFC. Direct the messages to one or more destinations by including the appropriate statements at the **[edit system syslog]** hierarchy level on the SFC:

- To a file, as described in [“Directing System Log Messages to a Log File” on page 11](#).
- To the terminal session of one or more specific users (or all users), as described in [“Directing System Log Messages to a User Terminal” on page 13](#).
- To the console, as described in [“Directing System Log Messages to the Console” on page 13](#).
- To a remote machine that is running the syslogd utility or to the other Routing Engine. For more information, see [“Directing Messages to a Remote Destination from the Routing Matrix Based on a TX Matrix Plus Router” on page 46](#).

As previously noted, the configuration statements included on the SFC also configure the same destinations on each connected LCC.

When specifying the severity level for local messages (at the **[edit system syslog (file | host | console | user)]** hierarchy level) and forwarded messages (at the **[edit system syslog host sfc0-master]** hierarchy level), you can set the same severity level for both, set a lower severity level for local messages, or set a higher severity level for local messages. The following examples describe the consequence of each configuration. (For simplicity, the examples use the **any** facility in every case. You can also specify different severities for different facilities, with more complex consequences.)

- Related Documentation
- [Configuring System Logging for a TX Matrix Plus Router on page 40](#)
 - [Routing Matrix with a TX Matrix Plus Router Solutions Page](#)

Impact of Different Local and Forwarded Severity Levels on System Log Messages on a TX Matrix Plus Router

This topic describes the impact of different local and forwarded severity levels configured for the system log messages on a TX Matrix Plus router:

- [Messages Logged When the Local and Forwarded Severity Levels Are the Same on page 43](#)
- [Messages Logged When the Local Severity Level Is Lower on page 43](#)
- [Messages Logged When the Local Severity Level Is Higher on page 44](#)

Messages Logged When the Local and Forwarded Severity Levels Are the Same

When the severity level is the same for local and forwarded messages, the log on the TX Matrix Plus router contains all messages from the logs on the T1600 routers in the routing matrix. For example, you can specify severity **info** for the `/var/log/messages` file, which is the default severity level for messages forwarded by T1600 routers:

```
[edit system syslog]
file messages {
  any info;
}
```

[Table 16 on page 43](#) specifies which messages in a routing matrix based on a TX Matrix Plus router are included in the logs on the T1600 routers and the TX Matrix Plus router:

Table 16: Example: Local and Forwarded Severity Level Are Both info

Log Location	Source of Messages	Lowest Severity Included
T1600 router	Local	info
TX Matrix Plus router	Local	info
	Forwarded from T1600 routers	info

Messages Logged When the Local Severity Level Is Lower

When the severity level is lower for local messages than for forwarded messages, the log on the TX Matrix Plus router includes fewer forwarded messages than when the severities are the same. Locally generated messages are still logged at the lower severity level, so their number in each log is the same as when the severities are the same.

For example, on a TX Matrix Plus router, you can specify severity **notice** for the `/var/log/messages` file and severity **critical** for forwarded messages:

```
[edit system syslog]
file messages {
```

```

    any notice;
  }
  host sfc0-master {
    any critical;
  }

```

Table 17 on page 44 specifies which messages in a routing matrix are included in the logs on the T1600 routers and the TX Matrix Plus router. The T1600 routers forward only those messages with severity **critical** and higher, so the log on the TX Matrix Plus router does not include the messages with severity **error**, **warning**, or **notice** that the T1600 routers log locally.

Table 17: Example: Local Severity Is notice, Forwarded Severity Is critical

Log Location	Source of Messages	Lowest Severity Included
T1600 router	Local	notice
TX Matrix Plus router	Local	notice
	Forwarded from T1600 routers	critical

Messages Logged When the Local Severity Level Is Higher

When the severity level is higher for local messages than for forwarded messages, the log on the TX Matrix Plus router includes fewer forwarded messages than when the severities are the same, and all local logs contain fewer messages overall.

For example, you can specify severity **critical** for the `/var/log/messages` file and severity **notice** for forwarded messages:

```

[edit system syslog]
file messages {
  any critical;
}
host sfc0-master {
  any notice;
}

```

Table 18 on page 44 specifies which messages are included in the logs on the T1600 routers and the TX Matrix Plus router. Although the T1600 routers forward messages with severity **notice** and higher, the TX Matrix Plus router discards any of those messages with severity lower than **critical** (does not log forwarded messages with severity **error**, **warning**, or **notice**). None of the logs include messages with severity **error** or lower.

Table 18: Example: Local Severity Is critical, Forwarded Severity Is notice

Log Location	Source of Messages	Lowest Severity Included
T1600 router	Local	critical
TX Matrix Plus router	Local	critical
	Forwarded from T1600 routers	critical

- Related Documentation**
- [Configuring System Logging for a TX Matrix Plus Router on page 40](#)

Configuring Optional Features for Forwarded Messages on a TX Matrix Plus Router

From the perspective of the user interface, the routing matrix appears as a single router. The TX Matrix Plus router (also called the switch-fabric chassis SFC) controls all the T1600 or T4000 routers (also called the line-card chassis LCC) in the routing matrix.

To configure additional optional features when specifying how the connected T1600 or T4000 LCCs forward messages to the SFC, include statements at the **[edit system syslog host sfc0-master]** hierarchy level. To include priority information (facility and severity level) in each forwarded message, include the **explicit-priority** statement. To insert a text string in each forwarded message, include the **log-prefix** statement. To use regular expression matching to specify more exactly which messages from a facility are forwarded, include the **match** statement.

```
[edit system syslog]
host sfc0-master {
    facility severity;
    explicit-priority;
    log-prefix string;
    match "regular-expression;
}
```

You can also include the **facility-override** statement at the **[edit system syslog host sfc0-master]** hierarchy level, but we do not recommend doing so. It is not necessary to use alternative facilities for messages forwarded to the SFC, because it runs the Junos system logging utility and can interpret the Junos OS-specific facilities. For more information about alternative facilities, see [“Changing the Alternative Facility Name for System Log Messages Directed to a Remote Destination” on page 15](#).

1. [Including Priority Information in Forwarded Messages on page 45](#)
2. [Adding a Text String to Forwarded Messages on page 46](#)
3. [Using Regular Expressions to Refine the Set of Forwarded Messages on page 46](#)

Including Priority Information in Forwarded Messages

When you include the **explicit-priority** statement at the **[edit system syslog host sfc0-master]** hierarchy level, messages forwarded to the TX Matrix Plus router (or the SFC) include priority information. For the information to appear in a log file on the SFC, you must also include the **explicit-priority** statement at the **[edit system syslog file filename]** hierarchy level for the file on the SFC. As a consequence, the log file with the same name on each platform in the routing matrix also includes priority information for locally generated messages.

To include priority information in messages directed to a remote machine from all routers in the routing matrix, also include the **explicit-priority** statement at the **[edit system syslog host hostname]** hierarchy level for the remote machine. For more information, see [“Directing Messages to a Remote Destination from the Routing Matrix Based on a TX Matrix Plus Router” on page 46](#).

In the following example, the `/var/log/messages` file on all routers includes priority information for messages with severity **notice** and higher from all facilities. The log on the TX Matrix Plus router SFC also includes messages with those characteristics forwarded from the connected T1600 or T4000 LCCs.

```
[edit system syslog]
host sfc0-master {
  any notice;
  explicit-priority;
}
file messages {
  any notice;
  explicit-priority;
}
```

Adding a Text String to Forwarded Messages

When you include the **log-prefix** statement at the `[edit system syslog host sfc0-master]` hierarchy level, the string that you define appears in every message forwarded to the TX Matrix Plus router. For more information, see [“Adding a Text String to System Log Messages Directed to a Remote Destination”](#) on page 19.

Using Regular Expressions to Refine the Set of Forwarded Messages

When you include the **match** statement at the `[edit system syslog host sfc0-master]` hierarchy level, the regular expression that you specify controls which messages from the connected T1600 or T4000 LCCs are forwarded to the TX Matrix Plus SFC. The regular expression is not applied to messages from the connected LCCs that are directed to destinations other than the SFC. For more information about regular expression matching, see [“Using Regular Expressions to Refine the Set of Logged Messages”](#) on page 25.

Directing Messages to a Remote Destination from the Routing Matrix Based on a TX Matrix Plus Router

From the perspective of the user interface, the routing matrix appears as a single router. The TX Matrix Plus router (also called the switch-fabric chassis SFC) controls all the T1600 or T4000 routers also called the line-card chassis LCC) in the routing matrix.

You can configure a routing matrix composed of a TX Matrix Plus router with connected T1600 or T4000 LCCs to direct system logging messages to a remote machine or the other Routing Engine on each routing router, just as on a single-chassis system. Include the **host** statement at the `[edit system syslog]` hierarchy level on the SFC:

```
[edit system syslog]
host (hostname | other-routing-engine) {
  facility severity;
  explicit-priority;
  facility-override facility;
  log-prefix string;
  match "regular-expression";
}
source-address source-address;
```

The TX Matrix Plus router directs messages to a remote machine or the other Routing Engine in the same way as a single-chassis system, and the optional statements (**explicit-priority**, **facility-override**, **log-prefix**, **match**, and **source-address**) also have the same effect as on a single-chassis system. For more information, see *Directing System Log Messages to a Remote Machine or the Other Routing Engine*.

For the TX Matrix Plus router to include priority information when it directs messages that originated on a connected T1600 or T4000 LCC to the remote destination, you must also include the **explicit-priority** statement at the **[edit system syslog host sfc0-master]** hierarchy level.

The **other-routing-engine** statement does not interact with message forwarding from the connected T1600 or T4000 LCCs to the SFC. For example, if you include the statement in the configuration for the Routing Engine in slot 0 (**re0**), the **re0** Routing Engine on each connected T1600 or T4000 LCC sends messages to the **re1** Routing Engine on its router only. It does not also send messages directly to the **re1** Routing Engine on the SFC.

Because the configuration on the SFC applies to the connected T1600 or T4000 LCCs, any LCC that has interfaces for direct access to the Internet also directs messages to the remote machine. The consequences include the following:

- If the LCCs are configured to forward messages to the SFC (as in the default configuration), the remote machine receives two copies of some messages: one directly from the T1600 or T4000 LCC and the other from the SFC. Which messages are duplicated depends on whether the severities are the same for local logging and for forwarded messages. For more information, see [“Configuring Message Forwarding to the TX Matrix Plus Router” on page 42](#).
- If the **source-address** statement is configured at the **[edit system syslog]** hierarchy level, all routers in the routing matrix report the same source address in messages directed to the remote machine. This is appropriate, because the routing matrix functions as a single routing router.
- If the **log-prefix** statement is included, the messages from all routers in the routing matrix include the same text string. You cannot use the string to distinguish between the routers in the routing matrix.

Related Documentation

- [Configuring System Logging for a TX Matrix Plus Router on page 40](#)
- [Routing Matrix with a TX Matrix Plus Router Solutions Page](#)

Configuring System Logging Differently on Each T1600 or T4000 Router in a Routing Matrix

We recommend that all routers in a routing matrix composed of a TX Matrix Plus router with T1600 or T4000 routers use the same configuration, which implies that you include system logging configuration statements on the TX Matrix Plus router only. In rare circumstances, however, you might choose to log different messages on different routers. For example, if one router in the routing matrix is experiencing problems with authentication, a Juniper Networks support representative might instruct you to log messages from the **authorization** facility with severity **debug** on that router.

To configure routers separately, include configuration statements in the appropriate groups at the **[edit groups]** hierarchy level on the TX Matrix Plus router:

- To configure settings that apply to the TX Matrix Plus router but not the T1600 or T4000 routers, include them in the **re0** and **re1** configuration groups.
- To configure settings that apply to particular T1600 or T4000 routers, include them in the **lccn-re0** and **lccn-re1** configuration groups, where **n** is the line-card chassis (LCC) index number of the router.

When you use configuration groups, do not issue CLI configuration-mode commands to change statements at the **[edit system syslog]** hierarchy level on the TX Matrix Plus router. If you do, the resulting statements overwrite the statements defined in configuration groups and apply to the T1600 or T4000 routers also. (We further recommend that you do not issue CLI configuration-mode commands on the T1600 or T4000 routers at any time.)

For more information about the configuration groups for a routing matrix, see the chapter about configuration groups in the *CLI User Guide*.

The following example shows how to configure the **/var/log/messages** files on three routers to include different sets of messages:

- On the TX Matrix Plus router, local messages with severity **info** and higher from all facilities. The file does not include messages from the T1600 or T4000 routers, because the **host sfc0-master** statement disables message forwarding.
- On the T1600 or T4000 router designated **LCC0**, messages from the **authorization** facility with severity **info** and higher.
- On the T1600 or T4000 router designated **LCC1**, messages with severity **notice** from all facilities.

```
[edit groups]
re0 {
  system {
    syslog {
      file messages {
        any info;
      }
      host sfc0-master {
        any none;
      }
    }
  }
}
re1 {
  ... same statements as for re0 ...
}
lcc0-re0 {
  system {
    syslog {
      file messages {
        authorization info;
      }
    }
  }
}
```

```

    }
  }
}
lcc0-re1 {
  ... same statements as for lcc0-re0 ...
}
lcc1-re0 {
  system {
    syslog {
      file messages {
        any notice;
      }
    }
  }
}
lcc0-re1 {
  ... same statements as for lcc1-re0 ...
}

```

- Related Documentation**
- [Configuring System Logging for a TX Matrix Plus Router on page 40](#)
 - [Routing Matrix with a TX Matrix Plus Router Solutions Page](#)

Displaying and Interpreting System Log Messages

This section explains how to display a log file and interpret the contents of system log messages:

For more information about the commands discussed in this section, see the [CLI Explorer](#).

- [Displaying a Log File from a Single-Chassis System on page 49](#)
- [Displaying a Log File from a Routing Matrix on page 50](#)
- [Interpreting System Log Messages on page 50](#)
- [Format of the message-source Field on page 57](#)
- [Examples: Displaying a Log File on page 59](#)

Displaying a Log File from a Single-Chassis System

To display a log file stored on a single-chassis system, enter Junos OS CLI operational mode and issue either of the following commands:

```

user@host> show log log-filename
user@host> file show log-file-pathname

```

By default, the commands display the file stored on the local Routing Engine. To display the file stored on a particular Routing Engine, prefix the file or pathname with the string **re0** or **re1** and a colon. The following examples both display the `/var/log/messages` file stored on the Routing Engine in slot 1:

```

user@host> show log re1:messages
user@host> file show re1:/var/log/messages

```

For information about the fields in a log message, see [“Interpreting Messages Generated in Standard Format by a Junos OS Process or Library” on page 55](#), [“Interpreting Messages Generated in Standard Format by Services on a PIC” on page 56](#), and [“Interpreting Messages Generated in Structured-Data Format” on page 51](#). For examples, see [“Examples: Displaying a Log File” on page 59](#).

Displaying a Log File from a Routing Matrix

One way to display a log file stored on the local Routing Engine of any of the individual platforms in a routing matrix (T640 routing nodes or TX Matrix platform) is to log in to a Routing Engine on the platform, enter Junos OS CLI operational mode, and issue the **show log** or **file show** command described in [“Displaying a Log File from a Single-Chassis System” on page 49](#).

To display a log file stored on a T640 routing node during a terminal session on the TX Matrix platform, issue the **show log** or **file show** command and add a prefix that specifies the T640 routing node's LCC index number as **lccn**, followed by a colon. The index can be from 0 (zero) through 3:

```
user@host> show log lccn:log-filename
user@host> file show lccn:log-file-pathname
```

By default, the **show log** and **file show** commands display the specified log file stored on the master Routing Engine on the T640 routing node. To display the log from a particular Routing Engine, prefix the file- or pathname with the string **lccn-master**, **lccn-re0**, or **lccn-re1**, followed by a colon. The following examples all display the **/var/log/messages** file stored on the master Routing Engine (in slot 0) on routing node LCC2:

```
user@host> show log lcc2:messages
user@host> show log lcc2-master:messages
user@host> show log lcc2-re0:messages
user@host> file show lcc2:/var/log/messages
```

If the T640 routing nodes are forwarding messages to the TX Matrix platform (as in the default configuration), another way to view messages generated on a T640 routing node during a terminal session on the TX Matrix platform is simply to display a local log file. However, the messages are intermixed with messages from other T640 routing nodes and the TX Matrix platform itself. For more information about message forwarding, see [“Impact of Different Local and Forwarded Severity Levels on System Log Messages on a TX Matrix Router” on page 34](#).

For information about the fields in a log message, see [“Interpreting Messages Generated in Structured-Data Format” on page 51](#), [“Interpreting Messages Generated in Standard Format by Services on a PIC” on page 56](#), and [“Interpreting Messages Generated in Standard Format by a Junos OS Process or Library” on page 55](#). For examples, see [“Examples: Displaying a Log File” on page 59](#).

Interpreting System Log Messages

The fields in a message written to the system log depend on whether the message was generated by a Junos OS process or subroutine library, or by services on a PIC, and whether

it is in standard format or structured-data format. For more information, see the following sections:

- [Interpreting Messages Generated in Structured-Data Format on page 51](#)
- [Interpreting Messages Generated in Standard Format by a Junos OS Process or Library on page 55](#)
- [Interpreting Messages Generated in Standard Format by Services on a PIC on page 56](#)

Interpreting Messages Generated in Structured-Data Format

Beginning in Junos OS Release 8.3, when the **structured-data** statement is included in the configuration for a log file, Junos OS processes and software libraries write messages to the file in structured-data format instead of the standard Junos format. For information about the **structured-data** statement, see “[Logging Messages in Structured-Data Format](#)” on page 12.

Structured-format makes it easier for automated applications to extract information from the message. In particular, the standardized format for reporting the value of variables (elements in the English-language message that vary depending on the circumstances that triggered the message) makes it easy for an application to extract those values. In standard format, the variables are interspersed in the message text and not identified as variables.

The structured-data format for a message includes the following fields (which appear here on two lines only for legibility):

```
<priority code>version timestamp hostname process processID TAG [[junos@2636.platform  
variable-value-pairs] message-text
```

[Table 19 on page 51](#) describes the fields. If the system logging utility cannot determine the value in a particular field, a hyphen (-) appears instead.

Table 19: Fields in Structured-Data Messages

Field	Description	Examples
<priority code>	Number that indicates the message's facility and severity. It is calculated by multiplying the facility number by 8 and then adding the numerical value of the severity. For a mapping of the numerical codes to facility and severity, see “ Specifying the Facility and Severity of Messages to Include in the Log ” on page 9.	<165> for a message from the pfe facility (facility=20) with severity notice (severity=5).
version	Version of the Internet Engineering Task Force (IETF) system logging protocol specification.	1 for the initial version

Table 19: Fields in Structured-Data Messages (*continued*)

Field	Description	Examples
<i>timestamp</i>	Time when the message was generated, in one of two representations: <ul style="list-style-type: none"> YYYY-MM-DDTHH:MM:SS.MSZ is the year, month, day, hour, minute, second and millisecond in Universal Coordinated Time (UTC) YYYY-MM-DDTHH:MM:SS.MS+/-HH:MM is the year, month, day, hour, minute, second and millisecond in local time; the hour and minute that follows the plus sign (+) or minus sign (-) is the offset of the local time zone from UTC 	2007-02-15T09:17:15.719Z is 9:17 AM UTC on 15 February 2007. 2007-02-15T01:17:15.719-08:00 is the same timestamp expressed as Pacific Standard Time in the United States.
<i>hostname</i>	Name of the host that originally generated the message.	router1
<i>process</i>	Name of the Junos OS process that generated the message.	mgd
<i>processID</i>	UNIX process ID (PID) of the Junos OS process that generated the message.	3046
<i>TAG</i>	Junos OS system log message tag, which uniquely identifies the message.	UI_DBASE_LOGOUT_EVENT
<i>junos@2636.platform</i>	An identifier for the type of hardware platform that generated the message. The <i>junos@2636</i> prefix indicates that the platform runs Junos OS. It is followed by a dot-separated numerical identifier for the platform type. For a list of the identifiers, see Table 21 on page 54 .	junos@2636.1.1.2.18 for the M120 router
<i>variable-value-pairs</i>	A variable-value pair for each element in the <i>message-text</i> string that varies depending on the circumstances that triggered the message. Each pair appears in the format variable = "value" .	username="regress"
<i>message-text</i>	English-language description of the event or error (omitted if the brief statement is included at the [edit system syslog file filename structured-data] hierarchy level). For the text for each message, see the chapters following System Log Messages.	User 'regress' exiting configuration mode

By default, the structured-data version of a message includes English text at the end, as in the following example (which appears on multiple lines only for legibility):


```
<165>1 2007-02-15T09:17:15.719Z router1 mgd 3046 UI_DBASE_LOGOUT_EVENT
[junos@2636.1.1.1.2.18 username="regress"] User 'regress' exiting configuration mode
```

When the brief statement is included at the `[edit system syslog file filename structured-data]` hierarchy level, the English text is omitted, as in this example:

```
<165>1 2007-02-15T09:17:15.719Z router1 mgd 3046 UI_DBASE_LOGOUT_EVENT
[junos@2636.1.1.1.2.18 username="regress"]
```

[Table 20 on page 53](#) maps the codes that appear in the **priority-code** field to facility and severity level.



NOTE: Not all of the facilities and severities listed in [Table 20 on page 53](#) can be included in statements at the `[edit system syslog]` hierarchy level (some are used by internal processes). For a list of the facilities and severity levels that can be included in the configuration, see “[Specifying the Facility and Severity of Messages to Include in the Log](#)” on page 9.

Table 20: Facility and Severity Codes in the priority-code Field

Facility (number)	Severity emergency	alert	critical	error	warning	notice	info	debug
kernel (0)	1	1	2	3	4	5	6	7
user (1)	8	9	10	11	12	13	14	15
mail (2)	16	17	18	19	20	21	22	23
daemon (3)	24	25	26	27	28	29	30	31
authorization (4)	32	33	34	35	36	37	38	39
syslog (5)	40	41	42	43	44	45	46	47
printer (6)	48	49	50	51	52	53	54	55
news (7)	56	57	58	59	60	61	62	63
uucp (8)	64	65	66	67	68	69	70	71
clock (9)	72	73	74	75	76	77	78	79
authorization-private (10)	80	81	82	83	84	85	86	87
ftp (11)	88	89	90	91	92	93	94	95
ntp (12)	96	97	98	99	100	101	102	103
security (13)	104	105	106	107	108	109	110	111

Table 20: Facility and Severity Codes in the priority-code Field (*continued*)

Facility (number)	Severity emergency	alert	critical	error	warning	notice	info	debug
console (14)	112	113	114	115	116	117	118	119
local0 (16)	128	129	130	131	132	133	134	135
dfc (17)	136	137	138	139	140	141	142	143
local2 (18)	144	145	146	147	148	149	150	151
firewall (19)	152	153	154	155	156	157	158	159
pfe (20)	160	161	162	163	164	165	166	167
conflict-log (21)	168	169	170	171	172	173	174	175
change-log (22)	176	177	178	179	180	181	182	183
interactive-commands (23)	184	185	186	187	188	189	190	191

Table 21 on page 54 lists the numerical identifiers for routing platforms that appear in the **platform** field. The identifier is derived from the platform's SNMP object identifier (OID) as defined in the Juniper Networks routing platform MIB. For more information about OIDs, see the *Network Management Administration Guide for Routing Devices*.

Table 21: Platform Identifiers in the platform Field

Identifier	Platform Name
1.1.1.2.1	M40 router
1.1.1.2.2	M20 router
1.1.1.2.3	M160 router
1.1.1.2.4	M10 router
1.1.1.2.5	M5 router
1.1.1.2.6	T640 routing node
1.1.1.2.7	T320 router
1.1.1.2.8	M40e router
1.1.1.2.9	M320 router
1.1.1.2.10	M7i router

Table 21: Platform Identifiers in the platform Field (*continued*)

Identifier	Platform Name
1.1.1.2.11	M10i router
1.1.1.2.17	TX Matrix platform
1.1.1.2.18	M120 router
1.1.1.2.27	T1600 router
1.1.1.2.37	TX Matrix Plus platform
1.1.1.2.83	T4000 router

Interpreting Messages Generated in Standard Format by a Junos OS Process or Library

The syntax of a standard-format message generated by a Junos OS process or subroutine library depends on whether it includes priority information:

- When the **explicit-priority** statement is included at the `[edit system syslog file filename]` or `[edit system syslog host (hostname | other-routing-engine)]` hierarchy level, a system log message has the following syntax:

```
timestamp message-source: %facility-severity-TAG: message-text
```

- When directed to the console or to users, or when the **explicit-priority** statement is not included for files or remote hosts, a system log message has the following syntax:

```
timestamp message-source: TAG: message-text
```

Table 22 on page 55 describes the message fields.

Table 22: Fields in Standard-Format Messages Generated by a Junos OS process or Library

Field	Description
<i>timestamp</i>	Time at which the message was logged.
<i>message-source</i>	Identifier of the process or component that generated the message and the routing platform on which the message was logged. This field includes two or more subfields, depending on how system logging is configured. See “The message-source Field on a TX Matrix Platform” on page 58 , The message-source Field on a T640 Routing Node in a Routing Matrix , and “The message-source Field on a Single-Chassis System” on page 57 .
<i>facility</i>	Code that specifies the facility to which the system log message belongs. For a mapping of codes to facility names, see Table: Numerical Codes for Severity Levels Reported in Priority Information in “Including Priority Information in System Log Messages” on page 22 .

Table 22: Fields in Standard-Format Messages Generated by a Junos OS process or Library (*continued*)

Field	Description
severity	Numerical code that represents the severity level assigned to the system log message. For a mapping of codes to severity names, see Table: <i>Numerical Codes for Severity Levels Reported in Priority Information</i> in "Including Priority Information in System Log Messages" on page 22.
TAG	Text string that uniquely identifies the message, in all uppercase letters and using the underscore (_) to separate words. The tag name begins with a prefix that indicates the generating software process or library. The entries in this reference are ordered alphabetically by this prefix. Not all processes on a routing platform use tags, so this field does not always appear.
message-text	Text of the message. For the text for each message, see the chapters following System Log Messages.

Interpreting Messages Generated in Standard Format by Services on a PIC

Standard-format system log messages generated by services on a PIC, such as the Adaptive Services (AS) PIC, have the following syntax:

```
timestamp (FPC Slot fpc-slot, PIC Slot pic-slot) {service-set} [SERVICE]:
optional-string TAG: message-text
```



NOTE: System logging for services on PICs is not configured at the [edit system syslog] hierarchy level as discussed in this chapter. For configuration information, see the *Junos Services Interfaces Configuration Guide*.

The (FPC Slot *fpc-slot*, PIC Slot *pic-slot*) field appears only when the standard system logging utility that runs on the Routing Engine writes the messages to the system log. When the PIC writes the message directly, the field does not appear.

Table 23 on page 56 describes the message fields.

Table 23: Fields in Messages Generated by a PIC

Field	Description
timestamp	Time at which the message was logged.
fpc-slot	Slot number of the Flexible PIC Concentrator (FPC) that houses the PIC that generated the message.
pic-slot	Number of the PIC slot on the FPC in which the PIC that generated the message resides.
service-set	Name of the service set that generated the message.

Table 23: Fields in Messages Generated by a PIC (*continued*)

Field	Description
SERVICE	Code representing the service that generated the message. The codes include the following: <ul style="list-style-type: none"> • FWNAT—Network Address Translation (NAT) service • IDS—Intrusion detection service
optional-string	A text string that appears if the configuration for the PIC includes the log-prefix statement at the [edit interfaces interface-name services-options syslog] hierarchy level. For more information, see the <i>Junos Services Interfaces Configuration Guide</i> .
TAG	Text string that uniquely identifies the message, in all uppercase letters and using the underscore (_) to separate words. The tag name begins with a prefix that indicates the generating PIC. The entries in this reference are ordered alphabetically by this prefix.
message-text	Text of the message. For the text of each message, see System Log Messages.

Format of the message-source Field

The *message-source* field discussed in “[Interpreting Messages Generated in Standard Format by a Junos OS Process or Library](#)” on page 55 has two or more subfields, depending on whether the message is logged on a single-chassis system or on a platform in a routing matrix, and whether message forwarding is configured in the routing matrix.

For more information, see the following sections:

- [The message-source Field on a Single-Chassis System on page 57](#)
- [The message-source Field on a TX Matrix Platform on page 58](#)

The message-source Field on a Single-Chassis System

The format of the *message-source* field in a message on a single-chassis system depends on whether the message was generated on the local Routing Engine or the other Routing Engine (on a system with two Routing Engines installed and operational). Messages from the other Routing Engine appear only if its configuration includes the **other-routing-engine** statement at the [edit system syslog host] hierarchy level.

- When the local Routing Engine generated the message, there are two subfields:

hostname process[process-ID]

- When the other Routing Engine generated the message, there are three subfields:

hostname reX process[process-ID]

hostname is the hostname of the local Routing Engine.

process[process-ID] is the name and PID of the process that generated the message. If the **reX** field also appears, the process is running on the other Routing Engine. If a process does not report its PID, the [process-ID] part does not appear.

reX indicates that the other Routing Engine generated the message (*X* is 0 or 1).

The message-source Field on a TX Matrix Platform

The format of the *message-source* field in a message on a TX Matrix platform depends on several factors:

- Whether the message was generated on the TX Matrix platform or a T640 routing node in the routing matrix. By default, the master Routing Engine on each T640 routing node forwards messages from all facilities with severity info and higher to the master Routing Engine on the TX Matrix platform. When you configure system logging on the TX Matrix platform, its logs include the forwarded messages. For more information, see [“Impact of Different Local and Forwarded Severity Levels on System Log Messages on a TX Matrix Router” on page 34](#).
- Whether the message was generated on the local Routing Engine or the other Routing Engine on the originating machine (TX Matrix platform or T640 routing node). Messages from the other Routing Engine appear only if its configuration includes the **other-routing-engine** statement at the **[edit system syslog host]** hierarchy level.
- Whether the message was generated by a kernel or user-space process, or by the microkernel on a hardware component.

[Table 24 on page 58](#) specifies the format of the message-source field in the various cases.

Table 24: Format of message-source Field in Messages Logged on TX Matrix Platform

Generating Machine	Generating Routing Engine	Process or Component	Format
TX Matrix platform	Local	Process	<i>hostname process[processID]</i>
		Component	<i>hostname scc-reX process[processID]</i>
	Other	Process	<i>hostname scc-reX scc-componentZ process</i>
		Component	<i>hostname scc-reX scc-componentZ process</i>
T640 routing node	Local	Process	<i>hostname lccY-masterprocess[processID]</i>
		Component	<i>hostname lccY-master scc-componentZ process</i>
	Other	Process	<i>hostname lccY-master lccY-reX process[processID]</i>
		Component	<i>hostname lccY-master lccY-reX lccY-componentZ process</i>

hostname is the hostname of the local Routing Engine on the TX Matrix platform.

lccY-master is the master Routing Engine on the T640 routing node with the indicated LCC index number (*Y* is from 0 through 3).

lccY-reX indicates that the backup Routing Engine on the T640 routing node generated the message (*X* is 0 or 1). The routing node has the indicated LCC index number (*Y* matches the value in the **lccY-master** field).

lccY-componentZ process identifies the hardware component and process on the T640 routing node that generated the message (*Y* matches the value in the **lccY-master** field and the range of values for *Z* depends on the component type). For example, **lcc2-fpc1 PFEMAN** refers to a process on the FPC in slot 1 on the T640 routing node with index LCC2.

process[process-ID] is the name and PID of the kernel or user-space process that generated the message. If the **scc-reX** or **lccY-reX** field also appears, the process is running on the other Routing Engine. If a process does not report its PID, the **[process-ID]** part does not appear.

scc-componentZ process identifies the hardware component and process on the TX Matrix platform that generated the message (the range of values for *Z* depends on the component type). For example, **spmb1 GSIB** refers to a process on one of the processor boards in the Switch Interface Board (SIB) with index 1.

scc-reX indicates that the other Routing Engine on the TX Matrix platform generated the message (*X* is 0 or 1).

Examples: Displaying a Log File

Display the contents of the **/var/log/messages** file stored on the local Routing Engine. (The **/var/log** directory is the default location for log files, so you do not need to include it in the filename. The **messages** file is a commonly configured destination for system log messages.)

```
user@host> show log messages Apr 11 10:27:25 router1 mgd[3606]:
  UI_DBASE_LOGIN_EVENT: User 'barbara' entering configuration mode
Apr 11 10:32:22 router1 mgd[3606]: UI_DBASE_LOGOUT_EVENT: User 'barbara' exiting
  configuration mode
Apr 11 11:36:15 router1 mgd[3606]: UI_COMMIT: User 'root' performed commit: no comment
Apr 11 11:46:37 router1 mib2d[2905]: SNMP_TRAP_LINK_DOWN: ifIndex 82, ifAdminStatus
  up(1), ifOperStatus down(2), ifName at-1/0/0
```

Display the contents of the file **/var/log/processes**, which has been previously configured to include messages from the **daemon** facility. When issuing the **file show** command, you must specify the full pathname of the file:

```
user@host> file show /var/log/processes Feb 22 08:58:24 router1 snmpd[359]:
  SNMPD_TRAP_WARM_START: trap_generate_warm: SNMP trap: warm start
Feb 22 20:35:07 router1 snmpd[359]: SNMPD_THROTTLE_QUEUE_DRAINED:
  trap_throttle_timer_handler: cleared all throttled traps
Feb 23 07:34:56 router1 snmpd[359]: SNMPD_TRAP_WARM_START: trap_generate_warm:
  SNMP trap: warm start
```

```
Feb 23 07:38:19 router1 snmpd[359]: SNMPD_TRAP_COLD_START: trap_generate_cold:
SNMP trap: cold start
```

Display the contents of the file `/var/log/processes` when the **explicit-priority** statement is included at the `[edit system syslog file processes]` hierarchy level:

```
user@host> file show /var/log/processes Feb 22 08:58:24 router1 snmpd[359]:
%DAEMON-3-SNMPD_TRAP_WARM_START: trap_generate_warm: SNMP trap: warm
start
Feb 22 20:35:07 router1 snmpd[359]:
%DAEMON-6-SNMPD_THROTTLE_QUEUE_DRAINED: trap_throttle_timer_handler: cleared
all throttled traps
Feb 23 07:34:56 router1 snmpd[359]:
%DAEMON-3-SNMPD_TRAP_WARM_START: trap_generate_warm: SNMP trap: warm
start
Feb 23 07:38:19 router1 snmpd[359]:
%DAEMON-2-SNMPD_TRAP_COLD_START: trap_generate_cold: SNMP trap: cold start
```

Getting Help About System Log Messages

System log message tag names begin with a prefix that indicates which Junos OS process, subroutine library, or service on a PIC generated the message. This section explains how to learn more about the messages with each prefix, both in this reference and while you are using the CLI.

For a list of the prefixes for messages described in this reference, see System Log Messages. For information about displaying and interpreting messages, see the following sections:

- [Displaying and Interpreting System Log Message Descriptions on page 60](#)
- [Examples: Displaying System Log Message Descriptions on page 62](#)

Displaying and Interpreting System Log Message Descriptions

This reference lists the messages available at the time of its publication. To display the list of messages that applies to the version of Junos OS that is running on a routing platform, enter the Junos OS CLI operational mode and issue the following command:

```
user@host> help syslog ?
```

To display the list of available descriptions for tags whose names begin with a specific character string, substitute the string (in all capital letters) for the variable **TAG-PREFIX** (there is no space between the prefix and the question mark):

```
user@host> help syslog TAG-PREFIX?
```

To display the complete descriptions for tags whose name includes a regular expression, substitute a Perl-based expression for the variable **regex**. The match is not case-sensitive. For information about Perl-based regular expressions, consult a Perl reference manual or website such as <http://perldoc.perl.org>.

```
user@host> help syslog regex
```

To display the complete description of a particular message, substitute its name for the variable **TAG** (in all capital letters):

user@host> help syslog TAG

Table 25 on page 61 describes the fields in a system log message description in this reference or in the CLI.

Table 25: Fields in System Log Message Descriptions

Field Name in Reference	Field Name in CLI	Description
—	Name	The message tag in all capital letters.
System Log Message	Message	<p>Text of the message written to the system log. In the log, a specific value is substituted for each variable that appears in italics in this reference or in angle brackets (<>) in the CLI.</p> <p>In this reference, the message text appears on the second line of the System Log Message field. The first line is the message tag (the same text as in the CLI Name field). The prefix on each tag identifies the message source and the rest of the tag indicates the specific event or error.</p>
—	Help	Short description of the message, which also appears in the right-hand column of CLI output for the help syslog command when the output lists multiple messages.
Description	Description	More detailed explanation of the message.
Type	Type	<p>Category to which the message belongs:</p> <ul style="list-style-type: none">• Error: The message reports an error or failure condition that might require corrective action.• Event: The message reports a condition or occurrence that does not generally require corrective action.
Severity	Severity	Message severity level as described in Table: System Log Message Severity Levels in “Specifying the Facility and Severity of Messages to Include in the Log” on page 9.

Table 25: Fields in System Log Message Descriptions (*continued*)

Field Name in Reference	Field Name in CLI	Description
Cause	Cause	(Optional) Possible cause for message generation. There can be more than one cause.
Action	Action	(Optional) Action you can perform to resolve the error or failure condition described in the message. If this field does not appear in an entry, either no action is required or the action is self-explanatory.

Examples: Displaying System Log Message Descriptions

Display the list of all currently available system log message descriptions:

```
user@host> help syslog ?

Possible completions:
<syslog-tag> Syslog tag
. . . . .
BOOTPD_ARG_ERR    Command-line option was invalid
BOOTPD_BAD_ID     Request failed because assembly ID was unknown
BOOTPD_BOOTSTRING tnp.bootpd provided boot string
BOOTPD_CONFIG_ERR tnp.bootpd could not parse configuration file;
                  used default settings
BOOTPD_CONF_OPEN  tnp.bootpd could not open configuration file
BOOTPD_DUP_REV    Extra boot string definitions for revision were
                  ignored
---(more 4%)---
```

Display the list of all currently available system log message descriptions for tags that begin with the letters **ACCT** (there is no space between **ACCT** and the question mark, and some descriptions are shortened for legibility):

```
user@host> help syslog ACCT?

Possible completions:
<syslog-tag>      System log tag or regular expression
ACCT_ACCOUNTING_FERROR Error occurred during file processing
ACCT_ACCOUNTING_FOPEN_ERROR Open operation failed on file
ACCT_ACCOUNTING_SMALL_FILE_SIZE Maximum file size is smaller than ...
ACCT_BAD_RECORD_FORMAT Record format does not match accounting profile
ACCT_CU_RTSLIB_ERROR Error occurred obtaining current class usage ...
ACCT_FORK_ERR      Could not create child process
ACCT_FORK_LIMIT_EXCEEDED Could not create child process because of limit
ACCT_GETHOSTNAME_ERROR gethostname function failed
ACCT_MALLOC_FAILURE Memory allocation failed
ACCT_UNDEFINED_COUNTER_NAME Filter profile used undefined counter name
ACCT_XFER_FAILED Attempt to transfer file failed
ACCT_XFER_POPEN_FAIL File transfer failed
```

Display the description of the **UI_CMDLINE_READ_LINE** message:

```
user@host> help syslog UI_CMDLINE_READ_LINE
```

```
Name:      UI_CMDLINE_READ_LINE
Message:   User '<users>', command '<input>'
Help:      User entered command at CLI prompt
Description: The indicated user typed the indicated command at the CLI
              prompt and pressed the Enter key, sending the command string
              to the management process (mgd).
Type:      Event: This message reports an event, not an error
Severity:  info
```


PART 2

System Log Messages

- [AAA System Log Messages on page 69](#)
- [ACCT System Log Messages on page 71](#)
- [ALARMD System Log Messages on page 75](#)
- [AMD System Log Messages on page 81](#)
- [ANALYZER System Log Messages on page 83](#)
- [ANTISPAM System Log Messages on page 85](#)
- [APPID System Log Messages on page 87](#)
- [APPIDD System Log Messages on page 89](#)
- [APPPXY System Log Messages on page 91](#)
- [APPTRACK System Log Messages on page 93](#)
- [ASP System Log Messages on page 97](#)
- [AUDITD System Log Messages on page 129](#)
- [AUTHD System Log Messages on page 133](#)
- [AUTOCONFD System Log Messages on page 137](#)
- [AUTOD System Log Messages on page 139](#)
- [AV System Log Messages on page 141](#)
- [BBE System Log Messages on page 145](#)
- [BFDD System Log Messages on page 147](#)
- [BGP System Log Messages on page 151](#)
- [BOOTPD System Log Messages on page 165](#)
- [CFMD System Log Messages on page 171](#)
- [CHASSISD System Log Messages on page 175](#)
- [CHASSISM System Log Messages on page 275](#)
- [CLKSYNCD System Log Messages on page 277](#)
- [COSD System Log Messages on page 287](#)
- [DCBX System Log Messages on page 303](#)
- [DCD System Log Messages on page 305](#)
- [DDOS System Log Messages on page 313](#)
- [DFCD System Log Messages on page 317](#)

- [DFWD System Log Messages on page 321](#)
- [DHCPD System Log Messages on page 323](#)
- [DIAM System Log Messages on page 329](#)
- [DOTIXD System Log Messages on page 331](#)
- [DYNAMIC System Log Messages on page 335](#)
- [ESWD System Log Messages on page 341](#)
- [EVENTD System Log Messages on page 351](#)
- [FABOAMD System Log Messages on page 361](#)
- [FC System Log Messages on page 363](#)
- [FCOE System Log Messages on page 369](#)
- [FIP System Log Messages on page 371](#)
- [FIPS System Log Messages on page 375](#)
- [FLOW System Log Messages on page 377](#)
- [FPCLOGIN System Log Messages on page 381](#)
- [FSAD System Log Messages on page 383](#)
- [FUD System Log Messages on page 393](#)
- [FWAUTH System Log Messages on page 399](#)
- [GPRSD System Log Messages on page 405](#)
- [HNCACHED System Log Messages on page 407](#)
- [ICCPD System Log Messages on page 409](#)
- [IDP System Log Messages on page 411](#)
- [JADE System Log Messages on page 419](#)
- [JCS System Log Messages on page 423](#)
- [JDIAMETERD System Log Messages on page 429](#)
- [JIVED System Log Messages on page 431](#)
- [JNUD System Log Messages on page 435](#)
- [JPTSPD System Log Messages on page 437](#)
- [JSERVICES System Log Messages on page 441](#)
- [JSRPD System Log Messages on page 445](#)
- [JTASK System Log Messages on page 455](#)
- [JTRACE System Log Messages on page 469](#)
- [KMD System Log Messages on page 471](#)
- [L2ALD System Log Messages on page 487](#)
- [L2CPD System Log Messages on page 503](#)
- [L2TPD System Log Messages on page 507](#)
- [LACP System Log Messages on page 537](#)
- [LACPD System Log Messages on page 539](#)

- [LFMD System Log Messages on page 541](#)
- [LIBJNX System Log Messages on page 543](#)
- [LIBJSNMP System Log Messages on page 553](#)
- [LIBMSRPC System Log Messages on page 559](#)
- [LICENSE System Log Messages on page 563](#)
- [LLDP System Log Messages on page 571](#)
- [LOGIN System Log Messages on page 573](#)
- [LPDFD System Log Messages on page 579](#)
- [LRMUX System Log Messages on page 581](#)
- [LSYSD System Log Messages on page 583](#)
- [MBG System Log Messages on page 585](#)
- [MCSN System Log Messages on page 601](#)
- [MIB2D System Log Messages on page 603](#)
- [MPLS System Log Messages on page 611](#)
- [NEXTHOP System Log Messages on page 615](#)
- [NSD System Log Messages on page 617](#)
- [NSTRACED System Log Messages on page 619](#)
- [NTPDATE System Log Messages on page 621](#)
- [NTPD System Log Messages on page 623](#)
- [PARSE System Log Messages on page 625](#)
- [PFE System Log Messages on page 627](#)
- [PFED System Log Messages on page 635](#)
- [PGCPD System Log Messages on page 637](#)
- [PING System Log Messages on page 639](#)
- [PKID System Log Messages on page 643](#)
- [PPMD System Log Messages on page 653](#)
- [PPPD System Log Messages on page 655](#)
- [PROFILER System Log Messages on page 663](#)
- [RDD System Log Messages on page 665](#)
- [RMOPD System Log Messages on page 669](#)
- [RPD System Log Messages on page 673](#)
- [RT System Log Messages on page 747](#)
- [RTLOG System Log Messages on page 761](#)
- [RTLOGD System Log Messages on page 763](#)
- [RTPERF System Log Messages on page 765](#)
- [SAVAL System Log Messages on page 767](#)
- [SDK System Log Messages on page 769](#)

- [SDXD System Log Messages on page 771](#)
- [SM System Log Messages on page 775](#)
- [SMTPD System Log Messages on page 777](#)
- [SNMP System Log Messages on page 779](#)
- [SNMPD System Log Messages on page 783](#)
- [SPD System Log Messages on page 797](#)
- [SSH System Log Messages on page 805](#)
- [SSHD System Log Messages on page 807](#)
- [SSL System Log Messages on page 809](#)
- [SYSTEM System Log Messages on page 813](#)
- [TFTPD System Log Messages on page 815](#)
- [TRANSPORTD System Log Messages on page 819](#)
- [UFDD System Log Messages on page 823](#)
- [UI System Log Messages on page 825](#)
- [UTMD System Log Messages on page 855](#)
- [VCCPD System Log Messages on page 857](#)
- [VM System Log Messages on page 863](#)
- [VRRPD System Log Messages on page 865](#)
- [WEB System Log Messages on page 869](#)
- [WEBFILTER System Log Messages on page 875](#)

CHAPTER 2

AAA System Log Messages

This chapter describes messages with the **AAA** prefix.

AAA_RADIUS_SERVER_STATE_CHANGE

System Log Message	Radius server <i>radius-server-name</i> state changed to <i>new-radius-server-state</i> on <i>interface-name</i>
Description	This notification signifies that the specified radius server has changed state from active to dead or vice-versa
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

CHAPTER 3

ACCT System Log Messages

This chapter describes messages with the **ACCT** prefix. They are generated by the accounting statistics process, which collects and records interface, filter, and class usage statistics.

ACCT_ACCOUNTING_FERROR

System Log Message	Unexpected error <i>error-code</i> from file <i>filename</i>
Description	An error prevented the accounting statistics process from processing the indicated file.
Type	Error: An error occurred
Severity	warning
Facility	LOG_PFE

ACCT_ACCOUNTING_FOPEN_ERROR

System Log Message	Failed to open file <i>filename: error-code</i>
Description	The accounting statistics process could not open the indicated file.
Type	Error: An error occurred
Severity	warning
Facility	LOG_PFE

ACCT_ACCOUNTING_SMALL_FILE_SIZE

System Log Message	File <i>filename</i> size (<i>file-size</i>) is smaller than record size (<i>record-size</i>)
Description	The size limit configured for the indicated file is smaller than the record to be written to it.
Type	Error: An error occurred
Severity	warning
Facility	LOG_PFE

ACCT_BAD_RECORD_FORMAT

System Log Message	Invalid statistics record: <i>entry</i>
---------------------------	---

Description The number of columns in the indicated record does not match the number of columns in the accounting profile.

Type Error: An error occurred

Severity warning

Facility LOG_PFE

ACCT_CU_RTSLIB_ERROR

System Log Message Error getting class usage statistics for interface *interface-name.unit-id: error-message*

Description The accounting statistics process could not obtain current class usage statistics.

Type Error: An error occurred

Severity error

Facility LOG_PFE

ACCT_FORK_ERR

System Log Message Unable to fork: *error-message*

Description The accounting statistics process could not create a child process for transferring files, for the indicated reason.

Type Error: An error occurred

Severity error

Facility LOG_PFE

ACCT_FORK_LIMIT_EXCEEDED

System Log Message Unable to fork: too many child processes

Description The accounting statistics process could not create a child process for transferring files, because adding another child would have made the number of children exceed the limit.

Type Error: An error occurred

Severity error

Facility LOG_PFE

ACCT_GETHOSTNAME_ERROR

System Log Message Error *error-code* trying to get hostname

Description A call to the gethostname() function failed.

Type Error: An error occurred

Severity error

Facility LOG_PFE

ACCT_MALLOC_FAILURE

System Log Message	Memory allocation failed while reallocating filter profile interface list
Description	The accounting statistics process could not allocate memory from the heap.
Type	Error: An error occurred
Severity	error
Facility	LOG_PFE
Cause	An internal software failure occurred.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18749 .

ACCT_THREAD_CREATE_FAILURE

System Log Message	Unable to create file transfer timeout thread: <i>error-message</i>
Description	The accounting statistics process could not create a thread to ensure that file transfers complete within the configured accounting-options time interval.
Type	Error: An error occurred
Severity	error
Facility	LOG_PFE

ACCT_UNDEFINED_COUNTER_NAME

System Log Message	Counter <i>profile-name</i> in accounting profile <i>counter-name</i> is not defined in a firewall using this filter profile
Description	The indicated filter profile referenced the indicated counter name, which is not defined in a firewall filter that uses the filter profile.
Type	Error: An error occurred
Severity	warning
Facility	LOG_PFE
Action	Change the filter profile counter name to match the name defined in the firewall configuration.

ACCT_XFER_FAILED

System Log Message	Error transferring <i>filename</i>
Description	An attempt to transfer the indicated file failed.
Type	Error: An error occurred

Severity error
Facility LOG_PFE

ACCT_XFER_POPEN_FAIL

System Log Message Error *error-code* in invoking command *command* to transfer file *filename*

Description A call to the popen() function failed when the accounting statistics process invoked the indicated command to transfer the indicated file.

Type Error: An error occurred

Severity error

Facility LOG_PFE

Action For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18750>.

ACCT_XFER_TIMEDOUT

System Log Message Aborted file transfer for: *filename*, *time-period* min. interval exceeded

Description The time required to transfer a file exceeded the time configured for accounting-options interval.

Type Error: An error occurred

Severity error

Facility LOG_PFE

CHAPTER 4

ALARMD System Log Messages

This chapter describes messages with the **ALARMD** prefix. They are generated by the alarm process (alarmd).

ALARMD_CONFIG_ACCESS_ERROR

System Log Message	<i>function-name: error-message</i>
Description	The alarm process (alarmd) experienced the indicated problem while attempting to parse the configuration database.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

ALARMD_CONFIG_CLOSE_ERROR

System Log Message	Unable to close configuration database
Description	The alarm process (alarmd) could not close the configuration database.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

ALARMD_CONFIG_PARSE_ERROR

System Log Message	Unable to parse configuration; using defaults
Description	The alarm process (alarmd) could not parse the configuration and used default values while initializing.
Type	Error: An error occurred
Severity	error

Facility	LOG_DAEMON
Action	Contact your technical support representative.

ALARMD_CONFIG_RECONFIG_ERROR

System Log Message	Re-configuration failed, using previous values
Description	The alarm process (alarmd) could not parse new configuration and used previous values.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

ALARMD_CONNECTION_FAILURE

System Log Message	after <i>count</i> attempts <i>process-name</i> connect returned error: <i>error-message</i>
Description	The alarm process (alarmd) was unable to connect to the indicated process
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

ALARMD_DECODE_ALARM_OBJECT_ERROR

System Log Message	Cannot decode error test from object <i>alarm-object</i> , reason <i>alarm-reason</i> for if_name <i>interface-type</i>
Description	The alarm process (alarmd) encountered invalide alarm object.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

ALARMD_EXISTS

System Log Message	alarmd already running; exiting
Description	The alarm process (alarmd) exited because it discovered that another alarmd process is already running.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

ALARMD_EXISTS_TERM_OTHER

System Log Message	Killing existing alarmd and exiting
Description	The alarm process (alarmd) discovered that another alarmd process is already running. It terminated the other process and exited.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

ALARMD_IFDALARM_TYPE_ERROR

System Log Message	Unknown interface alarm type: <i>alarm-type</i>
Description	The alarm process (alarmd) could not recognize an interface type alarm due to it's unknown alarm type.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

ALARMD_IFDEV_RTSLIB_FAILURE

System Log Message	<i>function-name: library-function-name</i> failed on <i>error-message</i> socket (<i>socket-option</i>)
Description	The alarm process (alarmd) failed to access an interface device because an error occurred during the indicated call to the routing socket library.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

ALARMD_IPC_MSG_ERROR

System Log Message	<i>function-name: error code error-code</i> , type <i>message-type</i> , subtype <i>message-subtype</i> , opcode <i>message-opcode</i>
Description	The alarm process (alarmd) detected an error in an interprocess communication (IPC) message with the indicated characteristics.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

Action Contact your technical support representative.

ALARMD_IPC_MSG_WRITE_ERROR

System Log Message alarmd_send_msg: ipc_msg_write failed: *error-message*.

Description The alarm process (alarmd) is not able to write a new ipc message to the given ipc pipe.

Type Error: An error occurred

Severity warning

Facility LOG_DAEMON

ALARMD_IPC_UNEXPECTED_MSG

System Log Message *function-name*: invalid message received: *message* (message type *message-type*, subtype *message-subtype*)

Description The alarm process (alarmd) received an unexpected message with the indicated characteristics.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

ALARMD_MEM_ALLOC_FAILURE

System Log Message *function-name*: alarmd memory allocation failed

Description The alarm process (alarmd) could not allocate memory.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

ALARMD_MGR_CONNECT

System Log Message *function-name* evSelectFD: initial pipe create aborted (errno *error-code*)

Description The alarm process (alarmd) could not open a pipe for interprocess communication (IPC).

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

ALARMD_MULTIPLE_ALARM_BIT_ERROR

System Log Message	Multiple alarm bits: <i>Oxalarm-bit</i>
Description	The alarm process (alarmd) expected one alarm bit set for an interface alarm when it received multiple.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

ALARMD_PIDFILE_OPEN

System Log Message	Unable to open PID file ' <i>filename</i> ': <i>errno error-code</i>
Description	The alarm process (alarmd) could not open the file where it stores its process ID (PID).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	The alarm process (alarmd) might have detected that another alarmd process was running and tried to read the file so that it could use the PID recorded there when terminating the other process.

ALARMD_PIPE_WRITE_ERROR

System Log Message	Pipe write error: <i>error-message</i>
Description	The alarm process (alarmd) experienced a fatal error while writing to a pipe.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	There was no reader for the pipe.

ALARMD_SOCKET_CREATE

System Log Message	Unable to create socket for <i>process-name</i> connection: <i>errno error-code</i>
Description	The alarm process (alarmd) could not create socket.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

ALARMD_UNEXPECTED_EXIT

System Log Message	evMainLoop returned <i>return-value</i> (errno <i>error-code</i>)
Description	The alarm process (alarmd) exited unexpectedly and reported the indicated error.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHAPTER 5

AMD System Log Messages

AMD_CONFIG_CHECK_FAILED

System Log Message	<i>function-name</i> : configuration database has errors
Description	The portion of the candidate configuration related to the ALARMMGMTD process (alarm-mgmt) was checked for validity during a 'commit' operation. The check failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	The configuration was invalid.
Action	Correct the invalid portion of the configuration as described in the error message on the console.

AMD_FILE_OPEN_FAILURE

System Log Message	Unable to open file ' <i>filename</i> ': <i>error-message</i>
Description	The ALARMMGMTD process (alarm-mgmt) could not open the indicated file.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

CHAPTER 6

ANALYZER System Log Messages

This chapter describes messages with the **ANALYZER** prefix on the Juniper Networks EX Series switches. They are generated by the sample process (sampled), which gathers information on mirrored traffic analysis for EX Series switches.

ANALYZER_INPUT_INTERFACES_LIMIT

System Log Message	Number of analyzer input interface is exceeding <i>error-message</i>
Description	In an analyzer session, the number of input interfaces exceeded the platform limit.
Type	Error: An error occurred
Severity	alert
Facility	LOG_DAEMON

CHAPTER 7

ANTISPAM System Log Messages

This chapter describes messages with the **ANTISPAM** prefix. They are generated by the antispam process, which decides what action should be performed when the device detects a message that it deems to be spam.

This chapter describes messages with the **ANTISPAM** prefix. They are generated by the antispam process, which decides what action should be performed when the device detects a message that it deems to be spam.

ANTISPAM_SPAM_DETECTED_MT

System Log Message	AntiSpam: SPAM detected: <i>source-name (source-address) action reason: reason username username roles roles</i>
Description	The email is detected as a spam; the IP address of the source and its name will be logged together with the reason for it being categorized as spam
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_PFE
Cause	The email is detected as a spam
Action	Verify the spam to make sure it is not a false positive

CHAPTER 8

APPID System Log Messages

This chapter describes messages with the **APPID** prefix. They are generated by the application identification process (appid), which is a passive application protocol identification library that implements a state machine for efficient pattern matching of regex-like application content signatures.

APPID_SIGNATURE_LICENSE_EXPIRED

System Log Message	APPID signature update license(ID= <i>feature-id</i>) has expired
Description	APPID signature update license key has expired. Signature update may not work any more.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

CHAPTER 9

APPIDD System Log Messages

This chapter describes messages with the **APPIDD** prefix. They are generated by the application identification process (appid), which is a passive application protocol identification library that implements a state machine for efficient pattern matching of regex-like application content signatures.

APPIDD_APPPACK_DOWNLOAD_RESULT

System Log Message	Application package download result(<i>status</i>)
Description	Application package download result
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

APPIDD_APPPACK_INSTALL_RESULT

System Log Message	Application package install result(<i>status</i>)
Description	Application package install result
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

APPIDD_APPPACK_UNINSTALL_RESULT

System Log Message	Application package uninstall result(<i>status</i>)
Description	Application package uninstall result
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

APPIDD_DAEMON_INIT_FAILED

System Log Message	Aborted. A failure was encountered <i>error-message</i>
---------------------------	---

Description An attempt to start AI policy daemon failed because an error was encountered during initialization.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

APPIDD_INTERNAL_ERROR

System Log Message Internal Error(*error-message*)

Description Application-Identification daemon encountered an internal error

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

APPIDD_SCHEDULED_UPDATE_FAILED

System Log Message Failed to update application package *error-message*

Description The scheduled application-identification application package update failed to start. Device will try it again at the next scheduled time

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

CHAPTER 10

APPPXY System Log Messages

This chapter describes messages with the **APPPXY** prefix. They are generated by the Application Proxy process (appxyd) which performs all of the services of a proxy, but only for specific applications. The application proxy will only process packets that related to the applications it supports.

This chapter describes messages with the **APPPXY** prefix. They are generated by the Application Proxy process (appxyd) which performs all of the services of a proxy, but only for specific applications. The application proxy will only process packets that related to the applications it supports.

APPPXY_SESSION_ABORT_MT

System Log Message	ApplicationProxy: session from <i>source-address:source-port</i> to <i>destination-address:destination-port</i> aborted due to <i>error-message</i> (code <i>error-code</i>)
Description	Report application protocol (ftp/http/pop3/smtp/imap) session is aborted
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_PFE

CHAPTER 11

APPTRACK System Log Messages

This chapter describes messages with the **APPTRACK** prefix. They are generated by the application tracking process (apptrack).

APPTRACK_SESSION_APP_UPDATE

System Log Message AppTrack app update: *source-address/source-port->destination-address/destination-port service-name application nested-application nat-source-address/nat-source-port->nat-destination-address/nat-destination-port src-nat-rule-name dst-nat-rule-name protocol-id policy-name source-zone-name destination-zone-name session-id-32 packets-from-client(bytes-from-client) packets-from-server(bytes-from-server) elapsed-time username roles encrypted*

Description A log message was sent by AppTrack, an application tracking tool, when an application identification service identified an application in the session.

Type Event: This message reports an event, not an error

Severity info

Facility ANY

APPTRACK_SESSION_APP_UPDATE_LS

System Log Message Lsys *logical-system-name*: AppTrack app update: *source-address/source-port->destination-address/destination-port service-name application nested-application nat-source-address/nat-source-port->nat-destination-address/nat-destination-port src-nat-rule-name dst-nat-rule-name protocol-id policy-name source-zone-name destination-zone-name session-id-32 packets-from-client(bytes-from-client) packets-from-server(bytes-from-server) elapsed-time username roles encrypted*

Description A log message was sent by AppTrack, an application tracking tool, when an application identification service identified an application in the session.

Type Event: This message reports an event, not an error

Severity info

Facility ANY

APPTRACK_SESSION_CLOSE

System Log Message	AppTrack session closed <i>reason:</i> <i>source-address/source-port->destination-address/destination-port service-name application nested-application</i> <i>nat-source-address/nat-source-port->nat-destination-address/nat-destination-port src-nat-rule-name dst-nat-rule-name protocol-id policy-name source-zone-name destination-zone-name session-id-32 packets-from-client(bytes-from-client) packets-from-server(bytes-from-server) elapsed-time username roles encrypted</i>
Description	A security session being tracked by AppTrack, an application tracking tool, was closed.
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

APPTRACK_SESSION_CLOSE_LS

System Log Message	Lsys <i>logical-system-name:</i> AppTrack session closed <i>reason:</i> <i>source-address/source-port->destination-address/destination-port service-name application nested-application</i> <i>nat-source-address/nat-source-port->nat-destination-address/nat-destination-port src-nat-rule-name dst-nat-rule-name protocol-id policy-name source-zone-name destination-zone-name session-id-32 packets-from-client(bytes-from-client) packets-from-server(bytes-from-server) elapsed-time username roles encrypted</i>
Description	A security session being tracked by AppTrack, an application tracking tool, was closed.
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

APPTRACK_SESSION_CREATE

System Log Message	AppTrack session created <i>source-address/source-port->destination-address/destination-port service-name application nested-application</i> <i>nat-source-address/nat-source-port->nat-destination-address/nat-destination-port src-nat-rule-name dst-nat-rule-name protocol-id policy-name source-zone-name destination-zone-name session-id-32 username roles encrypted</i>
Description	A security session that will be monitored by AppTrack, an application tracking tool, was created.
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

APPTRACK_SESSION_CREATE_LS

System Log Message	<i>Lsys logical-system-name: AppTrack session created source-address/source-port->destination-address/destination-port service-name application nested-application nat-source-address/nat-source-port->nat-destination-address/nat-destination-port src-nat-rule-name dst-nat-rule-name protocol-id policy-name source-zone-name destination-zone-name session-id-32 username roles encrypted</i>
Description	A security session that will be monitored by AppTrack, an application tracking tool, was created.
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

APPTRACK_SESSION_VOL_UPDATE

System Log Message	<i>AppTrack volume update: source-address/source-port->destination-address/destination-port service-name application nested-application nat-source-address/nat-source-port->nat-destination-address/nat-destination-port src-nat-rule-name dst-nat-rule-name protocol-id policy-name source-zone-name destination-zone-name session-id-32 packets-from-client(bytes-from-client) packets-from-server(bytes-from-server) elapsed-time username roles encrypted</i>
Description	Apptrack, an application tracking tool, sent periodic updates on the volume (byte and packet count) for the session that it is monitoring. The update interval is determined by the configuration.
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

APPTRACK_SESSION_VOL_UPDATE_LS

System Log Message	<i>Lsys logical-system-name: AppTrack volume update: source-address/source-port->destination-address/destination-port service-name application nested-application nat-source-address/nat-source-port->nat-destination-address/nat-destination-port src-nat-rule-name dst-nat-rule-name protocol-id policy-name source-zone-name destination-zone-name session-id-32 packets-from-client(bytes-from-client) packets-from-server(bytes-from-server) elapsed-time username roles encrypted</i>
Description	Apptrack, an application tracking tool, sent periodic updates on the volume (byte and packet count) for the session that it is monitoring. The update interval is determined by the configuration.
Type	Event: This message reports an event, not an error

Severity info
Facility ANY

CHAPTER 12

ASP System Log Messages

This chapter describes messages with the **ASP** prefix. They are generated by services on the Adaptive Services PIC (AS PIC), such as stateful firewall, Network Address Translation (NAT), and intrusion detection service (IDS). For information about configuring system logging for services on the AS PIC, see the *Junos Services Interfaces Configuration Guide*.

For information about the fields in messages with the ASP prefix, see “Interpreting Messages Generated in Standard Format by Services on a PIC” on page 43.

ASP_COS_RULE_MATCH

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name) application: application, source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type rule-set: rule-set-name, rule: rule-name, term: term-name*

Description A packet matched the indicated term in the indicated class-of-service (CoS) rule. If the rule belongs to a rule set, the name of the rule set is also displayed. The matching packet contained the indicated information about its protocol (numerical identifier and name), application, source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

ASP_IDS_HOST_RATE

System Log Message *Host destination-address, event-type ... rate=rate events/sec*

Description The indicated event occurred at the indicated rate (events per second) for the indicated destination IP address. The rate exceeds the intrusion detection services (IDS) threshold configured with the 'threshold' statement at the [edit services rule <rule-name> term <term-name> then logging] hierarchy level. This message is logged every 60 seconds until the rate no longer exceeds the threshold.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_PFE

ASP_IDS_HOST_RATE_APP

System Log Message Host *destination-address (application)*, *event-type* ... rate=*rate* events/sec

Description The indicated event occurred at the indicated rate (events per second) for the indicated application at the indicated destination IP address. The rate exceeds the intrusion detection services (IDS) threshold set by the 'threshold' statement at the [edit services ids rule <rule-name> term <term-name> then logging] hierarchy level. The application is specified by the 'applications' or 'application-sets' statement at the [edit services ids rule <rule-name> term <term-name> from] hierarchy level. This message is logged every 60 seconds until the rate no longer exceeds the threshold.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_PFE

ASP_IDS_INV_CLEAR_QUERY

System Log Message CLEAR: Invalid query type *received-value* expecting *expected-value*

Description Intrusion detection services (IDS) received a request to clear information from IDS tables. The request included the indicated type of query, which IDS cannot interpret.

Type Error: An error occurred

Severity critical

Facility LOG_PFE

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18751>.

ASP_IDS_INV_CLEAR_QUERY_VER

System Log Message CLEAR: Invalid query version *received-value* expecting *expected-value*

Description Intrusion detection services (IDS) received a request to clear information from IDS tables. The request's version number did not match the version number of requests that IDS can service.

Type Error: An error occurred

Severity critical

Facility LOG_PFE

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18752>.

ASP_IDS_INV_SHOW_QUERY

System Log Message SHOW: Invalid query type *received-value* expecting *expected-value*

Description Intrusion detection services (IDS) received a request to show information from IDS tables. The request included the indicated type of query, which IDS cannot interpret.

Type Error: An error occurred

Severity critical

Facility LOG_PFE

Action Contact your technical support representative.

ASP_IDS_INV_SHOW_QUERY_VER

System Log Message SHOW: Invalid query version *received-value* expecting *expected-value*

Description Intrusion detection services (IDS) received a request to show information from IDS tables. The request's version number did not match the version number of requests that IDS can service.

Type Error: An error occurred

Severity critical

Facility LOG_PFE

Action Contact your technical support representative.

ASP_IDS_LIMIT_FLOW_RATE_BY_DEST

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the packet with the indicated characteristics and did not create a new flow, because the flow rate at the firewall exceeded the intrusion detection services (IDS) limit configured by the 'rate' statement at the [edit services ids rule <rule-name> term <term-name> then session-limit by-destination] hierarchy level. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_PFE

ASP_IDS_LIMIT_FLOW_RATE_BY_PAIR

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the packet with the indicated characteristics and did not create a new flow, because the flow rate at the firewall exceeded the intrusion detection

services (IDS) limit configured by the 'rate' statement at the [edit services ids rule <rule-name> term <term-name> then session-limit by-pair] hierarchy level. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_PFE

ASP_IDS_LIMIT_FLOW_RATE_BY_SRC

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the packet with the indicated characteristics and did not create a new flow, because the flow rate at the firewall exceeded the intrusion detection services (IDS) limit configured by the 'rate' statement at the [edit services ids rule <rule-name> term <term-name> then session-limit by-source] hierarchy level. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_PFE

ASP_IDS_LIMIT_OPEN_FLOWS_BY_DEST

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the packet with the indicated characteristics and did not create a new flow, because the number of open flows exceeded the intrusion detection services (IDS) limit configured by the 'maximum' statement at the [edit services ids rule <rule-name> term <term-name> then session-limit by-destination] hierarchy level. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_PFE

ASP_IDS_LIMIT_OPEN_FLOWS_BY_PAIR

System Log Message	<i>syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type</i>
Description	The stateful firewall discarded the packet with the indicated characteristics and did not create a new flow, because the number of open flows exceeded the intrusion detection services (IDS) limit configured by the 'maximum' statement at the [edit services ids rule <rule-name> term <term-name> then session-limit by-pair] hierarchy level. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_PFE

ASP_IDS_LIMIT_OPEN_FLOWS_BY_SRC

System Log Message	<i>syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type</i>
Description	The stateful firewall discarded the packet with the indicated characteristics and did not create a new flow, because the number of open flows exceeded the intrusion detection services (IDS) limit configured by the 'maximum' statement at the [edit services ids rule <rule-name> term <term-name> then session-limit by-source] hierarchy level. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_PFE

ASP_IDS_LIMIT_PKT_RATE_BY_DEST

System Log Message	<i>syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type</i>
Description	The stateful firewall discarded the packet with the indicated characteristics, because the number of packets per second (aggregated over all monitored flows) exceeded the intrusion detection services (IDS) limit configured by the 'packets' statement at the [edit services ids rule <rule-name> term <term-name> then session-limit by-destination] hierarchy level. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_PFE

ASP_IDS_LIMIT_PKT_RATE_BY_PAIR

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the packet with the indicated characteristics, because the number of packets per second (aggregated over all monitored flows) exceeded the intrusion detection services (IDS) limit configured by the 'packets' statement at the [edit services ids rule <rule-name> term <term-name> then session-limit by-pair] hierarchy level. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_PFE

ASP_IDS_LIMIT_PKT_RATE_BY_SRC

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the packet with the indicated characteristics, because the number of packets per second (aggregated over all monitored flows) exceeded the intrusion detection services (IDS) limit configured by the 'packets' statement at the [edit services ids rule <rule-name> term <term-name> then session-limit by-source] hierarchy level. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_PFE

ASP_IDS_NO_MEM_SHOW_CMD

System Log Message Not enough memory for show command

Description Intrusion detection services (IDS) could not service a request to show information from IDS tables, because not enough memory was available.

Type	Error: An error occurred
Severity	critical

Facility LOG_PFE

ASP_IDS_NULL_CLEAR_QUERY

System Log Message Failure: NULL query for CLEAR command.

Description Intrusion detection services (IDS) invoked a query handler to service a request to clear information from IDS tables. The handler did not receive the request.

Type Event: This message reports an event, not an error

Severity critical

Facility LOG_PFE

Action Contact your technical support representative.

ASP_IDS_NULL_SHOW_QUERY

System Log Message Failure: NULL query for SHOW command.

Description Intrusion detection services (IDS) invoked a query handler to service a request to show information from IDS tables. The handler did not receive the request.

Type Event: This message reports an event, not an error

Severity critical

Facility LOG_PFE

Action Contact your technical support representative.

ASP_IDS_RULE_MATCH

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name) application: application, source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type rule-set: rule-set-name, rule: rule-name, term: term-name*

Description A packet matched the indicated term in the indicated intrusion detection services (IDS) rule. If the rule belongs to a rule set, the rule set name is also displayed. The matching packet contained the indicated information about its protocol (numerical identifier and name), application, source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

ASP_IDS_SYN_COOKIE_OFF

System Log Message Host *destination-address*, SYN-COOKIE protection deactivated

Description	Intrusion detection services (IDS) deactivated SYN cookie protection for the indicated destination address. IDS deactivates this protection when it learns from the stateful firewall that the rate of certain events has returned to a level below the threshold set by the 'threshold' statement at the [edit services ids rule <rule-name> term <term-name> then syn-cookie] hierarchy level. The relevant events include the ones reported by the ASP_IDS_TCP_SYN_ATTACK, ASP_SFW_SYN_DEFENSE, and ASP_SFW_TCP_SCAN system log messages.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_PFE

ASP_IDS_SYN_COOKIE_ON

System Log Message	Host <i>destination-address</i> , SYN-COOKIE protection activated
Description	Intrusion detection services (IDS) activated SYN cookie protection for the indicated destination address, because it learned from the stateful firewall that the rate of certain events exceeded the threshold set by the 'threshold' statement at the [edit services ids rule <rule-name> term <term-name> then syn-cookie] hierarchy level. The events include the ones reported by the ASP_IDS_TCP_SYN_ATTACK, ASP_SFW_SYN_DEFENSE, and ASP_SFW_TCP_SCAN system log messages. When SYN cookie protection is activated for a flow to a destination and the TCP handshake has not completed, the stateful firewall generates a SYN/ACK packet for each SYN packet directed to the destination.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_PFE

ASP_IDS_TCP_SYN_ATTACK

System Log Message	<i>syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type</i>
Description	The stateful firewall received the packet with the indicated characteristics and determined that it was a duplicate Transmission Control Protocol (TCP) SYN packet (the SYN flag was set and a SYN packet was already received for the flow to the destination). The event was reported to intrusion detection services (IDS) and can cause IDS to activate SYN cookie protection. The packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_PFE

ASP_L2TP_MESSAGE_INCOMPLETE

System Log Message	IPC message lacked variable portion
Description	The Layer 2 Tunneling Protocol (L2TP) did not process an interprocess communication (IPC) message because the variable portion of the message was missing.
Type	Error: An error occurred
Severity	error
Facility	LOG_PFE

ASP_L2TP_NO_MEM

System Log Message	Unable to allocate memory for L2TP flow for tunnel <i>tunnel-id</i> , session <i>session-id</i>
Description	The Layer 2 Tunneling Protocol (L2TP) could not allocate the memory it needed to create a flow for the indicated tunnel and session.
Type	Error: An error occurred
Severity	error
Facility	LOG_PFE
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18753 .

ASP_L2TP_OBJ_CAC_FAIL

System Log Message	Unable to allocate object-cache memory for flow (unit <i>unit-id</i> , tunnel <i>tunnel-id</i> , session <i>session-id</i>)
Description	The Layer 2 Tunneling Protocol (L2TP) could not allocate memory from an object cache for the flow defined by the indicated unit, tunnel, and session.
Type	Error: An error occurred
Severity	error
Facility	LOG_PFE
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18754 .

ASP_L2TP_STATS_BULK_QUERY_FAILED

System Log Message	Number of queries (<i>num-queries</i>) in statistics request exceeded limit (<i>max-queries</i>)
Description	The Layer 2 Tunneling Protocol (L2TP) did not process an interprocess communication (IPC) request for statistics because it included the indicated the number of queries, which exceeds the limit as indicated.
Type	Error: An error occurred

Severity error
Facility LOG_PFE

ASP_L2TP_STATS_VERSION_INVALID

System Log Message Invalid version *received-value* on statistics request (expected *expected-value*)

Description The Layer 2 Tunneling Protocol process (l2tpd) received a request for statistics with the indicated version, which is not the indicated, supported version.

Type Error: An error occurred

Severity error

Facility LOG_PFE

ASP_L2TP_TUN_GRP_ADD_FAIL_ALLOC

System Log Message Unable to add tunnel group for service set *service-set*: could not allocate ID

Description The Layer 2 Tunneling Protocol (L2TP) could not add a tunnel group for the indicated service set because it could not allocate an internal ID.

Type Error: An error occurred

Severity error

Facility LOG_PFE

ASP_L2TP_TUN_GRP_ADD_FAIL_EXISTS

System Log Message Unable to add tunnel group *group-id*: it already exists

Description The Layer 2 Tunneling Protocol (L2TP) could not add a tunnel group with the indicated ID because it already existed.

Type Error: An error occurred

Severity error

Facility LOG_PFE

ASP_L2TP_TUN_GRP_CHG_FAIL_ALLOC

System Log Message Unable to change tunnel group for service set *service-set*: could not allocate ID

Description The Layer 2 Tunneling Protocol (L2TP) could not change a tunnel group for the indicated service set because it could not allocate an internal ID.

Type Error: An error occurred

Severity error

Facility LOG_PFE

ASP_L2TP_TUN_GRP_CHG_FAIL_INVLD

System Log Message Unable to change tunnel group *group-id*: ID is invalid

Description The Layer 2 Tunneling Protocol (L2TP) could not change the tunnel group with the indicated internal ID, because the ID is invalid.

Type Error: An error occurred

Severity error

Facility LOG_PFE

ASP_L2TP_TUN_GRP_DEL_FAIL_INVLD

System Log Message Unable to delete tunnel group *group-id*: ID is invalid

Description The Layer 2 Tunneling Protocol (L2TP) could not delete the tunnel group with the indicated internal ID, because the ID is invalid.

Type Error: An error occurred

Severity error

Facility LOG_PFE

ASP_NAT_OUTOF_ADDRESSES

System Log Message natpool *nat-pool-name* is out of addresses

Description Network Address Translation (NAT) services could not allocate an address from the indicated NAT pool, because no addresses were available.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_PFE

ASP_NAT_OUTOF_PORTS

System Log Message natpool *nat-pool-name* is out of ports

Description Network Address Translation (NAT) services could not allocate a port from the indicated NAT pool, because no ports were available.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_PFE

ASP_NAT_POOL_RELEASE

System Log Message natpool release *address:port[count]*

Description Network Address Translation (NAT) services made the indicated number of ports available in the pool for the indicated address, starting at the indicated port number.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

ASP_NAT_PORT_BLOCK_ACTIVE

System Log Message *source-address ->
nat-source-address:nat-source-port-range-start-nat-source-port-range-end 0xvalue1*

Description When interim port block logging is configured, an interim port block log is generated at the configured interval which carries all the information logged in ASP_NAT_PORT_BLOCK_ALLOC including the time stamp.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

ASP_NAT_PORT_BLOCK_ALLOC

System Log Message *source-address ->
nat-source-address:nat-source-port-range-start-nat-source-port-range-end*

Description When Port block allocation is configured, a port block will be allocated and assigned to a private IP if it is a first connection from that private IP or if there are no ports available in previously allocated port block for that private IP. This has the range of NAT ports and NAT IP allocated for that private IP.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

ASP_NAT_PORT_BLOCK_RELEASE

System Log Message *source-address ->
nat-source-address:nat-source-port-range-start-nat-source-port-range-end 0xvalue1*

Description Allocated port block is released.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

ASP_NAT_RULE_MATCH

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name) application: application,
source-interface-nameseparatorsource-address:source-port ->
destination-addressdestination-port, event-type rule-set: rule-set-name, rule: rule-name,
term: term-name*

Description A packet matched the indicated term in the indicated Network Address Translation (NAT) rule. If the rule belongs to a rule set, the rule set name is also displayed. The matching packet contained the indicated information about its protocol (numerical identifier and

name), application, source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error
Severity info
Facility LOG_PFE

ASP_PCP_NAT_MAP_CREATE

System Log Message *source-address subscriber-address:source-port -> pcp-server-address
nat-source-address:nat-source-port*

Description Create the request mapping

Type Event: This message reports an event, not an error
Severity info
Facility LOG_PFE

ASP_PCP_NAT_MAP_DELETE

System Log Message *source-address subscriber-address:source-port -> pcp-server-address
nat-source-address:nat-source-port*

Description Delete the request mapping

Type Event: This message reports an event, not an error
Severity info
Facility LOG_PFE

ASP_PCP_TPC_ALLOC_ERR

System Log Message Memory allocation failed for Third party client: *source-address*

Description Allocation error for third party context

Type Event: This message reports an event, not an error
Severity info
Facility LOG_PFE

ASP_PCP_TPC_NOT_FOUND

System Log Message Third party context not found *source-address*

Description PCP third party context is not found

Type Event: This message reports an event, not an error
Severity info
Facility LOG_PFE

ASP_PGCP_IPC_MSG_WRITE_FAILED

System Log Message	Unable to write IPC message (type <i>message-type</i> , subtype <i>message-subtype</i>): status code <i>status</i>
Description	The Packet Gateway Control Protocol (PGCP) client on the MultiServices PIC could not write an interprocess communication (IPC) message to the end of its pipe.
Type	Error: An error occurred
Severity	error
Facility	LOG_PFE
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18755 .

ASP_PGCP_IPC_PIPE_WRITE_FAILED

System Log Message	Unable to write IPC message (type <i>message-type</i> , subtype <i>message-subtype</i>) to pipe: status code <i>status</i>
Description	The Packet Gateway Control Protocol (PGCP) client on the MultiServices PIC could not write the contents of its interprocess communication (IPC) pipe to the socket layer.
Type	Error: An error occurred
Severity	error
Facility	LOG_PFE
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18756 .

ASP_SFW_ALG_LEVEL_ADJUSTED

System Log Message	ALG <i>sfw-application-name</i> specified by stateful firewall or CoS rule was reduced to <i>nat-application-name</i> , because twice NAT does not support ALG <i>application</i>
Description	A twice Network Address Translation (NAT) rule is applied to the same source or destination addresses as a stateful firewall or class-of-service (CoS) rule that applies an application-level gateway (ALG) other than Internet Control Message Protocol (ICMP) or traceroute. The configuration is invalid, because only those ALGs are supported in combination with twice NAT. The ALG configured in the stateful firewall or CoS rule was ignored, and only the application configured in the twice-NAT rule was applied. The adaptive services software accomplished this internally by adjusting the indicated ALG value (which is not supported with twice NAT) to the indicated supported value.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_PFE

- Action** Change the configuration so that twice-NAT rules (defined at the [edit services nat] hierarchy level) are not applied to the same source or destination addresses as rules defined at the [edit services stateful-firewall] or [edit services cos] hierarchy level that include ALGs other than the supported ones.

ASP_SFW_ALG_PROMOTION_FAILED

- System Log Message** ALG promotion failed. Stateful firewall application *sfw-application-name* conflicts with NAT application *nat-application-name* or conflicts with QoS application; request creation of discard flow
- Description** A matching application-level gateway protocol (ALG) was found from both the indicated stateful firewall rule and either the indicated Network Address Translation (NAT) rule or a quality-of-service (QoS) rule, but the two ALGs were not at the same level.
- Type** Event: This message reports an event, not an error
- Severity** critical
- Facility** LOG_PFE
- Action** Resolve the conflicting application-protocol matching conditions in the rules at the [edit services stateful-firewall] hierarchy level and either the [edit services cos] (for QoS rules) or [edit services nat] (for NAT rules) hierarchy level.

ASP_SFW_APP_MSG_TOO_LONG

- System Log Message** *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*
- Description** The stateful firewall discarded the Transmission Control Protocol (TCP) packet with the indicated characteristics, because the packet was so large that it exhausted memory resources. The packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).
- Type** Event: This message reports an event, not an error
- Severity** notice
- Facility** LOG_PFE
- Action** Delete active flows to forcibly free memory, or wait for the system to reclaim memory. Consider creating more service sets among which resources can be divided. Otherwise, contact your technical support representative.

ASP_SFW_CHANGE_INACTIVITY_TIMER

- System Log Message** change global inactivity timer to *value1*, open timeout to *value2*, and close timeout to *value3*

Description The global inactivity timer, the close timeout, and the open timeout were set to the indicated values.

Type Event: This message reports an event, not an error

Severity critical

Facility LOG_PFE

ASP_SFW_CREATE_ACCEPT_FLOW

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name) application: application, source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type nat-information software-information*

Description The packet with the indicated characteristics matched a stateful firewall rule that has the 'accept' action, and the stateful firewall created a flow. If the flow requires Network Address Translation (NAT) services, NAT information appears at the end of the message. The matching packet contained the indicated information about its protocol (numerical identifier and name), application, source (logical interface name, IP address, and port number), and destination (IP address and port number), and if relevant, Software source and destination IP addresses

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

ASP_SFW_CREATE_DISCARD_FLOW

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name) application: application, source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The packet with the indicated characteristics matched a stateful firewall rule that has the 'discard' action, and the stateful firewall created a discard flow. The matching packet contained the indicated information about its protocol (numerical identifier and name), application, source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_PFE

ASP_SFW_CREATE_REJECT_FLOW

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name) application: application, source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The packet with the indicated characteristics matched a stateful firewall rule that has the 'reject' action, and the stateful firewall created a reject flow. The matching packet

contained the indicated information about its protocol (numerical identifier and name), application, source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_PFE

ASP_SFW_DELETE_FLOW

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name) application: application, source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type nat-information software-information*

Description The flow with the indicated characteristics was removed from the system. If the flow required Network Address Translation (NAT) services, NAT information appears at the end of the message. The flow indicated information about its protocol (numerical identifier and name), application, source (logical interface name, IP address, and port number), destination (IP address and port number), and if relevant, Software source and destination IP addresses.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_PFE

ASP_SFW_DROP_FLOW_DELETE

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name) application: application, source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type nat-information software-information*

Description Drop flow is deleted.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_PFE

ASP_SFW_FTP_ACTIVE_ACCEPT

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name) application: application, source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type nat-information*

Description When the stateful firewall receives PORT/EPRT commands in the control channel, it creates a flow in anticipation of an FTP data connection from client to server. The packet with the indicated characteristics matched such a flow. If the flow requires Network Address Translation (NAT) services, NAT information appears at the end of the message. The matching packet contained the indicated information about its protocol (numerical

identifier and name), application, source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_PFE

ASP_SFW_FTP_PASSIVE_ACCEPT

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name) application: application, source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type nat-information*

Description When the stateful firewall receives PASV/EPSV commands in the control channel, it creates a flow in anticipation of an FTP data connection from server to client. The packet with the indicated characteristics matched such a flow. If the flow requires Network Address Translation (NAT) services, NAT information appears at the end of the message. The matching packet contained the indicated information about its protocol (numerical identifier and name), application, source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_PFE

ASP_SFW_ICMP_ERROR_DROP

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the Internet Control Message Protocol (ICMP) error packet with the indicated characteristics, because the packet did not belong to an existing flow. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_PFE

ASP_SFW_ICMP_HEADER_LEN_ERROR

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the Internet Control Message Protocol (ICMP) packet with the indicated characteristics, because the length field in the packet header was

shorter than the minimum 8 bytes required for an ICMP packet. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_PFE

ASP_SFW_ICMP_PACKET_ERROR_LENGTH

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the Internet Control Message Protocol (ICMP) error packet with the indicated characteristics, because the packet contained fewer than 48 bytes of data, or more than 576. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_PFE

ASP_SFW_IP_FRAG_ASSEMBLY_TIMEOUT

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the packet with the indicated characteristics and all related IP fragments it had previously received, because all fragments did not arrive within the four-second reassembly timeout period. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_PFE

ASP_SFW_IP_FRAG_OVERLAP

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the packet with the indicated characteristics and all related IP fragments it had previously received, because the contents of two fragments

overlapped. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_PFE

ASP_SFW_IP_OPTION_DROP_PACKET

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the packet with the indicated characteristics, because the packet contained nonconfigured IP option types. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_PFE

ASP_SFW_IP_PACKET_CHECKSUM_ERROR

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the packet with the indicated characteristics, because the packet checksum was incorrect. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_PFE

ASP_SFW_IP_PACKET_DST_BAD

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the packet with the indicated characteristics, because the packet destination address was either a multicast address or was in the range reserved for experimental use (248.0.0.0 through 255.255.255.254). The discarded packet contained the indicated information about its protocol (numerical identifier and name),

source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_PFE

ASP_SFW_IP_PACKET_FRAG_LEN_INV

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the packet with the indicated characteristics and all related IP fragments it had previously received, because the length of a fragment was invalid. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_PFE

ASP_SFW_IP_PACKET_INCORRECT_LEN

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the IP packet with the indicated characteristics, because the packet length was invalid. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_PFE

ASP_SFW_IP_PACKET_LAND_ATTACK

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the IP packet with the indicated characteristics, because the source and destination address for the packet were the same (referred to as a land attack). The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_PFE

ASP_SFW_IP_PACKET_NOT_VERSION_4

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the IP packet with the indicated characteristics, because the packet version was not IP version 4 (IPv4). The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_PFE

ASP_SFW_IP_PACKET_PROTOCOL_ERROR

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the IP packet with the indicated characteristics, because the packet used an invalid protocol. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_PFE

ASP_SFW_IP_PACKET_SRC_BAD

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the packet with the indicated characteristics, because the packet source address was one of the following: (1) a multicast address (2) a broadcast address (3) in the range 127.0.0.0 through 127.255.255.255 (4) in the range 248.0.0.0 through 255.255.255.254, which is reserved for experimental use. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_PFE

ASP_SFW_IP_PACKET_TOO_LONG

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the IP packet with the indicated characteristics, because the packet contained more than 64 kilobytes (KB) of data (referred to as a ping-of-death attack). The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_PFE

ASP_SFW_IP_PACKET_TOO_SHORT

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the IP packet with the indicated characteristics, because the packet did not contain the minimum amount of data required. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_PFE

ASP_SFW_IP_PACKET_TTL_ERROR

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the IP packet with the indicated characteristics, because the packet had a time-to-live (TTL) value of 0 (zero). The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type	Event: This message reports an event, not an error
-------------	--

Severity notice
Facility LOG_PFE

ASP_SFW_NEW_POLICY

System Log Message install new configuration

Description A new stateful firewall policy was installed.

Type Event: This message reports an event, not an error

Severity critical

Facility LOG_PFE

ASP_SFW_NO_IP_PACKET

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall received the packet with the indicated characteristics, which was not an IP packet. The packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_PFE

ASP_SFW_NO_POLICY

System Log Message *source-address -> destination-address*No policy

Description The stateful firewall received packets with the indicated source and destination addresses. There was no matching policy for the traffic.

Type Event: This message reports an event, not an error

Severity critical

Facility LOG_PFE

ASP_SFW_NO_RULE_DROP

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the packet with the indicated characteristics, because the packet did not match and stateful firewall rules. In this case, the default action is to discard the packet. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_PFE

ASP_SFW_PING_DUPLICATED_SEQNO

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the Internet Control Message Protocol (ICMP) echo request packet with the indicated characteristics, because packet's sequence number was the same as in a previous packet. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_PFE

ASP_SFW_PING_MISMATCHED_SEQNO

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the Internet Control Message Protocol (ICMP) echo reply packet with the indicated characteristics, because the firewall had not previously received an echo request packet with the same sequence number. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_PFE

ASP_SFW_PING_OUTOF_SEQNO_CACHE

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the Internet Control Message Protocol (ICMP) echo request packet with the indicated characteristics, because it had not received echo replies for an excessive number of previously received echo requests. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_PFE

ASP_SFW_POLICY_REJECT

System Log Message	reject configuration because <i>reason</i>
Description	A newly installed stateful firewall policy was rejected for the indicated reason.

Type	Event: This message reports an event, not an error
Severity	critical
Facility	LOG_PFE

ASP_SFW_RULE_ACCEPT

System Log Message	<i>syslog-prefix error-code: proto protocol-id (protocol-name) application: application, source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type rule-set: rule-set-name, rule: rule-name, term: term-name</i>
---------------------------	---

Description	The packet with the indicated characteristics matched the indicated term in the indicated stateful firewall rule, which has an 'accept' action. If the rule belongs to a rule set, the rule set name is also displayed. The stateful firewall accepted the flow to which the packet belongs. The matching packet contained the indicated information about its protocol (numerical identifier and name), application, source (logical interface name, IP address, and port number), and destination (IP address and port number).
--------------------	---

Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_PFE

ASP_SFW_RULE_DISCARD

System Log Message	<i>syslog-prefix error-code: proto protocol-id (protocol-name) application: application, source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type rule-set: rule-set-name, rule: rule-name, term: term-name</i>
---------------------------	---

Description	The packet with the indicated characteristics matched the indicated term in the indicated stateful firewall rule, which has a 'discard' action. If the rule belongs to a rule set, the rule set name is also displayed. The stateful firewall discarded the packet. The matching packet contained the indicated information about its protocol (numerical identifier and name), application, source (logical interface name, IP address, and port number), and destination (IP address and port number).
--------------------	--

Type	Event: This message reports an event, not an error
Severity	notice

Facility LOG_PFE

ASP_SFW_RULE_REJECT

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name) application: application, source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type rule-set: rule-set-name, rule: rule-name, term: term-name*

Description The packet with the indicated characteristics matched the indicated term in the indicated stateful firewall rule, which has a 'reject' action. If the rule belongs to a rule set, the rule set name is also displayed. If the packet used the User Datagram Protocol (UDP), the stateful firewall generated an Internet Control Message Protocol (ICMP) error message. If the packet used the Transmission Control Protocol (TCP), the stateful firewall generated an RST packet. The matching packet contained the indicated information about its protocol (numerical identifier and name), application, source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_PFE

ASP_SFW_SYN_DEFENSE

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the packet with the indicated characteristics, because the Transmission Control Protocol (TCP) handshake that is used to establish a session did not complete quickly enough. The time limit is set by the 'open-timeout' statement at the [edit interfaces <services-interface> services-options] hierarchy level or is four seconds by default. The event was reported to intrusion detection services (IDS) and can cause IDS to activate SYN cookie protection. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_PFE

Cause Possible causes for the handshake failure include the following: (1) sequence numbers did not match in a SYN packet and a previous SYN packet (the second packet was not a retransmission) (2) sequence numbers did not match in a SYN/ACK packet and a previous SYN packet (3) either or both a SYN/ACK packet and an ACK packet did not arrive at the firewall within the time limit.

ASP_SFW_TCP_BAD_SYN_COOKIE_RESP

System Log Message	<i>syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type</i>
Description	The stateful firewall discarded the Transmission Control Protocol (TCP) ACK packet with the indicated characteristics, either because it is the first packet in a session, or because its sequence number did not match the sequence number in the SYN/ACK packet that the firewall previously generated for the session. The firewall generates SYN/ACK packets when SYN cookie protection is activated. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_PFE

ASP_SFW_TCP_FLAGS_ERROR

System Log Message	<i>syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type</i>
Description	The stateful firewall discarded the Transmission Control Protocol (TCP) packet with the indicated characteristics, because the flags in the packet were set in one of the following combinations: (1) FIN and RST (2) SYN and one or more of FIN, RST, and URG. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_PFE

ASP_SFW_TCP_HEADER_LEN_ERROR

System Log Message	<i>syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type</i>
Description	The stateful firewall discarded the Transmission Control Protocol (TCP) packet with the indicated characteristics, because the length field in the packet header was shorter than the minimum 20 bytes required for a TCP packet. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_PFE

ASP_SFW_TCP_NON_SYN_FIRST_PACKET

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the Transmission Control Protocol (TCP) packet with the indicated characteristics, because it was the first packet in the TCP session but the SYN flag was not set. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_PFE

ASP_SFW_TCP_PORT_ZERO

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the Transmission Control Protocol (TCP) packet with the indicated characteristics, because the source or destination port specified in the packet was zero (0). The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_PFE

ASP_SFW_TCP_RECONSTRUCT_DROP

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the Transmission Control Protocol (TCP) packet with the indicated characteristics, because the session to which the packet belongs violated TCP standards. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error

Severity	notice
Facility	LOG_PFE
Cause	Possible causes include the following: (1) the amount of previously received but unacknowledged data exceeded the TCP window (2) there were sequence number errors (gaps in the sequence or packets with overlapping numbers).

ASP_SFW_TCP_SCAN

System Log Message	<i>syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type</i>
Description	The stateful firewall received a Transmission Control Protocol (TCP) RST packet from a server, indicating that the server rejected a connection attempt directed to the indicated destination address and port. The event was reported to intrusion detection services (IDS) and can cause IDS to activate SYN cookie protection. The RST packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_PFE

ASP_SFW_TCP_SEQNO_AND_FLAGS_ZERO

System Log Message	<i>syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type</i>
Description	The stateful firewall discarded the Transmission Control Protocol (TCP) packet with the indicated characteristics, because the packet's sequence number was 0 (zero) and no flags were set. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_PFE

ASP_SFW_TCP_SEQNO_ZERO_FLAGS_SET

System Log Message	<i>syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type</i>
Description	The stateful firewall discarded the Transmission Control Protocol (TCP) packet with the indicated characteristics, because the packet's sequence number was 0 (zero) and one or more of the FIN, PSH, and RST flags were set. The discarded packet contained the

indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_PFE

ASP_SFW_UDP_HEADER_LEN_ERROR

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the User Datagram Protocol (UDP) packet with the indicated characteristics, because the length field in the packet header was shorter than the minimum 8 bytes required for an UDP packet. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_PFE

ASP_SFW_UDP_PORT_ZERO

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the User Datagram Protocol (UDP) packet with the indicated characteristics, because the source or destination port specified in the packet was zero (0). The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_PFE

ASP_SFW_UDP_SCAN

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall received an Internet Control Message Protocol (ICMP) error message from a server running at the indicated destination address and User Datagram Protocol

(UDP) port. The error packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_PFE

ASP_SFW_VERY_BAD_PACKET

System Log Message *syslog-prefix error-code: proto protocol-id (protocol-name), source-interface-nameseparatorsource-address:source-port -> destination-addressdestination-port, event-type*

Description The stateful firewall discarded the packet with the indicated characteristics, because the packet was malformed. The discarded packet contained the indicated information about its protocol (numerical identifier and name), source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type Event: This message reports an event, not an error
Severity critical
Facility LOG_PFE

ASP_SVC_SET_MAX_FLOWS_EXCEEDED

System Log Message Number of flows (currently *current-flows*) exceeded configured limit (*maximum-value*) *count* times in previous 60 seconds

Description A flow was not created for a service and service set, because the current number of flows for all supported services exceeded the limit configured with the 'max-flows' statement at the [edit services service-set <service-set-name>] hierarchy level. The message appears once per minute and reports the number of times in the previous 60 seconds that the system noted the excessive number of flows.

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_PFE

CHAPTER 13

AUDITD System Log Messages

This chapter describes messages with the **AUDITD** prefix. They are generated by the audit process (auditd), which notifies the RADIUS accounting server of user activity on the routing platform, such as login, logout, and execution of command-line interface (CLI) commands.

AUDITD_RADIUS_AV_AUTH_TYPE_ERROR

System Log Message	Unable to add authentication type to <i>type</i> record: <i>error-message</i>
Description	The audit process (auditd) experienced the indicated error when building RADIUS Authentication-type attribute-value (AV) pair for the login accounting request.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

AUDITD_RADIUS_AV_ERROR

System Log Message	Unable to create <i>type</i> record: <i>error-message</i>
Description	The audit process (auditd) experienced the indicated error when building RADIUS attribute-value (AV) pairs for the indicated type of accounting request, which can be a login or logout event, or a command issued in the CLI.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

AUDITD_RADIUS_AV_PORT_ERROR

System Log Message	Unable to add port number to <i>type</i> record: <i>error-message</i>
Description	The audit process (auditd) experienced the indicated error when building RADIUS Remote-port attribute-value (AV) pair for the login accounting request.
Type	Error: An error occurred
Severity	error

Facility LOG_DAEMON

AUDITD_RADIUS_OPEN_FAILED

System Log Message *function-name: unable to create RADIUS object handle (error-message)*

Description The audit process (auditd) could not create a RADIUS object handle, which it uses for various RADIUS operations.

Type Error: An error occurred

Severity emergency

Facility LOG_DAEMON

Action For more information, see
<http://kb.juniper.net/InfoCenter/index?page=content&id=KB18757>.

AUDITD_RADIUS_REQ_CREATE_FAILED

System Log Message Unable to create RADIUS request: *error-message*

Description The audit process (auditd) could not create a RADIUS accounting request for the indicated reason.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action For more information, see
<http://kb.juniper.net/InfoCenter/index?page=content&id=KB18758>.

AUDITD_RADIUS_REQ_DROPPED

System Log Message Discarded Accounting-Request message; no RADIUS server responded

Description The audit process (auditd) gathers information about system accounting events from other system processes and sends the information to RADIUS servers in an Accounting-Request message. The process repeatedly sent a message to all configured RADIUS servers without receiving a response, so it discarded the message.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause The RADIUS accounting servers are not correctly configured or are unreachable, or the server applications are not responding.

AUDITD_RADIUS_REQ_SEND_ERROR

System Log Message *function-name: error-message*

Description	The audit process (auditd) experienced the indicated error when it requested accounting information from a RADIUS server.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

AUDITD_RADIUS_REQ_TIMED_OUT

System Log Message	Retransmitted request to RADIUS server <i>radius-server</i>
Description	The audit process (auditd) gathers information about system accounting events from other system processes and sends the information to RADIUS servers in an Accounting-Request message. After failing to receive a response from the indicated server, auditd waited for a timeout period and resent the message.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	The RADIUS server is not responding. Possible reasons include (a) the server machine is down, too busy, or unreachable (b) the server application is down or too busy (c) the shared RADIUS secret sent by auditd does not match the secret on the server.

AUDITD_RADIUS_SERVER_ADD_ERROR

System Log Message	Unable to add RADIUS server <i>radius-server: error-message</i>
Description	The audit process (auditd) read the RADIUS accounting server configuration, but could not add the indicated server to the internal structure used to track servers.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see KB18757.

AUDITD_SOCKET_FAILURE

System Log Message	<i>function-name</i> : unable to <i>operation</i> socket (<i>error-message</i>)
Description	The audit process (auditd) listens on a Transmission Control Protocol (TCP) socket for system accounting events reported by other processes on the routing platform. The indicated socket operation failed with the indicated error.

Type	Error: An error occurred
Severity	emergency
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18759 .

AUDITD_TACPLUS_SHM_CREATE_FAILED

System Log Message	auditd shm create failed. stopping auditd-tacplus
Description	The audit process for tacplus failed to initialize shared memory for accounting records. This can be a temporary issue with system free memory. Please try configuring tacplus accounting again.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHAPTER 14

AUTHD System Log Messages

This chapter describes messages with the **AUTHD** prefix. They are generated by the generic authentication service process (authd) which is a security service that verifies an identity that is claimed by or for a system entity.

AUTHD_ACCOUNTING_STATE_CHANGE

System Log Message	New state (<i>new-state</i>)
Description	CLI command suspends or resumes accounting or begins baseline. Baseline completes when all volume and time counters have been baselined.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_AUTH

AUTHD_ACCT_ON_ACK_NOT_RECEIVED

System Log Message	Acct-On-Response is not yet received for profile: <i>profile-name</i> , logical system: <i>logical-system-name</i> , routing instance: <i>routing-instance</i>)
Description	The generic authentication service process (authd) did not send any authentication/accounting packet to the RADIUS server because it has not received Acct-On-Ack from the RADIUS server.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH

AUTHD_AUTH_CREATE_FAILED

System Log Message	Unable to allocate authentication handle: <i>error-message</i>
Description	The generic authentication service process (authd) could not allocate an authentication object for the indicated reason.
Type	Error: An error occurred
Severity	error

Facility LOG_AUTH

Action For more information see,
<http://kb.juniper.net/InfoCenter/index?page=content&id=KB18760>.

AUTHD_AUTH_SERVER_STATUS_CHANGE

System Log Message Status of authentication server *destination-address:destination-port* set to *new-state* (profile *profile-name*)

Description Authentication server status is changed to DOWN if it is unavailable, and it is again set to UP after revert interval timer expires

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_AUTH

AUTHD_RADIUS_GETHOSTNAME_FAILED

System Log Message Unable to obtain hostname for outgoing RADIUS message: *error-message*

Description The generic authentication service process (authd) could not obtain a hostname for an outgoing RADIUS message.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

Action For more information see, KB18760.

AUTHD_SERVER_INIT_BIND_FAIL

System Log Message Unable to bind to socket *file-descriptor: error-message* (errno *error-code*)

Description The generic authentication service process (authd) could not bind the server to the address specified.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

Action For more information, see
<http://kb.juniper.net/InfoCenter/index?page=content&id=KB18761>.

AUTHD_SERVER_INIT_LISTEN_FAIL

System Log Message Unable to listen on socket *file-descriptor: error-message* (errno *error-code*)

Description The generic authentication service process (authd) could not initialize listening on the server for the indicated socket.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

Action For more information, see
<http://kb.juniper.net/InfoCenter/index?page=content&id=KB18762>.

CHAPTER 15

AUTOCONF System Log Messages

This chapter describes messages with the **AUTOCONF** prefix. They are generated by the auto-configuration process (autoconfd).

AUTOCONF_AUTHENTICATE_LICENSE

System Log Message	Authentication failed due to license error. Total license failures <i>count</i>
Description	The auto-configuration process (autoconfd) failed to authenticate the clients because there were no licenses or an insufficient number of licenses. The indicated number of license failures occurred and the clients were denied access and configuration.
Type	Error: An error occurred
Severity	alert
Facility	LOG_DAEMON
Action	Add or update the license for authentication

CHAPTER 16

AUTOD System Log Messages

This chapter describes messages with the **AUTOD** prefix. They are generated by the autoinstallation process (autod), which controls the initialization of J Series Services Routers.

AUTOD_BIND_FAILURE

System Log Message	Unable to bind address to socket: <i>error-message</i>
Description	The autoinstallation process (autod) received the indicated error when it tried to bind a socket to an address.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

AUTOD_HOSTNAME_EXPANSION_FAILURE

System Log Message	Unable to expand compressed DNS domain name: <i>error-message</i>
Description	The autoinstallation process (autod) received the indicated error when it tried to expand a compressed Domain Name System (DNS) domain name.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

AUTOD_RECV_FAILURE

System Log Message	Unable to receive on socket: <i>error-message</i>
Description	The autoinstallation process (autod) received the indicated error when it tried to receive data on a socket.
Type	Error: An error occurred

Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18766 .

AUTOD_RES_MKQUERY_FAILURE

System Log Message	DNS query failed: <i>error-message</i>
Description	The autoinstallation process (autod) received the indicated error when it made a Domain Name System (DNS) query.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see KB18766.

AUTOD_SEND_FAILURE

System Log Message	Unable to send on socket: <i>error-message</i>
Description	The autoinstallation process (autod) received the indicated error when it tried to send data on a socket.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18767 .

AUTOD_SOCKET_CREATE_FAILURE

System Log Message	Unable to create socket: <i>error-message</i>
Description	The autoinstallation process (autod) received the indicated error when it tried to create a socket.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18768 .

CHAPTER 17

AV System Log Messages

This chapter describes messages with the **AV** prefix. They are generated by the antivirus scanning process (avd).

AV_PATTERN_GET_FAILED

System Log Message	AntiVirus: cannot retrieve pattern <i>error-message</i> file due to <i>error-code</i> (<i>status-code</i>).
Description	The device was unable to access or retrieve an antivirus pattern file from a server, identified by IP address and port number, through HTTP. The error code provides information you need to get help from Juniper Networks technical support
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_FIREWALL
Cause	Unable to retrieve an antivirus pattern file from the server
Action	Contact Juniper Networks technical support

AV_PATTERN_KEY_EXPIRED

System Log Message	AntiVirus: Attempt to <i>time</i> failed due to <i>date</i> , please renew to receive updates.
Description	The internal antivirus scanner was unsuccessful in downloading the antivirus pattern file, because the AV license key has been expired
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_FIREWALL
Cause	Download the antivirus pattern file while antivirus license key has been expired
Action	Renew the antivirus license key

AV_PATTERN_KL_CHECK_FAILED

System Log Message	AntiVirus: db file signature mismatch: <i>error-message</i> .
---------------------------	---

Description The device is unable to use Kaspersky's pattern file. The error message provides information you need to give Juniper Networks technical support

Type Event: This message reports an event, not an error

Severity critical

Facility LOG_FIREWALL

Cause The device is unable to use Kaspersky's pattern file

Action Contact Juniper Networks technical support. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18769>.

AV_PATTERN_TOO_BIG

System Log Message AntiVirus: The pattern file specified in server is too large(*file-size* bytes)

Description The pattern file size specified in the server initialization file (server.ini) exceeds the maximum prescribed limit

Type Event: This message reports an event, not an error

Severity alert

Facility LOG_FIREWALL

Cause The pattern file size specified in the server initialization file exceeds the limit

Action Contact Juniper Networks technical support. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18770>.

AV_PATTERN_UPDATED

System Log Message AntiVirus: Pattern file updated. Version: *version*; size: *file-size* bytes

Description The internal antivirus scanner successfully updated the pattern file and may have changed the size of the file in the process

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_FIREWALL

Cause The internal antivirus scanner successfully updated the antivirus pattern file

Action No recommended action

AV_PATTERN_WRITE_FS_FAILED

System Log Message AntiVirus: db file save failed: *error-code*

Description The device is unable to save contents of an antivirus pattern file to the file system

Type	Event: This message reports an event, not an error
Severity	critical
Facility	LOG_FIREWALL
Cause	The device is unable to save contents of an antivirus pattern file to the file system
Action	Contact Juniper Networks technical support

AV_SCANNER_READY

System Log Message	AntiVirus:The scan engine is ready.
Description	The antivirus scan engine is ready to scan the traffic
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_FIREWALL
Cause	The antivirus scan engine is ready
Action	No recommended action

AV_VIRUS_DETECTED_MT

System Log Message	AntiVirus: Virus detected: from <i>source-address:source-port</i> to <i>destination-address:destination-port</i> <i>source-zone source-zone-name filename</i> file <i>temporary-filename</i> virus name URL: http://www.viruslist.com/en/search?VN=url username <i>username</i> roles <i>roles</i>
Description	The antivirus scanner has detected a virus; the log will show source and destination port and IP, source zone, contaminated file, virus name and URL link with virus description
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_PFE

CHAPTER 18

BBE System Log Messages

This chapter describes messages with the **BBE** prefix.

BBE_MIBD_TRAP_HEADER_FAILURE

System Log Message	No memory for trap request header
Description	The bbe-mibd process could not allocate a trap header.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	The Routing Engine is low on memory.
Action	Contact your technical support representative.

BBE_MIBD_TRAP_SEND_FAILURE

System Log Message	Unable to send trap: <i>error-message</i>
Description	The bbe-mibd process could not send a trap header.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

CHAPTER 19

BFDD System Log Messages

This chapter describes messages with the **BFDD** prefix. They are generated by the Bidirectional Forwarding Detection protocol process (bfdd), which detects failures in the bidirectional path between two routing platforms.

BFDD_MIRROR_ERROR

System Log Message	Unable to establish BFD mirror connection between Routing Engines: <i>error-message</i>
Description	The Bidirectional Forwarding Detection process (bfdd) could not establish the mirror connection (which supports nonstop routing) between the master and backup Routing Engines.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Cause	The master and backup Routing Engines are running incompatible versions of the Junos OS.
Action	Update the Junos OS to compatible versions on the master and backup Routing Engines.

BFDD_MIRROR_VERSION_MISMATCH

System Log Message	Versions of BFD mirror software on Routing Engines are incompatible: <i>error-message</i>
Description	While trying to establish the mirror connection (which supports nonstop routing) between the master and backup Routing Engines, the Bidirectional Forwarding Detection process (bfdd) determined that the versions of Junos OS on the Routing Engines were incompatible.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	Update the Junos OS to compatible versions on the master and backup Routing Engines.

BFDD_READ_ERROR

System Log Message	Read error on <i>pipe-type</i> pipe: <i>reason (error-message)</i>
Description	The Bidirectional Forwarding Detection process (bfd) could not read the message available on the indicated type of pipe.
Type	Error: An error occurred
Severity	info
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18772 .

BFDD_TRAP_MHOP_STATE_DOWN

System Log Message	local discriminator: <i>session-id</i> , new state: <i>state</i> , peer addr: <i>pip-interface</i>
Description	The state changed to 'down' or 'admin down' for the indicated Bidirectional Forwarding Detection process (bfd) session.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

BFDD_TRAP_MHOP_STATE_UP

System Log Message	local discriminator: <i>session-id</i> , new state: <i>state</i> , peer addr: <i>pip-interface</i>
Description	The state changed to 'up' for the indicated Bidirectional Forwarding Detection process (bfd) session.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

BFDD_TRAP_SHOP_STATE_DOWN

System Log Message	local discriminator: <i>session-id</i> , new state: <i>state</i> , interface: <i>pip-interface</i> , peer addr: <i>remote-peer</i>
Description	The state changed to 'down' or 'admin down' for the indicated Bidirectional Forwarding Detection process (bfd) session.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

BFDD_TRAP_SHOP_STATE_UP

System Log Message	local discriminator: <i>session-id</i> , new state: <i>state</i> , interface: <i>pip-interface</i> , peer addr: <i>remote-peer</i>
Description	The state changed to 'up' for the indicated Bidirectional Forwarding Detection process (bfdd) session.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

BFDD_TRAP_STATE_DOWN

System Log Message	local discriminator: <i>session-id</i> , new state: <i>state</i>
Description	The state changed to 'down' or 'admin down' for the indicated Bidirectional Forwarding Detection process (bfdd) session.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

BFDD_TRAP_STATE_UP

System Log Message	local discriminator: <i>session-id</i> , new state: <i>state</i>
Description	The state changed to 'up' for the indicated Bidirectional Forwarding Detection process (bfdd) session.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

BFDD_WRITE_ERROR

System Log Message	<i>function-name</i> : write error on <i>pipe-type</i> pipe (<i>error-message</i>)
Description	The Bidirectional Forwarding Detection process (bfdd) could not write a message to the indicated type of pipe.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18773 .

CHAPTER 20

BGP System Log Messages

This chapter describes messages with the **BGP** prefix. They are generated by the Border Gateway Routing Protocol.

BGP_ADDR_NOT_FOUND

System Log Message	<i>function-name</i> : BGP peer <i>peer-name</i> local address <i>local-address</i> not found. Leaving peer idled
Description	The BGP speaker's local address was not found. The peer will be idled.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	None.

BGP_ALLOC_BUFFER_ALREADY_EXISTS

System Log Message	<i>function-name</i> : buffer already allocated, something screwed up!!
Description	BGP encountered an error while allocating the requested buffer. The buffer already exists and won't be allocated.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Action	None.

BGP_BIND_FAILED_ADDR_UNAVAILABLE

System Log Message	<i>function-name</i> : peer <i>peer-name</i> local address <i>local-address</i> unavailable, connection failed
Description	BGP was not able to bind the local address to the socket since the address is unavailable. The peer will be restarted.
Type	Event: This message reports an event, not an error

Severity warning
Facility LOG_DAEMON
Action None.

BGP_CEASE_PREFIX_LIMIT_EXCEEDED

System Log Message *peer-name*: Shutting down peer due to exceeding configured *message(limit)* for *nlri-type* *nlri: prefix-count* (instance *instance*)

Description The number of prefixes received/accepted on the BGP session exceeds the configured maximum limit. The BGP session with the peer will be torn down.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

Action BGP session will be reestablished but may be torn down again if the local speaker receives/accepts the same number of prefixes. You may want to modify the configuration statement to use a higher value for the received/accepted number of prefixes.

BGP_CFG_PATH_ATTRIBUTE_WARNING

System Log Message An attribute is configured to be both dropped and ignored. Drop path attribute will take precedence and the attribute will be dropped.

Description drop-path-attributes and ignore-path-attributes knob is configured for the same attribute. drop-path-attributes will take precedence and attribute will be dropped.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

BGP_CONNECT_FAILED

System Log Message bgp_connect_start: connect *peer-name*: *error-message*

Description There was an error connecting the socket to the addresss.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

Action None.

BGP_CONNECT_GET_SOCK_ERROR

System Log Message *function-name*: task_get_addr_local(*local-address*): *error-message*

Description There was an error connecting the non-blocking socket to the address immediately because BGP was not able to determine the local address bound to the socket file descriptor.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

Action None.

BGP_CONNECT_SOCK_SHUTDOWN

System Log Message bgp_peer_connected: Connection to *local-address* refused

Description There was an error connecting the non-blocking socket to the address immediately perhaps because the socket was shutdown (received a TCP RST) while BGP was trying to connect with the peer.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

Action None.

BGP_COPY_BUFFER_ALREADY_EXISTS

System Log Message *function-name*: destination already has buffer allocated!!

Description BGP encountered an error while copying the buffer to another structure. The destination structure already has a buffer allocated. The buffer pointed by the destination structure will be freed before copying the contents from the source.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

Action None.

BGP_ERROR_SENDING_KEEPALIVE

System Log Message *function-name*: error sending KEEPALIVE to *peer-name*: *error-message*

Description BGP failed to send keepalive to this peer. The BGP peer will be closed.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

Action None.

BGP_ERROR_UNEXPECTED_LOCAL_PREF

System Log Message *bgp_rcv_v4_update: external peer *peer-name* UPDATE included LOCALPREF attribute*

Description The local speaker has received an update message with a local attribute from an external peer.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

Action None.

BGP_FLUSH_FAILED_AFTER_RETRYING

System Log Message *function-name: sending to *peer-name* (sent *num-bytes-sent*, *num-bytes* remainargument) looping: *error-message**

Description The write call by BGP returned with soft error on multiple tries. The corresponding bgp peer will be closed.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

Action None.

BGP_FREE_NONEXISTENT_BUFFER

System Log Message *function-name: buffer not present, something screwed up!!*

Description BGP encountered an error while freeing the requested buffer. The buffer does not exist and won't be freed.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

Action None.

BGP_GATHER_FLUSH_FAILED

System Log Message *bgp_gather_timeout: Writing *num-bytes* bytes to *peer-name* failed: errno *error-code*, *error-message**

Description Write call by BGP returned with a hard error for this socket while attempting to flush the gather buffer.

Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Action	None.

BGP_IGNOREING_INVALID_PREFIX

System Log Message *function-name: peer peer-name UPDATE ignoring invalid unreachable route route-prefix/prefix-length (num-bytes of num-bytes-sent)*

Description The unreachable route received in the update message will be ignored as the prefix is invalid.

Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Action	None.

BGP_NLRI_MISMATCH

System Log Message *function-name: mismatch NLRI with peer-name: peer: <peer-nlri-type> (peer-nlri) us: <nlri-type> (nlri)*

Description The peer has requested some NLRIs during capability negotiation that are not supported by the local speaker. The session will settle for the common set among the one's advertised by the peer and us.

Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	None.

BGP_NO_ADDRESS_BOUND_TO_SOCKET

System Log Message *function-name: task_get_addr_local(): error-message*

Description The local address to which the socket is bound could not be ascertained perhaps because a TCP RST was received. Connection will not be accepted.

Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Action	None.

BGP_NO_INCOMING_INTERFACE_FOUND

System Log Message	<i>function-name</i> : Connection received from <i>peer-address</i> , no incoming interface
Description	The connection request packet received on the TCP socket from the peer had no matching interface. Connection will not be accepted.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Action	None.

BGP_OPEN_INTERNAL_VERSION_ERROR

System Log Message	<i>function-name</i> : internal error! peer <i>peer-name</i> , version <i>version</i>
Description	BGP attempted to send an open message but encountered an internal error, viz., unsupported BGP version number configured. The routing process will now exit.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Action	You may want to rectify the configuration to use a supported BGP version.

BGP_ORF_BAD_MSG_HEADER

System Log Message	<i>peer-name</i> : ORF msg header too short (<i>length</i>)
Description	ORF message length is less than minimum message length. The ORF message won't be processed.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Action	None.

BGP_ORF_LEN_EXCEEDS_MAX_PFXLEN

System Log Message	<i>peer-name</i> : ORF type prefix-based invalid length - seqnum <i>sequence-number</i> (length <i>orf-pfx-len</i> > max_plen <i>max-pfx-len</i>)
Description	BGP orf entry's prefix has an invalid length. The length is greater than the maximum prefix length of BGP orf entry's prefix.
Type	Event: This message reports an event, not an error

Severity error
Facility LOG_DAEMON
Action None.

BGP_ORF_MAXLEN_EXCEEDS_MAX_PFXLEN

System Log Message *peer-name*: ORF type prefix-based invalid maxlen seqnum *sequence-number* (maxlen *orf-pfx-max-len* > max_plen *max-pfx-len*)

Description BGP orf entry prefix has an invalid max length. The maxlen is less than the maximum prefix length of BGP orf entry's prefix.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

Action None.

BGP_ORF_MAXLEN_LESS_THAN_MINLEN

System Log Message *peer-name*: ORF type prefix-based invalid maxlen seqnum *sequence-number* (maxlen *orf-pfx-max-len* minlen < *orf-pfx-min-len*)

Description BGP orf entry prefix has an invalid max length. The maxlen is less than the min prefix length.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

Action None.

BGP_ORF_MAX_PFXLEN_LESS_THAN_LEN

System Log Message *peer-name*: ORF type prefix-based invalid maxlen seqnum *sequence-number* (maxlen *orf-pfx-max-len* length < *orf-pfx-len*)

Description BGP orf entry prefix has an invalid prefix max length. The max prefix length is less than BGP orf entry's prefix length.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

Action None.

BGP_ORF_MINLEN_EXCEEDS_MAX_PFXLEN

System Log Message	<i>peer-name</i> : ORF type prefix-based invalid minlen seqnum <i>sequence-number</i> (minlen <i>orf-pfx-min-len</i> > max_plen <i>max-pfx-len</i>)
Description	BGP orf entry prefix has an invalid min length. The minlen is greater than the maximum prefix length of BGP orf entry's prefix.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Action	None.

BGP_ORF_MINLEN_LESS_THAN_LEN

System Log Message	<i>peer-name</i> : ORF type prefix-based invalid minlen seqnum <i>sequence-number</i> (minlen <i>orf-pfx-min-len</i> = <i>length</i> < <i>orf-pfx-len</i>)
Description	BGP orf entry's prefix has an invalid min length. The minlen is less than or equal to BGP orf entry's prefix length.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Action	None.

BGP_ORF_PREFIX_BAD_LENGTH

System Log Message	<i>peer-name</i> : ORF msg type <i>orf-type</i> , bad length (<i>length</i>)
Description	ORF message read has an invalid length and won't be processed.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Action	None.

BGP_ORF_PREFIX_INVALID_LENGTH

System Log Message	<i>peer-name</i> : ORF type prefix-based invalid length - seqnum <i>sequence-number</i> (<i>length</i> <i>orf-pfx-len</i> > <i>len</i> <i>length</i>)
Description	Prefix-based ORF request can't be processed because prefix is invalid.
Type	Event: This message reports an event, not an error

Severity error
Facility LOG_DAEMON
Action None.

BGP_ORF_PREFIX_LESS_THAN_MINLEN

System Log Message *peer-name*: ORF type prefix-based length *length* is too short

Description Prefix-based ORF request can't be processed because prefix length is less than the minimum ORF prefix length.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

Action None.

BGP_ORF_PREFIX_LIMIT_EXCEEDED

System Log Message *peer-name*: Ignore ADD prefix-based ORF *nlri* *nlri-type* with seq *sequence-number* as orf count *count* reached max limit

Description Prefix-based ORF can't be added because prefix limit has been reached for this peer and *nlri*.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

Action None.

BGP_PREFIX_LIMIT_EXCEEDED

System Log Message *peer-name*: Configured *message(limit)* exceeded for *nlri-type* *nlri*: *prefix-count* (instance *instance*)

Description The number of prefixes received/accepted on the BGP session exceeds the configured maximum limit.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

Action You may want to modify the configuration statement to use a higher value for the received/accepted number of prefixes.

BGP_PREFIX_THRESH_EXCEEDED

System Log Message	<i>peer-name</i> : Configured <i>message</i> threshold(<i>percentage-value</i>) exceeded for <i>nlri-type</i> <i>nlri</i> : <i>prefix-count</i> (instance <i>instance</i>)
Description	The number of prefixes received on the BGP session exceeds the specified percentage of the configured maximum limit.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	You may want to modify the configuration statement to use a higher percentage threshold value for the received/accepted number of prefixes.

BGP_REFRESH_FOR_UNNEGOTIATED_NLRI

System Log Message	<i>peer-name</i> : received refresh request for NLRI <i>nlri-type</i> (<i>afi=afi</i> , <i>safi=safi</i>) not negotiated in this session
Description	The peer has sent a BGP refresh message for an <i>nlri</i> that was not negotiated. Refresh will not be scheduled for tables corresponding to this NLRI.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	None.

BGP_RESET_PENDING_CONNECTION

System Log Message	<i>peer-name</i> : resetting pending active connection
Description	The local BGP speaker received an open message in the connect state. The corresponding peer will be restarted.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	None.

BGP_SET_INTERFACE_FAILED

System Log Message	<i>function-name</i> : BGP peer <i>peer-name</i> interface not found. Leaving peer idled
Description	The local BGP speaker needs a shared interface. The interface was not found and the peer will be idled.

Type Event: This message reports an event, not an error
Severity warning
Facility LOG_DAEMON
Action None.

BGP SOCK_ADDR_NOT_FOUND

System Log Message *function-name: task_get_addr_local(peer-name): error-message*

Description BGP was unable to ascertain the socket address that is bound to this socket file descriptor.

Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON
Action None.

BGP_SPOOL_FLUSH_CONNECTION_CLOSED

System Log Message *function-name: sending num-bytes (sent num-bytes-sent) bytes to peer-name: connection closed*

Description Write call by BGP failed because the connection was closed.

Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON
Action None.

BGP_SPOOL_FLUSH_FAILED

System Log Message *function-name: sending num-bytes (sent num-bytes-sent) bytes to peer-name failed: error-message*

Description Write call by BGP returned with a hard error for this socket. The corresponding bgp peer will be closed.

Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON
Action None.

BGP_UNEXPECTED_MESSAGE_TYPE

System Log Message	<i>function-name: peer peer-name: message-type arrived, expected expected-type argument expected-type2</i>
Description	The message type received from the BGP peer is not the expected message type. The BGP peer will be shutdown.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	None.

BGP_UNUSABLE_ASPATH

System Log Message	<i>function-name: peer peer-name AS peer-as received path with bad AS path</i>
Description	The local BGP speaker received an update with an AS path that is not usable. The corresponding route will be rejected.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Action	None.

BGP_UNUSABLE_NEXTHOP

System Log Message	<i>function-name: peer peer-name next hop next-hop-address reason, ignoring routes in this update</i>
Description	The nexthop of the route is not usable. BGP will ignore all the routes in this update.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	None.

BGP_UPDATE_CONTAINS_GARBAGE

System Log Message	<i>function-name: peer peer-name UPDATE zero attribute length followed by num-bytes bytes of garbage</i>
Description	The update received from the peer has a zero path attribute length and contains garbage beyond the attribute length field.
Type	Event: This message reports an event, not an error

Severity warning
Facility LOG_DAEMON
Action None.

BGP_UPDATE_MISSING_PREFIXES

System Log Message *function-name: peer peer-name* UPDATE has path attributes but no reachable route prefixes.

Description The local speaker has received an update message with path attributes but no reachable route prefixes.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

Action None.

BGP_WRITE_CONNECTION_CLOSED

System Log Message bgp_send: sending *num-bytes* bytes to *peer-name*: connection closed

Description Write call by BGP failed because the connection was closed.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

Action None.

BGP_WRITE_FAILED

System Log Message bgp_send: sending *num-bytes* bytes to *peer-name* failed: *error-message*

Description Write call by BGP returned with a hard error for this socket.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

Action None.

BGP_WRITE_FAILED_AFTER_RETRYING

System Log Message bgp_send: sending to *peer-name* looping: *error-message*

Description BGP write failed because it encountered soft error on multiple tries.

Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Action	None.

BGP_WRITE_WOULD_BLOCK

System Log Message *bgp_send: sending *num-bytes* bytes to *peer-name* blocked (no spooling requested):
error-message*

Description BGP write to a non-blocking file descriptor would block as there is no buffer space available with the socket.

Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Action	None.

CHAPTER 21

BOOTPD System Log Messages

This chapter describes messages with the **BOOTPD** prefix.

BOOTPD_ARG_ERR

System Log Message	Ignoring unknown option <i>-option</i>
Description	The indicated option was provided on the 'tnp.bootpd' command line and is invalid. The boot parameter process (tnp.bootpd) initialized but ignored the invalid option.
Type	Error: An error occurred
Severity	warning
Facility	ANY
Action	Remove the invalid option from the 'tnp.bootpd' command line.

BOOTPD_BAD_ID

System Log Message	Unexpected ID 0 <i>assembly-id</i>
Description	As each hardware component on the routing platform initializes, it requests a boot string from the boot parameter process (tnp.bootpd). The boot strings are defined in the configuration file tnp.bootpd. A request failed because it included the indicated assembly ID, for which there is no definition in the file.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY

BOOTPD_BOOTSTRING

System Log Message	Boot string: <i>boot-string</i>
Description	As each hardware component on the routing platform initializes, it requests a boot string from the boot parameter process (tnp.bootpd). tnp.bootpd responded with the indicated boot string.
Type	Event: This message reports an event, not an error

Severity info
Facility ANY

BOOTPD_CONFIG_ERR

System Log Message Problems with configuration file '*filename*', using defaults

Description The boot parameter process (tnp.bootpd) could not read the indicated configuration file, so it initialized using default settings defined at compile time.

Type Error: An error occurred

Severity error

Facility ANY

Action Correct the configuration file.

BOOTPD_CONF_OPEN

System Log Message Unable to open configuration file '*filename*'

Description The boot parameter process (tnp.bootpd) could not open the indicated configuration file, so it initialized using default settings defined at compile time.

Type Event: This message reports an event, not an error

Severity notice

Facility ANY

Action Contact your technical support representative.

BOOTPD_DUP_PIC_SLOT

System Log Message Duplicate default value defined for PIC *pic-slot* in FPC *fpc-slot*

Description As each hardware component on the routing platform initializes, it requests a boot string from the boot parameter process (tnp.bootpd). The boot strings are defined in the configuration file for tnp.bootpd. There was more than one definition in the file for the indicated PIC slot in the indicated Flexible PIC Concentrator (FPC), so tnp.bootpd used the first definition it found.

Type Event: This message reports an event, not an error

Severity notice

Facility ANY

Action Remove the extra definitions from the configuration file.

BOOTPD_DUP_REV

System Log Message Duplicate revision: *major-version.minor-version*

Description	As each hardware component on the routing platform initializes, it requests a boot string from the boot parameter process (tnp.bootpd). The boot strings are defined in the configuration file for tnp.bootpd. There was more than one definition in the file for the indicated revision of a component, so tnp.bootpd used the first definition it found.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY
Action	Remove the extra definitions from the configuration file.

BOOTPD_DUP_SLOT

System Log Message	Duplicate slot default: <i>slot</i>
Description	As each hardware component on the routing platform initializes, it requests a boot string from the boot parameter process (tnp.bootpd). The boot strings are defined in the configuration file for tnp.bootpd. There was more than one definition in the file for the indicated slot (combination of component assembly ID and revision), so tnp.bootpd used the first definition it found.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY
Action	Remove the extra definitions from the configuration file.

BOOTPD_HWDB_ERROR

System Log Message	Operation in chassis hardware database failed: <i>error-message</i>
Description	The boot parameter process (tnp.bootpd) could not complete an operation in the hardware database maintained by the chassis process (chassisd), for the indicated reason.
Type	Error: An error occurred
Severity	error
Facility	ANY
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18774 .

BOOTPD_MODEL_CHK

System Log Message	Unexpected ID <i>Oxidentifier</i> for model <i>model</i>
Description	As each hardware component on the routing platform initializes, it requests a boot string from the boot parameter process (tnp.bootpd). A request failed because it included the indicated assembly ID, which is inconsistent with the routing platform's model number.

Type	Error: An error occurred
Severity	warning
Facility	ANY
Action	Contact your technical support representative.

BOOTPD_NEW_CONF

System Log Message	New configuration installed
Description	The boot parameter process (tnp.bootpd) loaded a new configuration file.
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

BOOTPD_NO_BOOTSTRING

System Log Message	No boot string found for type <i>board-type major-version.minor-version command-type</i>
Description	As each hardware component on the routing platform initializes, it requests a boot string from the boot parameter process (tnp.bootpd). The boot strings are defined in the configuration file for tnp.bootpd. The file did not include a boot string for the hardware component with the indicated characteristics.
Type	Error: An error occurred
Severity	warning
Facility	ANY
Action	Contact your technical support representative.

BOOTPD_NO_CONFIG

System Log Message	No configuration file ' <i>filename</i> ', using defaults
Description	The boot parameter process (tnp.bootpd) could not open the indicated configuration file, so it initialized using default settings defined at compile time.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY

BOOTPD_PARSE_ERR

System Log Message	<i>filename: return-value</i> parse errors on SIGHUP
Description	There was an error in the configuration file for the boot parameter process (tnp.bootpd), so it initialized using default settings defined at compile time.

Type	Error: An error occurred
Severity	error
Facility	ANY
Action	Correct the configuration file.

BOOTPD_REPARSE

System Log Message	Reparsing configuration file ' <i>filename</i> '
Description	The boot parameter process (tnp.bootpd) reparsed the indicated configuration file.
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

BOOTPD_SELECT_ERR

System Log Message	select: <i>error-message</i>
Description	The boot parameter process (tnp.bootpd) issued the select() system call, which returned the indicated error message.
Type	Error: An error occurred
Severity	warning
Facility	ANY
Action	Contact your technical support representative.

BOOTPD_TIMEOUT

System Log Message	Timeout <i>duration</i> unreasonable
Description	The indicated timeout value was specified for the -t argument on the 'tnp.bootpd' command line, or no value was provided. The value was not acceptable, so the boot parameter process (tnp.bootpd) initialized using the default value of 30 seconds.
Type	Error: An error occurred
Severity	warning
Facility	ANY
Action	Provide an acceptable value for the -t argument; acceptable values are '1' (second) and larger.

CHAPTER 22

CFMD System Log Messages

This chapter describes messages with the **CFMD** prefix. They are generated by the connectivity-fault management (CFM) process (cfmd), which supports Operation, Administration, and Maintenance (OAM) functions that are defined in the Institute of Electrical and Electronics Engineers (IEEE) 802.1ag standard for Ethernet interfaces.

CFMD_CCM_DEFECT_AIS

System Log Message	CFM defect: <i>error-message</i>
Description	A connectivity-fault management (CFM) maintenance endpoint (MEP) received an alarm indication signal (AIS) from the server level or a maintenance domain (MD) level lower than that of the MEP.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Cause	Adjacency loss or any other defect condition that brought down CFM.
Action	Log the AIS message and suppress the alarms, for the received MD level, or propagate the AIS message to higher levels.

CFMD_CCM_DEFECT_CROSS_CONNECT

System Log Message	CFM defect: <i>error-message</i>
Description	A connectivity-fault management (CFM) maintenance endpoint (MEP) received a continuity check message (CCM) that had an incorrect maintenance association (MA) ID or a maintenance domain (MD) level lower than that of the MEP, each of which indicates a cross-connect error.
Type	Event: This message reports an event, not an error
Severity	error
Facility	ANY
Cause	The configuration is invalid.

Action Check whether the configured MD name, format, and level, or the MA name or format, is different from the remote endpoint.

CFMD_CCM_DEFECT_ERROR

System Log Message CFM defect: *error-message*

Description A connectivity-fault management (CFM) maintenance endpoint (MEP) received a continuity check message (CCM) with an incorrect transmission interval or MEP ID, which indicates a configuration error.

Type Event: This message reports an event, not an error

Severity error

Facility ANY

Cause The configuration is invalid.

Action Verify that the configured continuity-check transmission interval does not differ from the remote endpoint, and that the configured MEP ID is valid.

CFMD_CCM_DEFECT_MAC_STATUS

System Log Message CFM defect: *error-message*

Description A connectivity-fault management (CFM) maintenance endpoint (MEP) received a continuity check message (CCM) that contained a 'Port Status' or 'Interface Status' type, length, value (TLV), which indicate a failed bridge port or aggregated port.

Type Event: This message reports an event, not an error

Severity error

Facility ANY

CFMD_CCM_DEFECT_NONE

System Log Message CFM defect: *error-message*

Description No defect was detected.

Type Event: This message reports an event, not an error

Severity error

Facility ANY

CFMD_CCM_DEFECT_RDI

System Log Message CFM defect: *error-message*

Description A connectivity-fault management (CFM) maintenance endpoint (MEP) received a continuity check message (CCM) that had the 'Remote Defect Indication' (RDI) bit set, which indicates that not all configured MEPs are returning CCMs to the transmitting MEP.

Type	Event: This message reports an event, not an error
Severity	error
Facility	ANY

CFMD_CCM_DEFECT_RMEP

System Log Message CFM defect: *error-message*

Description A connectivity-fault management (CFM) maintenance endpoint (MEP) did not receive three consecutive continuity check message (CCM)s from one of the other MEPs in its maintenance association (MA), which indicates a MEP failure or network failure.

Type	Event: This message reports an event, not an error
Severity	error
Facility	ANY

CFMD_CCM_DEFECT_UNKNOWN

System Log Message CFM defect: *error-message*

Description An unknown defect was detected.

Type	Event: This message reports an event, not an error
Severity	error
Facility	ANY

CFMD_PPM_READ_ERROR

System Log Message Read error on pipe from ppm: *reason (error-message)*

Description The connectivity fault management process (cfmd) could not read a message available on the read pipe from the periodic packet management process (ppmd).

Type	Error: An error occurred
Severity	error
Facility	ANY
Action	Contact your technical support representative.

CFMD_PPM_WRITE_ERROR

System Log Message *function-name*: write error on pipe to ppm: *error-message*

Description The connectivity fault management process (cfmd) could not write a message on the pipe to the periodic packet management process (ppmd).

Type	Error: An error occurred
Severity	error

Facility ANY

Action Contact your technical support representative.

CHAPTER 23

CHASSISD System Log Messages

This chapter describes messages with the **CHASSISD** prefix. They are generated by the chassis process (chassisd), which controls hardware components on the routing platform.

CHASSISD_ACQUIRE_MASTERSHIP

System Log Message	Acquire mastership notification
Description	The chassis process (chassisd) running on the master Routing Engine received a request to acquire mastership.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON
Cause	The Routing Engine was probably rebooting and graceful Routing Engine switchover is configured.

CHASSISD_ANTICF_PIM_CHECK_FAILED

System Log Message	PIM <i>pim-slot</i> failed anti-counterfeit check
Description	The indicated Physical Interface Module (PIM) failed the anti-counterfeit check performed by the chassis process (chassisd).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHASSISD_ANTICF_RE_CHECK_FAILED

System Log Message	Routing Engine failed anti-counterfeit check
Description	The Routing Engine failed the anti-counterfeit check performed by the chassis process (chassisd).
Type	Error: An error occurred
Severity	error

Facility LOG_DAEMON

CHASSISD_ANTICF_RE_ROM_READ_FAIL

System Log Message Unable to read serial number from anti-counterfeit device for Routing Engine

Description The chassis process (chassisd) could not read the serial number recorded in the ROM of the anti-counterfeit device for the Routing Engine.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_ANTICF_RE_SHA_READ_FAIL

System Log Message Unable to read SHA output from anti-counterfeit device for Routing Engine

Description The chassis process (chassisd) could not read Secure Hash Algorithm (SHA) information from the anti-counterfeit device for the Routing Engine.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_ANTICF_ROM_READ_FAILED

System Log Message Unable to read serial number from anti-counterfeit device for PIM *pim-slot*

Description The chassis process (chassisd) could not read the serial number recorded in the ROM of the anti-counterfeit device for the indicated Physical Interface Module.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_ANTICF_SHA_READ_FAILED

System Log Message Unable to read SHA output from anti-counterfeit device for PIM *pim-slot*

Description The chassis process (chassisd) could not read Secure Hash Algorithm (SHA) information from the anti-counterfeit device for the indicated Physical Interface Module (PIM).

Type Error: An error occurred

Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_ARGUMENT_ERROR

System Log Message	Unknown option <i>option</i>
Description	The indicated option, provided on the 'chassisd' command line, is invalid. The chassis process (chassisd) initialized but ignored the invalid option.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_BLOWERS_SPEED

System Log Message	Fans and impellers are now running at normal speed
Description	The fans (and impellers, if applicable) were running at the normal speed.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

CHASSISD_BLOWERS_SPEED_FULL

System Log Message	Fans and impellers being set to full speed [<i>reason</i>]
Description	For the indicated reason, the chassis process (chassisd) increased the speed of fans (and impellers, if applicable) to the maximum.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

CHASSISD_BLOWERS_SPEED_MEDIUM

System Log Message	Fans and impellers being set to intermediate speed
Description	The chassis process (chassisd) increased the speed of fans (and impellers, if applicable) to the intermediate level because of a temperature increase in the chassis.
Type	Event: This message reports an event, not an error
Severity	info

Facility LOG_DAEMON

CHASSISD_BUS_DEVICE_OPEN_FAILURE

System Log Message Unable to open '*bus-type*' bus device, error *error-message* (*error-code*)

Description The chassis process (chassisd) could not open the indicated bus device for the indicated reason.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18776>.

CHASSISD_CB_CLOCK_CHECKSUM

System Log Message Clock module on M120 CB had configuration data checksum error

Description The chassis process (chassisd) detected a checksum error for the clock module on an M120 Control Board (CB).

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

CHASSISD_CB_MASTER_BP_IGNORED

System Log Message Press of online/offline button ignored for master *fru-name fru-slot*

Description The online/offline button for the indicated control board was pressed, but the chassis process (chassisd) ignored the request. The control board for M40e and M160 routers is the Miscellaneous Control Subsystem (MCS). The control board for M320, T320, T640, MX240, MX480 and MX960 routers is the Control Board (CB).

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

Cause The control board was acting as master.

Action Switch mastership to the other control board before taking the control board offline.

CHASSISD_CB_READ

System Log Message Error reading midplane ID EEPROM, errno *error-code*

Description The chassis process (chassisd) could not read the EEPROM on the midplane.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_CB_RE_ONLINE_BP_IGNORED

System Log Message	Unable to take <i>fru-name fru-slot</i> offline because paired Routing Engine is online
Description	The online/offline button for the indicated control board was pressed, but the chassis process (chassisd) ignored the request. The control board for M40e and M160 routers is the Miscellaneous Control Subsystem (MCS). The control board for M320, T320, T640, MX240, MX480 and MX960 routers is the Control Board (CB).
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Cause	The Routing Engine paired with the indicated control board is still online.
Action	Take the Routing Engine offline before taking the control board offline.

CHASSISD_CFEB_POWER_FAILURE

System Log Message	<i>function-name</i> : unable to turn <i>state</i> power for CFEB <i>cfeb-slot</i>
Description	The chassis process (chassisd) could not turn on or turn off the power to the indicated Compact Forwarding Engine Board (CFEB).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18777 .

CHASSISD_CLEAR_CONFIG_ERROR

System Log Message	<i>function-name</i> : <i>status</i>
Description	The chassis process (chassisd) encountered an error while trying to clear the state information associated with a copy of the management process (mgd) that it spawned to commit the rescue configuration. The commit operation succeeded or failed as indicated.
Type	Error: An error occurred
Severity	error

Facility LOG_DAEMON

Cause An internal software failure occurred.

Action Contact your technical support representative.

CHASSISD_CLOCK_FAILURE

System Log Message *function-name: fru-name error-message*

Description The chassis process (chassisd) determined that the indicated clock source failed in the indicated way.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18778>.

CHASSISD_CLOCK_NOTICE

System Log Message *fru-name: message*

Description The clock-synchronization status of the indicated component (field-replaceable unit, or FRU) changed as indicated.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_DAEMON

CHASSISD_CLOCK_RESET_FAIL

System Log Message Zarlink module on Taz Base Board is not coming up after reset

Description The chassis process (chassisd) detected an error in the state of clock module.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

CHASSISD_CMB_READBACK_ERROR

System Log Message Readback error from chassis management bus for *fru-name fru-slot* ([*0xaddress*, *0xoffset*] -> *0xerror-code*)

Description The chassis process (chassisd) could not read back information from the Chassis Management Bus (CMB) about the indicated component (field-replaceable unit, or FRU).

Type Error: An error occurred

Severity	error
Facility	LOG_DAEMON
Cause	The probable cause is hardware error.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18779 .

CHASSISD_COMMAND_ACK_ERROR

System Log Message	Error occurred when <i>fru-name fru-slot</i> reported its online status: <i>error-message</i> (error code <i>error-code</i>)
Description	The chassis process requested that the indicated component (field-replaceable unit, or FRU) confirm that it was online. The indicated error occurred when the FRU sent its response. In the normal case, the chassis process performed any additional action necessary to guarantee that the FRU came online.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18780 .

CHASSISD_COMMAND_ACK_SFM_ERROR

System Log Message	<i>function-name: SFM sfm-slot</i> did not acknowledge FPC <i>fpc-slot</i> : error <i>error-message</i> (code <i>error-code</i>)
Description	The chassis process (chassisd) requires an acknowledgment from each Switching and Forwarding Module (SFM) before it registers a Flexible PIC Controller (FPC) as online. The acknowledgment message from the indicated SFM failed for the indicated FPC.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18781 .

CHASSISD_CONCAT_MODE_ERROR

System Log Message	Cannot set no-concatenated mode for FPC <i>fpc-slot</i> PIC <i>pic-slot</i>
Description	The chassis process (chassisd) could not set channelized mode for the indicated SONET/SDH Physical Interface Card (PIC). Channelized mode is configured by including the no-concatenate statement at the [edit chassis fpc 'slot' pic 'slot'] hierarchy level.

Type Event: This message reports an event, not an error
Severity warning
Facility LOG_DAEMON

CHASSISD_CONFIG_ACCESS_ERROR

System Log Message *function-name: error-message*

Description The chassis process (chassisd) experienced the indicated problem while attempting to parse the configuration database.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON
Cause An internal software failure occurred.
Action Contact your technical support representative.

CHASSISD_CONFIG_CHANGE_IFDEV_DEL

System Log Message Deleting *argument1 interface-typesdev-numberargument2* due to configuration change

Description The chassis process (chassisd) deleted the indicated interface devices due to a change in the configuration.

Type Event: This message reports an event, not an error
Severity warning
Facility LOG_DAEMON

CHASSISD_CONFIG_INIT_ERROR

System Log Message Unable to parse configuration; using defaults

Description The chassis process (chassisd) could not parse the configuration and used default values while initializing.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON
Action Contact your technical support representative.

CHASSISD_CONFIG_WARNING

System Log Message *function-name: warning-message, FPC fpc-slot PIC pic-slot*

Description The configuration that was specified for the indicated Physical Interface Card (PIC) is invalid for that type of PIC.

Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

CHASSISD_DEVICE_OPEN_ERROR

System Log Message	Unable to open <i>device-name</i> device file (errno <i>error-code</i>)
Description	The chassis process (chassisd) could not open the device file for the indicated device.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_EXEC_ERROR

System Log Message	<i>function-name: error-message</i>
Description	While trying to commit the rescue configuration, the chassis process (chassisd) encountered an error.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

CHASSISD_EXISTS

System Log Message	chassisd already running; exiting
Description	The chassis process (chassisd) exited because it discovered that another chassisd process is already running.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

CHASSISD_EXISTS_TERM_OTHER

System Log Message	Killing existing chassisd and exiting
Description	The chassis process (chassisd) discovered that another chassisd process is already running. It terminated the other process and exited.

Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

CHASSISD_FAN_FAILURE

System Log Message	<i>fru-name</i> in slot <i>fru-slot</i> failed
Description	The indicated fan or impeller failed. The chassis process (chassisd) raised an alarm and increased the speed of the remaining fans (and impellers, if applicable) to full speed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18782 .

CHASSISD_FASIC_CONFIG_COMPLETE

System Log Message	Fchip: configuration already completed
Description	The chassis process (chassisd) detected an attempt to configure an F chip on a Control Board (CB) when configuration was already complete.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHASSISD_FASIC_FTOKEN_ERROR

System Log Message	Fchip (CB <i>control-board-slot</i> , ID <i>fchip-id</i>): ftoken overflow/underflow set (<i>data</i>) at <i>address</i>
Description	The chassis process (chassisd) detected an underflow or overflow error on the indicated F chip on the indicated Control Board (CB).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18783 .

CHASSISD_FASIC_FTOKEN_INIT_ERROR

System Log Message	Fchip (CB <i>control-board-slot</i> , ID <i>fchip-id</i>): f8chip_ftoken_init() stuck in ftoken loop, <i>addr=address</i> , <i>data=data</i>
---------------------------	---

Description The chassis process (chassisd) encountered an error while initializing memory at the indicated address for the indicated F chip on the indicated Control Board (CB).

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18784>.

CHASSISD_FASIC_HSL_CONFIG_ERROR

System Log Message Fchip (CB *control-board-slot*, ID *fchip-id*): HSL configuration failed (error *error-message*)

Description The chassis process (chassisd) could not configure high speed links (HSL) for the indicated F chip on the indicated Control Board (CB).

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18785>.

CHASSISD_FASIC_HSL_LINK_ERROR

System Log Message Fchip (CB *control-board-slot*, ID *fchip-id*): link *link-id* failed because of *error-message*

Description The chassis process (chassisd) detected an error for the indicated high speed link (HSL) for the indicated F chip on the indicated Control Board (CB).

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18786>.

CHASSISD_FASIC_INIT_ERROR

System Log Message Fchips were not configured yet

Description The chassis process (chassisd) detected that F chips were not yet initialized on the Control Board (CB).

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18787>.

CHASSISD_FASIC_INPUT_DROP

System Log Message Fchip (CB *control-board-slot*, ID *fchip-id*): dropped *drop-rate* cells per second coming from Packet Forwarding Engine *pfe* on FPC *fpc-slot*

Description The Packet Forwarding Engine divides packets into smaller units called cells for more efficient processing. As the indicated F chip on the indicated Control Board (CB) processed data that was received from the indicated Packet Forwarding Engine on the indicated Flexible PIC Concentrator (FPC), it dropped the indicated number of cells per second.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18788>.

CHASSISD_FASIC_OUTPUT_DROP

System Log Message Fchip (CB *control-board-slot*, ID *fchip-id*): dropped *drop-rate* cells per second destined for Packet Forwarding Engine *pfe* on FPC *fpc-slot*

Description The Packet Forwarding Engine divides packets into smaller units called cells for more efficient processing. As the indicated F chip on the indicated Control Board (CB) processed data before sending it to the indicated Packet Forwarding Engine on the indicated Flexible Port Concentrator (FPC) for outgoing transmission, it dropped the indicated number of cells per second.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18789>.

CHASSISD_FASIC_PIO_READ_ERROR

System Log Message Fchip (CB *control-board-slot*, ID *fchip-id*): read error in *function-name()* for link#*link-id* at address *address* in register *register*

Description The indicated routine failed with a read error at the indicated address and register for the indicated F chip and link on the indicated Control Board (CB).

Type Error: An error occurred

Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18790 .

CHASSISD_FASIC_PIO_WRITE_ERROR

System Log Message	Fchip (CB <i>control-board-slot</i> , ID <i>fchip-id</i>): write error in <i>function-name()</i> for link# <i>link-id</i> at address <i>address</i> in register <i>register</i>
Description	The indicated routine failed with a write error at the indicated address and register for the indicated F chip and link on the indicated Control Board (CB).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18791 .

CHASSISD_FASIC_PLL_ERROR

System Log Message	Fchip (CB <i>control-board-slot</i> , ID <i>fchip-id</i>): unable to lock PLL
Description	The chassis process (chassisd) could not lock a phased-lock loop (PLL) for the indicated F chip on the indicated Control Board (CB).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18792 .

CHASSISD_FASIC_RESET_ERROR

System Log Message	Fchip (CB <i>control-board-slot</i> , ID <i>fchip-id</i>): reset failed
Description	The chassis process (chassisd) could not reset the indicated F chip on the indicated Control Board (CB).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18793 .

CHASSISD_FASIC_SRAM_ERROR

System Log Message	Fchip (CB <i>control-board-slot</i> , ID <i>fchip-id</i>): SRAM fuse did not initialize
Description	The chassis process (chassisd) detected that static RAM (SRAM) did not initialize properly for the indicated F chip on the indicated Control Board (CB).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18794 .

CHASSISD_FASIC_VERSION_ERROR

System Log Message	Fchip (CB <i>control-board-slot</i> , ID <i>fchip-id</i>): part number <i>part-number</i> and version <i>version</i> were invalid
Description	The indicated part number and version detected for the indicated F chip on the indicated Control Board (CB) were not valid values.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHASSISD_FCHIP_CONFIG_COMPLETE

System Log Message	Fchip: configuration already completed
Description	The chassis process (chassisd) detected an attempt to configure an F chip when configuration was already complete.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHASSISD_FCHIP_CONFIG_MD_ERROR

System Log Message	Fchip <i>fchip-id</i> : invalid number of Md chips (<i>count</i>) for Packet Forwarding Engine <i>pfe</i> on FPC <i>fpc-slot</i>
Description	The chassis process (chassisd) detected an invalid number of Md chips for the indicated F chip, Packet Forwarding Engine and Flexible PIC Concentrator (FPC).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

Action For more information, see
<http://kb.juniper.net/InfoCenter/index?page=content&id=KB18795>.

CHASSISD_FCHIP_CONFIG_RATE_ERROR

System Log Message Fchip *fchip-id*: unable to set rate limit on port *port*

Description The chassis process (chassisd) could not set the rate limit for the indicated F chip and port.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

CHASSISD_FCHIP_CONFIG_READ_ERROR

System Log Message Fchip *fchip-id*: unable to read configuration register

Description The chassis process (chassisd) could not read a configuration register on the indicated F chip.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

CHASSISD_FCHIP_FTOKEN_ERROR

System Log Message Fchip *fchip-id*: Ftoken overflow/underflow set (*data*) at *address*

Description The chassis process (chassisd) detected an underflow or overflow error on the indicated F chip.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_FCHIP_FTOKEN_INIT_ERROR

System Log Message Fchip *fchip-id*: fchip_ftoken_init() stuck in ftoken loop, addr=*address*, data=*data*

Description The chassis process (chassisd) encountered an error while initializing memory at the indicated address for the indicated F chip.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_FCHIP_HSR_ERROR

System Log Message Fchip high-speed receiver (HSR) error: *error-message*

Description The chassis process (chassisd) detected an error in the high-speed receiver (HSR) subsystem for the F chip with the indicated characteristics.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18796>.

CHASSISD_FCHIP_HSR_INIT_ERROR

System Log Message HSR: No vectors supplied

Description The chassis process (chassisd) could not initialize the high-speed receiver (HSR) subsystem for an F chip.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

CHASSISD_FCHIP_HSR_INIT_LINK_ERR

System Log Message Fchip *fchip-id*: unable to initialize HSR link *link-id*

Description The chassis process (chassisd) could not initialize the indicated high-speed receiver (HSR) link for the indicated F chip.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

CHASSISD_FCHIP_HSR_RESET_ERROR

System Log Message Fchip *fchip-id*: hsr_reset error in fchip_init() on link *link-id*

Description A high-speed receiver (HSR) reset error occurred during initialization of the indicated F chip and link.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

CHASSISD_FCHIP_HST_ERROR

System Log Message	Fchip high-speed transmitter (HST) error: <i>error-message</i>
Description	The chassis process (chassisd) detected an error in the high-speed transmitter (HST) subsystem for the F chip with the indicated characteristics.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18797 .

CHASSISD_FCHIP_HST_INIT_ERROR

System Log Message	HST: No vectors supplied
Description	The chassis process (chassisd) could not initialize the high-speed transmitter (HST) subsystem for an F chip.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHASSISD_FCHIP_HST_INIT_LINK_ERR

System Log Message	Fchip <i>fchip-id</i> : unable to initialize HST link <i>link-id</i>
Description	The chassis process (chassisd) could not initialize the indicated high-speed transmitter (HST) link for the indicated F chip.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHASSISD_FCHIP_HST_RESET_ERROR

System Log Message	Fchip <i>fchip-id</i> : hst_reset error in fchip_init() on link <i>link-id</i>
Description	A high-speed transmitter (HST) reset error occurred during initialization of the indicated F chip and link.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHASSISD_FCHIP_INIT_ERROR

System Log Message	Fchips were not configured yet
Description	The chassis process (chassisd) detected that F chips were not yet initialized.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHASSISD_FCHIP_LINK_ERROR

System Log Message	SIBsib-slot_F0: <i>link-type</i> link <i>link-id</i> was bad
Description	The chassis process (chassisd) detected an error for the indicated high-speed receiver (HSR) or high-speed transmitter (HST) link for an F chip on the indicated Switch Interface Board (SIB).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18798 .

CHASSISD_FCHIP_MONITOR_ERROR

System Log Message	F chip module was invalid
Description	The chassis process (chassisd) detected an invalid F-chip module while enabling or disabling the monitoring of F-chip functional blocks.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18799 .

CHASSISD_FCHIP_PIO_READ_ERROR

System Log Message	Fchip <i>fchip-id</i> : read error in <i>function-name()</i> for link# <i>link-id</i> , at address <i>address</i> in register <i>register</i>
Description	The indicated routine failed with a read error at the indicated address and register for the indicated F chip and link.
Type	Error: An error occurred

Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18800 .

CHASSISD_FCHIP_PIO_WRITE_ERROR

System Log Message	Fchip <i>fchip-id</i> : write error in <i>function-name()</i> for link# <i>link-id</i> , at address <i>address</i> in register <i>register</i>
Description	The indicated routine failed with a write error at the indicated address and register for the indicated F chip and link.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18801 .

CHASSISD_FCHIP_POLL_ERROR

System Log Message	Fchip <i>fchip-id</i> : <i>link-type link-id</i> poll returned error <i>error-code</i>
Description	An error with the indicated error number occurred during polling of the indicated high-speed receiver (HSR) or high-speed transmitter (HST) link for the indicated F chip.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FCHIP_RATE_ERROR

System Log Message	Fchip <i>fchip-id</i> : per-port rate limit was not enabled
Description	The chassis process (chassisd) detected that per-port rate limiting was not enabled when it attempted to set the rate limit on an individual port for the indicated F chip.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FCHIP_SIB_NOT_STARTED

System Log Message	Unable to start <i>fru-name fru-slot</i> because F chips were not initialized
Description	The indicated Switch Interface Board (SIB) did not start because the F chips on it were not initialized.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FCHIP_VERSION_ERROR

System Log Message	F chip <i>fchip-id</i> : part number (<i>part-number</i>) and version (<i>version</i>) were invalid
Description	The indicated part number and version detected for the indicated F chip were not valid values.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHASSISD_FEB_REVERSION

System Log Message	Reversion from FEB <i>fru-slot</i> to FEB <i>slot</i>
Description	The chassis daemon (chassisd) reverted to the indicated FEB from the specified FEB.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

CHASSISD_FEB_SWITCHOVER

System Log Message	Switchover from FEB <i>fru-slot</i> to FEB <i>slot</i>
Description	The chassis daemon (chassisd) switched to the indicated FEB from the specified FEB.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

CHASSISD_FHSR_READ_REG_ERROR

System Log Message	Fchip: fhsr_read() failed at address <i>address</i>
---------------------------	---

Description	The high-speed receiver (HSR) read routine failed at the indicated address on an F-chip register.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18802 .

CHASSISD_FHSR_WRITE_REG_ERROR

System Log Message	Fchip: fhsr_write() of value <i>value</i> failed at address <i>address</i>
Description	The high-speed receiver (HSR) write routine could not record the indicated value at the indicated address on an F-chip register.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18803 .

CHASSISD_FHST_READ_REG_ERROR

System Log Message	Fchip: fhst_read() failed at address <i>address</i>
Description	The high-speed transmitter (HST) read routine failed at the indicated address on an F-chip register.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18804 .

CHASSISD_FHST_WRITE_REG_ERROR

System Log Message	Fchip: fhst_write() of value <i>value</i> failed at address <i>address</i>
Description	The high-speed transmitter (HST) write routine could not record the indicated value at the indicated address on an F-chip register.
Type	Error: An error occurred
Severity	error

Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18805 .

CHASSISD_FILE_OPEN

System Log Message	File open: <i>filename</i> , error: <i>error-code</i> -- <i>error-message</i>
Description	The chassis process (chassisd) could not open the indicated file for the indicated reason.
Type	Error: An error occurred
Severity	critical
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18806 .

CHASSISD_FILE_STAT

System Log Message	File stat: <i>filename</i> , error: <i>error-code</i> -- <i>error-message</i>
Description	The chassis process (chassisd) could not open the indicated file because it could not obtain its status.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHASSISD_FM_ACTION_FPC_OFFLINE

System Log Message	FPC <i>fpc-slot</i> offline initiated to attempt healing of the fabric down condition.
Description	The chassis process took the indicated FPC offline in an attempt to heal a fabric down condition, which caused the router to be incapable of carrying traffic.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_ACTION_FPC_ONLINE

System Log Message	FPC <i>fpc-slot</i> online initiated to attempt healing of the fabric down condition.
Description	The chassis process put the indicated FPC online in an attempt to heal a fabric down condition, which caused the router to be incapable of carrying traffic.
Type	Event: This message reports an event, not an error

Severity notice
Facility LOG_DAEMON
Action Contact your technical support representative.

CHASSISD_FM_ACTION_FPC_POWER_OFF

System Log Message FPC *fpc-slot* power off initiated to take down interfaces since the FPC is incapable of forwarding traffic due to the fabric down condition.

Description The chassis process powered off the indicated FPC to take down the FPC's interfaces and signal neighboring routers that the router is incapable of carrying traffic on the indicated FPC.

Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON
Action Contact your technical support representative.

CHASSISD_FM_ACTION_FPC_RECOVERY

System Log Message FPC *fpc-slot* action initiated to attempt healing of the *error-message* condition.

Description The chassis process took the indicated FPC action in an attempt to heal a fabric degradation/down condition which caused the router to be running in degraded performance or incapable of carrying traffic.

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_DAEMON
Action Contact your technical support representative.

CHASSISD_FM_ACTION_FPC_RESTART

System Log Message FPC *fpc-slot* restart initiated to attempt healing of the fabric down condition.

Description The chassis process restarted the indicated FPC in an attempt to heal a fabric down condition, which caused the router to be incapable of carrying traffic.

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_DAEMON
Action Contact your technical support representative.

CHASSISD_FM_ACTION_PLANE_OFFLINE

System Log Message	Fabric plane <i>sib-plane</i> offline initiated to attempt healing of the fabric down condition.
Description	The chassis process took the indicated fabric plane offline in an attempt to heal a fabric down condition, which caused the router to be incapable of carrying traffic.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_ACTION_PLANE_ONLINE

System Log Message	Fabric plane <i>sib-plane</i> online initiated to attempt healing of the fabric down condition.
Description	The chassis process put the indicated fabric plane online in an attempt to heal a fabric down condition, which caused the router to be incapable of carrying traffic.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_BAD_STATE

System Log Message	<i>function-name</i> : unexpected state <i>statetype</i> for SIB# <i>sib-slot</i>
Description	The indicated function failed because it encountered the indicated type of unexpected internal state with respect to the indicated Switch Interface Board (SIB).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_DETECT_FPC_FABRIC_DEGRADED

System Log Message	Detected FPC fabric degradation exceeds threshold. If no fabric planes come online in <i>elapsed-time</i> seconds actions will be taken to address the fabric <i>error-message</i> condition.
Description	The chassis process detected that the fabric planes are functioning at a degraded capacity and the router is running with degraded performance or not capable of carrying traffic coming in through the interfaces.
Type	Error: An error occurred

Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_DETECT_PLANES_DOWN

System Log Message	All fabric planes in the system have gone down after interfaces have been created. If no fabric planes come online in <i>elapsed-time</i> seconds, actions will be taken to address the fabric down condition.
Description	The chassis process detected all the fabric planes went down after interfaces were created and the router is not capable of carrying traffic coming in through the interfaces.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_DETECT_UNREACHABLE

System Log Message	Some fabric destinations PFEs in the system have become unreachable after interfaces have been created. If the unreachable PFE destinations are not fixed in <i>elapsed-time</i> seconds, actions will be taken to address the fabric down condition.
Description	The chassis process detected that some Packet Forwarding Engine (PFE) destinations had become unreachable after interfaces were created, and the router is not capable of carrying traffic to the unreachable PFE destinations on the interfaces.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_ERROR

System Log Message	<i>function-name: error-message</i> (SIB# <i>sib-slot</i> , Packet Forwarding Engine <i>pfe</i> on FPC <i>fpc-slot</i>)
Description	During execution of the indicated fabric management routine, the indicated error occurred between the indicated Switch Interface Board (SIB) and the indicated Packet Forwarding Engine on the indicated Flexible PIC Concentrator (FPC).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18807>.

CHASSISD_FM_ERROR_CLOS_F13_HSR

System Log Message FM: *error-message* errors occurred on link from F2S-*f2-sib_SF*from-*fchip_s-port* to F13SIBto-*sfc-sib_SF3_to-fchip_d-port* on plane *sib-plane*

Description In a Tx-Plus routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the T1600 routing nodes (called ST-SIB-Ls) and the SIBs in the TX Matrix Plus platform (called F13SIBs and F2S-SIBs). The chassis process (chassisd) on the SFC routing node detected an error in the electrical path between the indicated port on the indicated F2SIB and F13SIB on the indicated plane.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_FM_ERROR_CLOS_F13_HST

System Log Message FM: *error-message* errors occurred on link from F13SIBfrom-*sfc-sib_SF1_from-fchip_s-port* to F2S-*f2-sib_SF*to-*fchip_d-port* on plane *sib-plane*

Description In a Tx-Plus routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the T1600 routing nodes (called ST-SIB-Ls) and the SIBs in the TX Matrix Plus platform (called F13SIBs and F2S-SIBs). The chassis process (chassisd) on the SFC routing node detected an error in the transmit electrical path between the indicated port on the indicated F13SIB and F2SIB on the indicated plane.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_FM_ERROR_CLOS_F2_HSR

System Log Message FM: *error-message* errors occurred on link from F13SIBfrom-*sfc-sib_SF1_from-fchip_s-port* to F2S-*f2-sib_SF*to-*fchip_d-port* on plane *sib-plane*

Description In a Tx-Plus routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the T1600 routing nodes (called ST-SIB-Ls) and the SIBs in the TX Matrix Plus platform (called F13SIBs and F2S-SIBs). The chassis process (chassisd) on the SFC routing node detected an error in the electrical

path between the indicated port on the indicated F2SIB and F13SIB on the indicated plane.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_ERROR_CLOS_F2_HST

System Log Message FM: *error-message* errors occurred on link from F2S-*f2-sib_SFfrom-fchip_s-port* to F13SIBto-*sfc-sib_SF1_to-fchip_d-port* on plane *sib-plane*

Description In a Tx-Plus routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the T1600 routing nodes (called ST-SIB-Ls) and the SIBs in the TX Matrix Plus platform (called F13SIBs and F2S-SIBs). The chassis process (chassisd) on the SFC routing node detected an error in the transmit electrical path between the indicated port on the indicated F2SIB and F13SIB on the indicated plane.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_ERROR_F13_FB_HSR_TXP

System Log Message *error-message* errors on LCC*lcc_FPCfpc-slot_pfe* link via ST_SIB_L*from-lcc-sib_FBfiber-bundle* to F13SIBto-*sfc-sib*

Description In a Tx-Plus routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the T1600 routing nodes (called ST-SIB-Ls) and the SIBs in the TX Matrix Plus platform (called F13SIBs and F2S-SIBs). The chassis process (chassisd) on the routing node that houses the indicated F13SIB detected an error in the electrical path between the indicated ports on the F13SIB and the indicated ST-SIB-L on the indicated LCC.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_ERROR_F13_FB_RX_VC

System Log Message *error-message on F13SIBfrom-sfc-sib_FBfiber-bundle VCSEL vcsel Channel vcsel-channel connected from LCC lcc SIB_L to-lcc-sib*

Description In a Tx-Plus routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the T1600 routing nodes (called ST-SIB-Ls) and the SIBs in the TX Matrix Plus platform (called F13SIBs and F2S-SIBs). The chassis process (chassisd) on the routing node that houses the indicated F13SIB detected the indicated error as packets that were traveling in the in the optical media from the indicated ST-SIB-L on the indicated LCC.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_FM_ERROR_F13_FB_TXP

System Log Message *F13SIBsib-slot_FB_fiber-bundle LCC lcc ST_SIB_Lto-lcc-sib is error-message*

Description In a Tx-Plus routing matrix, the fiber-optic cable between each Switch Interface Board in a T1600 routing node (called a ST-SIB-L) must connect to a specific SIB port on the TX-Plus Matrix platform (called a F13SIB). The cable connected at the indicated F13SIB had the indicated error.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_FM_ERROR_F13_FB_TX_VC

System Log Message *error-message on F13SIBfrom-sfc-sib_FBfiber-bundle VCSEL vcsel Channel vcsel-channel connected to LCC lcc SIB_L to-lcc-sib*

Description In a Tx-Plus routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the T1600 routing nodes (called ST-SIB-Ls) and the SIBs in the TX Matrix Plus platform (called F13SIBs and F2S-SIBs). The chassis process (chassisd) on the routing node that houses the indicated F13SIB detected the indicated error as packets that were traveling in the indicated direction were translated between electrical and optical media.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_FM_ERROR_F13_VC_PWR

System Log Message	FM: High power difference at F13SIB <i>from-sfc-sib_FBfiber-bundle</i> VCSEL <i>vcsel</i> Channel <i>vcsel-channel</i> connected to LCC <i>lcc</i> SIB_ <i>lsib-slot</i>
Description	In a Tx-Plus routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the T1600 routing nodes (called ST-SIB-Ls) and the SIBs in the TX Matrix Plus platform (called F13SIBs and F2S-SIBs). The chassis process (chassisd) on the SFC routing node that houses the indicated F13SIB detected higher than configured receive power difference levels on the indicated fiber-bundles connected to the indicated LCC ST-SIB-L.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_ERROR_LCC_SIB_CBL

System Log Message	Cable running from SFC <i>error-message lcc, lcc-sib-name</i> , to LCC <i>cable-name sc</i> is <i>sc-sib-name</i> on plane <i>sib-plane</i> .
Description	In a Multi-chassis routing matrix, the fiber-optic cable between each SIB in a LCC routing node (called a LCC SIB) must connect to a specific SIB port on the Switch chassis platform. The cable connected at the indicated line card chassis SIB had the indicated error.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_ERROR_LCC_SIB_HSR_PFE

System Log Message	<i>error-message</i> errors on link from FPC <i>lcc PFElc-name</i> to <i>pfe lcc-sib-name_asic-name,asic-port</i> on LCC <i>asic-chan</i> and plane <i>sib-plane</i>
Description	In a Multi-chassis routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the LCC routing nodes (called LCC SIBs) and the SIBs in the Switch Chassis platform (called F13SIBs and/or F2S-SIBs). The chassis process (chassisd) on the routing node that houses the indicated LCC SIB detected an error in the electrical path between the indicated LCC SIB and the indicated PFE on the FPC.
Type	Error: An error occurred

Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_ERROR_LCC_SIB_HSR_XC

System Log Message *error-message errors on link from SFCsc sc-sib-name to LCClcc lcc-sib-name asic-name_asic-port,asic-chan on plane sib-plane*

Description In a Multi-chassis routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the LCC routing nodes (called LCC SIBs) and the SIBs in the Switch Chassis platform (called F13SIBs and/or F2S-SIBs). The chassis process (chassisd) on the routing node that houses the indicated LCC SIB detected an error in the electrical path between the indicated ports on the LCC SIB and the corresponding SIB on Switch chassis.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_ERROR_LCC_SIB_OPTICS_FAULT

System Log Message *Optics module on LCCerror-message lcc, lcc-sib-name, connected to SFCcable-name sc is sc-sib-name on plane sib-plane.*

Description In a Multi-chassis routing matrix, fiber-optic modules are used to inter-connect each SIB in a LCC routing node (called a LCC SIB) to a specific SIB port on the Switch chassis platform. The optics module connected at the indicated line card chassis SIB had the indicated error.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_ERROR_LCC_SIB_RX_OPTICS

System Log Message *FM: error-message on optics channel in LCClcc_lcc-sib-name_opt-dev-nameoptics,optics-channel*

Description In a Multi-chassis routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the LCC routing nodes (called LCC SIBs) and the SIBs in the Switch Chassis platform (called F13SIBs and/or F2S-SIBs). The chassis process (chassisd) on the routing node that houses the indicated LCC SIB detected the indicated error in the optical media.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_ERROR_LCC_SIB_TX_OPTICS

System Log Message *error-message on optics channel in LCClcc_lcc-sib-name_opt-dev-nameoptics,optics-channel*

Description In a Multi-chassis routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the LCC routing nodes (called LCC SIBs) and the SIBs in the Switch Chassis platform (called F13SIBs and/or F2S-SIBs). The chassis process (chassisd) on the routing node that houses the indicated LCC SIB detected the indicated error as packets that were traveling in the indicated direction were translated between electrical and optical media.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_ERROR_SC_CLOS_F13_HSR

System Log Message *FM: error-message errors occurred on link from SFC sc, sc-f2ssib-name_asic-name_asic-port,asic-chan to sc-f13sib-name_dst-asic-name_dst-asic-port,dst-asic-chan on plane sib-plane*

Description In a Multi-chassis routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the LCC routing nodes (called LCC SIBs) and the SIBs in the Switch Chassis platform (called F13SIBs and/or F2S-SIBs). The chassis process (chassisd) on the SFC routing node detected an error in the electrical path between the indicated port on the indicated F2SIB and F13SIB on the indicated plane.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_ERROR_SC_CLOS_F13_HST

System Log Message *FM: error-message errors occurred on link from SFC sc, sc-f13sib-name_asic-name_asic-port,asic-chan to sc-f2ssib-name_dst-asic-name_dst-asic-port,dst-asic-chan on plane sib-plane*

Description	In a Multi-chassis routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the LCC routing nodes (called LCC SIBs) and the SIBs in the Switch Chassis platform (called F13SIBs and/or F2S-SIBs). The chassis process (chassisd) on the SFC routing node detected an error in the transmit electrical path between the indicated port on the indicated F13SIB and F2SIB on the indicated plane.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_ERROR_SC_CLOS_F2_HSR

System Log Message	FM: <i>error-message</i> errors occurred on link from SFC <i>sc</i> , <i>sc-f13sib-name_asic-name_asic-port,asic-chan</i> to <i>sc-f2ssib-name_dst-asic-name_dst-asic-port,dst-asic-chan</i> on plane <i>sib-plane</i>
Description	In a Multi-chassis routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the LCC routing nodes (called LCC SIBs) and the SIBs in the Switch Chassis platform (called F13SIBs and/or F2S-SIBs). The chassis process (chassisd) on the SFC routing node detected an error in the electrical path between the indicated port on the indicated F2SIB and F13SIB on the indicated plane.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_ERROR_SC_CLOS_F2_HST

System Log Message	FM: <i>error-message</i> errors occurred on link from SFC <i>sc</i> , <i>sc-f2ssib-name_asic-name_asic-port,asic-chan</i> to <i>sc-f13sib-name_dst-asic-name_dst-asic-port,dst-asic-chan</i> on plane <i>sib-plane</i>
Description	In a Multi-chassis routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the LCC routing nodes (called LCC SIBs) and the SIBs in the Switch Chassis platform (called F13SIBs and/or F2S-SIBs). The chassis process (chassisd) on the SFC routing node detected an error in the transmit electrical path between the indicated port on the indicated F2SIB and F13SIB on the indicated plane.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_FM_ERROR_SC_SIB_CBL

System Log Message	Cable running from LCCerror-message <i>sc</i> , <i>sc-sib-name</i> , to SFCcable-name <i>lcc</i> is <i>lcc-sib-name</i> on plane <i>sib-plane</i> .
Description	In a Multi-chassis routing matrix, the fiber-optic cable between each SIB in a LCC routing node (called a LCC SIB) must connect to a specific SIB port on the Switch chassis platform. The cable connected at the indicated switch chassis SIB had the indicated error.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_ERROR_SC_SIB_HSR_XC

System Log Message	<i>error-message</i> errors on link from LCClcc <i>lcc-sib-name</i> to SFCsc <i>sc-sib-name</i> <i>asic-name_asic-port,asic-chan</i> on plane <i>sib-plane</i>
Description	In a Multi-chassis routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the LCC routing nodes (called LCC SIBs) and the SIBs in the Switch Chassis platform (called F13SIBs and/or F2S-SIBs). The chassis process (chassisd) on the routing node that houses the indicated Switch chassis SIB detected an error in the electrical path between indicated ports on the Switch chassis SIB and the indicated LCC SIB on the indicated LCC.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_ERROR_SC_SIB_OPTICS_FAULT

System Log Message	Optics module on SFCerror-message <i>sc</i> , <i>sc-sib-name</i> , connected to LCCcable-name <i>lcc</i> is <i>lcc-sib-name</i> on plane <i>sib-plane</i> .
Description	In a Multi-chassis routing matrix, fiber-optic modules are used to inter-connect each SIB in a LCC routing node (called a LCC SIB) to a specific SIB port on the Switch chassis platform. The optics module connected at the indicated switch chassis SIB had the indicated error.
Type	Error: An error occurred
Severity	error

Facility LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_FM_ERROR_SC_SIB_RX_OPTICS

System Log Message FM: *error-message* on optics channel in
SFCsc_sc-sib-name_opt-dev-nameoptics,optics-channel

Description In a Multi-chassis routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the LCC routing nodes (called LCC SIBs) and the SIBs in the Switch Chassis platform (called F13SIBs and/or F2S-SIBs). The chassis process (chassisd) on the routing node that houses the indicated Switch chassis SIB detected the indicated error as packets were traveling in the optical media from the indicated LCC SIB on the indicated LCC.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_FM_ERROR_SC_SIB_TX_OPTICS

System Log Message *error-message* on optics channel in
SFCsc_sc-sib-name_opt-dev-nameoptics,optics-channel

Description In a Multi-chassis routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the LCC routing nodes (called LCC SIBs) and the SIBs in the Switch Chassis platform (called F13SIBs and/or F2S-SIBs). The chassis process (chassisd) on the routing node that houses the indicated Switch chassis SIB detected the indicated error as packets that were traveling in the indicated direction were translated between electrical and optical media.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_FM_ERROR_SIB_L_FB_HSR

System Log Message FM: HSR error *error-code* occurred on link from SIB-S port F(*s-row,s-port*) to SIB-L#*sib-slot* port F(*l-row,l-port*)

Description In a routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the T640 routing nodes (called SIB-Ls) and the SIBs in the TX Matrix platform (called SIB-Ss). The chassis process (chassisd) on the routing node that houses the indicated SIB-L detected an error in the electrical path between the indicated ports on the SIB-L and the corresponding SIB-S.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18808 .

CHASSISD_FM_ERROR_SIB_L_FB_RX_VC

System Log Message *error-message on LCC lcc SIB_Lfrom-lcc-sib_FBfiber-bundle VCSEL vcsel Channel vcsel-channel connected to F13SIBto-sfc-sib*

Description In a Tx-Plus routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the T1600 routing nodes (called ST-SIB-Ls) and the SIBs in the TX Matrix Plus platform (called F13SIBs and F2S-SIBs). The chassis process (chassisd) on the routing node that houses the indicated ST-SIB-L detected the indicated error as packets that were traveling in the optical media.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_ERROR_SIB_L_FB_SMF

System Log Message *FM: error-message error occurred on link to-from-sib SIB-L#sib-slot to-from-scc SCC*

Description In a routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the TX Matrix platform (the switch-card chassis, or SCC) and the SIBs in the T640 routing nodes (called SIB-Ls). The chassis process (chassisd) on the routing node that houses the indicated SIB-L detected the indicated error as packets that were traveling in the indicated direction were translated between electrical and optical media.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18809 .

CHASSISD_FM_ERROR_SIB_L_FB_TXP

System Log Message *LCC lcc ST-SIB-L:sib-slot Fiber-bundle:fiber-bundle is error-message*

Description In a Tx-Plus routing matrix, the fiber-optic cable between each Switch Interface Board in a T1600 routing node (called a ST-SIB-L) must connect to a specific SIB port on the

TX-Plus Matrix platform (called a F13SIB). The cable connected at the indicated ST-SIB-L had the indicated error.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_ERROR_SIB_L_FB_TX_VC

System Log Message *error-message on LCC lcc SIB_Lfrom-lcc-sib_FBfiber-bundle VCSEL vcse1 Channel vcse1-channel connected to F13SIBto-sfc-sib*

Description In a Tx-Plus routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the T1600 routing nodes (called ST-SIB-Ls) and the SIBs in the TX Matrix Plus platform (called F13SIBs and F2S-SIBs). The chassis process (chassisd) on the routing node that houses the indicated ST-SIB-L detected the indicated error as packets that were traveling in the indicated direction were translated between electrical and optical media.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_ERROR_SIB_L_HSR_PFE

System Log Message *FM: error-message on LCC:lcc FPCfpc-slot_pfe link to ST-SIB-Lto-lcc-sib_fchip-id*

Description In a Tx-Plus routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the T1600 routing nodes (called ST-SIB-Ls) and the SIBs in the TX Matrix Plus platform (called F13SIBs and F2S-SIBs). The chassis process (chassisd) on the routing node that houses the indicated ST-SIB-L detected an error in the electrical path between the indicated ST-SIB-L and the indicated PFE on the FPC.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FM_ERROR_SIB_L_HSR_TXP

System Log Message *FM: error-message on LCC:lcc FPCfpc-slot_pfe link connected by ST-SIB-Lfrom-lcc-sib_fchip-id_s-port_FBfiber-bundle to F13SIBto-sfc-sib*

Description In a Tx-Plus routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the T1600 routing nodes (called ST-SIB-Ls) and the SIBs in the TX Matrix Plus platform (called F13SIBs and F2S-SIBs). The chassis process (chassisd) on the routing node that houses the indicated ST-SIB-L detected an error in the electrical path between the indicated ports on the SIB-L and the corresponding F13SIB.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_FM_ERROR_SIB_L_MISMATCH

System Log Message FM: fiber cable from SIB-L#*sib-slot* possibly connected to wrong SIB-S

Description In a routing matrix, the fiber-optic cable between each Switch Interface Board in a T640 routing node (called a SIB-L) must connect to a specific SIB port on the TX Matrix platform (called a SIB-S). The cable originating at the indicated SIB-L was possibly plugged into the wrong SIB-S port or wrong SIB-S.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_FM_ERROR_SIB_L_VC_PWR

System Log Message FM: High power difference at LCC *lcc* SIB_L*sib-slot*_FB*fiber-bundle* VCSEL *vcsel* Channel *vcsel-channel* connected to F13SIB*from-sfc-sib*

Description In a Tx-Plus routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the T1600 routing nodes (called ST-SIB-Ls) and the SIBs in the TX Matrix Plus platform (called F13SIBs and F2S-SIBs). The chassis process (chassisd) on the routing node that houses the indicated ST-SIB-L detected higher than configured receive power levels on the indicated fiber-bundles connected to the indicated LCC ST-SIB-L.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_FM_ERROR_SIB_S_FB_HSR

System Log Message	FM: HSR error occurred on link from LCC <i>lcc</i> SIB-L port F(<i>l-row,l-port</i>) to SIB-S# <i>sib-slot</i> port F(<i>s-row,s-port</i>)
Description	In a routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the TX Matrix platform (called SIB-Ss) and the SIBs in the T640 routing nodes (called SIB-Ls). The chassis process (chassisd) on the TX Matrix platform detected an error in the electrical path between the indicated port on the indicated SIB-S and the indicated port on a SIB-L installed in the indicated routing node (line-card chassis, or LCC).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18810 .

CHASSISD_FM_ERROR_SIB_S_FB_SMF

System Log Message	FM: <i>error-message</i> error occurred on link <i>to-from-sib-s</i> SIB-S# <i>sib-slot</i> <i>to-from-lcc</i> LCC <i>lcc</i>
Description	In a routing matrix, packets traverse both electrical and optical media as they travel between the Switch Interface Boards (SIBs) in the TX Matrix platform (called SIB-Ss) and the SIBs in the T640 routing nodes (line-card chassis, or LCCs). The chassis process (chassisd) on the TX Matrix platform detected the indicated error as packets that were traveling to or from the indicated LCC were translated between electrical and optical media.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18811 .

CHASSISD_FM_FABRIC_DEGRADED

System Log Message	DPCs are seeing grant timeouts; System is blackholing Need to attempt fabric healing. Action will be taken after <i>elapsed-time</i> seconds, to address the fabric down condition.
Description	The chassis process detected that the fabric planes are functioning at a degraded capacity and the router is not capable of carrying traffic coming in through the interfaces.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_FM_FPC_FABRIC_DEGRADED

System Log Message FPC *fpc-slot* running with *error-message*,no attempt of healing due to configuration.

Description The chassis process (chassisd) did not attempt healing due to user configuration or insufficient online planes.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Change the configuration (chassis) that prevent the healing.

CHASSISD_FM_MEMORY_ERROR

System Log Message *function-name*: unable to allocate memory; *error-message*

Description The chassis process (chassisd) could not allocate memory for a fabric operation.

Type Error: An error occurred

Severity warning

Facility LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_FM_SIB_ERROR

System Log Message Fabric management error for SIB *sib-slot*: *error-message*

Description The chassis process (chassisd) detected the indicated type of error on the indicated Switch Interface Board (SIB) and performed the indicated action.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18812>.

CHASSISD_FM_SIB_FPC_TYPE_ERROR

System Log Message SIB *sib-slot* does not support features required for FPC Type 4

Description The indicated Switch Interface Board (SIB) does not support features required by the Flexible PIC Concentrator (FPC) Type 4.

Type Error: An error occurred

Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FPC_JAM_HSL2_PARAMS_TIMEOUT

System Log Message	<i>function-name</i> : attempt to jam params for <i>fru-name fru-slot</i> timed out
Description	The indicated component (field-replaceable unit, or FRU) did not transfer the parameters within the time that is normally sufficient. If attempt failed, the chassisd process raised an alarm and left the FRU offline.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

CHASSISD_FPC_NOT_FOUND

System Log Message	<i>function-name</i> : unable to find FPC for PIC attachment operation
Description	The chassis process (chassisd) attempted to bring a Physical Interface Card (PIC) online, but could not find the Flexible PIC Concentrator (FPC) that houses it.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FPC_OPTICS_HOT_NOTICE

System Log Message	<i>fru-name</i> temperature over <i>temperature</i> degrees C; non-high-temperature tolerant optics will be disabled in <i>duration</i> seconds if condition persists
Description	The temperature of FPC exceeded the trigger point to disable non-high-temperature tolerant optics. If the temperature did not decrease below the threshold within 10 minutes after message was logged, the chassisd process disable those affected optics.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Increase cooling on FRU or replace optics with high-temperature tolerant optics

CHASSISD_FPC_PIC_DETECT_TIMEOUT

System Log Message	<i>function-name</i> : PIC detection on FPC <i>fpc-slot</i> timed out
---------------------------	---

Description The chassis process (chassisd) expects to receive notification within a timeout period that each Flexible PIC Concentrator (FPC) has attached the Physical Interface Cards (PICs) that it houses. It did not receive notification from the indicated FPC.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18813>.

CHASSISD_FPC_TYPE_SIB_TYPE_ERROR

System Log Message Installed SIB type (SIB-I8-F16) does not support features required by FPC *fpc-slot*

Description The indicated Flexible PIC Concentrator (FPC) is Type 4, which is not supported by Switch Interface Board (SIB) type SIB-I8-F16.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_FRU_ALREADY_OFFLINE

System Log Message *fru-name fru-slot* already offline

Description The chassis process (chassisd) received a request to take the indicated component (field-replaceable unit, or FRU) offline, but the FRU was already offline.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

CHASSISD_FRU_ALREADY_ONLINE

System Log Message Received request to bring *fru-name fru-slot* online; it was already online

Description The chassis process (chassisd) received a request to bring the indicated component (field-replaceable unit, or FRU) online, but the FRU was already online.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

CHASSISD_FRU_EVENT

System Log Message	<i>function-name: state fru-name fru-slot</i>
Description	The state of the indicated component (field-replaceable unit, or FRU) changed as indicated.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

CHASSISD_FRU_FIRE_TEMP_CONDITION

System Log Message	<i>fru-name fru-slot sensor temperature temperature over threshold degrees C (message);</i> routing platform will shut down in <i>duration</i> seconds if condition persists
Description	The temperature of the specified component (field-replaceable unit, or FRU) exceeded the indicated temperature, which is the upper of two thresholds. The fans (and impellers, if applicable) that were cooling this FRU were in the indicated state. If the temperature does not go below the threshold within four seconds after the chassis process (chassisd) detects this condition, the chassisd process shuts down the routing platform. When this message was logged, the indicated number of seconds remained before shutdown.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Increase cooling in the area around the chassis.

CHASSISD_FRU_HIGH_TEMP_CONDITION

System Log Message	<i>fru-name fru-slot sensor temperature temperature over threshold degrees C (message)</i>
Description	The temperature of the specified component (field-replaceable unit, or FRU) exceeded the indicated temperature, which is the lower of two thresholds. The fans (and impellers, if applicable) that were cooling this FRU were in the indicated state. The chassis process (chassisd) increased the speed of all functioning fans (and impellers) that were cooling this component to full speed.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Action	Increase cooling in the area around the chassis.

CHASSISD_FRU_INVALID_SLOT

System Log Message	FRU <i>fru-name</i> is not supported in current slot
---------------------------	--

Description	The chassis process (chassisd) detected that the indicated hardware component (field-replaceable unit, or FRU) was inserted in a slot that is not valid for that component type.
Type	Error: An error occurred
Severity	critical
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18814 .

CHASSISD_FRU_IO_ERROR

System Log Message	<i>function-name: fru-name operation error: reason (error-message)</i>
Description	The chassis process (chassisd) could not perform the indicated I/O operation on the indicated component (field-replaceable unit, or FRU).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FRU_IO_OFFSET_ERROR

System Log Message	<i>function-name: fru-name operation error: reason 0xoffset (error-message)</i>
Description	The chassis process (chassisd) could not perform the indicated I/O operation at the indicated byte offset.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_FRU_IPC_WRITE_ERROR

System Log Message	<i>function-name: FRU fru-name, errno error-code, error-message</i>
Description	The chassis process (chassisd) could not send an interprocess communication (IPC) message to the indicated component (field-replaceable unit, or FRU) because of the indicated error.
Type	Error: An error occurred
Severity	warning

Facility LOG_DAEMON

CHASSISD_FRU_OFFLINE_FAILED

System Log Message Unable to take *fru-name fru-slot* offline because FRU sequencer is active: *reason*

Description The chassis process (chassisd) could not take the indicated component (field-replaceable unit, or FRU) offline for the indicated reason.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_DAEMON

CHASSISD_FRU_OFFLINE_NOTICE

System Log Message Taking *fru-name fru-slot* offline: *reason*

Description The chassis process (chassisd) took the indicated component (field-replaceable unit, or FRU) offline for the indicated reason.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_DAEMON

CHASSISD_FRU_OFFLINE_TIMEOUT

System Log Message Offline request timed out; *fru-name fru-slot* restarted

Description The indicated component (field-replaceable unit, or FRU) did not go offline within the time period that is normally sufficient for synchronized shutdown. After generating this message, the chassis process (chassisd) tried several times to take the FRU offline and powered it down if all attempts failed.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

CHASSISD_FRU_ONLINE_TIMEOUT

System Log Message *function-name*: attempt to bring *fru-name fru-slot* online timed out

Description The indicated component (field-replaceable unit, or FRU) did not come online within the time that is normally sufficient. After generating this message, the chassis process (chassisd) tried to bring the FRU online several more times. If all attempts failed, the chassisd process raised an alarm and left the FRU offline.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

CHASSISD_FRU_OVER_TEMP_CONDITION

System Log Message	<i>fru-name fru-slot sensor temperature temperature over threshold degrees C (message);</i> FRU will shut down in <i>duration</i> seconds if condition persists
Description	The temperature of the specified component (field-replaceable unit, or FRU) exceeded the indicated temperature, which is the upper of two thresholds. The fans (and impellers, if applicable) that were cooling this FRU were in the indicated state. If the temperature does not go below the threshold within four minutes after the chassis process (chassisd) detects this condition, the chassisd process shuts down the FRU or all FRUs in the same cooling zone. When this message was logged, the indicated number of seconds remained before shutdown.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Increase cooling in the area around the chassis.

CHASSISD_FRU_STEP_ERROR

System Log Message	<i>fru-name fru-slot at step step-number</i>
Description	The power-on sequence for the indicated component (field-replaceable unit, or FRU) failed at the indicated point.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHASSISD_FRU_UNRESPONSIVE

System Log Message	Error for <i>fru-name fru-slot: error-message; action</i>
Description	The chassis process (chassisd) tried to bring the indicated component (field-replaceable unit, or FRU) online, but the attempt failed in the indicated way. As a result, the chassisd process performed the indicated action.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

CHASSISD_FRU_UNRESPONSIVE_RETRY

System Log Message	Attempt <i>count</i> to power on <i>fru-name fru-slot</i> timed out; restarted it
Description	The chassis process (chassisd) tried the indicated number of times to bring the indicated component (field-replaceable unit, or FRU) online, but the attempts failed. In another

attempt to bring the FRU online, the chassisd process issued the restart command for the FRU.

Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON

CHASSISD_FRU_UNSUPPORTED

System Log Message chassisd invalidated support for *fru-name fru-slot*
Description The chassis process (chassisd) invalidated support for the indicated component (field-replaceable unit, or FRU) during initialization.
Type Error: An error occurred
Severity warning
Facility LOG_DAEMON

CHASSISD_FRU_VERSION_MISMATCH

System Log Message *component* version mismatch for *fru-name* -- expected *expected-value*, got *received-value*
Description The chassis process (chassisd) verifies that it supports the revision level or version of a component (field-replaceable unit, or FRU). The revision level for the indicated FRU was unsupported or otherwise invalid.
Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON
Action Upgrade the FRU.

CHASSISD_GASIC_ID_ERROR

System Log Message Fchip: invalid SIB slot
Description A routine tried to determine the identifier for an application-specific integrated circuit (ASIC) on a Switch Interface Board (SIB). The attempt failed, because the supplied SIB slot number was invalid.
Type Error: An error occurred
Severity error
Facility LOG_DAEMON
Action Contact your technical support representative.

CHASSISD_GBUS_NOT_READY

System Log Message	<i>function-name: fru-name</i> not ready for power up (RTIME_PWR_COND = 0x <i>value</i>)
Description	The GBUS was not ready when the chassis process (chassisd) first tried to power it on, and the power-up operation timed out.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	The probable cause is hardware error.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18815 .

CHASSISD_GBUS_READBACK_ERROR

System Log Message	Readback error from GBUS for <i>fru-name fru-slot</i> ([0x <i>gbus-address</i> , 0x <i>gbus-registers</i>] -> 0x <i>return-value</i>)
Description	There was an error when the chassis process (chassisd) tried to read back information from the GBUS on the indicated component (field-replaceable unit, or FRU).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	The probable cause is hardware error.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18816 .

CHASSISD_GBUS_RESET_EVENT

System Log Message	<i>fru-name#fru-slot - command</i>
Description	The chassis process (chassisd) reset the GBUS for the indicated component (field-replaceable unit, or FRU). This is a normal part of startup.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

CHASSISD_GBUS_SANITY_ERROR

System Log Message	<i>function-name: fru-name fru-slot</i> -- management bus failed sanity test
---------------------------	--

Description	The chassis process (chassisd) checks its management GBUS with a set of test operations when it is started. The tests failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_GENERIC_ERROR

System Log Message	<i>function-name: error-message</i>
Description	The chassis process (chassisd) detected the indicated error.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Perform any corrective actions mentioned in the error message.

CHASSISD_GENERIC_WARNING

System Log Message	<i>function-name: error-message</i>
Description	The chassis process (chassisd) generated the indicated warning message.
Type	Error: An error occurred
Severity	notice
Facility	LOG_DAEMON

CHASSISD_GETTIMEOFDAY

System Log Message	Unexpected error from gettimeofday: <i>error-code -- error-message</i>
Description	The chassis process (chassisd) could not obtain the time of day because of the indicated error.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON

CHASSISD_GRES_UNSUPP_PIC

System Log Message	Unable to enable graceful Routing Engine switchover; PIC does not support it
Description	The chassis process (chassisd) could not enable graceful Routing Engine switchover because an installed PIC does not support it.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

CHASSISD_HIGH_TEMP_CONDITION

System Log Message Chassis temperature over *temperature* degrees C (*message*)

Description The temperature of one or more components (field-replaceable units, or FRUs) exceeded the indicated temperature, which is the lower of two thresholds. The fans (and impellers, if applicable) were in the indicated state. The chassis process (chassisd) increased the speed of all functioning fans and impellers to full speed.

Type Event: This message reports an event, not an error
Severity warning
Facility LOG_DAEMON
Action Increase cooling in the area around the chassis.

CHASSISD_HOST_TEMP_READ

System Log Message Error reading host temperature sensor

Description The chassis process (chassisd) could not read the temperature sensors on the routing platform.

Type Error: An error occurred
Severity notice
Facility LOG_DAEMON

CHASSISD_HSR_CONFIG_READ_ERROR

System Log Message *function-name*: unable to read configuration for HSR *identifier*

Description The indicated function could not read the configuration for the indicated high-speed receiver (HSR).

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

CHASSISD_HSR_CONFIG_WRITE_ERROR

System Log Message *function-name*: unable to write configuration for HSR *identifier*

Description The indicated routine could not write to the configuration for the indicated high-speed receiver (HSR).

Type Error: An error occurred

Severity error
Facility LOG_DAEMON

CHASSISD_HSR_ELEMENTS_ERROR

System Log Message Provided number of HSR elements (*count*) was invalid

Description The indicated routine for processing a certain number of high-speed receiver (HSR) elements failed, because the supplied number of elements was invalid.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

CHASSISD_HSR_FIFO_ERROR

System Log Message *function-name*: FIFO read failed for HSR *identifier*

Description A first in, first out (FIFO) read error occurred during execution of the indicated routine on the indicated high-speed receiver (HSR).

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18817>.

CHASSISD_I2CS_READBACK_ERROR

System Log Message Readback error from I2C slave for *fru-name fru-slot* ([*0xi2cs-address*, *0xoffset*] -> *0xerror-code*)

Description The chassis process (chassisd) could not read back information from the I2C slave (I2CS) about the indicated component (field-replaceable unit, or FRU).

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause The probable cause is hardware error.

Action Contact your technical support representative.

CHASSISD_I2C_BAD_IDEEPROM_FORMAT

System Log Message Invalid IDEEPROM format for *fru-name*

Description	The chassis process (chassisd) determined that the ID EEPROM format specified for the indicated type of hardware component (field-replaceable unit, or FRU) is not valid for it.
Type	Error: An error occurred
Severity	critical
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18818 .

CHASSISD_I2C_FIC_PRESENCE_READ

System Log Message	<i>function-name: fru-name</i> unable to get presence masks (<i>error-message</i>)
Description	The chassis process (chassisd) could not read I2C data with presence information about the indicated component (field-replaceable unit, or FRU).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_I2C_GENERIC_ERROR

System Log Message	<i>function-name: error-message</i>
Description	The indicated error occurred during an I2C access library operation.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_I2C_INVALID_ASSEMBLY_ID

System Log Message	' <i>Oxassembly-id</i> ' is invalid value for <i>fru-name</i> assembly ID
Description	The assembly ID for the indicated component (field-replaceable unit, or FRU) was not valid for its type.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_I2C_IOCTL_FAILURE

System Log Message	<i>function-name: operation</i> ioctl failure for group <i>group-id</i> at address <i>0xaddress</i> (errno <i>error-code</i>)
Description	The chassis process (chassisd) could not perform the indicated ioctl() operation on the I2C data for the indicated component (field-replaceable unit, or FRU).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_I2C_IO_FAILURE

System Log Message	<i>function-name: fru-name</i> operation failed for group <i>group-id</i> at address <i>0xaddress</i>
Description	The chassis process (chassisd) could not perform the indicated I/O operation on the I2C data for the indicated component (field-replaceable unit, or FRU).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_I2C_MIDPLANE_CORRUPT

System Log Message	Corruption on midplane ID EEPROM (ID: <i>0xassembly-id</i> , MAC address: <i>0xmac-address</i> , <i>0xversion</i>)
Description	The chassis process (chassisd) found corrupted information when it tried to verify the parameters of the midplane's I2C ID EEPROM.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_I2C_RANGE_ERROR

System Log Message	<i>function-name:</i> requested offset was out of range (offset <i>offset</i> + nbytes <i>count</i> > 256)
Description	The indicated offset, which is greater than 256, was specified in a read request for an I2C device.
Type	Error: An error occurred

Severity	error
Facility	LOG_DAEMON
Cause	No I2C device uses or has storage above an offset of 256.
Action	Contact your technical support representative.

CHASSISD_I2C_READ_ERROR

System Log Message	<i>function-name</i> : read error for group <i>group-id</i> at address <i>0xaddress</i> , offset <i>offset</i>
Description	The chassis process (chassisd) could not read I2C data from the indicated device.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18819 .

CHASSISD_I2C_WRITE_ERROR

System Log Message	<i>function-name</i> : write error for group <i>group-id</i> at address <i>0xaddress</i> , offset <i>offset</i>
Description	The chassis process (chassisd) could not write I2C data to the indicated device.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_IDEEPROM_READ_ERROR

System Log Message	Unable to read <i>fru-name</i> ID EEPROM
Description	The chassis process (chassisd) could not read the I2C ID EEPROM of the indicated component (field-replaceable unit, or FRU).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_IFDEV_CREATE_FAILURE

System Log Message	<i>function-name</i> : unable to create interface device for <i>interface-name</i> (<i>error-message</i>)
---------------------------	---

Description	The chassis process (chassisd) creates initial interface devices for newly installed Physical Interface Cards (PICs) and pseudodevices. It could not create a device for the indicated PIC or pseudodevice.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	Necessary resources might have been unavailable.
Action	Contact your technical support representative.

CHASSISD_IFDEV_CREATE_NOTICE

System Log Message	<i>function-name: created device-name for interface-name</i>
Description	The chassis process (chassisd) created the initial interface device for the indicated newly installed Physical Interface Card (PIC) or pseudodevice.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

CHASSISD_IFDEV_DETACH_ALL_PSEUDO

System Log Message	ifdev_detach(pseudo devices: all)
Description	The chassis process (chassisd) detached the interface devices for all pseudodevices.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

CHASSISD_IFDEV_DETACH_FPC

System Log Message	ifdev_detach_fpc(<i>fpc-slot</i>)
Description	The chassis process (chassisd) detached the interface devices for all Physical Interface Cards (PICs) installed in the indicated Flexible PIC Concentrator (FPC).
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18821 .

CHASSISD_IFDEV_DETACH_PIC

System Log Message	<code>ifdev_detach_pic(<i>fpc-slot/pic-slot</i>)</code>
Description	The chassis process (chassisd) detached the interface devices for the indicated Physical Interface Card (PIC).
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18822 .

CHASSISD_IFDEV_DETACH_PSEUDO

System Log Message	<code>ifdev_detach(pseudo devices: porttype <i>port-type</i>, sdev=<i>sdev-number</i>, edev=<i>edev-number</i>)</code>
Description	The chassis process (chassisd) detached the interface devices for the indicated pseudodevices.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

CHASSISD_IFDEV_DETACH_TLV_ERROR

System Log Message	<code>ifdev_detach: rtslib_ifdm_change_tlvs failed for slot <i>fpc-slot</i> dev idx <i>device-id</i> <i>error-message</i></code>
Description	The chassis process (chassisd) asked the kernel to remove the indicated interface from the kernel interface table. The request failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHASSISD_IFDEV_GETBYNAME_NOTICE

System Log Message	<code><i>function-name</i>: ifdm get_by_name failed for <i>interface-type</i> interface device <i>interface-name</i> (<i>error-message</i>)</code>
Description	The chassis process (chassisd) failed to find the indicated interface device, even though it just created it.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

Cause There was a problem with interface state creation.

Action Contact your technical support representative.

CHASSISD_IFDEV_GET_BY_INDEX_FAIL

System Log Message *function-name: rtslib_ifdm_get_by_index failed: error-code - error-message*

Description The chassis process (chassisd) could not obtain information about an interface device.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

CHASSISD_IFDEV_GET_BY_NAME_FAIL

System Log Message Unable to retrieve information for interface device *interface-name: error-message*

Description The chassis process (chassisd) could not obtain information about the indicated interface device.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

CHASSISD_IFDEV_NO_MEMORY

System Log Message *function-name: unable to allocate memory for interface-type interface*

Description The chassis process (chassisd) could not allocate memory when creating an interface device for the indicated interface type.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause Resources on the system are extremely limited.

Action Eliminate the resource limitations and restart the PIC that houses the interface for which the interface device could not be created.

CHASSISD_IFDEV_RETRY_NOTICE

System Log Message *function-name: attempt count to add interface device interface-name failed (error-message)*

Description The chassis process (chassisd) tried the indicated number of times to create the indicated interface device, but the attempts failed. After generating this message, the chassisd process waited a while for resources to free up and tried again.

Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	Necessary resources might have been unavailable. They should become available soon.

CHASSISD_IFDEV_RTSLIB_FAILURE

System Log Message	<i>function-name: library-function-name failed (error-message)</i>
Description	The chassis process (chassisd) could not create an interface device because an error occurred during the indicated call to the routing socket library.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_IFILTER_INSTALL_ERROR

System Log Message	<i>function-name: RTSOCK Implicit Filter install failed. error=error-code</i>
Description	The chassis process (chassisd) could not install a global implicit rtsock filter most likely due to a file operation error.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHASSISD_IOCTL_FAILURE

System Log Message	<i>function-name: reason for fru-name (error-message)</i>
Description	The chassis process (chassisd) could not perform the indicated ioctl() operation on the indicated component (field-replaceable unit, or FRU).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_IPC_ANNOUNCE_TIMEOUT

System Log Message	<i>function-name: no ack received from fru-type for fru-name fru-slot state change (0xsent-mask, acks 0xack-mask)</i>
---------------------------	---

Description	The chassis process (chassisd) notified the indicated components (field-replaceable units, or FRUs) that the component in the indicated slot was changing state. It did not receive the expected acknowledgment.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_IPC_CONNECTION_DROPPED

System Log Message	Dropped IPC connection for <i>fru-name fru-slot</i>
Description	The chassis process (chassisd) dropped its interprocess communication (IPC) connection to the indicated component (field-replaceable unit, or FRU).
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18823 .

CHASSISD_IPC_DAEMON_WRITE_ERROR

System Log Message	pipe_write failure for <i>connection-id</i> ; connection error: <i>error-message</i> (errno <i>error-code</i>)
Description	The chassis process (chassisd) could not write to a socket, because of the indicated error. The socket is for a connection to another process that runs on the Routing Engine and helps manage the chassis.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18824 .

CHASSISD_IPC_ERROR

System Log Message	<i>function-name: error-message</i>
Description	An error occurred when the chassis process (chassisd) received an interprocess communication (IPC) message.
Type	Error: An error occurred
Severity	error

Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_IPC_FLUSH_ERROR

System Log Message	<i>function-name</i> : flush operation failed for <i>fru-name fru-slot</i>
Description	The chassis process (chassisd) could not write to a socket that it was using to communicate with the indicated component (field-replaceable unit, or FRU).
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_IPC_MSG_DROPPED

System Log Message	Dropping message from connection queue: type = <i>message-type</i> , subtype = <i>message-subtype</i>
Description	The chassis process (chassisd) dropped an interprocess communication (IPC) message because the message queue had already reached maximum capacity.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	The connection to a component (field-replaceable unit, or FRU) no longer exists, so the chassisd process cannot send all messages immediately as it usually does.
Action	Contact your technical support representative. For more information, see http://juniper.net/InfoCenter/index?page=content&id=KB18825

CHASSISD_IPC_MSG_ERROR

System Log Message	<i>function-name</i> : error code <i>error-code</i> , type <i>message-type</i> , subtype <i>message-subtype</i> , opcode <i>message-opcode</i>
Description	The chassis process (chassisd) detected an error in an interprocess communication (IPC) message with the indicated characteristics.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_IPC_MSG_FRU_NOT_FOUND

System Log Message	<i>function-name</i> : unable to locate FRU for message with type <i>message-type</i> , subtype <i>message-subtype</i> , opcode <i>message-opcode</i>
Description	The chassis process (chassisd) could not locate a component (field-replaceable unit, or FRU) to handle the interprocess communication (IPC) message with the indicated characteristics that it received. The message was ignored.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_IPC_MSG_QFULL_ERROR

System Log Message	Dropping message from connection queue: type = <i>message-type</i> , subtype = <i>message-subtype</i>
Description	The chassis process (chassisd) had to discard a message because the queue of messages waiting for a connection was already full.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHASSISD_IPC_MSG_UNHANDLED

System Log Message	<i>function-name</i> : unable to handle <i>fru-name</i> message with type <i>message-type</i> , subtype <i>message-subtype</i> , length <i>length</i> , opcode <i>message-opcode</i> , error <i>error-code</i>
Description	The chassis process (chassisd) received an interprocess communication (IPC) message about the indicated FRU. The message had the indicated characteristics. The chassisd process could not handle the message.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18826 .

CHASSISD_IPC_UNEXPECTED_MSG

System Log Message	<i>function-name</i> : invalid message received: <i>message</i> (message type <i>message-type</i> , subtype <i>message-subtype</i>)
---------------------------	--

Description The chassis process (chassisd) received a unexpected message with the indicated characteristics.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_IPC_UNEXPECTED_RECV

System Log Message Received unexpected message from *connection-id*: type = *message-type*, subtype = *message-subtype*

Description The chassis process (chassisd) received an unexpected message from a peer connection.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

CHASSISD_IPC_WRITE_ERROR

System Log Message *function-name*: pipe_write failure for SCC connection with error *error-code* (*error-message*)

Description A line-card chassis in a routing matrix attempted to send data to the TX Matrix platform (switch-card chassis, or SCC) over a pipe. The attempt failed with the indicated error.

Type Error: An error occurred

Severity warning

Facility LOG_DAEMON

CHASSISD_IPC_WRITE_ERR_NO_PIPE

System Log Message FRU has no connection pipe *function-name* *fru-name*

Description The chassis process (chassisd) could not send a message to the indicated component (field-replaceable unit, or FRU) because the interprocess communication (IPC) pipe to the FRU no longer existed.

Type Error: An error occurred

Severity warning

Facility LOG_DAEMON

CHASSISD_IPC_WRITE_ERR_NULL_ARGS

System Log Message FRU has no connection arguments *function-name* *fru-name*

Description	The chassisd process (chassisd) could not send a message to the indicated component (field-replaceable unit, or FRU) because one or more required parameters had a null value.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18827 .

CHASSISD_ISSU_BLOB_ERROR

System Log Message	<i>fru-name: error-message</i>
Description	The chassisd process (chassisd) detected the indicated error while handling blobs (opaque information) for the indicated field replaceable unit (fru). The blobs are used by the fru to store state information across in service software upgrade(issu) reboot.
Type	Error: An error occurred
Severity	notice
Facility	LOG_DAEMON

CHASSISD_ISSU_DAEMON_ERROR

System Log Message	Daemon [<i>process-name</i>] state:< <i>state</i> > error:< <i>error-message</i> >
Description	The chassisd process (chassisd) encountered the indicated error in the indicated in service software upgrade (issu) state for the indicated daemon.
Type	Error: An error occurred
Severity	notice
Facility	LOG_DAEMON

CHASSISD_ISSU_ERROR

System Log Message	<i>action error-code(error-message)</i>
Description	The chassisd process (chassisd) encountered the indicated error for the indicated in service software upgrade process (issu) action.
Type	Error: An error occurred
Severity	notice
Facility	LOG_DAEMON

CHASSISD_ISSU_FRU_ERROR

System Log Message	<i>fru-name: state:[state] error-message</i>
---------------------------	--

Description The chassisd process (chassisd) encountered the indicated error during the in service software upgrade for the indicated field replaceable unit (fru).

Type Error: An error occurred

Severity notice

Facility LOG_DAEMON

CHASSISD_ISSU_FRU_IPC_ERROR

System Log Message *fru-name: state:[state] error:[message] reason:[error-message]*

Description The chassisd process (chassisd) detected the indicated error for the indicated field replaceable unit (fru) during in service software upgrade (issu).

Type Error: An error occurred

Severity notice

Facility LOG_DAEMON

CHASSISD_JTREE_ERROR

System Log Message jtree terminate operation returned *error-code*

Description The chassis process (chassisd) received the indicated error when executing the JUNOS system call that terminates the jtree.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

CHASSISD_LCC_RELEASE_MASTERSHIP

System Log Message Backup Routing Engine became master, because JUNOS version of former master did not match SCC master

Description The chassis process (chassisd) running on the master Routing Engine on a T640 routing node (line-card chassis, or LCC, in a routing matrix) relinquished mastership to the backup Routing Engine in the LCC.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_DAEMON

Cause The version of the JUNOS software on the master Routing Engine did not match the version on the TX Matrix platform's master Routing Engine. The version on the backup Routing Engine did match the TX Matrix platform.

CHASSISD_LOST_MASTERSHIP

System Log Message Routing Engine lost mastership; exiting

Description The chassis process (chassisd) running on the master Routing Engine exited, because mastership switched to the other Routing Engine.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_MAC_ADDRESS_AE_ERROR

System Log Message chassisd MAC address allocation error for *aedevic-id*

Description The chassis process (chassisd) could not obtain a media access control (MAC) address for the indicated aggregated Ethernet interface because of an internal error.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

CHASSISD_MAC_ADDRESS_ATS_ERROR

System Log Message chassisd MAC address allocation error for *atsdevice-id*

Description The chassis process (chassisd) could not obtain a media access control (MAC) address for the indicated ATS Ethernet interface because of an internal error.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

CHASSISD_MAC_ADDRESS_CBP_ERROR

System Log Message chassisd MAC address allocation error for CBP

Description The chassis process (chassisd) could not obtain a media access control (MAC) address for a customer backbone port because of an internal error.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

CHASSISD_MAC_ADDRESS_ERROR

System Log Message chassisd MAC address allocation exceed error for FPC *fpc-slot*, PIC *pic-slot*, port *port*

Description The chassis process (chassisd) could not obtain a media access control (MAC) address for the indicated interface because of an internal error.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18828 .

CHASSISD_MAC_ADDRESS_FABRIC_ERR

System Log Message	Unable to allocate MAC address for fabric interface <i>device-id</i>
Description	The chassis process (chassisd) could not obtain a media access control (MAC) address for the indicated fabric interface because of an internal error.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18829 .

CHASSISD_MAC_ADDRESS_IRB_ERROR

System Log Message	chassisd MAC address allocation error for IRB
Description	The chassis process (chassisd) could not obtain a media access control (MAC) address for an integrated routing and bridging interface because of an internal error.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHASSISD_MAC_ADDRESS_PIP_ERROR

System Log Message	chassisd MAC address allocation error for PIP
Description	The chassis process (chassisd) could not obtain a media access control (MAC) address for a provider instance port because of an internal error.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHASSISD_MAC_ADDRESS_PLT_ERROR

System Log Message	chassisd MAC address allocation error for PLT
Description	The chassis process (chassisd) could not obtain a media access control (MAC) address for the pseudo logical tunnel interface because of an internal error.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

CHASSISD_MAC_ADDRESS_SWFAB_ERR

System Log Message Unable to allocate MAC address for swfabric interface *device-id*
Description The chassis process (chassisd) could not obtain a media access control (MAC) address for the indicated swfabric interface because of an internal error.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

CHASSISD_MAC_ADDRESS_VIRB_ERROR

System Log Message chassisd MAC address allocation error for IRB
Description The chassis process (chassisd) could not obtain a media access control (MAC) address for an integrated routing and bridging interface because of an internal error.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

CHASSISD_MAC_ADDRESS_VLAN_ERROR

System Log Message chassisd MAC address allocation error for VLAN
Description The chassis process (chassisd) could not obtain a media access control (MAC) address for a vlan interface because of an internal error.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

CHASSISD_MAC_ADDRESS_VTEP_ERROR

System Log Message chassisd MAC address allocation error for VTEP
Description The chassis process (chassisd) could not obtain a media access control (MAC) address for an integrated routing and bridging interface because of an internal error.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

CHASSISD_MAC_DEFAULT

System Log Message	Using default MAC address base
Description	The chassis process (chassisd) used the default base media access control (MAC) address.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

CHASSISD_MAIN_THREAD_STALLED

System Log Message	main chassis-control thread stalled for <i>duration</i> sec -- exiting
Description	Chassis control daemon main thread did not run for a long duration.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	A core dump of chassis control daemon will be attempted.

CHASSISD_MALLOC_FAILURE

System Log Message	<i>function-name</i> : chassisd malloc failed, aborting
Description	The chassis process (chassisd) could not allocate memory. The chassisd process tried to continue functioning, but the lack of memory usually causes the process to fail. An administrator needs to restart it at some point.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18830 .

CHASSISD_MASTER_CG_REMOVED

System Log Message	Master <i>fru-name</i> (slot <i>fru-slot</i>) removed; powering it down
Description	The master Clock Generator (CG) was removed. The CG provides the clock for interfaces timing, so those interfaces might drop packets and experience other errors until a new clock source has been established.
Type	Error: An error occurred
Severity	critical

Facility LOG_DAEMON

CHASSISD_MASTER_PCG_REMOVED

System Log Message Master PCG (slot *pcg-slot*) removed; powering down Packet Forwarding Engine complex

Description The master Packet Forwarding Engine Clock Generator (PCG) was removed. The PCG provides the system clock for all application-specific integrated circuits (ASICs) in the routing platform, so packet forwarding halts until the Packet Forwarding Engine is restarted and a PCG is functioning as master.

Type Error: An error occurred

Severity critical

Facility LOG_DAEMON

CHASSISD_MASTER_SCG_REMOVED

System Log Message Master SCG (slot *fru-slot*) removed; powering it down

Description The master SONET Clock Generator (SCG) was removed. The SCG provides the clock for SONET/SDH interface timing, so those interfaces might drop packets and experience other errors until a new clock source is established.

Type Error: An error occurred

Severity critical

Facility LOG_DAEMON

CHASSISD_MBUS_ERROR

System Log Message *fru-name fru-slot*: management bus failed sanity test

Description Startup tests on the indicated FRU's management bus failed.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_MCHASSIS_SWITCH_WARNING

System Log Message CB settings on *chassis-type old-index* changed: switch is now '*value*', chassis index is now *0xnew-index*

Description A toggle switch on the back of the Control Board on each platform in a routing matrix is set to 'M' (multichassis) on the T640 routing nodes and to 'S' (single-chassis) on the TX Matrix platform. On a T640 routing node, the adjacent dial is set to the node's index number in the routing matrix (0 through 3); on the TX Matrix platform it is set to 0. The setting of the toggle switch, the dial, or both, changed to the indicated values on the indicated platform. The new settings take effect when the routing matrix next reboots.

Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	If the changes were accidental, return the toggle and dial to the correct settings before the next reboot. If the changes were intended, disconnect and move the cables on the TX Matrix platform Switch Interface Board (SIB) to the row that corresponds to the T640 routing node's new index number.

CHASSISD_MCS_INTR_ERROR

System Log Message	Received SIGUSR2 without any interrupts pending
Description	The chassis process (chassisd) received the indicated interrupt signal. The signal normally indicates that an event on the Miscellaneous Control Subsystem (MCS) requires servicing. However, the chassisd process did not find such an event pending. This error does not usually cause component failure.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_MGR_CONNECT

System Log Message	<i>function-name</i> evSelectFD: initial pipe create aborted (errno <i>error-code</i>)
Description	The chassis process (chassisd) could not to open a pipe for interprocess communication (IPC) to a component (field-replaceable unit, or FRU).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_MIC_OFFLINE_NOTICE

System Log Message	Taking MIC <i>mic-slot</i> in FPC <i>fpc-slot</i> offline: <i>reason</i>
Description	The chassis process (chassisd) took the indicated MIC offline, for the indicated reason.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

CHASSISD_MULTILINK_BUNDLES_ERROR

System Log Message	Unable to set multilink Frame Relay UNI NNI bundles for PIC <i>pic-slot</i> in FPC <i>fpc-slot</i>
Description	The chassis process (chassisd) could not create multilink Frame Relay user-to-network interface and network-to-network interface (MLFR UNI NNI [FRF.16]) bundles for the indicated PIC.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_MXC_LINK

System Log Message	MXC: <i>operation: filename, error: error-code -- error-message</i>
Description	The chassis process (chassisd) could not link the specified package to the application services (AS-MXC) PIC.
Type	Error: An error occurred
Severity	critical
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_NO_CGS

System Log Message	No <i>fru-name</i> status
Description	The chassis process (chassisd) could not find an operational Clock Generator (CG). To continue functioning properly, interfaces that use a CG as their clock source must find another source.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_NO_PCGS

System Log Message	No PCG status
Description	The chassis process (chassisd) could not find an operational Packet Forwarding Engine Clock Generator (PCG). Packet forwarding is halted until a PCG becomes operational.
Type	Error: An error occurred

Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_NO_SCGS

System Log Message	No SCG <i>state</i>
Description	The chassis process (chassisd) could not find an operational SONET Clock Generator (SCG). To continue functioning correctly, SONET/SDH interfaces that use an SCG as their clock source must find another source.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_OFFLINE_NOTICE

System Log Message	Routing Engine offline: <i>message</i>
Description	The chassis process (chassisd) took the Routing Engine offline.
Type	Event: This message reports an event, not an error
Severity	critical
Facility	LOG_DAEMON

CHASSISD_OID_GEN_FAILED

System Log Message	Unable to generate OID: <i>oid (error-message)</i>
Description	The chassis process (chassisd) could not generate an object identifier (OID) for the indicated object.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_OVER_TEMP_CONDITION

System Log Message	Chassis temperature over <i>temperature</i> degrees C (<i>message</i>); routing platform will shutdown in <i>duration</i> seconds if condition persists
Description	The temperature of one or more components (field-replaceable units, or FRUs) exceeded the indicated temperature, which is the upper of two thresholds. The fans (and impellers,

if applicable) were in the indicated state. If the temperature does not go below the threshold within four minutes after the chassis process (chassisd) detects this condition, the chassisd process shuts down the routing platform. When this message was logged, the indicated number of seconds remained before shutdown.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Increase cooling in the area around the chassis. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18832 .

CHASSISD_OVER_TEMP_SHUTDOWN_TIME

System Log Message	Chassis temperature above <i>temperature</i> degrees C <i>description</i> (> <i>duration</i> seconds); powering down all FRUs
Description	The chassis process (chassisd) shut down the routing platform because the temperature of one or more components exceeded the indicated threshold temperature for the indicated amount of time. Continued operation at the excessive temperature could damage the routing platform.
Type	Error: An error occurred
Severity	critical
Facility	LOG_DAEMON
Action	Increase cooling in the area around the chassis. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18833

CHASSISD_PARSE_COMPLETE

System Log Message	Using new configuration
Description	The chassis process (chassisd) successfully parsed its configuration file.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

CHASSISD_PCI_ERROR

System Log Message	<i>function-name: error-message</i>
Description	While performing an operation on the PCI bus, the chassis process (chassisd) encountered the indicated error.
Type	Error: An error occurred
Severity	error

Facility	LOG_DAEMON
Cause	A software or a hardware problem occurred.
Action	Contact your technical support representative.

CHASSISD_PDU_BREAKER_TRIP

System Log Message	Circuit breaker tripped for PDU <i>pdu-slot</i>
Description	The circuit breaker was tripped for the indicated power distribution unit (PDU).
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	Turn on the affected PDU manually.

CHASSISD_PDU_NOT_OK

System Log Message	<i>error-message</i> for PDU <i>pdu-slot</i> (status bits: <i>0xstatus-code</i>)
Description	The chassis process (chassisd) detected the indicated error condition for the indicated power distribution unit (PDU).
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_PEER_UNCONNECTED

System Log Message	<i>function-name</i> : peer not connected
Description	The chassis process (chassisd) processed a packet for a peer with an invalid or missing connection.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Cause	In most cases, this error is caused by peers transitioning up and down unexpectedly. The error is usually transient and nonfatal.

CHASSISD_PEM_BREAKER_TRIP

System Log Message	Circuit breaker tripped for power supply <i>pem-slot</i>
---------------------------	--

Description The circuit breaker was tripped for the indicated power entry module (PEM).

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

Action Turn on the affected PEM manually.

CHASSISD_PEM_IMPROPER

System Log Message Power supply *pem-slot* improper for platform

Description Old PEM is not supported in this platform.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Replace old PEM with proper newer PEM

CHASSISD_PEM_INPUT_BAD

System Log Message *error-message* for power supply *pem-slot* (status bits: *0xstatus-code*); check circuit breaker

Description The chassis process (chassisd) detected the indicated error condition for the indicated power entry module (PEM).

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

Action Check the status of the circuit breaker and the input connections.

CHASSISD_PEM_NOT_SUFFICIENT

System Log Message Unable to power up FPC *fpc-slot*, because no three-input 240-A power supply is installed

Description On the T1600 router, the T1600-FPC4 ES Flexible PIC Concentrator (FPC) requires that at least one three-input 240-A power supply be installed. The chassis process (chassisd) did not power on the T1600-FPC4 ES in the indicated slot because the required power supply is not installed.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Install at least one three-input 240-A power supply.

CHASSISD_PEM_OVERLOAD

System Log Message	Overload condition for power supply <i>pem-slot</i> (status bits: <i>0xstatus-code</i>);
Description	The indicated power entry module (PEM) reported an output voltage overload condition.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	There might have been excessive load on the PEM.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18834 .

CHASSISD_PEM_TEMPERATURE

System Log Message	Temperature check bit set for power supply <i>pem-slot</i> ; airflow might be inadequate
Description	The chassis process (chassisd) detected that the 'temperature check bit' was set in the status bit mask for the indicated power entry module (PEM).
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	The PEM might have exceeded its temperature threshold, possibly because the airflow through it was inadequate.

CHASSISD_PEM_VOLTAGE

System Log Message	Power supply <i>pem-slot</i> reports problem; check output voltage
Description	The indicated power entry module (PEM) reported a problem with its output voltage.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	There might have been excessive load on the PEM.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18835 .

CHASSISD_PFE_LAUNCH_ERROR

System Log Message	Failed to launch PFE: <i>error-message</i>
---------------------------	--

Description The chassis process (chassisd) failed to launch the PFE image.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

CHASSISD_PIC_CMD_GIVEUP

System Log Message *function-name*: attempt *fpc-slot* to bring PIC *pic-slot* in FPC *count* online timed out; stopped trying

Description The chassis process (chassisd) tried the indicated number of times to bring the indicated PIC online, but stopped trying after all attempts failed.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_PIC_CMD_TIMEOUT

System Log Message *function-name*: attempt to bring PIC *pic-slot* in FPC *fpc-slot* online timed out

Description The chassis process (chassisd) tried to bring the indicated Physical Interface Card (PIC) online. The attempt took longer than the standard time allotted for that operation.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_PIC_CONFIG_CONFLICT

System Log Message *fpc pic-slot* *pic fpc-slot* port mirror instance *instance* will be applied to both the PICs

Description The PIC configuration will be applied to all PICs on the FPC

Type Event: This message reports an event, not an error

Severity unknown

Facility LOG_DAEMON

CHASSISD_PIC_CONFIG_ERROR

System Log Message Unable to create interface devices during attachment of PIC *pic-slot* in FPC *fpc-slot*: graceful switchover not supported

Description	The chassis process (chassisd) did not create an interface device for the indicated PIC because graceful switchover was enabled but is not supported in combination with that PIC type. A PIC must have an interface device to come online, so it remained offline.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Remove the PIC or upgrade the Junos OS.

CHASSISD_PIC_HWERROR

System Log Message	PIC <i>pic-slot</i> in FPC <i>fpc-slot</i> (PIC type <i>pic-type</i> , version <i>version</i>) had hardware error
Description	The indicated PIC experienced a hardware error. The chassis process (chassisd) did not bring the PIC online.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18836 .

CHASSISD_PIC_OFFLINE_NOTICE

System Log Message	Taking PIC <i>pic-slot</i> in FPC <i>fpc-slot</i> offline: <i>reason</i>
Description	The chassis process (chassisd) took the indicated Physical Interface Card (PIC) offline, for the indicated reason.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

CHASSISD_PIC_OID_GEN_FAILED

System Log Message	Unable to generate OID for PIC: <i>pic-name</i> (<i>error-message</i>)
Description	The chassis process (chassisd) could not generate an object identifier (OID) for the indicated Physical Interface Card (PIC).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_PIC_OID_UNKNOWN

System Log Message	Unable to find OID for PIC: <i>i2c-id</i>
Description	The chassis process (chassisd) could not determine the object identifier (OID) for the Physical Interface Card (PIC) with the indicated identifier.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_PIC_PORT_ERROR

System Log Message	chassisd pic/port check and set error for FPC <i>fpc-slot</i> , PIC <i>pic-slot</i> , port <i>port</i>
Description	The chassis process (chassisd) could not set the port attributes for the indicated interface because of an internal error.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHASSISD_PIC_RESET_ON_SWITCHOVER

System Log Message	PIC <i>pic-slot</i> in FPC <i>fpc-slot</i> (type <i>pic-type</i> : <i>pic-name</i> , version <i>version</i>) does not support GRES and will be reset on switchover
Description	The chassis process (chassisd) noted that the Physical Interface Card (PIC) with the indicated characteristics needs to be reset when a graceful switchover occurs.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

CHASSISD_PIC_SPEED_INVALID

System Log Message	Set speed for so- <i>fpc-slot/pic-slot/port</i> to <i>default-value</i> because configured value <i>current-value</i> is invalid
Description	The chassis process (chassisd) set the speed for the indicated Physical Interface Card (PIC) to the indicated value, because the configured value is either higher than the maximum valid value or lower than the minimum valid value.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

Action Reconfigure the PIC with a valid speed.

CHASSISD_PIC_VERSION_ERROR

System Log Message	Hardware version (<i>pic-slot</i>) of PIC <i>fpc-slot</i> in FPC <i>pic-type</i> (PIC type version) is not supported
Description	The chassis process (chassisd) did not bring the indicated Physical Interface Card (PIC) online, because its hardware version is not supported.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Cause	The PIC requires a hardware upgrade.
Action	Contact your technical support representative.

CHASSISD_PIDFILE_OPEN

System Log Message	Unable to open PID file ' <i>filename</i> ': <i>errno error-code</i>
Description	The chassis process (chassisd) could not open the file where it stores its process ID (PID).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	The chassisd process might have detected that another chassisd process was running and tried to read the file so that it could use the PID recorded there when terminating the other process.

CHASSISD_POWER_CHECK

System Log Message	<i>fru-name fru-slot</i> not powering up
Description	The chassis process (chassisd) could not power up the indicated component (field-replaceable unit, or FRU), because the FRU did not respond.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18837 .

CHASSISD_POWER_EVENT

System Log Message	Unable to turn off power to <i>fru-name fru-slot</i> ; a stand-alone test jumper might be installed
Description	The chassis process (chassisd) could not turn off power to the indicated component (field-replaceable unit, or FRU).
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	A common reason is that a standalone test jumper is installed.

CHASSISD_POWER_ON_CHECK_FAILURE

System Log Message	<i>fru-name-fru-slot</i> is already powered on, no need to re-power
Description	The chassis process (chassisd) is getting a power- not-on status for a FRU (field-replaceable unit) that is already powered on.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	This could be due to bad hardware or communication failure between hardware and software.

CHASSISD_POWER_RATINGS_EXCEEDED

System Log Message	PIM/module in slot <i>fru-slot</i> left offline to avoid exceeding chassis power ratings
Description	The chassis process (chassisd) did not bring online the component (field-replaceable unit, or FRU) in the indicated slot, because doing so causes the total power demand of components in the chassis to exceed the chassis' power ratings. On a J-series Services Router, the component is a Physical Interface Module (PIM) or other module that installs in a PIM slot.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHASSISD_PSD_RELEASE_MASTERSHIP

System Log Message	Backup Routing Engine became master, because JUNOS version of former master did not match RSD master
Description	The chassis process (chassisd) running on the master Routing Engine on a System-Domain routing node relinquished mastership to the backup Routing Engine in the PSD.

Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON
Cause	The version of the JUNOS software on the master Routing Engine did not match the version on the RSD platform's master Routing Engine. The version on the backup Routing Engine did match the RSD platform.

CHASSISD_PSM_NOT_OK

System Log Message	<i>error-message</i> for PDU <i>pdu-slot</i> PSM <i>psm-slot</i> (status bits: <i>0xstatus-code</i>)
Description	The chassis process (chassisd) detected the indicated error condition for the indicated power supply module (PSM).
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_PSM_NOT_OK_1

System Log Message	<i>error-message</i> for PSM <i>psm-slot</i> (status bits: <i>0xstatus-code</i>)
Description	The chassis process (chassisd) detected the indicated error condition for the indicated power supply module (PSM).
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_PSM_TRIP

System Log Message	Power supply module <i>psm-slot</i> tripped
Description	The indicated power supply module (PSM) was tripped.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

CHASSISD_PSU_ERROR

System Log Message	<i>error-message</i> power supply <i>pem-slot</i> (status bits: <i>0xstatus-code</i>); status failure
---------------------------	--

Description	The chassis process (chassisd) detected the indicated error condition for the indicated power supply unit (PSU).
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18838 .

CHASSISD_PSU_FAN_FAIL

System Log Message	Fan Fail for power supply <i>pem-slot</i>
Description	PSU Fan fail bit is set in the status for the indicated power supply unit (PSU)
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18839 .

CHASSISD_PSU_INPUT_BAD

System Log Message	<i>error-message</i> power supply <i>pem-slot</i> (status bits: <i>0xstatus-code</i>); Input failure
Description	The chassis process (chassisd) detected the input voltage/warning fault condition for the indicated power supply unit (PSU).
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	Check the status of the input connections. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18840 .

CHASSISD_PSU_OVERLOAD

System Log Message	Overload condition for power supply <i>pem-slot</i> (status bits: <i>0xstatus-code</i>);
Description	The indicated power supply unit (PSU) reported an output voltage overload condition.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	There might have been excessive load on the PSU.

Action For more information, see
<http://kb.juniper.net/InfoCenter/index?page=content&id=KB18841>.

CHASSISD_PSU_TEMPERATURE

System Log Message Temperature check bit set for power supply *pem-slot*; airflow might be inadequate

Description The chassis process (chassisd) detected that the 'temperature check bit' was set in the status bit mask for the indicated power supply unit (PSU).

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

Cause The PSU might have exceeded its temperature threshold, possibly because the airflow through it was inadequate.

Action For more information, see
<http://kb.juniper.net/InfoCenter/index?page=content&id=KB18842>.

CHASSISD_PSU_VOLTAGE

System Log Message Power supply *pem-slot* reports problem; check output voltage

Description The indicated power supply unit (PSU) reported a problem with its output voltage.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

Cause There might have been excessive load on the PSU.

Action For more information, see
<http://kb.juniper.net/InfoCenter/index?page=content&id=KB18843>.

CHASSISD_RANGE_CHECK

System Log Message *function-name*: '0x*value*' is invalid value for *object-name* (out of range)

Description The indicated value was outside the valid range of values for the indicated object.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

CHASSISD_RECONNECT_SUCCESSFUL

System Log Message	Successfully reconnected on soft restart
Description	The chassis process (chassisd) successfully reconnected with each Packet Forwarding Engine after a soft restart.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

CHASSISD_RELEASE_MASTERSHIP

System Log Message	Release mastership notification
Description	The chassis process (chassisd) running on the master Routing Engine received a request to release mastership.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON
Cause	The Routing Engine was probably rebooting and graceful Routing Engine switchover is configured.

CHASSISD_RE_CONSOLE_FE_STORM

System Log Message	Console device encountering framing error storm on Routing Engine <i>routing-engine-slot</i> (possibly a bad console cable)
Description	At least one console device on the Routing Engine has encountered excessive framing errors. This can be indicative of a bad cable connected to the device (especially true in the case of a serial console port.)
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHASSISD_RE_CONSOLE_ME_STORM

System Log Message	Console device encountering modem error storm on Routing Engine <i>routing-engine-slot</i> (possibly a bad console cable)
Description	At least one console device on the Routing Engine has encountered excessive modem errors. This can be indicative of a bad cable connected to the device (especially in the case of a serial console port).
Type	Error: An error occurred
Severity	error

Facility LOG_DAEMON

CHASSISD_RE_INIT_INVALID_RE_SLOT

System Log Message re_init: re *routing-engine-slot*, out of range

Description The chassis process (chassisd) could not initialize a Routing Engine because the slot number specified for it was invalid.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

CHASSISD_RE_OVER_TEMP_CONDITION

System Log Message Routing Engine *routing-engine-slot* temperature (*temperature* C) over *threshold* degrees C

Description The temperature of the indicated Routing Engine exceeded the indicated temperature, which is the upper of two thresholds.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Increase cooling in the area around the chassis. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18844>.

CHASSISD_RE_OVER_TEMP_SHUTDOWN

System Log Message Routing Engine *routing-engine-slot* temperature above *threshold* degrees C for too long; *action*

Description The chassis process (chassisd) performed the indicated action because the temperature of the indicated Routing Engine exceeded the maximum threshold for more than four minutes. Continued operation at the excessive temperature could damage routing platform components.

Type Error: An error occurred

Severity critical

Facility LOG_DAEMON

Action Increase cooling in the area around the chassis. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18845>.

CHASSISD_RE_OVER_TEMP_WARNING

System Log Message Routing Engine *routing-engine-slot* temperature (*temperature* C) over *threshold* degrees C, *component* will shutdown in *duration* seconds if condition persists

Description	The temperature of the indicated Routing Engine exceeded the indicated temperature, which is the upper of two thresholds. If the temperature does not go below the threshold within four minutes after the chassis process (chassisd) detects this condition, the chassisd process shuts down the indicated component. When this message was logged, the indicated number of seconds remained before shutdown.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Increase cooling in the area around the chassis. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18846 .

CHASSISD_RE_WARM_TEMP_CONDITION

System Log Message	Routing Engine <i>routing-engine-slot</i> temperature (<i>temperature</i> C) is above warm temperature limit (<i>threshold</i> C)
Description	The temperature of the indicated Routing Engine exceeded the indicated temperature, which is the lower of two thresholds.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Action	Increase cooling in the area around the chassis.

CHASSISD_ROOT_MOUNT_ERROR

System Log Message	Unable to determine the mount point for root directory: <i>error-message</i>
Description	The chassis process (chassisd) could not determine the mount point for the root file system.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHASSISD_RTS_SEQ_ERROR

System Log Message	ifmsg sequence gap <i>expected-value</i> - <i>received-value</i>
Description	The chassis process (chassisd) received a routing socket message out of order.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

Cause A routing socket message was lost because of excessive load or lack of memory.

CHASSISD_SBOARD_VERSION_MISMATCH

System Log Message	Version mismatch: chassisd message version <i>expected-value fru-name</i> message version <i>received-value</i> local IPC version <i>local-ipc-version</i> remote IPC version <i>remote-ipc-version</i>
Description	The chassis process (chassisd) verifies that it supports the revision level or version of a component (field-replaceable unit, or FRU). The revision level for the indicated FRU was unsupported or otherwise invalid.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	Either a previous software upgrade did not complete successfully, or the chassisd process or FRU did not restart after a successful software upgrade.
Action	Upgrade the software and reboot the routing platform.

CHASSISD_SENSOR_RANGE_NOTICE

System Log Message	<i>fru-name fru-slot</i> temperature is <i>temperature</i> degrees C, which is outside operating range
Description	The temperature sensor on the indicated component (field-replaceable unit, or FRU) reported the indicated temperature, which is outside the acceptable operating range.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	Some sensors generate erroneous readings when a FRU starts up. When this happens, the chassis process (chassisd) rereads the sensor at a later time.

CHASSISD_SERIAL_ID

System Log Message	Serial ID read error: <i>error-code</i> -- <i>error-message</i>
Description	The chassis process (chassisd) could not obtain the Routing Engine's serial number from the kernel because of the indicated error.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON

CHASSISD_SFC_FPM_CHCFG_WARNING

System Log Message	SFC Front Panel craft interface setting is changed : Chassis Number 0x <i>old-index</i> -> 0x <i>index</i> , Config Size 0x <i>old-size</i> -> 0x <i>size</i>
---------------------------	---

Description	SFC Front Panel Dial Switches Chassis Number and Config Size are changed. Chassis Number setting change is ignored. Config Size setting change affects the SFC operation mode on next reboot.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	If the changes were accidental, return the dial to the correct settings before the next reboot. If the changes were intended, make sure the right hardware configuration is present.

CHASSISD_SFM_MODE_ERROR

System Log Message	<i>function-name: error-message</i>
Description	The chassis process could not configure a requested operational mode for a Switching and Forwarding Module (SFM), for the indicated reason.
Type	Error: An error occurred
Severity	info
Facility	LOG_DAEMON
Cause	Possible reasons include (a) the requested mode is available only with certain versions of an application-specific integrated circuit (ASIC) (b) not all SFMs are online as required by the requested mode (c) cross-connect mode cannot be configured if an OC-192c Physical Interface Card (PIC) is installed.

CHASSISD_SFM_NOT_ONLINE

System Log Message	<i>function-name: SFM sfm-slot not online</i>
Description	The indicated Switching and Forwarding Module (SFM) was offline.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_SHUTDOWN_NOTICE

System Log Message	Shutdown reason: <i>reason</i>
Description	Although the chassis process (chassisd) normally does not exit or shut down except when the Routing Engine reboots, it shut down for the indicated reason.
Type	Event: This message reports an event, not an error

Severity warning
Facility LOG_DAEMON

CHASSISD_SIB_INVALID_SLOT

System Log Message *fru-name* in invalid slot *slot*

Description The chassis process (chassisd) detected the presence of the switch interface board (SIB) in an invalid slot. The SIB remains offline.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18848>.

CHASSISD_SIGPIPE

System Log Message SIGPIPE received

Description The chassis process (chassisd) received a signal indicating that its attempt to write to a pipe failed because the reader (which could be another process or thread) did not exist.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

Cause The entity at the other end of the pipe exited or closed the connection.

CHASSISD_SMB_ERROR

System Log Message smb_read: fpga download not complete: val *return-value*, *action*

Description The system management bus (SMB) could not download field-programmable gate array (FPGA) information and returned the indicated status code. The chassis process (chassisd) took the indicated action.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

CHASSISD_SMB_INVALID_PS

System Log Message *function-name*: invalid power supply status code (0x*status-code*)

Description The chassis process (chassisd) could not set the status (enabled or disabled) for a power supply, because it received the indicated power supply status code, which is invalid.

Type	Error: An error occurred
Severity	critical
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18849 .

CHASSISD_SMB_IOCTL_FAILURE

System Log Message	<i>function-name: 'operation' ioctl failed on system management bus (address 0xmemory-address, cmd 0xcommand)</i>
Description	The indicated ioctl() operation failed at the indicated address on the system management bus (SMB).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18850 .

CHASSISD_SMB_READ_FAILURE

System Log Message	<i>function-name: read() failed on system management bus (address 0xmemory-address)</i>
Description	A read() operation failed at the indicated address on the system management bus (SMB).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18851 .

CHASSISD_SNMP_TRAP1

System Log Message	SNMP trap generated: <i>trap (argument1 value1)</i>
Description	The chassisd process (chassisd) generated the indicated simple network management protocol (snmp) trap with the indicated value.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

CHASSISD_SNMP_TRAP10

System Log Message	SNMP trap generated: <i>trap (argument1 value1, argument2 value2, argument3 value3, argument4 value4, argument5 value5, argument6 value6, argument7 value7, argument8 value8, argument9 value9, argument10 value10)</i>
Description	The chassis process (chassisd) generated a Simple Network Management Protocol (SNMP) trap with the ten indicated argument-value pairs.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

CHASSISD_SNMP_TRAP3

System Log Message	ENTITY trap generated: <i>trap (argument1 value1, argument2 value2, argument3 value3)</i>
Description	The chassisd process (chassisd) generated the indicated simple network management protocol (snmp) trap with the three indicated argument-value pairs.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

CHASSISD_SNMP_TRAP6

System Log Message	SNMP trap generated: <i>trap (argument1 value1, argument2 value2, argument3 value3, argument4 value4, argument5 value5, argument6 value6)</i>
Description	The chassis process (chassisd) generated a Simple Network Management Protocol (SNMP) trap with the six indicated argument-value pairs.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

CHASSISD_SNMP_TRAP7

System Log Message	SNMP trap generated: <i>trap (argument1 value1, argument2 value2, argument3 value3, argument4 value4, argument5 value5, argument6 value6, argument7 value7)</i>
Description	The chassis process (chassisd) generated a Simple Network Management Protocol (SNMP) trap with the seven indicated argument-value pairs.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

CHASSISD_SPI_IOCTL_FAILURE

System Log Message	<i>function-name: reason 0xaddress, error error-message</i>
Description	The chassis process (chassisd) could not perform the indicated ioctl() operation on the indicated register of the spi device.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_SPMB_RESTART

System Log Message	SPMB <i>slot</i> restarted
Description	The indicated Switch Processor Mezzanine Board (SPMB) restarted.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

CHASSISD_SPMB_RESTART_TIMEOUT

System Log Message	Attempt <i>count</i> to restart SPMB <i>slot</i> timed out; <i>action</i>
Description	The chassis process (chassisd) tried the indicated number of times to bring the indicated Switch Processor Mezzanine Board (SPMB) online. The chassisd process performed the indicated action as a result of the failure.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

CHASSISD_SSB_FAILOVERS

System Log Message	<i>fru-name</i> failover occurred <i>count</i> times
Description	The indicated packet-switching component or control board failed over to a redundant neighbor the indicated number of times, which exceeds the maximum limit.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	There is probably a system error.

Action Contact your technical support representative.

CHASSISD_STANDALONE_FPC_NOTICE

System Log Message chassisd running in standalone FPC mode *mode*

Description The chassis process (chassisd) was running in the indicated standalone Flexible PIC Concentrator (FPC) mode. This message was logged in case the administrator wants it to run in a different mode.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

CHASSISD_SYSCTL_ERROR

System Log Message *function-name: sysctl-error* error from *sysctl-function-name: error-message* (errno *error-code*)

Description The chassis process (chassisd) received the indicated error from the indicated sysctl() operation.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

CHASSISD_TEMP_HOT_NOTICE

System Log Message *fru-name* temperature of *temperature* degrees C is above limit (*threshold* degrees)

Description The temperature of the chassis, or of the indicated component (field-replaceable unit, or FRU), exceeded the lower of two thresholds. The chassis process (chassisd) increased the speed of all functioning fans (and impellers, if applicable) to full speed. If the temperature did not decrease below the threshold within 4 minutes after this message was logged, the chassisd process shut down the routing platform.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

Action Increase cooling in the area around the chassis.

CHASSISD_TEMP_SENSOR_FAILURE

System Log Message *function-name*: unable to read temperature sensor for *fru-name*

Description The temperature sensor for the indicated component (field-replaceable unit, or FRU) either did not respond to a request from the chassis process (chassisd) for a temperature reading or sent a value that is outside the normal operating range.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18852 .

CHASSISD_TERM_SIGNAL

System Log Message	Received SIGTERM request, shutting down
Description	The chassis process (chassisd) received the SIGTERM signal, indicating that it should terminate. It began the procedure for clean shutdown and exit, but possibly restarted automatically after exiting.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

CHASSISD_TIMER_CLR_ERR

System Log Message	<i>function-name: message</i>
Description	The chassis process (chassisd) could not clear the state of the timer it had set to track the timeout period for an event.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHASSISD_TIMER_ERR

System Log Message	Unable to schedule timeout for <i>description</i>
Description	The chassis process (chassisd) could not start a timer to track the timeout period for the indicated event. The seriousness of this error depends on the event.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_TIMER_VAL_ERR

System Log Message	Null timer ID
Description	The chassis process (chassisd) started a timer to track the timeout period for an event. The timer returned a null identifier, so the chassisd process could not clear the timer.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18853 .

CHASSISD_UNEXPECTED_EXIT

System Log Message	evMainLoop returned <i>return-value</i> (errno error-code)
Description	The chassis process (chassisd) exited unexpectedly and reported the indicated error.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18854 .

CHASSISD_UNEXPECTED_VALUE

System Log Message	<i>function-name</i> : 'value' is invalid value for <i>object-name</i>
Description	The indicated value was specified for the indicated object in a message received by the chassis process (chassisd). The value is invalid for that type of object.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_UNSUPPORTED_FPC

System Log Message	FPC with I2C ID of <i>0xi2c-id</i> is not supported
Description	A Flexible PIC Concentrator (FPC) of the indicated type was installed in the routing platform. The software does not support that FPC type on this platform.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_UNSUPPORTED_MODEL

System Log Message	Model <i>model</i> unsupported with this version of chassisd
Description	The version of the chassis process (chassisd) software that is installed on the routing platform does not support this type of chassis.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_UNSUPPORTED_PIC

System Log Message	PIC <i>pic-slot</i> in FPC <i>fpc-slot</i> (type <i>pic-type</i> , version <i>version</i>) is not supported
Description	The indicated Physical Interface Card (PIC) is either not supported on this routing platform or is not supported by the installed version of the chassis process (chassisd) software. The chassisd process did not bring the PIC online.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_UNSUPPORTED_PIC_MODE

System Log Message	Application mode <i>mode</i> is not supported for PIC <i>pic-slot</i> in FPC <i>fpc-slot</i>
Description	The indicated Physical Interface Card (PIC) does not support the indicated application mode configured for it.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	Check which application modes are supported for the PIC.

CHASSISD_UNSUPPORTED_SIB

System Log Message	SIB with assembly ID <i>assembly-id</i> is not supported <i>reason</i>
Description	The chassis process (chassisd) detected the presence of a new Switch Interface Board (SIB) with the indicated assembly ID. The SIB remains offline, because it is not a supported type.
Type	Error: An error occurred

Severity error
Facility LOG_DAEMON
Action Contact your technical support representative.

CHASSISD_VCHASSIS_CONVERT_ERROR

System Log Message *function-name: fpc-slot/pic-slot/port conversion timeout; type type-string*
Description The chassis process (chassisd) timed out awaiting notification from an fpc that an interface being converted to or from a vc-port was deleted.
Type Error: An error occurred
Severity error
Facility LOG_DAEMON

CHASSISD_VCHASSIS_LICENSE_ERROR

System Log Message Virtual Chassis License not installed
Description A virtual-chassis operational mode command was executed without a valid virtual chassis license being installed.
Type Error: An error occurred
Severity error
Facility LOG_DAEMON

CHASSISD_VCHASSIS_MEMBER_LIST_NOTICE

System Log Message Members: *member-list*
Description List of virtual-chassis members
Type Event: This message reports an event, not an error
Severity notice
Facility LOG_DAEMON

CHASSISD_VCHASSIS_MEMBER_OP_NOTICE

System Log Message Member change: *vc operation* of member *member-id*
Description The change being made to the member
Type Event: This message reports an event, not an error
Severity notice
Facility LOG_DAEMON

CHASSISD_VCHASSIS_MEMBER_UPDATE_NOTICE

System Log Message	Membership update: Member <i>old-member-id->member-id</i> , Mode <i>old-member-mode->member-mode</i> , <i>master-member-id</i> M <i>backup-member-id</i> B, Master <i>master-change</i> , Members <i>members-change</i>
Description	A virtual-chassis membership change is being reported
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

CHASSISD_VERSION_MISMATCH

System Log Message	Version mismatch: chassisd message version <i>expected-value fru-name fru-slot</i> message version <i>received-value</i> local IPC version <i>local-ipc-version</i> remote IPC version <i>remote-ipc-version</i>
Description	As a component (field-replaceable unit, or FRU) comes online, the chassis process (chassisd) verifies that the FRU's revision level or version is supported. The revision level of the indicated FRU was unsupported or otherwise invalid.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	Either a previous software upgrade did not complete successfully, or the chassisd process or FRU did not restart after a successful software upgrade.
Action	Upgrade the software and reboot the routing platform.

CHASSISD_VOLTAGE_READ_FAILED

System Log Message	Unable to read voltage from <i>fru-name</i> (group <i>group-id</i> , address <i>address</i> , channel <i>voltage-channel</i>)
Description	The chassis process (chassisd) could not read voltage data from the indicated component (field-replaceable unit, or FRU).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18855 .

CHASSISD_VOLTAGE_SENSOR_INIT

System Log Message	Unable to initialize voltage sensor for <i>fru-name</i> (group <i>group-id</i> , address <i>address</i>)
Description	The chassis process (chassisd) could not initialize the voltage sensor for the indicated component (field-replaceable unit, for FRU).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHASSISD_VSERIES_LICENSE_ERROR

System Log Message	CHASSISD_VSERIES_LICENSE_ERROR: <i>error-message</i>
Description	A virtual Appliance Operational Command was executed without a valid virtual appliance license being installed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHASSISD_ZONE_BLOWERS_SPEED

System Log Message	Fans and impellers in zone <i>zone</i> are now running at normal speed
Description	The fans (and impellers, if applicable) in zone were running at the normal speed.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

CHASSISD_ZONE_BLOWERS_SPEED_FULL

System Log Message	Fans and impellers in zone <i>zone</i> being set to full speed [<i>reason</i>]
Description	For the indicated reason, the chassis process (chassisd) increased the speed of fans (and impellers, if applicable) in zone to the maximum.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

CHASSISD_ZONE_BLOWERS_SPEED_OFF

System Log Message	Fans and impellers in zone <i>zone</i> being set to off [<i>reason</i>]
---------------------------	---

Description The fans (and impellers, if applicable) in zone were off.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_DAEMON

CHAPTER 24

CHASSISM System Log Messages

This chapter describes messages with the **CHASSISM** prefix. They are generated by the chassis manager process (chassism), which controls hardware components on the routing platform.

CHASSISM_SYSTEM

System Log Message	<i>reason: error-message</i>
Description	A system call made by this process failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	It is possible that the kernel lacked the resources to fulfill the request.

CHAPTER 25

CLKSYNCD System Log Messages

This chapter describes messages with the **CLKSYNCD** prefix.

CLKSYNCD_EVENT_BITS_DPLL_STATUS

System Log Message	ifIndex: <i>snmp-interface-index</i> , ifName: <i>interface-name</i> , dpll_state: <i>dpll-state</i>
Description	Signifies SyncE DPLL status changed(Unknown, LockAcq, Locked, Holdover, FreeRun).
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_EVENT_DPLL_STATUS

System Log Message	dpll_state: <i>dpll-state</i>
Description	Signifies DPLL status changed(Unknown, LockAck, Locked, Holdover, FreeRun).
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_EVENT_LED_STATE_CHANGED

System Log Message	ifIndex: <i>snmp-interface-index</i> , ifName: <i>interface-name</i> , led-state: <i>led-state</i>
Description	Signifies LED color changed.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_EVENT_PRI_REF_CHANGED

System Log Message	<i>ifIndex: snmp-interface-index, ifName: interface-name</i>
Description	Signifies Primary reference changed.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_EVENT_PRI_SRC_RECOVERED

System Log Message	<i>ifIndex: snmp-interface-index, ifName: interface-name</i>
Description	Signifies Primary source recovered.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_EVENT_PTP_CLOCK_ACCU_CHG

System Log Message	<i>gm_id: ptp-gm-id, clock_accuracy: clock-accuracy</i>
Description	Signifies PTP clock accuracy changed.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_EVENT_PTP_CLOCK_CLASS_CHG

System Log Message	<i>gm_id: ptp-gm-id, clock_class: clock-class</i>
Description	Signifies PTP clock class changed.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_EVENT_PTP_GM_CHG

System Log Message	<i>gm_id: ptp-gm-id</i>
Description	Signifies PTP Grand Master changed.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_EVENT_PTP_HYBRID_STATUS

System Log Message	<i>hybrid_state: hybrid-state</i>
Description	Signifies Hybrid state changed (Init, FreqAcq, FreqLckPhaseAcq, FreqPhaseLck)
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_EVENT_PTP_SERVO_STATUS

System Log Message	<i>spll_state: servo-state</i>
Description	Signifies PTP servo state changed(Init, FreeRun, Holdover, Acquiring, FreqLock, PhaseAlinged).
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_EVENT_RX_QL_CHANGED

System Log Message	<i>ifIndex: snmp-interface-index, ifName: interface-name, new_rx_ssm_ql: ql-code</i>
Description	Signifies RX quality level changed.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_EVENT_SEC_REF_CHANGED

System Log Message	ifIndex: <i>snmp-interface-index</i> , ifName: <i>interface-name</i>
Description	Signifies Secondary reference changed.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_EVENT_SEC_SRC_RECOVERED

System Log Message	ifIndex: <i>snmp-interface-index</i> , ifName: <i>interface-name</i>
Description	Signifies Secondary recovered failed. .
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_EVENT_SQUELCH_CLEAR

System Log Message	ifIndex: <i>snmp-interface-index</i> , ifName: <i>interface-name</i>
Description	Interface activated.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_EVENT_SQUELCH_SET

System Log Message	ifIndex: <i>snmp-interface-index</i> , ifName: <i>interface-name</i>
Description	Interface squelched.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_EVENT_SYNCE_DPLL_STATUS

System Log Message	<i>ifIndex: snmp-interface-index, ifName: interface-name, dpll_state: dpll-state</i>
Description	Signifies SyncE DPLL status changed(Unknown, LockAck, Locked, Holdover, FreeRun).
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_EVENT_TX_QL_CHANGED

System Log Message	<i>ifIndex: snmp-interface-index, ifName: interface-name, new_tx_ssm_ql: ql-code</i>
Description	Signifies TX quality level changed.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_FAULT_ACBC_NOT_COMPATIBLE

System Log Message	<i>majorVer=snmp-interface-index, minorVer=interface-name</i>
Description	ACBC FPGA version is not compatible is SET.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_FAULT_CPLD_NOT_COMPATIBLE

System Log Message	<i>majorVer=snmp-interface-index, minorVer=interface-name</i>
Description	Boot-cpld version is not compatible is SET.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_FAULT_EFD_CLEAR

System Log Message	ifIndex: <i>snmp-interface-index</i> , ifName: <i>interface-name</i>
Description	exceeded frequency deviation is CLEARed.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_FAULT_EFD_SET

System Log Message	ifIndex: <i>snmp-interface-index</i> , ifName: <i>interface-name</i>
Description	exceeded frequency deviation is SET.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_FAULT_LOS_CLEAR

System Log Message	ifIndex: <i>snmp-interface-index</i> , ifName: <i>interface-name</i>
Description	linkStatus is up.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_FAULT_LOS_SET

System Log Message	ifIndex: <i>snmp-interface-index</i> , ifName: <i>interface-name</i>
Description	linkStatus is down.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_FAULT_LO_ESMC_CLEAR

System Log Message	ifIndex: <i>snmp-interface-index</i> , ifName: <i>interface-name</i>
Description	loss of ESMC is CLEARed.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_FAULT_LO_ESMC_SET

System Log Message	ifIndex: <i>snmp-interface-index</i> , ifName: <i>interface-name</i>
Description	loss of ESMC is SET.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_FAULT_LTI_CLEAR

System Log Message	ifIndex: <i>snmp-interface-index</i> , ifName: <i>interface-name</i>
Description	loss of timing info is CLEARed.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_FAULT_LTI_SET

System Log Message	ifIndex: <i>snmp-interface-index</i> , ifName: <i>interface-name</i>
Description	loss of timing info is SET.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_FAULT_PRI_SRC_FAILED

System Log Message ifIndex: *snmp-interface-index*, ifName: *interface-name*

Description Signifies Primary source failed.

Type Event: This message reports an event, not an error

Severity warning

Facility ANY

Action Contact your technical support representative.

CLKSYNCD_FAULT_PTP_UNI_NEG_RATE_REJ_CLEAR

System Log Message streamHandle: *stream-handle*, remotelpAddr: *remote-address*

Description Signifies acceptance of grant duration for PTP Signalling messages.

Type Event: This message reports an event, not an error

Severity notice

Facility ANY

Action Contact your technical support representative.

CLKSYNCD_FAULT_PTP_UNI_NEG_RATE_REJ_SET

System Log Message streamHandle: *stream-handle*, remotelpAddr: *remote-address*

Description Signifies rejecting or receiving rejection for PTP Signalling messages.

Type Event: This message reports an event, not an error

Severity warning

Facility ANY

Action Contact your technical support representative.

CLKSYNCD_FAULT_QL_FAIL_CLEAR

System Log Message ifIndex: *snmp-interface-index*, ifName: *interface-name*

Description quality level failed is CLEARed.

Type Event: This message reports an event, not an error

Severity notice

Facility ANY

Action Contact your technical support representative.

CLKSYNCD_FAULT_QL_FAIL_SET

System Log Message	ifIndex: <i>snmp-interface-index</i> , ifName: <i>interface-name</i>
Description	quality level failed is SET.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	ANY
Action	Contact your technical support representative.

CLKSYNCD_FAULT_SEC_SRC_FAILED

System Log Message	ifIndex: <i>snmp-interface-index</i> , ifName: <i>interface-name</i>
Description	Signifies Secondary source failed.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	ANY
Action	Contact your technical support representative.

CHAPTER 26

COSD System Log Messages

This chapter describes messages with the **COSD** prefix. They are generated by the class-of-service (CoS) process (cosd), which enables the routing platform to provide different levels of service to applications based on packet classifications.

COSD_AGGR_CONFIG_INVALID

System Log Message	Error: Cannot have config <i>error-message interface-name</i>
Description	The class-of-service (CoS) process (cosd) did not apply the config on this interface because it was not valid in this case.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	One possible cause is if any Class-of-Service is configured on an interface which is a part of an aggregated interface
Action	Remove or change the config from/on the interface.

COSD_CHASSIS_SCHED_MAP_INVALID

System Log Message	Chassis scheduler map incorrectly applied to interface <i>interface-name: error-message</i>
Description	The class-of-service (CoS) process (cosd) did not apply a chassis scheduler map to the indicated interface, because the configuration used to apply the scheduler map was invalid.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	One possible cause is that the chassis scheduler map is applied to a specific interface. For most interface types, a scheduler map must be applied to all interfaces on the PIC; therefore, a wildcard must be used to specify the interfaces. One exception to this rule is the Gigabit Ethernet IQ PIC.

Action Correct the configuration used to apply the chassis scheduler map to the interface.

COSD_CLASSIFIER_NO_SUPPORT_LSI

System Log Message Cannot support classifier type *classifier-type* on lsi interface *interface-name*

Description The Differentiated Services code point (DSCP) classifier and the 802.1p classifier are only supported on I-Chip based Flexible PIC Concentrators (FPCs).

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Remove the DSCP or the 802.1p classifier configuration from the routing instance

COSD_CLASS_8021P_UNSUPPORTED

System Log Message ieee-802.1 classifier is not valid on interface *interface-name*

Description The IEEE 802.1p classifier is not supported on the indicated interface.

Type Error: An error occurred

Severity warning

Facility LOG_DAEMON

Action Remove the 802.1p classifier configuration from the interface, or configure an interface encapsulation type that supports 802.1p classifiers.

COSD_CLASS_NO_SUPPORT_IFD

System Log Message BA/Fixed Classifier or Rewrite on Physical Interface is not allowed when ethernet switching family is configured: interace *interface-name*

Description The Rewrite is not supported on this interface when ethernet switching is enabled

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Remove the classifier configuration from the interface, instead apply it on the logical interface where ethernet switching family is enabled

Action Remove the Rewrite configuration from the interface, instead apply it on the logical interface where ethernet switching family is enabled

COSD_CLASS_NO_SUPPORT_L3_IFL

System Log Message	BA/Fixed Classifier or Rewrite config is not allowed on logical interface (<i>interface-name</i>) with inet/inet6 family
Description	The Rewrite is not supported on this logical interface
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Remove the classifier configuration from the logical interface, instead apply it on the main interface if inet/inet6 is configured on one of its logical interfaces
Action	Remove the Rewrite configuration from the logical interface, instead apply it on the main interface if inet/inet6 is configured on one of its logical interfaces

COSD_CONF_OPEN_FAILURE

System Log Message	Unable to open: <i>filename</i> , using default CoS forwarding classes, do 'commit full' in cli to avoid this message
Description	The class-of-service (CoS) process (cosd) could not read configuration data.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	All of the following reasons: mgd -l fails after upgrade-the file cosd.conf does not exist and is not created because of the mgd -l failure The first commit is 'commit' and not 'commit full'-the file cosd.conf does not commit and is not created automatically [class-of-service forwarding-classes] does not exist-the file cosd.conf does not get exported with plain 'commit'
Action	Do a 'commit full'

COSD_DB_OPEN_FAILED

System Log Message	Unable to open configuration database: <i>error-message(name)</i>
Description	The class-of-service (CoS) process (cosd) could not read configuration data for the indicated reason.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	The specified database does not exist

Action Contact your technical support representative.

COSD_EXACT_RATE_UNSUPP_INTERFACE

System Log Message	Unable to apply scheduler map <i>scheduler-map</i> to interface <i>interface-name</i> because it does not support exact-rate transmission
Description	The class-of-service (CoS) process (cosd) did not apply the indicated scheduler map to the indicated interface, because a scheduler named in the scheduler map specifies exact transmission rate. The interface is housed on a type of PIC that does not support exact transmission rate, such as an IQ2 PIC. In terms of configuration, the 'exact' statement is included in the scheduler definition at the [edit class-of-service schedulers <scheduler-name> transmit-rate (<rate> percent <percentage>)] hierarchy level. The scheduler is included in the scheduler map that is applied to the interface.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Remove the 'exact' statement from the scheduler in the scheduler map applied to the interface.

COSD_EXACT_RATE_UNSUPP_SESSION

System Log Message	Unable to apply CoS to L2TP session <i>session-id</i> , because scheduler map <i>scheduler-map</i> specifies exact rate transmission
Description	The class-of-service (CoS) process (cosd) did not apply CoS settings to the indicated Layer 2 Tunneling Protocol (L2TP) session, because the scheduler map specified by the RADIUS server for the session is configured for exact transmission rate. Exact transmission rate is not supported for L2TP sessions on the type of PIC that houses the interface, such as an IQ2 PIC. In terms of configuration, the 'exact' statement is included in a scheduler definition at the [edit class-of-service schedulers <scheduler-name> transmit-rate (<rate> percent <percentage>)] hierarchy level. The scheduler is included in a scheduler map that is associated with a traffic control profile. The traffic control profile is named by an attribute in the RADIUS server's configuration file, which makes the profile apply to the session.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Remove the 'exact' statement from the scheduler in the scheduler map applied to the session.

COSD_EXP_RW_L2_IFL_NOT_SUPPORTED

System Log Message	EXP Rewrite on IFL is not allowed when ethernet switching family is configured: interace <i>interface-name</i>
---------------------------	--

Description	EXP rewrite is not supported on this logical interface.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Remove the exp rewrite configuration from the logical interface.

COSD_FABRIC_QUEUE_OVERFLOW

System Log Message	Fabric Queue depth for fpc <i>fpc-slot</i> pfe <i>pfe</i> <i>queue-name</i> priority <i>queue-index</i> <i>queue-number</i> exceeded threshold <i>percentage-value</i> percentage
Description	The fabric queue is overflowing on the Flexible PIC Concentrator/Packet Forwarding Engine.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	No action required

COSD_FRAGMENTATION_MAP_CONFLICT

System Log Message	Interface <i>compression-device</i> matches wildcard <i>wildcard-interface-name</i> , but fragmentation map <i>fragmentation-map</i> was not applied because interface is compression device for link interface <i>link-interface-name</i>
Description	The indicated fragmentation map is normally applied to interfaces that match the indicated wildcard. The class-of-service (CoS) process (cosd) did not apply the fragmentation map to the indicated interface, even though it matches the wildcard, because the interface is acting as a compression device for the indicated link interface.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	Correct the configuration of the fragmentation map.

COSD_HIGH_PRIO_QUEUES_INTERFACE

System Log Message	Unable to apply scheduler map <i>scheduler-map</i> to interface <i>interface-name</i> , because multiple schedulers in map have "high," "medium-high," or "strict-high" priority
Description	The class-of-service (CoS) process (cosd) did not apply the indicated scheduler map to the indicated interface, because the map includes more than one scheduler that has high, medium-high, or strict-high priority. For interfaces that are housed by certain PICs, such as an IQ2 PIC, the scheduler map can include only one scheduler that specifies one of those three priority levels. In terms of configuration, the 'priority' statement at the [edit

class-of-service schedulers <scheduler-name>] hierarchy level has the value 'high, ' 'medium-high, ' or 'strict-high' for more than one of the schedulers in the map.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Correct the configuration so that the scheduler map includes only one scheduler with high, medium-high, or strict-high priority.

COSD_HIGH_PRIO_QUEUES_SESSION

System Log Message Unable to apply CoS to L2TP session *session-id*, because multiple schedulers in scheduler map *scheduler-map* have "high," "medium-high," or "strict-high" priority

Description The class-of-service (CoS) process (cosd) did not apply CoS settings to the indicated Layer 2 Tunneling Protocol (L2TP) session because the scheduler map specified by the RADIUS server for the session includes more than one scheduler that has high, medium-high, or strict-high priority. For interfaces that are housed by certain Physical Interface Cards (PICs), such as an IQ2 PIC, the scheduler map can include only one scheduler that specifies one of those three priority levels. In terms of configuration, the 'priority' statement at the [edit class-of-service schedulers <scheduler-name>] hierarchy level has the value 'high, ' 'medium-high, ' or 'strict-high' for more than one of the schedulers in the map. The map is associated with a traffic control profile that is named by an attribute in the RADIUS server's configuration file, which makes the profile apply to the session.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Correct the configuration so that the scheduler map includes only one scheduler with high, medium-high, or strict-high priority.

COSD_IFD_OUTPUT_SHAPING_RATE_ERR

System Log Message Traffic shaping not supported on interface device *interface-name*

Description The class-of-service (CoS) process (cosd) did not apply the shaping rate that is configured for the indicated interface.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	Shaping rate is valid only for interfaces housed by IQ and IQ2 PICs, and the interface is on a different type of PIC.

Action Remove the shaping rate configuration from the interface.

COSD_IFD_SHAPER_ERR

System Log Message port shaper not allowed on interface *interface-name*

Description The non-queuing dense port concentrators (DPCs) did not support the specified shaping rate.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause The port shaper was not supported on the non-queuing DPCs.

Action Remove the shaping rate configuration from the interface.

COSD_INTERFACE_NO_MEDIA

System Log Message Unable to obtain media information for interface *interface-name*

Description The message sent by the kernel for the indicated interface did not include required media information.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause An internal software failure occurred.

Action Contact your technical support representative.

COSD_L2TP_COS_NOT_CONFIGURED

System Log Message Unable to apply CoS to L2TP session *session-id* because session-aware CoS is not enabled for interface *interface-name*

Description The class-of-service (CoS) process (cosd) did not apply CoS settings to the indicated Layer 2 Tunneling Protocol (L2TP) session on the indicated interface, because the interface is not configured to support session-aware CoS for L2TP. In terms of configuration, the 'per-session-scheduler' statement is not included at the [edit interfaces <interface-name> unit <logical-unit-number>] hierarchy level.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Include the 'per-session-scheduler' statement in the configuration for the interface.

COSD_L2TP_COS_NOT_SUPPORTED

System Log Message	Unable to apply CoS to L2TP session <i>session-id</i> on interface <i>interface-name</i> : it does not support CoS
Description	The class-of-service (CoS) process (cosd) did not apply CoS settings to the indicated Layer 2 Tunneling Protocol (L2TP) session on the indicated interface. The interface is configured to support session-aware CoS for L2TP, but is not on a PIC that supports that feature, such as an IQ2 PIC. In terms of configuration, the 'per-session-scheduler' statement is included at the [edit interfaces <interface-name> unit <logical-unit-number>] hierarchy level.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Determine whether the interface is on an PIC that supports session-aware CoS; if not, remove the 'per-session-scheduler' statement.

COSD_L2TP_SHAPING_NOT_CONFIGURED

System Log Message	Unable to apply CoS to L2TP session <i>session-id</i> because session-aware shaping is not enabled for interface <i>interface-name</i>
Description	The class-of-service (CoS) process (cosd) did not apply CoS settings to the indicated Layer 2 Tunneling Protocol (L2TP) session on the indicated interface, because session-aware traffic shaping for L2TP is not configured on the PIC that houses the interface. In terms of configuration, the 'session-shaping' statement is not included at the [edit chassis fpc <slot-number> pic <pic-number> traffic-manager mode] hierarchy level.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Include the 'session-shaping' statement in the configuration for the PIC.

COSD_LARGE_DELAY_BUFFER_INVALID

System Log Message	Error for interface <i>interface-name</i> <i>error-message</i>
Description	The class-of-service (CoS) process (cosd) did not apply the large delay buffer setting that is configured for the indicated interface.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

Cause The interface is not housed on one of the PIC types that support large delay buffer.

Action Remove the large delay buffer configuration from the interface.

COSD_MALLOC_FAILED

System Log Message malloc failed: *error-message*

Description The class-of-service (CoS) process (cosd) could not dynamically allocate memory for the indicated reason.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause A software bug caused a memory leak or the Routing Engine did not have sufficient memory.

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18862>.

COSD_MAX_FORWARDING_CLASSES_ABC

System Log Message exceeding max 4 forwarding-class support.

Description User configuration exceeds the maximum number of forwarding class that is supported.

Type Error: An error occurred

Severity warning

Facility LOG_DAEMON

Action Configure only four forwarding classes

COSD_MPLS_DSCP_CLASS_NO_SUPPORT

System Log Message Cannot support MPLS DSCP classifier on ifl *interface-name*

Description The MPLS Differentiated Services code point (DSCP) classifier is only supported on I-Chip based Flexible PIC Concentrators (FPCs). It is not supported on Q2 PICs.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Remove the MPLS DSCP classifier configuration from the logical interface.

COSD_MULTILINK_CLASS_CONFLICT

System Log Message	Fragmentation map <i>fragmentation-map</i> for wildcard <i>wildcard-interface-name</i> specified multilink class <i>class-name</i> for queue <i>queue-number</i> on interface <i>interface-name</i> , which exceeds configured limit of <i>limit</i>
Description	The indicated fragmentation map is normally applied to interfaces that match the indicated wildcard, and specifies the indicated multilink class setting for queues on those interfaces. The class-of-service (CoS) process (cosd) did not apply the fragmentation map to the indicated interface, even though it matches the wildcard, because the setting in the map exceeds the indicated class limit, which is configured on the interface itself.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	Correct the configuration so that the multilink class setting in the fragmentation map does not exceed the class limit for the interface.

COSD_NULL_INPUT_ARGUMENT

System Log Message	NULL input argument : <i>error-message</i>
Description	The pointer that was passed to this function was NULL.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

COSD_OUT_OF_DEDICATED_QUEUES

System Log Message	Queue usage count for interface <i>interface-name</i> is at <i>percentage-value</i> percent
Description	The class-of-service (CoS) process (cosd) is running out of dedicated queues.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

COSD_RATE_LIMIT_INVALID

System Log Message	Unable to apply scheduler map <i>scheduler-map</i> to interface <i>interface-name</i> . <i>description</i> .
Description	The class-of-service (CoS) process (cosd) did not apply the indicated scheduler map to the indicated interface, because the number of rate limited queues in the scheduler map exceeded the limit supported by this interface or the priority is not supported. The interface is housed in a type of PIC that does not support the number of configured rate

limited queues or the priority is not supported. In terms of configuration, the 'rate-limit' statement is included in the scheduler definition at the [edit class-of-service schedulers <scheduler-name> transmit-rate <rate> | percent <percentage>] hierarchy level. The scheduler is included in the scheduler map applied to the interface.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Either limit the number of rate-limited schedulers in this scheduler map to the allowed maximum for this PIC and interface type or check the allowed priority for rate-limited queues

COSD_RATE_LIMIT_NOT_SUPPORTED

System Log Message Unable to apply scheduler map *scheduler-map* to interface *interface-name* because it does not support rate limiting

Description The class-of-service (CoS) process (cosd) did not apply the indicated scheduler map to the indicated interface, because a scheduler named in the scheduler map is configured for rate limiting. The interface is housed in a type of PIC that does not support rate limiting. In terms of configuration, the 'rate-limit' statement is included in the scheduler definition at the [edit class-of-service schedulers <scheduler-name> transmit-rate <rate> | percent <percentage>] hierarchy level. The scheduler is included in the scheduler map applied to the interface.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Remove the 'rate-limit' statement from the scheduler in the scheduler map applied to the interface.

COSD_REWRITE_RULE_LIMIT_EXCEEDED

System Log Message Number of rewrite rules applied to interface *interface-name* exceeds limit (*maximum-value*)

Description The class-of-service (CoS) process (cosd) determined that the number of rewrite rules applied to the indicated interface exceeds the indicated limit for the interface. In terms of configuration, too many rewrite rules are included at the [edit class-of-service interfaces <interface-name> unit <logical-unit-number> rewrite-rules] hierarchy level.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Remove rewrite rules from the configuration for the interface.

COSD_RL_IFL_NEEDS_SHAPING

System Log Message	"rate-limit" configured in <i>scheduler-map</i> , but ifl <i>interface-name</i> does not have output shaper configured. It will use the ifd-shaping rate/ifd-transmit rate for implementation of rate-limit.
Description	The 'rate-limit' statement is configured in one or more schedulers that are part of the indicated scheduler map. In order to apply this scheduler map to the indicated interface, output shaping rate should be configured on the interface. Since no output shaping rate is configured, the transmit rate or shaping rate of the parent interface will be used instead.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	Configure output shaping rate for the indicated interface

COSD_SCHEDULER_MAP_CONFLICT

System Log Message	Forwarding classes " <i>first-forwarding-class</i> " and " <i>second-forwarding-class</i> " in scheduler map <i>scheduler-map</i> both map to queue <i>queue-number</i>
Description	Both of the indicated forwarding classes, which are defined in the indicated scheduler map, map to the same indicated queue. The double mapping is invalid.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Map only one forwarding class to the queue.

COSD_SCHED_AVG_CONST_UNSUPPORTED

System Log Message	Averaging constant not supported on interface <i>interface-name</i> . Value set in scheduler-map <i>scheduler-map</i> (<i>scheduler name</i>) will be ignored.
Description	Configuring averaging constant is not supported on the indicated interface. Value set in the indicated scheduler will be ignored.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	Remove the averaging-constant configuration from the indicated scheduler.

COSD_SCHED_MAP_GROUP_CONFLICT

System Log Message	Interface <i>interface-name</i> cannot be bound to scheduler-map <i>scheduler-map</i> . It will be bound to default scheduler-map
Description	Interfaces belonging to a group cannot be bound to different scheduler maps. They will be bound to the default scheduler map.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Map only one scheduler map to all the interfaces of a group.

COSD_SHAPER_GROUP_CONFLICT

System Log Message	Interface <i>interface-name</i> cannot be bound to configured shaping-rate. It will be bound to default rate
Description	Interfaces belonging to a group cannot be bound to different shaping rates. They will be bound to the default shaping rate.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Map only one shaping rate to all interfaces of a group.

COSD_STREAM_IFD_CREATE_FAILURE

System Log Message	Unable to create special master interface device for <i>interface-name</i>
Description	The class-of-service (CoS) process (cosd) could not create the indicated internal interface device, which it needs for application of a chassis scheduler map.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

COSD_TIMER_ERROR

System Log Message	Unable to set retry timer for rtsock write operation: <i>error-message</i>
---------------------------	--

Description	The class-of-service (CoS) process (cosd) used a routine from the rtsock library to write to the kernel, but the kernel did not accept the request. The cosd process could not set the retry timer for the request, for the indicated reason.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

COSD_TRICOLOR_ALWAYS_ON

System Log Message	tri-color is always enabled in this platform. There is no need to explicitly set it.
Description	Tri-color marking is always enabled on this platform. There is no need to explicitly set it.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	Remove the 'tri-color' configuration statement

COSD_TRICOLOR_NOT_SUPPORTED

System Log Message	Unable to apply scheduler <i>scheduler-map</i> to interface <i>interface-name</i> , because it does not support tricolor marking
Description	The class-of-service (CoS) process (cosd) did not apply the indicated scheduler map to the indicated interface, because a scheduler included in the map specifies a packet loss priority (PLP) that is supported only with tricolor marking (TCM). The interface does not support TCM, either because TCM is not enabled or the interface is on a router that does not support TCM. In terms of configuration, the value 'medium-high' or 'medium-low' is specified for the 'loss-priority' statement in a scheduler definition at the [edit class-of-service schedulers <scheduler-name> drop-profile-map] hierarchy level. The scheduler is included in the scheduler map applied to the interface, but the 'tri-color' statement is either not included at the [edit class-of-service] hierarchy level, or is not supported.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Change the value of the 'loss-priority' statement in the scheduler or include the 'tri-color' statement to enable TCM on the router.

COSD_TX_QUEUE_RATES_TOO_HIGH

System Log Message	Unable to apply scheduler map <i>scheduler-map</i> to interface <i>interface-name</i> : sum of scheduler transmission rates exceeds interface shaping or transmission rate
Description	The class-of-service (CoS) process (cosd) did not apply the indicated scheduler map to the indicated interface, because the sum of the queue transmission rates defined in the schedulers in the scheduler map exceeds the shaping or transmission rate for the interface. In terms of configuration, the 'transmit-rate' statement is specified for each scheduler at the [edit class-of-service schedulers <scheduler-name>] hierarchy level. The sum of the configured transmission rates exceeds the transmission or shaping rate of the interface.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Decrease the value of one or more 'transmit-rate' statements so that the sum is less than the interface transmission or shaping rate.

COSD_UNKNOWN_CLASSIFIER

System Log Message	classifier type <i>classifier-type</i> is invalid
Description	The class-of-service (CoS) process (cosd) did not recognize the indicated classifier type from the rtsock library.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

COSD_UNKNOWN_REWRITE

System Log Message	rtsock rewrite type <i>type</i> is invalid
Description	The class-of-service (CoS) process (cosd) did not recognize the indicated rewrite type from the rtsock library.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Cause	An internal software failure occurred.

Action Contact your technical support representative.

COSD_UNKNOWN_TRAFFIC_CLASS_MAP

System Log Message traffic-class-map type *traffic-class-map-type* is invalid

Description The class-of-service (CoS) process (cosd) did not recognize the indicated traffic-class-map type from the rtsock library.

Type Error: An error occurred

Severity warning

Facility LOG_DAEMON

Cause An internal software failure occurred.

Action Contact your technical support representative.

COSD_UNKNOWN_TRANSLATION_TABLE

System Log Message rtsock translation table type *translation-table-type* is invalid

Description The class-of-service (CoS) process (cosd) did not recognize the indicated translation table type from the rtsock library.

Type Error: An error occurred

Severity warning

Facility LOG_DAEMON

Cause An internal software failure occurred.

Action For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18866>.

COSD_WAN_QUEUE_OVERFLOW

System Log Message Wan Queue depth for fpc *fpc-slot* Interface *interface-name* queue-index *queue-number* exceeded threshold *percentage-value*

Description A queue from the WAN is overflowing on the Flexible PIC Concentrator.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

Action No action required

CHAPTER 27

DCBX System Log Messages

This chapter describes messages with the **DCBX** prefix. They are generated by the interface process (lldpd), which is a discovery and capability exchange protocol to discover peers and exchange information.

DCBX_PFC_DISABLED

System Log Message	IF <i>interface-name</i> : PFC is getting disabled
Description	PFC is getting disabled through DCBX.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON
Cause	The DCBX PFC parameters negotiation is not successful

DCBX_PFC_ENABLED

System Log Message	IF <i>interface-name</i> : PFC is getting enabled
Description	PFC is getting enabled through DCBX.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON
Cause	The DCBX PFC parameters negotiation is successful

DCBX_VERSION

System Log Message	IF <i>interface-name</i> : DCBX TLV version 1.0 received
Description	Ignoring received Data Center Bridging Protocol (DCBX) packet due to old version 1.0
Type	Error: An error occurred
Severity	info
Facility	LOG_DAEMON

Cause The software on the Host Bus Adapter (HBA) is not up-to-date

CHAPTER 28

DCD System Log Messages

This chapter describes messages with the **DCD** prefix. They are generated by the interface process (dcd), which controls the physical interface devices and logical interfaces in the routing platform.

DCD_AE_CONFIG_WARNING

System Log Message	<i>interface-name</i> : AE is not supported in OSE mode for <i>pic-type</i> PIC type
Description	Aggregated Ethernet cannot be configured on PD-5-10XGE-SFPP that is not explicitly configured for linerate mode.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	Set this PIC to linerate mode, or remove the Aggregated Ethernet configuration for the PD-5-10XGE-SFPP link.

DCD_FWD_CLASS_ACC_NOT_SUPPORTED

System Log Message	<i>interface-name</i> : Forwarding-class accounting is supported only on MPCs
Description	Forwarding-class accounting is supported only on LU based MPCs.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

DCD_FWD_CLASS_ACC_NOT_SUPPORTED_IFL

System Log Message	<i>interface-name.interface-unit</i> : Forwarding-class accounting is not supported on this MPC
Description	Forwarding-class accounting on the logical interface is supported only on LU based MPCs.
Type	Error: An error occurred
Severity	error

Facility LOG_DAEMON

DCD_GRE_CONFIG_INVALID

System Log Message	Either tunnel key or clear-dont-fragment-bit must be configured for this GRE tunnel (<i>interface-name</i>), to enable post fragmentation
Description	This interface needs either the tunnel key or the clear-dont-fragment-bit to be configured along with allow-fragmentation
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Configure either the tunnel key or clear-dont-fragment-bit for this tunnel

DCD_GRE_CONFIG_NOT_SUPPORTED

System Log Message	The clear-dont-fragment-bit option is not supported on GRE tunnel (<i>interface-name</i>), due to the FPC not supporting it
Description	This interface is configured on a Flexible PIC Concentrator (FPC) that does not support the clear- dont-fragment-bit statement at the [edit interfaces] hierarchy level.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Move the Physical Interface Card (PIC) to an FPC that is based on an I-Chip. For more information, see KB25385.

DCD_MALLOC_FAILED_INIT

System Log Message	Memory allocation failed during initialization for configuration load
Description	The interface process (dcd) could not dynamically allocate memory in preparation for loading a configuration.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	A software bug caused a memory leak, or the routing platform had insufficient memory.
Action	Contact your technical support representative.

DCD_PARSE_CFG_WARNING

System Log Message	<i>configuration-statement</i> : <i>warning-message</i>
---------------------------	---

Description	The interface-control process (dcd) found a discrepant configuration
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Cause	This is a warning message and the current configuration has a few discrepancies to be addressed.
Action	Contact your technical support representative.

DCD_PARSE_EMERGENCY

System Log Message	dcd_config: errors while parsing configuration file
Description	The interface process (dcd) encountered an unhandled internal state while parsing the configuration database.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	There might be a bug in the dcd process' parser.
Action	Contact your technical support representative.

DCD_PARSE_ERROR_CLOCK

System Log Message	PIC housing interface <i>interface-name</i> does not support clocking as configured
Description	The 'clocking' statement is included at the [edit interfaces] hierarchy level for the indicated interface, but is not supported by the 10-Gigabit Ethernet IQ2 PIC.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	Remove the 'clocking' statement from the configuration for the interface.

DCD_PARSE_ERROR_HIER_SCHEDULER

System Log Message	<i>interface-name</i> : hierarchical or shared scheduler is not valid on this interface
Description	The 'hierarchical-scheduler' statement is included at the [edit interfaces] hierarchy level for the indicated interface, but is not supported either by the PIC or the configured type of encapsulation.
Type	Error: An error occurred

Severity	warning
Facility	LOG_DAEMON
Action	Remove the 'hierarchical-scheduler' statement from the configuration for the interface.

DCD_PARSE_ERROR_IFLSET

System Log Message	Interface <i>interface-name</i> does not support 'interface-set' statement
Description	The 'interface-set' statement is included at the [edit interfaces] hierarchy level for the indicated interface, but is not supported by the interface.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	Remove the 'interface-set' statement from the configuration for the interface.

DCD_PARSE_ERROR_MAX_HIER_LEVELS

System Log Message	<i>interface-name</i> : PIC or encapsulation type does not support 'maximum-hierarchy-levels' statement
Description	The 'hierarchical-scheduler maximum-hierarchy-levels' statement is included at the [edit interfaces] hierarchy level for the indicated interface, but is not supported either by the PIC or the configured type of encapsulation.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	Remove the 'hierarchical-scheduler maximum-hierarchy-levels' statement from the configuration for the interface.

DCD_PARSE_ERROR_MAX_HIER_LEVELS_2

System Log Message	<i>interface-name</i> : PIC or encapsulation type does not support 3 levels of scheduler hierarchy
Description	The PIC or encapsulation type configured on the indicated interface supports upto two hierarchy levels and requires including the maximum-hierarchy-levels statement in the hierarchial schedulers configuration.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	To configure two-level hierarchical scheduling, include the maximum-hierarchy-levels statement at the [edit interfaces interface-name hierarchial-scheduler].

DCD_PARSE_ERROR_SCHEDULER

System Log Message	<i>interface-name</i> : PIC or encapsulation type does not support 'per-unit-scheduler' or 'shared-scheduler' statement
Description	The 'per-unit-scheduler' or 'shared-scheduler' statement is included at the [edit interfaces] hierarchy level for the indicated interface, but is not supported either by the PIC or the configured type of encapsulation.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	Remove the 'per-unit-scheduler' or 'shared-scheduler' statement from the configuration for the interface.

DCD_PARSE_ERROR_SCHEDULER_LIMIT

System Log Message	<i>interface-name</i> : exceeds the allowed limit (<i>maximum-value</i>) of 'per-unit-scheduler' interface statement for PIC= <i>pic-slot</i> on FPC= <i>fpc-slot</i>
Description	The 'per-unit-scheduler' statement is enabled on more interfaces than what this PIC would support.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	Remove the 'per-unit-scheduler' statement from the configuration for the interface.

DCD_PARSE_ERROR_VLAN_TAGGING

System Log Message	<i>interface-name</i> : PIC type does not support flexible-vlan-tagging statement
Description	The 'flexible-vlan-tagging' statement is included at the [edit interfaces] hierarchy level for the indicated interface, but is not supported by the PIC that houses the interface.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	Remove the 'flexible-vlan-tagging' statement from the configuration for the interface.

DCD_PARSE_MINI_EMERGENCY

System Log Message	dcd_mini_config: errors while parsing configuration overlay
Description	The interface process (dcd) encountered an unhandled internal state during interface parsing.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	There might be a bug in the dcd process' parser.
Action	Contact your technical support representative. For more information, see KB18870.

DCD_PARSE_STATE_EMERGENCY

System Log Message	An unhandled state was encountered during interface parsing
Description	The interface process (dcd) encountered an unhandled internal state during interface parsing.
Type	Error: An error occurred
Severity	emergency
Facility	LOG_DAEMON
Cause	There might be a bug in the dcd process' parser.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18870 .

DCD_PARSE_WARN_INCOMPATIBLE_CFG

System Log Message	<i>configuration-statement</i> : Incompatible configuration detected : <i>warning-message</i>
Description	The interface process (dcd) found a configuration that will not be supported in future releases.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Cause	This is a warning and the configuration will not be supported in future releases.
Action	Contact your technical support representative.

DCD_RLT_CONFIG_UNSUPPORTED

System Log Message	IFD <i>interface-name</i> cannot be a member interface of rLT
Description	All member interfaces of a redundant logical tunnel interface have to exist on Trio based MPCs only.
Type	Error: An error occurred

Severity error
Facility LOG_DAEMON
Action Do not configure this interface as a member interface of redundant logical tunnel.

CHAPTER 29

DDOS System Log Messages

This chapter describes messages with the **DDOS** prefix. They are generated by the distributed denial-of-service attack (DDoS), which is a denial-of-service (DoS) attack originating from multiple source addresses.

DDOS_PROTOCOL_VIOLATION_CLEAR

System Log Message	Protocol <i>protocol-name</i> has returned to normal. Violated at <i>source-name</i> for <i>repeat-count</i> times, from <i>time-first-detected</i> to <i>time-last-detected</i>
Description	The ddos system detected that the incoming traffic for a violated control protocol returned to normal.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	Check the network configuration.

DDOS_PROTOCOL_VIOLATION_SET

System Log Message	Protocol <i>protocol-name</i> is violated at <i>source-name</i> for <i>repeat-count</i> times, started at <i>time-first-detected</i>
Description	The ddos system detected that the incoming traffic for a control protocol exceeded the configured bandwidth. This could be a ddos attack.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	Check the network configuration and shut down the problem source.

DDOS_RTsock_FAILURE

System Log Message	Failed to <i>action argument</i> , error= <i>error-code</i>
Description	The ddos system process (jddosd) experienced the indicated error with a routing socket.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

DDOS_SCFD_FLOW_AGGREGATED

System Log Message	Flows of protocol <i>protocol-name</i> on slot <i>source-name</i> are aggregated to <i>level</i> level(s)
Description	The ddos system has aggregated flows to a coarse granularity.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	check network configuration

DDOS_SCFD_FLOW_CLEARED

System Log Message	A flow of protocol <i>protocol-name</i> on <i>source-name</i> with source addr <i>source-address</i> is cleared. Found at <i>time-first-detected</i> , last observed <i>time-last-detected</i> .
Description	The ddos system cleared a monitored control flow. Its arriving rate may still be above its bandwidth.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	check logs and the flow may be discovered again

DDOS_SCFD_FLOW_DEAGGREGATED

System Log Message	Flows of protocol <i>protocol-name</i> on slot <i>source-name</i> are deaggregated to <i>level</i> level(s)
Description	The ddos system has deaggregated flows to a finer granularity.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	check network configuration

DDOS_SCFD_FLOW_FOUND

System Log Message	A new flow of protocol <i>protocol-name</i> on <i>source-name</i> with source addr <i>source-address</i> is found at <i>time-first-detected</i>
Description	The ddos system detected a control flow that exceeded its allowed bandwidth. It could be a ddos attack flow.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	check network configuration and shut down problem source

DDOS_SCFD_FLOW_RETURN_NORMAL

System Log Message	A flow of protocol <i>protocol-name</i> on <i>source-name</i> with source addr <i>source-address</i> returned normal and is removed from monitoring. Found at <i>time-first-detected</i> , last observed at <i>time-last-detected</i>
Description	The ddos system detected that the incoming traffic for a violated flow returned to normal and the flow was removed from monitoring.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	check network configurtaion

DDOS_SCFD_FLOW_TIMEOUT

System Log Message	A flow of protocol <i>protocol-name</i> on <i>source-name</i> with source addr <i>source-address</i> is timed out. Found at <i>time-first-detected</i> , last observed at <i>time-last-detected</i>
Description	The ddos system timed out a monitored control flow. Its arriving rate may still be above its bandwidth.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	check logs and the flow may be discovered again

CHAPTER 30

DFCD System Log Messages

This chapter describes messages with the **DFCD** prefix. They are generated by the dynamic flow control process (dfcd), which monitors packet flows using dynamically alterable filtering criteria.

DFCD_FTAP_PIC_UNSUPPORTED

System Log Message	PIC housing interface <i>interface-name</i> does not support flow-tap service
Description	The PIC that houses the indicated interface does not support flow-tap service.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

DFCD_GENCFG_MALLOC_FAILED

System Log Message	GENCFG mem alloc failed !!!
Description	The dynamic flow capture process (dfcd) could not allocate memory for gencfg message.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18874 .

DFCD_GENCFG_WRITE_FAILED

System Log Message	GENCFG write failed for Reason: <i>error-message (error-code)</i>
Description	The dynamic flow capture process (dfcd) could not send gencfg message, for the indicated reason.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

Action For more information, see
<http://kb.juniper.net/InfoCenter/index?page=content&id=KB18875>.

DFCD_LINH_MALLOC_FAILED

System Log Message GENCFG mem alloc failed !!!

Description The dynamic flow capture process (dfcd) could not allocate memory for linh message.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action For more information, see
<http://kb.juniper.net/InfoCenter/index?page=content&id=KB18876>.

DFCD_LI_NEXT_HOP_ADD_FAILED

System Log Message Unable to add li next hop for subscriber interface: *error-message (error-code)*

Description The dynamic flow capture process (dfcd) could not add a subscriber li next hop, for the indicated reason.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

DFCD_NEXT_HOP_ADD_FAILED

System Log Message Unable to add service next hop: *error-message (error-code)*

Description The dynamic flow capture process (dfcd) could not add a service next hop, for the indicated reason.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

DFCD_NEXT_HOP_DELETE_FAILED

System Log Message Unable to delete service next hop: *error-message (error-code)*

Description The dynamic flow capture process (dfcd) could not delete a service next hop, for the indicated reason.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

DFCD_SAMPLE_CLASS_ADD_FAILED

System Log Message	Unable to add sample class: <i>error-message (error-code)</i>
Description	The dynamic flow capture process (dfcd) could not add a sample class, for the indicated reason.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

DFCD_SAMPLE_CLASS_DELETE_FAILED

System Log Message	Unable to delete sample class: <i>error-message (error-code)</i>
Description	The dynamic flow capture process (dfcd) could not delete a sample class, for the indicated reason.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHAPTER 31

DFWD System Log Messages

This chapter describes messages with the **DFWD** prefix. They are generated by the firewall process (dfwd), which manages compilation and downloading of Junos firewall filters.

DFWD_MALLOC_FAILED_INIT

System Log Message	Memory allocation failed during initialization for configuration load
Description	The firewall process (dfwd) could not dynamically allocate memory in preparation for loading a configuration.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	A software bug caused a memory leak, or the routing platform had insufficient memory.
Action	Contact your technical support representative.

DFWD_PARSE_FILTER_EMERGENCY

System Log Message	dfwd encountered errors while parsing filter index file
Description	The firewall process (dfwd) encountered an unhandled internal state while parsing a filter index file.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	There might be a bug in the parser.
Action	Contact your technical support representative.

DFWD_PARSE_STATE_EMERGENCY

System Log Message	dfwd encountered unhandled state while parsing interface
---------------------------	--

Description	The firewall process (dfwd) encountered an unhandled internal state while parsing an interface.
Type	Error: An error occurred
Severity	emergency
Facility	LOG_DAEMON
Cause	There might be a bug in the parser.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18879 .

DFWD_POLICER_LIMIT_EXCEEDED

System Log Message Number of interface policers configured is exceeding maximum allowed *total-count*.

Description	The firewall process (dfwd) detected that number of interface policers configured is exceeding maximum allowed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Reduce the number of interface policers to within allowed limit.

CHAPTER 32

DHCPD System Log Messages

This chapter describes messages with the **DHCPD** prefix. They are generated by the Dynamic Host Configuration Protocol (DHCP) server process (dhcpcd) for J Series Services Routers, which automatically allocates network IP addresses and delivers configuration settings to client hosts in a Transmission Control Protocol (TCP)/IP network.

DHCPD_BIND_FAILURE

System Log Message	bind() to port <i>port</i> failed: <i>error-message</i>
Description	The Dynamic Host Configuration Protocol server process (dhcpcd) received the indicated error when it tried to bind a socket to the indicated local port.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH
Action	Contact your technical support representative.

DHCPD_DEGRADED_MODE

System Log Message	Running in degraded mode because of <i>reason</i> : <i>error-message</i>
Description	The Dynamic Host Configuration Protocol server process (dhcpcd) began running in degraded mode because the indicated unrecoverable error occurred.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH
Cause	There might be a problem with the lease cache directory used to store persistent lease information.
Action	Contact your technical support representative.

DHCPD_MEMORY_ALLOCATION_FAILURE

System Log Message	Unable to allocate memory for <i>object-name</i> : <i>error-message</i>
---------------------------	---

Description The Dynamic Host Configuration Protocol server process (dhcpcd) could not allocate memory from the heap for the indicated object.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

Action Contact your technical support representative.

DHCPD_OPTION_HOST_NAME

System Log Message *option value*

Description The Dynamic Host Configuration Protocol server process (dhcpcd) received a DHCPACK packet with the Host Name option set.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_AUTH

DHCPD_OPTION_LOG_SERVER

System Log Message *option value*

Description The Dynamic Host Configuration Protocol server process (dhcpcd) received a DHCPACK packet with the Log Server option set.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_AUTH

DHCPD_OPTION_NTP_SERVER

System Log Message *option value*

Description The Dynamic Host Configuration Protocol server process (dhcpcd) received a DHCPACK packet with the NTP Server option set.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_AUTH

DHCPD_OVERLAY_CONFIG_FAILURE

System Log Message Unable to open overlay configuration: *error-message*

Description The Dynamic Host Configuration Protocol server process (dhcpcd) could not open an overlay configuration file for parsing.

Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH
Action	Contact your technical support representative.

DHCPD_OVERLAY_PARSE_FAILURE

System Log Message	Unable to parse overlay configuration because of <i>count</i> syntax errors
Description	The Dynamic Host Configuration Protocol server process (dhcpcd) could not parse its overlay configuration because the configuration contained the indicated number of syntax errors.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

DHCPD_RECVMSG_FAILURE

System Log Message	Exiting due to too many recvmsg() failures
Description	The Dynamic Host Configuration Protocol server process (dhcpcd) could not receive data from the network, which it needs to do during normal operation.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH
Action	Contact your technical support representative.

DHCPD_RTsock_FAILURE

System Log Message	Error with rtsock: <i>error-message</i>
Description	The Dynamic Host Configuration Protocol server process (dhcpcd) experienced the indicated error with a routing socket.
Type	Error: An error occurred
Severity	info
Facility	LOG_AUTH
Cause	An internal software failure occurred.

Action Contact your technical support representative.

DHCPD_SENDSMSG_FAILURE

System Log Message sendmsg() from *source-address* to port *destination-port* at *destination-address* via interface *interface-name* and routing instance *routing-instance* failed: *error-message*

Description The Dynamic Host Configuration Protocol server process (dhcpcd) could not send data from the indicated source (address, interface, and routing instance) to the indicated destination (port and address), which it needs to do during normal operation.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

Action Contact your technical support representative.

DHCPD_SENDSMSG_NOINT_FAILURE

System Log Message sendmsg() from *source-address* to port *destination-port* at *destination-address* via routing instance *routing-instance* failed: *error-message*

Description The Dynamic Host Configuration Protocol server process (dhcpcd) could not send data from the indicated source (address and routing instance) to the indicated destination (port and address), which it needs to do during normal operation.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

Action Contact your technical support representative.

DHCPD_SETSOCKOPT_FAILURE

System Log Message setsockopt(*socket-option*) failed: *error-message*

Description The Dynamic Host Configuration Protocol server process (dhcpcd) could not set the indicated socket option.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

Action Contact your technical support representative.

DHCPD_SOCKET_FAILURE

System Log Message socket(*arguments*) failed: *error-message*

Description The Dynamic Host Configuration Protocol server process (dhcpcd) could not create a socket.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

Action Contact your technical support representative.

CHAPTER 33

DIAM System Log Messages

This chapter describes messages with the **DIAM** prefix.

DIAM_PEER_CONN_STATE_CHANGE

System Log Message	Diameter Peer <i>diameter-peer</i> <i>diameter-peer-conn-state</i> on SPIC <i>spic-name</i>
Description	This notification signifies that the diameter connection state to specified diameter peer on the specified Session PIC has changed from UP to DOWN/FAIL or vice-versa.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

DIAM_PEER_OUTQ_HIGH_WATERMARK

System Log Message	Diameter Peer [<i>diameter-peer</i>] Outgoing queue on SPIC [<i>spic-name</i>] hit HIGH water mark percent of [<i>diameter-peer-outq-high-wmark</i>]
Description	This notification signifies that the outgoing queue size of the specified diameter peer has reached higher watermark on the specified Session PIC.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

DIAM_PEER_OUTQ_LOW_WATERMARK

System Log Message	Diameter Peer [<i>diameter-peer</i>] Outgoing queue on SPIC [<i>spic-name</i>] hit LOW water mark percent of [<i>diameter-peer-outq-low-wmark</i>]
Description	This notification signifies that the outgoing queue size of the specified diameter peer has reached Lower watermark on the specified Session PIC.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

DIAM_PROFILE_STATE_CHANGE

System Log Message	Diameter Application Profile [<i>diameter-app-profile</i>] is [<i>diameter-app-profile-state</i>]
Description	This notification signifies that the specified diameter profile has changed state from UP to DOWN or vice-versa.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

DIAM_SPIC_UNAVAILABLE

System Log Message	SPIC [<i>spic-name</i>] which was assigned Diameter Netowrk Element [<i>diameter-network-element</i>] is not available
Description	This notification signifies that the specified Session pic which was assigned a Diameter Network Element did not respond within 300 seconds.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

DIAM_TARGET_STATE_CHANGE

System Log Message	Diameter target [<i>diameter-target</i>] is [<i>diameter-target-state</i>]
Description	This notification signifies that the specified diameter target has changed state from UP to DOWN or vice-versa.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

CHAPTER 34

DOT1XD System Log Messages

This chapter describes messages with the **DOT1XD** prefix. They are generated by the authentication processes such as 802.1X, MAC RADIUS, or captive portal, which control access to a network through a Juniper Networks EX Series Ethernet Switch.

DOT1XD_AUTH_SESSION_DELETED

System Log Message	<i>user-type</i> User <i>username</i> session with MacAddress <i>mac-address</i> interface <i>interface-name</i> vlan <i>vlan-name</i> deleted
Description	Authenticated session has been deleted.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

DOT1XD_MKA_FAIL_ACTION_USER_ALLOWED

System Log Message	<i>user-type</i> User <i>username</i> MacAddress <i>mac-address</i> on macsec best effort interface <i>interface-name</i> allowed without macsec
Description	Dot1x user access is allowed as macsec is not must-secure, though we cannot establish a macsec session with the authenticated user
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

DOT1XD_MKA_FAIL_ACTION_USER_PROHIBITED

System Log Message	<i>user-type</i> User <i>username</i> MacAddress <i>mac-address</i> on macsec must interface <i>interface-name</i> denied, cannot establish macsec session
Description	Dot1x user access is denied as macsec is must-secure and we cannot establish a macsec session with the authenticated user
Type	Event: This message reports an event, not an error
Severity	info

Facility LOG_DAEMON

DOT1XD_MKA_SECURE_CHANNEL_CREATED

System Log Message Macsec receive secure channel created for *mac-addresse* on interface *interface-name*

Description Macsec enabled secure channel is created for a receiver.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

DOT1XD_MKA_SECURE_CHANNEL_DELETED

System Log Message Macsec receive secure channel deleted for *mac-addresse* on interface *interface-name*

Description Macsec enabled secure channel is deleted for a receiver.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

DOT1XD_RCVD_EAPLOGOF_ATHNTCTNG

System Log Message *user-type* User *username* EAP Logoff received from MacAddress *mac-addresse* interface *interface-name* vlan *vlan-name* while authenticating

Description EAP Log off received while authenticating.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

DOT1XD_RCVD_EAPLOGOF_ATHNTICTD

System Log Message *user-type* User *username* EAP Logoff received or MKA timeout for MacAddress *mac-addresse* interface *interface-name* vlan *vlan-name* while authenticated

Description EAP Log off received while authenticated.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

DOT1XD_RCVD_EAPLOGOF_CONNECTNG

System Log Message *user-type* User *username* EAP Logoff received from MacAddress *mac-addresse* interface *interface-name* vlan *vlan-name* while connecting

Description EAP Log off received while connecting.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

DOT1XD_USR_ACCESS_DENIED

System Log Message *user-type* User *username* authentication failed in MacAddress *mac-addresse* interface *interface-name* vlan *vlan-name*

Description User is unauthenticated and denied access on port.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

DOT1XD_USR_ATHNTICTD_GST_VLAN

System Log Message *user-type* User *username* non responsive host *mac-addresse* on interface *interface-name* moved to guest vlan *vlan-name*

Description User has been authenticated on guest vlan if it is configured and authentication using mac-radius for a non-responsive client failed.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

DOT1XD_USR_AUTHENTICATED

System Log Message Custom_log *user-type* User *username* logged in MacAddress *mac-addresse* interface *interface-name* vlan *vlan-name*

Description User is authenticated and allowed access on port.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

DOT1XD_USR_ON_SRVR_FAIL_VLAN

System Log Message *user-type* User *username* logged in MacAddress *mac-addresse* interface *interface-name* authenticated on server fail vlan *vlan-name*

Description User gets authenticated on server fail vlan if it is configured and when radius server is not reachable.

Type Event: This message reports an event, not an error
Severity info

Facility LOG_DAEMON

DOT1XD_USR_ON_SRVR_REJECT_VLAN

System Log Message *user-type* User *username* logged in MacAddress *mac-addresse* interface *interface-name* authenticated on server reject vlan *vlan-name*

Description User gets authenticated on server reject vlan if it is configured and when radius server rejects the access request.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

DOT1XD_USR_SESSION_DISCONNECTED

System Log Message *user-type* User *username* session with MacAddress *mac-addresse* interface *interface-name* vlan *vlan-name* disconnected

Description User session has been disconnected.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

DOT1XD_USR_SESSION_HELD

System Log Message *user-type* User *username* session with MacAddress *mac-addresse* interface *interface-name* vlan *vlan-name* is held

Description User session has been held and dot1x shall retry authentication after held timer expires.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

DOT1XD_USR_UNATHNTCTD_CLI_CLRD

System Log Message Clearing the interface *interface-name* due to user action

Description User is unauthenticated due to cli clearing.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

CHAPTER 35

DYNAMIC System Log Messages

This chapter describes messages with the **DYNAMIC** prefix. They are generated by the Access Manager client which is used in the dynamic VPN feature. The dynamic VPN feature further simplifies remote access by enabling users to establish Internet Protocol Security (IPsec) VPN tunnels without having to manually configure VPN settings on their PCs or laptops. Instead, authenticated users can simply download the Access Manager Web client to their computers. This Layer 3 remote access client uses client-side configuration settings that it receives from the server to create and manage a secure end-to-site VPN tunnel to the server.

DYNAMIC_VPN_AUTH_CONNECT_FAIL

System Log Message	Unable to connect to fwauthd on socket <i>file-descriptor: error-message</i>
Description	The connection manager authentication process could not connect to fwauthd daemon on the indicated socket.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_AUTH

DYNAMIC_VPN_AUTH_FAIL

System Log Message	Username/password and token are <i>username</i>
Description	The connection manager authentication process was unable to authenticate the indicated user/token
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_AUTH

DYNAMIC_VPN_AUTH_INVALID

System Log Message	<i>type username</i> is invalid
Description	The connection manager authentication failed due to invalid user/token
Type	Event: This message reports an event, not an error

Severity error
Facility LOG_AUTH

DYNAMIC_VPN_AUTH_MUL_CONN

System Log Message Connection exists for *type username* at *client-name client-id*

Description Connection already existed for this user

Type Event: This message reports an event, not an error
Severity error
Facility LOG_AUTH

DYNAMIC_VPN_AUTH_NO_CONFIG

System Log Message Authentication failed for *type username* due to unavailable client config

Description The connection manager authentication process was unable to obtain client config for the indicated user/token

Type Event: This message reports an event, not an error
Severity error
Facility LOG_AUTH

DYNAMIC_VPN_AUTH_NO_LICENSE

System Log Message Authentication failed for *type username* due to unavailable license

Description The connection manager authentication process was unable to obtain license for the indicated user/token

Type Event: This message reports an event, not an error
Severity error
Facility LOG_AUTH

DYNAMIC_VPN_AUTH_OK

System Log Message *type username* with *client-name client-id* authenticated successfully.

Description The connection manager authentication process was able to authenticate the indicated user/token successfully

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_AUTH

DYNAMIC_VPN_CLIENT_CONFIG_WRITE

System Log Message Client VPN config is saved in file *filename* for user *username*

Description Connection manager writes client VPN config to file before sending to client.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_AUTH

DYNAMIC_VPN_CONN_DEL_NOTIFY

System Log Message Connection manager receives SA deleted notification for ike-id *gateway-id*

Description Connection manager receives SA deleted notification from IKED.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_AUTH

DYNAMIC_VPN_CONN_DEL_REQUEST

System Log Message Connection manager receives delete request from the client for user *username* ike-id *gateway-id*

Description Connection manager receives connection delete request from the client.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_AUTH

DYNAMIC_VPN_CONN_EST_NOTIFY

System Log Message Connection manager receives SA established notification for ike-id *gateway-id*

Description Connection manager receives SA established notification from IKED.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_AUTH

DYNAMIC_VPN_INIT_SUCCESSFUL

System Log Message Connection manager initialization succeeded.

Description Connection manager is initialized successfully.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_AUTH

DYNAMIC_VPN_LICENSE_ASSIGNED

System Log Message	Dynamic VPN license granted, license <i>limit</i> free, <i>count</i> overdrafted, <i>current-value</i> used
Description	The Access Manager client has successfully acquired a license and is permitted to connect to the device.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_FIREWALL

DYNAMIC_VPN_LICENSE_CHECK_FAILED

System Log Message	Dynamic VPN license check failed for user <i>username</i>
Description	No Access Manager license is available at the moment.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH

DYNAMIC_VPN_LICENSE_CHECK_OK

System Log Message	Dynamic VPN license check succeed for user <i>username</i>
Description	Preliminary check on Access Manager license is successful for the given user.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_AUTH

DYNAMIC_VPN_LICENSE_EXHAUSTED

System Log Message	Dynamic VPN license denied, no available license
Description	The device is out of Access Manager licenses. Connection request from the Access Manager client is denied.
Type	Error: An error occurred
Severity	error
Facility	LOG_FIREWALL

DYNAMIC_VPN_LICENSE_FREED

System Log Message	Dynamic VPN license returned, license <i>limit</i> free, <i>count</i> overdrafted, <i>current-value</i> used
Description	The Access Manager client has disconnected and returned its license.
Type	Event: This message reports an event, not an error

Severity info
Facility LOG_FIREWALL

DYNAMIC_VPN_LICENSE_FREE_FAILED

System Log Message Server failed to free an Access Manager for *username*
Description The Access Manager client attempt to return a license has failed.

Type Event: This message reports an event, not an error
Severity error
Facility LOG_AUTH

DYNAMIC_VPN_LICENSE_FREE_OK

System Log Message Server successfully freed an Access Manager license for *username*
Description The Access Manager client successfully returned a license.

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_AUTH

DYNAMIC_VPN_LICENSE_GET_FAILED

System Log Message Server failed to get an Access Manager license for *username*
Description No Access Manager license is available at the moment.

Type Event: This message reports an event, not an error
Severity error
Facility LOG_AUTH

DYNAMIC_VPN_LICENSE_GET_OK

System Log Message Server successfully got an Access Manager license for *username*
Description The Access Manager client successfully obtained a license.

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_AUTH

DYNAMIC_VPN_LICENSE_INSTALLED

System Log Message Dynamic VPN license *name* installed, license *limit* total, *count* free
Description An Access Manager license was installed successfully on this device.

Type Event: This message reports an event, not an error

Severity info
Facility LOG_FIREWALL

DYNAMIC_VPN_LICENSE_REQUIRED

System Log Message Dynamic VPN license denied, no license installed
Description Requested operation requires an Access Manager license to be installed on this device.

Type Error: An error occurred
Severity error
Facility LOG_FIREWALL

DYNAMIC_VPN_LICENSE_UNINSTALLED

System Log Message Dynamic VPN license *name* deleted, license *limit* total, *count* free
Description An Access Manager license is removed from this device.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_FIREWALL

CHAPTER 36

ESWD System Log Messages

This chapter describes messages with the **ESWD** prefix. They are generated by the ethernet bridging process (eswd).

ESWD_BPDU_BLOCK_ERROR_DISABLED

System Log Message	<i>interface-name</i> : bpdu-block disabled port
Description	This condition occurs when bpdu-block error condition is detected.
Type	Error: An error occurred
Severity	alert
Facility	LOG_DAEMON

ESWD_BPDU_BLOCK_ERROR_ENABLED

System Log Message	<i>interface-name</i> : bpdu-block enabled port
Description	This condition occurs when bpdu-block error condition is cleared.
Type	Error: An error occurred
Severity	alert
Facility	LOG_DAEMON

ESWD_DAI_FAILED

System Log Message	<i>count type</i> received, interface <i>interface-name</i> [index <i>interface-device-index</i>], vlan <i>vlan-name</i> [index <i>vlan-id</i>], sender ip/mac <i>sender-address/mac1</i> , receiver ip/mac <i>destination-address/mac2</i>
Description	The ARP request/response received on this port cannot be linked to any of the IPs assigned by DHCP.
Type	Error: An error occurred
Severity	alert
Facility	LOG_DAEMON

ESWD_DHCP_UNTRUSTED

System Log Message	<i>count</i> untrusted <i>type</i> received, interface <i>interface-name</i> [index <i>interface-device-index</i>], vlan <i>vlan-name</i> [index <i>vlan-id</i>], server ip/mac <i>source-address/mac1</i> , offer ip/client mac <i>client-address/mac2</i>
Description	DHCP server packets are being received on a port which was not meant to receive server traffic.
Type	Error: An error occurred
Severity	alert
Facility	LOG_DAEMON

ESWD_GLOBAL_MAC_LIMIT_ERROR

System Log Message	<i>error-message</i> .
Description	ESWD currently has learnt maximum number of MAC and ESWD does not allow new MAC to be learnt in this condition.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Cause	ESWD reaches global mac learn limit

ESWD_INVALID_MAC_ADDRESS

System Log Message	Invalid MAC address <i>mac-addresse</i> received on <i>interface-name</i>
Description	Received a MAC address that is not in the configured valid MAC addresses for this interface.
Type	Error: An error occurred
Severity	alert
Facility	LOG_DAEMON
Cause	MAC address recieved is not configured as a valid MAC address for this interface.

ESWD_LEARNT_FDB_MEMORY_ERROR

System Log Message	FDB entry for <i>error-message</i> creation failed as ESWD is running low on memory.
Description	ESWD is currently running low on resources and ESWD does not allow MAC to be learnt in this condition.
Type	Error: An error occurred
Severity	error

Facility LOG_DAEMON

Cause It is possible that the ESWD lacked the resources to fulfill the request.

ESWD_MAC_LIMIT_ALERT

System Log Message MAC limit is less than the current number of MACs for the interface. You might want to remove some of the MACs for interface *interface-name* using ``clear ethernet-switching table'` command

Description Log message alerting user to clear the MACs because the number of MACs learned on an interface exceeds the mac limit

Type Error: An error occurred

Severity alert

Facility LOG_DAEMON

ESWD_MAC_LIMIT_BLOCK

System Log Message MAC limit (*limit*) exceeded at *interface-name*: shutting down the interface

Description Interface was blocked because the number of MAC addresses learned on an interface has exceeded the user configured limit.

Type Error: An error occurred

Severity alert

Facility LOG_DAEMON

Cause More learning requests were received by the system than the user configured.

ESWD_MAC_LIMIT_DROP

System Log Message MAC limit (*limit*) exceeded at *interface-name*: dropping the packet from src *mac-address*

Description Learning request was dropped because the number of MAC addresses learned on an interface has reached the user configured limit.

Type Error: An error occurred

Severity alert

Facility LOG_DAEMON

Cause More learning requests were received by the system than the user configured.

ESWD_MAC_LIMIT_EXCEEDED

System Log Message MAC limit (*limit*) exceeded at *interface-name*

Description Number of MAC addresses learned on an interface has exceeded the user configured limit.

Type	Error: An error occurred
Severity	alert
Facility	LOG_DAEMON
Cause	More learning requests were received by the system than the user configured.

ESWD_MAC_MOVE_LIMIT_BLOCK

System Log Message *mac-move-type (limit) exceeded at vlan-name for MAC address mac-addresse; shutting down interface interface-name*

Description Data traffic on interface was halted because the number of times that a MAC addresses moved to a different interface exceeded the user-configured limit.

Type	Error: An error occurred
Severity	alert
Facility	LOG_DAEMON
Cause	A MAC address moved to a different interface more times per second than the user configured.

ESWD_MAC_MOVE_LIMIT_DROP

System Log Message *mac-move-type (limit) exceeded at vlan-name for MAC address mac-addresse; dropping the packet on interface interface-name*

Description Learning request was dropped because the number of times a MAC address moved to a different interface exceeded the user-configured limit.

Type	Error: An error occurred
Severity	alert
Facility	LOG_DAEMON
Cause	A MAC address moved to a different interface more times per second than the user configured.

ESWD_MAC_MOVE_LIMIT_EXCEEDED

System Log Message *mac-move-type (limit) exceeded at vlan-name for MAC address mac-addresse on interface interface-name*

Description The number of times that a MAC address moved to a different interface within a VLAN exceeded the user-configured limit.

Type	Error: An error occurred
Severity	alert
Facility	LOG_DAEMON

Cause A MAC address moved to a different interface more times per second than the user configured.

ESWD_MAC_SMAC_BRIDGE_MAC_IDENTICAL

System Log Message Bridge Address *argument: mac-addresse* SMAC is equal to bridge mac hence don't learn

Description Source mac being same as bridge mac address (mac2me mac) shall not be added to fdb table.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause Dynamic learnt mac or Static mac when learnt or cofigured similar to that of bridge mac address (mac2me mac).

ESWD_MIRROR_ERROR

System Log Message Unable to establish mirror connection between Routing Engines: *error-message*

Description The indicated error occurred when the layer2 control protocol process (l2cpd) tried to establish the nonstop routing mirror connection between the master and standby Routing Engines.

Type Error: An error occurred

Severity warning

Facility LOG_DAEMON

Cause The master and standby Routing Engines are running incompatable versions of the Junos OS.

Action Update the Junos OS on the master Routing Engine, standby Routing Engine, or both, so that they are running compatible versions.

ESWD_MIRROR_VERSION_MISMATCH

System Log Message Versions of mirror software on Routing Engines are incompatible: *error-message*

Description While trying to establish the nonstop routing mirror connection between the master and standby Routing Engines, the layer2 control protocol process (l2cpd) determined that the version of the nonstop routing mirror software on the Routing Engines did not match.

Type Error: An error occurred

Severity warning

Facility LOG_DAEMON

Cause The master and standby Routing Engines are running incompatible versions of the Junos OS.

Action Update the Junos OS on the master Routing Engine, standby Routing Engine, or both, so that they are running compatible versions.

ESWD_MODULE_SHUTDOWN_FAILURE

System Log Message ESWD: *error-message* Module shutdown failed

Description While deleting the instance of logical-switch, RST/MST Module shutdown failed.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action For more information, see KB18890.

ESWD_NDI_FAILED

System Log Message *count type* received, interface *interface-name*[index *interface-device-index*], vlan *vlan-name*[index *vlan-id*], sender ip/mac *sender-address/mac1*, receiver ip/mac *destination-address/mac2*

Description The Neighbor discovery request/response received on this port cannot be linked to any of the IPs assigned by DHCPv6.

Type Error: An error occurred

Severity alert

Facility LOG_DAEMON

ESWD_OUT_OF_LOW_MEMORY

System Log Message *error-message*.

Description ESWD is out of memory overload condition and ESWD can learn new macs now

Type Error: An error occurred

Severity info

Facility LOG_DAEMON

ESWD_PPM_READ_ERROR

System Log Message Read error on pipe from pppmd: *reason (error-message)*

Description The ethernet bridging process (eswd) could not read a message available on the read pipe from the periodic packet management process (ppmd).

Type Error: An error occurred

Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18888 .

ESWD_PPM_WRITE_ERROR

System Log Message	<i>function-name</i> : write error on pipe to pcmd (<i>error-message</i>)
Description	The ethernet bridging process (eswd) could not write a message on the pipe to the periodic packet management process (ppmd).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18889 .

ESWD_STATIC_FDB_MEMORY_WARNING

System Log Message	<i>error-message</i> .
Description	ESWD is currently running low on resources and further creation of FDB static entry may fail.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Cause	It is possible that the ESWD lacked the resources to fulfill the request.

ESWD_STP_BASE_MAC_ERROR

System Log Message	Failed to get <i>error-message</i> . All modules will remain disabled.
Description	This condition occurs when STP cannot derive the base MAC address of the system.
Type	Error: An error occurred
Severity	alert
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18890 .

ESWD_STP_LOOP_PROTECT_CLEARED

System Log Message	<i>interface-name</i> : loop protect cleared for instance <i>instance-id</i>
---------------------------	--

Description This condition occurs when STP loop protect condition is cleared.

Type Error: An error occurred

Severity alert

Facility LOG_DAEMON

ESWD_STP_LOOP_PROTECT_IN_EFFECT

System Log Message *interface-name*: loop protect in effect for instance *instance-id*

Description This condition occurs when STP loop protect condition occurs.

Type Error: An error occurred

Severity alert

Facility LOG_DAEMON

ESWD_STP_ROOT_PROTECT_CLEARED

System Log Message *interface-name*: root protect cleared for instance *instance-id*

Description This condition occurs when STP root protect condition is cleared.

Type Error: An error occurred

Severity alert

Facility LOG_DAEMON

ESWD_STP_ROOT_PROTECT_IN_EFFECT

System Log Message *interface-name*: root protect in effect for instance *instance-id*

Description This condition occurs when STP root protect condition occurs.

Type Error: An error occurred

Severity alert

Facility LOG_DAEMON

ESWD_STP_STATE_CHANGE_INFO

System Log Message *context-name* state for interface *interface-name* context id *instance-id* changed from *old-state* to *new-state*

Description Message is logged to the syslog server when ever there is a state change.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

ESWD_ST_CTL_BW_INFO

System Log Message	<i>interface-name</i> : configured storm control speed <i>level</i> is greater than interface speed <i>bandwidth</i> . Storm control will be set to the latter
Description	Log message to alert the user to the bandwidth setting limits.
Type	Error: An error occurred
Severity	alert
Facility	LOG_DAEMON

ESWD_ST_CTL_ERROR_DISABLED

System Log Message	<i>interface-name</i> : storm control disabled port
Description	This condition occurs when storm control error condition is detected.
Type	Error: An error occurred
Severity	alert
Facility	LOG_DAEMON

ESWD_ST_CTL_ERROR_ENABLED

System Log Message	<i>interface-name</i> : storm control enabled port
Description	This condition occurs when storm-control error condition is cleared.
Type	Error: An error occurred
Severity	alert
Facility	LOG_DAEMON

ESWD_ST_CTL_ERROR_IN_EFFECT

System Log Message	<i>interface-name</i> : storm control in effect on the port
Description	This condition occurs when storm control error condition is detected.
Type	Error: An error occurred
Severity	alert
Facility	LOG_DAEMON

ESWD_ST_CTL_INFO

System Log Message	storm control is enabled for interface <i>interface-name</i>
Description	Log message to alert the user to the storm control setting.
Type	Error: An error occurred
Severity	alert

Facility LOG_DAEMON

ESWD_VLAN_MAC_LIMIT_EXCEEDED

System Log Message *vlan vlan-name mac mac-addresse (tag vlan-id), vlan limit exceeded*

Description Number of MAC addresses learned on a vlan has exceeded the user configured limit.

Type Error: An error occurred

Severity alert

Facility LOG_DAEMON

Cause More learning request were received by the system than the user configured.

ESWD_VMEMBER_MAC_LIMIT_DROP

System Log Message *vlan vlan-name mac mac-addresse (tag vlan-id) interface interface-name, per port per vlan limit exceeded*

Description Number of MAC addresses learned on a per port per vlan has exceeded the user configured limit.

Type Error: An error occurred

Severity alert

Facility LOG_DAEMON

Cause More learning request were received by the system than the user configured.

CHAPTER 37

EVENTD System Log Messages

This chapter describes messages with the **EVENTD** prefix. They are generated by the event policy process (eventd), which performs configured actions in response to events on a routing platform that trigger system log messages.

EVENTD_ACK_FAILED

System Log Message	Unable to send acknowledgment: <i>error-message</i>
Description	JUNOS processes can request that the event processing process (eventd) notify them when a specific event occurs. The eventd process could not send an acknowledgment for a registration request, for the indicated reason.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

EVENTD_ALARM_CLEAR

System Log Message	User <i>username</i> cleared alarm: " <i>timestamp: message</i> "
Description	An administrator has acknowledged and cleared a security alarm.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

EVENTD_ALARM_FILE

System Log Message	Could not open the eventd alarm file ' <i>filename</i> ' for writing
Description	The event processing process (eventd) could not open the alarm statistics file for writing.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

EVENTD_AUDIT_DISABLED

System Log Message	Security audit alarm module " <i>module</i> " disabled
Description	An administrator disabled a security audit module.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

EVENTD_AUDIT_ENABLED

System Log Message	Security audit alarm module " <i>module</i> " enabled
Description	An administrator enabled a security audit module.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

EVENTD_AUDIT_SHOW

System Log Message	User <i>username</i> viewed security audit log with arguments: <i>arguments</i>
Description	An administrator viewed the security audit log.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

EVENTD_COMMAND_SUBSTITUTE_ERROR

System Log Message	Variable substitution failed for command ' <i>command</i> '
Description	The event processing process (eventd) can be configured to execute a JUNOS command-line interface (CLI) command when a specified event occurs. The command can include one or more variables (such as an interface name), which the eventd process replaces with actual values related to the event when it issues the command. Variable substitution failed for the indicated command.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.

EVENTD_CONFIG_CHANGE_FAILED

System Log Message	Configuration change failed: <i>error-message</i> while executing policy <i>policy-name</i> with user <i>username</i> privileges
Description	The event processing process (eventd) could not execute the commands to change configuration data.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

EVENTD_CONFIG_CHANGE_SUCCESS

System Log Message	Configuration change successful: while executing policy <i>policy-name</i> with user <i>username</i> privileges
Description	The event processing process (eventd) successfully executed the commands to change configuration data.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

EVENTD_ESCRIPT_EXECUTION

System Log Message	Trying to execute the script ' <i>filename</i> ' from ' <i>directory-name</i> '
Description	The event process (eventd) executing the configured event script from the specified location.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

EVENTD_ESCRIPT_NOT_CONFIGURED

System Log Message	Trying to execute the non configured script ' <i>filename</i> ' from ' <i>directory-name</i> '
Description	The event process (eventd) executing the non configured event script from the specified location.
Type	Error: An error occurred
Severity	info
Facility	LOG_DAEMON

EVENTD_EVENT_SEND_FAILED

System Log Message	Unable to send event notification: <i>error-message</i>
---------------------------	---

Description Junos processes can request that the event processing process (eventd) notify them when a specific event occurs. The eventd process could not send an event notification for the indicated reason.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18891>.

EVENTD_FORK_ERR

System Log Message Unable to fork: *error-message*

Description The event processing process (eventd) could not create a child process for executing policies.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18892>.

EVENTD_JAIL_SOCKET_FAILURE

System Log Message Could not create jail socket: *error-message*

Description The event processing process (eventd) could not create a jail socket.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

EVENTD_PARSE_CONTROL_INFO_FAILED

System Log Message *error-message*: error in parsing control info

Description Control information received with remote syslog messages are not parsed successfully.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

EVENTD_PIPE_CREATION_FAILED

System Log Message Unable to create pipe: *error-message*

Description The event processing process (eventd) could not create a pipe for interprocess communication.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

EVENTD_POLICY_ACTION_FAILED

System Log Message Unable to execute '*action*' action in policy *policy-name*

Description The event processing process (eventd) could not perform the indicated action, which is specified by the indicated policy.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

EVENTD_POLICY_LIMIT_EXCEEDED

System Log Message Unable to execute policy '*policy-name*' because current number of policies (*count*) exceeds system limit (*limit*)

Description The event processing process (eventd) could not execute the indicated policy, because the indicated number of currently executing policies exceeded the indicated maximum defined by the system.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

EVENTD_POLICY_UPLOAD_FAILED

System Log Message Unable to upload file '*filename*' to destination '*destination-name*' for policy '*policy-name*'

Description The event processing process (eventd) could not upload the indicated file to the indicated destination.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

EVENTD_POPEN_FAIL

System Log Message Error *error-code* in invoking command '*command*'

Description A call to the popen() function failed when the event processing process (eventd) invoked the indicated command.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

EVENTD_READ_ERROR

System Log Message recvmmsg() failed: *error-message*

Description The event processing process (eventd) could not read an event sent to it, for the indicated reason.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

EVENTD_REGEX_INVALID

System Log Message Invalid regular expression '*regular-expression*' provided for attribute value

Description The event processing process (eventd) received a request that included the indicated regular expression as the value for an attribute. The regular expression is not valid.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

EVENTD_REG_VERSION_MISMATCH

System Log Message Registration version *expected-value* did not match expected version (*received-value*)

Description The event processing process (eventd) received a registration request with the indicated version indicator, which does not match the indicated version expected by the eventd process.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

EVENTD_ROTATE_COMMAND_FAILED

System Log Message Command '*command*' failed during rotation of file '*filename*': *error-message*

Description The event processing process (eventd) invoked the indicated command while attempting to rotate the indicated file. The command failed.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

EVENTD_ROTATE_FORK_EXCEEDED

System Log Message	Unable to fork: too many child processes
Description	The event processing process (eventd) could not create a child process for rotating files because adding another child would have made the number of children exceed the limit.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

EVENTD_ROTATE_FORK_FAILED

System Log Message	Unable to fork: <i>error-message</i>
Description	The event processing process (eventd) could not create a child process for rotating files, for the indicated reason.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

EVENTD_SCRIPT_CHECKSUM_MISMATCH

System Log Message	<i>checksum</i> checksum value does not match for script <i>filename</i>
Description	Current checksum value of the script does not match with the checksum configured under [event-options event-script] hierarchy. As a result any event-policy configured inside the script will not be read
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

EVENTD_SECURITY_LOG_CLEAR

System Log Message	User <i>username</i> cleared <i>count</i> security log(s)
Description	An administrator has cleared one or more security audit logs.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

EVENTD_SET_PROCESS_PRIV_FAILED

System Log Message	Unable to set process privilege level to that of user ' <i>username</i> ': <i>error-message</i>
Description	In preparation for executing an action defined in a policy, the event processing process (eventd) tried to change its privilege level to that of the indicated JUNOS user. The

attempt failed. It made the attempt because the user-name statement is included at one of several possible levels under the [edit event-options policy <policy-name> then] hierarchy level.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

EVENTD_SET_TIMER_FAILED

System Log Message evSetTimer failed: *error-message*

Description The event processing process (eventd) starts a timer whenever an internal event needs to be generated. It could not activate the timer for the indicated reason.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

EVENTD_SYSLOG_FWD_FAILED

System Log Message Unable to forward syslog message to PSD (*psd-id*), errno: *error-code*

Description The event processing process (eventd) encountered a system error when forwarding a syslog message to indicated protected system domain (PSD).

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

EVENTD_TEST_ALARM

System Log Message This is test alarm *argument1* of *argument2*

Description This is an alarm test for the eventd alarm infrastructure.

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_DAEMON

EVENTD_TRANSFER_COMMAND_FAILED

System Log Message Command '*error-code*' failed during transfer of file '*command*': *filename*

Description The event processing process (eventd) invoked the indicated command while attempting to transfer the indicated file. The command failed.

Type Error: An error occurred
Severity error

Facility LOG_DAEMON

EVENTD_TRANSFER_FORK_EXCEEDED

System Log Message Unable to fork: too many child processes

Description The event processing process (eventd) could not create a child process for transferring files, because adding another child would have made the number of children exceed the limit.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

EVENTD_TRANSFER_FORK_FAILED

System Log Message Unable to fork: *error-message*

Description The event processing process (eventd) could not create a child process for transferring files, for the indicated reason.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

EVENTD_VERSION_MISMATCH

System Log Message Event version *expected-value* did not match expected version (*received-value*)

Description The event processing process (eventd) received an event with the indicated version indicator, which does not match the indicated version expected by the eventd process.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18893>.

EVENTD_XML_FILENAME_INVALID

System Log Message XML syntax of output filename was invalid

Description An event script created an output file and wrote the filename to standard output (stdout) with Extensible Markup Language (XML) tagging like the following: <event-script-output-filename> output-file.tgz</event-script-output-filename>. The event processing process read the output filename and determined that its XML syntax was invalid.

Type Error: An error occurred

Severity error
Facility LOG_DAEMON

CHAPTER 38

FABOAMD System Log Messages

This chapter describes messages with the **FABOAMD** prefix on the Juniper Networks QFabric QFX3000 switch. They are generated by the QFabric switch Operations, Administration, and Maintenance (OAM) process (faboamd), which enables OAM operations (such as a fabric ping) across different devices in the QFabric switch.

FABOAMD_DEBUGGING

System Log Message	<i>reason: index error-message</i>
Description	A system call made by the Fabric OAM (faboamd) failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	It is possible that the kernel did not have enough resources to fulfill the request.

CHAPTER 39

FC System Log Messages

This chapter describes messages with the **FC** prefix. They are generated by the Fibre Channel process (*fcd*) which connects servers to disks and tape devices in a storage area network.

FC_FABRIC_CREATED

System Log Message	Fabric <i>fc-fabric-name</i> fabric-id <i>fc-fabric-id</i> fabric-type <i>fc-fabric-type</i> created
Description	Fibre channel fabric is created.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

FC_FABRIC_DELETED

System Log Message	Fabric <i>fc-fabric-name</i> fabric-id <i>fc-fabric-id</i> fabric-type <i>fc-fabric-type</i> deleted
Description	Fibre channel fabric is deleted.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

FC_FABRIC_WWN_ASSIGNED

System Log Message	Fabric <i>fc-fabric-name</i> fabric-wwn <i>wwn</i> is set
Description	Fabric_WWN has been set for a fibre channel fabric.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

FC_FABRIC_WWN_CLEARED

System Log Message	Fabric <i>fc-fabric-name</i> fabric-wwn is cleared
---------------------------	--

Description Fabric_WWN is cleared for a fibre channel fabric.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

FC_FLOGI_VN_PORT_LOGIN_FAILED

System Log Message Fabric *fc-fabric-name* interface *interface-name* enode-mac *enode-mac-address* wwn *wwn* - *reason*

Description FIP FLOGI/FDISC from the end node has failed.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

FC_LOGICAL_INTERFACE_CREATED

System Log Message Fabric *fc-fabric-name* interface *interface-name* created

Description Fibre channel logical interface is created.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

FC_LOGICAL_INTERFACE_DELETED

System Log Message Fabric *fc-fabric-name* interface *interface-name* deleted

Description Fibre channel logical interface is deleted.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

FC_LOGICAL_INTERFACE_ISOLATED

System Log Message Fabric *fc-fabric-name* interface *interface-name* reason - *reason*

Description Fibre channel logical interface is isolated.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause Protocol error or repeated failure must have occurred.

Action Check physical connection and reason code for isolation.

Action Interface disable followed by enable might clear this problem.

FC_PROXY_NP_PORT_AVAILABLE

System Log Message Fabric *fc-fabric-name* NP_Port *interface-name*

Description NP_Port is available.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

FC_PROXY_NP_PORT_LB_ADDED

System Log Message Fabric *fc-fabric-name* NP_Port *interface-name* added to fabric load balance list

Description NP_Port is added to the fabric load balance list.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

FC_PROXY_NP_PORT_LB_REMOVED

System Log Message Fabric *fc-fabric-name* NP_Port *interface-name* removed from fabric load balance list

Description NP_Port is removed from the fabric load balance list.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

FC_PROXY_NP_PORT_LOGIN_ABORTED

System Log Message Fabric *fc-fabric-name* NP_Port *interface-name* login aborted

Description Login from NP_Port has aborted.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause It is possible that the NP_Port or fibre channel switch is experiencing timeouts.

FC_PROXY_NP_PORT_LOGIN_FAILED

System Log Message Fabric *fc-fabric-name* NP_Port *interface-name* login failed - *error-message*

Description	Login from NP_Port has failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	NP_Port login is rejected by the fibre channel switch.
Action	Check fibre channel switch configuration.

FC_PROXY_NP_PORT_LOGOUT

System Log Message	Fabric <i>fc-fabric-name</i> NP_Port <i>interface-name</i> logged out by core switch
Description	NP_Port is logged out from the fabric port.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

FC_PROXY_NP_PORT_NPIV_FAILED

System Log Message	Fabric <i>fc-fabric-name</i> NP_Port <i>interface-name</i> attached fabric port does not support NPIV
Description	Fabric port on the fibre channel switch does not support NPIV.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

FC_PROXY_NP_PORT_OFFLINE

System Log Message	Fabric <i>fc-fabric-name</i> NP_Port <i>interface-name</i> is offline
Description	Proxy NP_Port is down.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

FC_PROXY_NP_PORT_ONLINE

System Log Message	Fabric <i>fc-fabric-name</i> NP_Port <i>interface-name</i> fcid: <i>fcid</i> online
Description	Login from NP_Port is completed.
Type	Event: This message reports an event, not an error

Severity info
Facility LOG_DAEMON

FC_PROXY_NP_PORT_RESTORE_FAILED

System Log Message Fabric *fc-fabric-name* NP_Port *wwn:interface-name* restore failed - *reason*

Description FCoE session restoration failed since no NP-Port was found.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON
Cause FCoE session information was incorrectly stored.

FC_PROXY_NP_PORT_UNAVAILABLE

System Log Message Fabric *fc-fabric-name* NP_Port *interface-name*

Description NP_Port is unavailable. The maximum login limit has been reached.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

FC_PROXY_VN_PORT_LOGIN_ABORTED

System Log Message Fabric *fc-fabric-name* NP_Port *interface-name* FDISC is aborted for wwn *wwn*

Description FLOGI or FDISC from the VN_port (end node) is aborted.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON
Cause It is possible that the NP_Port or fibre channel switch is experiencing timeouts.

FC_PROXY_VN_PORT_LOGIN_FAILED

System Log Message Fabric *fc-fabric-name* NP_Port *interface-name* FDISC rejected for wwn *wwn* - *error-message*

Description FLOGI or FDISC from the VN_Port (end node) has failed.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON
Cause VN_Port login is rejected by the fibre channel switch.

CHAPTER 40

FCOE System Log Messages

This chapter describes messages with the **FCOE** prefix. They are generated by the Fibre Channel process (fcd) which connects servers to disks and tape devices in a storage area network.

FCOE_LOGICAL_INTERFACE_CREATED

System Log Message	Fabric <i>fc-fabric-name</i> interface <i>interface-name</i> mac <i>mac-address</i> created
Description	Fibre channel over Ethernet logical interface is created.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

FCOE_LOGICAL_INTERFACE_DELETED

System Log Message	Fabric <i>fc-fabric-name</i> interface <i>interface-name</i> mac <i>mac-address</i> deleted
Description	Fibre channel over Ethernet logical interface is deleted.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

FCOE_LOGICAL_INTERFACE_ISOLATED

System Log Message	Fabric <i>fc-fabric-name</i> interface <i>interface-name</i> mac <i>mac-address</i> reason - <i>reason</i>
Description	Fibre channel over Ethernet logical interface is isolated.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	Protocol error or repeated failure must have occurred.
Action	Check physical connection and reason code for isolation.

Action Interface disable followed by enable might clear this problem.

CHAPTER 41

FIP System Log Messages

This chapter describes messages with the **FIP** prefix. They are generated by the Fibre Channel process (fcd) which connects servers to disks and tape devices in a storage area network.

FIP_ENODE_CLEARED

System Log Message	Fabric <i>fc-fabric-name</i> interface <i>interface-name</i> enode-mac <i>enode-mac-address</i>
Description	FIP end node is removed from a fibre channel fabric.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

FIP_ENODE_FKA_TIMER_EXPIRED

System Log Message	Fabric <i>fc-fabric-name</i> interface <i>interface-name</i> enode-mac <i>enode-mac-address</i> keepalive timer expired
Description	FIP end node keepalive timer expired.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

FIP_ENODE_LEARNED

System Log Message	Fabric <i>fc-fabric-name</i> interface <i>interface-name</i> enode-mac <i>enode-mac-address</i>
Description	FIP End node is learnt on a fibre channel fabric.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

FIP_ENODE_TIMER_EXPIRED

System Log Message	Timer expired for host <i>enode-mac-address</i>
---------------------------	---

Description	FIP end node timer expired.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	Keep alives from end node are not seen

FIP_FCF_TIMER_EXPIRED

System Log Message	Timer expired for fcf <i>fc-fabric-mac-address</i>
Description	FIP FCF timer expired.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	Multicast Discovery Advertisements acting as keep alives from FCF are not seen

FIP_MAX_FCOE_FILTERS_REACHED

System Log Message	Maximum number of allowed FCoE filters (<i>slot</i>) reached for this slot <i>maximum-value</i>
Description	Maximum number of allowed FCoE filters reached.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

FIP_MAX_SESSIONS_REACHED

System Log Message	Maximum number of allowed FIP sessions (<i>slot</i>) reached for this slot <i>maximum-value</i>
Description	Maximum number of allowed FIP sessions reached.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

FIP_PROTOCOL_STARTED

System Log Message	Fabric <i>fc-fabric-name</i> interface <i>interface-name</i> fcf-mac <i>mac-address</i> FIP protocol started
Description	FIP protocol is started on an interface.
Type	Event: This message reports an event, not an error
Severity	info

Facility LOG_DAEMON

FIP_PROTOCOL_STOPPED

System Log Message Fabric *fc-fabric-name* interface *interface-name* fcf-mac *mac-address* FIP protocol stopped

Description FIP protocol is stopped on an interface.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

FIP_VN_PORT_FKA_TIMER_EXPIRED

System Log Message Fabric *fc-fabric-name* interface *interface-name* enode-mac *enode-mac-address* wwn *wwn* vn-mac *vn-mac-address*

Description VN_Port keepalive timer expired.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

FIP_VN_PORT_LOGIN_FAILED

System Log Message Fabric *fc-fabric-name* interface *interface-name* enode-mac *enode-mac-address* wwn *wwn* - *reason*

Description FIP FLOGI/FDISC from the end node has failed.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause VN_Port login is rejected. Its possible that the maximum session limit has reached.

Action Check the number of sessions on the end node or the number of sessions on the gateway

FIP_VN_PORT_SESSION_CLEARED

System Log Message Fabric *fc-fabric-name* interface *interface-name* enode-mac *enode-mac-address* wwn *wwn* vn-mac *vn-mac-address* fcid *fcid*

Description VN_Port login session is terminated.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

FIP_VN_PORT_SESSION_CREATED

System Log Message	Fabric <i>fc-fabric-name</i> interface <i>interface-name</i> enode-mac <i>enode-mac-address</i> wwn <i>wwn</i> vn-mac <i>vn-mac-address</i> fcid <i>fcid</i>
Description	FIP FLOGI/FDISC from the end node is completed.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

FIP_VN_PORT_TIMER_EXPIRED

System Log Message	Timer expired for session <i>vn-mac-address</i>
Description	FIP Vn port timer expired.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	Keep alives from Vn port / sessions are not seen

CHAPTER 42

FIPS System Log Messages

FIPS_KNOWN_ANSWER_TEST

System Log Message *username :test-name* Known Answer Test: Passed

Description FIPS Known Answer Test passed.

Type Event: This message reports an event, not an error

Severity info

Facility ANY

CHAPTER 43

FLOW System Log Messages

This chapter describes messages with the FLOW prefix. They are generated by the process that handles flows on routers running the Junos OS with enhanced services.

FLOW_APP_POLICY_VIOLATION

System Log Message	Application <i>service-name</i> policy violation occurred <i>threshold</i> times within <i>time-period</i> seconds
Description	A log was generated when a deny or reject policy match on one application occurred according to the configured threshold within the specified time window.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_PFE

FLOW_DSTIP_POLICY_VIOLATION

System Log Message	Destination ip <i>destination-address</i> policy violation occurred <i>threshold</i> times within <i>time-period</i> seconds
Description	A log was generated when a deny or reject policy match on one destination IP address occurred according to the configured threshold within the specified time window.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_PFE

FLOW_HIGH_WATERMARK_TRIGGERED

System Log Message	Number of sessions <i>current-flows</i> exceeded the high watermark <i>limit</i> . Early aging triggered.
Description	Early aging of sessions is triggered when the number of concurrent session entries in the session table exceeds the configured high watermark. When the number of concurrent sessions drops below the configured low watermark, the router stops aggressively aging out sessions. This message notifies you that the session high watermark has been exceeded and aggressive aging of sessions has begun.
Type	Event: This message reports an event, not an error

Severity info
Facility LOG_USER

FLOW_HIGH_WATERMARK_TRIGGERED_LS

System Log Message *Lsys logical-system-name*: Number of sessions *current-flows* exceeded the high watermark *limit*. Early aging triggered.

Description Early aging of sessions is triggered when the number of concurrent session entries in the session table exceeds the configured high watermark. When the number of concurrent sessions drops below the configured low watermark, the router stops aggressively aging out sessions. This message notifies you that the session high watermark has been exceeded and aggressive aging of sessions has begun.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_USER

FLOW_IP_ACTION

System Log Message Flow IP action detected attack attempt: *source-address/source-port --> destination-address/destination-port* from interface *interface-name*, from zone *source-zone-name*, action *action*.

Description Flow IP action notification is generated when a new connection matches security flow IP action filter that has been setup to log or has ip-notify action.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_PFE

FLOW_IP_ACTION_LS

System Log Message *Lsys logical-system-name*: Flow IP action detected attack attempt:*source-address/source-port --> destination-address/destination-port* from interface *interface-name*, from zone *source-zone-name*, action *action*.

Description Flow IP action notification is generated when a new connection matches security flow IP action filter that has been setup to log or has ip-notify action.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_PFE

FLOW_LOW_WATERMARK_TRIGGERED

System Log Message Number of sessions *current-flows* dropped below the low watermark *limit*. Early aging stopped.

Description Early aging of sessions is triggered when the number of concurrent session entries in the session table exceeds the configured high watermark. When the number of concurrent sessions drops below the configured low watermark, the router stops aggressively aging out sessions. This message notifies you that the number of concurrent sessions has dropped below the configured low watermark, and that aggressive aging of sessions has stopped.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_USER

FLOW_LOW_WATERMARK_TRIGGERED_LS

System Log Message *Lsys logical-system-name*: Number of sessions *current-flows* dropped below the low watermark *limit*. Early aging stopped.

Description Early aging of sessions is triggered when the number of concurrent session entries in the session table exceeds the configured high watermark. When the number of concurrent sessions drops below the configured low watermark, the router stops aggressively aging out sessions. This message notifies you that the number of concurrent sessions has dropped below the configured low watermark, and that aggressive aging of sessions has stopped.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_USER

FLOW_POLICY_VIOLATION

System Log Message Policy *policy-name* violation occurred *threshold* times within *time-period* seconds

Description A log was generated when a deny or reject policy match occurred according to the configured threshold within the specified time window.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_PFE

FLOW_REASSEMBLE_FAIL

System Log Message FCB ageout before all fragments arrive, source *source-address* destination *destination-address* ipid *assembly-id*

Description A log was generated when an FCB age out occurred before all fragments arrived.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

FLOW_REASSEMBLE_SUCCEED

System Log Message	Packet merged source <i>source-address</i> destination <i>destination-address</i> ipid <i>assembly-id</i> succeed
Description	A log was generated when the reassemble succeeded.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_PFE

FLOW_SRCIP_POLICY_VIOLATION

System Log Message	Source ip <i>source-address</i> policy violation occurred <i>threshold</i> times within <i>time-period</i> seconds
Description	A log was generated when a deny or reject policy match on one source IP address occurred according to the configured threshold within the specified time window.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_PFE

FPCLOGIN System Log Messages

FPCLOGIN_ADDRESS_GET_FAILED

System Log Message	Unable to determine IP address of TGM in slot <i>slot</i>
Description	A user tried to log in to the Physical Interface Module (PIM) in the indicated slot on a Flexible PIC Concentrator (FPC). In response, the FPC login process (pimlogin) tried to determine the PIM's IP address. It could not do so, and the login attempt failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

FPCLOGIN_IPC_RECEIVE_FAILED

System Log Message	Unable to receive IPC message from <i>process-name</i>
Description	The Flexible PIC Concentrator (FPC) login process (pimlogin) could not process an interprocess communication (IPC) message from the indicated other process. The 'wxd' process is the WX Physical Interface Module process.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

FPCLOGIN_IPC_SEND_FAILED

System Log Message	Unable to send IPC message to <i>process-name</i>
Description	The Flexible PIC Concentrator (FPC) login process (pimlogin) could not send an interprocess communication (IPC) message to the indicated other process. The 'wxd' process is the WX Physical Interface Module process (wxd).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

FPCLOGIN_LOGIN_FAILED

System Log Message	fpclogin failed: <i>error-message</i>
Description	A user tried to log in to a Physical Interface Module (PIM). The attempt failed for the indicated reason.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

FPCLOGIN_MESSAGE_INVALID

System Log Message	Message from <i>process-name</i> <i>error-message</i>
Description	The message that the Flexible PIC Concentrator (FPC) login process (pimlogin) received from the indicated other process was invalid in the indicated way. The 'wxd' process is the WX Physical Interface Module process (wxd).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

FPCLOGIN_SOCKET_OPERATION_FAILED

System Log Message	Unable to complete ' <i>error-message</i> ' operation
Description	The Flexible PIC Concentrator (FPC) login process (pimlogin) could not perform the indicated operation on a routing socket.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHAPTER 45

FSAD System Log Messages

This chapter describes messages with the **FSAD** prefix. They are generated by the File System Access process (fsad), which provides Trivial FTP (TFTP) support for file transfer between services PICs and other routing platform components.

FSAD_CONFIG_ERROR

System Log Message	Reason: <i>reason</i>
Description	The configuration file for the File System Access process (fsad) might contain an error.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

FSAD_CONNTIMEDOUT

System Log Message	Connection timed out to the client (<i>connection-type</i> , <i>ip-address</i>) having request type <i>port</i>
Description	The File System Access process (fsad) flushed all state information about the timed-out connection.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

FSAD_DIR_CREATE

System Log Message	Failed to create directory <i>directory-name</i> : <i>error-message</i>
Description	The File System Access process (fsad) could not create the indicated directory.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

FSAD_DIR_STAT

System Log Message	<i>function-name: stat()</i> failed for pathname <i>pathname: reason</i>
Description	The File System Access process (fsad) received a request for a nonexistent file or directory.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	The path does not exist.
Action	Make sure the path specified in the request is valid.

FSAD_FAILED

System Log Message	In <i>enclosing-function-name: function-name()</i> returned: <i>reason</i>
Description	An internal error occurred inside a function in the File System Access process (fsad).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

FSAD_FILE_FAILED

System Log Message	<i>enclosing-function-name: function-name</i> failed for file ' <i>filename</i> ' with error message <i>reason</i>
Description	An internal error occurred while the File System Access process (fsad) was performing a file operation.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

FSAD_FILE_REMOVE

System Log Message	Unable to remove file ' <i>filename</i> ': <i>reason</i>
---------------------------	--

Description	The File System Access process (fsad) could not remove the indicated file for the indicated reason.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	The file to be removed does not exist or its permissions do not allow the operation.
Action	Make sure that the file exists and that its permissions allow it to be deleted.

FSAD_FILE_RENAME

System Log Message	Unable to rename file ' <i>source-filename</i> ' to ' <i>destination-filename</i> ': <i>reason</i>
Description	The File System Access process (fsad) could not rename the indicated file for the indicated reason.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	Either the source file does not exist, or one or both of the source and destination pathnames are incorrect.
Action	Make sure the source and destination paths exist and that the rename operation is allowed.

FSAD_FILE_STAT

System Log Message	<i>function-name</i> : stat() failed for file pathname <i>pathname</i> : <i>reason</i>
Description	The File System Access process (fsad) received a request for a nonexistent file.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	The file path does not exist.
Action	Make sure the path specified in the request is valid.

FSAD_FILE_SYNC

System Log Message	Unable to sync file ' <i>filename</i> ': <i>reason</i>
---------------------------	--

Description When closing a file, the File System Access process (fsad) executes the sync() system call to ensure that any changes to the file are committed to disk. This operation failed for the indicated file.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

FSAD_FLOWC_IPC_PAYLOAD_SIZE

System Log Message Received flowc IPC message with incorrect length: message type *message-type*, subtype *message-subtype*, opcode *operation-code*, length *length* (expected length *expected-value*)

Description The File System Access process (fsad) received a flow collector IPC message in which the payload length was incorrect.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

FSAD_FLOWC_IPC_SUBTYPE

System Log Message Received flowc IPC message with incorrect subtype: message type *message-type*, subtype *message-subtype*, opcode *operation-code*, length *length*

Description The File System Access process (fsad) received a flow collector IPC message in which the subtype field was incorrect.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

FSAD_FLOWC_IPC_TYPE

System Log Message Received flowc IPC message with incorrect type: message type *message-type*, subtype *message-subtype*, opcode *operation-code*, length *length*

Description The File System Access process (fsad) received a flow collector IPC message in which the type field was incorrect.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

FSAD_FLOWC_IPC_VERSION

System Log Message Received flowc IPC message with incorrect version *received-value* (expected version *expected-value*)

Description The File System Access process (fsad) received a flow collector IPC message in which the version field was incorrect.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

FSAD_FLOWC_SERVICE_INACTIVE

System Log Message *reason*

Description The File System Access process (fsad) received a request for the Flow Collector Transfer Log Archive service, which is not currently active.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

FSAD_FREE_SPACE_LOG

System Log Message Unable to move temporary file *temporary-filename* (size *file-size* KB) to log file *log-filename* because free disk space (*count* KB) is insufficient

Description The File System Access process (fsad) could not move the CDR temporary file of the indicated size to the log file, because it is larger than the amount of free disk space.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

FSAD_FREE_SPACE_TMP

System Log Message Unable to write CDR batch output to file *temporary-filename* because free disk space (*count* KB) is insufficient

Description The File System Access process (fsad) could not write CDR batch output to the indicated temporary file, because the amount of free disk space was insufficient.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

FSAD_FS_STAT

System Log Message statfs() failed for pathname *pathname*: *reason*

Description The File System Access process (fsad) encountered an error in getting filesystem statistics.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

FSAD_GEN_IPC_PAYLOAD_SIZE

System Log Message Received IPC message with incorrect length: message type *message-type*, subtype *message-subtype*, opcode *operation-code*, length *length* (expected length *expected-value*)

Description The File System Access process (fsad) received an IPC message in which the payload length was incorrect.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

FSAD_GEN_IPC_SUBTYPE

System Log Message Received IPC message with incorrect subtype: message type *message-type*, subtype *message-subtype*, opcode *operation-code*, length *length*

Description The File System Access process (fsad) received an IPC message in which the subtype field was incorrect.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

FSAD_GEN_IPC_TYPE

System Log Message Received IPC message with incorrect type: message type *message-type*, subtype *message-subtype*, opcode *operation-code*, length *length*

Description The File System Access process (fsad) received an IPC message in which the type field was incorrect.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

FSAD_GEN_IPC_VERSION

System Log Message Received generic IPC message with incorrect version *received-value* (expected version *expected-value*)

Description The File System Access process (fsad) received an IPC message in which the version field was incorrect.

Type Error: An error occurred

Severity error
Facility LOG_DAEMON

FSAD_GEN_SERVICE_INACTIVE

System Log Message Received IPC message for inactive service *service-name*

Description The File System Access process (fsad) received an IPC message for a service that is currently not active.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

FSAD_GEN_SERVICE_INIT_FAILED

System Log Message Failed to initialize service *service-name*

Description The File System Access process (fsad) could not initialize the indicated service.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

FSAD_MAXCONN

System Log Message Upper limit reached in fsad for handling connections

Description The File System Access process (fsad) stopped accepting new connections because it reached an internal limit for handling connections.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

FSAD_MEMORYALLOC_FAILED

System Log Message *allocation-function-name* failed in the function *function-name* (*line-number*)

Description The File System Access process (fsad) could not allocate memory. The system might be running low on memory.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause An internal software failure occurred.

Action Contact your technical support representative.

FSAD_NOT_ROOT

System Log Message	Must be run as root
Description	The user who attempted to start the File System Access process (fsad) was not the root user.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

FSAD_PARENT_DIRECTORY

System Log Message	<i>directory-name</i> : invalid directory: <i>message</i>
Description	The parent directory specified in the request for a file was not valid.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Make sure the path specified in the request is valid.

FSAD_PATH_IS_DIRECTORY

System Log Message	File path cannot be a directory (<i>pathname</i>)
Description	The File System Access process (fsad) received a request on a directory instead of a regular file.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	The file path points to a directory.
Action	Make sure the path points to a regular file.

FSAD_PATH_IS_NOT_DIRECTORY

System Log Message	invalid path ' <i>pathname</i> ' : not a directory : <i>action</i>
Description	The File System Access process (fsad) received a request for a pathname that was not a directory.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

FSAD_PATH_IS_SPECIAL

System Log Message	Not a regular file (<i>pathname</i>)
Description	The File System Access process (fsad) received a request for a pathname that points to a nonregular file.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Make sure the path points to a regular file.

FSAD_RECVERROR

System Log Message	fsad received error <i>message</i> from client having request type <i>connection-type</i> at (<i>ip-address</i> , <i>port</i>)
Description	The File System Access process (fsad) received a packet with the indicated error message from the other end of a connection.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

FSAD_RENAME

System Log Message	<i>function-name</i> : failed to rename temporary file <i>filename</i> to <i>new-filename</i> : <i>reason</i>
Description	The File System Access process (fsad) could not rename the indicated temporary file for the indicated reason.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

FSAD_TERMINATED_CONNECTION

System Log Message	Open file ' <i>filename</i> ' closed due to process shutdown
Description	The File System Access process (fsad) terminated a connection, stored the connection's (unwritten) data to disk, and purged it from its data structures.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

FSAD_TRACEOPEN_FAILED

System Log Message	Open operation on trace file ' <i>pathname</i> ' returned error <i>error-message</i>
Description	The File System Access process (fsad) failed to open the indicated trace file.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

FSAD_USAGE

System Log Message	Incorrect usage, <i>message</i>
Description	The File System Access process (fsad) displayed its usage statement.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Cause	The fsad process was invoked with incorrect command-line arguments.
Action	Check the usage and invoke the fsad process with the correct command-line arguments.

CHAPTER 46

FUD System Log Messages

This chapter describes messages with the **FUD** prefix. They are generated by the UDP forwarding process (fud), which forwards UDP (User Datagram Protocol) packets from a network to a server for services that run over UDP.

FUD_ARGUMENT_FAILURE

System Log Message	Unknown option " <i>option</i> "
Description	One or more options provided on the 'fud' command line were invalid. The UDP forwarding process (fud) initialized but ignored the invalid options.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Reissue the 'fud' command with the correct options.

FUD_BAD_SERVER_ADDR_FAILURE

System Log Message	Destination address of <i>destination-address</i> is invalid
Description	One or more server addresses configured for the UDP forwarding process (fud) were invalid.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Reconfigure the fud process with valid server addresses.

FUD_BIND_FAILURE

System Log Message	bind(port <i>port</i>) failed: <i>error-message</i>
Description	The UDP forwarding process (fud) received the indicated error when it tried to bind a socket to a local address.
Type	Error: An error occurred

Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

FUD_DAEMON_FAILURE

System Log Message	Unable to run in the background as daemon: <i>error-message</i>
Description	The UDP forwarding process (fud) could not create a version of itself to run in the background as a daemon.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

FUD_MEMORY_ALLOCATION_FAILURE

System Log Message	Unable to allocate <i>count</i> bytes of memory: <i>error-message</i>
Description	The UDP forwarding process (fud) could not allocate the indicated amount of memory from the heap.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18897 .

FUD_PERMISSION_FAILURE

System Log Message	<i>program-name</i> must be run as root
Description	The user who attempted to start the UDP forwarding process (fud) was not the root user, so the process did not start.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Become the root user before issuing the 'fud' command.

FUD_PIDLOCK_FAILURE

System Log Message	Unable to lock PID file; another <i>program-name</i> was running
---------------------------	--

Description	The UDP Forwarding process (fud) attempted to lock the file that records its process ID (PID), which serves to prevent multiple instances of the fud process from running simultaneously. The attempt failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	Another instance of the fud process is running.
Action	Check whether another fud process is running, and stop it if appropriate.

FUD_PIDUPDATE_FAILURE

System Log Message	Unable to update PID file for <i>program-name</i>
Description	The UDP Forwarding process (fud) attempted to update the file that records its process ID (PID), which serves to prevent multiple instances of the fud process from running simultaneously. The attempt failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	Another instance of the fud process is running.
Action	Check whether another fud process is running, and stop it if appropriate.

FUD_RECVMSG_FAILURE

System Log Message	Exiting because of repeated recvmsg() failures
Description	The UDP Forwarding process (fud) could not receive data from the network, which it needs to do during normal operation.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

FUD_RTsock_WRITE_FAILURE

System Log Message	Unable to write to routing socket: <i>error-message</i>
Description	The UDP Forwarding process (fud) could not write to its routing socket for the indicated reason.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18898 .

FUD_SENDSMSG_FAILURE

System Log Message sendmsg() to *destination-address* port *port* on interface *interface-name* rt_inst *routing-instance* failed: *error-message*

Description The UDP Forwarding process (fud) could not send data to the indicated destination port and address via the indicated interface and routing instance, which it needs to do during normal operation.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18899 .

FUD_SENDSMSG_NOINT_FAILURE

System Log Message sendmsg() to *destination-address* port *port* rt_inst *routing-instance* failed: *error-message*

Description The UDP Forwarding process (fud) could not send data to the indicated destination port and address via the indicated routing instance, which it needs to do during normal operation.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18900 .

FUD_SETSOCKOPT_FAILURE

System Log Message setsockopt(*arguments*) failed: *error-message*

Description The UDP Forwarding process (fud) could not set the indicated socket option.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18901>.

FUD_SOCKET_FAILURE

System Log Message `socket(arguments) failed: error-message`

Description The UDP Forwarding process (fud) could not create a socket.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18902>.

FWAUTH System Log Messages

This chapter describes messages with the **FWAUTH** prefix. They are generated by the process that authenticates users when they initiate a connection across a firewall.

FWAUTH_FTP_LONG_PASSWORD

System Log Message	Authentication for user <i>username</i> at <i>client-address</i> was denied (long password).
Description	The length of the password must not exceed 128 characters.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_PFE

FWAUTH_FTP_LONG_PASSWORD_LS

System Log Message	<i>Lsys logical-system-name</i> : Authentication for user <i>username</i> at <i>client-address</i> was denied (long password).
Description	The length of the password must not exceed 128 characters.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_PFE

FWAUTH_FTP_LONG_USERNAME

System Log Message	Authentication for user <i>username</i> at <i>client-address</i> was denied (long username).
Description	The length of the username must not exceed 64 characters.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_PFE

FWAUTH_FTP_LONG_USERNAME_LS

System Log Message	<i>Lsys logical-system-name</i> : Authentication for user <i>username</i> at <i>client-address</i> was denied (long username).
---------------------------	--

Description The length of the username must not exceed 64 characters.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

FWAUTH_FTP_USER_AUTH_ACCEPTED

System Log Message User *username* of group *group-name* at *client-address* is accepted.

Description The authenticated user can start accessing protected resources.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

FWAUTH_FTP_USER_AUTH_ACCEPTED_LS

System Log Message Lsys *logical-system-name*: User *username* of group *group-name* at *client-address* is accepted.

Description The authenticated user can start accessing protected resources.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

FWAUTH_FTP_USER_AUTH_FAIL

System Log Message User *username* at *client-address* is rejected.

Description User authentication failed because the username or password was invalid.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

FWAUTH_FTP_USER_AUTH_FAIL_LS

System Log Message Lsys *logical-system-name*: User *username* at *client-address* is rejected.

Description User authentication failed because the username or password was invalid.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

FWAUTH_HTTP_USER_AUTH_ACCEPTED

System Log Message User *username* of group *group-name* at *client-address* is accepted.

Description The authenticated user can start accessing protected resources.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

FWAUTH_HTTP_USER_AUTH_FAIL

System Log Message User *username* at *client-address* is rejected.

Description User authentication failed because the username or password was invalid.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

FWAUTH_HTTP_USER_AUTH_FAIL_LS

System Log Message Lsys *logical-system-name*: User *username* at *client-address* is rejected.

Description User authentication failed because the username or password was invalid.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

FWAUTH_HTTP_USER_AUTH_OK_LS

System Log Message Lsys *logical-system-name*: User *username* of group *group-name* at *client-address* is accepted.

Description The authenticated user can start accessing protected resources.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

FWAUTH_TELNET_LONG_PASSWORD

System Log Message Authentication for user *username* at *client-address* was denied (long password).

Description The length of the password must not exceed 128 characters.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

FWAUTH_TELNET_LONG_PASSWORD_LS

System Log Message Lsys *logical-system-name*: Authentication for user *username* at *client-address* was denied (long password).

Description The length of the password must not exceed 128 characters.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

FWAUTH_TELNET_LONG_USERNAME

System Log Message Authentication for user *username* at *client-address* was denied (long username).

Description The length of username must not exceed 64 characters.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

FWAUTH_TELNET_LONG_USERNAME_LS

System Log Message Lsys *logical-system-name*: Authentication for user *username* at *client-address* was denied (long username).

Description The length of username must not exceed 64 characters.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

FWAUTH_TELNET_USER_AUTH_ACCEPTED

System Log Message User *username* of group *group-name* at *client-address* is accepted.

Description The authenticated user can start accessing protected resources

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

FWAUTH_TELNET_USER_AUTH_FAIL

System Log Message User *username* at *client-address* is rejected.

Description User authentication failed because the username or password was invalid.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_PFE

FWAUTH_TELNET_USER_AUTH_FAIL_LS

System Log Message *Lsys logical-system-name: User username at client-address is rejected.*
Description User authentication failed because the username or password was invalid.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_PFE

FWAUTH_TELNET_USER_AUTH_OK_LS

System Log Message *Lsys logical-system-name: User username of group group-name at client-address is accepted.*
Description The authenticated user can start accessing protected resources

Type Event: This message reports an event, not an error
Severity info
Facility LOG_PFE

FWAUTH_WEBAUTH_FAIL

System Log Message WebAuth user *username* at *client-address* is rejected/timed out.
Description The provided user credentials are not valid.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_PFE

FWAUTH_WEBAUTH_FAIL_LS

System Log Message *Lsys logical-system-name: WebAuth user username at client-address is rejected/timed out.*
Description The provided user credentials are not valid.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_PFE

FWAUTH_WEBAUTH_SUCCESS

System Log Message WebAuth user *username* of group *group-name* at *client-address* is accepted.

Description The authenticated user can start accessing protected resources.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

FWAUTH_WEBAUTH_SUCCESS_LS

System Log Message *Lsys logical-system-name: WebAuth user username of group group-name at client-address is accepted.*

Description The authenticated user can start accessing protected resources.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

CHAPTER 48

GPRSD System Log Messages

This chapter describes messages with the **GPRSD** prefix. They are generated by the general packet radio service process (gprsd) that integrates with existing GSM networks and offers mobile subscribers with packet switched data services access to corporate networks and the Internet.

GPRSD_MEMORY_ALLOC_FAILED

System Log Message	Unable to allocate <i>count</i> bytes of memory
Description	The general packet radio service daemon process (gprsd) could not allocate the indicated number of bytes of memory.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	It is possible that system memory is exhausted.
Action	Increase the amount of RAM in the Routing Engine.

GPRSD_RESTART_CCFG_READ_FAILED

System Log Message	Subcomponent could not read configuration database
Description	As the general packet radio service daemon process (gprsd) restarted, one or more of its subcomponents could not read its configuration information from the configuration database. The gprsd process restarted regardless without affecting routing performance.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHAPTER 49

HNCACHED System Log Messages

This chapter describes messages with the HNCACHED prefix. They are generated by the hostname-caching process (hncached) which stores hostnames in a temporary storage area in order to be able to retrieve them faster.

HNCACHED_HOST_ADDRESS_CHANGED

System Log Message	Detected change in IP addresses for host: <i>hostname</i>
Description	The hostname-caching process (hostname-cached) detected that the set of IP addresses for the specified hostname changed
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

HNCACHED_NAME_RESOLUTION_FAILURE

System Log Message	Failed to resolve hostname: <i>hostname</i> (<i>error-message</i>)
Description	The hostname-caching process (hostname-cached) failed to resolve the specified hostname for indicated reason
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	1) If the hostname used in config is incorrect, fix it. 2) Ensure that the configured name-server is reachable and is working.

CHAPTER 50

ICCPD System Log Messages

This chapter describes messages with the **ICCPD** prefix. They are generated by the interchassis communication process (iccpd).

ICCPD_ASSERT_SOFT

System Log Message	Soft assertion failed at line <i>line-number</i> in file ' <i>source-filename</i> ' with error " <i>message</i> ", but iccpd with PID <i>pid</i> continued running
Description	The source code for the interchassis communication process (iccpd) includes internal self-consistency checks. As the iccpd process with the indicated process ID (PID) executed the binary compiled from the indicated source file, a check failed at the indicated line number in the file. The iccpd process created a diagnostic core file for analysis by technical support personnel and continued to run.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Examine the messages that immediately follow this message in the system log for information about possible causes. Contact a technical support representative, and be ready to provide the list of messages and the diagnostic core file, if requested. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18907 .

ICCPD_OPEN_ERROR

System Log Message	<i>error-message</i> : open error on pipe
Description	The interchassis communication process (iccpd) could not initialize.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18908 .

ICCPD_READ_ERROR

System Log Message	Read error on pipe from <i>client-name</i> : <i>reason</i> (<i>error-message</i>)
Description	The interchassis communication process (iccpd) could not read a message on a pipe for the indicated client.
Type	Error: An error occurred
Severity	info
Facility	LOG_DAEMON
Action	Contact your technical support representative.

ICCPD_WRITE_ERROR

System Log Message	write error on pipe to <i>client-name</i> :
Description	The interchassis communication process (iccpd) could not write a message on a pipe for the indicated client.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

IDP System Log Messages

IDP_APPDDOS_APP_ATTACK_EVENT

IDP_APPDDOS_APP_ATTACK_EVENT_LS

Copyright © 2015, Juniper Networks, Inc.

Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_PFE

IDP_APPDDOS_APP_STATE_EVENT

System Log Message	DDOS Application threshold crossed at <i>epoch-time</i> on <i>ddos-application-name</i> , < <i>destination-zone-name:destination-interface-name:destination-address:destination-port</i> > for <i>protocol-name</i> protocol and service <i>service-name</i> in rule <i>rule-name</i> of rulebase <i>rulebase-name</i> in policy <i>policy-name</i> . repeats <i>repeat-count</i> message: <i>message</i> context-value: <i>context-value</i>
Description	The application-level distributed denial-of-service (AppDDoS) state transition occurred when the number of application transactions exceeded the user-configured connection or context thresholds
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_PFE

IDP_APPDDOS_APP_STATE_EVENT_LS

System Log Message	Lsys <i>logical-system-name</i> : DDOS Application threshold crossed at <i>epoch-time</i> on <i>ddos-application-name</i> , < <i>destination-zone-name:destination-interface-name:destination-address:destination-port</i> > for <i>protocol-name</i> protocol and service <i>service-name</i> in rule <i>rule-name</i> of rulebase <i>rulebase-name</i> in policy <i>policy-name</i> . repeats <i>repeat-count</i> message: <i>message</i> context-value: <i>context-value</i>
Description	The application-level distributed denial-of-service (AppDDoS) state transition occurred when the number of application transactions exceeded the user-configured connection or context thresholds
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_PFE

IDP_ATTACK_LOG_EVENT

System Log Message	IDP: at <i>epoch-time</i> , <i>message-type</i> Attack log < <i>source-address:source-port->destination-address:destination-port</i> > for <i>protocol-name</i> protocol and service <i>service-name</i> application <i>application-name</i> by rule <i>rule-name</i> of rulebase <i>rulebase-name</i> in policy <i>policy-name</i> . attack: repeat= <i>repeat-count</i> , action= <i>action</i> , threat-severity= <i>threat-severity</i> , name= <i>attack-name</i> , NAT < <i>nat-source-address:nat-source-port->nat-destination-address:nat-destination-port</i> >, time-elapsed= <i>elapsed-time</i> , inbytes= <i>inbound-bytes</i> , outbytes= <i>outbound-bytes</i> , inpackets= <i>inbound-packets</i> , outpackets= <i>outbound-packets</i> , intf: <i>source-zone-name:source-interface-name->destination-zone-name:destination-interface-name</i> , packet-log-id: <i>packet-log-id</i> and misc-message <i>message</i>
--------------------	--

Description	IDP Attack log generated for attack
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_PFE

IDP_ATTACK_LOG_EVENT_LS

System Log Message Lsys *logical-system-name*: IDP: At *epoch-time*, *message-type* Attack log
 <*source-address/source-port->destination-address/destination-port*> for *protocol-name*
 protocol and service *service-name* application *application-name* by rule *rule-name* of
 rulebase *rulebase-name* in policy *policy-name*. attack: repeat=*repeat-count*, action=*action*,
 threat-severity=*threat-severity*, name=*attack-name*, NAT
 <*nat-source-address:nat-source-port->nat-destination-address:nat-destination-port*>,
 time-elapsed=*elapsed-time*, inbytes=*inbound-bytes*, outbytes=*outbound-bytes*,
 inpackets=*inbound-packets*, outpackets=*outbound-packets*,
 intf:*source-zone-name:source-interface-name->destination-zone-name:destination-interface-name*,
 packet-log-id: *packet-log-id* and misc-message *message*

Description	IDP Attack log generated for attack
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_PFE

IDP_COMMIT_COMPLETED

System Log Message IDP policy commit is complete.

Description IDP policy commit has completed. Policy compile and load however may have been a success or failure.

Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_AUTH

IDP_COMMIT_FAILED

System Log Message IDP policy commit failed. Exiting from compilation.

Description There was an error while trying to commit the active policy in IDPD. Device will continue running the current IDP policy.

Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH

IDP_DAEMON_INIT_FAILED

System Log Message	Aborting...A failure was encountered; <i>error-message</i>
Description	An attempt to start IDP policy daemon failed because an error was encountered during initialization.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18909 .

IDP_IGNORED_IPV6_ADDRESSES

System Log Message	IDP ignores IPv6 addresses for the ' <i>rulebase-name</i> '
Description	IDP IPv6 support is not enabled for the rulebase.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_AUTH

IDP_INTERNAL_ERROR

System Log Message	Encountered an error(<i>error-message</i>)
Description	IDP daemon encountered an internal error
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18910 .

IDP_POLICY_COMPILATION_FAILED

System Log Message	IDP compilation of policy[<i>idp-policy</i>] failed : [<i>reason</i>]
Description	IDP policy compiler encountered an error while compiling or packaging the policy.Device will continue running the existing IDP policy
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_AUTH

IDP_POLICY_LOAD_FAILED

System Log Message	IDP policy loading failed ;policy[<i>idp-policy</i>], detector[<i>idp-detector</i>] ,failure detail[<i>reason</i>]
Description	A compiled and optimized IDP policy could not be loaded into IDP engine. Device will continue running the existing IDP policy.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH

IDP_POLICY_LOAD_SUCCEEDED

System Log Message	IDP policy[<i>idp-policy</i>] and detector[<i>idp-detector</i>] loaded successfully(<i>message</i>).
Description	A compiled and optimized IDP policy was loaded successfully into the IDP engine. All subsequent sessions will be processed as per this new IDP policy.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_AUTH

IDP_POLICY_UNLOAD_FAILED

System Log Message	Failed to unload IDP policy. reason: <i>reason</i> .
Description	A running IDP policy could not be unloaded from IDP engine. Device will continue running the IDP policy.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH

IDP_POLICY_UNLOAD_SUCCEEDED

System Log Message	IDP policy unloaded successfully.
Description	A running IDP policy was unloaded successfully from the IDP engine.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_AUTH

IDP_SCHEDULEDUPDATE_START_FAILED

System Log Message	Failed to start scheduled update(<i>error:error-message</i>)
Description	The scheduled IDP security package update failed to start. Device will try it again at the next scheduled time

Type Error: An error occurred
Severity error
Facility LOG_AUTH

IDP_SCHEDULED_UPDATE_STARTED

System Log Message Scheduled update has started(at *timestamp*)
Description The scheduled IDP security package update has started.

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_AUTH

IDP_SECURITY_INSTALL_RESULT

System Log Message security package install result(*status*)
Description IDP background process has returned the security package install result

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_AUTH

IDP_SESSION_LOG_EVENT

System Log Message IDP: at *epoch-time*, *event-name*.
Description IDP session threshold crossing event

Type Event: This message reports an event, not an error
Severity info
Facility LOG_PFE

IDP_SESSION_LOG_EVENT_LS

System Log Message *Lsys logical-system-name*: IDP: At *epoch-time*, *event-name*.
Description IDP session threshold crossing event

Type Event: This message reports an event, not an error
Severity info
Facility LOG_PFE

IDP_SIGNATURE_LICENSE_EXPIRED

System Log Message IDP Signagure update license(ID=*feature-id*) has expired
Description IDP signature update license key has expired. Signature update may not work any more.

Type Event: This message reports an event, not an error
Severity warning
Facility LOG_AUTH

CHAPTER 52

JADE System Log Messages

This chapter describes messages with the **JADE** prefix. They are generated by the Junos XML protocol authentication process (*jade*), which authenticates and checks authorization of client applications using the Junos XML management protocol.

JADE_ATTRIBUTES_TOO_LONG

System Log Message	Attribute number or length in client <i>junoscript</i> tag was too large
Description	The JUNOScript client passed too many attributes in the initial <junoscript> tag, or the attributes were too long.
Type	Error: An error occurred
Severity	error
Facility	ANY

JADE_AUTH_FAILURE

System Log Message	Authentication failed for user ' <i>username</i> ' : <i>error-message</i>
Description	The username or password supplied by the client was incorrect.
Type	Error: An error occurred
Severity	notice
Facility	ANY

JADE_AUTH_SUCCESS

System Log Message	Authentication succeeded for user ' <i>username</i> '
Description	The jade authentication process authenticated the indicated user.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY

JADE_EXEC_ERROR

System Log Message	CLI xml-mode exec error: <i>error-message</i>
---------------------------	---

Description The JUNOScript authentication process (jade) could not start because of an internal error.

Type Error: An error occurred

Severity error

Facility ANY

JADE_IRI_AUTH_SUCCESS

System Log Message Authentication succeeded for user '*username*' over IRI '*routing-instance*'

Description The jade authentication process authenticated the indicated user over IRI.

Type Event: This message reports an event, not an error

Severity notice

Facility ANY

JADE_PAM_ERROR

System Log Message PAM error: *error-message*

Description The JUNOScript authentication process (jade) could not process the credentials supplied by the client.

Type Error: An error occurred

Severity error

Facility ANY

JADE_PAM_NO_LOCAL_USER

System Log Message Unable to get local username from PAM: *error-message*

Description The JUNOScript authentication process (jade) could not obtain a local username while processing the credentials supplied by the client.

Type Error: An error occurred

Severity error

Facility ANY

JADE_SOCKET_ERROR

System Log Message Socket operation '*operation*' failed: *error-message*

Description The indicated socket operation, initiated by the JUNOScript authentication process (jade), failed for the indicated reason.

Type Error: An error occurred

Severity error

Facility ANY

CHAPTER 53

JCS System Log Messages

This chapter describes messages with the JCS prefix. They are generated by the Juniper Control System (jcsd) process which provides the user interface to the control processes for the management modules and switch modules in the JCS 1200 platform.

JCS_BBD_LOAD_FAILURE

System Log Message	Blade <i>slot</i> load BBD failure: <i>error-message</i>
Description	The JCS process (jcsd) could not load blade bay data for the specified blade.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

JCS_BBD_LOCAL_MISMATCH

System Log Message	Blade <i>slot</i> BBD <i>error-message</i> mismatch (<i>expected-value</i> != <i>received-value</i>)
Description	The blade bay data retrieved for the specified blade does not match the data loaded during the reboot process. This error usually indicates that blade bay data in the JCS Management Module was changed since the last reboot.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18913 .

JCS_BBD_NOT_FOUND

System Log Message	Blade <i>slot</i> bay data not found
Description	Blade bay data was not found for the specified blade.
Type	Error: An error occurred
Severity	error

Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18914 .

JCS_BBD_NOT_VALID

System Log Message	Blade <i>slot</i> BBD is invalid
Description	The blade bay data for the specified blade is invalid.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18915 .

JCS_BBD_PARSE_ERROR

System Log Message	Blade <i>slot</i> bay data parse error - <i>error-message</i>
Description	The blade bay data for the specified blade did not parse correctly.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18916 .

JCS_BBD_PEER_MISMATCH

System Log Message	Peer blade <i>slot</i> BBD <i>error-message</i> mismatch (<i>expected-value</i> != <i>received-value</i>)
Description	The blade bay data retrieved for the specified peer blade does not match the data retrieved for the local blade. This error indicates that blade bay data in the JCS Management Module was not configured properly.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18917 .

JCS_BBD_SYSTEM_CONFLICT

System Log Message	Local BBD <i>error-message</i> (<i>value</i>) conflicts with blade <i>slot</i>
---------------------------	--

Description The blade bay data retrieved for the local blade conflicts with another blade in the JCS. This error indicates that blade bay data in the JCS Management Module was not configured properly.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

JCS_INVALID_BANDWIDTH_ERROR

System Log Message Invalid bandwidth percent (*value*)

Description The specified switch bandwidth is invalid. The bandwidth is defined as a percentage between 1 and 100.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

JCS_KERNEL_RSD_LINK_DOWN

System Log Message Kernel RSD link is DOWN (*error-message*)

Description The JCS process (jcsd) has disabled kernel RSD communication for the specified reason.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18918>.

JCS_KERNEL_RSD_LINK_ENABLED

System Log Message Kernel RSD link is ENABLED (*error-message*)

Description The JCS process (jcsd) has verified the blade bay data and enabled kernel RSD communication.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

JCS_MM_COMMUNICATION_ERROR

System Log Message MM communication error (*error-message*)

Description The JCS process (jcsd) could not send an SNMP request to the Management Module because of the indicated error.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18919 .

JCS_MM_COMMUNICATION_OK

System Log Message	MM communication is OK
Description	The JCS process (jcsd) has established a communication link with the Management Module.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

JCS_PEER_BLADE_STATE

System Log Message	Peer blade <i>slot</i> is <i>state</i>
Description	The JCS process (jcsd) detects a change of state for the indicated blade.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

JCS_READ_BANDWIDTH_ERROR

System Log Message	Read bandwidth error (<i>error-code</i>)
Description	The indicated error occurred when attempting to read the current switch bandwidth.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18920 .

JCS_READ_BBD_ERROR

System Log Message	Read blade bay data (<i>error=error-code</i>)
Description	The indicated error occurred when attempting to read the current blade bay data via a sysctl call.
Type	Error: An error occurred

Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18921 .

JCS_SWITCH_BANDWIDTH_CONFIG

System Log Message	Switch <i>slot</i> bandwidth <i>value1</i> percent (<i>value2</i> KBPS)
Description	The indicated JCS Switch Module has changed the bandwidth configuration to the specified value.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

JCS_SWITCH_COMMUNICATION_ERROR

System Log Message	Switch <i>slot</i> communication error (<i>error-message</i>)
Description	The JCS process (jcsd) could not send an SNMP request to the indicated Switch Module because of the indicated error.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18922 .

CHAPTER 54

JDIAMETERD System Log Messages

This chapter describes messages with the **JDIAMETERD** prefix. They are generated by the `jdiameter` process (`jdiameterd`). `Jdiameter` is an open source software implementation of the Diameter Base Protocol that is written in Java.

JDIAMETERD_FUNC_HSHAKE_FAIL

System Log Message	Application <i>diameter-function</i> cannot generate handshake, disconnecting
Description	The Diameter process(<code>jdiameterd</code>) failed to generate handshake message to the process that implements the Diameter-function. The connection was closed so that a new connection with full resynchronization could be established.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

JDIAMETERD_FUNC_LOCACCEPT_NFOUND

System Log Message	Path <i>pathname</i> does not match any application
Description	The Diameter process(<code>jdiameterd</code>) rejected a RE function side connection because there is no matching diameter-function.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

JDIAMETERD_FUNC_NSCK_LISTEN_FAIL

System Log Message	Unable to listen on internal-ip
Description	The Diameter process(<code>jdiameterd</code>) is unable to listen on the internal ip socket for function side connections.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

JDIAMETERD_FUNC_OUT_OF_SYNC

System Log Message	Application <i>diameter-function</i> is out of sync, disconnecting
Description	The Diameter process (jdiameterd) was out of sync with the process that implements the Diameter function. The connection was closed so that a new connection with full resynchronization could be established.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

JDIAMETERD_FUNC_PICACCEPT_NFOUND

System Log Message	Port <i>remote-port</i> does not match any application
Description	The Diameter process(jdiameterd) rejected a PIC function side connection because there is no matching diameter-function.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

JDIAMETERD_FUNC_TOO_MANY_BADE2ES

System Log Message	Application <i>diameter-function</i> has too many bad end-to-end-ids, disconnecting
Description	A daemon impelenting diameter function, sent too many messages with bad end-to-end-ids the connection will be closed, so a new connection with full resynchronization could be established.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

JDIAMETERD_FUNC_USCK_LISTEN_FAIL

System Log Message	Unable to listen on <i>pathname</i>
Description	The Diameter process(jdiameterd) is unable to listen on the unix socket for function side connections.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHAPTER 55

JIVED System Log Messages

This chapter describes messages with the **JIVED** prefix. They are generated by the mag-service process (jived).

JIVED_ALREADY_RUNNING

System Log Message	Another copy of this program is running
Description	Another instance of the mag-service process (jived) is already running. Only one instance can run at a time.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

JIVED_EVLIB_FUNC_FAILED

System Log Message	<i>function-name: event-function-name: reason</i>
Description	A function in the event library used by the mag-service process (jived) failed with the indicated error.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.

JIVED_INITIATE_CONN_FAILED

System Log Message	<i>function-name: aborting, failed to connect to mgd.</i>
Description	The mag-service process (jived) failed to initiate the connection to RE.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

Cause An internal software failure occurred.

JIVED_INIT_FAILED

System Log Message *error-message: reason*

Description The mag-service process (jived) failed to initialize.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

JIVED_NOT_ROOT

System Log Message JIVED must run as root

Description The mag-service process (jived) must be run with root privileges.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause jived being run without root privilege

JIVED_PIDFILE_LOCK_FAILED

System Log Message Unable to lock pid file

Description The mag-service process (jived) failed to lock the file that records its process ID (PID). The lock file is used to prevent multiple instances of the jived process from running simultaneously.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause Another instance of the jived process is already running.

JIVED_PIDFILE_UPDATE_FAILED

System Log Message can not update process PID file: *reason*

Description The mag-service process (jived) failed to update the file that records its process ID (PID). The lock file is used to prevent multiple instances of the jived process from running simultaneously.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON
Cause An internal software failure occurred.

JIVED_SNMP_SEND_TRAP_FAILED

System Log Message *error-message: trap*
Description The mag-service process (jived) failed in the attempt to send an SNMP trap
Type Error: An error occurred
Severity error
Facility LOG_DAEMON

CHAPTER 56

JNUD System Log Messages

JNUD_CONFIG_ERROR

System Log Message	Configuration database has errors
Description	The Junos Node Unifier process (jnud) detected an error in the JNU configuration database.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

JNUD_INIT_FAILED

System Log Message	jnud initialization failure: <i>error-message</i>
Description	Initialization of the Junos Node Unifier process (jnud) failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

JPTSPD System Log Messages

This chapter describes messages with the **JPTSPD** prefix. They are generated by the packet-triggered subscriber process (jptspd) which creates and manages packet-triggered subscriber interfaces. A packet-triggered subscriber interface is created when the router receives a packet with an IP source address that does not match any entries in the demultiplexer table. When the router detects an unmatched packet, it generates a trigger event that determines whether to create a dynamic subscriber interface or configure an existing interface.

JPTSPD_INIT_FAILURE

System Log Message	JPTSPD failed to initialize
Description	The packet triggered subscriber process (jptspd) initialization failed.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	One possible cause is that the system is out of memory.
Action	Contact your technical support representative.

JPTSPD_OUT_OF_MEMORY

System Log Message	Out of memory
Description	The packet triggered subscriber process (jptspd) could not dynamically allocate memory.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	A software bug caused a memory leak, or too many subscriber and service sessions.
Action	Contact your technical support representative.

JPTSPD_PIC_CONNECTED

System Log Message	JPTSPD connected to pic <i>pic-name</i>
Description	The packet triggered subscriber process (jptspd) connected to a PIC.
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

JPTSPD_PIC_DISCONNECTED

System Log Message	JPTSPD disconnected to pic <i>pic-name reason</i>
Description	The packet triggered subscriber process (jptspd) disconnected to a PIC.
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

JPTSPD_SRC_FAST_SYNC_ABORT

System Log Message	JPTSPD fast synchronization was aborted <i>partition-name</i>
Description	The packet triggered subscriber process (jptspd) aborted fast synchronization with SRC.
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY
Cause	One possible cause is that the connection between jptspd and SRC is down.

JPTSPD_SRC_FAST_SYNC_DONE

System Log Message	JPTSPD fast synchronization was done <i>partition-name</i>
Description	The packet triggered subscriber process (jptspd) finished fast synchronization with SRC.
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

JPTSPD_SRC_FAST_SYNC_START

System Log Message	JPTSPD fast synchronization started <i>partition-name</i>
Description	The packet triggered subscriber process (jptspd) started fast synchronization with SRC.
Type	Event: This message reports an event, not an error

Severity info

Facility ANY

JPTSPD_SRC_FULL_SYNC_ABORT

System Log Message JPTSPD full synchronization was aborted *partition-name*

Description The packet triggered subscriber process (jptspd) aborted full synchronization with SRC.

Type Event: This message reports an event, not an error

Severity info

Facility ANY

Cause One possible cause is that the connection between jptspd and SRC is down.

JPTSPD_SRC_FULL_SYNC_DONE

System Log Message JPTSPD full synchronization was done *partition-name*

Description The packet triggered subscriber process (jptspd) finished full synchronization with SRC.

Type Event: This message reports an event, not an error

Severity info

Facility ANY

JPTSPD_SRC_FULL_SYNC_START

System Log Message JPTSPD full synchronization started *partition-name*

Description The packet triggered subscriber process (jptspd) started full synchronization with SRC.

Type Event: This message reports an event, not an error

Severity info

Facility ANY

CHAPTER 58

JSERVICES System Log Messages

This chapter describes messages with the **JSERVICES** prefix.

JSERVICES_NAT_OUTOF_ADDRESSES

System Log Message	natpool <i>nat-pool-name</i> is out of addresses
Description	Network Address Translation (NAT) services could not allocate an address from the indicated NAT pool, because no addresses were available.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	ANY

JSERVICES_NAT_OUTOF_PORTS

System Log Message	natpool <i>nat-pool-name</i> is out of ports
Description	Network Address Translation (NAT) services could not allocate a port from the indicated NAT pool, because no ports were available.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	ANY

JSERVICES_NAT_POOL_RELEASE

System Log Message	natpool release <i>address:port[count]</i>
Description	Network Address Translation (NAT) services made the indicated number of ports available in the pool for the indicated address, starting at the indicated port number.
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

JSERVICES_NAT_PORT_BLOCK_ACTIVE

System Log Message	<i>source-address -> nat-source-address:nat-source-port-range-start-nat-source-port-range-end Oobject-create-time</i>
Description	Network Address Translation (NAT) services will generate interim log at the configured interval when the interim log is enabled, which will carry all the information logged in JSERVICES_NAT_PORT_BLOCK_ALLOC including the create-timestamp.
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

JSERVICES_NAT_PORT_BLOCK_ALLOC

System Log Message	<i>source-address -> nat-source-address:nat-source-port-range-start-nat-source-port-range-end Oobject-create-time</i>
Description	Network Address Translation (NAT) services allocated a port block for the indicated private address, with the defined range of ports and NAT IP allocated to it.
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

JSERVICES_NAT_PORT_BLOCK_RELEASE

System Log Message	<i>source-address -> nat-source-address:nat-source-port-range-start-nat-source-port-range-end Oobject-create-time</i>
Description	Network Address Translation (NAT) services released a port block associated with the indicated private address, with the defined range of ports and NAT IP allocated to it.
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

JSERVICES_NAT_RULE_MATCH

System Log Message	<i>proto protocol-id (protocol-name) application: application, interface-name:source-address:source-port -> destination-address:destination-port, Match NAT rule-set: rule-set-name, rule: rule-name, term: term-name</i>
Description	The packet with the indicated characteristics matched the indicated term in the indicated nat rule. The matching packet contained the indicated information about its protocol

(numerical identifier and name), application, source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

JSERVICES_SESSION_CLOSE

System Log Message *application:application, source-interface-name source-address:source-port source-nat-information -> destination-address destination-port:destination-nat-information (protocol-name)*

Description The session with the indicated characteristics is removed. The NAT data is available in the message if the session requires Network Address Translation (NAT).

Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY
Action	None

JSERVICES_SESSION_OPEN

System Log Message *application:application, source-interface-name source-address:source-port source-nat-information -> destination-address destination-port:destination-nat-information (protocol-name)*

Description The packet with the indicated characteristics is accepted by the configured plugins after a policy check. As a result, a new session is created and opened for traffic. The NAT information is available in the message if the policy requires Network Address Translation (NAT).

Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY
Action	None

JSERVICES_SFW_RULE_ACCEPT

System Log Message *proto protocol-id (protocol-name) application: application, interface: source-interface-name,source-address:source-port -> destination-address:destination-port, Match SFW event-type rule-set: rule-set-name, rule: rule-name, term: term-name*

Description The packet with the indicated characteristics matched the indicated term in the indicated stateful firewall rule, which has an 'accept' action. If the rule belongs to a rule set, the rule set name is also displayed. The stateful firewall accepted the flow to which the packet belongs. The matching packet contained the indicated information about its

protocol (numerical identifier and name), application, source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

JSERVICES_SFW_RULE_DISCARD

System Log Message *proto protocol-id (protocol-name) application: application, source-address:source-port -> destination-address:destination-port, Match SFW event-type rule-set: rule-set-name, rule: rule-name, term: term-name*

Description The packet with the indicated characteristics matched the indicated term in the indicated stateful firewall rule, which has a 'discard' action. If the rule belongs to a rule set, the rule set name is also displayed. The stateful firewall discarded the packet. The matching packet contained the indicated information about its protocol (numerical identifier and name), application, source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY

JSERVICES_SFW_RULE_REJECT

System Log Message *proto protocol-id (protocol-name) application: application, source-address:source-port -> destination-address:destination-port, Match SFW event-type rule-set: rule-set-name, rule: rule-name, term: term-name*

Description The packet with the indicated characteristics matched the indicated term in the indicated stateful firewall rule, which has a 'reject' action. If the rule belongs to a rule set, the rule set name is also displayed. If the packet used the User Datagram Protocol (UDP), the stateful firewall generated an Internet Control Message Protocol (ICMP) error message. If the packet used the Transmission Control Protocol (TCP), the stateful firewall generated an RST packet. The matching packet contained the indicated information about its protocol (numerical identifier and name), application, source (logical interface name, IP address, and port number), and destination (IP address and port number).

Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY

CHAPTER 59

JSRPD System Log Messages

This chapter describes messages with the **JSRPD** prefix. They are generated by the Juniper Services Redundancy Protocol (jsrpd) process, which controls chassis clustering.

JSRPD_DAEMONIZE_FAILED

System Log Message	Aborting, unable to run in the background as a daemon: <i>error-message</i>
Description	The Juniper Services Redundancy Protocol process (JSRPD) failed to create a version of itself to run in the background.
Type	Error: An error occurred
Severity	emergency
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18923 .

JSRPD_DUPLICATE

System Log Message	Another copy of this program is running
Description	The Juniper Services Redundancy Protocol process (JSRPD) detected that another version of itself is already running.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

JSRPD_NODE_STATE_CHANGE

System Log Message	Node <i>chassis-id</i> state due to <i>reason</i>
Description	The Juniper Services Redundancy Protocol process (JSRPD) detected an event, such as failover, that caused the state of the chassis cluster node to change due to the reason indicated in the log.
Type	Event: This message reports an event, not an error

Severity	error
Facility	LOG_DAEMON
Cause	A link failure occurred and the secondary node is disabled.
Cause	The secondary node has recovered from link failure and is being rebooted to recover from the disabled state.
Action	Contact your technical support representative.

JSRPD_NOT_ROOT

System Log Message	Must be run as root
Description	The Juniper Services Redundancy Protocol process (JSRPD) can be instantiated only by the user with root privileges.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

JSRPD_PID_FILE_LOCK

System Log Message	Unable to lock PID file: <i>error-message</i>
Description	The Juniper Services Redundancy Protocol process (JSRPD) failed to lock the PID file, which serves to prevent multiple instances of the process from running simultaneously.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

JSRPD_PID_FILE_UPDATE

System Log Message	Unable to update process PID file: <i>error-message</i>
Description	The Juniper Services Redundancy Protocol process (JSRPD) failed to update the PID file, which serves to prevent multiple instances of the process from running simultaneously.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

JSRPD_REDUNDANCY_MODE_CHANGE

System Log Message	Redundancy mode change will not be effective until all nodes in the cluster are rebooted simultaneously
---------------------------	---

Description The Juniper Services Redundancy Protocol process (JSRPD) detected a change in chassis cluster redundancy mode. The new mode is not effective until all nodes in the cluster are rebooted.

Type Error: An error occurred

Severity warning

Facility LOG_DAEMON

JSRPD_REDUNDANCY_MODE_MISMATCH

System Log Message Change in HA redundancy mode detected..please reboot all nodes in the cluster simultaneously!!

Description The Juniper Services Redundancy Protocol process (JSRPD) detected a change in the chassis cluster redundancy mode configuration and detected that only some (not all) of the nodes rebooted. The new mode is not effective until all nodes in the cluster are rebooted.

Type Error: An error occurred

Severity warning

Facility LOG_DAEMON

JSRPD_RG_STATE_CHANGE

System Log Message Redundancy-group *rg-id* transitioned from '*old-state*' to '*new-state*' state due to *reason*

Description The Juniper Services Redundancy Protocol process (JSRPD) detected an event that caused the state of the chassis cluster redundancy group to change due to the reason indicated in the log.

Type Event: This message reports an event, not an error

Severity alert

Facility LOG_DAEMON

JSRPD_SET_CS_MON_FAILURE

System Log Message Cold-sync Monitor failed for redundancy-group *rg-id*

Description The Juniper Services Redundancy Protocol process (JSRPD) detected cold-sync monitoring failure for a redundancy group.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

JSRPD_SET_HW_MON_FAILURE

System Log Message hw-mon failed for redundancy-group *rg-id*

Description The Juniper Services Redundancy Protocol process (JSRPD) detected hardware failures.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

JSRPD_SET_INTF_MON_FAILURE

System Log Message Interface Monitor failed for redundancy-group *rg-id*

Description The Juniper Services Redundancy Protocol process (JSRPD) detected interface monitoring failure for a redundancy group.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

JSRPD_SET_IP_MON_FAILURE

System Log Message IP Monitor failed for redundancy-group *rg-id*

Description The Juniper Services Redundancy Protocol process (JSRPD) detected IP address monitoring failure for a redundancy group.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

JSRPD_SET_LOOPBACK_MON_FAILURE

System Log Message Loopback Monitor failed for redundancy-group *rg-id*

Description The Juniper Services Redundancy Protocol process (JSRPD) detected data path loopback monitoring failure for a redundancy group.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

JSRPD_SET_MBUF_MON_FAILURE

System Log Message Memory buffer monitor failed for redundancy-group *rg-id*

Description The Juniper Services Redundancy Protocol process (JSRPD) detected memory buffer monitoring failure for a redundancy group.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

JSRPD_SET_NEXTHOP_MON_FAILURE

System Log Message Fabric nexthop monitor failed for redundancy-group *rg-id*

Description The Juniper Services Redundancy Protocol process (JSRPD) detected fabric nexthop monitoring failure for a redundancy group.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

JSRPD_SET_NPC_MON_FAILURE

System Log Message NPC Monitor failed for redundancy-group *rg-id*

Description The Juniper Services Redundancy Protocol process (JSRPD) detected Network Processing Card (NPC) monitoring failure for a redundancy group.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

JSRPD_SET_OTHER_INTF_MON_FAIL

System Log Message Interface Monitor failed on other node for redundancy-group *rg-id*

Description The Juniper Services Redundancy Protocol process (JSRPD) detected interface monitoring failure on the other node for a redundancy group.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

JSRPD_SET_SPU_MON_FAILURE

System Log Message SPU Monitor failed for redundancy-group *rg-id*

Description The Juniper Services Redundancy Protocol process (JSRPD) detected Services Processing Unit (SPU) monitoring failure for a redundancy group.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

JSRPD_SOCKET_CREATION_FAILURE

System Log Message Socket creation (server) failed unexpectedly *error-message*.

Description The Juniper Services Redundancy Protocol process (JSRPD) failed to create a socket.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18925 .

JSRPD_SOCKET_LISTEN_FAILURE

System Log Message	Socket listen (server) failed unexpectedly. <i>error-message</i>
Description	The Juniper Services Redundancy Protocol process (JSRPD) failed to listen on a socket.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18926 .

JSRPD_SOCKET_RECV_HB_FAILURE

System Log Message	Socket reception of heartbeat from failed unexpectedly <i>error-message</i> .
Description	The Juniper Services Redundancy Protocol process (JSRPD) failed to receive heartbeat.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18927 .

JSRPD_UNSET_CS_MON_FAILURE

System Log Message	Cold-sync Monitor failure recovered for redundancy-group <i>rg-id</i>
Description	The Juniper Services Redundancy Protocol process (JSRPD) detected that the previous cold-sync monitoring failure no longer exists for a redundancy group.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

JSRPD_UNSET_HW_MON_FAILURE

System Log Message	hw-mon failure recovered for redundancy-group <i>rg-id</i>
---------------------------	--

Description The Juniper Services Redundancy Protocol process (JSRPD) detected that the previous hardware failures no longer exists for a redundancy group.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

JSRPD_UNSET_INTF_MON_FAILURE

System Log Message Interface Monitor failure recovered for redundancy-group *rg-id*

Description The Juniper Services Redundancy Protocol process (JSRPD) detected that the previous interface monitoring failure no longer exists for a redundancy group.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

JSRPD_UNSET_IP_MON_FAILURE

System Log Message IP Monitor failure recovered for redundancy-group *rg-id*

Description The Juniper Services Redundancy Protocol process (JSRPD) detected that the previous IP address monitoring failure no longer exists for a redundancy group.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

JSRPD_UNSET_LOOPBACK_MON_FAILURE

System Log Message Previous loopback monitor failure no longer exist for redundancy-group *rg-id*

Description The Juniper Services Redundancy Protocol process (JSRPD) detected that the previous data path loopback monitoring failure no longer exists for a redundancy group.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

JSRPD_UNSET_MBUF_MON_FAILURE

System Log Message Previous memory buffer monitor failure no longer exist for redundancy-group *rg-id*

Description The Juniper Services Redundancy Protocol process (JSRPD) detected that the previous memory buffer monitoring failure no longer exists for a redundancy group.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

JSRPD_UNSET_NEXTHOP_MON_FAILURE

System Log Message Previous fabric nexthop monitor failure no longer exists for redundancy-group *rg-id*

Description The Juniper Services Redundancy Protocol process (JSRPD) detected that the previous fabric nexthop monitoring failure no longer exists for a redundancy group.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

JSRPD_UNSET_NPC_MON_FAILURE

System Log Message NPC Monitor failure recovered for redundancy-group *rg-id*

Description The Juniper Services Redundancy Protocol process (JSRPD) detected that the previous Network Processing Card (NPC) monitoring failure no longer exists for a redundancy group.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

JSRPD_UNSET_OTHER_INTF_MON_FAIL

System Log Message Interface Monitor failure recovered on other node for redundancy-group *rg-id*

Description The Juniper Services Redundancy Protocol process (JSRPD)\ detected that the previous interface monitoring failure on the other node no longer exists for a redundancy group.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

JSRPD_UNSET_SPU_MON_FAILURE

System Log Message SPU Monitor failure recovered for redundancy-group *rg-id*

Description The Juniper Services Redundancy Protocol process (JSRPD) detected that the previous Services Processing Unit (SPU) monitoring failure no longer exists for a redundancy group.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

JSRPD_USAGE

System Log Message	Usage: jsrpd [-C] [-N] [-X] [-d debug-level] [-l] [-v]
Description	The Juniper Services Redundancy Protocol process (JSRPD) was invoked with incorrect options.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

CHAPTER 60

JTASK System Log Messages

This chapter describes messages with the **JTASK** prefix.

JTASK_ABORT

System Log Message	abort <i>executable-name</i> [<i>pid</i>] version <i>version</i> built by <i>builder</i> on <i>date</i> : <i>error-message</i>
Description	Process terminated because of an internal error.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Examine the messages that immediately follow this message in the system log for information about possible causes.
Cause	An internal software failure occurred.

JTASK_ACTIVE_TERMINATE

System Log Message	Exiting with active tasks: <i>task-name</i>
Description	After receiving multiple termination requests, the process exited without performing the indicated cleanup tasks.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

JTASK_ASSERT

System Log Message	Assertion failed <i>executable-name</i> [<i>pid</i>]: file " <i>source-filename</i> ", line <i>line-number</i> : " <i>message</i> "
Description	The source code for the process includes internal self-consistency checks. A check failed at the indicated line number in the indicated source file, causing the process that was using the indicated binary and had the indicated process ID (PID) to terminate. The process created a diagnostic core dump for analysis by technical support personnel.
Type	Error: An error occurred

Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Examine the messages that immediately follow this message in the system log for information about possible causes. Contact a technical support representative, and be ready to provide the list of messages and the diagnostic core dump, if requested.

JTASK_ASSERT_SOFT

System Log Message	Soft assertion failed <i>executable-name</i> [<i>pid</i>]: file " <i>source-filename</i> ", line <i>line-number</i> : " <i>message</i> ", daemon continued running
Description	The source code for the process includes internal self-consistency checks. A check failed at the indicated line number in the indicated source file, but the process that was using the indicated binary and had the indicated process ID (PID) continued running. The process created a diagnostic core dump for analysis by technical support personnel.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Examine the messages that immediately follow this message in the system log for information about possible causes. Contact a technical support representative, and be ready to provide the list of messages and the diagnostic core dump, if requested.

JTASK_BFD_READ_ERROR

System Log Message	Read error on pipe from bfdd: <i>reason</i> (<i>error-message</i>)
Description	The process could not read a message available on the read pipe from the Bidirectional Forwarding Detection process (bfdd).
Type	Error: An error occurred
Severity	info
Facility	LOG_DAEMON
Action	Contact your technical support representative.

JTASK_BFD_WRITE_ERROR

System Log Message	<i>function-name</i> : write error on pipe to bfdd (<i>error-message</i>)
Description	The process could not write a message on the pipe to the Bidirectional Forwarding Detection process (bfdd).

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

JTASK_CFG_CALLBACK_LONGRUNTIME

System Log Message	<i>function-name</i> : excessive runtime <i>time</i> during <i>action</i> of <i>module</i>
Description	The indicated submodule of the process ran uninterrupted for the indicated period of time, which is considered excessive.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	The duration was noted because task accounting is enabled. The function might be implemented inefficiently.

JTASK_CFG_SCHED_CUMU_LONGRUNTIME

System Log Message	<i>function-name</i> : excessive runtime (total of <i>time</i> in <i>count</i> callbacks) after <i>action</i> of <i>module</i>
Description	Several submodules of the process ran uninterrupted for the indicated period of time, which is considered excessive.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	The duration was noted because task accounting is enabled. The function might be implemented inefficiently.

JTASK_EXIT

System Log Message	Exit <i>executable-name</i> [<i>pid</i>] version <i>version</i> built by <i>builder</i> on <i>date</i> , caller <i>address</i>
Description	The process exited, either in response to a user request or because of a system error.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON
Cause	A system resource was unavailable, process did not understand an error, or a user terminated the process.

Action Examine the messages that immediately follow this message in the system log for information about possible causes.

JTASK_LOCK_FLOCKED

System Log Message Unable to obtain a lock on *filename*, is another copy of rpd running?

Description The process could not obtain the mutual exclusion lock that prevents more than one instance of process from running simultaneously. The system terminated the indicated process.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause Another process process is running.

Action Use the 'show system process' command to verify that another process is running.

JTASK_LOCK_LOCKED

System Log Message Unable to obtain a lock on *filename*, *program-name*[*pid*] is still running

Description The process could not obtain the mutual exclusion lock that prevents more than one instance of process from running simultaneously. The system terminated this instance of process.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause Another process is running.

Action Use the 'show system process' command to verify that another process is running.

JTASK_MGMT_TIMEOUT

System Log Message Connection to management peer *process-name* timed out waiting for input

Description The connection between the process and the indicated management process (mgd) timed out before input arrived from the mgd process.

Type Error: An error occurred

Severity warning

Facility LOG_DAEMON

JTASK_MODE_SWITCH

System Log Message	Switching to <i>mode</i> -bit mode
Description	Tasking application process is attempting to switch between 32- and 64-bit operating mode.
Type	Error: An error occurred
Severity	notice
Facility	LOG_DAEMON

JTASK_MODE_SWITCH_FAIL

System Log Message	Mode switch failed: <i>error-message</i>
Description	Tasking application process could not switch to the configured 32- or 64-bit operating mode.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

JTASK_OS_MEMHIGH

System Log Message	Using <i>size</i> KB of memory, <i>percentage-value</i> percent of available
Description	The process is using the indicated amount and percentage of Routing Engine memory, which is considered excessive.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	Either process is leaking memory or the use of system resources is excessive, perhaps because routing filters are misconfigured or the configured network topology is very complex.
Action	Increase the amount of RAM in the Routing Engine. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB19121 .

JTASK_PARSE_BAD_COMMAND

System Log Message	<i>executable-name</i> : problem processing debug shell command for command-line option <i>option</i> , command ' <i>command</i> ': <i>error-message</i>
Description	An invalid debug shell command was specified on the command line.
Type	Error: An error occurred

Severity	error
Facility	LOG_DAEMON
Action	Reissue the command and correct the error described.

JTASK_PARSE_BAD_FILE

System Log Message	<i>executable-name</i> : problem processing file for command-line option <i>option</i> , file ' <i>filename</i> ': <i>error-message</i>
Description	An invalid debug shell command file was specified on the command line.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Reissue the command and correct the error described.

JTASK_PARSE_BAD_LR_NAME

System Log Message	<i>executable-name</i> : logical system name " <i>logical-system-name</i> " exceeds <i>count</i> characters
Description	The indicated logical system name exceeds the indicated maximum number of characters.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Assign a shorter name.

JTASK_PARSE_BAD_OPTION

System Log Message	<i>executable-name</i> : command-line option <i>option</i> is invalid
Description	The command line used to start the indicated process included the indicated option, which is invalid. The process did not start.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Reissue the command without the invalid option.

JTASK_PARSE_CMD_ARG

System Log Message	<i>executable-name</i> : missing required argument for command-line option <i>option</i>
Description	The command line used to start the indicated process did not include the argument required by the indicated option. The process did not start.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Reissue the command and include the required argument. Examine the messages that immediately follow this message in the system log for information about possible causes. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18885 .

JTASK_PARSE_CMD_DUPLICATE

System Log Message	<i>executable-name</i> : command-line option <i>option</i> is a duplicate
Description	The command line used to start the indicated process included the indicated duplicate option. The process did not start.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Reissue the command without the duplicate option.

JTASK_PARSE_CMD_EXTRA

System Log Message	<i>executable-name</i> : command-line option <i>option</i> is extraneous
Description	The command line used to start the indicated process included the indicated option, which is extraneous. The process did not start.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Reissue the command and omit the extraneous option. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18945 .

JTASK_PTHREAD_CREATE

System Log Message	Task pthread worker creation failed
Description	During process initialization, creation of a thread has failed.
Type	Error: An error occurred
Severity	alert
Facility	LOG_DAEMON
Action	Restart the application from the CLI (e.g. restart routing)

JTASK_SCHED_CUMU_LONGRUNTIME

System Log Message	<i>function-name</i> : excessive runtime (total of <i>time</i> in <i>count</i> callbacks) after <i>action</i> of <i>module</i>
Description	Several submodules of the process ran uninterrupted for the indicated period of time, which is considered excessive.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	The duration was noted because task accounting is enabled. The function might be implemented inefficiently.

JTASK_SCHED_MODULE_LONGRUNTIME

System Log Message	<i>function-name</i> : excessive runtime <i>time</i> during <i>action</i> of <i>module</i>
Description	Several submodules of the process ran uninterrupted for the indicated period of time, which is considered excessive.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	The duration was noted because task accounting is enabled. The function might be implemented inefficiently.

JTASK_SCHED_TASK_LONGRUNTIME

System Log Message	<i>function-name</i> ran for <i>total-time</i> (<i>user-time</i> user, <i>system-time</i> system) doing <i>action</i>
Description	A task callback within the process ran uninterrupted for the indicated period of time, which is considered excessive.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	The duration was noted because task accounting is enabled. The function might be implemented inefficiently.

JTASK_SIGNAL_TERMINATE

System Log Message	<i>signal-name</i> termination signal received
Description	In response to the indicated termination request, the process terminated adjacencies with neighbors and shut down.

Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

JTASK_SNMP_CONN_EINPROGRESS

System Log Message	<i>function-name: error-message</i>
Description	The indicated error occurred while the process was connecting to the Simple Network Management Protocol (SNMP) master agent.
Type	Error: An error occurred
Severity	info
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18945 .

JTASK_SNMP_CONN_QUIT

System Log Message	<i>function-name: unable to connect to SNMP agent (pathname): error-message</i>
Description	The process could not connect to the indicated Simple Network Management Protocol (SNMP) master agent.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18946 .

JTASK_SNMP_CONN_RETRY

System Log Message	<i>function-name: reattempting connection to SNMP agent (pathname): error-message</i>
Description	The process tried again to connect to the indicated Simple Network Management Protocol (SNMP) master agent after a connection attempt failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

JTASK_SNMP_INVALID_SOCKET

System Log Message	<i>function-name: socket file-descriptor is invalid</i>
Description	The process could not send a message to a Simple Network Management Protocol (SNMP) master agent because the indicated socket is invalid.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

JTASK_SNMP_SOCKETOPT_BLOCK

System Log Message *function-name*: unable to set nonblocking option
Description The process could not set a socket to nonblocking mode after connecting to the Simple Network Management Protocol (SNMP) master agent.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

JTASK_SNMP_SOCKETOPT_RECVBUF

System Log Message *function-name*: unable to set recvbuf option
Description The process could not set the size of the kernel receive buffer, which allows it to accept the largest possible packet from the Simple Network Management Protocol (SNMP) master agent.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON
Action For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18946>.

JTASK_SNMP_SOCKETOPT_SENDBUF

System Log Message *function-name*: unable to set sendbf option
Description The process could not set the size of the kernel send buffer, which allows it to send the largest possible packet to the Simple Network Management Protocol (SNMP) master agent.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON
Action For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18947>.

JTASK_START

System Log Message Start *executable-name*[*pid*] version *version* built *date*

Description	The process started.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

JTASK_SYSTEM

System Log Message *reason: error-message*

Description A system call made by the routing protocol process (process) failed.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	It is possible that the kernel lacked the resources to fulfill the request. The process process will recover.
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB19122 .

JTASK_TASK_BEGIN

System Log Message Commencing routing updates version *process-version*, built *date* by *builder*

Description The process started.

Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

JTASK_TASK_CHILDKILLED

System Log Message *task-name* terminated by SIG*signal-name*core-dump-status

Description While a child process of the process was performing the indicated operation, it terminated in response to the indicated signal.

Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

JTASK_TASK_CHILDSTOPPED

System Log Message *task-name* stopped by SIG*signal-name*

Description While a child process of the process was performing the indicated operation, it stopped in response to the indicated signal.

Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

JTASK_TASK_DYN_REINIT

System Log Message	Dynamic reconfiguration in process
Description	The process reinitialized.

Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

JTASK_TASK_FORK

System Log Message	Unable to fork <i>task-name: error-message</i>
Description	The routing protocol process failed to create the indicated child process.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

JTASK_TASK_GETWD

System Log Message	<i>getwd: error-message</i>
Description	The <code>getwd()</code> system call made by the routing protocol process (process) failed.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	It is possible that the kernel lacked the resources to fulfill the request. The process process will recover.

JTASK_TASK_MASTERSHIP

System Log Message	Assuming mastership
Description	The process became active when the Routing Engine on which it was running assumed mastership.

Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

JTASK_TASK_NOREINIT

System Log Message	Reinitialization not possible
Description	The process failed to reinitialize as requested, because it was running in a state that did not allow reconfiguration.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

JTASK_TASK_PIDCLOSED

System Log Message	Unable to close and remove <i>filename: error-message</i>
Description	The process tried to close and remove the file that records its process ID (PID), which serves to prevent multiple instances of process from running simultaneously. The attempt failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

JTASK_TASK_PIDFLOCK

System Log Message	flock(<i>filename</i> , LOCK_EX): <i>error-message</i>
Description	The process issued the flock() system call on the file that records its process ID (PID), which serves to prevent multiple instances of process from running simultaneously. The system call failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

JTASK_TASK_PIDWRITE

System Log Message	Unable to write to fd <i>filename: error-message</i>
Description	The process tried to write to the file that records its process ID (PID), which serves to prevent multiple instances of process from running simultaneously. The attempt failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

JTASK_TASK_REINIT

System Log Message	Reinitializing
---------------------------	----------------

Description	The process reinitialized.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

JTASK_TASK_SIGNALIGNORE

System Log Message	<code>sigaction(SIG$signal$-name): error-message</code>
Description	The process informed the kernel that it wished to ignore the indicated signal, but the kernel failed to process the request.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

JTASK_TERMINATE_DISK_SPACE

System Log Message	<code>disk full, terminating executable-name[pid] version version built by builder on date.BACKTRACE: message</code>
Description	The routing process has terminated due to no disk space available.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	disk-full
Action	Examine disk storage, especially /tmp and /var/tmp, for old or obsolete files such as old core files or old log files that can be safely removed.

CHAPTER 61

JTRACE System Log Messages

This chapter describes messages with the **JTRACE** prefix.

JTRACE_FAILED

System Log Message	Unable to write to trace file <i>filename</i>
Description	This process could not write to the indicated trace file, and stopped attempting to do so. The next commit of the configuration database will reenale tracing.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

CHAPTER 62

KMD System Log Messages

This chapter describes messages with the **KMD** prefix. They are generated by the key management process (kmd), which provides IP Security (IPSec) authentication services for encryption PICs.

KMD_CFG_IF_ID_POOL_NOT_FOUND

System Log Message	Unable to allocate logical interface for IPSec interface from pool <i>pool-name</i> : pool not found
Description	The key management process (kmd) maintains pools of logical interfaces for assignment to IP Security (IPSec) interfaces. It could not allocate a logical interface, because it could not access the indicated pool.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH

KMD_CFG_IF_ID_POOL_NO_ENTRY

System Log Message	Unable to return logical interface <i>interface-name.interface-unit</i> to pool <i>pool-name</i> : no entry in pool for interface
Description	The key management process (kmd) maintains pools of logical interfaces for assignment to IP Security (IPSec) interfaces. It could not return the indicated logical interface to the indicated pool, because there was no entry for the interface in the pool.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH

KMD_CFG_IF_ID_POOL_NO_INTERFACE

System Log Message	Unable to allocate logical interface for IPSec interface from pool <i>pool-name</i> : no interfaces available
Description	The key management process (kmd) maintains pools of logical interfaces for assignment to IP Security (IPSec) interfaces. It could not allocate a logical interface, because none were available in the indicated pool.

Type Error: An error occurred
Severity error
Facility LOG_AUTH

KMD_CFG_IF_ID_POOL_RETURN_FAILED

System Log Message Unable to return logical interface to pool *pool-name*: pool not found

Description The key management process (kmd) maintains pools of logical interfaces for assignment to IP Security (IPSec) interfaces. It could not return a logical interface to the indicated pool, because it could not access the pool.

Type Error: An error occurred
Severity error
Facility LOG_AUTH

KMD_DPD_FAILOVER_MANUAL_TUNNEL

System Log Message Tunnel *tunnel-name* did not fail over: it is manual type

Description An IP Security (IPSec) tunnel normally fails over to its backup when the key management process (kmd) detects a dead peer. Failover was not attempted for the indicated tunnel, which is configured as a manual type and so does not support failover.

Type Error: An error occurred
Severity error
Facility LOG_AUTH

KMD_DPD_FAILOVER_MAX_ATTEMPTS

System Log Message Number of failover attempts exceeded limit *count* for tunnel *tunnel-name*

Description An IP Security (IPSec) tunnel fails over to its backup when the key management process (kmd) detects a dead peer. The key management process (kmd) stopped making failover attempts for the indicated tunnel, because the number of attempts exceeded the indicated limit configured for Internet Key Exchange (IKE) Phase 1 negotiations.

Type Error: An error occurred
Severity error
Facility LOG_AUTH

Cause Failover attempts can fail repeatedly if both the primary and backup peers are unreachable during the failover.

KMD_DPD_FAILOVER_NO_ACTIVE_PEER

System Log Message Tunnel *tunnel-name* did not fail over: no active peer configured

Description An IP Security (IPSec) tunnel normally fails over to its backup when the key management process (kmd) detects a dead peer. Failover was not attempted because the configuration for the indicated tunnel does not include information about an active peer.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

KMD_DPD_FAILOVER_NO_BACKUP_PEER

System Log Message Tunnel *tunnel-name* did not fail over: no backup peer configured

Description An IP Security (IPSec) tunnel normally fails over to its backup when the key management process (kmd) detects a dead peer. A failover attempt failed when the kmd process found that the configuration for the indicated tunnel does not include information about a backup peer.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

KMD_DPD_FAILOVER_NO_TUNNEL_CFG

System Log Message Tunnel did not fail over: tunnel configuration not found

Description An IP Security (IPSec) tunnel normally fails over to its backup when the key management process (kmd) detects a dead peer. Failover was not attempted because there was no configuration information for the tunnel.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

KMD_DPD_REMOTE_ADDRESS_CHANGED

System Log Message Remote peer address for tunnel *tunnel-name* changed from *old-address* to *new-address*

Description The remote peer address in the configuration for the indicated tunnel changed to a new value as indicated.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_AUTH

KMD_PM_DUPLICATE_LIFE_DURATION

System Log Message Duplicate SA life duration value given in Quick Mode notification from *remote-address:remote-port*

Description The IKE Quick Mode notification message from the indicated remote gateway and remote port contains duplicate value for life duration. Hence Quick Mode notification payload is dropped.

Type Error: An error occurred

Severity error

Facility LOG_SYSLOG

KMD_PM_IKE_SERVER_LOOKUP_FAILED

System Log Message No IKE server to connect Phase-1 to *remote-peer*

Description The IKE Phase-1 negotiation with indicated remote gateway address failed because there is no corresponding IKE server running locally.

Type Error: An error occurred

Severity error

Facility LOG_SYSLOG

KMD_PM_IKE_SERVER_NOT_FOUND

System Log Message Failed to connect to *remote-address:remote-port* as there is no IKE server context available in instance *service-set*

Description There is no local IKE server context in the indicated service set, hence failed to send the SPI delete notification request.

Type Error: An error occurred

Severity error

Facility LOG_SYSLOG

KMD_PM_IKE_SRV_NOT_FOUND_DELETE

System Log Message Unable to notify remote peer *remote-address:remote-port* that SPI was deleted: no IKE server for service set *service-set*

Description The indicated service set did not have a local Internet Key Exchange (IKE) server context for the indicated remote peer (address and port). As a result, notification about deletion of a security parameter index (SPI) was not sent.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

KMD_PM_ILLEGAL_REMOTE_GW_ID

System Log Message Aborting Phase-1 negotiation. Cannot initiate negotiation with invalid Phase-1 remote *remote-peer* in instance: *service-set*

Description The specified remote gateway identity is neither an IPv4 address nor an IPv6 address. Hence Phase-1 negotiation can not be started

Type Error: An error occurred

Severity error

Facility LOG_SYSLOG

KMD_PM_INCONSISTENT_P2_IDS

System Log Message Inconsistent phase-2 (IPsec) identities, local : initiator = *local-initiator* responder = *local-responder* remote : initiator = *remote-initiator* responder = *remote-responder*

Description Initiator and responder identities at the local end are inconsistent with the remote peer's identities. Quick Mode negotiation is aborted.

Type Error: An error occurred

Severity error

Facility LOG_SYSLOG

KMD_PM_INVALID_LIFE_TYPE

System Log Message Invalid life type *units-type* found in the Quick Mode notification from *remote-address:remote-port*

Description The IKE Quick Mode notification message from the indicated remote gateway and remote port contains invalid life type. Second and Kilobytes are the only supported life types currently. Hence Quick Mode notification payload is dropped.

Type Error: An error occurred

Severity error

Facility LOG_SYSLOG

KMD_PM_LIFETIME_TO_SHORT

System Log Message Lifetime negotiated for SA, "*sa-name*", is too short for reliable rekeying, changed from *lifetime* to *adjusted-lifetime* seconds

Description The negotiated lifetime for the IPsec SA is too low to reliably rekey the IPsec SA. Used lifetime was set to the minimum required value.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_AUTH

KMD_PM_NO_LIFETIME

System Log Message Duplicate life time payloads present in the notification from *remote-address:remote-port*. Dropping the notification.

Description The IKE Quick Mode notification message from the indicated remote gateway and remote port contains two life type fields and there is no life duration field. Quick Mode notification is being dropped since it has insufficient information about life duration.

Type Error: An error occurred

Severity error

Facility LOG_SYSLOG

KMD_PM_NO_LIFE_TYPE

System Log Message Quick mode notification from *remote-address:remote-port* contains lifetime duration without corresponding SA lifetime payload.

Description The IKE Quick Mode notification message from the indicated remote gateway and remote port does not contain life type, hence existing life duration cannot be interpreted to be of a particular life type. Quick Mode notification payload is dropped.

Type Error: An error occurred

Severity error

Facility LOG_SYSLOG

KMD_PM_NO_PROPOSAL_FOR_PHASE1

System Log Message Aborting Phase-1 negotiation. No proposal found to initiate negotiation between local:*local-peer* and remote *remote-peer* in instance:*service-set*

Description It is not possible to start the Phase-1 negotiation to the indicated remote gateway because there is no proposal present.

Type Error: An error occurred

Severity error

Facility LOG_SYSLOG

KMD_PM_NO_SPD_PHASE1_FUNC_PTR

System Log Message Phase-1 SPD handler is not registered in instance:*service-set*

Description Phase-1 negotiation can not be initiated as initialization function failed.

Type Error: An error occurred

Severity error

Facility LOG_SYSLOG

KMD_PM_P1_POLICY_LOOKUP_FAILURE

System Log Message Policy lookup for Phase-1 [*negotiation-role*] failed for p1_local=*local-peer* p1_remote=*remote-peer*

Description The IKE Phase-1 negotiation with the indicated remote gateway address failed because there is no IKE policy configured for use against the indicated remote gateway.

Type Error: An error occurred

Severity error

Facility LOG_SYSLOG

KMD_PM_P2_POLICY_LOOKUP_FAILURE

System Log Message Policy lookup for Phase-2 [*negotiation-role*] failed for p1_local=*local-peer* p1_remote=*remote-peer* p2_local=*local-prefix* p2_remote=*remote-prefix*

Description The IKE Phase-2 negotiation with the indicated remote gateway address failed because the traffic selectors proposed by the remote gateway address do not match any of the policies configured for the indicated local gateway address. The proposed traffic selectors are indicated by the Phase-2 local and remote IP prefixes.

Type Error: An error occurred

Severity error

Facility LOG_SYSLOG

KMD_PM_PHASE1_GROUP_UNSPECIFIED

System Log Message Used DH group 1 because Phase 1 proposal did not specify group

Description The key management process (kmd) assigned Diffie-Hellman (DH) group 1 to an Internet Key Exchange (IKE) Phase 1 proposal because no group was specified.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_AUTH

KMD_PM_PHASE1_POLICY_SEARCH_FAIL

System Log Message No ike-policy found for ike-access-profile: *access-profile*, instance:*service-set*

Description The key management process (kmd) could not retrieve the Phase 1 policy referenced by the indicated Internet Key Exchange (IKE) access profile for the indicated dynamic-endpoint service set.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

KMD_PM_PHASE2_POLICY_LOOKUP_FAIL

System Log Message Unable to retrieve policy for Phase 2 from *negotiation-role* (Phase 1 local peer *local-peer*, remote peer *remote-peer*; Phase 2 local peer *local-prefix*, remote peer *remote-prefix*)

Description The key management process (kmd) could not retrieve a policy from the indicated participant to use during Internet Key Exchange (IKE) Phase 2 negotiation for the indicated local and remote peers. The traffic selectors proposed by the remote peer (represented by the indicated Phase 2 IP prefixes) do not match any local peer policies.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

KMD_PM_PROTO_INVALID

System Log Message Invalid protocol *protocol-id* was negotiated for SA *sa-name*

Description During Internet Key Exchange (IKE) Phase 2, the indicated protocol was chosen for the indicated security association (SA). It is not a valid value, so the SA was not established.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

KMD_PM_PROTO_IPCOMP_UNSUPPORTED

System Log Message Unsupported IPComp protocol was negotiated for SA *sa-name*

Description During Internet Key Exchange (IKE) Phase 2, the IP Payload Compression Protocol (IPComp) was chosen for the indicated security association (SA). IPComp is not supported, so the SA was not established.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

KMD_PM_PROTO_ISAKMP_RESV_UNSUPP

System Log Message Unsupported protocol ISAKMP or RESERVED was negotiated for SA *sa-name*

Description During Internet Key Exchange (IKE) Phase 2, either Internet Security Association and Key Management Protocol (ISAKMP) or the value RESERVED was chosen as the protocol for the indicated security association (SA). They are not supported values, so the SA was not established.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

KMD_PM_SA_CFG_NOT_FOUND

System Log Message SA *sa-name* configuration not found

Description The key management process (kmd) could not retrieve configuration information for the indicated security association (SA), and so could not record the values that were negotiated for the SA during Internet Key Exchange (IKE) Phase 2. The SA was not established.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

KMD_PM_SA_ESTABLISHED

System Log Message Local gateway: *local-address*, Remote gateway: *remote-address*, Local ID: *local-initiator*, Remote ID: *remote-responder*, Direction: *argument1*, SPI: *index1*, AUX-SPI: *index2*, Mode: *mode*, Type: *type*

Description A security association has been established

Type Event: This message reports an event, not an error

Severity info

Facility LOG_SYSLOG

KMD_PM_SA_INDEX_GEN_FAILED

System Log Message Unable to generate pair index for SA *sa-name* in service set *service-set*

Description The key management process (kmd) could not generate a pair index for the indicated security association (SA) in the indicated service set. The kmd process canceled Internet Key Exchange (IKE) Phase 2 negotiation.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

KMD_PM_SA_PEER_ABSENT

System Log Message No active peer found in tunnel configuration block *sa-name*

Description Failed to find active peer information in the tunnel configuration block. Hence unable to send SA delete notifications to the peer.

Type Error: An error occurred

Severity error

Facility LOG_SYSLOG

KMD_PM_SA_PEER_NOT_FOUND

System Log Message Unable to find active peer for SA *sa-name*

Description The key management process (kmd) could not retrieve information about an active peer from the configuration for the indicated security association (SA). As a result, it could not notify peers that an SA was deleted.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

KMD_PM_SPI_DELETE_REJECT

System Log Message IKE Phase-2 delete:In instance *service-set* rejecting request to delete SPI size *sizeu* != 4
Local gateway *local-address:local-port*, Remote gateway *remote-address:remote-port*

Description The SPI size in the delete notification is invalid. Hence delete request is rejected. Quick Mode notification payload is dropped.

Type Error: An error occurred

Severity error

Facility LOG_SYSLOG

KMD_PM_UNEQUAL_PAYLOAD_LENGTH

System Log Message Inconsistent payload lengths in Quick Mode responder life time notification from
remote-address:remote-port

Description IKE Quick Mode notification is dropped because of unequal payload length received in the message.

Type Error: An error occurred

Severity error

Facility LOG_SYSLOG

KMD_PM_UNINITIALISE_ERROR

System Log Message Invalid policy managerhandle to uninitialized *service-set*

Description Failed to uninitialized the Policy manager object while deleting the indicated service set.

Type Error: An error occurred

Severity error

Facility LOG_SYSLOG

KMD_PM_UNINITIALIZE_FAILED

System Log Message Unable to uninitialized service set *service-set*: invalid policy manager handle

Description The key management process could not delete the indicated service set, because lack of a valid handle prevented the kmd process from uninitialized the policy manager object for the service set.

Type Error: An error occurred
Severity error
Facility LOG_AUTH

KMD_PM_UNKNOWN_P1_IDENTITIES

System Log Message Failed to initiate the Phase-1 negotiation for local:*local-peer* and remote:*remote-peer* in instance:*service-set*

Description Phase-1 negotiation can not be started because either the local gateway identity or the remote gateway identity is unknown.

Type Error: An error occurred
Severity error
Facility LOG_SYSLOG

KMD_PM_UNKNOWN_PHASE2_ENTITIES

System Log Message No Phase-2 entities present in tunnel configuration block *sa-name*

Description Unable to initiate Phase-2 negotiation because of unknown local and remote traffic selectors in the indicated security association configuration block. For Adaptive Service PIC, the security association configuratin block refers to the tunnel configured under a service set with a given rule name and term name.

Type Error: An error occurred
Severity error
Facility LOG_SYSLOG

KMD_PM_UNKNOWN_QM_NOTIFICATION

System Log Message Unknown Quick mode notification *notification-name* (*notification-type*) (*size length* bytes) from *remote-address:remote-port* for protocol=*protocol-idd* spi(*sizeu*)=*data*

Description The notification message sent by the indicated remote gateway and remote port is not recognized. Hence Quick Mode notification payload is dropped.

Type Error: An error occurred
Severity error
Facility LOG_SYSLOG

KMD_PM_UNSUPPORTED_KEY

System Log Message Key type = *type*, not supported

Description The specified key type is unsupported. Public/Private and Pre-shared key are the only types supported presently.

Type Error: An error occurred

Severity error
Facility LOG_SYSLOG

KMD_PM_UNSUPPORTED_MODE

System Log Message New group mode not supported currently

Description The IKE New Group mode negotiations failed, because this is not a supported feature currently.

Type Error: An error occurred

Severity error

Facility LOG_SYSLOG

KMD_SNMP_EXTRA_RESPONSE

System Log Message PIC *pic-slot* sent additional response after reply to SNMP query: *error-message*

Description The indicated PIC sent an additional unexpected message after it responded to a request from the key management process (kmd) for Simple Network Management Protocol (SNMP) statistics about IP Security (IPSec) security associations (SAs). As a result, the kmd process discarded the initial response.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

KMD_SNMP_FATAL_ERROR

System Log Message Fatal SNMP error occurred: *error-message*

Description The key management process (kmd) could not retrieve Simple Network Management Protocol (SNMP) statistics about IP Security (IPSec) security associations (SAs), because the indicated fatal SNMP error occurred.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

KMD_SNMP_MALLOC_FAILED

System Log Message Unable to allocate memory for reply buffer; SNMP query to PIC *pic-slot* failed

Description The key management process (kmd) could not allocate memory for the buffer it uses to store Simple Network Management Protocol (SNMP) statistics about IP Security (IPSec) security associations (SAs). As a result, it could not retrieve statistics from the indicated PIC.

Type Error: An error occurred

Severity error
Facility LOG_AUTH

KMD_SNMP_PIC_CONNECTION_FAILED

System Log Message Unable to connect to PIC *pic-slot*; SNMP query failed

Description The key management process (kmd) could not open a connection to the indicated PIC. As a result, it could not retrieve Simple Network Management Protocol (SNMP) statistics about IP Security (IPSec) security associations (SAs).

Type Error: An error occurred

Severity error

Facility LOG_AUTH

KMD_SNMP_PIC_NO_RESPONSE

System Log Message PIC *pic-slot* did not respond to SNMP query: *error-message*

Description The indicated PIC did not respond to a request from the key management process (kmd) for Simple Network Management Protocol (SNMP) statistics about IP Security (IPSec) security associations (SAs).

Type Error: An error occurred

Severity error

Facility LOG_AUTH

Action For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18933>.

KMD_SNMP_PIC_SLOT_NOT_FOUND

System Log Message Unable to retrieve slot information for PIC *pic-slot*; SNMP query failed

Description The key management process (kmd) could not retrieve information about the slot housing the indicated PIC. As a result, it could not retrieve Simple Network Management Protocol (SNMP) statistics about IP Security (IPSec) security associations (SAs) from the PIC.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

KMD_VPN_DFBIT_STATUS_MSG

System Log Message The DF-BIT for VPN *vpn-name* has been set to *argument*.

Description VPN DF bit status has been set.

Type Event: This message reports an event, not an error

Severity info
Facility LOG_DAEMON

KMD_VPN_DOWN_ALARM_USER

System Log Message VPN *vpn-name* from *remote-address* is down.
Description Notification to user that VPN monitor detects IPSec SA is down.
Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

KMD_VPN_PV_LIFETIME_CHANGED

System Log Message Config key lifetime changed
Description The key lifetime has been changed by a user.
Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

KMD_VPN_PV_PHASE1

System Log Message IKE Phase-1 Failure: *source-address* [*spi=destination-address*, *src_ip=error-message*, *dst_ip=data*]
Description The threshold value set has been reached due to several ike-phase1 failures that have occurred.
Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON

KMD_VPN_PV_PHASE2

System Log Message IKE Phase-2 Failure: *source-address* [*spi=destination-address*, *src_ip=error-message*, *dst_ip=data*]
Description The threshold value set has been reached due to several ike-phase2 failures that have occurred.
Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON

KMD_VPN_PV_PSK_CHANGED

System Log Message Pre-shared key changed

Description The pre-shared key has been changed by a user.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

KMD_VPN_UP_ALARM_USER

System Log Message VPN *vpn-name* from *remote-address* is up.

Description Notification to user that VPN monitor detects IPSec SA is up.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

CHAPTER 63

L2ALD System Log Messages

This chapter describes messages with the **L2ALD** prefix. They are generated by the Layer 2 address learning process (l2ald), which supports the dynamic acquisition of information about media access control (MAC) addresses in a Layer 2 bridge environment.

L2ALD_BD_CREATE_FAILURE

System Log Message	BD <i>bridge-domain</i> creation failed. Attempting to recover after some interval
Description	The Layer 2 address learning process (l2ald) failed to create BD in kernel. This can happen when kernel cannot allocate BD due to temporary resource exhaustion or due to over configuration. The first case is automatically handled by l2ald. The latter case can be recovered from by removing configurations which are beyond platform limitations
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	Contact your technical support representative.

L2ALD_BD_CREATE_RETRY_SUCCESS

System Log Message	BD <i>bridge-domain</i> creation succeeded after <i>retry-count</i> retries.
Description	The Layer 2 address learning process (l2ald) successfully recovered from initial BD creation that failed. The initial failure could have been because of temporary resource exhaustion in kernel or due to over configuration. The retry mechanism has recovered successfully from that state
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	Contact your technical support representative.

L2ALD_BD_NAME_RESTRICTION

System Log Message	Reserved character '/' is not allowed as part of bridge-domain(<i>bridge-domain</i>) name. Any firewall filter applied to this bridge-domain might fail to work.
Description	firewall filter will not work for restricted BD name
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	Contact your technical support representative.

L2ALD_DEFAULT_VLAN_DISABLED

System Log Message	Internal vlan " <i>bridge-domain/default</i> " creation failed.!!
Description	Default vlan feature has been disabled due to an existing vlan configuration with vlan-id 1.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	explicit configuration of vlan by name default or removal of the vlan configured with vlan-id 1.

L2ALD_DUPLICATE_RBEB_MAC

System Log Message	Duplicate RBEB mac has been detected (<i>mac-address</i>). LE already exists with pbbn_id : <i>pbbn-id</i> . Rejecting LE create with pbbn_id : <i>new-pbbn-id</i>
Description	The l2 learning process (l2ald) already has this particular BEB mac existing for a different PBBN ID.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

L2ALD_FREE_MAC_FAILED

System Log Message	ERROR: <i>error-message</i>
Description	Before a MAC address is freed from system, it is removed from all lists and the kernel. Due to unexpected events, a mac about to be freed is found to be still in a list
Type	Error: An error occurred

Severity	warning
Facility	LOG_DAEMON
Cause	Unexpected sequence of events or loops in the topology or some kind of misconfiguration.

L2ALD_GENCFG_OP_FAILED

System Log Message	Unable to complete gencfg operation <i>operation</i> (major <i>type</i> , minor <i>subtype</i>): <i>error-message</i>
Description	The Layer 2 address learning process (l2ald) could not send Layer 2 forwarding-related information to the Packet Forwarding Engines, because the indicated operation failed during configuration generation.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

L2ALD_IFBD_COUNT_EXCEED

System Log Message	<i>warning-message</i> ; current count is <i>count</i>
Description	When max number of ifbd / vmmember supported exceed due to user configuration, warning message will be generated.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

L2ALD_IPC_MESSAGE_ERROR

System Log Message	Message (type <i>message-type</i> , subtype <i>message-subtype</i> , opcode <i>message-opcode</i>) received with error <i>error-message</i>
Description	The Layer 2 address learning process (l2ald) detected an error in an interprocess communication (IPC) message with the indicated characteristics.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

L2ALD_IPC_MESSAGE_INVALID

System Log Message	Invalid message received (message type <i>message</i> , subtype <i>message-type</i>): <i>message-subtype</i>
---------------------------	---

Description	The Layer 2 address learning process (l2ald) received a message with the indicated characteristics. The message was invalid for the indicated reason.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

L2ALD_IPC_MESSAGE_SEND_FAILED

System Log Message	Unable to send IPC message to <i>peer-name identifier</i>
Description	The Layer 2 address learning process (l2ald) could not send an interprocess communication (IPC) message to the indicated Layer 2 peer.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	Contact your technical support representative.

L2ALD_IPC_PIPE_WRITE_ERROR

System Log Message	Unable to write on pipe: <i>error-message</i>
Description	The Layer 2 address learning process (l2ald) could not write to an interprocess communication (IPC) pipe for the indicated reason.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	One possible reason is that there was no reader for the pipe.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18934 .

L2ALD_MAC_LIMIT_EXCEEDED_BD

System Log Message	Limit on learned MAC addresses exceeded for routing instance ' <i>routing-instance</i> ', domain ' <i>bridge-domain:vlan-id</i> '; mac-limit is <i>count mac-address</i> THE PACKET with mac-address of <i>drop-packet</i>
Description	The Layer 2 address learning process (l2ald) stopped adding addresses to the MAC address table that were learned by interfaces in the indicated bridge-domain, because the indicated count of learned addresses exceeds the limit configured or default limit for the bridge-domain.

Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Action	Increase the limit on addresses learned by interfaces in the bridge-domain, by increasing the value of the 'mac-table-size' statement at the [edit vlans <vlan-name> switch-options] hierarchy level.

L2ALD_MAC_LIMIT_EXCEEDED_BLOCK

System Log Message	Limit on learned MAC addresses exceeded for <i>interface-name</i> ; current count is <i>count</i> SHUTTING THE INTERFACE
Description	The Layer 2 address learning process (l2ald) blocked the indicated interface, because the indicated count of learned addresses exceeds the limit configured for the interface.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Action	Increase the limit on addresses learned by the interface by increasing the value of the 'interface-mac-limit' statement at the appropriate location under the [edit routing-instances <routing-instance-name> bridge-domains <bridge-domain-name> bridge-options] or the [edit routing-instances <routing-instance-name> protocols vpls] hierarchy level.

L2ALD_MAC_LIMIT_EXCEEDED_IF

System Log Message	Limit on learned MAC addresses exceeded for <i>interface-name</i> ; current count is <i>count</i> <i>mac-address</i> THE PACKET with mac address: <i>drop-packet</i>
Description	The Layer 2 address learning process (l2ald) stopped adding addresses to the MAC address table that were learned by the indicated interface, because the indicated count of learned addresses exceeds the limit configured for the interface.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Action	Increase the limit on addresses learned by the interface by increasing the value of the 'interface-mac-limit' statement at the appropriate location under the [edit routing-instances <routing-instance-name> bridge-domains <bridge-domain-name> bridge-options] or the [edit routing-instances <routing-instance-name> protocols vpls] hierarchy level.

L2ALD_MAC_LIMIT_EXCEEDED_IFBD

System Log Message	Limit on learned MAC addresses exceeded for <i>interface-name</i> ; current count is <i>count</i> <i>mac-address</i> THE PACKET with mac address: <i>drop-packet</i>
Description	The Layer 2 address learning process (l2ald) stopped adding addresses to the MAC address table that were learned by the indicated interface:vlan-id, because the indicated count of learned addresses exceeds the limit configured for the interface:vlan-id.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Action	Increase the limit on addresses learned by the interface by increasing the value of the 'interface-mac-limit' statement at the appropriate location under the [edit routing-instances <routing-instance-name> bridge-domains <bridge-domain-name> bridge-options] or the [edit routing-instances <routing-instance-name> protocols vpls] hierarchy level.

L2ALD_MAC_LIMIT_REACHED_BD

System Log Message	Limit on learned MAC addresses reached for routing instance ' <i>routing-instance</i> ', domain ' <i>bridge-domain:vlan-id</i> '; current count is <i>count</i>
Description	The Layer 2 address learning process (l2ald) stopped adding addresses to the MAC address table that were learned by interfaces in the indicated bridging domain, because the indicated count of learned addresses exceeds the configured or default limit for the bridge-domain.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Action	Increase the limit on addresses learned by interfaces in the bridge domain, by increasing the value of the 'interface-mac-limit' statement at the [edit routing-instances <routing-instance-name> bridge-domains <bridge-domain-name> bridge-options] hierarchy level.

L2ALD_MAC_LIMIT_REACHED_GLOBAL

System Log Message	Global limit on learned MAC addresses reached; current count is <i>count</i>
Description	The Layer 2 address learning process (l2ald) stopped adding addresses to the MAC address table, because the indicated count of learned addresses exceeds the limit for the router.
Type	Event: This message reports an event, not an error
Severity	warning

Facility LOG_DAEMON

Action Increase the limit on addresses learned by the interfaces on the router by increasing the value of the 'global-mac-limit' statement at the [edit protocols l2-learning] hierarchy level.

L2ALD_MAC_LIMIT_REACHED_IF

System Log Message Limit on learned MAC addresses reached for *interface-name*; current count is *count*

Description The Layer 2 address learning process (l2ald) stopped adding addresses to the MAC address table that were learned by the indicated interface, because the indicated count of learned addresses exceeds the limit configured for the interface.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

Action Increase the limit on addresses learned by the interface by increasing the value of the 'interface-mac-limit' statement at the appropriate location under the [edit routing-instances <routing-instance-name> bridge-domains <bridge-domain-name> bridge-options] or the [edit routing-instances <routing-instance-name> protocols vpls] hierarchy level.

L2ALD_MAC_LIMIT_REACHED_IFBD

System Log Message Limit on learned MAC addresses reached for *interface-name*; current count is *count*

Description The Layer 2 address learning process (l2ald) stopped adding addresses to the MAC address table that were learned by the indicated interface:vlan-id, because the indicated count of learned addresses exceeds the limit configured for the interface:vlan-id.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

Action Increase the limit on addresses learned by the interface by increasing the value of the 'interface-mac-limit' statement at the appropriate location under the [edit routing-instances <routing-instance-name> bridge-domains <bridge-domain-name> bridge-options] or the [edit routing-instances <routing-instance-name> protocols vpls] hierarchy level.

L2ALD_MAC_LIMIT_REACHED_RTT

System Log Message Limit on learned MAC addresses reached for routing instance '*routing-instance*'; current count is *count*

Description The Layer 2 address learning process (l2ald) stopped adding addresses to the MAC address table that were learned by interfaces in the indicated routing instance, because

the indicated count of learned addresses exceeds the configured or default limit for the routing instance.

Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Action	Increase the limit on addresses learned by interfaces in the routing-instance, by increasing the value of the 'interface-mac-limit' statement at the [edit routing-instances <routing-instance-name> protocol l2-learning] or the [edit routing-instances <routing-instance-name> protocols vpls] hierarchy level.

L2ALD_MAC_LIMIT_RESET_BD

System Log Message	Resumed adding MAC addresses learned from routing instance ' <i>routing-instance</i> ', domain ' <i>bridge-domain:vlan-id</i> '; current count is <i>count</i>
Description	The Layer 2 address learning process (l2ald) resumed adding addresses to the MAC address table that were learned by interfaces in the indicated bridging domain, because the indicated count of learned addresses no longer exceeds the limit configured for the domain.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	The probable reason that the count of addresses went below the limit is that addresses in the table reached the age limit and were removed.

L2ALD_MAC_LIMIT_RESET_GLOBAL

System Log Message	Resumed adding MAC addresses for router; current count is <i>count</i>
Description	The Layer 2 address learning process (l2ald) resumed adding addresses to the MAC address table, because the indicated count of learned addresses no longer exceeds the configured limit.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	The probable reason that the count of addresses went below the limit is that addresses in the table reached the age limit and were removed.

L2ALD_MAC_LIMIT_RESET_IF

System Log Message	Resumed adding MAC addresses learned by <i>interface-name</i> ; current count is <i>count</i>
---------------------------	---

Description	The Layer 2 address learning process (l2ald) resumed adding addresses to the MAC address table that were learned by the indicated interface, because the indicated count of learned addresses no longer exceeds the limit configured for the interface.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	The probable reason that the count of addresses went below the limit is that addresses in the table reached the age limit and were removed.

L2ALD_MAC_LIMIT_RESET_RTT

System Log Message	Resumed adding MAC addresses learned from routing instance ' <i>routing-instance</i> '; current count is <i>count</i>
Description	The Layer 2 address learning process (l2ald) resumed adding addresses to the MAC address table that were learned by interfaces in the indicated bridging domain, because the indicated count of learned addresses no longer exceeds the limit configured for the instance.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	The probable reason that the count of addresses went below the limit is that addresses in the table reached the age limit and were removed.

L2ALD_MAC_MOVE_EXCEEDED_BD

System Log Message	Limit on MAC moves exceeded at VLAN <i>bridge-domain</i> for MAC <i>mac-address</i> moved from interface <i>interface-name</i> to interface <i>interface-name</i> ; Mac move limit is <i>count</i> . <i>drop-packet</i> THE PACKET
Description	When the same MAC address is learned on a different interface, or on the same interface but a different unit number, it is considered a MAC move. When this happens beyond the configured value, an error is sent
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Cause	The probable reason for mac moves is the loops in the topology or some kind of misconfiguration.

L2ALD_MAC_MOVE_EXCEEDED_BD_ACTION_NONE

System Log Message	Limit on MAC moves exceeded at VLAN <i>bridge-domain</i> for MAC <i>mac-address</i> moved from interface <i>interface-name</i> to interface <i>interface-name1</i> ; Mac move limit is <i>count</i> . No action (Forwarding the packet)
Description	When the same MAC address is learned on a different interface, or on the same interface but a different unit number, it is considered a MAC move. When this happens beyond the configured value, an error is sent
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Cause	The probable reason for mac moves is the loops in the topology or some kind of misconfiguration.

L2ALD_MAC_MOVE_NOTIFICATION

System Log Message	MAC Moves detected in the system
Description	When the same MAC address is learned on a different interface, or on the same interface but a different unit number, it is considered a MAC move. When this happens frequently for a specific time duration, a notification is sent
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	The probable reason for mac moves is the loops in the topology or some kind of misconfiguration.

L2ALD_MAC_MOVE_NOTIF_ACTION

System Log Message	MAC move <i>error-message</i>
Description	When the same MAC address is learned on a different interface, or on the same interface but a different unit number, it is considered a MAC move. When this happens frequently for a specific time duration, and bridge domain has action enabled, the IFL on which the mac is learnt last is blocked for the bridge domain. A notification is sent with blocking/unblocking event, Offending MAC (for blocking), IFL name and bridge domain.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON
Cause	The probable reason for mac moves is the loops in the topology or some kind of misconfiguration. The blocking action is taken to stop the loop for a configurable duration.

L2ALD_MAC_MOVE_NOTIF_EXTENSIVE

System Log Message	MAC move <i>error-message</i>
Description	When the same MAC address is learned on a different interface, or on the same interface but a different unit number, it is considered a MAC move. When this happens frequently for a specific time duration, a notification is sent with details on the interface, bridge-domain.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	The probable reason for mac moves is the loops in the topology or some kind of misconfiguration. This message is invoked based on the user configurable knob

L2ALD_MAC_MOVE_SHUTDOWN

System Log Message	Shutting down the interface <i>bridge-domain</i> . Detected excessive mac moves for MAC <i>mac-address</i> in vlan <i>interface-name</i> from interface <i>interface-name1</i> ;Mac move limit is <i>count</i> .
Description	When the same MAC address is learned on a different interface, or on the same interface but a different unit number, it is considered a MAC move. When this happens frequently for a specific time duration, a notification is sent with details on the interface, bridge-domain.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Cause	The probable reason for mac moves is the loops in the topology or some kind of misconfiguration.

L2ALD_MALLOC_FAILED

System Log Message	Unable to allocate memory: <i>error-message</i>
Description	The Layer 2 address learning process (l2ald) could not allocate memory while creating a data structure.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

L2ALD_MANAGER_CONNECT

System Log Message	Unable to create pipe to Layer 2 address-learning manager: <i>error-message</i>
Description	The Layer 2 address learning process (l2ald) could not open a pipe for interprocess communication (IPC) with a Layer 2 address-learning manager process.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

L2ALD_NAME_LENGTH_IF_DEVICE

System Log Message	Unable to add interface device <i>interface-name</i> ; name exceeds limit of <i>length</i> characters
Description	The Layer 2 address learning process (l2ald) did not add an entry for the indicated interface device to the interface table, because its name exceeds the indicated limit on the number of characters.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

L2ALD_NAME_LENGTH_IF_FAMILY

System Log Message	Unable to add interface family <i>interface-family</i> ; name exceeds limit of <i>length</i> characters
Description	The Layer 2 address learning process (l2ald) did not add an entry for the indicated interface family to the interface table, because its name exceeds the indicated limit on the number of characters.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

L2ALD_NAME_LENGTH_IF_LOGICAL

System Log Message	Unable to add logical interface <i>interface-name</i> ; name exceeds limit of <i>length</i> characters
Description	The Layer 2 address learning process (l2ald) did not add an entry for the indicated logical interface to the interface table, because its name exceeds the indicated limit on the number of characters.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

L2ALD_PBBN_IFL_REVA

System Log Message Unable to initialize Provider Backbone Bridging on interface *interface-name*. It is present on a Rev A card.

Description The Layer 2 address learning process (l2ald) could not initialize the interface for the provider backbone bridging (PBB) feature because the interface was on a revision A card.

Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Cause	Revision A cards do not support provider backbone bridging (PBB) features.
Action	Contact your technical support representative.

L2ALD_PBBN_REINSTATE_IFBDS

System Log Message Hardware VCs are being restored for data packet.They were de-programmed because *interface-name* had an interface on a Rev A card.

Description The Layer 2 address learning process (l2ald) reinstated certain hardware circuits to resume data traffic. The circuits were brought down because the provider backbone bridging (PBB) feature had discovered that one of the interfaces was on a revision A card.

Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Cause	The interface is no longer present on the revision A card.
Action	Contact your technical support representative.

L2ALD_PBBN_RETRACT_IFBDS

System Log Message Provider Backbone Bridging feature detected on interface *interface-name* on a Rev A card. VCs are being de-programmed.

Description The Layer 2 address learning process (l2ald) retracted certain hardware circuits to block data traffic. The circuits were brought down because the provider backbone bridging (PBB) feature had discovered that one of the interfaces was on a revision A card.

Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Cause	An interface was discovered on the revision A card. Revision A cards do not support provider backbone bridging (PBB) features.
Action	Contact your technical support representative.

L2ALD_PIP_IFD_READ_RETRY

System Log Message	Retry count exceeded trying to read <i>pip-interface</i> from the kernel. Retry count is <i>retry-count</i>
Description	The Layer 2 address learning process (l2ald) could not read the provide-in-provider interface (pip0) interface from the kernel.
Type	Error: An error occurred
Severity	critical
Facility	LOG_DAEMON
Cause	The chassis process may have been too slow in creating the interface.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18935 .

L2ALD_RPD_LR_ALLOC_FAILED

System Log Message	Unable to allocate context data for rpd connection
Description	The Layer 2 Address learning Protocol process (l2ald) could not allocate a memory for context information while attempting to initialize a connection to the routing protocol process (rpd).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

L2ALD_RPD_SESS_CREATE_FAILED

System Log Message	Unable to establish session with rpd (<i>error-code</i>)
Description	The Layer 2 Address learning Protocol process (l2ald) could not establish a session with the routing protocol process (rpd).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

L2ALD_RPD_SESS_HANDLE_ALLOC_FAIL

System Log Message	Unable to allocate session handle for rpd connection: <i>error-message (error-code)</i>
Description	The Layer 2 Address learning Protocol process (l2ald) could not allocate a session handle while attempting to initialize a connection to the routing protocol process (rpd).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

L2ALD_RPD_SOCKET_ALLOC_FAILED

System Log Message	Unable to allocate socket address for rpd connection
Description	The Layer 2 Address learning Protocol process (l2ald) could not allocate a socket address structure while attempting to initialize a connection to the routing protocol process (rpd).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

L2ALD_RPD_STATE_ALLOC_FAILED

System Log Message	Unable to allocate l2ald rpd state
Description	The Layer 2 Address learning Protocol process (l2ald) could not allocate a memory for l2ald rpd state information while attempting to initialize a connection to the routing protocol process (rpd).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

L2ALD_RPD_VERSION_MISMATCH

System Log Message	Versions of rpd and librpd did not match; not retrying
Description	The Layer 2 Address learning Protocol process (l2ald) determined that the versions of the routing protocol process (rpd) and. routing protocol library (librpd) were different. It halted its attempt to connect to the rpd process.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

L2ALD_ST_CTL_DISABLED

System Log Message	<i>interface-name</i> : storm control disabled port
---------------------------	---

Description This condition occurs when storm control condition is detected.

Type Event: This message reports an event, not an error

Severity alert

Facility LOG_DAEMON

L2ALD_ST_CTL_ENABLED

System Log Message *interface-name*: storm control enabled port

Description This condition occurs when storm-control condition is cleared.

Type Event: This message reports an event, not an error

Severity alert

Facility LOG_DAEMON

L2ALD_ST_CTL_IN_EFFECT

System Log Message *interface-name*: storm control in effect on the port

Description This condition occurs when storm control condition is detected.

Type Event: This message reports an event, not an error

Severity alert

Facility LOG_DAEMON

CHAPTER 64

L2CPD System Log Messages

This chapter describes messages with the **L2CPD** prefix. They are generated by the Layer 2 Control Protocol process (l2cpd), which supports the transmission of control messages for Layer 2 spanning tree protocols in a Layer 2 bridge environment.

L2CPD_KERNEL_VERSION

System Log Message	Kernel version (<i>kernel-version</i>) of routing sockets was not required version (<i>l2cpd-version</i>)
Description	The Layer 2 Control Protocol process (l2cpd) determined that the indicated version of routing sockets, which the kernel supports, is not the version that it requires.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Upgrade the kernel package.

L2CPD_KERNEL_VERSION_OLD

System Log Message	Kernel version (<i>kernel-version</i>) of routing socket message type <i>message-type</i> is older than the required version (<i>l2cpd-version</i>)
Description	The Layer 2 Control Protocol process (l2cpd) determined that the kernel supports an indicated older version of the indicated routing socket message type than it requires.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Upgrade the kernel package.

L2CPD_KERNEL_VERSION_UNSUPP

System Log Message	Kernel version of routing socket message type ' <i>message-type</i> ' was not required version (<i>l2cpd-version</i>)
Description	The Layer 2 Control Protocol process (l2cpd) determined that the kernel does not support the version of the indicated routing socket message type that it requires.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Upgrade the kernel package.

L2CPD_MIRROR_ERROR

System Log Message Unable to establish mirror connection between Routing Engines: *error-message*

Description The Layer 2 Control Protocol process (l2cpd) could not establish the mirror connection (which supports nonstop routing) between the master and backup Routing Engines.

Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Cause	The master and backup Routing Engines are running incompatible versions of the JUNOS software.
Action	Update the JUNOS software to compatible versions on the master and backup Routing Engines.

L2CPD_MIRROR_VERSION_MISMATCH

System Log Message Versions of mirror software on Routing Engines are incompatible: *error-message*

Description While trying to establish the mirror connection (which supports nonstop routing) between the master and backup Routing Engines, the Layer 2 Control Protocol process (l2cpd) determined that the versions of JUNOS software on the Routing Engines were incompatible.

Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	Update the JUNOS software to compatible versions on the master and backup Routing Engines.

L2CPD_PPM_READ_ERROR

System Log Message Read error on pipe from ppmd: *reason (error-message)*

Description The Layer 2 Control Protocol process (l2cpd) could not read a message available on the read pipe from the periodic packet management process (ppmd).

Type	Error: An error occurred
Severity	error

Facility LOG_DAEMON
Action Contact your technical support representative.

L2CPD_PPM_WRITE_ERROR

System Log Message *function-name: write error on pipe to ppm (error-message)*

Description The Layer 2 Control Protocol process (l2cpd) could not write a message on the pipe to the periodic packet management process (ppmd).

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative. For more information, see KB18939.

L2CPD_XSTP_SHUTDOWN_FAILED

System Log Message Unable to shut down *error-message* module

Description The Layer 2 Control Protocol process (l2cpd) could not shut down the indicated Rapid Spanning Tree Protocol (RSTP) or Multiple Spanning Tree Protocol (MSTP) module.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

CHAPTER 65

L2TPD System Log Messages

This chapter describes messages with the **L2TPD** prefix. They are generated by the Layer 2 Tunneling Protocol (L2TP) process (l2tpd), which provides services that enable tunneling of Point-to-Point Protocol (PPP) sessions across a Layer 3 IP network.

L2TPD_COS_PROFILE_ADD

System Log Message	Unable to add CoS profile <i>profile-name</i> (L2TP tunnel <i>tunnel-id</i> , session <i>session-id</i>): <i>error-message</i>
Description	The Layer 2 Tunneling Protocol process (l2tpd) could not add the indicated class-of-service (CoS) profile to the indicated session on the indicated tunnel, which is associated with a user.
Type	Error: An error occurred
Severity	error
Facility	LOG_NEWS
Action	Remove the CoS profile from the RADIUS database or contact your technical support representative.

L2TPD_COS_PROFILE_DELETE

System Log Message	Unable to delete CoS profile (L2TP tunnel <i>tunnel-id</i> , session <i>session-id</i>): <i>error-message</i>
Description	The Layer 2 Tunneling Protocol process (l2tpd) could not delete a class-of-service (CoS) profile from the indicated session on the indicated tunnel, which is associated with a user.
Type	Error: An error occurred
Severity	error
Facility	LOG_NEWS
Action	Remove the CoS profile from the RADIUS database or contact your technical support representative.

L2TPD_DB_ADD_FAILED

System Log Message	Unable to add node for <i>node-name</i> to internal database
Description	The Layer 2 Tunneling Protocol process (l2tpd) maintains a copy of the Junos configuration database in memory. It could not add the indicated node to the in-memory database.
Type	Error: An error occurred
Severity	error
Facility	LOG_NEWS

L2TPD_DB_DELETE_FAILED

System Log Message	Unable to delete node for <i>node-name</i> from internal database
Description	The Layer 2 Tunneling Protocol process (l2tpd) maintains a copy of the Junos configuration database in memory. It could not delete the indicated node to the in-memory database.
Type	Error: An error occurred
Severity	error
Facility	LOG_NEWS

L2TPD_DB_INIT_FAILED

System Log Message	Unable to initialize root node <i>object-name</i> in internal database: <i>error-message</i>
Description	The Layer 2 Tunneling Protocol process (l2tpd) maintains a copy of the Junos configuration database in memory. It could not initialize the root node for the indicated object in the in-memory database.
Type	Error: An error occurred
Severity	error
Facility	LOG_NEWS

L2TPD_DB_TUN_GRP_ALLOC_FAILED

System Log Message	Unable to allocate memory for tunnel group
Description	The Layer 2 Tunneling Protocol process (l2tpd) could not allocate memory for the data structure used to record tunnel group information.
Type	Error: An error occurred
Severity	error
Facility	LOG_NEWS

L2TPD_DEFAULT_PROTO_CREATE_FAIL

System Log Message	Unable to create default L2TP module
Description	The Layer 2 Tunneling Protocol process (l2tpd) could not create a default L2TP module.
Type	Error: An error occurred
Severity	error
Facility	LOG_NEWS

L2TPD_EVLIB_CREATE_FAILED

System Log Message	Unable to create event context: <i>error-message</i>
Description	The Layer 2 Tunneling Protocol process (l2tpd) could not create a context for handling asynchronous events.
Type	Error: An error occurred
Severity	emergency
Facility	LOG_NEWS

L2TPD_EVLIB_FD_DEREGISTER_FAILED

System Log Message	Unable to deregister file descriptor: not registered
Description	The Layer 2 Tunneling Protocol process (l2tpd) could not deregister a file descriptor, because it did not exist.
Type	Error: An error occurred
Severity	error
Facility	LOG_NEWS

L2TPD_EVLIB_FD_DESELECT_FAILED

System Log Message	Unable to deselect file descriptor: <i>error-message</i>
Description	The Layer 2 Tunneling Protocol process (l2tpd) could not deselect a file descriptor.
Type	Error: An error occurred
Severity	error
Facility	LOG_NEWS

L2TPD_EVLIB_FD_NOT_REGISTERED

System Log Message	No file descriptor registered
Description	The Layer 2 Tunneling Protocol process (l2tpd) could not find a registered file descriptor while attempting to set an event mask.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_EVLIB_FD_SELECT_FAILED

System Log Message Unable to select file descriptor for events *event-id: error-message*
Description The Layer 2 Tunneling Protocol process (l2tpd) could not select the file descriptor for the indicated events.
Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_EVLIB_TIMER_CLEAR_FAILED

System Log Message Unable to clear event timer: *error-message*
Description The Layer 2 Tunneling Protocol process (l2tpd) could not clear an event timer for the indicated reason.
Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_EVLIB_TIMER_SET_FAILED

System Log Message Unable to set event timer: *error-message*
Description The Layer 2 Tunneling Protocol process (l2tpd) could not set an event timer for the indicated reason.
Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_FILTER_FILE_OPEN_FAILED

System Log Message Unable to open file *filename*
Description The Layer 2 Tunneling Protocol process (l2tpd) could not open the indicated filter file.
Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_GLOBAL_CFG_ADD_FAILED

System Log Message	Unable to add global configuration for PIC <i>pic-slot</i> (errno <i>error-code</i>)
Description	The Layer 2 Tunneling Protocol process (l2tpd) could not add the global configuration for the indicated PIC.
Type	Error: An error occurred
Severity	error
Facility	LOG_NEWS

L2TPD_GLOBAL_CFG_CHANGE_FAILED

System Log Message	Unable to change global configuration for PIC <i>pic-slot</i> (errno <i>error-code</i>)
Description	The Layer 2 Tunneling Protocol process (l2tpd) could not change the global configuration for the indicated PIC.
Type	Error: An error occurred
Severity	error
Facility	LOG_NEWS

L2TPD_GLOBAL_CFG_DELETE_FAILED

System Log Message	Unable to delete global configuration for PIC <i>pic-slot</i> (errno <i>error-code</i>)
Description	The Layer 2 Tunneling Protocol process (l2tpd) could not delete the global configuration for the indicated PIC.
Type	Error: An error occurred
Severity	error
Facility	LOG_NEWS

L2TPD_IFD_ADD_FAILED

System Log Message	<i>function-name</i> : unable to add interface device <i>interface-name</i>
Description	The Layer 2 Tunneling Protocol process (l2tpd) maintains a copy of the Junos configuration database in memory. It could not add the indicated interface device to the in-memory database.
Type	Error: An error occurred
Severity	error
Facility	LOG_NEWS

L2TPD_IFD_DELETE_FAILED

System Log Message	<i>function-name</i> : unable to delete interface device <i>interface-name</i>
---------------------------	--

Description The Layer 2 Tunneling Protocol process (l2tpd) maintains a copy of the Junos configuration database in memory. It could not delete the indicated interface device from the in-memory database.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_IFD_MSG_REGISTER_FAILED

System Log Message Unable to register message handler for interface device: *error-message*

Description The Layer 2 Tunneling Protocol process (l2tpd) could not register an interface device message handler.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_IFD_ROOT_ALLOC_FAILED

System Log Message Unable to allocate memory for interface device root node: *error-message*

Description The Layer 2 Tunneling Protocol process (l2tpd) maintains a copy of the Junos configuration database in memory. It could not allocate memory in the in-memory database for the root node for an interface device.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_IFL_ADD_FAILED

System Log Message *function-name*: unable to add interface *interface-name*

Description The Layer 2 Tunneling Protocol process (l2tpd) maintains a copy of the Junos configuration database in memory. It could not add the indicated logical interface to the in-memory database.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_IFL_DELETE_FAILED

System Log Message *function-name*: unable to delete interface *interface-name*

Description The Layer 2 Tunneling Protocol process (l2tpd) maintains a copy of the Junos configuration database in memory. It could not delete the indicated logical interface from the in-memory database.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_IFL_MSG_REGISTER_FAILED

System Log Message Unable to register message handler for interface: *error-message*

Description The Layer 2 Tunneling Protocol process (l2tpd) could not register a logical interface message handler.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_IFL_NOT_FOUND

System Log Message Unable to find logical interface (L2TP tunnel *tunnel-id*, session *session-id*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not retrieve a logical interface in the indicated tunnel and session.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_IFL_ROOT_ALLOC_FAILED

System Log Message Unable to allocate memory for interface root node: *error-message*

Description The Layer 2 Tunneling Protocol process (l2tpd) maintains a copy of the Junos configuration database in memory. It could not allocate memory in the in-memory database for the root node for a logical interface.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_INSTANCE_CREATE_FAILED

System Log Message Unable to create L2TP instance *tunnel-group*

Description The Layer 2 Tunneling Protocol process (l2tpd) could not create an L2TP instance for the indicated tunnel group.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_INSTANCE_RESTART_FAILED

System Log Message Unable to trigger restart of L2TP instance *tunnel-group*
Description The Layer 2 Tunneling Protocol process (l2tpd) could not restart the L2TP instance for the indicated tunnel group.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_INTERFACE_ID_NOT_FOUND

System Log Message Unable to find interface ID *interface-name*
Description The Layer 2 Tunneling Protocol process (l2tpd) could not find the indicated interface ID in the copy of the Junos configuration database that it maintains in memory.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_MESSAGE_REGISTER_FAILED

System Log Message Unable to register L2TP message handler: *error-message*
Description The Layer 2 Tunneling Protocol process (l2tpd) could not register an L2TP message handler.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_MLPPP_BUNDLE_ALLOC_FAILED

System Log Message Unable to allocate MLPPP bundle
Description The Layer 2 Tunneling Protocol process (l2tpd) could not allocate memory for a multilink Point-to-Point Protocol (MLPPP) bundle.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_MLPPP_BUNDLE_CREATE_FAILED

System Log Message	Unable to create MLPPP bundle (L2TP tunnel <i>tunnel-id</i> , session <i>session-id</i>)
Description	The Layer 2 Tunneling Protocol process (l2tpd) could not create a multilink Point-to-Point Protocol (MLPPP) bundle in the indicated tunnel and session.
Type	Error: An error occurred
Severity	error
Facility	LOG_NEWS

L2TPD_MLPPP_BUNDLE_INVALID_ID

System Log Message	MLPPP bundle ID was invalid
Description	The identifier assigned to a multilink Point-to-Point Protocol (MLPPP) bundle was invalid.
Type	Error: An error occurred
Severity	error
Facility	LOG_NEWS

L2TPD_MLPPP_COPY_CFG_FAILED

System Log Message	Unable to copy MLPPP configuration (L2TP tunnel <i>tunnel-id</i> , session <i>session-id</i>)
Description	The Layer 2 Tunneling Protocol process (l2tpd) could not copy the multilink Point-to-Point Protocol (MLPPP) configuration for the indicated tunnel and session.
Type	Error: An error occurred
Severity	error
Facility	LOG_NEWS

L2TPD_MLPPP_ID_ALLOC_FAILED

System Log Message	Unable to allocate MLPPP ID map
Description	The Layer 2 Tunneling Protocol process (l2tpd) could not allocate memory for a multilink Point-to-Point Protocol (MLPPP) identifier map data structure.
Type	Error: An error occurred
Severity	error
Facility	LOG_NEWS

L2TPD_MLPPP_ID_BITMAP_ALLOC_FAIL

System Log Message	Unable to allocate bitmap field for MLPPP ID map
Description	The Layer 2 Tunneling Protocol process (l2tpd) could not allocate memory for a bitmap field in a multilink Point-to-Point Protocol (MLPPP) identifier map data structure.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_MLPPP_ID_NODE_ADD_FAILED

System Log Message Unable to add node for bundle *bundle* to MLPPP ID map

Description The Layer 2 Tunneling Protocol process (l2tpd) could not add a node for the indicated multilink Point-to-Point Protocol (MLPPP) bundle to an MLPPP identifier map data structure.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_MLPPP_ID_ROOT_ALLOC_FAILED

System Log Message Unable to allocate root node for MLPPP ID map

Description The Layer 2 Tunneling Protocol process (l2tpd) could not allocate the root note for a multilink Point-to-Point Protocol (MLPPP) identifier map data structure.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_MLPPP_LINK_CREATE_FAILED

System Log Message Unable to create MLPPP bundle links (L2TP tunnel *tunnel-id*, session *session-id*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not create multilink Point-to-Point Protocol (MLPPP) bundle links for the indicated tunnel and session.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_MLPPP_LINK_MAX_EXCEEDED

System Log Message Unable to add link: maximum number of sessions exceeded for MLPPP bundle *bundle* (L2TP tunnel *tunnel-id*, session *session-id*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not add a link for the indicated multilink Point-to-Point Protocol (MLPPP) bundle in the indicated tunnel and session, because the maximum number of links was exceeded.

Type Error: An error occurred
Severity error

Facility LOG_NEWS

L2TPD_MLPPP_POOL_ADDRESS_FAILED

System Log Message Unable to assign pool address for MLPPP bundle *bundle* (L2TP tunnel *tunnel-id*, session *session-id*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not assign a pool address for the indicated multilink Point-to-Point Protocol (MLPPP) bundle in the indicated tunnel and session.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_MLPPP_SESSION_CREATE_FAIL

System Log Message Unable to create MLPPP session (L2TP tunnel *tunnel-id*, session *session-id*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not create a multilink Point-to-Point Protocol (MLPPP) session for the indicated tunnel and session.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_MLPPP_SESSION_DELETE_FAIL

System Log Message Unable to delete session for MLPPP bundle *bundle* (L2TP tunnel *tunnel-id*, session *session-id*, errno *error-code*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not delete the session configuration for the indicated multilink Point-to-Point Protocol (MLPPP) bundle in the indicated tunnel and session.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_MLPPP_SPEED_MISMATCH

System Log Message Unable to add link: speed differs for bundle *bundle* (L2TP tunnel *tunnel-id*, session *session-id*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not add a link for the indicated multilink Point-to-Point Protocol (MLPPP) bundle in the indicated tunnel and session, because the bundle speed does not match.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_NH_DELETE_FAILED

System Log Message Unable to delete next hop *next-hop*

Description The Layer 2 Tunneling Protocol process (l2tpd) could not delete the indicated next hop.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_POLICER_ADD_FAILED

System Log Message Unable to add policer *filter-name* (L2TP tunnel *tunnel-id*, session *session-id*): *error-message*

Description The Layer 2 Tunneling Protocol process (l2tpd) could not add the indicated policer to the indicated session on the indicated tunnel, which is associated with a user.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

Action Remove the policer from the RADIUS database or contact your technical support representative.

L2TPD_POLICER_PROFILE_DEL_FAILED

System Log Message Unable to delete policer profile (L2TP tunnel *tunnel-id*, session *session-id*): *error-message*

Description The Layer 2 Tunneling Protocol process (l2tpd) could not delete a policer profile from the indicated session on the indicated tunnel, which is associated with a user.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

Action Remove the policer profile from the RADIUS database or contact your technical support representative.

L2TPD_POOL_ADDRESS_FAILED

System Log Message Unable to assign pool address (L2TP tunnel *tunnel-id*, session *session-id*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not assign a pool address in the indicated tunnel and session.

Type Error: An error occurred

Severity error
Facility LOG_NEWS

L2TPD_POOL_ASSIGN_ADDRESS_FAILED

System Log Message Unable to assign L2TP pool address: pool *pool-name* is invalid or has no free addresses

Description The Layer 2 Tunneling Protocol process (l2tpd) could not assign an address from the indicated address pool, either because the pool was invalid or had no free addresses.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_PPP_ROUTE_ADD_FAILED

System Log Message Unable to add PPP peer route (L2TP tunnel *tunnel-id*, session *session-id*)

Description The Layer 2 Tunneling Protocol process (l2tpd) maintains a copy of the Junos configuration database in memory. It could not add information about a Point-to-Point Protocol (PPP) peer route to the in-memory configuration for the indicated tunnel and session.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_PPP_ROUTE_DELETE_FAILED

System Log Message Unable to remove PPP peer route (L2TP tunnel *tunnel-id*, session *session-id*)

Description The Layer 2 Tunneling Protocol process (l2tpd) maintains a copy of the Junos configuration database in memory. It could not delete information about a Point-to-Point Protocol (PPP) peer route from the in-memory configuration for the indicated tunnel and session.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_PROFILE_NOT_FOUND

System Log Message Profile *profile-name* not found

Description The Layer 2 Tunneling Protocol process (l2tpd) could not locate an access profile from the configuration in order to find radius servers to authenticate.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_PROFILE_NO_RADIUS_SERVERS

System Log Message Can't find radius servers for profile '*profile-name*

Description The Layer 2 Tunneling Protocol process (l2tpd) could not locate any radius servers for the configured access profile.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_RADIUS_ACCT_PORT_ZERO

System Log Message RADIUS server accounting port is zero

Description The Layer 2 Tunneling Protocol process (l2tpd) determined that the RADIUS server accounting port is zero, which is not a valid value.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_RADIUS_GETHOSTNAME_FAILED

System Log Message Unable to obtain hostname for outgoing RADIUS message: *error-message*

Description The Layer 2 Tunneling Protocol process (l2tpd) could not obtain a hostname for an outgoing RADIUS message.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_RADIUS_RT_INST_ENOENT

System Log Message Ignoring RADIUS server *radius-server*: routing instance *routing-instance* did not exist

Description The Layer 2 Tunneling Protocol process (l2tpd) did not use the indicated RADIUS server because the indicated routing instance specified for the server did not exist.

Type Error: An error occurred

Severity notice

Facility LOG_NEWS

L2TPD_RADIUS_RT_INST_NOT_FOUND

System Log Message Ignoring RADIUS server *radius-server*: unable to retrieve routing instance *routing-instance* (*error-message*)

Description The Layer 2 Tunneling Protocol process (l2tpd) did not use the indicated RADIUS server because it could not retrieve the indicated routing instance specified for the server.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_RADIUS_SERVER_NOT_FOUND

System Log Message Unable to find RADIUS server (tunnel *tunnel-id*, session *session-id*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not locate a RADIUS server during Point-to-Point Protocol (PPP) authentication of the indicated tunnel and session.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_RADIUS_SRC_ADDR_BIND_FAIL

System Log Message Ignoring RADIUS server *radius-server*: unable to bind to source address *source-address* (*error-message*)

Description The Layer 2 Tunneling Protocol process (l2tpd) did not use the indicated RADIUS server because it could not bind to the indicated source address.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_RADIUS_SRC_ADDR_ENOENT

System Log Message Ignoring RADIUS server *radius-server*: source address *source-address* did not exist

Description The Layer 2 Tunneling Protocol process (l2tpd) did not use the indicated RADIUS server because the indicated source address did not exist in the routing instance for the server.

Type Error: An error occurred

Severity notice

Facility LOG_NEWS

L2TPD_RPD_ASYNC_UNREG_FAILED

System Log Message Unable to unregister with rpd (*return-value*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not unregister asynchronously with the routing protocol process (rpd).

Type Error: An error occurred

Severity error
Facility LOG_NEWS

L2TPD_RPD_ROUTE_ADD_CB_FAILED

System Log Message Unable to add route *address/prefix-length* asynchronously (gateway *gateway-id* [*gateway-name*], L2TP tunnel *tunnel-id*, session *session-id*): *error-code*

Description The Layer 2 Tunneling Protocol process (l2tpd) could not add a route on an asynchronous callback for the indicated address and prefix, gateway, tunnel, and session.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_RPD_ROUTE_ADD_FAILED

System Log Message Unable to add route *address/prefix-length* (gateway *gateway-id* [*gateway-name*], L2TP tunnel *tunnel-id*, session *session-id*): *error-message* (*error-code*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not add a route for the indicated address and prefix, gateway, tunnel, and session.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_RPD_ROUTE_DELETE_CB_FAILED

System Log Message Unable to delete route *address/prefix-length* asynchronously (gateway *gateway-id* [*gateway-name*], L2TP tunnel *tunnel-id*, session *session-id*): *error-code*

Description The Layer 2 Tunneling Protocol process (l2tpd) could not delete a route on an asynchronous callback for the indicated address and prefix, gateway, tunnel, and session.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_RPD_ROUTE_DELETE_FAILED

System Log Message Unable to delete route *address/prefix-length* (gateway *gateway-id* [*gateway-name*], L2TP tunnel *tunnel-id*, session *session-id*): *error-message* (*error-code*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not delete a route for the indicated address and prefix, gateway, tunnel, and session.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_RPD_ROUTE_PREFIX_TOO_LONG

System Log Message Unable to add route *address/prefix-length*: prefix too long (L2TP tunnel *tunnel-id*, session *session-id*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not add a route for the indicated address and prefix, tunnel, and session.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_RPD_SESS_CREATE_FAILED

System Log Message Unable to establish session with rpd (*error-code*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not establish a session with the routing protocol process (rpd).

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_RPD_SESS_HANDLE_ALLOC_FAIL

System Log Message Unable to allocate session handle for rpd connection: *error-message* (*error-code*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not allocate a session handle while attempting to initialize a connection to the routing protocol process (rpd).

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_RPD_SOCKET_ALLOC_FAILED

System Log Message Unable to allocate socket address for rpd connection

Description The Layer 2 Tunneling Protocol process (l2tpd) could not allocate a socket address structure while attempting to initialize a connection to the routing protocol process (rpd).

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_RPD_TBL_LOCATE_BY_NAME

System Log Message Unable to locate rpd table by name: *error-message* (*error-code*)

Description The Layer 2 Tunneling Protocol process (l2tpd) attempted to retrieve a routing protocol process table by providing the table name. The attempt failed.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_RPD_TBL_LOCATE_FAILED

System Log Message Unable to locate table *table-name* for *identifier* (*return-value*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not retrieve the indicated routing protocol process table.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_RPD_VERSION_MISMATCH

System Log Message Versions of rpd and librpd did not match; not retrying

Description The Layer 2 Tunneling Protocol process (l2tpd) determined that the versions of the routing protocol process (rpd) and routing protocol library (librpd) were different. It halted its attempt to connect to the rpd process.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_RTSLIB_ASYNC_OPEN_FAILED

System Log Message Unable to open asynchronous routing socket connection

Description The Layer 2 Tunneling Protocol process (l2tpd) could not open a routing socket connection asynchronously. It uses the connection to communicate with the Junos operating system kernel.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_RTSLIB_OPEN_FAILED

System Log Message Unable to open routing socket connection

Description The Layer 2 Tunneling Protocol process (l2tpd) could not open a routing socket connection, which it uses to communicate with the Junos operating system kernel.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_SERVER_START_FAILED

System Log Message Startup of L2TP server failed
Description The Layer 2 Tunneling Protocol (L2TP) server did not start.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_SERVICE_NH_ADD_FAILED

System Log Message Unable to add service next hop (L2TP tunnel *tunnel-id*, session *session-id*): *error-message* (*error-code*)
Description The Layer 2 Tunneling Protocol process (l2tpd) maintains a copy of the Junos configuration database in memory. It could not add information about a service next hop to the in-memory configuration for the indicated tunnel and session.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_SERVICE_NH_DELETE_FAILED

System Log Message Unable to remove service next hop *next-hop* (VRF *vrf*, L2TP tunnel *tunnel-id*, session *session-id*)
Description The Layer 2 Tunneling Protocol process (l2tpd) maintains a copy of the Junos configuration database in memory. It could not remove information about the indicated service next hop from the in-memory configuration for the indicated tunnel and session.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_SESSION_CFG_ADD_ERROR

System Log Message Unable to add L2TP tunnel *tunnel-id*, session *session-id* to PIC configuration (*errno error-code*)
Description The Layer 2 Tunneling Protocol process (l2tpd) maintains a copy of the Junos configuration database in memory. It could not add information about the indicated session and tunnel to the in-memory configuration for the PIC.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_SESSION_CFG_ADD_FAILED

System Log Message Unable to add L2TP tunnel *tunnel-id*, session *session-id* to PIC configuration

Description The Layer 2 Tunneling Protocol process (l2tpd) maintains a copy of the Junos configuration database in memory. It could not add information about the indicated session and tunnel to the in-memory configuration for the PIC.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_SESSION_CFG_DELETE_FAILED

System Log Message Unable to remove L2TP tunnel *tunnel-id*, session *session-id* from PIC configuration

Description The Layer 2 Tunneling Protocol process (l2tpd) maintains a copy of the Junos configuration database in memory. It could not remove information about the indicated session and tunnel from the in-memory configuration for the PIC.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_SESSION_DELETE_FAILED

System Log Message Unable to delete session (L2TP tunnel *tunnel-id*, session *session-id*, *errno error-code*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not delete information about the indicated tunnel and session.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_SESSION_IFF_NOT_FOUND

System Log Message Unable to find family structure for interface *interface-name* (L2TP tunnel *tunnel-id*, session *session-id*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not retrieve the interface family structure for the indicated logical interface index in the indicated tunnel and session.

Type Error: An error occurred
Severity error

Facility LOG_NEWS

L2TPD_SESSION_IFL_ADD_FAILED

System Log Message *function-name*: unable to assign session *session-id* to interface *interface-name*

Description The Layer 2 Tunneling Protocol process (l2tpd) could not associate the indicated session with the indicated logical interface.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_SESSION_IFL_ALLOC_FAILED

System Log Message *function-name*: unable to allocate memory for session *session-id*, interface *interface-name*

Description The Layer 2 Tunneling Protocol process (l2tpd) could not allocate memory for the indicated session to be associated with the indicated logical interface.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_SESSION_IFL_CLI_TREE_ALLOC

System Log Message Unable to allocate memory for session tree for interface *interface-name*

Description The Layer 2 Tunneling Protocol process (l2tpd) maintains a copy of the Junos configuration database in memory. It could not allocate memory for a command-line interface (CLI)-specific session tree structure for the indicated logical interface.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_SESSION_IFL_DELETED

System Log Message *function-name*: interface *interface-name* is deleted

Description The Layer 2 Tunneling Protocol process (l2tpd) detected that the configuration information for the indicated logical interface was deleted for a session.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_SESSION_IFL_DELETE_FAILED

System Log Message *function-name*: unable to delete session *identifier* from interface *interface-name*

Description The Layer 2 Tunneling Protocol process (l2tpd) could not delete information about a session from the configuration information for a logical interface.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_SESSION_IFL_GET_FAILED

System Log Message *function-name*: unable to find interface *interface-name*

Description The Layer 2 Tunneling Protocol process (l2tpd) could not retrieve configuration information about the indicated logical interface, to which it was going to add session information.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_SESSION_IFL_NOT_EQUAL

System Log Message *function-name*: interface *interface-name* not equal

Description The Layer 2 Tunneling Protocol process (l2tpd) could not add a session for the indicated logical interface.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_SESSION_IFL_NOT_FOUND

System Log Message Unable to find interface *interface-name* (L2TP tunnel *tunnel-id*, session *session-id*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not find the indicated logical interface corresponding to the indicated tunnel and session.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_SESSION_IFL_OCCUPIED

System Log Message *function-name*: interface *interface-name* already has associated session (*value1/value2*)

Description The Layer 2 Tunneling Protocol process (l2tpd) determined that the indicated logical interface already had an associated session.

Type Error: An error occurred

Severity error
Facility LOG_NEWS

L2TPD_SESSION_IFL_REMOVE_FAILED

System Log Message Unable to remove L2TP tunnel *tunnel-id*, session *session-id* from logical interface (errno *error-code*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not remove information about the indicated tunnel and session from the record it maintains for a logical interface.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_SESSION_INVALID_PEER_IP

System Log Message Invalid peer address *peer-address* in IPCP UP (L2TP tunnel *tunnel-id*, session *session-id*); closing session

Description The Layer 2 Tunneling Protocol process (l2tpd) received an IP Control Protocol (IPCP) 'UP' message for the indicated tunnel and session that included the indicated IP address for a peer. The address was invalid, and the l2tpd process started closing down the session.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_SESSION_IP_DUPLICATE

System Log Message IP address *peer-address/prefix-length* (*vrf*) already used in other session (L2TP tunnel *tunnel-id*, session *session-id*); closing session

Description The Layer 2 Tunneling Protocol process (l2tpd) received an IP Control Protocol (IPCP) 'UP' message for the indicated tunnel and session that included the indicated IP address for a peer. The address was already used by another session, and the l2tpd process started closing down the session.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_SESSION_ROUTE_ADD_FAILED

System Log Message Unable to add PPP route (L2TP tunnel *tunnel-id*, session *session-id*, errno *error-code*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not add a Point-to-Point Protocol (PPP) route for the indicated tunnel and session.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_SESSION_RT_TBL_NOT_FOUND

System Log Message Unable to find route table *table-id* for interface *interface-name* (L2TP tunnel *tunnel-id*, session *session-id*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not retrieve the indicated routing table associated with the indicated logical interface in the indicated tunnel and session.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_SESSION_TUNNEL_ID_MISMATCH

System Log Message Tunnel ID *tunnel-id* in message does not match L2TP tunnel *l2tp-tunnel-id*, session *session-id*

Description The Layer 2 Tunneling Protocol process (l2tpd) received a message with the indicated tunnel identifier, which did not match the identifier stored for the indicated tunnel and session.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_SETSOCKOPT_FAILED

System Log Message setsockopt() failed *operation: error-message*

Description The Layer 2 Tunneling Protocol process (l2tpd) could not set socket options during the indicated operation.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_SET_ASYNC_CONTEXT

System Log Message Unable to set asynchronous context (errno *error-code*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not set asynchronous context for a routing socket connection, which it uses to communicate with the Junos operating system kernel.

Type Error: An error occurred

Severity error
Facility LOG_NEWS

L2TPD_SHOW_MULTILINK

System Log Message Detail level *level* is not supported by 'show services l2tp multilink' command

Description The 'show services l2tp multilink' command was issued with the indicated option to specify the amount of information to return, but the command does not support that option.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_SHOW_SESSION

System Log Message Detail level *level* is not supported by 'show services l2tp session' command

Description The 'show services l2tp session' command was issued with the indicated option to specify the amount of information to return, but the command does not support that option.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_SHOW_TUNNEL

System Log Message Detail level *level* is not supported by 'show services l2tp tunnel' command

Description The 'show services l2tp tunnel' command was issued with the indicated option to specify the amount of information to return, but the command does not support that option.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_SOCKET_FAILED

System Log Message socket() failed *operation: error-message*

Description The Layer 2 Tunneling Protocol process (l2tpd) could not open socket during the indicated operation.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_SUBUNIT_ROUTE_ALLOC_FAILED

System Log Message	Unable to allocate L2TP route (tunnel <i>tunnel-id</i> , session <i>session-id</i>)
Description	The Layer 2 Tunneling Protocol process (l2tpd) could not allocate a subunit route record for the indicated tunnel and session.
Type	Error: An error occurred
Severity	error
Facility	LOG_NEWS

L2TPD_TRACE_FILE_OPEN_FAILED

System Log Message	Unable to open trace file: <i>error-message</i>
Description	The Layer 2 Tunneling Protocol process (l2tpd) could not open its trace file.
Type	Error: An error occurred
Severity	error
Facility	LOG_NEWS

L2TPD_TUNNEL_CFG_ADD_FAILED

System Log Message	Unable to add L2TP tunnel <i>tunnel-id</i> to PIC configuration (errno <i>error-code</i>)
Description	The Layer 2 Tunneling Protocol process (l2tpd) maintains a copy of the Junos configuration database in memory. It could not add information about the indicated tunnel to the in-memory configuration for the PIC.
Type	Error: An error occurred
Severity	error
Facility	LOG_NEWS

L2TPD_TUNNEL_CFG_ADD_INV_ADDR

System Log Message	Unable to add L2TP tunnel <i>tunnel-id</i> to PIC configuration: address invalid
Description	The Layer 2 Tunneling Protocol process (l2tpd) maintains a copy of the Junos configuration database in memory. It could not add information about the indicated tunnel to the in-memory configuration for the PIC, because the local or remote address provided for the tunnel was invalid.
Type	Error: An error occurred
Severity	error
Facility	LOG_NEWS

L2TPD_TUNNEL_CFG_DELETE_FAILED

System Log Message	Unable to remove L2TP tunnel <i>tunnel-id</i> from PIC configuration
---------------------------	--

Description The Layer 2 Tunneling Protocol process (l2tpd) maintains a copy of the Junos configuration database in memory. It could not remove information about the indicated tunnel from the in-memory configuration for the PIC.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_TUNNEL_DELETE_FAILED

System Log Message Unable to delete L2TP tunnel *tunnel-id* (errno *error-code*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not delete information about the indicated tunnel.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_TUNNEL_DEST_IF_LOOKUP_FAIL

System Log Message Unable to find destination interface for L2TP tunnel *tunnel-id* remote address: *error-message*

Description The Layer 2 Tunneling Protocol process (l2tpd) tried to use route lookup to determine which local logical interface to use to reach the remote end of the indicated tunnel. The attempt failed.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_TUNNEL_GROUP_ADD_FAILED

System Log Message Unable to create L2TP tunnel group

Description The Layer 2 Tunneling Protocol process (l2tpd) could not create a tunnel group.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_TUNNEL_GROUP_CFG_ADD_FAIL

System Log Message Unable to add tunnel group *tunnel-group* (service set *service-set*) to configuration for PIC *pic-slot*: *error-message*

Description The Layer 2 Tunneling Protocol process (l2tpd) maintains a copy of the Junos configuration database in memory. It could not add information about the indicated tunnel group and service set to the in-memory configuration for the indicated PIC.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_TUNNEL_GROUP_CFG_DEL_FAIL

System Log Message Unable to delete tunnel group *tunnel-group* (service set *service-set*): *error-code*

Description The Layer 2 Tunneling Protocol process (l2tpd) could not delete information about the indicated tunnel group and service set.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_TUNNEL_GROUP_CREATE_FAILED

System Log Message Unable to create L2TP module for tunnel group *address*

Description The Layer 2 Tunneling Protocol process (l2tpd) could not create the indicated protocol tunnel group.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_TUNNEL_GROUP_DELETE_FAILED

System Log Message Unable to delete L2TP tunnel group *tunnel-group-id* (errno *error-code*)

Description The Layer 2 Tunneling Protocol process (l2tpd) could not delete information about the indicated tunnel group.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

L2TPD_TUNNEL_GROUP_IDX_MISMATCH

System Log Message Tunnel group index *index1* in message does not match index *index2* stored for L2TP tunnel *tunnel-id*

Description The Layer 2 Tunneling Protocol process (l2tpd) received a message with the indicated tunnel group index, which did not match the indicated group tunnel index stored for the indicated tunnel.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_TUNNEL_GROUP_RESTART_FAIL

System Log Message Unable to restart L2TP module for tunnel group
Description The Layer 2 Tunneling Protocol process (l2tpd) could not restart a protocol tunnel group.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_USER_AUTHN_NOT_FOUND

System Log Message Unable to find user profile *username* during PPP authentication
Description The Layer 2 Tunneling Protocol process (l2tpd) could not retrieve the user profile for the indicated username, which it needs for Point-to-Point Protocol (PPP) authentication of a session.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_USER_AUTHN_ORDER_UNKNOWN

System Log Message Unknown authentication order *authentication-order* (tunnel *tunnel-id*, session *session-id*)
Description The Layer 2 Tunneling Protocol process (l2tpd) did not recognize the indicated authentication order, which was specified for Point-to-Point (PPP) authentication of the indicated tunnel and session.

Type Error: An error occurred
Severity error
Facility LOG_NEWS

L2TPD_USER_AUTHN_PWD_NOT_FOUND

System Log Message Unable to retrieve password during PPP authentication of user *username*
Description The Layer 2 Tunneling Protocol process (l2tpd) could not retrieve the password for the indicated username, which it needs for Point-to-Point Protocol (PPP) authentication of a session.

Type Error: An error occurred
Severity error

Facility LOG_NEWS

CHAPTER 66

LACP System Log Messages

This chapter describes messages with the **LACP** prefix. The Link Aggregation Control Protocol (LACP) provides a method to control the bundling of several physical ports together to form a single logical channel. LACP allows a network device to negotiate an automatic bundling of links by sending LACP packets to the peer (directly connected device that also implements LACP).

LACP_INTF_DOWN

System Log Message	<i>interface-name</i> : Interface marked down due to lacp timeout on member <i>child-interface-name</i>
Description	The Link Aggregation Control Protocol process (lacpd) experienced timeout hence interface marked down.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

CHAPTER 67

LACPD System Log Messages

This chapter describes messages with the **LACPD** prefix. They are generated by the Link Aggregation Control Protocol (LACPD) process (lacpd), which supports LACP functions for aggregated Ethernet interfaces.

LACPD_ISSU_ACK_TIMEOUT

System Log Message	<i>error-message</i> : Peer port did not move to long timeout for ISSU
Description	The Link Aggregation Control Protocol process (lacpd) sends a request during ISSU to peer to move to Long Timeout. As per the information received in the PDU peer did not move to Long Timeout.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

LACPD_MEMORY_ALLOCATION_FAILED

System Log Message	Unable to allocate memory for interface <i>interface-name</i>
Description	The Link Aggregation Control Protocol process (lacpd) could not allocate memory for the indicated interface.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

LACPD_TIMEOUT

System Log Message	<i>error-message</i> : lacp current while timer expired current Receive State: CURRENT
Description	The Link Aggregation Control Protocol process (lacpd) experienced timeout hence Receive State will change from Current to Expired/Defaulted.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

CHAPTER 68

LFMD System Log Messages

This chapter describes messages with the **LFMD** prefix. They are generated by the link-fault management process (lfmd), which supports Operation, Administration, and Maintenance (OAM) functions that are defined in the Institute of Electrical and Electronics Engineers (IEEE) 802.3ah standard for Ethernet interfaces.

LFMD_3AH_LINKDOWN

System Log Message	<i>(interface-name)</i> : 802.3ah link-fault status changed to fault with reason <i>reason</i>
Description	802.3ah link-fault status for given interface has changed to fault
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

LFMD_3AH_LINKUP

System Log Message	<i>(interface-name)</i> : 802.3ah link-fault status changed to good
Description	802.3ah link-fault status for given interface has changed to good
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

LFMD_3AH_LOCAL_LB_CHANGED

System Log Message	<i>(interface-name)</i> : <i>action</i> remote-loopback on local port on peer's request
Description	802.3ah local loopback status changed on given interface on peer request
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

LFMD_3AH_LT_LOOP_CLEARED

System Log Message	<i>(interface-name)</i> : 802.3ah loop tracking marked interface up for reason " <i>reason</i> "
---------------------------	--

Description 802.3ah loop tracking marked given interface up for specified reason

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

LFMD_3AH_LT_LOOP_DETECTED

System Log Message (*interface-name*): 802.3ah loop tracking detected loop. Marking interface down.

Description 802.3ah loop tracking detected loop on given interface and marked interface down

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

LFMD_3AH_REQ_REMOTE_LB_CHANGE

System Log Message (*interface-name*): requesting remote-loopback *action* to peer

Description 802.3ah requested peer loopback status change on given interface

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

LFMD_RTsock_OPEN_FAILED

System Log Message Unable to open synchronous routing socket: *error-message*

Description The Ethernet Operation, Administration and Management link-fault management process (lfmd) could not open a routing socket to create a connection.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

CHAPTER 69

LIBJNX System Log Messages

This chapter describes messages with the **LIBJNX** prefix. They are generated by processes that call routines in the libjuniper library, which includes routines for creating and managing child processes, parsing machine and interface addresses, tracing, file I/O, and other functions.

LIBJNX_AUDIT_ERROR

System Log Message	<i>function-name: error-message</i>
Description	A Junos process could not notify the audit process (auditd) about user activity related to system accounting, because of an interprocess communication (IPC) error.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	Any of the following reasons: auditd was not running auditd was still initializing after a restart there was a socket error.
Action	Contact your technical support representative.

LIBJNX_AUDIT_TACPLUS_ERROR

System Log Message	<i>function-name: message error-message</i>
Description	A Junos process could not notify the audit process (auditd) about user activity related to system accounting, because of an interprocess communication (IPC) error.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	Any of the following reasons: failure in writing tacacs+ accounting data to auditd failure in auditd shared memory operations
Action	Contact your technical support representative.

LIBJNX_COMPRESS_EXEC_FAILED

System Log Message	Unable to compress file ' <i>filename</i> ' using <i>program-name</i> : <i>error-message</i>
Description	A Junos process tried to use the indicated utility to create a compressed version of the indicated old system log file. The attempt failed for the indicated reason.
Type	Error: An error occurred
Severity	info
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

LIBJNX_DEFAULT_IP_ADDR_NOT_SET

System Log Message	Unable to retrieve system default IP address: not set in kernel (<i>error-message</i>)
Description	A Junos process could not retrieve the system default IP address from the kernel, because the address is not defined there.
Type	Error: An error occurred
Severity	critical
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18948 .

LIBJNX_EVLIB_FAILURE

System Log Message	<i>function-name</i> : <i>error-message</i>
Description	A Junos process called the indicated function in the event library. The function failed for the indicated reason.
Type	Error: An error occurred
Severity	emergency
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18949 .

LIBJNX_EXEC_EXITED

System Log Message	Command stopped: PID <i>pid</i> , signal= <i>'return-value'</i> <i>core-dump-status</i> , command <i>'command'</i>
Description	A Junos process created a child process to execute the indicated command for it. The child process stopped unexpectedly.
Type	Error: An error occurred
Severity	notice
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

LIBJNX_EXEC_FAILED

System Log Message	Child exec failed for command <i>'command'</i> : <i>error-message</i>
Description	A Junos process called the <code>exec()</code> system call while creating a child process to execute the indicated command for it. The system call failed.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

LIBJNX_EXEC_PIPE

System Log Message	Unable to create pipes for command <i>'command'</i> : <i>error-message</i>
Description	A Junos process created a child process to execute the indicated command for it. Its attempt to create pipes for communication with the child failed.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

LIBJNX_EXEC_SIGNED

System Log Message	Command received signal: PID <i>pid</i> , signal <i>signal-name</i> core-dump-status, command ' <i>command</i> '
Description	A Junos process created a child process to execute the indicated command for it. The child process received the indicated signal and exited.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18950 .

LIBJNX_EXEC_WEXIT

System Log Message	Command exited: PID <i>pid</i> , status <i>return-value</i> core-dump-status, command ' <i>command</i> '
Description	A Junos process created a child process to execute the indicated command for it. The child process exited abnormally with the indicated exit code.
Type	Error: An error occurred
Severity	notice
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative. For more information, see KB18950.

LIBJNX_FILE_COPY_FAILED

System Log Message	Failed to copy from <i>source-filename</i> to <i>destination-filename</i>
Description	A Junos process could not copy the indicated source file to the indicated destination name or location.
Type	Error: An error occurred
Severity	error
Facility	ANY

LIBJNX_FILE_SYSTEM_FAIL

System Log Message	<i>pathname</i> : <i>error-message</i>
Description	A Junos process could not obtain status information for the indicated file system.

Type	Event: This message reports an event, not an error
Severity	error
Facility	ANY

LIBJNX_FILE_SYSTEM_SPACE

System Log Message	Not enough space left on device <i>pathname</i>
Description	A Junos process found that the indicated file system did not have the free space needed for storing temporary files.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	ANY

LIBJNX_INVALID_XML_DATA

System Log Message	Invalid XML data '\data'
Description	The XML parser closed its session with a client application because the indicated XML data sent by the client was invalid.
Type	Error: An error occurred
Severity	error
Facility	ANY

LIBJNX_LOGIN_ACCOUNTS_NOT_LOCKED

System Log Message	No user accounts were locked.
Description	No user accounts had been locked.
Type	Error: An error occurred
Severity	notice
Facility	ANY

LIBJNX_LOGIN_ACCOUNT_LOCKED

System Log Message	Account for user ' <i>username</i> ' has been locked out from logins
Description	Logins from a locked account are not permitted.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY

LIBJNX_LOGIN_ACCOUNT_NOT_LOCKED

System Log Message	Account for user ' <i>username</i> ' was not locked.
---------------------------	--

Description The user account had not been locked.

Type Error: An error occurred

Severity notice

Facility ANY

LIBJNX_LOGIN_ACCOUNT_UNLOCKED

System Log Message Account for user '*username*' has been unlocked for logins

Description Logins from an unlocked account are permitted again.

Type Event: This message reports an event, not an error

Severity notice

Facility ANY

LIBJNX_LOGIN_ACCT_NOT_UNLOCKED

System Log Message Failed to unlock account for user '*username*'.

Description An attempt to unlock the user account failed.

Type Error: An error occurred

Severity error

Facility ANY

LIBJNX_PRIV_LOWER_FAILED

System Log Message Unable to lower privilege level: *error-message*

Description A Junos process attempted to revert its effective user ID to the original user. The attempt failed.

Type Error: An error occurred

Severity error

Facility ANY

Cause An internal software failure occurred.

Action Contact your technical support representative.

LIBJNX_PRIV_RAISE_FAILED

System Log Message Unable to raise privilege level: *error-message*

Description A Junos process attempted to set its effective user ID to the root user. The attempt failed.

Type Error: An error occurred

Severity	error
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

LIBJNX_REPLICATE_RCP_ERROR

System Log Message	<i>operation: operational-status</i>
Description	The rcp command failed during replication.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18951 .

LIBJNX_REPLICATE_RCP_EXEC_FAILED

System Log Message	<i>rcp failed: error-message</i>
Description	A Junos process created a child process to copy a file to the other Routing Engine. The copy operation failed.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

LIBJNX_SNMP_ENGINE_FILE_FAILURE

System Log Message	<i>function-name: operation: operation filename: error-message</i>
Description	A Junos process could not perform the indicated operation on the indicated SNMP engine data file.
Type	Error: An error occurred
Severity	critical
Facility	ANY

Cause An internal software failure occurred.

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18952>.

LIBJNX_SNMP_ENGINE_SCAN_FAILURE

System Log Message *function-name: fscanf : filename scanning: data Error: error-message*

Description A Junos process could not perform the scan operation on the indicated SNMP engine data file.

Type Error: An error occurred

Severity critical

Facility ANY

Cause An internal software failure occurred.

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18953>.

LIBJNX_SOCKET_BUFF_ERROR

System Log Message Socket buffer error - '*error-message*':

Description JUNOS system can not allocate the requested amount of the socket buffer.

Type Error: An error occurred

Severity error

Facility ANY

Cause An internal software failure occurred.

Action Contact your technical support representative.

LIBJNX_SOCKET_FAILURE

System Log Message *operation: error-message*

Description Various system processes use Transmission Control Protocol (TCP), User Datagram Protocol (UDP), and Reliable Data Protocol (RDP) sockets. The indicated socket operation failed for the indicated reason.

Type Error: An error occurred

Severity emergency

Facility ANY

Cause An internal software failure occurred.

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18954>.

LIBJNX_SOCKET_FLUSH_TIMEOUT

System Log Message exit flush timeout *error-message*

Description Various system processes use sockets for Inter-process Communication, and during the termination phase of the process the socket is flushed to ensure all the data sent has been received by the peer process. If the flush operation takes an excessive amount of time, the flush is aborted and process termination completes.

Type Error: An error occurred

Severity error

Facility ANY

Cause An internal software failure occurred.

Action Contact your technical support representative.

LIBJNX_XML_DECODE_FAILED

System Log Message Invalid XML encoding '*data*', skipping to ':'

Description The XML parser ignored the indicated XML data sent by a client application, because the XML encoding of the data was invalid. The parser skipped ahead to the likely endpoint for the invalid data.

Type Error: An error occurred

Severity error

Facility ANY

Cause A possible cause is improper escaping of character constants in the data stream.

Action Contact your technical support representative.

CHAPTER 70

LIBJSNMP System Log Messages

This chapter describes messages with the **LIBJSNMP** prefix. They are generated by the libjsnmp process.

LIBJSNMP_CTX_FAILURE

System Log Message	snmp_ms_trap_api return <i>argument</i>
Description	Sub-agents SNMP context either too long or of zero size
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

LIBJSNMP_IPC_ERROR

System Log Message	<i>argument: sock:port (type:port-type)</i>
Description	Error in SNMP related IPC messages size mismatch, corruption or memory failure
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

LIBJSNMP_IPC_READ_ERROR

System Log Message	Unable to read <i>inbound-bytes</i> bytes: sock: port (type: port-type)
Description	Error in reading IPC messages during SNMP related messaging

Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

LIBJSNMP_MTHD_API_UNKNOWN_TYPE

System Log Message	unknown oev type: <i>tag-type</i>
Description	Internal error - Unknown SNMP object indexing type
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

LIBJSNMP_NS_LOG_CRIT

System Log Message	CRIT: <i>argument</i>
Description	Logs for SNMP critical message
Type	Error: An error occurred
Severity	critical
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

LIBJSNMP_NS_LOG_EMERG

System Log Message	EMERG: <i>argument</i>
Description	SNMP errors with LOG_EMERG as severity
Type	Error: An error occurred
Severity	emergency
Facility	ANY
Cause	An internal software failure occurred.

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18955>.

LIBSNMP_NS_LOG_ERR

System Log Message ERR: *argument*

Description SNMP errors with LOG_ERR as severity

Type Error: An error occurred

Severity error

Facility ANY

Cause An internal software failure occurred.

Action Contact your technical support representative.

LIBSNMP_OID_GEN_FAILED

System Log Message Unable to generate OID: *object-name (system-error-message)*

Description Unable to translate SNMP object string to OID

Type Error: An error occurred

Severity error

Facility ANY

Cause An internal software failure occurred.

Action Contact your technical support representative.

LIBSNMP_READ_LEN_ERR

System Log Message error *error-code* reading routing socket

Description Failure while reading rtsocket for SNMP related operation

Type Error: An error occurred

Severity error

Facility ANY

Cause An internal software failure occurred.

Action Contact your technical support representative.

LIBSNMP_RTMSIZE_MISMATCH_ERR

System Log Message routing socket msg size *argument* of *argument1d* (call buf = *argument2*)

Description	Error in message length while reading rtsocket for SNMP related operation
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

LIBJSNMP_SMS_HDR_ERR

System Log Message	problem with hdr size (<i>record-size</i>) or msg size (<i>size</i>)
Description	Discrepancy in sub-agent message length and header size
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

LIBJSNMP_SMS_MSG_ERR

System Log Message	received <i>received-value</i> bytes, expected <i>expected-value</i> bytes
Description	Various discrepancies in sub-agent message lengths. SNMP Message errors
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

LIBJSNMP_SNMP_PH_INIT_ERR

System Log Message	snmp platform hooks initialization failure: <i>argument</i>
Description	Error during initialization of snmp platform hook library
Type	Error: An error occurred
Severity	error
Facility	ANY

Cause An internal software failure occurred.

Action Contact your technical support representative.

LIBSNMP_SOCKET_OPEN_ERR

System Log Message routing socket open error *argument*

Description Failure in opening routing socket

Type Error: An error occurred

Severity error

Facility ANY

Cause An internal software failure occurred.

Action Contact your technical support representative.

LIBSNMP_SOCKET_VER_MISMATCH

System Log Message routing socket version mismatch

Description Routing socket version mismatch between kernel and application

Type Error: An error occurred

Severity error

Facility ANY

Cause An internal software failure occurred.

Action Contact your technical support representative.

LIBSNMP_TRAP_API_FAILURE

System Log Message *function-name*: Trap API: *argument argument1*

Description Misc. error while creating SNMP traps

Type Error: An error occurred

Severity error

Facility ANY

Cause An internal software failure occurred.

Action Contact your technical support representative.

LIBJSNMP_TRAP_UTILS_ERR

System Log Message	unknown trap object: <i>object-name</i>
Description	Trying to send invalid object as varbind while creating SNMP traps
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

CHAPTER 71

LIBMSRPC System Log Messages

This chapter describes messages with the **LIBMSRPC** prefix. They are generated by the mspinfo process, which is responsible for RPC communication between the Routing Engine (RE) and the Multiservices PICs.

LIBMSRPC_CLIENT_INIT_FAILED

System Log Message	Can't create msrpc client: <i>error-message</i>
Description	A Junos process (mspinfo) could not establish initialization of the RPC client.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	Possible reasons: process is out of memory
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18956 .

LIBMSRPC_CLIENT_KCOM_FAILED

System Log Message	Can't initialize kcom for msrpc client: <i>error-message</i>
Description	A Junos process (mspinfo) could not establish initialization of the kcom subsystem.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	Possible reasons: can't initialize kcom services.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18957 .

LIBMSRPC_CLIENT_KCOM_NO_IF

System Log Message	No active extension-provider interfaces
---------------------------	---

Description	A Junos process (mspinfo) could not find any configured and active extension-provider interfaces.
Type	Error: An error occurred
Severity	notice
Facility	ANY
Cause	Possible reasons: can't initialize kcom services.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18958 .

LIBMSRPC_CLIENT_NO_CONNECTION

System Log Message	Failed connecting <i>fpc=fpc-slot</i> , <i>pic=pic-slot</i>
Description	Remote execution of the command given from the RE to the PIC failed, can not connect to the PIC.
Type	Error: An error occurred
Severity	notice
Facility	ANY
Cause	Possible reasons: a)PIC appears online but is not responding b)msrpc server is not running on the PIC.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18959 .

LIBMSRPC_CLIENT_NO_REPLY

System Log Message	Error executing " <i>command</i> ": no reply from the PIC
Description	Remote execution of the command given from the RE to the PIC failed, no reply from the PIC.
Type	Error: An error occurred
Severity	notice
Facility	ANY
Cause	Possible reasons: a)wrong command b)insufficient permissions c)wrong arguments d)PIC appears online but is not responding e)msrpc server is not running on the PIC.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18960 .

LIBMSRPC_CLIENT_PIC_DOWN

System Log Message	Interface <i>interface-name</i> is down
Description	Remote execution of the command given from the RE to the PIC failed, the PIC is down.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	Possible reasons: the given PIC is not responding and/or is offline.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18961 .

LIBMSRPC_CLIENT_WRONG_OUTPUT

System Log Message	Error executing " <i>command</i> ": output length exceeds <i>correct-length</i> characters
Description	Remote execution of the command given from the RE to the PIC failed, PIC returned unexpected output.
Type	Error: An error occurred
Severity	notice
Facility	ANY
Cause	Possible reasons: a)wrong command b)wrong arguments.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18962 .

CHAPTER 72

LICENSE System Log Messages

This chapter describes messages with the **LICENSE** prefix. They are generated by processes that call routines in the liblicense library, which provide software license management functions on a routing platform.

LICENSE_CONNECT_FAILURE

System Log Message	Connection could not be set up: <i>error-message</i>
Description	The indicated error occurred because a connection to the license-check process was not established.
Type	Error: An error occurred
Severity	error
Facility	ANY

LICENSE_CONN_TO_LI_CHECK_FAILURE

System Log Message	Process could not connect to license-check in <i>maximum-value</i> tries; giving up
Description	The indicated process failed to connect to the license-check process after the indicated maximum tries.
Type	Error: An error occurred
Severity	error
Facility	ANY

LICENSE_CONN_TO_LI_CHECK_SUCCESS

System Log Message	Connected to license-check
Description	The indicated process successfully connected to the license-check process.
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

LICENSE_EXPIRED

System Log Message	License for feature <i>feature-name(feature-id)</i> expired
Description	The time-based license for the indicated feature expired. The feature remains inactive until a new license is installed.
Type	Event: This message reports an event, not an error
Severity	alert
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=/KB18966 .

LICENSE_EXPIRED_KEY_DELETED

System Log Message	License key " <i>filename</i> " has expired.
Description	The indicated license-key has been removed from the file-system.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY

LICENSE_GRACE_PERIOD_APPROACHING

System Log Message	License grace period for feature <i>feature-name(feature-id)</i> will expire in <i>time</i>
Description	The indicated amount of time remained before the license grace period for the indicated feature would expire. If a new license was not installed within that time, the feature became inactive.
Type	Event: This message reports an event, not an error
Severity	alert
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18967 .

LICENSE_GRACE_PERIOD_EXCEEDED

System Log Message	License grace period for feature <i>feature-name(feature-id)</i> will expire in <i>time</i> (limit = <i>maximum-value</i>)
Description	The grace period for a scale license is about to expire. Unless the scale license is upgraded, the license will scale back to the licensed limit once the grace period expires.
Type	Event: This message reports an event, not an error

Severity	alert
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18968 .

LICENSE_GRACE_PERIOD_EXPIRED

System Log Message	License grace period for feature <i>feature-name(feature-id)</i> has expired
Description	The grace period for a licensable feature has expired. Strict license enforcement will remain active until a new license is installed.
Type	Event: This message reports an event, not an error
Severity	alert
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18969 .

LICENSE_INCORRECT_USAGE_API

System Log Message	Incorrect usage of API. Use the API <code>lc_write_scale_usage</code> .
Description	The indicated process has called an incorrect usage of a liblicense API
Type	Error: An error occurred
Severity	warning
Facility	ANY

LICENSE_INVALID_FEATURE_ID

System Log Message	It is an invalid feature id: <i>feature-id</i>
Description	The indicated process has encountered an invalid feature id.
Type	Error: An error occurred
Severity	error
Facility	ANY

LICENSE_JVERSION_READ_ERROR

System Log Message	Failed to get JUNOS version : error: <i>system-error-message</i>
Description	The indicated process encountered a system error while trying to obtain release version of JUNOS.
Type	Error: An error occurred
Severity	error

Facility ANY

LICENSE_LIST_MANAGEMENT

System Log Message Error occurred for feature *feature-name*: *error-message* (system error: *system-error-message*)

Description The management process (mgd) could not complete a license management command related to the indicated feature. If a system error is reported, it caused the problem.

Type Error: An error occurred

Severity error

Facility ANY

LICENSE_NEARING_EXPIRY

System Log Message License for feature *feature-name*(*feature-id*) expires in *time*

Description At the time this message was logged, the indicated amount of time remained before the time-based license for the indicated feature would expire. If a new license was not installed within that time, the feature became inactive.

Type Event: This message reports an event, not an error

Severity alert

Facility LOG_DAEMON

Action For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB18970>.

LICENSE_READ_ERROR

System Log Message recvmmsg() failed:*error-message*

Description The indicated process failed to read an event sent to it, for the indicated reason.

Type Error: An error occurred

Severity error

Facility ANY

LICENSE_REG_ERROR

System Log Message Registration request failed: *current-value*

Description The license registration request failed. A request needs to be resent to the license-check process.

Type Error: An error occurred

Severity error

Facility ANY

LICENSE_REVOKE_DB_CREATE_FAILURE

System Log Message	Failed to create license revoked db <i>filename : error-message</i>
Description	The indicated process failed to create license revoked db.
Type	Error: An error occurred
Severity	error
Facility	ANY

LICENSE_REVOKE_DB_OPEN_FAILURE

System Log Message	Unable to open license revoke db <i>filename : error-message</i>
Description	The indicated process failed to open license revoked db.
Type	Error: An error occurred
Severity	error
Facility	ANY

LICENSE_SHM_ATTACH_FAILURE

System Log Message	Failed to attach shared memory
Description	The indicated process failed to attach the shared memory.
Type	Error: An error occurred
Severity	error
Facility	ANY

LICENSE_SHM_CREATE_FAILURE

System Log Message	Failed to allocate shared memory
Description	The indicated process failed to allocate the shared memory.
Type	Error: An error occurred
Severity	error
Facility	ANY

LICENSE_SHM_DETACH_FAILURE

System Log Message	Failed to detach shared memory <i>error-argument</i>
Description	The indicated process failed to release the shared memory.
Type	Error: An error occurred
Severity	error

Facility ANY

LICENSE_SHM_DIR_OPEN_FAILURE

System Log Message Unable to create directory *filename: error-message*

Description The indicated process encountered a system error while attempting to create the directory.

Type Error: An error occurred

Severity error

Facility ANY

LICENSE_SHM_FILE_OPEN_FAILURE

System Log Message Failed to open the shared memory file *filename*, *errno=error-message*

Description The indicated process encountered a system error while attempting to open the shared memory file.

Type Error: An error occurred

Severity error

Facility ANY

LICENSE_SHM_KEY_CREATE_FAILURE

System Log Message Failed to create key for shared memory from the file *filename*

Description The indicated process encountered a system error while creating an IPC identifier from a pathname.

Type Error: An error occurred

Severity error

Facility ANY

LICENSE_SHM_SCALE_READ_FAILURE

System Log Message Failed to read license scale usage

Description The indicated process failed to read scale usage data.

Type Error: An error occurred

Severity error

Facility ANY

LICENSE_SHM_SCALE_UPDATE_FAILURE

System Log Message Failed to update license scale usage

Description The indicated process failed to update scale usage data.

Type Error: An error occurred
Severity error
Facility ANY

LICENSE_SHM_USAGE_READ_FAILURE

System Log Message Failed to read license feature usage shared memory
Description The indicated process has failed to read feature usage shared memory.

Type Error: An error occurred
Severity error
Facility ANY

LICENSE_SHM_USAGE_WRITE_FAILURE

System Log Message Failed to update license feature usage shared memory
Description The indicated process has failed to update feature usage shared memory.

Type Error: An error occurred
Severity error
Facility ANY

LICENSE_SIGNATURE_VERIFY_FAILED

System Log Message Signature verification failed: *error-message*
Description The management process (mgd) could not verify a license because the license's signature was invalid.

Type Error: An error occurred
Severity error
Facility ANY

LICENSE_UNKNOWN_RESPONSE_TYPE

System Log Message unknown message type received: *current-value*
Description An unknown response type was received from the license-check process.

Type Error: An error occurred
Severity error
Facility ANY

LICENSE_VERIFICATION_FILE_ERROR

System Log Message License verification failed for file '*error-message*': *filename* (system error: *system-error-message*)

Description The management process (mgd) could not verify the indicated license file because of the indicated internal file-handling error.

Type Error: An error occurred

Severity error

Facility ANY

CHAPTER 73

LLDP System Log Messages

This chapter describes messages with the **LLDP** prefix. They are generated by the link layer discovery protocol process (lldpd) which is used by MX Series routers, ACX Series routers, and EX Series switches to learn and distribute device information on network links. The information allows the switch to quickly identify a variety of devices, including IP telephones, resulting in a LAN that interoperates smoothly and efficiently.

LLDP_NEIGHBOR_DOWN

System Log Message	A neighbor of interface <i>interface-name</i> has gone down. Now, this interface has <i>neighbor-count</i> neighbor/s.
Description	LLDP has detected that a neighbor has gone down for an interface.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON
Cause	TTL is expired for RDB neighbor. So deleting neighbor from rdb.

LLDP_NEIGHBOR_UP

System Log Message	A neighbor has come up for interface <i>interface-name</i> . Now, this interface has <i>neighbor-count</i> neighbor/s.
Description	LLDP has detected that a neighbor has come up for an interface.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON
Cause	New neighbor has come up. Adding neighbor to rdb.

LOGIN System Log Messages

This chapter describes messages with the **LOGIN** prefix. They are generated by the login process (login), which performs authentication for Telnet sessions.

LOGIN_ABORTED

System Log Message	Client aborted login
Description	A login attempt was cancelled, either by the remote user or in response to a signal.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_AUTH

LOGIN_ATTEMPTS_THRESHOLD

System Log Message	Threshold for unsuccessful authentication attempts (<i>limit</i>) reached by user ' <i>username</i> '
Description	The user made too many failed login attempts.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_AUTH

LOGIN_FAILED

System Log Message	Login failed for user <i>username</i> from host <i>source-address</i>
Description	A login attempt failed for the indicated username.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_AUTH

LOGIN_FAILED_LIMIT

System Log Message	Specified number of login failures (<i>limit</i>) for user ' <i>username</i> ' reached from ' <i>source-address</i> '
Description	Several login attempts failed for the indicated username.

Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_AUTH

LOGIN_FAILED_SET_CONTEXT

System Log Message	Failed to set context for user <i>username</i>
Description	The login process (login) could not set login context properties for the indicated user and cancelled the authentication attempt.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH

LOGIN_FAILED_SET_LOGIN

System Log Message	Failed to set login ID for user <i>username</i> : <i>error-message</i>
Description	The login process (login) could not assume the user ID of the indicated user and cancelled the authentication attempt.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH

LOGIN_HOSTNAME_UNRESOLVED

System Log Message	Unable to resolve hostname <i>hostname</i> : <i>error-message</i>
Description	The login process (login) could not resolve the indicated remote hostname for the indicated reason.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH
Cause	An internal software failure occurred.

LOGIN_INFORMATION

System Log Message	User <i>username</i> logged in from host <i>hostname</i> on device <i>tty-name</i>
Description	The indicated username was authenticated and logged into the shell specified for it in the password file.
Type	Event: This message reports an event, not an error
Severity	info

Facility LOG_AUTH

LOGIN_MALFORMED_USER

System Log Message Invalid username: *username*

Description The indicated username was invalid.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_AUTH

LOGIN_PAM_AUTHENTICATION_ERROR

System Log Message Failed password for user *username*

Description The login process (login) could not authenticate the indicated user via PAM.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_AUTH

LOGIN_PAM_ERROR

System Log Message Failure while authenticating user *username*: *error-message*

Description The PAM authentication process failed for the indicated username, for the indicated reason.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

LOGIN_PAM_MAX_RETRIES

System Log Message Too many retries while authenticating user *username*

Description The number of failed PAM authentication attempts for the indicated user exceeded the maximum limit.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

LOGIN_PAM_STOP

System Log Message Failed to end PAM session: *error-message*

Description The login process (login) could not end the PAM authentication session, for the indicated reason.

Type Error: An error occurred
Severity error
Facility LOG_AUTH

LOGIN_PAM_USER_UNKNOWN

System Log Message Attempt to authenticate unknown user *username*
Description The login process (login) failed to authenticate the indicated user via PAM because the username was unknown.

Type Event: This message reports an event, not an error
Severity error
Facility LOG_AUTH

LOGIN_PASSWORD_EXPIRED

System Log Message Forcing change of expired password for user *username*
Description The password provided for the indicated username was expired and the user was prompted to set a new one.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_AUTH

LOGIN_REFUSED

System Log Message Login of user *username* from host *hostname* on device *tty-name* was refused: *reason*
Description A login attempt for the indicated username was rejected for the indicated reason.

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_AUTH

LOGIN_ROOT

System Log Message User *username* logged in as root from host *hostname* on device *tty-name*
Description The indicated username was authenticated as a superuser and logged into the shell specified for the root user in the password file.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_AUTH

LOGIN_TIMED_OUT

System Log Message	Login attempt timed out after <i>duration</i> seconds
Description	A login attempt failed to complete in the maximum time allowed.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_AUTH

CHAPTER 75

LPDFD System Log Messages

This chapter describes messages with the **LPDFD** prefix. They are generated by the local policy decision function process (lpdfd). A policy decision function is a component in the IP multimedia subsystem that controls traffic entering the packet-switched network by allocating or denying IP bearer resources.

LPDFD_DYN_PDB_OPEN_FAILED

System Log Message	Failed to open profile database: <i>error-message</i>
Description	The local policy decision function process (lpdfd) failed to open the profile database.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18972 .

LPDFD_DYN_REGISTER_FAILED

System Log Message	Dynamic config register failed: <i>error-message</i>
Description	The local policy decision function process (lpdfd) failed to register with the dynamic configuration subsystem.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18973 .

LPDFD_PCONN_SERVER

System Log Message	<i>argument</i> : Cannot retrieve peer info for session. Error: <i>error-message</i>
Description	The local policy decision function process (lpdfd) pconn server failed to initialize

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

LRMUX System Log Messages

This chapter describes messages with the **LRMUX** prefix. They are generated by the logical router multiplexer process (`lrmuxd`), which manages the multiple instances of the routing protocols process (`rpd`) on a machine running logical routers.

LRMUX_FAILED_EXEC

System Log Message	Failed to exec <i>command</i>
Description	The Logical System Multiplexer process (<code>lrmuxd</code>) issued the <code>exec()</code> system call to start a routing process (<code>rpd</code>) to check the validity of the configuration. The system call failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

LRMUX_LRPD_PID_LOCK

System Log Message	Lock not found on PID file <i>filename</i>
Description	The Logical System Multiplexer process (<code>lrmuxd</code>) could not find a lock for a logical system.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	A logical system process (<code>rpd</code>) died.

LRMUX_LRPD_PID_OPEN

System Log Message	Unable to open PID file <i>filename</i>
Description	The Logical System Multiplexer process (<code>lrmuxd</code>) could not open the indicated PID lock file for a logical system process (<code>rpd</code>).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

LRMUX_LRPD_SEND_HUP

System Log Message	Unable to send signal to PID <i>pid</i>
Description	The Logical System Multiplexer process (lrmuxd) could not forward a SIGHUP signal to a logical system process (rpd).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

LSYSD System Log Messages

This chapter describes messages with the **LSYSD** prefix. They are generated by the logical system process (lsysd), which handles logical systems on devices running Junos OS.

LRMUX_FAILED_EXEC

System Log Message	Failed to exec <i>command</i>
Description	The Logical System Multiplexer process (lrmuxd) issued the exec() system call to start a routing process (rpd) to check the validity of the configuration. The system call failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

LRMUX_LRPD_PID_LOCK

System Log Message	Lock not found on PID file <i>filename</i>
Description	The Logical System Multiplexer process (lrmuxd) could not find a lock for a logical system.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	A logical system process (rpd) died.

LRMUX_LRPD_PID_OPEN

System Log Message	Unable to open PID file <i>filename</i>
Description	The Logical System Multiplexer process (lrmuxd) could not open the indicated PID lock file for a logical system process (rpd).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

LRMUX_LRPD_SEND_HUP

System Log Message	Unable to send signal to PID <i>pid</i>
Description	The Logical System Multiplexer process (lrmuxd) could not forward a SIGHUP signal to a logical system process (rpd).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHAPTER 78

MBG System Log Messages

This chapter describes messages with the **MBG** prefix.

MBG_ADDR_ALLOC_ALLOCATED

System Log Message	Address allocation failed, routing-instance <i>routing-instance</i> address <i>address</i> in use.
Description	Address allocation failed - requested address in use.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

MBG_ADDR_ALLOC_MM

System Log Message	Address allocation failed, routing-instance <i>routing-instance</i> pool-name <i>pool-name</i> in Maintenance Mode.
Description	Address allocation failed - address pool in maintenance mode.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

MBG_ADDR_ALLOC_NO_ADDR

System Log Message	Address allocation failed, no address available in routing-instance <i>routing-instance</i> pool-name <i>pool-name</i> .
Description	Address allocation failed - no address available in pool(group).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Configure additional addresses for allocation.

MBG_ADDR_ALLOC_NO_POOL

System Log Message Address allocation failed, routing-instance *routing-instance* definition for pool-name *pool-name* not found.

Description Address allocation failed - pool configuration not found.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

MBG_ADDR_ALLOC_NO_VRF

System Log Message Address allocation failed, routing-instance ID *routing-instance* not found.

Description Address allocation failed - routing-instance configuration not found.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

MBG_ADDR_ALLOC_UNDEFINED

System Log Message Address allocation failed, routing-instance *routing-instance* address *address* is not configured.

Description Address allocation failed - address has not been configured for allocation.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Configure the requested address for allocation.

MBG_ADDR_APFE_DN

System Log Message Anchor PFE *pic-name* went down.

Description Anchor PFE went DOWN.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

MBG_ADDR_APFE_UP

System Log Message Anchor PFE *pic-name* came up.

Description Anchor PFE came UP.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

MBG_ADDR_INIT_OK

System Log Message Mobile Subscriber IP Address allocation Library initialized.
Description Mobile Subscriber IP Address allocation Library initialized.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

MBG_ADDR_MM_ACK

System Log Message Maintenance Mode Ack sent for routing-instance *routing-instance* pool-name *pool-name*.
Description Mobile Subscriber IP Address allocation library Address pool maintenance mode acknowledged. Configuration modifications can now be made to the address pool.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

MBG_ADDR_MM_ENABLE

System Log Message Routing-instance *routing-instance* pool-name *pool-name* placed in Maintenance Mode.
Description Mobile Subscriber IP Address allocation Library Address pool maintenance mode enabled.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

MBG_ADDR_NO_MEMORY_HEAP

System Log Message Out of heap memory.
Description Mobile Subscriber IP Address memory allocation - out of heap memory.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

MBG_ADDR_NO_MEMORY_OC

System Log Message Out of object-cache memory
Description Mobile Subscriber IP Address memory allocation - out of object-cache memory.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

MBG_ADDR_PRIMARY

System Log Message High-availability state set to Primary.
Description Mobile Subscriber IP Address allocation Library high-availability state set to Primary.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

MBG_ADDR_SECONDARY

System Log Message High-availability state set to Secondary.
Description Mobile Subscriber IP Address allocation Library high-availability state set to Secondary.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

MBG_ADDR_STANDALONE

System Log Message High-availability state set to Standalone.
Description Mobile Subscriber IP Address allocation Library high-availability state set to Standalone.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

MBG_CFG_COMMIT_FAIL

System Log Message Failed to create mobiled commit task
Description Child Mobility Daemon failed to create subtask for committing configuration.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON
Cause Task creation failure possibly because of limited resources (memory/CPU cycles)
Action Internal Software failure, Contact technical help

MBG_CFG_DB_OPEN_FAIL

System Log Message	Commit check daemon failed to open configuration database
Description	Mobility Daemon failed to open static configuration database during initialization.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	Failed possibly because Mobiled failed to parse it or configuration not found
Action	Check if router configuration is in place, Contact technical help

MBG_CG_CONF_SERVER_REGIST_FAIL

System Log Message	Failed to register configuration plugin for chargemand charge
Description	Mobiled charging configuration server failed to get register.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

MBG_CG_CP_MM_STATE_CHANGE

System Log Message	Gateway type <i>gw-personality</i> gateway name <i>gateway-name</i> profile name <i>profile-name</i> new state <i>new-state</i> old state <i>old-state</i>
Description	This indicates that given charging profile underwent a change in the maintenance-mode.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

MBG_CG_EVENT_SERVER_REGIST_FAIL

System Log Message	Failed to register event plugin for chargemand charge
Description	Mobiled charging event notification server failed to get register.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

MBG_CG_TSP_MM_STATE_CHANGE

System Log Message	Gateway type <i>gw-personality</i> gateway name <i>gateway-name</i> profile name <i>profile-name</i> new state <i>new-state</i> old state <i>old-state</i>
---------------------------	--

Description This indicates that given transport profile underwent a change in the maintenance-mode.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

MBG_CG_UI_SERVER_REGIST_FAIL

System Log Message Failed to register ui plugin for chargemand charge

Description Mobilized charging UI server failed to get register.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

MBG_CMD_ATTACH_FAIL

System Log Message unable to attach to SMD shared province

Description CMD unable to attach to SMD shared province.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

MBG_CMD_CDR_DEST

System Log Message Gateway type *gw-personality* gateway name *gateway-name* CDR destination *status-code* server name *profile-name* fpc slot id *fpc-slot* pic slot id *pic-slot*

Description This signifies change in the destination of the CDRs (Charging Data Record).

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

MBG_CMD_CDR_ENCODING_FAIL

System Log Message Gateway type *gw-personality* gateway name *gateway-name* charging id *charging-id* lrsn id *lrsn-id*

Description For the specified charging id charging data record encoding failed.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

MBG_CMD_CONF_CLIENT_INIT_FAIL

System Log Message	Gateway type <i>gw-personality</i> gateway name <i>gateway-name</i> charging configuration client init failed
Description	UI client has failed to connect to mobiled charging UI server.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

MBG_CMD_EVE_CLIENT_INIT_FAIL

System Log Message	Gateway type <i>gw-personality</i> gateway name <i>gateway-name</i> charging event client plugin registration failed
Description	Event client has failed to connect to mobiled charging event server.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

MBG_CMD_GTPP_DOWN

System Log Message	Gateway type <i>gw-personality</i> gateway name <i>gateway-name</i> GTPP client <i>profile-name</i> down on fpc slot id <i>fpc-slot</i> pic slot id <i>pic-slot</i>
Description	This event signifies that the specified server has been marked dead.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

MBG_CMD_GTPP_UP

System Log Message	Gateway type <i>gw-personality</i> gateway name <i>gateway-name</i> GTPP client <i>profile-name</i> up on fpc slot id <i>fpc-slot</i> pic slot id <i>pic-slot</i>
Description	This event signifies that the specified server has been marked alive.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

MBG_CMD_GTPP_VER_MIS_MATCH

System Log Message	Gateway type <i>gw-personality</i> gateway name <i>gateway-name</i> CGF id <i>peer-id</i> version mismatch configured version <i>configured-version</i> received version <i>received-version</i>
Description	This event signifies that the version not supported message received from the CGF server.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

MBG_CMD_GW_SER_UP

System Log Message Charging is UP for Gateway type *gw-personality* gateway name *gateway-name* fpc slot id *fpc-slot* pic slot id *pic-slot*

Description This signifies the Charging daemon is UP on the SPIC.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

MBG_CMD_HA_CHARGED_CONNEC_FAIL

System Log Message Failed to establish connection to Charged gateway type *gw-personality* gateway name *gateway-name*

Description Backup chargemand failed to establish connection with charged.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

MBG_CMD_HMEM_THRES

System Log Message Gateway type *gw-personality* gateway name *gateway-name* fpc slot id *fpc-slot* pic slot id *pic-slot* SPIC memory reaches to *limit* alarm type *alarm-type*

Description This event is sent out when the utilization exceeds or falls below configured high threshold of internal memory space for charging data records.

Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON

MBG_CMD_IRI_EXTRACT_FAIL

System Log Message Gateway type *gw-personality* Gateway name *gateway-name* failed to extract the IRI address for chargemand to charged fpc slot *fpc-slot* pic slot *pic-slot*

Description Failed to extract the internal routing instance of the corresponding chargemand.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

MBG_CMD_LMEM_THRES

System Log Message	Gateway type <i>gw-personality</i> gateway name <i>gateway-name</i> fpc slot id <i>fpc-slot</i> pic slot id <i>pic-slot</i> SPIC memory reaches to <i>limit</i> alarm type <i>alarm-type</i>
Description	This event is sent out when the utilization exceeds or falls below configured low threshold of internal memory space for charging data records.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

MBG_CMD_MMEM_THRES

System Log Message	Gateway type <i>gw-personality</i> gateway name <i>gateway-name</i> fpc slot id <i>fpc-slot</i> pic slot id <i>pic-slot</i> SPIC memory reaches to <i>limit</i> alarm type <i>alarm-type</i>
Description	This event is sent out when the utilization exceeds or falls below configured medium threshold of internal memory space for charging data records.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

MBG_CMD_PMNGR_IPC_REGISTER_FAIL

System Log Message	Path manager IPC register failed gateway type <i>gw-personality</i> gateway name <i>gateway-name</i> fpc id <i>fpc-slot</i> pic id <i>pic-slot</i>
Description	IPC registration of the path manager has failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

MBG_CMD_PMNGR_SERVER_CONNEC_FAIL

System Log Message	Failed to establish the pathmgr server connection gateway type <i>gw-personality</i> gateway name <i>gateway-name</i>
Description	Failed to create the path manager server connection.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

MBG_CMD_RE_DISK_FULL

System Log Message	RE hard disk full gateway type <i>gw-personality</i> gateway name <i>gateway-name</i>
---------------------------	---

Description Disk full message received by chargemand from the charged.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

MBG_CMD_RE_DISK_FULL_RESOLVED

System Log Message Received RE hard disk full resolved status messagegateway type *gw-personality* gateway name *gateway-name*

Description RE Disk full has resolved and disk is available for the storage.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

MBG_CMD_RE_DISK_OFFLINE

System Log Message Received RE disk offline in batch response messagegateway type *gw-personality* gateway name *gateway-name*

Description RE local storage disk is not available.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

MBG_CMD_RE_DISK_ONLINE

System Log Message RE hard disk is available. gateway type *gw-personality* gateway name *gateway-name*

Description RE local storage disk is available.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

MBG_CMD_TIMER_START_FAIL

System Log Message Gateway type *gw-personality* gateway name *gateway-name*Failed to start the timer *event-type*

Description For the specified event timer has failed to start.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

MBG_CMD_TIMER_STOP_FAIL

System Log Message	Gateway type <i>gw-personality</i> gateway name <i>gateway-name</i> Failed to stop the timer event-type
Description	For the specified event timer has failed to stop.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

MBG_CMD_TSP_LOOK_UP_FAIL

System Log Message	Gateway type <i>gw-personality</i> gateway name <i>gateway-name</i> Failed to access transport profile Id <i>group-id</i>
Description	Transport profile does not exists in the data base.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

MBG_CMD_UI_CLIENT_INIT_FAIL

System Log Message	Gateway type <i>gw-personality</i> gateway name <i>gateway-name</i> charging UI client plugin registration failed
Description	Configuration client has failed to connect to mobiled charging configuration server.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

MBG_CMD_WFA_FULL

System Log Message	Gateway type <i>gw-personality</i> gateway name <i>gateway-name</i> WFA is full TSP Id <i>group-id</i>
Description	Batch/DRT messages will not be created until the WFA becomes free
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

MBG_CONF_SERVER_INIT_FAIL

System Log Message	Mobility configuration server creation failed
Description	Mobility Configuration server (which communicates with peers on SPIC) creation failed, there is one configuration server for all the peers.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	Configuration server creation failure possibly because of limited resources (memory/CPU cycles)
Action	Internal software failure, Contact technical help

MBG_EVENT_SERVER_INIT_FAIL

System Log Message	Mobility event server creation failed
Description	Mobility Event server (which communicates with peers on SPIC) creation failed, there is one event server for all the peers.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	Event server creation failure possibly because of limited resources (memory/CPU cycles)
Action	Internal software failure, Contact technical help

MBG_GW_TASK_CREATION_FAILURE

System Log Message	Failed to create Gateway Module task
Description	Mobility Daemon failed to create Gateway Module task.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	Gateway Module task creation failure possibly because of limited resources (memory/CPU cycles)
Action	Internal software failure, Contact technical help

MBG_IF_TASK_CREATION_FAILURE

System Log Message	Failed to create IF module task
Description	Mobility Daemon failed to create IF Module task.
Type	Error: An error occurred
Severity	error

Facility	LOG_DAEMON
Cause	IF Module task creation failure possibly because of limited resources (memory/CPU cycles)
Action	Internal software failure, Contact technical help

MBG_INIT_FAIL

System Log Message	Failed to create Mobility Main task
Description	During Mobility infrastructure initializations, Main task creation failed.
Type	Error: An error occurred
Severity	critical
Facility	LOG_DAEMON
Cause	Main task creation failed possibly because of task block memory allocation failure
Action	Internal software failure, Contact technical help

MBG_MM_TASK_CREATE_FAIL

System Log Message	Failed to create Maintenance Mode Server Task
Description	Mobility Daemon failed to create maintenance mode server task.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	Maintenance mode task creation failure possibly because of limited resources (memory/CPU cycles)
Action	Internal software failure, Contact technical help

MBG_PKG_NOT_FOUND

System Log Message	Mobility software package jmobile is not present
Description	The mobility software package (jmobile) is not currently installed after jinstall package installation.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	Mobility package is not installed

Action Install jmobile mobility package

MBG_PLATFORM_NOT_SUPPORTED

System Log Message Mobility software is not compatible with the current platform

Description Mobility software is compatible with MODEL_MX960, MODEL_MX480 and MODEL_MX240.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause Platform is not supported by Mobility software

Action Change to compatible platform, Contact technical help

MBG_ROUTING_SOCKET_INIT_FAIL

System Log Message Routing Socket Initialization failure

Description During Mobility infrastructure initialization, internal routing socket library initialization failed, which is used by different application modules for communication.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause Routing socket open failure

Action Internal software failure, Contact technical help

MBG_TIMER_CREATE_FAIL

System Log Message Timer task creation failure for Mobility Daemon

Description Mobility Daemon failed to create alarm timer task, which is a periodic timer to poll alarm related stats.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause Failed to create timer task possibly because of limited resources (memory/CPU cycles)

Action Internal software failure, Contact technical help

MBG_UI_SERVER_INIT_FAIL

System Log Message	Mobility UI server creation failed
Description	MObility UI server (which communicates with peers on SPIC) creation failed, there is one UI server for all peers.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	UI server creation failure possibly because of limited resources (memory/CPU cycles)
Action	Internal software failure, Contact technical help

CHAPTER 79

MCSN System Log Messages

This chapter describes messages with the **MCSN** prefix. They are generated by the multicast snooping process (mcsnoopd), which enables a Layer 2 device to examine the content of Layer 3 packets to determine which actions to perform.

MCSN_SYSTEM

System Log Message *reason: error-message*

Description A system call made by the multicast snooping process (mcsnoopd) failed.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause It is possible that the kernel lacked the resources to fulfill the request. The mcsnoopd process will recover.

CHAPTER 80

MIB2D System Log Messages

This chapter describes messages with the **MIB2D** prefix. They are generated by the Management Information Base II (MIB II) process (mib2d), which services requests for information gathered and reported by the Simple Network Management Protocol (SNMP).

MIB2D_ATM_ERROR

System Log Message	<i>function-name: error-message</i>
Description	The MIB II process (mib2d) could not process ATM-related information.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

MIB2D_CONFIG_CHECK_FAILED

System Log Message	<i>function-name: configuration database has errors</i>
Description	The portion of the candidate configuration related to the MIB II process (mib2d) was checked for validity during a 'commit' operation. The check failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	The configuration was invalid.
Action	Correct the invalid portion of the configuration as described in the error message on the console.

MIB2D_COUNTER DECREASING

System Log Message	<i>function-name: counter counter-name decreasing for type(index), new(new-value) old(<old-value)</i>
Description	The MIB II process (mib2d) received a counter which value is less than the last retrieved value.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

MIB2D_FILE_OPEN_FAILURE

System Log Message	Unable to open file ' <i>filename</i> ': <i>error-message</i>
Description	The MIB II process (mib2d) could not open the indicated file.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

MIB2D_IFD_IFDINDEX_FAILURE

System Log Message	Ifd index assigned to <i>interface-name</i> changed from <i>old-value</i> to <i>new-value</i> , removing old interface
Description	There was a change to the ifd Index assigned to the indicated existing interface.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

MIB2D_IFD_IFINDEX_FAILURE

System Log Message	SNMP index assigned to <i>interface-name</i> changed from <i>old-value</i> to <i>new-value</i>
Description	There was a change to the SNMP ifIndex assigned to the indicated existing interface.
Type	Error: An error occurred

Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

MIB2D_IFL_IFINDEX_FAILURE

System Log Message	SNMP index assigned to <i>interface-name.interface-unit</i> changed from <i>old-value</i> to <i>new-value</i>
Description	There was a change to the SNMP ifIndex assigned to the indicated existing interface.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

MIB2D_IF_FLAPPING_MISSING

System Log Message	<i>function-name</i> : interface flapping missing: ifname(<i>interface-name</i>) old if_anydown_flaps(<i>old-value</i>) if_anydown_flaps(<i>new-value</i>)
Description	The MIB II process (mib2d) is blocked on the kernel for synchronous message. If there is an interface flap (down and then back up again) in the time mib2d is blocked in the kernel, mib2d will miss asynchronous messages from the kernel about state changes.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

MIB2D_KVM_FAILURE

System Log Message	<i>function-name</i> : <i>reason</i> : <i>error-message</i>
Description	A call to the indicated function in the kernel virtual memory library failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

MIB2D_MASTERSHIP_UPDATE

System Log Message	Mastership switched new Chassis State <i>chassis-type</i> , new RE State <i>state</i>
Description	mib2d process updated its Mastership state. This can happen during GRES, or at daemon startup.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

MIB2D_PMON_OVERLOAD_CLEARED_TRAP

System Log Message	Overload name: <i>overload-name</i> , interface: <i>interface-name</i>
Description	The MIB II process (mib2d) generated a jnxPMonOverloadCleared trap when it detected the clearing of an overload condition on the indicated monitoring services interface.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

MIB2D_PMON_OVERLOAD_SET_TRAP

System Log Message	Overload name: <i>overload-name</i> , interface: <i>interface-name</i>
Description	The MIB II process (mib2d) generated a jnxPMonOverloadSet trap when it detected an overload condition on the indicated monitoring services interface.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

MIB2D_RTSLIB_READ_FAILURE

System Log Message	<i>function-name</i> : failed in operation <i>object-name</i> : <i>index</i> (<i>error-message</i>)
Description	A call to the indicated function in the routing socket library failed during the indicated operation on the indicated object.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18978 .

MIB2D_RTSLIB_SEQ_MISMATCH

System Log Message	<i>function-name</i> : sequence mismatch (<i>expected-value</i> , <i>received-value</i>), resyncing
Description	The indicated function in the routing socket library detected a sequence number mismatch. The MIB II process (mib2d) will resynchronize its data with the Junos kernel.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

MIB2D_SNMP_INDEX_ASSIGN

System Log Message	<i>function-name</i> : reason snmpid(<i>snmp-interface-index</i>) ifname(<i>interface-name.interface-unit</i>)
Description	MIB2D can not assign snmp index for each interface.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18979 .

MIB2D_SNMP_INDEX_DUPLICATE

System Log Message	<i>function-name</i> : duplicate snmpid(<i>snmp-interface-index</i>) old ifname(<i>interface-name.interface-unit</i>) new ifname(<i>new-interface-name.kernel-interface-unit</i>)
Description	The SNMP index for first interface name was assigned the same SNMP index as second interface name.
Type	Error: An error occurred
Severity	emergency
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18980 .

MIB2D_SNMP_INDEX_UPDATE_STAT

System Log Message	<i>function-name</i> <i>reason</i> <i>filename</i>
---------------------------	--

Description	MIB2D can not get the status of SNMP index file
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18981 .

MIB2D_SNMP_INDEX_WRITE

System Log Message	<i>function-name: reason filename</i>
Description	MIB2D can not write into a file containing all the indices
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18982 .

MIB2D_SYSCTL_FAILURE

System Log Message	<i>function-name: sysctl type failed: error-message</i>
Description	A request to the Junos kernel for system data failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

MIB2D_TRAP_HEADER_FAILURE

System Log Message	<i>function-name: trap_request_header failed</i>
Description	The MIB II process (mib2d) could not allocate a trap header.
Type	Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause The Routing Engine is low on memory.

Action Contact your technical support representative.

MIB2D_TRAP_SEND_FAILURE

System Log Message *function-name: trap_request_send: error-message*

Description The MIB II process (mib2d) could not send a trap header.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause An internal software failure occurred.

Action Contact your technical support representative.

CHAPTER 81

MPLS System Log Messages

This chapter describes messages with the **MPLS** prefix. They are generated by the Multiprotocol Label Switching (MPLS) Operation, Administration, and Maintenance (OAM) process (mplsoamd), which supports traceroute operations for LDP label-switched paths (LSPs).

MPLS_OAM_FANOUT_LIMIT_REACHED

System Log Message	<i>fec-address</i> : traceroute fanout limit was reached
Description	The traceroute fanout limit was reached.
Type	Error: An error occurred
Severity	info
Facility	LOG_DAEMON
Action	Raise the traceroute fanout limit parameter.

MPLS_OAM_INVALID_SOURCE_ADDRESS

System Log Message	<i>fec-address</i> : source address <i>ip-address</i> is invalid
Description	The traceroute utility is configured to use an invalid source address.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Configure traceroute to use a valid source address.

MPLS_OAM_PATH_LIMIT_REACHED

System Log Message	<i>fec-address</i> : traceroute path limit was reached
Description	The traceroute path limit was reached.
Type	Error: An error occurred
Severity	info

Facility LOG_DAEMON
Action Raise the traceroute path limit parameter.

MPLS_OAM_SEND_FAILED

System Log Message *fec-address: unable to send probe (error-message)*

Description The Multiprotocol Label Switching (MPLS) Operation, Administration, and Maintenance (OAM) process (mplsoamd) could not send a traceroute probe packet.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

MPLS_OAM_SOCKET_OPEN_FAILED

System Log Message *fec-address: unable to open socket (error-message)*

Description The Multiprotocol Label Switching (MPLS) Operation, Administration, and Maintenance (OAM) process (mplsoamd) could not open a socket to initiate a traceroute operation.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

MPLS_OAM_SOCKET_SELECT_FAILED

System Log Message *fec-address: unable to select socket (error-message)*

Description The Multiprotocol Label Switching (MPLS) Operation, Administration, and Maintenance (OAM) process (mplsoamd) could not select a socket to initiate a traceroute operation.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

MPLS_OAM_TRACEROUTE_INTERRUPTED

System Log Message *fec-address: topology update interrupted traceroute*

Description A traceroute operation was interrupted by a topology change.

Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON
Action	Wait for the next scheduled traceroute operation.

MPLS_OAM_TTL_EXPIRED

System Log Message	<i>fec-address</i> : traceroute TTL limit was reached
Description	The time-to-live (TTL) limit for the traceroute utility was reached.
Type	Error: An error occurred
Severity	info
Facility	LOG_DAEMON
Action	Raise the traceroute TTL limit parameter.

MPLS_OAM_UNREACHABLE

System Log Message	<i>fec-address</i> : traceroute encountered unreachable node
Description	The traceroute utility encountered a node that does not have a computable destination address. The Multiprotocol Label Switching (MPLS) Operation, Administration, and Maintenance (OAM) process (mplsoamd) therefore could not send a probe to the node.
Type	Error: An error occurred
Severity	info
Facility	LOG_DAEMON
Action	Contact your technical support representative.

CHAPTER 82

NEXTHOP System Log Messages

This chapter describes messages with the **NEXTHOP** prefix. They are generated by the process that decides the next hop.

NEXTHOP_COMPONENTS_LIMIT_REACHED

System Log Message	Limit on components reached for flood next hop for routing instance ' <i>routing-instance</i> '
Description	The limit on the number of logical interfaces for a next hop was reached for the indicated routing instance and bridging domain. Only a subset of new interfaces were added to the next hop.
Type	Event: This message reports an event, not an error
Severity	error
Facility	ANY

CHAPTER 83

NSD System Log Messages

This chapter describes messages with the **NSD** prefix. They are generated by the network security process (nsd), which manages firewall configuration on routers running Junos OS with enhanced services.

NSD_MEMORY_ALLOC_FAILED

System Log Message	Unable to allocate <i>count</i> bytes of memory
Description	The network security process (nsd) could not allocate the indicated number of bytes of memory.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	It is possible that system memory is exhausted.
Action	Increase the amount of RAM in the Routing Engine. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18983 .

NSD_RESTART_COMP_CFG_READ_FAILED

System Log Message	Subcomponent could not read configuration database
Description	As the network security process (nsd) restarted, one or more of its subcomponents could not read its configuration information from configuration database. The nsd process restarted anyway, and routing performance was not affected.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

NSD_SEC_NODE_COMP_SYNC_FAILED

System Log Message	One or more subcomponents could not sync their state on backup RE
Description	One or more subcomponents of the network security process (nsd) failed to synchronize their state when the nsd restarted on secondary mode.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18984 .

NSTRACED System Log Messages

This chapter describes messages with the **NSTRACED** prefix. They are generated by the USP trace process (nstraced).

NSTRACED_MEMORY_ALLOC_FAILED

System Log Message	Unable to allocate <i>count</i> bytes of memory
Description	The USP trace process (nstraced) could not allocate the indicated number of bytes of memory.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	System memory was exhausted.
Action	Increase the amount of RAM in the Routing Engine. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18985 .

NSTRACED_RESTART_CFG_READ_FAILED

System Log Message	Subcomponent could not read configuration database
Description	When the USP trace process (nstraced) restarted, it could not read its configuration information from the configuration database.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

CHAPTER 85

NTPDATE System Log Messages

This chapter describes messages with the **NTPDATE** prefix. They are generated by the Network Time Protocol process (ntpd) process, which regularly synchronizes system time with internet time servers.

NTPDATE_TIME_CHANGED

System Log Message	step time offset <i>new-value</i> sec
Description	The ntp service changed the time of day
Type	Error: An error occurred
Severity	info
Facility	ANY

CHAPTER 86

NTPD System Log Messages

This chapter describes messages with the **NTPD** prefix. They are generated by the Network Time Protocol process (ntpd) process, which regularly synchronizes system time with internet time servers.

NTPD_CHANGED_TIME

System Log Message	time reset <i>rate</i> s
Description	The ntp service changed the time of day
Type	Error: An error occurred
Severity	info
Facility	ANY

CHAPTER 87

PARSE System Log Messages

This chapter describes messages with the **PARSE** prefix. They are generated by the Virtual Router Redundancy Protocol (VRRP) process (vrrpd), which provides the user interface for management of VRRP groups.

PARSE_WARN_DUPLICATE_ROUTER_AD

System Log Message	Duplicate 'router-advertisement' configured for interface <i>interface-name</i>
Description	Duplicate router-advertisement is configured for given interface.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON

PARSE_WARN_NO_LS_ROUTER_AD_CFG

System Log Message	'router-advertisement' is not configured for interface <i>interface-name</i> , logical system: <i>logical-router-name</i> . It is configured on logical system: <i>logical-system-name</i>
Description	Router-advertisement is not configured for an interface (part of a logical system) having IPv6 vrrp config. Instead its configured on another logical system.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON

PARSE_WARN_NO_ROUTER_AD_CFG

System Log Message	'router-advertisement' is not configured for interface <i>interface-name</i>
Description	Router-advertisement is not configured for an interface having IPv6 vrrp config.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON

PARSE_WARN_PROXY_ARP_CFG_ERR

System Log Message	Cannot have more than one VRRP group on subnet <i>ip-address</i> when proxy arp is configured
Description	When proxy arp is configured, you cannot have more than one VRRP group configured on same subnet.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON

CHAPTER 88

PFE System Log Messages

This chapter describes messages with the **PFE** prefix. They are generated by the Packet Forwarding Engine controller, which manages packet forwarding functions.

PFE_ANALYZER_CFG_FAILED

System Log Message	Error in Analyzer <i>error-message</i> for index = <i>index</i> error-code = <i>error-code</i>
Description	The configuration analyzer terminated because an error occurred during the configuration.
Type	Error: An error occurred
Severity	error
Facility	ANY

PFE_ANALYZER_SHIM_CFG_FAILED

System Log Message	Error in Analyzer <i>error-message</i> for index = <i>index</i> error-code = <i>error-code</i>
Description	The configuration analyzer terminated because an error occurred while the chip was being programmed.
Type	Error: An error occurred
Severity	error
Facility	ANY

PFE_ANALYZER_TABLE_WRITE_FAILED

System Log Message	<i>index</i> Could not create analyzer <i>error-message</i> table
Description	The logical interfaces (ifl) index failed to configure the analyzer because of an error.
Type	Error: An error occurred
Severity	error
Facility	ANY

PFE_ANALYZER_TASK_FAILED

System Log Message	Following task failed : <i>error-message</i>
---------------------------	--

Description The task analyzer terminated because an error occurred during the task.

Type Error: An error occurred

Severity error

Facility ANY

PFE_CBF_UNSUPPORTED

System Log Message Internet Processor I does not support CoS-based forwarding

Description The Internet Processor I application-specific integrated circuit (ASIC) does not support class-of-service (CoS)-based forwarding (CBF).

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_PFE

PFE_COS_B2_ONE_CLASS

System Log Message COSMAN: classifier *classifier-id-new* for ifl *index* replaces classifier *classifier-id-old* still used

Description Only one classifier can be active on a B2-based FPC at any given time.

Type Error: An error occurred

Severity error

Facility LOG_PFE

PFE_COS_B2_UNSUPPORTED

System Log Message COSMAN: B2 FPC cannot support classifier type *classifier-type-name*

Description B2-based FPCs can only handle IP precedence classifiers. They do not support any other classifier.

Type Error: An error occurred

Severity error

Facility LOG_PFE

PFE_FW_DELETE_MISMATCH_ERR

System Log Message Instance mismatch for type (*installed-firewall-name* != *deleted-firewall-name*) ifl *logical-interface-index* family *protocol-family*

Description Before a firewall is deleted, it is sanity checked against what is installed in the forwarding topology. A mismatch was detected between the firewall to be deleted and the forwarding topology, and the delete operation was canceled.

Type Error: An error occurred

Severity error
Facility LOG_PFE

PFE_FW_IF_DIALER_ERR

System Log Message DFW: output *type (firewall-name)* on ifl *logical-interface-index* rejected, invalid interface

Description Firewalls that use the ipsec-sa action to forward traffic to an IP Security (IPSec) security association (SA) cannot be configured on the ES PIC that services the SA. That configuration creates traffic loops within the router and was probably unintended. The problematic filter was automatically removed from the indicated interface.

Type Error: An error occurred
Severity error
Facility LOG_PFE

PFE_FW_IF_INPUT_ERR

System Log Message DFW: input *type (firewall-name)* on ifl *logical-interface-index* rejected, invalid interface

Description Firewalls that use the ipsec-sa action to forward traffic to an IP Security (IPSec) security association (SA) cannot be configured on the ES PIC that services the SA. That configuration creates traffic loops within the router and was probably unintended. The problematic firewall was automatically removed from the indicated interface.

Type Error: An error occurred
Severity error
Facility LOG_PFE

PFE_FW_IF_OUTPUT_ERR

System Log Message DFW: output *type (firewall-name)* on ifl *logical-interface-index* rejected, invalid interface

Description Firewalls that use the ipsec-sa action to forward traffic to an IP Security (IPSec) security association (SA) cannot be configured on the ES PIC that services the SA. That configuration creates traffic loops within the router and was probably unintended. The problematic firewall was automatically removed from the indicated interface.

Type Error: An error occurred
Severity error
Facility LOG_PFE

PFE_FW_PSF_DELETE_MISMATCH_ERR

System Log Message Instance mismatch for *type (installed-firewall-name != deleted-firewall-name)* hardware label *index* family *protocol-family*

Description Before a postservice firewall is deleted, it is sanity checked against what is installed in the forwarding topology. A mismatch was detected between the firewall to be deleted and the forwarding topology, and the delete operation was canceled.

Type	Error: An error occurred
Severity	error
Facility	LOG_PFE

PFE_FW_SYSLOG_ETH

System Log Message	<i>FW: interface-name action destination-address source-address protocol-name (count packets)</i>
Description	An Ethernet frame matched against a stateless firewall filter with the indicated 'syslog' action (A = Accept, D = Discard, R = Reject).
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_PFE

PFE_FW_SYSLOG_IP

System Log Message	<i>FW: interface-name action protocol-name source-address destination-address source-port-or-type destination-port-or-code (count packets)</i>
Description	An IP packet matched against a stateless firewall filter with the indicated 'syslog' action (A = Accept, D = Discard, R = Reject).
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_PFE

PFE_FW_SYSLOG_IP6_GEN

System Log Message	<i>FW: interface-name action protocol-name source-address destination-address (count packets)</i>
Description	An IP version 6 (IPv6) packet matched against a stateless firewall filter with the indicated 'syslog' action (A = Accept, D = Discard, R = Reject).
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_PFE

PFE_FW_SYSLOG_IP6_ICMP

System Log Message	<i>FW: interface-name action protocol-name source-address destination-address type type code error-code (count packets)</i>
Description	An IP version 6 (IPv6) Internet Control Message Protocol (ICMP) packet matched against a stateless firewall filter with the indicated 'syslog' action (A = Accept, D = Discard, R = Reject).

Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_PFE

PFE_FW_SYSLOG_IP6_TCP_UDP

System Log Message FW: *interface-name action protocol-name source-address destination-address sport:source-port dport:destination-port (count packets)*

Description An IP version 6 (IPv6) Transmission Control Protocol/User Datagram Protocol (TCP/UDP) packet matched against a stateless firewall filter with the indicated 'syslog' action (A = Accept, D = Discard, R = Reject).

Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_PFE

PFE_MGCP_MEM_INIT_FAILED

System Log Message Failed to create memory pool for *error-message*

Description Failed to initialize the MGCP memory pool.

Type	Error: An error occurred
Severity	error
Facility	LOG_PFE

PFE_MGCP_REG_HDL_FAIL

System Log Message Failed to register *object-name* handle

Description Failed to register the handler with the external module.

Type	Error: An error occurred
Severity	error
Facility	LOG_PFE

PFE_NH_RESOLVE_THROTTLED

System Log Message Next-hop resolution requests from interface *logical-interface-index* throttled

Description The Packet Forwarding Engine throttled next-hop resolution requests from the indicated interface, because the high number of requests might constitute an attempted denial-of-service (DoS) attack. Examples of events that generate next-hop resolution requests include an attempt to forward a packet without an Address Resolution Protocol (ARP) entry and receiving a multicast data packet with no matching route. Normally, the Packet Forwarding Engine forwards the requests to the Routing Engine.

Type	Event: This message reports an event, not an error
-------------	--

Severity info

Facility LOG_PFE

PFE_SCCP_ADD_PORT_FAIL

System Log Message Failed to add SCCP ALG port to application definition table

Description Failed to add the SCCP port to the application definition table.

Type Error: An error occurred

Severity error

Facility LOG_PFE

PFE_SCCP_DEL_PORT_FAIL

System Log Message Failed to remove SCCP ALG port from application definition table

Description Failed to delete the SCCP port from application definition table.

Type Error: An error occurred

Severity error

Facility LOG_PFE

PFE_SCCP_REG_NAT_VEC_FAIL

System Log Message Failed to add SCCP ALG vector to flow module

Description Failed to register the SCCP vector with the flow module.

Type Error: An error occurred

Severity error

Facility LOG_PFE

PFE_SCCP_REG_RM_FAIL

System Log Message Failed to register SCCP client to Resource Manager

Description Failed to register the SCCP Resource Manager client.

Type Error: An error occurred

Severity error

Facility LOG_PFE

PFE_SCCP_REG_VSIP_FAIL

System Log Message Failed to register SCCP client to VoIP State IP port

Description Failed to register the SCCP client to VoIP State IP port.

Type Error: An error occurred

Severity error
Facility LOG_PFE

PFE_SCCP_RM_CLIENTID_FAIL

System Log Message Failed to get SCCP Resource Manager client identifier
Description Failed to get the SCCP Resource Manager client identifier.

Type Error: An error occurred
Severity error
Facility LOG_PFE

PFE_SCREEN_MT_CFG_ERROR

System Log Message failed to *operation* the screen config due to *error-message*
Description failed to change the configuration of screen module

Type Error: An error occurred
Severity error
Facility LOG_PFE

PFE_SCREEN_MT_CFG_EVENT

System Log Message [*operation*]: screen name - *context-name*
Description configuration of screen module is changed

Type Event: This message reports an event, not an error
Severity info
Facility LOG_PFE

PFE_SCREEN_MT_ZONE_BINDING_ERROR

System Log Message screen *index1* failed to apply to zone *index2* due to *reason*
Description failed to bind screen to zone

Type Error: An error occurred
Severity error
Facility LOG_PFE

PFE_SIP_MEM_INIT_FAILED

System Log Message Failed to create memory pool for *object-name*
Description Failed to create a memory pool for SIP.

Type Error: An error occurred

Severity error
Facility LOG_PFE

PFE_SIP_REG_HDL_FAIL

System Log Message Failed to register *object-name* handle
Description Failed to register the handler with the external module.

Type Error: An error occurred
Severity error
Facility LOG_PFE

CHAPTER 89

PFED System Log Messages

This chapter describes messages with the **PFED** prefix. They are generated by the Packet Forwarding Engine process, which gathers and reports Packet Forwarding Engine statistics.

PFED_NOTIFICATION_STATS_FAILED

System Log Message	Unable to retrieve notification statistics
Description	The Packet Forwarding Engine process (pfed) could not retrieve Packet Forwarding Engine notification statistics.
Type	Error: An error occurred
Severity	info
Facility	LOG_PFE

CHAPTER 90

PGCPD System Log Messages

This chapter describes messages with the **PGCPD** prefix. They are generated by the pgcpd process. This process decodes Packet Gateway Control Protocol (PGCP) messages that virtual packet gateways (VPG) receive from the packet gateway controller (PGC) and translates these messages to interprocess communication (IPC) messages.

PGCPD_SHUTDOWN

System Log Message	The pgcpd process shut down
Description	The packet gateway control process (pgcpd) state was shut down.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

PGCPD_STARTUP

System Log Message	The pgcpd process just started up
Description	The packet gateway control process (pgcpd) just started up
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

PGCPD_SWITCH_OVER

System Log Message	switch over
Description	Switch over from active to backup Routing Engine
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

CHAPTER 91

PING System Log Messages

This chapter describes messages with the **PING** prefix. They are generated by the ping command, which tests whether a remote machine is accessible across the network.

PING_EGRESS_JITTER_THRESH_EXCEED

System Log Message	pingCtlOwnerIndex = <i>test-owner</i> , pingCtlTestName = <i>test-name</i>
Description	The jitter for the egress trip time exceeded the configured threshold during the indicated test conducted by the indicated user.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

PING_EGRESS_STDDEV_THRESH_EXCEED

System Log Message	pingCtlOwnerIndex = <i>test-owner</i> , pingCtlTestName = <i>test-name</i>
Description	The standard deviation of the egress trip time exceeded the configured threshold during the indicated test conducted by the indicated user.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

PING_EGRESS_THRESHOLD_EXCEEDED

System Log Message	pingCtlOwnerIndex = <i>test-owner</i> , pingCtlTestName = <i>test-name</i>
Description	The egress trip time measured for a probe exceeded the configured threshold during the indicated test conducted by the indicated user.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

PING_INGRESS_JTR_THRESH_EXCEED

System Log Message	pingCtlOwnerIndex = <i>test-owner</i> , pingCtlTestName = <i>test-name</i>
Description	The jitter for the ingress trip time exceeded the configured threshold during the indicated test conducted by the indicated user.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

PING_INGRESS_STDDV_THRESH_EXCEED

System Log Message	pingCtlOwnerIndex = <i>test-owner</i> , pingCtlTestName = <i>test-name</i>
Description	The standard deviation of the ingress trip time exceeded the configured threshold during the indicated test conducted by the indicated user.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

PING_INGRESS_THRESHOLD_EXCEEDED

System Log Message	pingCtlOwnerIndex = <i>test-owner</i> , pingCtlTestName = <i>test-name</i>
Description	The ingress trip time measured for a probe exceeded the configured threshold during the indicated test conducted by the indicated user.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

PING_PROBE_FAILED

System Log Message	pingCtlOwnerIndex = <i>test-owner</i> , pingCtlTestName = <i>test-name</i>
Description	The number of successive probe failures exceeded the pingCtlTrapProbeFailureFilter threshold.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

PING_RTT_JTR_THRESH_EXCEED

System Log Message	pingCtlOwnerIndex = <i>test-owner</i> , pingCtlTestName = <i>test-name</i>
Description	The jitter for the round trip time exceeded the configured threshold during the indicated test conducted by the indicated user.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

PING_RTT_STDDV_THRESH_EXCEED

System Log Message pingCtlOwnerIndex = *test-owner*, pingCtlTestName = *test-name*
Description The standard deviation of the round trip time exceeded the configured threshold during the indicated test conducted by the indicated user.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

PING_RTT_THRESHOLD_EXCEEDED

System Log Message pingCtlOwnerIndex = *test-owner*, pingCtlTestName = *test-name*
Description The round trip time measured for a probe exceeded the configured threshold during the indicated test conducted by the indicated user.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

PING_TEST_COMPLETED

System Log Message pingCtlOwnerIndex = *test-owner*, pingCtlTestName = *test-name*
Description All probes were sent and the number of failed probes was less than the pingCtlTrapTestFailureFilter threshold.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

PING_TEST_FAILED

System Log Message pingCtlOwnerIndex = *test-owner*, pingCtlTestName = *test-name*
Description All probes were sent but the number of failed probes equaled or exceeded the pingCtlTrapTestFailureFilter threshold.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

PING_UNKNOWN_THRESH_TYPE_EXCEED

System Log Message	pingCtlOwnerIndex = <i>test-owner</i> , pingCtlTestName = <i>test-name</i>
Description	An unknown type of threshold event was reported during the indicated test conducted by the indicated user.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

CHAPTER 92

PKID System Log Messages

This chapter describes messages with the **PKID** prefix. They are generated by the Public Key Infrastructure process (pkid), which supports Public Key Infrastructure by maintaining keypairs, certificates and CRLs. It also provides a mechanism to authenticate and enroll certificates.

PKID_AFTER_KEY_GEN_SELF_TEST

System Log Message	Running FIPS self-tests after key generation
Description	Running FIPS self-tests for PRNG, HMAC-SHA, RSA, and DSA.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

PKID_CERT_BASIC_CNSTRS_INV_CA

System Log Message	Basic constraints field contains an invalid CA flag for the CA certificate <i>argument1</i>
Description	Certificate doesn't have valid CA flag.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

PKID_CERT_BASIC_CNSTRS_MISSING

System Log Message	Basic constraints field is missing for the CA certificate <i>argument1</i>
Description	Certificate has no basic constraints field.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

PKID_CERT_ID_LOOKUP_FAIL

System Log Message	Certificate chain does not contain certificate with ID <i>argument1</i> and Type <i>argument2</i>
---------------------------	---

Description Certificate chain doesn't contain certificate with valid ID. The IKE-ID must match with once of the certificate's ID.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

PKID_CERT_NOT_AFTER_FAIL

System Log Message Certificate *argument1* has expired, not valid after *argument2*

Description Certificate is expired. Get new certificate to continue.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

PKID_CERT_NOT_BEFORE_FAIL

System Log Message Certificate *argument1* is not valid until *argument2*

Description Certificate validity period is in future. Use the certificate after it becomes valid.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

PKID_CERT_SIGN_VERIFY_FAIL

System Log Message Signature verification failed for certificate *type-string*

Description Signature validation failed for the certificate. The certificate might be tampered.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

PKID_CORRUPT_CERT

System Log Message Certificate subject field does not match length: *error-message*

Description The certificate subject name and length are inconsistent.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

PKID_CRL_CERTIFICATE_REVOKED

System Log Message	Certificate <i>argument1</i> with serial number <i>argument2</i> is revoked
Description	Signature verification failed for CRL file received from CA server.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

PKID_CRL_CHECK_SKIPPED

System Log Message	CRL check skipped for certificate <i>argument1</i> with serial <i>argument2</i> due to CRL download failure
Description	Skipped CRL check as disable on-download-failure option is configured for the CA profile.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

PKID_CRL_DOWNLOAD_FAIL_LF

System Log Message	CRL download failed due to large file for CA <i>type-string</i> , next retry <i>user-seconds</i> seconds
Description	CRL file size has exceeded the allowed limit. Reduce CRL file size on CA server to download CRL successfully.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

PKID_CRL_DOWNLOAD_SUCCESS

System Log Message	CRL download successful for CA <i>type-string</i> , next refresh <i>user-seconds</i> seconds
Description	CRL downloaded from CA server. Next refresh interval is based on configured value or CRL expiry time, whichever is earlier.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

PKID_CRL_LOCAL_CERT_REVOKED

System Log Message	Local certificate <i>argument1</i> is revoked, subject <i>argument2</i> serial-number <i>argument3</i>
Description	Local certificate cannot be used for PKI based authentication as it is revoked by CA server or CA is unreachable. Please use new local certificate or make sure that CA server is reachable.

Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON

PKID_CRL_SIGNATURE_FAIL

System Log Message CRL signature verification failed for CA *type-string*
Description Signature verification failed for CRL file received from CA server.

Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON

PKID_FIPS_DSA_NOT_ALLOWED

System Log Message DSA *argument1 argument2* not loaded because the Digital Signature Algorithm (DSA) is not permitted in a FIPS-compliant system .
Description DSA key-pair or certificate not loaded because it is not FIPS compliant

Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON

PKID_FIPS_KAT_SUCCESS

System Log Message FIPS *test-name* Known Answer Test executed successfully
Description The FIPS Known Answer Test completed successfully.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

PKID_FIPS_RSA_TOO_WEAK

System Log Message RSA *argument1 argument2* not loaded because the modulus size (*argument3* bits) is not permitted in a FIPS-compliant system.
Description Weak RSA key-pair or certificate not loaded because it is not FIPS compliant

Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON

PKID_NO_CA_CERT

System Log Message CA Certificate for certificate *type-string* not found in local database

Description CA certificate for the local certificate is not present in local storage. Enroll CA certificate to continue.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

PKID_NO_KEYPAIR

System Log Message Keypair not found for local certificate *type-string*

Description Keypair must be generated for the local certificate. After generating keypair, enroll the local certificate to continue.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

PKID_NO_LOCAL_CERT

System Log Message Local certificate *type-string* is not enrolled

Description Local certificate is not present in storage. Enroll local certificate to continue.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

PKID_OCSP_CA_CERT_MISSING

System Log Message The OCSP response from responder *argument1* cannot be verified; the CA certificate is missing.

Description OCSP response cannot be verified, missing CA.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

PKID_OCSP_CONNECTION_FAILOVER

System Log Message The OCSP responder failed over from *argument1* to *argument2* because of a connection failure.

Description OCSP connection failed, failover next responder.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

PKID_OCSP_FALLBACK_TO_CRL

System Log Message The OCSP check was skipped. CRL is being used for revocation check for certificate *argument1*

Description Use CRL to check revocation status as OCSP responder is unreachable.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

PKID_OCSP_NONCE_CHECK_FAIL

System Log Message The nonce check failed for OCSP responder *argument1*.

Description Nonce check failed for OCSP response.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

PKID_OCSP_RESPONSE_INT_ERROR

System Log Message The OCSP responder *argument1* has an internal error.

Description Response from OCSP responder has internal error.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

PKID_OCSP_RESPONSE_MALFORMED

System Log Message The OCSP response from responder *argument1* is malformed.

Description Response from OCSP responder is malformed.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

PKID_OCSP_RESPONSE_SIGN_REQUIRED

System Log Message The OCSP request was rejected by responder *argument1* as it requires signed requests.

Description OCSP responder accepts signed requests only.

Type Event: This message reports an event, not an error

Severity error
Facility LOG_DAEMON

PKID_OCSP_RESPONSE_TRY_LATER

System Log Message The OCSP responder *argument1* is busy; try later.
Description OCSP responder expects to try revocation check later.

Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON

PKID_OCSP_RESPONSE_UNAUTHORIZED

System Log Message The OCSP responder *argument1* does not accept requests from unauthorized clients.
Description OCSP responder accepts requests from authorized clients.

Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON

PKID_OCSP_RESP_CA_CERT_MISSING

System Log Message The OCSP responder *argument1* certificate cannot be verified; the CA certificate is missing.
Description OCSP responder certificate verification failed, missing CA.

Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON

PKID_OCSP_RESP_CERT_REVOKED

System Log Message The revocation check failed for OCSP responder certificate, subject *argument1* serial-number *argument2*
Description The revocation check for OCSP responder certificate failed.

Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON

PKID_OCSP_RESP_CERT_VERIFY_FAIL

System Log Message The OCSP responder *argument1* certificate signature verification failed.
Description OCSP responder certificate verification failed.

Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON

PKID_OCSP_SIGN_VERIFY_FAIL

System Log Message The OCSP response signature verification failed for responder *argument1*
Description OCSP responder signature verification failed.

Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON

PKID_OCSP_SKIP_REVOCATION_CHECK

System Log Message The OCSP revocation check was skipped for certificate *argument1*
Description Skip OCSP revocation check as responder is unreachable.

Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON

PKID_PV_ASYM_KEYGEN

System Log Message Asymmetric key-pair (*error-message*) generation failure
Description An asymmetric key has failed to generate.

Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON

PKID_PV_CERT_DEL

System Log Message Certificate deletion has occurred for *type-string*
Description A certificate has been deleted.

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_DAEMON

PKID_PV_CERT_LOAD

System Log Message Certificate *type-string* has been successfully loaded
Description A certificate has been loaded.

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_DAEMON

PKID_PV_KEYPAIR_DEL

System Log Message Key-Pair deletion failed for *type-string*
Description Key-Pair deletion for a digital signature failed.

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_DAEMON

PKID_PV_KEYPAIR_GEN

System Log Message A *argument1* bit *argument2* key-Pair has been generated for *argument3*
Description Key-Pair for a digital signature is generated.

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_DAEMON

PKID_PV_OBJECT_READ

System Log Message A PKI object was read into memory fro *source-filename*
Description A PKI object was read from storage.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

PKID_SCEP_INV_DIGEST_ALG

System Log Message Enrollment failed as SCEP server response was signed with *argument1* digest, when client request was signed with *argument2* digest.
Description SCEP enrollment failed as server response was signed with wrong algorithm

Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON

PKID_SCEP_INV_ENCRYPT_ALG

System Log Message Enrollment failed as SCEP server response was encrypted with *argument1* algorithm, when client request was encrypted with *argument2* algorithm.

Description SCEP enrollment failed as server response was encrypted with wrong algorithm

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

PKID_UNABLE_TO_GET_CRL

System Log Message Failed to retrieve CRL from received file for CA *type-string*

Description Failed to retrieve CRL from received CRL file from CA server. Check the CRL file format.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

CHAPTER 93

PPMD System Log Messages

This chapter describes messages with the **PPMD** prefix. They are generated by the periodic packet management process (ppmd), which maintains routing protocol adjacencies for the routing protocol process (rpd).

PPMD_ASSERT_SOFT

System Log Message	Soft assertion failed at line <i>line-number</i> in file ' <i>source-filename</i> ' with error " <i>message</i> ", but ppmd with PID <i>pid</i> continued running
Description	The source code for the periodic package management process (ppmd) includes internal self-consistency checks. As the ppmd process with the indicated process ID (PID) executed the binary compiled from the indicated source file, a check failed at the indicated line number in the file. The ppmd process created a diagnostic core file for analysis by technical support personnel and continued to run.
Type	Error: An error occurred
Severity	error
Facility	LOG_NEWS
Cause	An internal software failure occurred.
Action	Examine the messages that immediately follow this message in the system log for information about possible causes. Contact a technical support representative, and be ready to provide the list of messages and the diagnostic core file, if requested. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB19021 .

PPMD_MIRROR_ERROR

System Log Message	Unable to establish BFD mirror connection between Routing Engines: <i>error-message</i>
Description	The PPMD could not establish the mirror connection between the master and backup Routing Engines.
Type	Error: An error occurred
Severity	warning
Facility	LOG_NEWS

Cause The master and backup Routing Engines are running incompatible versions of the Junos OS.

Action Update the Junos OS to compatible versions on the master and backup Routing Engines.

PPMD_OPEN_ERROR

System Log Message *function-name: open error on pipe to protocol-name (error-message)*

Description The periodic packet management process (ppmd) could not initialize the indicated protocol.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

Action Contact your technical support representative.

PPMD_READ_ERROR

System Log Message Read error on pipe from *protocol-name: reason (error-message)*

Description The periodic packet management process (ppmd) could not read a message on a pipe for the indicated protocol.

Type Error: An error occurred

Severity info

Facility LOG_NEWS

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB19022>.

PPMD_WRITE_ERROR

System Log Message *function-name: write error on pipe to protocol-name (error-message)*

Description The periodic packet management process (ppmd) could not write a message on a pipe for the indicated protocol.

Type Error: An error occurred

Severity error

Facility LOG_NEWS

Action Contact your technical support representative.

PPPD System Log Messages

This chapter describes messages with the **PPPD** prefix. They are generated by the Point-to-Point Protocol (PPP) process (pppd), which processes packets that use PPP.

PPPD_AUTH_CREATE_FAILED

System Log Message	Unable to allocate authentication handle: <i>error-message</i>
Description	The Point-to-Point Protocol process (pppd) could not allocate an authentication object, for the indicated reason.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH

PPPD_CHAP_AUTH_IN_PROGRESS

System Log Message	Interface <i>interface-name</i> received response ' <i>operation</i> ' with CHAP ID <i>message-id</i> , but was still authenticating previous response
Description	The Point-to-Point Protocol process (pppd) received another Challenge Handshake Authentication Protocol (CHAP) response from a peer while authenticating a previous CHAP response sent by that peer. The peer is resending CHAP responses faster than the pppd process can process them.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH

PPPD_CHAP_GETHOSTNAME_FAILED

System Log Message	<i>interface-name</i> : Unable to obtain hostname for outgoing CHAP message: <i>error-message</i>
Description	The Point-to-Point Protocol process (pppd) could not obtain the hostname needed to fill in the 'Name' field in an outgoing CHAP packet.
Type	Error: An error occurred
Severity	error

Facility LOG_AUTH

PPPD_CHAP_INVALID_IDENTIFIER

System Log Message Interface *interface-name* received '*operation*' message with CHAP ID *message-id* instead of expected ID *expected-value*

Description The Point-to-Point Protocol process (pppd) received a Challenge Handshake Authentication Protocol (CHAP) message from a peer that included the indicated message identifier, which did not match the indicated expected value.

Type Error: An error occurred

Severity info

Facility LOG_AUTH

PPPD_CHAP_INVALID_OPCODE

System Log Message *interface-name*: received invalid operation code *operation* (type *operation-code*, CHAP ID *message-id*)

Description The Point-to-Point Protocol process (pppd) received a Challenge Handshake Authentication Protocol (CHAP) message that included the indicated operation code, which is invalid.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

PPPD_CHAP_LOCAL_NAME_UNAVAILABLE

System Log Message Unable to determine value for 'Name' in outgoing CHAP packet

Description The Point-to-Point Protocol process (pppd) could not determine the value needed to fill in the 'Name' field in an outgoing Challenge Handshake Authentication Protocol (CHAP) packet, because either the local name was not specified or pppd could not determine the hostname.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

PPPD_CHAP_OPERATION_UNEXPECTED

System Log Message *interface-name*: unexpected operation type *operation* (CHAP ID *message-id*)

Description The Challenge Handshake Authentication Protocol (CHAP) message with the indicated identifier had the indicated operation type, which the Point-to-Point Protocol process (pppd) did not expect.

Type Error: An error occurred

Severity info
Facility LOG_AUTH

PPPD_CHAP_REPLAY_ATTACK_DETECTED

System Log Message *interface-name*: received operation with CHAP ID *message-id*, which is identical to an outstanding challenge. Peer is trying to exhort response value.

Description During an exchange of authentication messages, a peer responded to a challenge message from the Point-to-Point Protocol process (pppd) by returning the same message. The pppd process did not respond to the peer, because doing so would provide the answer to the original challenge. The peer must provide the answer on its own for authentication to succeed.

Type Error: An error occurred
Severity error
Facility LOG_AUTH

PPPD_EVLIB_CREATE_FAILURE

System Log Message Unable to create event context: *error-message*

Description The Point-to-Point Protocol process (pppd) could not create a context for handling asynchronous events, for the indicated reason.

Type Error: An error occurred
Severity error
Facility LOG_AUTH

PPPD_LOCAL_CREATE_FAILED

System Log Message Unable to allocate LOCAL module handle: *error-message*

Description The Point-to-Point Protocol process (pppd) attempted to allocate a locally configured 'password' authentication module as part of its authentication sequence. The allocation failed.

Type Error: An error occurred
Severity error
Facility LOG_AUTH

PPPD_MEMORY_ALLOCATION_FAILURE

System Log Message Unable to allocate memory for object *object-name*: *error-message*

Description The Point-to-Point Protocol process (pppd) could not allocate memory from the heap for the indicated object.

Type Error: An error occurred

Severity	error
Facility	LOG_AUTH
Action	Contact your technical support representative.

PPPD_PAP_GETHOSTNAME_FAILED

System Log Message	Unable to obtain hostname for PAP message sent from interface <i>interface-name</i> : <i>error-message</i>
Description	The Point-to-Point Protocol process (pppd) could not obtain the hostname it needed to fill in the 'Name' field in an outgoing Password Authentication Protocol (PAP) packet sent from the indicated interface.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH

PPPD_PAP_INVALID_IDENTIFIER

System Log Message	Interface <i>interface-name</i> received ' <i>operation</i> ' message with PAP ID <i>message-id</i> instead of expected ID <i>expected-value</i>
Description	The Point-to-Point Protocol process (pppd) received a Password Authentication Protocol (PAP) message from a peer that included the indicated identifier, which did not match the indicated expected value.
Type	Error: An error occurred
Severity	info
Facility	LOG_AUTH

PPPD_PAP_INVALID_OPCODE

System Log Message	Interface <i>interface-name</i> received ' <i>operation</i> ' message with PAP ID <i>message-id</i> and invalid operation code <i>operation-code</i>
Description	The Point-to-Point Protocol process (pppd) received a Password Authentication Protocol (PAP) message from a peer that included the indicated operation code, which is invalid.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH

PPPD_PAP_LOCAL_PASSWORD_UNAVAIL

System Log Message	Unable to determine value for 'Password' in outgoing PAP packet
Description	The Point-to-Point Protocol process (pppd) could not determine the value to write in the 'Password' field in an outgoing Password Authentication Protocol (PAP) packet.

Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH
Cause	The local password was not defined for the local hostname.

PPPD_PAP_OPERATION_UNEXPECTED

System Log Message	<i>interface-name</i> : unexpected operation type <i>operation</i> (PAP ID <i>message-id</i>)
Description	The Point-to-Point Protocol process (pppd) received a Password Authentication Protocol (PAP) message with the indicated identifier and operation type. The operation type was not valid.
Type	Error: An error occurred
Severity	info
Facility	LOG_AUTH

PPPD_POOL_ADDRESSES_EXHAUSTED

System Log Message	No addresses available in pool " <i>pool-name</i> " to assign to remote peer on interface <i>interface-name</i>
Description	The Point-to-Point Protocol process (pppd) could not assign an address from the indicated address pool to the remote peer on the indicated interface, because there were no more addresses available in the pool.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH
Action	Increase the number of addresses in the address pool.

PPPD_RADIUS_ADD_SERVER_FAILED

System Log Message	Unable to add RADIUS server <i>radius-server</i> for profile <i>access-profile</i> : <i>error-message</i>
Description	The Point-to-Point Protocol process (pppd) could not add the indicated RADIUS server for the indicated access profile.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH

PPPD_RADIUS_ALLOC_PASSWD_FAILED

System Log Message	Unable to allocate RADIUS password of size <i>size</i> : <i>error-message</i>
---------------------------	---

Description	The Point-to-Point Protocol process (pppd) could not allocate space for a temporary Challenge Handshake Authentication Protocol (CHAP) RADIUS password of the indicated size.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH

PPPD_RADIUS_CREATE_FAILED

System Log Message	Unable to allocate RADIUS module handle: <i>error-message</i>
Description	The Point-to-Point Protocol process (pppd) attempted to allocate a RADIUS authentication module as part of its authentication sequence. The allocation failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH

PPPD_RADIUS_CREATE_REQ_FAILED

System Log Message	Unable to create RADIUS access request message: <i>error-message</i>
Description	The Point-to-Point Protocol process (pppd) could not create an access request message to send to the RADIUS server.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH

PPPD_RADIUS_GETADDRINFO_FAILED

System Log Message	Unable to resolve radius-sever address: <i>error-message</i>
Description	The Point-to-Point Protocol process (pppd) could not resolve radius-server address configured.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH

PPPD_RADIUS_GETHOSTNAME_FAILED

System Log Message	Unable to obtain hostname for outgoing RADIUS message: <i>error-message</i>
Description	The Point-to-Point Protocol process (pppd) could not obtain the hostname it needed to fill in the PPP_IDENTIFIER field in an outgoing RADIUS message.
Type	Error: An error occurred

Severity error
Facility LOG_AUTH

PPPD_RADIUS_MESSAGE_UNEXPECTED

System Log Message Unknown response from RADIUS server: *return-value*

Description The RADIUS authentication module for the Point-to-Point Protocol process (pppd) received a message from the RADIUS server that it could not process.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

PPPD_RADIUS_NO_VALID_SERVERS

System Log Message Unable to find valid RADIUS server for profile *access-profile*

Description The Point-to-Point Protocol process (pppd) could not access a valid RADIUS server to use for the indicated access profile.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

PPPD_RADIUS_OPEN_FAILED

System Log Message rad_auth_open failed: *error-message*

Description The Point-to-Point Protocol process (pppd) could not create a RADIUS object handle, which it uses to communicate with the RADIUS server.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

PPPD_RADIUS_ROUTE_INST_ENOENT

System Log Message Ignored RADIUS server *radius-server* for profile *access-profile* because routing instance *routing-instance* did not exist

Description The indicated routing instance, which the Point-to-Point Protocol process (pppd) uses for routing of RADIUS packets, was not defined.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_AUTH

Cause The process of adding the required routing instance was still in progress when the message was logged.

Action None required. Authentication with the indicated RADIUS server is automatically reattempted, and can succeed when the interface exists.

CHAPTER 95

PROFILER System Log Messages

This chapter describes messages with the **PROFILER** prefix. They are generated by the profiler service process (profilerd) which captures accurate and granular detail of the traffic pattern over a specific time period. The profiler process provides details on the threats are encountered by the network as well as details about the mix of application traffic.

PROFILER_RECONFIGURE_SIGHUP

System Log Message	SIGHUP - re-reading configuration
Description	In response to a SIGHUP signal, the profiler service process (profilerd) read its configuration from the configuration database
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

RDD System Log Messages

This chapter describes messages with the **RDD** prefix. They are generated by the redundant interfaces process (rdd), which manages redundant interfaces when they are configured on Adaptive Services PICs.

RDD_EVLIB_CREATE_FAILURE

System Log Message	evCreate failed (<i>error-message</i>)
Description	The redundant interfaces process (rdd) could not create a context used for handling all asynchronous events (such as timers and message availability).
Type	Error: An error occurred
Severity	emergency
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB19023 .

RDD_IFDEV_ADD_FAILURE

System Log Message	<i>function-name</i> : unable to add interface device <i>interface-name</i> (<i>error-message</i>)
Description	The redundant interfaces process (rdd) could not create an interface device because an error occurred during the indicated call to the routing socket library.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

RDD_IFDEV_DELETE_FAILURE

System Log Message	<i>function-name</i> : rtslib delete operation failed for interface device <i>interface-name</i> (<i>error-message</i>)
Description	The redundant interfaces process (rdd) could not delete an interface device because an error occurred during the indicated call to the routing socket library.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

RDD_IFDEV_GET_FAILURE

System Log Message *function-name*: rtslib get operation failed for interface device *interface-name* (*error-message*)

Description The redundant interfaces process (rdd) could not get an interface device because an error occurred during the indicated call to the routing socket library.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

RDD_IFDEV_INCOMPATIBLE_REVERT

System Log Message *function-name*: did not revert *rsp-interface-name* back to primary interface *primary-interface-name*; PIC is incompatible with secondary

Description The redundant interfaces process (rdd) tried to migrate service processing for the indicated redundant interface from the secondary interface back to the indicated primary interface. The attempt failed because the Adaptive Services (AS) Physical Interface Cards (PICs) that house the primary and secondary interfaces are not compatible.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

RDD_IFDEV_INCOMPATIBLE_SWITCH

System Log Message Unable to switch *rsp-interface-name* to secondary interface *secondary-interface-name*; PIC is incompatible with primary

Description The redundant interfaces process (rdd) tried to migrate service processing for the indicated redundant interface from the primary interface to the indicated secondary interface. The attempt failed because the Adaptive Services (AS) Physical Interface Cards (PICs) that house the primary and secondary interfaces are not compatible.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

RDD_IFDEV_RETRY_NOTICE

System Log Message	<i>function-name</i> : repeated attempt to add interface device <i>interface-name</i> failed (<i>error-message</i>)
Description	The redundant interfaces process (rdd) tried repeatedly to create the indicated interface device, but the attempts failed. After generating this message, rdd waited a while for resources to free up and tried again.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	Necessary resources might have been unavailable. They should become available soon.

RDD_NEW_INTERFACE_STATE

System Log Message	Event <i>event-name</i> changed state of interface <i>interface-name</i> from ' <i>old-state</i> ' to ' <i>new-state</i> '
Description	The indicated event on the indicated redundant interface changed the interface state as indicated.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

RMOPD System Log Messages

This chapter describes messages with the **RMOPD** prefix. They are generated by the Simple Network Management Protocol (SNMP) remote operations process (rmopd), which services SNMP requests for execution of ping and traceroute operations.

RMOPD_ADDRESS_MULTICAST_INVALID

System Log Message	Multicast address is not allowed
Description	When a Simple Network Management Protocol (SNMP) client requests a remote operation, it can specify the addresses of the source and target hosts for the operation. A request failed because the client specified a multicast address for either or both the source and target hosts.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

RMOPD_ADDRESS_SOURCE_INVALID

System Log Message	Source address invalid: <i>error-message</i>
Description	When a Simple Network Management Protocol (SNMP) client requests a remote operation, it can specify the address to use as the source host for the operation, along with the corresponding address type (such as IP version 4 [IPv4]). Either the specified address was invalid because it did not match the specified address type, or the address could not be resolved.
Type	Error: An error occurred
Severity	notice
Facility	LOG_DAEMON

RMOPD_ADDRESS_STRING_FAILURE

System Log Message	Unable to convert numeric address to string: <i>error-message</i>
Description	The remote Simple Network Management Protocol (SNMP) operations process (rmopd) could not convert a numeric host address to the corresponding hostname text string.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

RMOPD_ADDRESS_TARGET_INVALID

System Log Message rmop_util_set_address status message: *error-message*

Description When a Simple Network Management Protocol (SNMP) client requests a remote operation, it must specify the address of the target host along with the corresponding address type (such as IP version 4 [IPv4]). Either the specified address was invalid because it did not match the specified address type, or the address could not be resolved.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

RMOPD_ICMP_ADDR_TYPE_UNSUPPORTED

System Log Message Only IPv4 source address is supported

Description When a Simple Network Management Protocol (SNMP) client requests a remote operation, it can specify the address type (such as IP version 4 [IPv4]) of the source and target hosts for the operation. The client specified an unsupported address type.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

RMOPD_IFINDEX_NOT_ACTIVE

System Log Message ifindex: *snmp-interface-index*

Description When a Simple Network Management Protocol (SNMP) client requests a remote operation, it can specify which interface to use as the source host address, identifying it by either its numerical index or its name. The indicated index was invalid because it represents an inactive interface.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

RMOPD_IFINDEX_NO_INFO

System Log Message No information for *snmp-interface-index*, message: *error-message*

Description When a Simple Network Management Protocol (SNMP) client requests a remote operation, it can specify which interface to use as the source host address, identifying it

by either its numerical index or its name. The SNMP remote operations process (rmopd) could not find any information about the interface with the indicated index.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

RMOPD_IFNAME_NOT_ACTIVE

System Log Message ifname: *interface-name*

Description When a Simple Network Management Protocol (SNMP) client requests a remote operation, it can specify which interface to use as the source host address, identifying it by either its numerical index or its name. The indicated name was invalid because it represents an inactive interface.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

RMOPD_IFNAME_NO_INFO

System Log Message No information for *interface-name*, message: *error-message*

Description When a Simple Network Management Protocol (SNMP) client requests a remote operation, it can specify which interface to use as the source host address, identifying it by either its numerical index or its name. The SNMP remote operations process (rmopd) could not find any information about the interface with the indicated name.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

RMOPD_ROUTING_INSTANCE_NO_INFO

System Log Message No information for routing instance *routing-instance*: *error-message*

Description The indicated routing instance does not exist, so the Simple Network Management Protocol (SNMP) remote operations process (rmopd) could not retrieve information about it.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

RMOPD_TRACEROUTE_ERROR

System Log Message Message: *error-message*

Description The traceroute application reported the indicated error message to the Simple Network Management Protocol (SNMP) remote operations process (rmopd).

Type Error: An error occurred

Severity notice

Facility LOG_DAEMON

CHAPTER 98

RPD System Log Messages

This chapter describes messages with the **RPD** prefix. They are generated by the routing protocol process (rpd) which controls the routing protocols that run on the router. This process starts all the configured routing protocols and handles all the routing messages. It maintains one or more routing tables, which consolidate the routing information learned from all routing protocols. From this routing information, the routing protocol process determines the active routes to network destinations and installs these routes into the Routing Engine's forwarding table. Finally, it implements routing policy, which allows you to control the routing information that is transferred between the routing protocols and the routing table.



NOTE: When an interface goes down, individual RPD_IGMP_LEAVE and RPD_MLD_LEAVE messages are no longer generated per group or per host. Instead, a single message (such as RPD_IGMP_ALL_SUBSCRIBERS_DELETED) is generated for the interface.

RPD_AMT_CFG_ADDR_FMLY_INVALID

System Log Message	Valid address family information is required
Description	An invalid address family value was encountered while parsing AMT configuration.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	ANY
Action	Modify the configuration statement to use a valid value.

RPD_AMT_CFG_ANYCAST_INVALID

System Log Message	An invalid anycast-prefix is configured
Description	An invalid anycast prefix was encountered while parsing AMT configuration.
Type	Event: This message reports an event, not an error
Severity	warning

Facility	ANY
Action	Modify the configuration statement to use a valid value.

RPD_AMT_CFG_ANYCAST_MCAST

System Log Message	Anycast-prefix <i>route-prefix</i> cannot be a multicast address
Description	A multicast address cannot be configured as the anycast-prefix
Type	Event: This message reports an event, not an error
Severity	warning
Facility	ANY
Action	Modify the configuration statement to use a valid value.

RPD_AMT_CFG_LOC_ADDR_INVALID

System Log Message	An invalid local-address is configured
Description	An invalid local address was encountered while parsing AMT configuration.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	ANY
Action	Modify the configuration statement to use a valid value.

RPD_AMT_CFG_LOC_ADDR_MCAST

System Log Message	Local-address <i>route-prefix</i> cannot be a multicast address
Description	A multicast address cannot be configured as the local-address.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	ANY
Action	Modify the configuration statement to use a valid value.

RPD_AMT_CFG_PREFIX_LEN_SHORT

System Log Message	Prefix length <i>prefix-length</i> is too short for prefix <i>route-prefix</i>
Description	The prefix length for the indicated prefix is too short and it has a non-zero host portion. Excess host bits will be ignored.
Type	Event: This message reports an event, not an error
Severity	warning

Facility ANY

RPD_AMT_CFG_RELAY_INVALID

System Log Message Invalid relay information is configured

Description Invalid relay configuration was encountered while parsing AMT configuration.

Type Event: This message reports an event, not an error

Severity warning

Facility ANY

Action Modify the configuration statement to use a valid value.

RPD_AMT_RELAY_DISCOVERY

System Log Message AMT relay discovery message from gateway *destination-address* port *destination-port* at *time*

Description AMT relay discovery event.

Type Event: This message reports an event, not an error

Severity info

Facility ANY

RPD_AMT_TUNNEL_CREATE

System Log Message Tunnel created between gateway *destination-address* port *destination-port* relay *source-address* port *source-port* on interface *interface-name* at *time*

Description AMT tunnel create event.

Type Event: This message reports an event, not an error

Severity info

Facility ANY

RPD_AMT_TUNNEL_DELETE

System Log Message Tunnel deleted between gateway *destination-address* port *destination-port* relay *source-address* port *source-port* on interface *interface-name* at *time*

Description AMT tunnel delete event.

Type Event: This message reports an event, not an error

Severity info

Facility ANY

RPD_AMT_UCAST_STRM_LMT_EXCEEDED

System Log Message	AMT ucast stream cnt exceeded max ucast streamlimit and this should not have happened
Description	unicast stream limit cannot exceed the maximum unicast stream limit configured. This should not have happened.
Type	Event: This message reports an event, not an error
Severity	error
Facility	ANY

RPD_BGP_CFG_ADDR_INVALID

System Log Message	Invalid <i>argument</i> address <i>ip-address</i>
Description	An invalid local or neighbor address was encountered while parsing BGP configuration.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	Modify the configuration statement to use a valid value.

RPD_BGP_CFG_LOCAL_ASNUM_WARN

System Log Message	local as-number cannot be set to confederation as-number <i>data-id</i> , statement ignored
Description	Local autonomous-system number cannot be set to the confederation autonomous-system number. Statement will be ignored.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_BGP_NEIGHBOR_LLST_EXPIRED

System Log Message	<i>peer-name</i> : Long-lived stale timer expired for <i>nlri-type</i> nlri (instance <i>instance</i>) -- purging stale routes
Description	The graceful restart long-lived stale timer (LLST) expired for a peer. Routes from that peer that were previously held in Long-Lived Stale state will now be purged.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_BGP_NEIGHBOR_STATE_CHANGED

System Log Message	BGP peer <i>peer-name</i> changed state from <i>old-state</i> to <i>new-state</i> (event <i>event-type</i>) (instance <i>instance</i>)
Description	During BGP negotiation with the local router, the state of the indicated BGP neighbor (peer) changed as indicated. The ESTABLISHED state is the final state in the neighbor negotiation.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	For more information, see KB19051.

RPD_DYN_CFG_BUSY_SIGNAL_FAILED

System Log Message	Dynamic config <i>action</i> busy signal failed: <i>error-message</i>
Description	The routing protocol process (rpd) failed to notify the dynamic configuration clients about its availability to process the dynamic configuration requests.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB19053 .

RPD_DYN_CFG_GET_PROFILE_FAILED

System Log Message	Get dynamic profiles failed: <i>error-code</i>
Description	The routing protocol process (rpd) tried to load a profile from the database and failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

RPD_DYN_CFG_GET_PROF_NAME_FAILED

System Log Message	Get profile name for session <i>client-session-id</i> failed: <i>error-code</i>
Description	The routing protocol process (rpd) tried to get the profile name from the session snapshot and failed.
Type	Error: An error occurred
Severity	error

Facility LOG_DAEMON

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB19054>.

RPD_DYN_CFG_GET_SES_STATE_FAILED

System Log Message Get session state for session *client-session-id* failed: *error-code*

Description The routing protocol process (rpd) failed to get the session state from the session snapshot.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB19056>.

RPD_DYN_CFG_GET_SES_TYPE_FAILED

System Log Message Get session type for session *client-session-id* failed: *error-code*

Description The routing protocol process (rpd) tried to get the session type from the session snapshot and failed.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

RPD_DYN_CFG_GET_SNAPSHOT_FAILED

System Log Message Get session id *client-session-id* snapshot failed: *error-code*

Description The routing protocol process (rpd) tried to load client session data from the database and failed.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB19057>.

RPD_DYN_CFG_PDB_CLOSE_FAILED

System Log Message Failed to close profile database: *error-code*

Description The routing protocol process (rpd) tried to close the profile database and failed.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action For more information, see
<http://kb.juniper.net/InfoCenter/index?page=content&id=KB19058>.

RPD_DYN_CFG_PDB_OPEN_FAILED

System Log Message Failed to open profile database: *error-code*

Description The routing protocol process (rpd) tried to open the profile database and failed.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action For more information, see
<http://kb.juniper.net/InfoCenter/index?page=content&id=KB19059>.

RPD_DYN_CFG_REGISTER_FAILED

System Log Message Dynamic config registration failed: *error-message*

Description The routing protocol process (rpd) tried to register with the dynamic configuration subsystem and failed.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action For more information, see
<http://kb.juniper.net/InfoCenter/index?page=content&id=KB19061>.

RPD_DYN_CFG_REQUEST_ACK_FAILED

System Log Message Failed to ack request *data-id*: *error-code*

Description The routing protocol process (rpd) tried to acknowledge a dynamic configuration request and failed.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action For more information, see
<http://kb.juniper.net/InfoCenter/index?page=content&id=KB19062>.

RPD_DYN_CFG_RESPONSE_SLOW

System Log Message Dynamic config response for session id *client-session-id* took *system-seconds* seconds

Description The routing protocol process (rpd) is responding slowly to dynamic config requests.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

RPD_DYN_CFG_SCHEMA_OPEN_FAILED

System Log Message Could not open configuration schema: *error-message*

Description The routing protocol process (rpd) tried to open the configuration schema and failed.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action For more information, see
<http://kb.juniper.net/InfoCenter/index?page=content&id=KB19063>.

RPD_DYN_CFG_SES_RECOVERY_FAILED

System Log Message Recovery of session *client-session-id* failed

Description The routing protocol process (rpd) tried to recover a session and failed.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative. For more information, see
<http://kb.juniper.net/InfoCenter/index?page=content&id=KB19066>.

RPD_DYN_CFG_SET_CONTEXT_FAILED

System Log Message Set dynamic config context for profile *profile-name* session *client-session-id* failed

Description The routing protocol process (rpd) tried to set up the dynamic configuration context and failed.

Type Error: An error occurred

Severity error
Facility LOG_DAEMON

RPD_DYN_CFG_SMID_RECOVERY_FAILED

System Log Message Dynamic config send recovery complete failed: *error-code*
Description The routing protocol process (rpd) tried to send recovery complete to SMID and failed.
Type Error: An error occurred
Severity error
Facility LOG_DAEMON

RPD_DYN_CFG_SMID_REG_FAILED

System Log Message Failed to open session database: *error-code*
Description The routing protocol process (rpd) tried to register with SMID and failed.
Type Error: An error occurred
Severity info
Facility LOG_DAEMON

RPD_DYN_CFG_SMID_UNREG_FAILED

System Log Message Failed to unregister with SMID: *error-code*
Description The routing protocol process (rpd) tried to unregister with SMID and failed.
Type Error: An error occurred
Severity error
Facility LOG_DAEMON

RPD_ESIS_ADJDOWN

System Log Message ES-IS lost *adjacency-type* adjacency to *neighbor-nsap-netn* on *interface-name*, reason: *reason*
Description An ES-IS adjacency with the indicated neighboring router was terminated. The local router no longer exchanges routing information with, or directs traffic to, the neighboring router.
Type Event: This message reports an event, not an error
Severity notice
Facility LOG_DAEMON
Cause The communication path to the neighboring router was disrupted, a protocol error occurred, or the neighboring router was powered down.

RPD_ESIS_ADJUP

System Log Message	ES-IS new <i>adjacency-type</i> adjacency to <i>neighbor-nsap-netn</i> on <i>interface-name</i>
Description	An ES-IS adjacency was established with the indicated neighboring router. The local router can now exchange information with it.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

RPD_FEC129_AII_COLLISION

System Log Message	Attachment-individual-identifier <i>attachment-individual-identifier</i> in VPN <i>vpn-name</i> learned from PE <i>peer-address</i> with RD <i>route-discriminator</i> is also configured locally
Description	The remote provider edge (PE) router with the indicated address which is a member of the indicated virtual private network (VPN) advertised an attachment individual identifier (AII), but the AII is already associated with a local site.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

RPD_FEC129_AII_COLLISION_CLEARED

System Log Message	Attachment-individual-identifier collision cleared for All <i>attachment-individual-identifier</i> in VPN <i>vpn-name</i>
Description	A collision between two attachment individual identifiers (AII) with the indicated value has been cleared for the indicated virtual private network (VPN).
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

RPD_FEC129_REMOTE_AII_COLLISION

System Log Message	Attachment-individual-identifier <i>attachment-individual-identifier</i> in VPN <i>vpn-name</i> learned from PE <i>peer-address</i> with RD <i>route-discriminator</i> was also learned from PE <i>neighbor-address</i> with RD <i>route-discriminator2</i>
Description	Two provider edge (PE) routers which are members of the the indicated virtual private network (VPN) are both configured with the same attachment-individual-identifier (AII). The identities of the two PEs are indicated by the IP addresses and first and second route discriminators.
Type	Event: This message reports an event, not an error
Severity	error

Facility LOG_DAEMON

RPD_IFD_INDEXCOLLISION

System Log Message Physical interface collision -- same name, different index (new *new-interface-name new-index* old *old-interface-name old-value*)

Description The routing protocol process (rpd) received a message from the kernel in which the numerical index associated with the indicated interface name differed from the index-to-name mapping maintained by rpd.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause It is possible that rpd discarded some interface messages from the kernel without processing them because it received more messages than it could handle. It will recover.

RPD_IFD_NAMECOLLISION

System Log Message Physical interface collision -- different name, same index (new *new-interface-name new-index*, old *old-interface-name old-value*)

Description The routing protocol process (rpd) received a message from the kernel in which the name associated with the indicated numerical interface index differed from the name-to-index mapping maintained by rpd.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause It is possible that rpd discarded some interface messages from the kernel without processing them because it received more messages than it could handle. It will recover.

RPD_IFL_INDEXCOLLISION

System Log Message Logical interface collision -- same name, different index (new *new-interface-name new-index* old *old-interface-name old-value*)

Description The routing protocol process (rpd) received a message from the kernel in which the numerical index associated with the indicated interface name differed from the index-to-name mapping maintained by rpd.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause It is possible that rpd discarded some interface messages from the kernel without processing them because it received more messages than it could handle. It will recover.

RPD_IFL_NAMECOLLISION

System Log Message	Logical interface collision -- different name, same index (new <i>new-interface-name new-index</i> , old <i>old-interface-name old-value</i>)
Description	The routing protocol process (rpd) received a message from the kernel in which the name associated with the indicated numerical interface index differed from the name-to-index mapping maintained by rpd.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	It is possible that rpd discarded some interface messages from the kernel without processing them because it received more messages than it could handle. It will recover.

RPD_IGMP_ACCOUNTING_OFF

System Log Message	<i>interface-name time</i>
Description	Internet Group Management Protocol (IGMP) accounting for the indicated interface was disabled at the indicated time.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

RPD_IGMP_ACCOUNTING_ON

System Log Message	<i>interface-name time</i>
Description	Internet Group Management Protocol (IGMP) accounting for the indicated interface was enabled at the indicated time.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

RPD_IGMP_ALL_SUBSCRIBERS_DELETED

System Log Message	All IGMP subscribers on interface <i>interface-name</i> deleted at <i>time</i> because the interface is down
Description	All IGMP subscribers have been deleted because the interface is down.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

RPD_IGMP_CFG_CREATE_ENTRY_FAILED

System Log Message	Could not create entry for <i>entry</i> .
Description	Internet Group Management Protocol (IGMP) failed to create the indicated configuration entry. The configuration request failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

RPD_IGMP_CFG_GROUP_OUT_OF_RANGE

System Log Message	The combination of group-count <i>count</i> and group-increment <i>ip-address</i> causes some of the groups out of range.
Description	The configuration request failed because the indicated configuration object contained a group that is out of range.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Modify configuration statement to use a valid value.

RPD_IGMP_CFG_INVALID_VALUE

System Log Message	The <i>object-name</i> configuration object <i>identifier</i> field has an invalid value of <i>value</i>
Description	The configuration request failed because the indicated configuration object contained the indicated invalid value.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Modify configuration statement to use a valid value.

RPD_IGMP_CFG_SOURCE_OUT_OF_RANGE

System Log Message	The combination of source-count <i>count</i> and source-increment <i>ip-address</i> causes some of the sources out of range.
Description	The configuration request failed because the indicated configuration object contained a source that is out of range.
Type	Error: An error occurred

Severity	error
Facility	LOG_DAEMON
Action	Modify configuration statement to use a valid value.

RPD_IGMP_DYN_CFG_ALREADY_BOUND

System Log Message	Dynamic configuration session id <i>client-session-id</i> for interface <i>interface-name</i> is already bound to interface <i>old-interface-name</i> .
Description	The indicated dynamic configuration session id is already bound to another interface. The dynamic configuration instantiation request was rejected.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Unbind session id from existing interface.

RPD_IGMP_DYN_CFG_INVALID_STMT

System Log Message	Invalid dynamic configuration statement: <i>configuration-statement</i>
Description	The indicated dynamic configuration statement was invalid. The dynamic configuration instantiation request was rejected.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Remove the unsupported configuration statement.

RPD_IGMP_DYN_CFG_SES_ID_ADD_FAIL

System Log Message	Failed to add dynamic configuration session id <i>client-session-id</i> to interface <i>interface-name</i> .
Description	Failed to associate the indicated dynamic configuration session id to specified interface. The dynamic configuration instantiation request was rejected.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

RPD_IGMP_DYN_CFG_SES_ID_MISMATCH

System Log Message	Dynamic configuration entry for interface <i>interface-name</i> with session id <i>client-session-id</i> found an existing entry with a different session id of <i>client-session-id-1</i> .
Description	The dynamic configuration instantiation request matched an existing dynamic configuration block that had a different session id. The dynamic configuration instantiation request was rejected.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

RPD_IGMP_GROUP_LIMIT_EXCEED

System Log Message	IGMP group limit exceeded Instance: <i>instance</i> Interface: <i>interface-name</i> .Group Limit: <i>group-limit</i> Current Group Count: <i>current-groups</i>
Description	IGMP groups on this interface exceeds limit configured for this group on this interface in this instance.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_IGMP_GROUP_THRESHOLD_EXCEED

System Log Message	IGMP group threshold exceeded Instance: <i>instance</i> Interface: <i>interface-name</i> Group Threshold: <i>group-threshold</i> Current Group Count: <i>current-groups</i>
Description	IGMP groups on this interface exceeds threshold configured for this group on this interface in this instance.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_IGMP_GRP_THRESH_LIMIT_BELOW

System Log Message	IGMP group count went below configured threshold/limitInstance: <i>instance</i> Interface: <i>interface-name</i> .Group Limit: <i>group-limit</i> Group Threshold : <i>group-threshold</i> Current Group Count: <i>current-groups</i>
Description	IGMP groups on this interface are now below the limit configured for this group on this interface in this instance.
Type	Event: This message reports an event, not an error

Severity warning
Facility LOG_DAEMON

RPD_IGMP_JOIN

System Log Message Listener *source-address* sent a join to *destination-address* for group *group-address* source *sender-address* on interface *interface-name* at *time*

Description IGMP join event.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

RPD_IGMP_LEAVE

System Log Message Listener *source-address* sent a leave to *destination-address* for group *group-address* source *sender-address* on interface *interface-name* at *time*

Description IGMP leave event.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

RPD_IGMP_MEMBERSHIP_TIMEOUT

System Log Message Membership timeout for listener *source-address* for group *group-address* source *sender-address* on interface *interface-name* at *time*

Description IGMP group membership timeout.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

RPD_IGMP_ROUTER_VERSION_MISMATCH

System Log Message IGMP version mismatch on *interface-name*. Local version: *local-version* Remote version: *remote-version*

Description The IGMP version running on the local router does not match the one received in the query

Type Event: This message reports an event, not an error
Severity warning
Facility LOG_DAEMON

RPD_ISIS_ADJDOWN

System Log Message	IS-IS lost <i>Lisis-level</i> adjacency to <i>neighbor-system-ids</i> on <i>interface-name</i> , reason: <i>reason</i>
Description	An IS-IS adjacency with the indicated neighboring router was terminated. The local router no longer exchanges routing information with, or directs traffic to, the neighboring router.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON
Cause	The communication path to the neighboring router was disrupted, a protocol error occurred, or the neighboring router was powered down.
Action	For more information, see KB19067.

RPD_ISIS_ADJUP

System Log Message	IS-IS new <i>Lisis-level</i> adjacency to <i>neighbor-system-ids</i> on <i>interface-name</i>
Description	An IS-IS adjacency was established with the indicated neighboring router. The local router can now exchange information with it.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

RPD_ISIS_ADJUPNOIP

System Log Message	IS-IS new <i>Lisis-level</i> adjacency to <i>neighbor-system-ids</i> on <i>interface-name</i> without an address
Description	An IS-IS adjacency was established with the indicated neighboring router, which is not configured for IS-IS for IP.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON
Cause	The neighboring router is misconfigured: it is enabled for IS-IS but not for exchange of IP route information.
Action	Configure the neighboring router for IS-IS with IP, or remove it from the IS-IS mesh.

RPD_ISIS_LDP_SYNC

System Log Message	IS-IS interface <i>interface-name</i> advertised with infinite metric for <i>duration</i> seconds already due to loss of synchronization with LDP
---------------------------	---

Description	The IS-IS protocol lost synchronization with the Label Distribution Protocol (LDP) on the indicated interface. As a consequence, it began advertising an infinite metric for the interface and has been doing so for the indicated number of seconds.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	Determine why LDP lost synchronization with IS-IS.

RPD_ISIS_LSPCKSUM

System Log Message	IS-IS <i>Lisis-level</i> LSP checksum error, interface <i>interface-name</i> , LSP id <i>lspl</i> , sequence <i>sequence-number</i> , checksum <i>checksum</i> , lifetime <i>duration</i>
Description	The indicated IS-IS informational link-state PDU (LSP) failed an internal checksum validity test, implying that it was corrupted.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Cause	The packet was corrupted in transit between the neighboring IS-IS router and this router, or memory on one of the routers was corrupted.
Action	None, unless a large number of these messages appear in the system log file. The corrupted LSP is silently discarded. For mor einformation, see KB19068.

RPD_ISIS_NO_ROUTERID

System Log Message	IS-IS instance does not have a valid router ID
Description	The IS-IS instance did not have a valid router ID.
Type	Error: An error occurred
Severity	alert
Facility	LOG_DAEMON
Cause	When a router ID is not explicitly configured for an instance, IPv4 addresses configured under the instance are considered in the selection of the router ID. In this case, the instance did not have a router ID configured and no IPv4 addresses were configured.
Action	Either configure a router ID by including the 'routing-instance' statement under the instance, or configure an IPv4 address by including the 'family inet' statement under one of the interfaces of the instance. You can also configure both.

RPD_ISIS_OVERLOAD

System Log Message	IS-IS database overload
Description	The IS-IS link-state database is full and no additional memory can be allocated for it.
Type	Error: An error occurred
Severity	alert
Facility	LOG_DAEMON
Cause	No additional memory is available for storing IS-IS link-state information. Either system resources are exhausted or a software error occurred (such as a memory leak in the routing protocol process [rpd]). In the former case, IS-IS might be carrying too much information, or the router configuration includes too many features that use large amounts of system memory.
Action	Perform one or more of the following actions: (1) Check for unusually high memory usage by the IS-IS task or rpd, (2) Unconfigure features that use large amounts of memory, (3) Add more memory to the Routing Engine, (4) Carry fewer IS-IS routes. For more information, see KB19069.

RPD_KRT_CCC_IFL_MODIFY

System Log Message	<i>error-code, error-message</i>
Description	The routing protocol process (rpd) attempted to modify the state for a logical interface that is related to circuit cross-connect (CCC), but the request failed.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON
Cause	It is possible that the kernel lacked the resources to fulfill the request. The rpd process will recover.

RPD_KRT_DELETED_RTT

System Log Message	<i>task-name</i> : received deleted routing table from the kernel for family <i>address-family-type</i> table ID <i>table-id</i>
Description	The routing protocol process (rpd) received a message from the kernel that referred to a routing table that no longer exists.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

RPD_KRT_IFA_GENERATION

System Log Message	<i>ifa generation mismatch -- ifl interface-name rpd rpd-generation kernel kernel-generation</i>
Description	The routing protocol process (rpd) received a message from the kernel in which the interface address associated with the indicated numerical index differed from the address-to-index mapping maintained by rpd.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON
Cause	It is possible that rpd discarded some interface messages from the kernel without processing them because it received more messages than it could handle. It will recover.

RPD_KRT_IFDCHANGE

System Log Message	<i>task-name CHANGE for ifd interface-device-index address/prefix-length failed, error "error-message"</i>
Description	The routing protocol process (rpd) sent a request to the kernel to change the state of the indicated interface. The request failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	It is possible that the kernel lacked the resources to fulfill the request. The rpd process will recover.

RPD_KRT_IFDEST_GET

System Log Message	<i>task-name IFDEST GET for ifd rpd-interface-name failed, error "error-message"</i>
Description	The routing protocol process (rpd) requested state information about the indicated interface from the kernel. The request failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	It is possible that the kernel lacked the resources to fulfill the request. The rpd process will recover.

RPD_KRT_IFDGET

System Log Message	<i>task-name GET index for ifd interface-name failed, error "error-message"</i>
---------------------------	---

Description	The routing protocol process (rpd) requested state information about the indicated interface from the kernel. The request failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	It is possible that the kernel lacked the resources to fulfill the request. The rpd process will recover.

RPD_KRT_IFD_CELL_RELAY_INV_MODE

System Log Message	Invalid mode (<i>mode</i>) specified for interface device <i>interface-name</i> ; defaulting to port mode
Description	The routing protocol process (rpd) received a message from the kernel that specified the cell-relay encapsulation for the indicated physical interface, but the specified cell-relay mode (port, or trunk user-to-network interface [UNI], or trunk network-to-network interface [NNI]) was invalid.
Type	Error: An error occurred
Severity	notice
Facility	LOG_DAEMON

RPD_KRT_IFD_CELL_RELAY_NO_MODE

System Log Message	No mode specified for interface device <i>interface-name</i> ; defaulting to port mode
Description	The routing protocol process (rpd) received a message from the kernel that specified the cell-relay encapsulation for the indicated physical interface, but not the cell-relay mode.
Type	Error: An error occurred
Severity	notice
Facility	LOG_DAEMON

RPD_KRT_IFD_GENERATION

System Log Message	ifd <i>interface-device-index</i> generation mismatch -- rpd <i>rpd-generation</i> kernel <i>kernel-generation</i>
Description	The routing protocol process (rpd) received a message from the kernel in which the physical interface associated with the indicated numerical index differed from the interface-to-index mapping maintained by rpd.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

Cause It is possible that rpd discarded some interface messages from the kernel without processing them because it received more messages than it could handle. It will recover.

RPD_KRT_IFL_CELL_RELAY_INV_MODE

System Log Message Invalid mode (*mode*) specified for logical interface *interface-name*; defaulting to port mode

Description The routing protocol process (rpd) received a message from the kernel that specified the cell-relay encapsulation for the indicated logical interface, but the specified cell-relay mode (port, virtual-circuit, or virtual-path) was invalid.

Type Error: An error occurred

Severity notice

Facility LOG_DAEMON

RPD_KRT_IFL_CELL_RELAY_NO_MODE

System Log Message No mode specified for logical interface *interface-name*; defaulting to port mode

Description The routing protocol process (rpd) received a message from the kernel that specified the cell-relay encapsulation for the indicated logical interface but not the cell-relay mode.

Type Error: An error occurred

Severity notice

Facility LOG_DAEMON

RPD_KRT_IFL_GENERATION

System Log Message ifl *logical-interface-index* generation mismatch -- rpd *rpd-interface-name* *rpd-generation* kernel *kernel-interface-name.kernel-interface-unit* *kernel-generation*

Description The routing protocol process (rpd) received a message from the kernel in which the logical interface associated with the indicated numerical index differed from the interface-to-index mapping maintained by rpd.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_DAEMON

Cause It is possible that rpd discarded some interface messages from the kernel without processing them because it received more messages than it could handle. It will recover.

RPD_KRT_KERNEL_BAD_ROUTE

System Log Message *task-name*: lost *interface-hierarchy* *logical-interface-index* for route *route-prefix*

Description As it restarted, the routing protocol process (rpd) could not process a route obtained from the kernel because the route contained references to objects that are no longer valid.

Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	rpd did not recognize some elements in the route message, such as the logical interface index or an address family.
Action	rpd can probably solve the problem, but check the entry for the indicated route prefix in the forwarding table. If the prefix's route and forwarding table entry are inconsistent, contact a technical support representative for instructions. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB19070 .

RPD_KRT_NEXTHOP_OVERFLOW

System Log Message	<i>type route-prefix</i> : number of next hops (<i>count</i>) exceeded the maximum allowed (<i>maximum-value</i>) -- truncating
Description	The number of next hops for the indicated route exceeded the indicated limit for a single route add operation.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An indexed next hop can use multiple forwarding next hops per forwarding class. It is possible to have more next hops per route than can be carried in a single message. This requires that next hops be reused across forwarding classes, which is not recommended.
Action	Eliminate common next hops across forwarding classes, thereby reducing the total number of next hops that must be specified.

RPD_KRT_NOIFD

System Log Message	No device <i>interface-device-index</i> for interface <i>logical-interface-index</i> (<i>interface-name</i>)
Description	The routing protocol process (rpd) received a message from the kernel that associated the indicated physical interface device and logical interface. The rpd process has no record of the device.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	It is possible that rpd discarded some interface messages from the kernel without processing them because it received more messages than it could handle. It will recover.

RPD_KRT_VERSION

System Log Message	Routing socket version mismatch (kernel <i>kernel-version</i> != rpd <i>rpd-version</i>) -- kernel upgrade required
Description	The routing protocol process (rpd) discovered that the kernel does not support the version of routing sockets it requires.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	The kernel version is older than the rpd version.
Action	Upgrade the kernel package.

RPD_KRT_VERSIONNONE

System Log Message	Routing socket message type <i>message-type</i> 's version is not supported by kernel, expected <i>rpd-version</i> -- kernel upgrade required
Description	The routing protocol process (rpd) discovered that the kernel does not support the routing socket message types that it requires.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	The kernel version is older than the rpd version.
Action	Upgrade the kernel package.

RPD_KRT_VERSIONOLD

System Log Message	Routing socket message type <i>message-type</i> 's version is older than expected (<i>kernel-version</i> < <i>rpd-version</i>) -- consider upgrading the kernel
Description	The routing protocol process (rpd) discovered that the kernel uses an older version of routing socket message types than it does.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	The kernel version is older than the rpd version.
Action	Upgrade the kernel package.

RPD_KRT_VPLS_IFL_MODIFY

System Log Message	Unable to modify VPLS-related state: <i>error-code</i> (<i>errno error-message</i>)
Description	The routing protocol process (rpd) attempted to modify the state for a logical interface that is related to virtual private LAN service (VPLS), but the request failed.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON
Cause	It is possible that the kernel lacked the resources to fulfill the request. The rpd process will recover.

RPD_L2VPN_INSTANCE_NOT_FOUND

System Log Message	Routing Instance <i>routing-instance</i>
Description	The routing protocol process (rpd) received an update for the indicated routing-instance, but was unable to find the layer2 VPN instance object. This could result in inconsistent rpd state between PEs or Routing Engines.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Action	Please check routing-instance configuration.

RPD_L2VPN_LABEL_ALLOC_FAILED

System Log Message	Unable to allocate <i>label-type</i> labels for site <i>name</i> with ID <i>identifier</i> in instance <i>vpn-name</i>
Description	The routing protocol process (rpd) could not allocate labels of the indicated type for the indicated site (name and ID) in the indicated virtual private network (VPN) virtual circuit (VC), because the resulting number of labels would have exceeded the limit.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

RPD_L2VPN_REMOTE_SITE_COLLISION

System Log Message	Two remote PEs (RDs <i>route-discriminator</i> and <i>route-discriminator2</i>) have the same site ID (<i>identifier</i>) in VPN <i>vpn-name</i>
Description	The routing protocol process (rpd) for the indicated virtual private network (VPN) received an advertisement from a remote provider edge (PE) router with the first indicated route discriminator, but the associated site ID also belongs to a remote site with the second route discriminator.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

RPD_L2VPN_SITE_COLLISION

System Log Message Same site ID *identifier* configured on remote PE (RD *route-discriminator*) and local PE in VPN *vpn-name* (non-multihomed site *name*)

Description The routing protocol process (rpd) for the indicated virtual private network (VPN) received an advertisement from a remote provider edge (PE) router, but the associated site ID belongs to a local site.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

RPD_LAYER2_VC_BFD_DOWN

System Log Message BFD session for Layer 2 VC *vc-name* went down

Description The routing protocol process (rpd) determined that the Bidirectional Forwarding Detection (BFD) protocol session for the indicated Layer 2 virtual private network (VPN) virtual circuit (VC) terminated.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_DAEMON

RPD_LAYER2_VC_BFD_UP

System Log Message BFD session for Layer 2 VC *vc-name* came up

Description The routing protocol process (rpd) determined that the Bidirectional Forwarding Detection (BFD) protocol session for the the indicated Layer 2 virtual private network (VPN) virtual circuit (VC) came up.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_DAEMON

RPD_LAYER2_VC_DOWN

System Log Message State of Layer 2 VC *vc-name* changed from UP to *state*

Description The state of the indicated Layer 2 virtual private network (VPN) virtual circuit (VC) changed as indicated (to either down or deleted).

Type Event: This message reports an event, not an error

Severity notice
Facility LOG_DAEMON

RPD_LAYER2_VC_PING_DOWN

System Log Message Ping failure for Layer 2 VC *vc-name*

Description The routing protocol process (rpd) determined that the Ping for the indicated Layer 2 virtual private network (VPN) virtual circuit (VC) failed.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_DAEMON

RPD_LAYER2_VC_UP

System Log Message State of Layer 2 VC *vc-name* changed to UP

Description The state of the indicated Layer 2 virtual private network (VPN) virtual circuit (VC) changed to up.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

RPD_LDP_BFD_DOWN

System Log Message LDP BFD session for FEC *fec-address* went down

Description The routing protocol process (rpd) determined that the Label Distribution Protocol (LDP) Bidirectional Forwarding Detection (BFD) protocol session for the indicated forwarding equivalence class (FEC) terminated.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_DAEMON

RPD_LDP_BFD_DOWN_TRACEROUTE_FAIL

System Log Message LDP BFD sessions for FEC *fec-address* going down due to traceroute failure

Description The routing protocol process (rpd) determined that the Label Distribution Protocol (LDP) Bidirectional Forwarding Detection (BFD) protocol session for the indicated forwarding equivalence class (FEC) was terminated due to traceroute failure.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_DAEMON

RPD_LDP_BFD_UP

System Log Message	LDP BFD session for FEC <i>fec-address</i> came up
Description	The routing protocol process (rpd) determined that the Label Distribution Protocol (LDP) Bidirectional Forwarding Detection (BFD) protocol session for the indicated forwarding equivalence class (FEC) came up.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

RPD_LDP_GR_CFG_IGNORED

System Log Message	LDP needs <i>duration</i> seconds for restart. Instance restart-duration is <i>time-period</i> seconds only. Graceful restart will not be attempted
Description	Instance restart-duration is less than that needed by LDP to finish graceful-restart. LDP GR will not be attempted.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	Modify the instance restart-duration and ldp GR configurations.

RPD_LDP_INTF_BLOCKED

System Log Message	Duplicate session ID detected from <i>neighbor-address</i> i, interface <i>interface-name</i> , blocking interface
Description	Label Distribution Protocol (LDP) operations were blocked on the indicated interface because the same session ID was detected across multiple interfaces but per-interface transport addresses are in use.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_LDP_INTF_UNBLOCKED

System Log Message	LDP interface <i>interface-name</i> is now unblocked
Description	The indicated interface returned to the normal Label Distribution Protocol (LDP) operational state. It was previously blocked because the routing protocol process (rpd) noticed that a duplicate session ID was being used.
Type	Event: This message reports an event, not an error
Severity	warning

Facility LOG_DAEMON

RPD_LDP_NBRDOWN

System Log Message LDP neighbor *neighbor-addressi (interface-name)* is down

Description A Label Distribution Protocol (LDP) adjacency was terminated because the indicated neighbor stopped communicating. If the adjacency was the only one with this neighbor, the routing protocol process (rpd) terminated the associated LDP session.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_DAEMON

RPD_LDP_NBRUP

System Log Message LDP neighbor *neighbor-addressi (interface-name)* is up

Description A Label Distribution Protocol (LDP) adjacency with the indicated neighbor became active. The routing protocol process (rpd) established an LDP session with the neighbor if one did not already exist.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

RPD_LDP_PING_DOWN

System Log Message LDP LSP ping failure for FEC *fec-address*

Description The routing protocol process (rpd) determined that LSP ping returned error for the indicated forwarding equivalence class (FEC) of Label Distribution Protocol (LDP).

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_DAEMON

RPD_LDP_SESSIONDOWN

System Log Message LDP session *neighbor-addressi* is down, reason: *reason*

Description The routing protocol process (rpd) terminated a Label Distribution Protocol (LDP) session with the indicated neighbor and deleted all labels exchanged during the session.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_DAEMON

RPD_LDP_SESSIONUP

System Log Message	LDP session <i>neighbor-address</i> is up
Description	The routing protocol process (rpd) established a Label Distribution Protocol (LDP) session with the indicated neighbor. The routers began exchanging labels.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

RPD_LMP_ALLOC_ACK

System Log Message	Unknown context in ALLOC_ACK message
Description	The routing protocol process (rpd) received a label allocation acknowledgment that contained invalid context.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

RPD_LMP_ALLOC_REQUEST_TIMEOUT

System Log Message	Allocation request timeout for context <i>address</i> , client request ID <i>0xrequest-id</i>
Description	The label allocation request with the indicated client request ID and for the indicated context timed out before completion.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

RPD_LMP_CONTROL_CHANNEL

System Log Message	<i>operation</i> operation failed: control channel <i>logical-interface-index</i> unknown
Description	The routing protocol process (rpd) received a message that specified the indicated type of operation on the indicated control channel. The channel does not exist.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

RPD_LMP_NO_CALLBACK

System Log Message	No function callback for label removed event
Description	The routing protocol process (rpd) could not notify a client that a label was removed, because there was no function callback for the removal event.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

RPD_LMP_NO_MEMORY

System Log Message *function-name: malloc() failed (error-message, errno error-code)*

Description The routing protocol process (rpd) could not allocate memory.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.

RPD_LMP_NO_PEER

System Log Message Peer *peer-id* not found for TE link *link-name* (index *link-id*)

Description The routing protocol process (rpd) could not locate the indicated peer while processing a TE LINK message for the traffic-engineering link with the indicated name and index.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

RPD_LMP_PEER

System Log Message *operation* operation failed: peer *peer-name* (index *peer-id*) *reason*

Description The routing protocol process (rpd) could not perform the indicated operation for the peer with the indicated name and index, for the indicated reason.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

RPD_LMP_PEER_IFL

System Log Message *operation* operation failed because *reason* for peer *peer-name* (index *peer-id*): *error-message* (errno *error-code*)

Description The routing protocol process (rpd) could not perform the indicated operation for the peer with the indicated name and index, for the indicated reason.

Type	Error: An error occurred
Severity	error

Facility LOG_DAEMON

RPD_LMP_PEER_INDEX

System Log Message No more peer indexes

Description No more peer indexes were available for allocation.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

RPD_LMP_RESOURCE

System Log Message *operation* operation failed: resource *resource* (type *type*, index *index*) *reason*

Description The routing protocol process (rpd) could not perform the indicated operation for the resource with the indicated name, type, and index, for the indicated reason.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

RPD_LMP_RESOURCE_NO_LINK

System Log Message TE link *link-id* not found for resource *resource* (type *type*, index *index*)

Description The routing protocol process (rpd) could not locate the indicated traffic-engineering link for the resource with the indicated name, type, and index.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

RPD_LMP_SEND

System Log Message *function-name*: handling write exception (*error-message*, errno *error-code*)

Description The routing protocol process (rpd) could not send a message to the Label Management Protocol (LMP) process (lmpd).

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

RPD_LMP_SEND_ALLOCATION_MESSAGE

System Log Message Unable to send allocation message: *error-message* (*error-code*)

Description The routing protocol process (rpd) could not send an allocation message.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

RPD_LMP_SYSFAIL

System Log Message Unable to start *type* timer

Description The routing protocol process (rpd) discovered that the Label Management Protocol (LMP) process (lmpd) was not running. The rpd process attempted to start the indicated type of timer for restarting the lmpd process or reestablishing a connection to it, but the attempt failed.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.

Action Examine the messages that immediately follow this message in the system log for information about possible reasons that lmpd failed.

RPD_LMP_TE_LINK

System Log Message *operation* operation failed: TE link *link-name* (index *index*) *reason*

Description The routing protocol process (rpd) could not perform the indicated operation for the traffic-engineering link with the indicated name and index, for the indicated reason.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

RPD_LMP_TE_LINK_INDEX

System Log Message No more TE-link indexes

Description No more traffic-engineering link indexes were available for allocation.

Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

RPD_LMP_UNEXPECTED_OPCODE

System Log Message *message-type* message had unexpected operation code *operation-code*

Description The routing protocol process (rpd) received the indicated type of message, which had the indicated invalid operation code.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see KB19072.

RPD_MC_CFG_CREATE_ENTRY_FAILED

System Log Message	Could not create entry for <i>entry</i> .
Description	The multicast configuration request failed because the routing protocol process (rpd) failed to create the specified configuration entry.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

RPD_MC_CFG_FWDCACHE_CONFLICT

System Log Message	Multicast forwarding-cache: reuse value must be less than or equal to suppress value
Description	Multicast forwarding-cache reuse value is configured to be greater than the suppress value. Reuse value must be less than or equal to the suppress value.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_MC_CFG_PREFIX_LEN_SHORT

System Log Message	Multicast <i>argument</i> : prefix length <i>prefix-length</i> is too short for prefix <i>route-prefix</i> , ignoring excess host bits
Description	The prefix length for the indicated prefix is too short and it has a non-zero host portion. Excess host bits will be ignored.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_MC_COSD_WRITE_ERROR

System Log Message	Unable to write to pipe to COS process: (<i>error-message</i>)
Description	The routing protocol process (rpd) could not write a message on the write pipe to the Class Of Service process (cosd).

Type	Error: An error occurred
Severity	info
Facility	LOG_DAEMON
Action	Contact your technical support representative.

RPD_MC_DESIGNATED_PE_CHANGE

System Log Message	Designated forwarder changed to <i>ip-address</i> for backup-pe-group <i>group-name</i> in <i>routing-instance</i> instance
Description	The routing protocol daemon (rpd) assigned the indicated Provider Edge (PE) as the new designated forwarder of the indicated routing instance for the indicated backup-pe-group.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

RPD_MC_DYN_CFG_ALREADY_BOUND

System Log Message	Dynamic configuration session id <i>client-session-id</i> for interface <i>interface-name</i> is already bound to interface <i>old-interface-name</i> .
Description	The dynamic configuration instantiation request was rejected because the specified dynamic configuration session ID was already bound to another interface.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Unbind the session ID from the existing interface.

RPD_MC_DYN_CFG_SES_ID_ADD_FAIL

System Log Message	Failed to add dynamic configuration session id <i>client-session-id</i> to interface <i>interface-name</i> .
Description	The dynamic configuration instantiation request was rejected because the routing protocol process failed to associate the specified dynamic configuration session ID with the specified interface.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

RPD_MC_DYN_CFG_SES_ID_MISMATCH

System Log Message	Dynamic configuration entry for interface <i>interface-name</i> with session id <i>client-session-id</i> found an existing entry with a different session id of <i>client-session-id-1</i> .
Description	The dynamic configuration instantiation request was rejected because the request matched an existing dynamic configuration block that had a different session ID.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

RPD_MC_FWD_CACHE_SUPPRESSED

System Log Message	Number of entries (<i>routing-instance</i>) in Multicast Forwarding cache exceeded configured suppress_val (<i>address-family</i>) in instance <i>num-mc-fwd-cache-entries</i> for family <i>num-mc-fwd-cache-suppress</i>
Description	Multicast forwarding cache suppressed as number of entries in the cache exceeded configured suppress value.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

RPD_MC_FWD_CACHE_THRESH_BELOW

System Log Message	Number of entries (<i>routing-instance</i>) in Multicast Forwarding cache went below configured warning threshold (<i>address-family%%</i>) in instance <i>num-mc-fwd-cache-entries</i> for family <i>num-mc-fwd-cache-threshold</i>
Description	Number of entries in the multicast forwarding cache went below configured warning threshold value.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

RPD_MC_FWD_CACHE_THRESH_EXCEED

System Log Message	Number of entries (<i>routing-instance</i>) in Multicast Forwarding cache exceeded configured warning threshold (<i>address-family%%</i>) in instance <i>num-mc-fwd-cache-entries</i> for family <i>num-mc-fwd-cache-threshold</i>
Description	Number of entries in the multicast forwarding cache exceeded configured warning threshold value.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

RPD_MC_FWD_CACHE_UNSUPPRESSED

System Log Message Number of entries (*routing-instance*) in Multicast Forwarding cache went below configured reuse_val (*address-family*) in instance *num-mc-fwd-cache-entries* for family *num-mc-fwd-cache-reuse*

Description Multicast forwarding cache suppressed as number of entries in the cache went below configured reuse value.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

RPD_MC_LOCAL_DESIGNATED_PE

System Log Message Local PE is now the designated forwarder for backup-pe-group *group-name* in *routing-instance* instance

Description The routing protocol daemon (rpd) selected the local Provider Edge (PE) as the designated forwarder of the indicated routing instance for the indicated backup-pe-group.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_DAEMON

RPD_MC_OIF_REJECT

System Log Message *group-address source-address (flow-rate bps)* rejected due to lack of bandwidth on *interface-name* (maximum *maximum-flow-rate* bps, admitted *admitted-flow-rate* bps) *oif-map-interface-name*

Description When multicast bandwidth admission control is applied, an interface may not be put into the downstream interface list for a forwarding cache if the interface does not have enough bandwidth for the flow, even when a multicast protocol determines that there are local/downstream receivers.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

RPD_MC_OIF_RE_ADMIT

System Log Message *group-address source-address (flow-rate bps)* admitted due to newly available bandwidth on *interface-name* (maximum *maximum-flow-rate* bps, admitted *admitted-flow-rate* bps) *oif-map-interface-name*

Description The indicated downstream interface that was previously rejected was readmitted for the flow because there was newly available bandwidth on the interface.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

RPD_MIRROR_ERROR

System Log Message Unable to establish mirror connection between Routing Engines: *error-message*

Description The routing protocol process (rpd) could not establish the mirror connection (which supports nonstop routing) between the master and backup Routing Engines.

Type Error: An error occurred

Severity warning

Facility LOG_DAEMON

Cause The master and backup Routing Engines are running incompatible versions of the Junos OS .

Action Update the Junos OS to compatible versions on the master and backup Routing Engines.

RPD_MIRROR_VERSION_MISMATCH

System Log Message Versions of mirror software on Routing Engines are incompatible: *error-message*

Description While trying to establish the mirror connection between the master and backup Routing Engines (which supports nonstop routing), the routing protocol process (rpd) determined that the versions of Junos OS on the Routing Engines were incompatible.

Type Error: An error occurred

Severity warning

Facility LOG_DAEMON

Action Update the Junos OS to compatible versions on the master and backup Routing Engines.

RPD_MLD_ACCOUNTING_OFF

System Log Message *interface-name time*

Description The Multicast Listener Discovery (MLD) accounting for the indicated interface was disabled at the indicated time.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

RPD_MLD_ACCOUNTING_ON

System Log Message	<i>interface-name time</i>
Description	The Multicast Listener Discovery (MLD) accounting for the indicated interface was enabled at the indicated time.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

RPD_MLD_ALL_SUBSCRIBERS_DELETED

System Log Message	All MLD subscribers on interface <i>interface-name</i> deleted at <i>time</i> because the interface is down
Description	All MLD subscribers have been deleted because the interface is down.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

RPD_MLD_CFG_CREATE_ENTRY_FAILED

System Log Message	Could not create entry for <i>entry</i> .
Description	MLD failed to create the indicated configuration entry. The configuration request failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

RPD_MLD_CFG_GROUP_OUT_OF_RANGE

System Log Message	The combination of group-count <i>count</i> and group-increment <i>ip-address</i> causes some of the groups out of range.
Description	The configuration request failed because the indicated configuration object contained a group that is out of range.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Modify configuration statement to use a valid value.

RPD_MLD_CFG_INVALID_VALUE

System Log Message	The <i>object-name</i> configuration object <i>identifier</i> field has an invalid value of <i>value</i>
Description	The configuration request failed because the indicated configuration object contained the indicated invalid value.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Modify configuration statement to use a valid value.

RPD_MLD_CFG_SOURCE_OUT_OF_RANGE

System Log Message	The combination of source-count <i>count</i> and source-increment <i>ip-address</i> causes some of the sources out of range.
Description	The configuration request failed because the indicated configuration object contained a source that is out of range.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Modify configuration statement to use a valid value.

RPD_MLD_DYN_CFG_ALREADY_BOUND

System Log Message	Dynamic configuration session id <i>client-session-id</i> for interface <i>interface-name</i> is already bound to interface <i>old-interface-name</i> .
Description	The indicated dynamic configuration session id is already bound to another interface. The dynamic configuration instantiation request was rejected.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Unbind session id from existing interface.

RPD_MLD_DYN_CFG_INVALID_STMT

System Log Message	Invalid dynamic configuration statement: <i>configuration-statement</i>
Description	The indicated dynamic configuration statement was invalid. The dynamic configuration instantiation request was rejected.
Type	Error: An error occurred

Severity	error
Facility	LOG_DAEMON
Action	Remove the unsupported configuration statement.

RPD_MLD_DYN_CFG_SES_ID_ADD_FAIL

System Log Message	Failed to add dynamic configuration session id <i>client-session-id</i> to interface <i>interface-name</i> .
Description	Failed to associate the indicated dynamic configuration session id to specified interface. The dynamic configuration instantiation request was rejected.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

RPD_MLD_DYN_CFG_SES_ID_MISMATCH

System Log Message	Dynamic configuration entry for interface <i>interface-name</i> with session id <i>client-session-id</i> found an existing entry with a different session id of <i>client-session-id-1</i> .
Description	The dynamic configuration instantiation request matched an existing dynamic configuration block that had a different session id. The dynamic configuration instantiation request was rejected.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

RPD_MLD_GROUP_LIMIT_EXCEED

System Log Message	MLD group limit exceed Instance: <i>instance</i> Interface: <i>interface-name</i> .Group Limit: <i>group-limit</i> Current Group Count: <i>current-groups</i>
Description	MLD groups on this interface exceeds limit configured for this group on this interface in this instance.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_MLD_GROUP_THRESHOLD_EXCEED

System Log Message	MLD group threshold exceed Instance: <i>instance</i> Interface: <i>interface-name</i> Group Threshold: <i>group-threshold</i> Current Group Count: <i>current-groups</i>
---------------------------	--

Description MLD groups on this interface exceeds threshold configured for this group on this interface in this instance.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

RPD_MLD_GRP_THRESH_LIMIT_BELOW

System Log Message MLD group count went below configured threshold/limitInstance:*instance* Interface:*interface-name*.Group Limit:*group-limit* Group Threshold:*group-threshold* Current Group Count: *current-groups*

Description MLD groups on this interface are below limit configured for this group on this interface in this instance.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

RPD_MLD_JOIN

System Log Message Listener *source-address* sent a join to *destination-address* for group *group-address* source *sender-address* on interface *interface-name* at *time*

Description MLD join event.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

RPD_MLD_LEAVE

System Log Message Listener *source-address* sent a leave to *destination-address* for group *group-address* source *sender-address* on interface *interface-name* at *time*

Description MLD leave event.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

RPD_MLD_MEMBERSHIP_TIMEOUT

System Log Message Membership timeout for listener *source-address* for group *group-address* source *sender-address* on interface *interface-name* at *time*

Description MLD group membership timeout.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

RPD_MLD_ROUTER_VERSION_MISMATCH

System Log Message MLD version mismatch on *interface-name*. Local version: *local-version* Remote version: *remote-version*

Description The MLD version running on the local router does not match the one received in the query

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

RPD_MPLS_DYNAMIC_POOL_EXHAUSTED

System Log Message Label allocation failure : Dynamic label pool exhausted

Description There was a failure while allocating a label.The dynamic label pool space got exhausted.

Type Error: An error occurred

Severity warning

Facility LOG_DAEMON

RPD_MPLS_INTERFACE_ROUTE_ERROR

System Log Message Unable to add route in table *table-name* for label *mpls-label* pointing to *interface-name*

Description There was a failure in adding a Multiprotocol Label Switching (MPLS) route pointing to an interface

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_DAEMON

RPD_MPLS_INTF_MAX_LABELS_ERROR

System Log Message Maximum labels exceeded - failed to stack additional label to nexthop on interface *interface-name* nhid: *next-hop* fnh: *memory-address* lspname: *lsp-name* label: *data-buffer*

Description There was a failure in stacking additional label to a nexthop which already has maximum number of labels allowed for the interface

Type Error: An error occurred

Severity warning

Facility LOG_DAEMON

RPD_MPLS_LABEL_LIMIT_EXCEEDED

System Log Message	Label allocation failure : Label limit <i>label-limit</i> exceeded
Description	There was a failure while allocating a label.The dynamic label limit got exceeded while allocating new label.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON

RPD_MPLS_LABEL_THRESHOLD_LIMIT_EXCEEDED

System Log Message	<i>tag-type</i> label space usage crossed threshold limit of 90 percent
Description	The label space usage has exceeded the threshold limit for this particular label space.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_MPLS_LOSS_DELAY_NOTICE

System Log Message	MPLS <i>lsp-name</i>
Description	Loss and delay over a lsp has crossed configured threshold values
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_MPLS_LSP_AUTOBW_NOTICE

System Log Message	mpls LSP <i>lsp-name</i> Autobw already in progress, ignoring new trigger
Description	The auto-bandwidth adjustment for the indicated Multiprotocol Label Switching (MPLS) label-switched path (LSP) already in progress, ignoring new trigger.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

RPD_MPLS_LSP_BANDWIDTH_CHANGE

System Log Message	MPLS LSP <i>lsp-name</i> bandwidth changed, lsp bandwidth <i>bandwidth</i> bps
Description	The bandwidth associated with the indicated Multiprotocol Label Switching (MPLS) label-switched path (LSP) changed.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

RPD_MPLS_LSP_CHANGE

System Log Message MPLS LSP *lsp-name* change on *path-type(pathname)* Route *lsp-rro* lsp bandwidth *bandwidth* bps

Description The indicated Multiprotocol Label Switching (MPLS) label-switched path (LSP) was rerouted and its Record Route Object (RRO) changed.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

RPD_MPLS_LSP_DOWN

System Log Message MPLS LSP *lsp-name* down on *path-type(pathname)*

Description The indicated Multiprotocol Label Switching (MPLS) label-switched path (LSP) went down and could not be used to send traffic.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

RPD_MPLS_LSP_SWITCH

System Log Message MPLS LSP *lsp-name* switch from *old-path-type(old-pathname)* to *new-path-type(new-pathname)*, Route *lsp-rro: reason* lsp bandwidth *bandwidth* bps

Description The indicated Multiprotocol Label Switching (MPLS) label-switched path (LSP) switched from primary path to secondary path or vice versa.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

RPD_MPLS_LSP_UP

System Log Message MPLS LSP *lsp-name* up on *path-type(pathname)* Route *lsp-rro* lsp bandwidth *bandwidth* bps

Description The indicated Multiprotocol Label Switching (MPLS) label-switched path (LSP) came up and could be used to send traffic.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

RPD_MPLS_OAM_LSP_PING_REPLY_ERR

System Log Message Received ping reply with an error: *error-code*.

Description Received a LSP ping reply with an error code, for the ping request sent. If any failure action is configured, the failure action will get executed

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

RPD_MPLS_OAM_PING_REPLY_TIMEOUT

System Log Message LSP ping reply timed out *lsp-name*

Description LSP ping timed out waiting for a reply. If any failure action is configured, the failure action will get executed

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

RPD_MPLS_OAM_READ_ERROR

System Log Message Unable to read from pipe to MPLS OAM process: *reason (error-message)*

Description The routing protocol process (rpd) could not read a message available on the read pipe from the MPLS Operation, Administration, and Maintenance process (mplsoamd).

Type Error: An error occurred

Severity info

Facility LOG_DAEMON

Action Contact your technical support representative.

RPD_MPLS_OAM_WRITE_ERROR

System Log Message Unable to write to pipe to MPLS OAM process: *(error-message)*

Description The routing protocol process (rpd) could not write a message on the write pipe to the MPLS Operation, Administration, and Maintenance process (mplsoamd).

Type Error: An error occurred

Severity info

Facility LOG_DAEMON

Action Contact your technical support representative.

RPD_MPLS_PATH_BANDWIDTH_CHANGE

System Log Message	MPLS path <i>pathname</i> (lsp <i>lsp-name</i>) bandwidth changed, path bandwidth <i>bandwidth</i> bps
Description	The bandwidth associated with the indicated Multiprotocol Label Switching (MPLS) path changed.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_MPLS_PATH_BFD_DOWN

System Log Message	BFD session for MPLS path <i>pathname</i> went down on LSP <i>lsp-name</i>
Description	The routing protocol process (rpd) determined that the Bidirectional Forwarding Detection (BFD) protocol session for the indicated Multiprotocol Label Switching (MPLS) path terminated on the indicated label-switched path (LSP).
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

RPD_MPLS_PATH_BFD_UP

System Log Message	BFD session for MPLS path <i>pathname</i> came up on LSP <i>lsp-name</i>
Description	The routing protocol process (rpd) determined that the Bidirectional Forwarding Detection (BFD) protocol session for the the indicated Multiprotocol Label Switching (MPLS) path came up on the indicated label-switched path (LSP).
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

RPD_MPLS_PATH_BW_NOT_AVAILABLE

System Log Message	Unable to satisfy bandwidth configured for MPLS path <i>pathname</i> on LSP <i>lsp-name</i>
Description	The bandwidth setting for the indicated Multiprotocol Label Switching (MPLS) path and label-switched path (LSP) was changed recently, but attempts to apply the new setting failed. The LSP continued to use the previous amount of bandwidth.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

Action Determine the reason that the bandwidth could not change and make the necessary changes to the software configuration, hardware configuration, or both.

RPD_MPLS_PATH_DOWN

System Log Message MPLS path *pathname* down on LSP *lsp-name*

Description The indicated Multiprotocol Label Switching (MPLS) path went down on the indicated label-switched path (LSP).

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

RPD_MPLS_PATH_PING_DOWN

System Log Message LSP ping failure occurred for MPLS path *pathname* on LSP *lsp-name*

Description The routing protocol process (rpd) determined that the LSP ping returned error for the indicated Multiprotocol Label Switching (MPLS) path terminated on the indicated label-switched path (LSP).

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_DAEMON

RPD_MPLS_PATH_UP

System Log Message MPLS path *pathname* up on LSP *lsp-name* path bandwidth *bandwidth* bps

Description The indicated Multiprotocol Label Switching (MPLS) path came up on the indicated label-switched path (LSP).

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

RPD_MPLS_REQ_BW_NOT_AVAILABLE

System Log Message Requested bandwidth unavailable for MPLS path *pathname* on LSP *lsp-name*

Description After a successful CSPF computation, network conditions changed and RSVP failed to set up the path with the requested bandwidth which resulted in a path error. The LSP did not come up if the error occurred when the LSP was initially established. Otherwise, during an optimization or auto-bandwidth adjustment, the LSP continued to stay up on the old path and used the previous amount of bandwidth.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

RPD_MPLS_TABLE_ROUTE_ERROR

System Log Message Unable to add route in table *table-name* for label *mpls-label* pointing to *next-table-name*

Description There was a failure in adding a Multiprotocol Label Switching (MPLS) route pointing to another MPLS routing table

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_DAEMON

RPD_MSDP_CFG_SA_LIMITS_CONFLICT

System Log Message Threshold value *threshold* must be less than or equal to maximum value *maximum-value*. Setting threshold to maximum

Description The MSDP active-source-limit threshold is either undefined or exceeds the maximum value. Threshold will be set to maximum.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

Action Consider modifying the MSDP active-source-limit configurations.

RPD_MSDP_CFG_SRC_INVALID

System Log Message *argument* is an invalid source address

Description The indicated MSDP source is configured with an invalid address

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

Action Modify the configuration statement to use a valid value.

RPD_MSDP_PEER_DOWN

System Log Message MSDP peer *peer-address* peer-group *peer-group* out of Established state

Description The indicated MSDP peer left the Established state. The routing protocol process (rpd) deleted all active sources learned from the peer and will no longer send 'Source Active' messages to it.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_DAEMON

RPD_MSDP_PEER_UP

System Log Message MSDP peer *peer-address* peer-group *peer-group* into Established state

Description The indicated MSDP peer entered the Established state.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

RPD_MSDP_SRC_ACTIVE_OVER_LIMIT

System Log Message Number of MSDP source-active messages about *originator* exceeded configured limit (*msdp-sa-max*)

Description The number of MSDP source-active messages received from the indicated instance, peer, or source exceeded the configured limit. All source-active messages are discarded until the limit is no longer exceeded. During periods when the event reported by this message occurs frequently, the routing protocol process (rpd) does not log every occurrence.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

RPD_MSDP_SRC_ACTIVE_OVER_LOGWARN

System Log Message Number of MSDP source-active messages about *originator* exceeded configured log warning (*msdp-sa-warn-thresh*)

Description The number of MSDP source-active messages received from the indicated instance, peer, or source exceeded the configured log warning. All source-active messages are discarded until the limit is no longer exceeded. During periods when the event reported by this message occurs frequently, the routing protocol process (rpd) does not log every occurrence.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

RPD_MSDP_SRC_ACTIVE_OVER_THRESH

System Log Message Number of MSDP source-active messages about *originator* exceeded configured threshold(*msdp-sa-count*)

Description The number of MSDP source-active messages received from the indicated instance, peer, or source exceeded the configured threshold. Until the threshold is no longer exceeded, a random early discard (RED) profile is applied to incoming messages so that

only some of them are accepted. During periods when the event reported by this message occurs frequently, the routing protocol process (rpd) does not log every occurrence.

Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON

RPD_MSDP_SRC_ACTIVE_UNDER_LIMIT

System Log Message Number of MSDP source-active messages about *originator* no longer over configured log warning (*msdp-sa-max*)

Description The number of MSDP source-active messages received from the indicated instance, peer, or source no longer exceeded the configured limit. Active-source messages are no longer discarded automatically. During periods when the event reported by this message occurs frequently, the routing protocol process does not log every occurrence.

Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON

RPD_MSDP_SRC_ACTIVE_UNDER_LOGWAR

System Log Message Number of MSDP source-active messages about *originator* no longer exceeded configured log-warning (*msdp-sa-warn-thresh*)

Description The number of MSDP source-active messages received from the indicated instance, peer, or source under the configured log warning. All source-active messages are discarded until the limit is no longer exceeded. During periods when the event reported by this message occurs frequently, the routing protocol process (rpd) does not log every occurrence.

Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON

RPD_MSDP_SRC_ACTIVE_UNDER_THRESH

System Log Message Number of MSDP source-active messages about *originator* no longer exceeded configured threshold (*msdp-sa-count*)

Description The number of MSDP source-active messages received from the indicated instance, peer, or source no longer exceeded the configured threshold. A random early discard (RED) profile is no longer applied to incoming messages. During periods when the event reported by this message occurs frequently, the routing protocol process (rpd) does not log every occurrence.

Type Event: This message reports an event, not an error

Severity error
Facility LOG_DAEMON

RPD_MVPN_CFG_PREFIX_LEN_SHORT

System Log Message MVPN *argument*: prefix length *prefix-length* is too short for prefix *route-prefix*, ignoring excess host bits

Description The prefix length for MVPN source or group object is too short and the indicated prefix has a non-zero host portion. Excess host bits will be ignored.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

RPD_MVPN_HOT_ROOT_STANDBY_STATUS

System Log Message MVPN instance *instance*: *status*

Description MVPN Hot Root Standby status changed

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

RPD_MVPN_SENDER_BASED_RPF_STATUS

System Log Message MVPN instance *instance*: *status*

Description MVPN Sender-Based RPF status changed

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

RPD_OSPF_CFGNBR_P2P

System Log Message Ignored configured neighbors on point-to-point realm *realm-name* interface *interface-name* area *area-id*

Description For point-to-point interfaces, OSPF neighbors are learned by using hello messages, so the implicit configuration of neighbors was ignored for the indicated point-to-point interface.

Type Error: An error occurred

Severity warning

Facility LOG_DAEMON

Action Remove the neighbor configuration for the indicated interface.

RPD_OSPF_IF_COST_CHANGE

System Log Message	Interface <i>interface-name</i> (<i>interface-address</i>) area <i>area-idi</i> : cost changed <i>cost</i> -> <i>metric</i>
Description	OSPF interface cost changed due to change in interface bandwidth.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

RPD_OSPF_LDP_SYNC

System Log Message	OSPF realm <i>realm-name</i> interface <i>interface-name</i> area <i>area-idi</i> advertised with infinite metric for <i>duration</i> seconds already due to loss of synchronization with LDP
Description	The OSPF protocol lost synchronization with the Label Distribution Protocol (LDP) on the indicated interface. As a consequence, it began advertising an infinite metric for the interface and has been doing so for the indicated number of seconds.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	Determine why LDP lost synchronization with OSPF.

RPD_OSPF_LSA_MAXIMUM_EXCEEDED

System Log Message	OSPF realm <i>realm-name</i> number of non-local LSAs exceeded maximum limit
Description	The number of non self-generated LSAs exceeded maximum limit specified for database protection in the indicated realm. Consequently, all non self-generated LSA were deleted and all neighbors were killed. The router will not send any OSPF hellos and will ignore any incoming OSPF packets till ignore-time has elapsed.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

RPD_OSPF_LSA_WARNING_EXCEEDED

System Log Message	OSPF realm <i>realm-name</i> number of non-local LSAs exceeded warning limit
Description	The number of non self-generated LSAs exceeded warning limit specified for database protection in the indicated realm.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

RPD_OSPF_NBRDOWN

System Log Message	OSPF neighbor <i>neighbor-address</i> (realm <i>realm-name</i> interface <i>interface-name</i> area <i>area-idi</i>) state changed from <i>old-state</i> to <i>new-state</i> due to <i>event-name</i> (event reason: <i>reason</i>)
Description	An OSPF adjacency with the indicated neighboring router was terminated. The local router no longer exchanges routing information with, or directs traffic to, the neighboring router.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON
Action	For more information, see KB19074.

RPD_OSPF_NBRUP

System Log Message	OSPF neighbor <i>neighbor-address</i> (realm <i>realm-name</i> interface <i>interface-name</i> area <i>area-idi</i>) state changed from <i>old-state</i> to <i>new-state</i> due to <i>event-name</i> (event reason: <i>reason</i>)
Description	An OSPF adjacency was established with the indicated neighboring router. The local router can now exchange information with it.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

RPD_OSPF_OVERLOAD

System Log Message	OSPF instance <i>instance</i> topology <i>topology</i> is going into overload state: number of export prefixes (<i>count</i>) exceeded maximum allowed (<i>maximum-value</i>)
Description	The indicated topology in the indicated OSPF instance became overloaded and will remain in that state until an administrator intervenes.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Cause	The number of export prefixes exceeded the configured limit.
Action	Unconfigure or modify export policies that inject a large number of routes.

RPD_OSPF_TOPO_IF_COST_CHANGE

System Log Message	Interface <i>interface-name</i> (<i>interface-address</i>) area <i>area-idi</i> topology <i>topology</i> : cost changed <i>cost</i> -> <i>metric</i>
Description	OSPF topology interface cost changed due to change in interface bandwidth.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

RPD_PIM_BSR_DROP_PKT

System Log Message Instance *routing-instance*: Dropping BSR packets as BSR send queue exceeded limit of *limit* packet drop count is *count*

Description The routing protocol process (rpd) is dropping PIM BSR packets in order to prevent BSR packet send queue from growing unbounded and deplete memory. This is usually an indication of an abnormal network activity like malicious pkt being received.

Type Event: This message reports an event, not an error
Severity warning
Facility LOG_DAEMON

RPD_PIM_BSR_SEND_Q_THRESHOLD

System Log Message Instance *routing-instance*: BSR packet send queue length is now *count*, BSR packets will be dropped if queue length exceeds *limit*

Description The routing protocol process (rpd) has large amount of PIM BSR messages to send out. Usually an indication of an abnormal network activity like malicious pkt being received.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_DAEMON

RPD_PIM_FOUND_NON_BIDIR_NBR

System Log Message Instance *routing-instance* received a PIM Hello from a non-Bidir capable neighbor *neighbor-address* on *interface-name*

Description The routing protocol process (rpd) declared that the indicated PIM neighbor is not PIM-Bidir capable. As a result, PIM-Bidir will be disabled on the indicated interface.

Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON

RPD_PIM_GRP_RP_MAP_LIMIT_BELOW

System Log Message PIM (group-prefix, RP) current count (*routing-instance*) went below configured limit (*address-family*) in PIM Routing Instance: *pim-rpg-count* for Address Family: *pim-rpg-max*

Description Currently active PIM (group-prefix, RP) count went below configured maximum from above configured maximum earlier.

Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

RPD_PIM_GRP_RP_MAP_LIMIT_EXCEED

System Log Message PIM (group-prefix, RP) (*routing-instance*) exceeds configured maximum (*address-family*) in PIM Routing Instance: *pim-rpg-count* for Address Family: *pim-rpg-max*

Description Currently active PIM (group-prefix, RP) count has exceeded configured maximum.

Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

RPD_PIM_GRP_RP_MAP_THRES_EXCEED

System Log Message PIM (group-prefix, RP) (*routing-instance*) exceeds configured warning threshold (*address-family*) in PIM Routing Instance: *pim-rpg-count* for Address Family: *pim-rpg-threshold*

Description Currently active PIM (group-prefix, RP) count has exceeded configured maximum.

Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

RPD_PIM_JP_INFINITE_HOLDTIME

System Log Message Instance *routing-instance*: Received PIM J/P msg with holdtime 0xffff from *source-address* intf *interface-name*

Description The RPD received a PIM Join/Prune message with holdtime set to 0xffff (infinite).

Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_PIM_NBRDOWN

System Log Message Instance *routing-instance*: PIM neighbor *neighbor-address* (*interface-name*) removed due to: *reason*

Description The routing protocol process (rpd) declared the indicated PIM neighbor inactive.

Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

RPD_PIM_NBRUP

System Log Message	Instance <i>routing-instance</i> : PIM new neighbor <i>neighbor-address</i> interface <i>interface-name</i>
Description	The routing protocol process (rpd) discovered the indicated new PIM neighbor on the indicated interface.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

RPD_PIM_NON_BIDIR_RPF

System Log Message	Instance <i>routing-instance</i> indicated that the RPF interface, <i>interface-name</i> , to the RPA <i>rp-address</i> is not a PIM-BIDIR enabled interface
Description	The routing protocol process (rpd) declared that the indicated PIM Bidir RPF interface is not a PIM-Bidir enabled interface. As a result, PIM-Bidir forwarding will not work properly.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

RPD_PIM_REGISTER_LIMIT_BELOW

System Log Message	PIM Register current count (<i>routing-instance</i>) went below configured limit (<i>address-family</i>) in PIM Routing Instance: <i>pim-register-count</i> for Address Family: <i>pim-register-max</i>
Description	Currently active PIM registers count went below configured maximum from above configured maximum earlier. Only those registers that result in creation of (S, G) are counted.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

RPD_PIM_REGISTER_LIMIT_EXCEED

System Log Message	PIM Register count (<i>routing-instance</i>) exceeds configured maximum (<i>address-family</i>) in PIM Routing Instance: <i>pim-register-count</i> for Address Family: <i>pim-register-max</i>
Description	Currently active PIM registers count went below configured maximum from above configured maximum earlier. Only those registers that result in creation of (S, G) are counted.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

RPD_PIM_REG_THRESH_EXCEED

System Log Message	PIM Register count (<i>routing-instance</i>) exceeds configured warning threshold (<i>address-family</i>) in PIM Routing Instance: <i>pim-register-count</i> for Address Family: <i>pim-register-threshold</i>
Description	Currently active PIM registers count went below configured maximum from above configured maximum earlier. Only those registers that result in creation of (S, G) are counted.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

RPD_PIM_SG_LIMIT_BELOW

System Log Message	PIM (S,G) current count (<i>routing-instance</i>) went below configured limit (<i>address-family</i>) in PIM Routing Instance: <i>pim-sg-count</i> for Address Family: <i>pim-sg-max</i>
Description	Currently active PIM (S, G)/(*, G) count went below configured maximum from above configured maximum earlier.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

RPD_PIM_SG_LIMIT_EXCEED

System Log Message	PIM (S,G) current count (<i>routing-instance</i>) exceeds configured maximum (<i>address-family</i>) in PIM Routing Instance: <i>pim-sg-count</i> for Address Family: <i>pim-sg-max</i>
Description	Currently active PIM (S, G)/(*, G) count has exceeded configured maximum.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

RPD_PIM_SG_THRESHOLD_EXCEED

System Log Message	PIM (S,G) current count (<i>routing-instance</i>) exceeds configured warning threshold (<i>address-family</i>) in PIM Routing Instance: <i>pim-sg-count</i> for Address Family: <i>pim-sg-threshold</i>
Description	Currently active PIM sg count has exceeded configured threshold.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

RPD_PLCY_CFG_COMMUNITY_FAIL

System Log Message	Failed to parse community string under policy-options: <i>error-message</i>
Description	The routing protocol process (rpd) encountered a non-catastrophic error in bgp community member string while parsing policy-options.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_PLCY_CFG_FWDCLASS_OVERRIDDEN

System Log Message	<i>argument</i> supersedes forwarding-class under policy-statement <i>policy-name</i>
Description	During configuration parsing, a destination-class or source-class statement overrode the forwarding-class statement.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_PLCY_CFG_IFALL_NOMATCH

System Log Message	The interface 'all' statement under policy-statement <i>policy-name</i> will not match anything
Description	Interface 'all' does not have any special meaning under the policy-options hierarchy unlike under various other hierarchies.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_PLCY_CFG_PARSE_GEN_FAIL

System Log Message	Policy warning: <i>error-message</i>
Description	A conflict was detected while parsing the policy-options configuration hierarchy.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_PLCY_CFG_PREFIX_LEN_SHORT

System Log Message	prefix length <i>prefix-length</i> is too short for prefix <i>route-prefix</i> under policy-statement <i>policy-name</i> , ignoring excess host bits
Description	The prefix length for the indicated prefix is too short and it has a non-zero host portion. Excess host bits will be ignored.

Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_PPM_READ_ERROR

System Log Message	Read error on pipe from ppm: <i>reason (error-message)</i>
Description	The routing protocol process (rpd) could not read a message available on the read pipe from the periodic packet management process (ppmd).
Type	Error: An error occurred
Severity	info
Facility	LOG_DAEMON
Action	Contact your technical support representative.

RPD_PPM_WRITE_ERROR

System Log Message	<i>function-name</i> : write error on pipe to ppm (error-message)
Description	The routing protocol process (rpd) could not write a message on the pipe to the periodic packet management process (ppmd).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

RPD_RA_CFG_CREATE_ENTRY_FAILED

System Log Message	Could not create entry for <i>entry</i> .
Description	The configuration request failed because the IPv6 routing advertisements failed to create the indicate configuration entry.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

RPD_RA_CFG_INVALID_VALUE

System Log Message	The <i>object-name</i> configuration object <i>identifier</i> field has an invalid value of <i>value</i>
Description	The configuration request failed because the configuration object contained the indicated invalid value.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Change the value in the configuration statement to a valid one.

RPD_RA_DYN_CFG_ALREADY_BOUND

System Log Message Dynamic configuration session id *client-session-id* for interface *interface-name* is already bound to interface *old-interface-name*.

Description The dynamic configuration instantiation request was rejected because the indicated session ID was already bound to another interface.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Unbind session id from existing interface.

RPD_RA_DYN_CFG_INVALID_STMT

System Log Message Invalid dynamic configuration statement: *configuration-statement*

Description The dynamic configuration instantiation request was rejected because the indicated dynamic configuration statement was invalid.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Remove the unsupported configuration statement.

RPD_RA_DYN_CFG_SES_ID_ADD_FAIL

System Log Message Failed to add dynamic configuration session id *client-session-id* to interface *interface-name*.

Description The dynamic configuration instantiation request was rejected because it failed to associate the indicated session ID with the specified interface.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

RPD_RA_DYN_CFG_SES_ID_MISMATCH

System Log Message	Dynamic configuration entry for interface <i>interface-name</i> with session id <i>client-session-id</i> found an existing entry with a different session id of <i>client-session-id-1</i> .
Description	The dynamic configuration instantiation request was rejected because it matched an existing dynamic configuration block that had a different session ID.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

RPD_RDISC_CKSUM

System Log Message	Bad checksum for router solicitation from <i>source-address</i> to <i>destination-address</i>
Description	The routing protocol process (rpd) ignored a router discovery solicitation message from the indicated address because the checksum in the message's ICMP header was invalid.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	The solicitation message was incorrectly generated or damaged in transit.
Action	Examine the host that generated the solicitation message.

RPD_RDISC_NOMULTI

System Log Message	Ignoring interface <i>interface-address</i> on <i>interface-name</i> -- multicast not available
Description	The indicated interface was configured for router discovery, but does not support IP multicast operations as required. The routing protocol process (rpd) did not enable router discovery on the interface.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Action	Do not configure router discovery on the interface.

RPD_RDISC_NORECVIF

System Log Message	Unable to locate interface for router solicitation from <i>source-address</i> to <i>destination-address</i>
---------------------------	---

Description	The routing protocol process (rpd) ignored a router discovery solicitation message from the indicated router because the router's IP address does not share the IP prefix of the local router. The local router is not a candidate for the indicated router because they are not on the same network.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	Although the indicated router seems to be locally attached, no interfaces on the local router are configured to handle its IP address. Either the indicated router is configured with the wrong IP address, or the local router is not correctly configured for the network that the indicated router is using.
Action	Ignore this message if it indicates the desired configuration, or reconfigure one or both routers to share a common network.

RPD_RDISC_SOLICITADDR

System Log Message Expected multicast (*expected-address*) for router solicitation from *source-address* to *destination-address*

Description A router discovery solicitation message received from the indicated address was not sent to the expected multicast address for all routers.

Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	Examine the configuration of the router that generated the router discovery solicitation message.

RPD_RDISC_SOLICITICMP

System Log Message Nonzero ICMP code (*value*) for router solicitation from *source-address* to *destination-address*

Description The routing protocol process (rpd) ignored a router discovery solicitation message from the indicated router because the ICMP code in the message header was nonzero.

Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	The solicitation message was incorrectly generated.
Action	Examine the host that generated the solicitation message.

RPD_RDISC_SOLICITLEN

System Log Message	Insufficient length (<i>length</i>) for router solicitation from <i>source-address</i> to <i>destination-address</i>
Description	The routing protocol process (rpd) ignored a router discovery solicitation message from the indicated router, because the indicated message length is too short.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	The solicitation message was incorrectly generated.
Action	Examine the host that generated the solicitation message.

RPD_RIP_AUTH_ACK

System Log Message	Ack with invalid authentication from <i>source-address</i> (<i>interface-name</i>)
Description	The routing protocol process (rpd) ignored an RIP ack because the ack authentication failed.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

RPD_RIP_AUTH_REQUEST

System Log Message	Request with invalid authentication from <i>source-address</i> (<i>interface-name</i>)
Description	The routing protocol process (rpd) ignored an RIP request because the request authentication failed.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

RPD_RIP_AUTH_UPDATE

System Log Message	Update with invalid authentication from <i>source-address</i> (<i>interface-name</i>)
Description	The routing protocol process (rpd) ignored a RIP update because authentication of the update failed.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

RPD_RIP_JOIN_BROADCAST

System Log Message	Unable to get broadcast address on <i>interface-name</i> ; using the all-ones address
Description	RIP cannot run on the indicated interface because the routing protocol process (rpd) could not obtain the broadcast address on the interface as required for running RIP version 1 or version 2 in compatibility mode.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

RPD_RIP_JOIN_MULTICAST

System Log Message	Unable to join multicast group on <i>interface-name</i> : <i>error-message</i>
Description	RIP cannot run on the indicated interface, because the routing protocol process (rpd) could not join the RIP multicast group as required for RIP version 2 multicast updates.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

RPD_RSVP_BACKUP_DOWN

System Log Message	Backup for protecting LSP <i>lsp-name</i> down, using bypass <i>bypass-lsp-name</i> <i>reason</i>
Description	When link protection is enabled, a backup label-switched path (LSP) is needed to maintain a protected LSP's control-plane connectivity when topology failures are detected. The backup LSP for the indicated protected LSP failed. The failure can cause traffic loss because the protected LSP tears down when there is no backup. If the reason for the backup failure can be determined, it is reported in the message.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_RSVP_BYPASS_DOWN

System Log Message	RSVP bypass <i>bypass-lsp-name</i> for protecting interface <i>interface-name</i> went down <i>reason</i>
Description	The indicated RSVP link-protection bypass, which was protecting the indicated interface, was terminated. If the reason for the termination can be determined, it is reported in the message.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_RSVP_BYPASS_UP

System Log Message	RSVP bypass <i>bypass-lsp-name</i> for protecting interface <i>interface-name</i> came up
Description	The indicated RSVP link-protection bypass was established to protect the indicated interface.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_RSVP_COS_CFG_WARN

System Log Message	RSVP: Error while checking the existence of [edit class-of-service]: <i>error-message</i>
Description	RSVP detected an error while parsing configurations under the CoS hierarchy. RSVP CoS configurations will be ignored.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_RSVP_INCORRECT_FLOWSPEC

System Log Message	Bandwidth in PATH Tspec greater than RESV flowspec for <i>lsp-name</i>
Description	A downstream router sent an incorrect Resv message with a bandwidth in flowspec less than the bandwidth required by TSPEC in the Path message.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

RPD_RSVP_LSP_SWITCH

System Log Message	RSVP LSP <i>lsp-name</i> switched to backup; using bypass LSP <i>bypass-lsp-name</i> , route <i>lsp-rro</i>
Description	RSVP detected a failure downstream for the indicated label-switched path (LSP) and switched it to a backup using the indicated bypass LSP.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON
Cause	The downstream interface or router for the LSP went down.

RPD_RSVP_MAXIMUM_SESSIONS

System Log Message	RSVP maximum session limit of <i>limit</i> reached
Description	The routing protocol process (rpd) could not set up an RSVP session because the indicated limit on the number of sessions was reached.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_RSVP_NBRDOWN

System Log Message	RSVP neighbor <i>neighbor-address</i> down on interface <i>interface-name</i> nbr-type <i>neighbor-type</i> , <i>reason</i>
Description	The RSVP neighbor to the indicated address was terminated.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Cause	The communication path to the neighboring router was disrupted, a protocol error occurred, or the neighboring router was powered down.
Action	For more information, see KB19075.

RPD_RSVP_NBRUP

System Log Message	RSVP neighbor <i>neighbor-address</i> up on interface <i>interface-name</i> nbr-type <i>neighbor-type</i>
Description	An RSVP neighbor was established to the indicated address.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_RT_CFG_BR_CONFLICT

System Log Message	static route: <i>route-prefix</i> is also configured as backup-router destination, turn on retain flag to ensure proper functionality
Description	A conflict occurred between the system backup router configuration and the indicated static route.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

Action Add the retain flag to the static route

RPD_RT_CFG_CREATE_ENTRY_FAILED

System Log Message Could not create entry *entry*

Description RT failed to create the indicated configuration entry. The configuration request failed.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Contact your technical support representative.

RPD_RT_CFG_INVALID_VALUE

System Log Message The *object-name* configuration object *identifier* field has an invalid value of *value*

Description The configuration request failed because the indicated configuration object contained the indicated invalid value.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action Modify configuration statement to use a valid value.

RPD_RT_CFG_TABLE_NON_MATCHING

System Log Message Routing-table *table-name* under routing-instance *instance* associated with session-id *session-id* does not match the instance

Description The dynamic config request with a specific session id and routing-instance cannot be completed because a routing-table where routes should be added does not match the instance

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

RPD_RT_DUPLICATE_RD

System Log Message routing-instance *routing-instance* has duplicate route-distinguisher *route-discriminator* as routing-instance *existing-routing-instance*

Description The route-distinguisher assigned to this routing instance has already been assigned to another routing instance (as indicated).

Type Error: An error occurred

Severity error
Facility LOG_DAEMON

RPD_RT_DYN_CFG_INST_NOT_FOUND

System Log Message Routing-instance *instance* associated with session-id *session-id* not found

Description The dynamic-config request for a specific session id and routing instance cannot be completed because the instance was not found

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

RPD_RT_DYN_CFG_TABLE_NOT_FOUND

System Log Message Routing-table *table-name* under routing-instance *instance* associated with session-id *session-id* not found

Description The dynamic config request with a specific session id and routing-instance cannot be completed because a routing table where routes should be added was not found

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

RPD_RT_ERROR

System Log Message *rt_event_event-name*: fatal state error

Description A route in the routing table was found to be in an unrecoverable error state.

Type Error: An error occurred

Severity critical

Facility LOG_DAEMON

Action For more information, see KB19076.

RPD_RT_IFUP

System Log Message UP route for interface *interface-name* index *logical-interface-index* *address/prefix-length*

Description The interface route for the indicated interface and prefix changed state from down to up, becoming available for routing.

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_DAEMON

RPD_RT_INST_CFG_RESERVED_NAME

System Log Message	The routing-instance name <i>instance</i> is reserved and cannot be used
Description	The routing-instances configuration was rejected by rpd because of a reserved routing-instance name was used
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

RPD_RT_INST_IMPORT_PLCY_WARNING

System Log Message	Instance <i>routing-instance: commandrouting-options instance-import</i>]error-message
Description	The policy configured for instance-import in the indicated instance needs modification to become operational.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_RT_PATH_LIMIT_BELOW

System Log Message	Number of paths (<i>count</i>) in table <i>table-name</i> is now less than the configured maximum (<i>limit</i>)
Description	The number of paths in the indicated routing table previously equaled or exceeded the indicated limit, but went down to the indicated number, which is below the limit.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_RT_PATH_LIMIT_REACHED

System Log Message	Number of paths (<i>count</i>) in table <i>table-name status</i> configured maximum (<i>limit</i>)
Description	The indicated total number of paths in the indicated routing table equaled or exceeded the indicated configured limit. Attempts to add some types of path to the table fail while this condition holds, but the path count can exceed the limit if paths are forcibly added (for example, for static routes). This message first appears in the log when the limit is reached and repeats periodically until the number of paths goes below the limit.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

RPD_RT_PATH_LIMIT_WARNING

System Log Message	Number of paths (<i>count</i>) in table <i>table-name</i> reached warning threshold (<i>threshold</i> percent of configured maximum <i>limit</i>)
Description	The indicated total number of paths in the indicated routing table reached the threshold for a warning. The threshold is the indicated percentage of the indicated configured limit on the number of paths.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_RT_PREFIX_LIMIT_BELOW

System Log Message	Number of prefixes (<i>prefix-count</i>) in table <i>table-name</i> is now less than the configured maximum (<i>limit</i>)
Description	The number of prefixes in the indicated routing table previously equaled or exceeded the indicated limit, but went down to the indicated number, which is below the limit.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

RPD_RT_PREFIX_LIMIT_REACHED

System Log Message	Number of prefixes (<i>prefix-count</i>) in table <i>table-name</i> status configured maximum (<i>limit</i>)
Description	The indicated total number of prefixes in the indicated routing table equaled or exceeded the indicated configured limit. Attempts to add some types of prefix to the table fail while this condition holds, but the prefix count can exceed the limit if prefixes are forcibly added (for example, for static routes). This message first appears in the log when the limit is reached and repeats periodically until the number of prefixes goes below the limit.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

RPD_RT_PREFIX_LIMIT_WARNING

System Log Message	Number of prefixes (<i>prefix-count</i>) in table <i>table-name</i> reached warning threshold (<i>threshold</i> percent of configured maximum <i>limit</i>)
Description	The indicated total number of prefixes in the indicated routing table reached the threshold for a warning. The threshold is the indicated percentage of the indicated configured limit on the number of prefixes.
Type	Event: This message reports an event, not an error

Severity warning
Facility LOG_DAEMON

RPD_RT_SHOWMODE

System Log Message invalid display mode (*mode*)

Description The indicated display mode was specified in a 'show route' command and is unsupported.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

RPD_RT_TAG_ID_ALLOC_FAILED

System Log Message Unable to allocate *object-name* for routing instance *instance*

Description The routing protocol process (rpd) could not allocate either labels or subunits (as indicated) for the indicated routing instance, because the result number of objects would have exceeded the limit.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

RPD_RV_SESSIONDOWN

System Log Message Route validation session *ip-address, old-state -> new-state*

Description An route validation session with the indicated RPKI cache was terminated. The local router no longer receives route validation information from the RPKI cache server.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_DAEMON

Cause The communication path to the RPKI cache server was disrupted, a protocol error occurred, or the RPKI cache server was powered down.

RPD_START

System Log Message Start *executable-name[pid]* version *version* built *date*

Description The routing protocol process (rpd) started.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

RPD_SYSTEM

System Log Message	<i>reason: error-message</i>
Description	A system call made by the routing protocol process (rpd) failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	It is possible that the kernel lacked the resources to fulfill the request. The rpd process will recover.

RPD_VPLS_CW_NOT_SUPPORTED

System Log Message	Control-word not supported for instance <i>instance</i> on this platform with no-tunnel-services
Description	no-tunnel-services is configured for a VPLS instance along with control-word on a platform which does not support control-word.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	Default to not using any control-word.

RPD_VPLS_INTF_NOT_IN_SITE

System Log Message	Some interfaces of instance <i>instance</i> are not configured under its single site
Description	Some interfaces of the indicated vpls instance have not been configured under the sole site of the instance.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON
Action	Configure all interfaces of the instace under its single site.

CHAPTER 99

RT System Log Messages

This chapter describes messages with the **RT** prefix. They are generated on routers running Junos OS by the Packet Forwarding Engine as it processes packets for security control in real time.

RT_ALG_ERR_GATE

System Log Message	<i>name</i> ALG message.
Description	ALG tried to open gate, but encounter error
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_PFE

RT_ALG_ERR_INIT

System Log Message	<i>name</i> ALG initialization failed.
Description	Specific ALG initialization process failed
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_PFE

RT_ALG_ERR_MEM_ALLOC

System Log Message	<i>name</i> ALG message.
Description	ALG tried to allocate memory, such as session cookie, but failed
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_PFE

RT_ALG_ERR_NAT

System Log Message	<i>name</i> ALG message.
---------------------------	--------------------------

Description ALG called NAT API to translate IP/PORT in payload, but encounter error

Type Event: This message reports an event, not an error

Severity error

Facility LOG_PFE

RT_ALG_ERR_RES_ALLOC

System Log Message *name* ALG message.

Description ALG tried to allocate pre-reserved resources, such as ASL group, failed

Type Event: This message reports an event, not an error

Severity error

Facility LOG_PFE

RT_ALG_NTC_FSM_DROP

System Log Message *name* ALG message.

Description Packet hit incorrect finite state machine, drop it

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_PFE

RT_ALG_NTC_PARSE_ERR

System Log Message *name* ALG message.

Description ALG parse packet payload encounter error

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_PFE

RT_ALG_NTC_PKT_MALFORMED

System Log Message *name* ALG message.

Description Packet payload format incorrect, or payload element value incorrect

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_PFE

RT_ALG_WRN_CAPACITY_LMT

System Log Message *name* ALG message.

Description Requirement exceeded ALG pre-defined capacity limitation

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_PFE

RT_ALG_WRN_CFG_NEED

System Log Message *name ALG message*

Description Necessary configurations need apply to let traffic pass

Type Event: This message reports an event, not an error

Severity warning

Facility LOG_PFE

RT_FLOW_SESSION_CLOSE

System Log Message *session closed reason: source-address/source-port->destination-address/destination-port service-name
nat-source-address/nat-source-port->nat-destination-address/nat-destination-port
src-nat-rule-name dst-nat-rule-name protocol-id policy-name source-zone-name
destination-zone-name session-id-32 packets-from-client(bytes-from-client)
packets-from-server(bytes-from-server) elapsed-time application nested-application
username(roles) packet-incoming-interface encrypted*

Description A security session was closed.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_USER

RT_FLOW_SESSION_CLOSE_LS

System Log Message *Lsys logical-system-name: session closed reason:
source-address/source-port->destination-address/destination-port service-name
nat-source-address/nat-source-port->nat-destination-address/nat-destination-port
src-nat-rule-name dst-nat-rule-name protocol-id policy-name source-zone-name
destination-zone-name session-id-32 packets-from-client(bytes-from-client)
packets-from-server(bytes-from-server) elapsed-time application nested-application
username(roles) packet-incoming-interface encrypted*

Description A security session was closed.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_USER

RT_FLOW_SESSION_CREATE

System Log Message session created *source-address/source-port->destination-address/destination-port service-name*
nat-source-address/nat-source-port->nat-destination-address/nat-destination-port
src-nat-rule-name dst-nat-rule-name protocol-id policy-name source-zone-name
destination-zone-name session-id-32 username(roles) packet-incoming-interface

Description A security session was created.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_USER

RT_FLOW_SESSION_CREATE_LS

System Log Message *Lsys logical-system-name:* session created
source-address/source-port->destination-address/destination-port service-name
nat-source-address/nat-source-port->nat-destination-address/nat-destination-port
src-nat-rule-name dst-nat-rule-name protocol-id policy-name source-zone-name
destination-zone-name session-id-32 username(roles) packet-incoming-interface

Description A security session was created.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_USER

RT_FLOW_SESSION_DENY

System Log Message session denied *source-address/source-port->destination-address/destination-port*
service-name protocol-id(icmp-type) policy-name source-zone-name
destination-zone-name application nested-application username(roles)
packet-incoming-interface encrypted

Description A security session was not permitted by policy.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_USER

RT_FLOW_SESSION_DENY_LS

System Log Message *Lsys logical-system-name:* session denied
source-address/source-port->destination-address/destination-port service-name
protocol-id(icmp-type) policy-name source-zone-name destination-zone-name application
nested-application username(roles) packet-incoming-interface encrypted

Description A security session was not permitted by policy.

Type Event: This message reports an event, not an error
Severity info
Facility LOG_USER

RT_H323_NAT_COOKIE_NOT_FOUND

System Log Message *object-name* cannot find cookie from session
Description Failed to find the H.323 NAT cookie.

Type Error: An error occurred
Severity error
Facility LOG_PFE

RT_IPSEC_AUTH_FAIL

System Log Message IPsec error, *error-message*
Description HMAC verification failed for received IPsec packet \ Possibly due to a mis-match in authentication keys.

Type Error: An error occurred
Severity error
Facility LOG_PFE

RT_IPSEC_BAD_SPI

System Log Message IPsec tunnel on int *interface-name* with tunnel ID 0xtunnel-id received a packet with a bad SPI. *source-address->destination-address/length, type, SPI 0xindex, SEQ 0xsequence-number*.
Description Received IPsec packet with bad SPI

Type Error: An error occurred
Severity error
Facility LOG_PFE

RT_IPSEC_DECRYPT_BAD_PAD

System Log Message Decryption failure: *error-message*
Description Decryption error due to invalid padding content \ during ESP padding check.

Type Error: An error occurred
Severity error
Facility LOG_PFE

RT_IPSEC_PV_DECRYPTION

System Log Message	Decryption failure: <i>error-message</i>
Description	Threshold value set has been reached due to \ several decryption failures that have occurred.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_PFE

RT_IPSEC_PV_ENCRYPTION

System Log Message	Encryption failure: <i>error-message</i>
Description	Threshold value set has been reached due to \ several encryption failures that have occurred.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_PFE

RT_IPSEC_PV_REPLAY

System Log Message	Replay packet detected on IPsec tunnel on <i>interface-name</i> with tunnel ID <i>Oxtunnel-id!</i> From <i>source-address</i> to <i>destination-address/length</i> , <i>type</i> , SPI <i>Oxindex</i> , SEQ <i>Oxsequence-number</i> .
Description	Threshold value set has been reached due to \ several replay attacks that have occurred.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_PFE

RT_IPSEC_PV_SYM_KEYGEN

System Log Message	Symmetric key generation failure: <i>error-message</i>
Description	A symmetric key has failed to generate.
Type	Error: An error occurred
Severity	error
Facility	LOG_PFE

RT_IPSEC_REPLAY

System Log Message	Replay packet detected on IPsec tunnel on <i>interface-name</i> with tunnel ID <i>Oxtunnel-id!</i> From <i>source-address</i> to <i>destination-address/length</i> , <i>type</i> , SPI <i>Oxindex</i> , SEQ <i>Oxsequence-number</i> .
---------------------------	--

Description Received IPSec replay packet

Type Error: An error occurred

Severity error

Facility LOG_PFE

RT_MGCP_CALL_LIMIT_EXCEED

System Log Message Exceed maximum call *max active call number**maximum-value*

Description The maximum MGCP active call limit has been exceeded.

Type Error: An error occurred

Severity error

Facility LOG_PFE

RT_MGCP_DECODE_FAIL

System Log Message Failed to decode MGCP packet

Description Failed to decode MGCP message.

Type Error: An error occurred

Severity error

Facility LOG_PFE

RT_MGCP_MEM_ALLOC_FAILED

System Log Message Failed to allocate memory for *object-name*

Description Failed to allocate memory for the MGCP objects.

Type Error: An error occurred

Severity error

Facility LOG_PFE

RT_MGCP_REM_NAT_VEC_FAIL

System Log Message Failed to remove MGCP *object-name* from flow module

Description Failed to remove the MGCP ALG vector from the flow module.

Type Error: An error occurred

Severity error

Facility LOG_PFE

RT_MGCP_RM_CLIENTID_FAIL

System Log Message MGCP ALG Resource Manager client registration failed

Description Failed to obtain the MGCP Resource Manager client identifier.

Type Error: An error occurred

Severity error

Facility LOG_PFE

RT_MGCP_UNREG_BY_RM

System Log Message MGCP ALG client has been unregistered by Resource Manager

Description The Resource Manager has unregistered the MGCP Resource Manager client.

Type Error: An error occurred

Severity error

Facility LOG_PFE

RT_SCCP_CALL_LIMIT_EXCEED

System Log Message Failed to create SCCP ALG call, call limit *maximum-value* exceeded

Description The maximum SCCP call limit has been exceeded.

Type Error: An error occurred

Severity error

Facility LOG_PFE

RT_SCCP_CALL_RATE_EXCEED

System Log Message The SCCP active call rate limit *maximum-value* has been exceeded

Description The SCCP active call rate limit has been exceeded.

Type Error: An error occurred

Severity error

Facility LOG_PFE

RT_SCCP_DECODE_FAIL

System Log Message Failed to decode SCCP packet from *source-address->destination-address*

Description Failed to decode SCCP packet.

Type Error: An error occurred

Severity error

Facility LOG_PFE

RT_SCCP_NAT_COOKIE_NOT_FOUND

System Log Message Failed to find SCCP ALG cookie from session

Description Failed to find SCCP NAT cookie.

Type Error: An error occurred

Severity error

Facility LOG_PFE

RT_SCCP_REM_NAT_VEC_FAIL

System Log Message Failed to remove SCCP ALG vector from flow module

Description Failed to remove the SCCP ALG vector from the flow module.

Type Error: An error occurred

Severity error

Facility LOG_PFE

RT_SCCP_UNREG_RM_FAIL

System Log Message Failed to unregister SCCP client from Resource Manager when the ALG was unregistered

Description Failed to unregister SCCP client from Resource Manager when the ALG was unregistered.

Type Error: An error occurred

Severity error

Facility LOG_PFE

RT_SCREEN_ICMP

System Log Message *attack-name* source: *source-address*, destination: *destination-address*, zone name: *source-zone-name*, interface name: *interface-name*, action: *action*

Description ICMP attack category

Type Event: This message reports an event, not an error

Severity error

Facility LOG_PFE

RT_SCREEN_ICMP_LS

System Log Message [*sys: logical-system-name*] *attack-name* source: *source-address*, destination: *destination-address*, zone name: *source-zone-name*, interface name: *interface-name*, action: *action*

Description ICMP attack category

Type Event: This message reports an event, not an error

Severity error

Facility LOG_PFE

RT_SCREEN_IP

System Log Message	<i>attack-name</i> source: <i>source-address</i> , destination: <i>destination-address</i> , protocol-id: <i>protocol-id</i> , zone name: <i>source-zone-name</i> , interface name: <i>interface-name</i> , action: <i>action</i>
Description	IP attack category
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_PFE

RT_SCREEN_IP_LS

System Log Message	[<i>sys: logical-system-name</i>] <i>attack-name</i> source: <i>source-address</i> , destination: <i>destination-address</i> , protocol-id: <i>protocol-id</i> , zone name: <i>source-zone-name</i> , interface name: <i>interface-name</i> , action: <i>action</i>
Description	IP attack category
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_PFE

RT_SCREEN_SESSION_LIMIT

System Log Message	<i>attack-name message: ip-address</i> , zone name: <i>source-zone-name</i> , interface name: <i>interface-name</i> , action: <i>action</i>
Description	Session limit category
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_PFE

RT_SCREEN_SESSION_LIMIT_LS

System Log Message	[<i>sys: logical-system-name</i>] <i>attack-name message: ip-address</i> , zone name: <i>source-zone-name</i> , interface name: <i>interface-name</i> , action: <i>action</i>
Description	Session limit category
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_PFE

RT_SCREEN_TCP

System Log Message	<i>attack-name</i> source: <i>source-address:source-port</i> , destination: <i>destination-address:destination-port</i> , zone name: <i>source-zone-name</i> , interface name: <i>interface-name</i> , action: <i>action</i>
Description	TCP attack category
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_PFE
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB19078 .

RT_SCREEN_TCP_DST_IP

System Log Message	<i>attack-name</i> destination: <i>destination-address</i> , zone name: <i>source-zone-name</i> , interface name: <i>interface-name</i> , action: <i>action</i>
Description	TCP destination IP attack category
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_PFE

RT_SCREEN_TCP_DST_IP_LS

System Log Message	[<i>sys: logical-system-name</i>] <i>attack-name</i> destination: <i>destination-address</i> , zone name: <i>source-zone-name</i> , interface name: <i>interface-name</i> , action: <i>action</i>
Description	TCP destination IP attack category
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_PFE

RT_SCREEN_TCP_LS

System Log Message	[<i>sys: logical-system-name</i>] <i>attack-name</i> source: <i>source-address:source-port</i> , destination: <i>destination-address:destination-port</i> , zone name: <i>source-zone-name</i> , interface name: <i>interface-name</i> , action: <i>action</i>
Description	TCP attack category
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_PFE

RT_SCREEN_TCP_SRC_IP

System Log Message *attack-name* source: *source-address*, zone name: *source-zone-name*, interface name: *interface-name*, action: *action*

Description TCP source IP attack category

Type Event: This message reports an event, not an error

Severity error

Facility LOG_PFE

RT_SCREEN_TCP_SRC_IP_LS

System Log Message [*sys: logical-system-name*] *attack-name* source: *source-address*, zone name: *source-zone-name*, interface name: *interface-name*, action: *action*

Description TCP source IP attack category

Type Event: This message reports an event, not an error

Severity error

Facility LOG_PFE

RT_SCREEN_UDP

System Log Message *attack-name* source: *source-address:source-port*, destination: *destination-address:destination-port*, zone name: *source-zone-name*, interface name: *interface-name*, action: *action*

Description UDP attack category

Type Event: This message reports an event, not an error

Severity error

Facility LOG_PFE

Action For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB19079>.

RT_SCREEN_UDP_LS

System Log Message [*sys: logical-system-name*] *attack-name* source: *source-address:source-port*, destination: *destination-address:destination-port*, zone name: *source-zone-name*, interface name: *interface-name*, action: *action*

Description UDP attack category

Type Event: This message reports an event, not an error

Severity error

Facility LOG_PFE

RT_SCREEN_WHITE_LIST

System Log Message	bypass SYN proxy source: <i>source-address</i> , destination: <i>destination-address</i> , zone name: <i>source-zone-name</i> , interface name: <i>interface-name</i>
Description	Screen white list category for bypassing a screen
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_PFE

RT_SCREEN_WHITE_LIST_LS

System Log Message	[<i>sys: logical-system-name</i>] bypass SYN proxy source: <i>source-address</i> , destination: <i>destination-address</i> , zone name: <i>source-zone-name</i> , interface name: <i>interface-name</i>
Description	Screen white list category for bypassing a screen
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_PFE

RT_SCTP_LOG_INFO

System Log Message	***SCTP configuration: <i>message</i>
Description	SCTP log info.
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

RT_SCTP_PKT_INFO

System Log Message	***SCTP (type <i>message-type</i> <i>source-address/source-port</i> -> <i>destination-address/destination-port</i>) <i>message</i>
Description	SCTP packet info.
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

CHAPTER 100

RTLOG System Log Messages

This chapter describes messages with the **RTLOG** prefix. They are generated on routers running Junos OS by the system log module of the Packet Forwarding Engine as it processes packets for security control in real time.

RTLOG_JLOG_TEST

System Log Message	JLOG test OK, jlog_handle= <i>current-value</i>
Description	Test JSF Log plugin registration.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_PFE

RTLOG_UTP_TCP_SYN_FLOOD

System Log Message	source: <i>source-address-source-port</i> , destination: <i>destination-address-destination-port</i> , zone name: <i>filter-name</i> , interface name: <i>interface-name</i>
Description	Security LOG UTP fake TCP SYN flood attack.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_PFE

RTLOG_UTP_TCP_SYN_FLOOD_LS

System Log Message	lsys: <i>logical-system-name</i> source: <i>source-address-source-port</i> , destination: <i>destination-address-destination-port</i> , zone name: <i>filter-name</i> , interface name: <i>interface-name</i>
Description	The security LOG UTP faked a TCP SYN flood attack with the name Lsys.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_PFE

RTLOGD System Log Messages

This chapter describes messages with the **RTLOGD** prefix. They are generated by the system log utility for real-time processing of packets for security control (rtlogd) on routers running Junos OS.

RTLOGD_LOG_BIND_ERROR

System Log Message	Failed to bind socket to PFE: <i>error-message</i>
Description	The system logging utility for real-time security processing of packets (rtlogd) could not connect to a log generation module on the Packet Forwarding Engine.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB19083 .

RTLOGD_LOG_READ_ERROR

System Log Message	Failed to read from PFE: <i>error-message</i>
Description	The system logging utility for real-time security processing of packets (rtlogd) forwards logs from log generation modules on the Packet Forwarding Engine to the JUNOS event process (eventd) for recording in the system log. The rtlogd process could not read logs from the Packet Forwarding Engine for the indicated reason.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB19084 .

RTPERF System Log Messages

This chapter describes messages with the **RTPERF** prefix. They are related to performance logs for the data plane.



NOTE: These system log messages are not supported on MX Series.

RTPERF_CPU_THRESHOLD_EXCEEDED

System Log Message	FPC <i>fpc-slot</i> PIC <i>pic-slot</i> CPU utilization exceeds threshold, current value= <i>current-value</i>
Description	PFE cpu threshold exceeded
Type	Event: This message reports an event, not an error
Severity	critical
Facility	LOG_PFE

RTPERF_CPU_USAGE_OK

System Log Message	FPC <i>fpc-slot</i> PIC <i>pic-slot</i> CPU utilization returns to normal, current value= <i>current-value</i>
Description	PFE cpu usage okay
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_PFE

CHAPTER 103

SAVAL System Log Messages

This chapter describes messages with the SAVAL prefix. They are generated by the MAC SA Validate system (jsavald) process.

SAVAL_RT SOCK_FAILURE

System Log Message	Error with rtsock: <i>error-message</i>
Description	The MAC SA Validate system process (jsavald) experienced the indicated error with a routing socket.
Type	Error: An error occurred
Severity	info
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

SDK System Log Messages

This chapter describes messages with the **SDK** prefix.

SDK_VMMD_COMMAND_OPTIONS

System Log Message	sdk_vmmd_cmd_opts called with option <i>index</i> arg <i>argument</i>
Description	App-engine virtual machine management process cmd line options not handled by junos_app_init
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

SDK_VMMD_MOD_LAG

System Log Message	<i>cn-name</i> : use-lacp= <i>use-lacp</i>
Description	Either received first nodealive or missed a nodealive; modify the LAG settings accordingly
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

SDXD System Log Messages

This chapter describes messages with the **SDX** prefix. They are generated by the Session and Resource Control (SRC) process (sdx), which provides a user interface for deploying Internet services.

SDXD_BEEP_FIN_FAIL

System Log Message	Graceful close of BEEP session failed
Description	The Session and Resource Control (SRC) process (sdx) could not send a request to the SRC server to close a Blocks Extensible Exchange Protocol (BEEP) session. It sends this request when the session becomes unconfigured.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON
Cause	The usual cause is that the session was already partially or completely closed.
Action	None required. The sdx process recovers automatically in this situation.

SDXD_BEEP_INIT_FAIL

System Log Message	BEEP initialization failed
Description	The Session and Resource Control (SRC) process (sdx) could not initialize the Blocks Extensible Exchange Protocol (BEEP), which it uses to connect to an SRC server.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure might have occurred.

SDXD_CHANNEL_START_FAIL

System Log Message	Notification channel could not be started (<i>error-code</i>): <i>message</i>
---------------------------	---

Description	The indicated Blocks Extensible Exchange Protocol (BEEP) channel could not be started for the indicated reason.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Cause	The usual cause is an abnormal operation, which might be described in the system log message.

SDXD_CONNECT_FAIL

System Log Message	Connection to SDX server failed: <i>message</i>
Description	The Session and Resource Control (SRC) process (sdx) could not connect to an SRC server for the indicated reason.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON
Cause	There was a network problem or the server was not running.

SDXD_DAEMONIZE_FAIL

System Log Message	Aborting, unable to run in the background as a daemon: <i>error-message</i>
Description	The Service Deployment System process (sdx) could not create a version of itself to run in the background as a daemon.
Type	Error: An error occurred
Severity	emergency
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB19088 .

SDXD_EVLIB_FAILURE

System Log Message	<i>function-name: error-message</i>
Description	The Service Deployment System process (sdx) called the indicated function in the event library. The function failed with the indicated error.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

Cause An internal software failure occurred.

SDXD_KEEPAIVES_MISSED

System Log Message No server keepalives received for three intervals

Description The Session and Resource Control (SRC) process (sxdx) and SRC server exchange keepalive messages at regular intervals. The process did not receive a keepalive from the server for three consecutive keepalive intervals. In this case, it closes the session and tries to connect to another SRC server.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_DAEMON

SDXD_KEEPAIVE_SEND_FAIL

System Log Message Unable to send keepalive

Description The Session and Resource Control (SRC) process (sxdx) could not send a keepalive message to the SRC server, which it does periodically to maintain its connection to the server.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_DAEMON

Cause There might have been a network problem.

SDXD_MGMT_SOCKET_IO

System Log Message management daemon I/O failure: *reason*

Description The Service Deployment System process (sxdx) could not read from or write to the management socket that it uses to communicate with the JUNOS management process (mgd).

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause The mgd process might have exited abnormally.

SDXD_OUT_OF_MEMORY

System Log Message Insufficient memory during *operation*

Description The Service Deployment System (sxdx) attempted to allocate memory for an internal object during the indicated operation. The attempt failed.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

SDXD_PID_FILE_UPDATE

System Log Message Unable to update process PID file: *error-message*

Description The Service Deployment System process (sdx) attempted to update the file that records its process ID (PID), which serves to prevent multiple instances of sdx from running simultaneously. The attempt failed.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

SDXD_SOCKET_FAILURE

System Log Message *operation* failed: *error-message*

Description The Service Deployment System process (sdx) uses Transmission Control Protocol (TCP) sockets for communication with the SRC server. The indicated operation, which might be for socket creation or binding to a local address, failed with the indicated error.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

SM System Log Messages

This chapter describes messages with the **SM** prefix.

SM_IPPOOL_MM_STATE_CHANGE

System Log Message In [*logical-system-name:routing-instance*] pool *pool-name* MM state changed *prev-maintenance-mode* (*new-maintenance-mode*)

Description This notification signifies that the maintenance-mode state changed for the given pool

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

SM_IPPOOL_POOL_THRESH_EXCEEDED

System Log Message In [*logical-system-name:routing-instance*] pool *pool-name* exceeded threshold *current-threshold* (*configured-threshold*)

Description This notification signifies that the pool utilization for the given pool has exceeded the configured threshold

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

SMTPD System Log Messages

This chapter describes messages with the **SMTPD** prefix. They are generated by smtp client process (smtpd).

SMTPD_DROP_MAIL_PAYLOAD

System Log Message	Dropped mail to user: <i>error-message</i> . Send failed or queued reached max
Description	The smtp client process (smtpd) attempted to send the mail payload to the configured gateway mail server failed due to one of the following reasons: network connection failure, error in the payload, or sent failed after retries. The mail is dropped.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

SMTPD_NO_CONFIGURED_SERVER

System Log Message	Unable to send mail to <i>error-message</i> . Configure server with relay
Description	The smtp client process (smtpd) is unable to send mail payload. A gateway server must be configured. This server must allow relaying.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

SNMP System Log Messages

This chapter describes messages with the **SNMP** prefix. They are generated by two kinds of processes:

- Processes that perform SNMP operations, such as the MIB II process (mib2d) and the SNMP agent process (snmpd). Those processes also generate messages with prefixes that match their names, as described in [MIB2D System Log Messages on page ?](#) and [SNMPD System Log Messages on page ?](#).
- Processes that are instrumented to generate system log messages when they send SNMP traps. The SNMP remote operations process (rmopd) is one such process. It also generates messages with the RMOPD_ prefix, which are described in [RMOPD System Log Messages on page ?](#).

SNMP_GET_ERROR1

System Log Message	<i>function-name operation failed for object-name: index1 index1 (error-message)</i>
Description	An SNMP Get or GetNext request failed for the indicated object, which has the indicated index.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

SNMP_GET_ERROR2

System Log Message	<i>function-name operation failed for object-name: index1 index1 index2 index2 (error-message)</i>
Description	An SNMP Get or GetNext request failed for the indicated object, which has the indicated indexes.
Type	Error: An error occurred

Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

SNMP_GET_ERROR3

System Log Message	<i>function-name operation failed for object-name: index1 index1 index2 index2 index3 index3 (error-message)</i>
Description	An SNMP Get or GetNext request failed for the indicated object, which has the indicated indexes.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

SNMP_GET_ERROR4

System Log Message	<i>function-name operation failed for object-name: index1 index1 index2 index2 index3 index3 index4 index4 (error-message)</i>
Description	An SNMP Get or GetNext request failed for the indicated object, which has the indicated indexes.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

SNMP_RTSLIB_FAILURE

System Log Message	<i>function-name: reason: error-message</i>
Description	A call to the indicated function in the routing socket library failed with the indicated error.
Type	Error: An error occurred
Severity	emergency

Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB19107 .

SNMP_TRAP_LINK_DOWN

System Log Message	ifIndex <i>snmp-interface-index</i> , ifAdminStatus <i>admin-status</i> , ifOperStatus <i>operational-status</i> , ifName <i>interface-name</i>
Description	The SNMP agent process (snmpd) generated a linkDown trap because the indicated interface changed state to 'down'.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

SNMP_TRAP_LINK_UP

System Log Message	ifIndex <i>snmp-interface-index</i> , ifAdminStatus <i>admin-status</i> , ifOperStatus <i>operational-status</i> , ifName <i>interface-name</i>
Description	The SNMP agent process (snmpd) generated a linkUp trap because the indicated interface changed state to 'up'.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

SNMP_TRAP_TRACERT_PATH_CHANGE

System Log Message	traceRouteCtlOwnerIndex = <i>test-owner</i> , traceRouteCtlTestName = <i>test-name</i>
Description	The Simple Network Management Protocol (SNMP) remote operations process (rmopd) generated a traceRoutePathChange trap because two probes with the same time-to-live (TTL) value returned with different IP addresses.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

SNMP_TRAP_TRACERT_TEST_COMPLETED

System Log Message	traceRouteCtlOwnerIndex = <i>test-owner</i> , traceRouteCtlTestName = <i>test-name</i>
Description	The Simple Network Management Protocol (SNMP) remote operations process (rmopd) generated a tracerouteTestCompleted trap because the test completed and the full path to the target was determined.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

SNMP_TRAP_TRACERT_TEST_FAILED

System Log Message traceRouteCtlOwnerIndex = *test-owner*, traceRouteCtlTestName = *test-name*

Description The Simple Network Management Protocol (SNMP) remote operations process (rmopd) generated a tracerouteTestFailed trap because the test completed and the full path to the target was not determined.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

SNMPD System Log Messages

This chapter describes messages with the **SNMPD** prefix. They are generated by the Simple Network Management Protocol (SNMP) agent process (snmpd), which responds to SNMP requests. As necessary, it passes the requests to subagent processes running on its machine and forwards the traps they generate to the SNMP manager.

SNMPD_AUTH_FAILURE

System Log Message	<i>function-name: message from source-address to destination-address (index1)</i>
Description	The indicated function failed because the authorization check failed for the interface, Simple Network Management Protocol (SNMP) community, or user making the request.
Type	Error: An error occurred
Severity	notice
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

SNMPD_AUTH_PRIVILEGES_EXCEEDED

System Log Message	<i>function-name: source-address: request exceeded community privileges</i>
Description	The indicated function failed because the Simple Network Management Protocol (SNMP) community making the access request did not have the required privileges.
Type	Error: An error occurred
Severity	notice
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

SNMPD_AUTH_RESTRICTED_ADDRESS

System Log Message	<i>function-name</i> : request from address <i>source-address</i> not allowed
Description	The indicated function failed because access requests from the indicated source address are not allowed.
Type	Error: An error occurred
Severity	notice
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

SNMPD_AUTH_WRONG_PDU_TYPE

System Log Message	<i>function-name</i> : <i>source-address</i> : unauthorized SNMP PDU type: <i>pdu-type</i>
Description	The indicated function failed because the indicated type of protocol data unit (PDU) is not supported.
Type	Error: An error occurred
Severity	notice
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

SNMPD_BIND_INFO

System Log Message	Source address for trap socket was set to <i>bind-address</i>
Description	The source address for the indicated type of socket used by the Simple Network Management Protocol (SNMP) agent process (snmpd) was set to the indicated address.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON
Cause	An administrator changed the JUNOS configuration for the process or for an interface.
Cause	The online/offline state changed for a Physical Interface Card (PIC). This can also cause the address to become newly available or unavailable.

SNMPD_CONFIG_ERROR

System Log Message	Configuration database has errors
Description	The Simple Network Management Protocol (SNMP) agent process (snmpd) detected an error in the SNMP configuration database.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

SNMPD_CONTEXT_ERROR

System Log Message	<i>function-name: error in operation context context-name</i>
Description	The indicated operation (addition or deletion) failed during configuration of the indicated Simple Network Management Protocol (SNMP) context.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

SNMPD_ENGINE_ID_CHANGED

System Log Message	Warning: <i>warning-message</i>
Description	The Simple Network Management Protocol (SNMP) agent process (snmpd) maintains an engine id. This engine id has changed .
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

SNMPD_FILE_FAILURE

System Log Message	<i>function-name: fopen filename: error-message</i>
Description	The Simple Network Management Protocol (SNMP) agent process (snmpd) could not access the indicated file.
Type	Error: An error occurred
Severity	emergency
Facility	LOG_DAEMON

Cause An internal software failure occurred.

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB19108>.

SNMPD_GROUP_ERROR

System Log Message *function-name: error in operation group: 'group-id' user 'username' model 'model'*

Description The indicated operation (creation, installation, or deletion) failed during configuration of the indicated group.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause An internal software failure occurred.

Action Contact your technical support representative.

SNMPD_HEALTH_MON_THRESH_CROSS

System Log Message *syslog-subtagdelimiterevent-name*

Description A system parameter monitored by the self-monitoring feature crossed a rising or falling threshold.

Type Event: This message reports an event, not an error

Severity error

Facility LOG_DAEMON

Cause System resources were being consumed.

SNMPD_INIT_FAILED

System Log Message *snmpd initialization failure: error-message*

Description Initialization of the Simple Network Management Protocol (SNMP) agent process (snmpd) failed.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause An internal software failure occurred.

Action Contact your technical support representative.

SNMPD_LIBJUNIPER_FAILURE

System Log Message	<i>function-name: system_default_inaddr: error-message</i>
Description	The indicated function from the Juniper Networks Simple Network Management Protocol (SNMP) library failed and returned the indicated error to the SNMP agent process (snmpd).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

SNMPD_MISSING_REGISTRATION

System Log Message	Detected missing OID registration for context " <i>context-name</i> "
Description	The Simple Network Management Protocol (SNMP) agent process (snmpd) has detected OID registration pertaining to the shared MIBs is missing at snmpd side.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.

SNMPD_RADIX_FAILURE

System Log Message	<i>function-name: radix_add failed: error-message</i>
Description	The Simple Network Management Protocol (SNMP) agent process (snmpd) uses radix trees to store valid client prefixes, which are used to determine authorization for requests from users and communities. It could not create a new entry in a radix tree.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

SNMPD_RECEIVE_FAILURE

System Log Message	<i>function-name: receive message failure: error-message</i>
---------------------------	--

Description	The indicated error occurred while the Simple Network Management Protocol (SNMP) agent process (snmpd) was receiving either a protocol data unit (PDU) from the User Datagram Protocol (UDP) or a message from a subagent.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

SNMPD_RMONFILE_FAILURE

System Log Message *function-name: operation: operation filename: error-message*

Description	The indicated operation failed on the indicated remote monitoring (RMON) data file.
Type	Error: An error occurred
Severity	critical
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB19109 .

SNMPD_RMON_COOKIE

System Log Message *function-name: Null cookie*

Description	An invalid data pointer was returned when the remote monitoring (RMON) asynchronous completion handler performed an RMON alarm operation.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

SNMPD_RMON_EVENTLOG

System Log Message *syslog-subtagdelimitermessage*

Description	The indicated remote monitoring (RMON) event completed.
--------------------	---

Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

SNMPD_RMON_MIBERROR

System Log Message *function-name*: internal Get request error: *description*, alarm *alarm-id*, error *error-message*, variable: *name* (*oid*)

Description A Get request for a monitored object instance failed during initialization of the indicated remote monitoring (RMON) alarm.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

SNMPD_RTSLIB_ASYNC_EVENT

System Log Message *function-name*: sequence mismatch (*expected-value*, *received-value*), resyncing

Description A notification from the kernel to the Simple Network Management Protocol (SNMP) agent process (snmpd) was lost.

Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

SNMPD_SCRIPT_OID_ERROR

System Log Message *function-name*: OID *oid* is not juniper enterprise mib(*filename*)

Description The OID provided by the Simple Network Management Protocol (SNMP) pass-through mechanism is not under Juniper private enterprise Management Information Base (MIB).

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

SNMPD_SCRIPT_REGISTERED

System Log Message SNMP script *filename* registered with oid *oid* and with priority *priority*

Description SNMP script has registered with OID and priority.

Type	Event: This message reports an event, not an error
-------------	--

Severity info
Facility LOG_DAEMON

SNMPD_SEND_FAILURE

System Log Message *function-name: send type (index1) failure: error-message*

Description The Simple Network Management Protocol (SNMP) agent process (snmpd) could not send either a protocol data unit (PDU) to the User Datagram Protocol (UDP) or a message to a subagent.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON
Cause An internal software failure occurred.

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB19110>.

SNMPD_SET_FAILED

System Log Message Snmp set failed: *error-message*

Description Configuration data was changed using an Simple Network Management Protocol (SNMP) Set request, but the SNMP agent process (snmpd) could not save the changes to the configuration database.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON
Cause An internal software failure occurred.

Action Contact your technical support representative.

SNMPD_SMOID_GEN_FAILURE

System Log Message Unable to generate OID from *product-name* (*error-message*)

Description The Simple Network Management Protocol (SNMP) agent process (snmpd) could not generate a value for the self-monitoring object identifier (OID) of the indicated product.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON
Cause An internal software failure occurred.

Action Contact your technical support representative.

SNMPD_SOCKET_FAILURE

System Log Message *function-name: socket failure: reason (error-message)*

Description The Simple Network Management Protocol (SNMP) agent process (snmpd) uses sockets for communication with subagents. A socket operation, such as creation or removal, failed.

Type Error: An error occurred

Severity emergency

Facility LOG_DAEMON

Cause An internal software failure occurred.

Action Contact your technical support representative.

SNMPD_SOCKET_FATAL_FAILURE

System Log Message *function-name: socket failure: reason (error-message)*

Description The Simple Network Management Protocol (SNMP) agent process (snmpd) uses sockets for communication with subagents. The process exited after a socket operation, such as creation or removal, failed.

Type Error: An error occurred

Severity emergency

Facility LOG_DAEMON

Cause An internal software failure occurred.

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB19111>.

SNMPD_SYSLIB_FAILURE

System Log Message *function-name: system function 'system-function-name' failed: error-message*

Description The indicated function from the Simple Network Management Protocol (SNMP) system library failed and returned the indicated error to the SNMP agent process (snmpd).

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause An internal software failure occurred.

Action Contact your technical support representative.

SNMPD_SYSOID_FAILURE

System Log Message Unable to determine sysObjectID from internal model: *model*

Description The Simple Network Management Protocol (SNMP) agent process (snmpd) could not determine the value of the sysObjectID object.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause An internal software failure occurred.

Action Contact your technical support representative.

SNMPD_SYSOID_GEN_FAILURE

System Log Message Unable to generate OID for product *product-name* (*error-message*)

Description The Simple Network Management Protocol (SNMP) agent process (snmpd) could not generate a value for the sysObjectID object for the indicated product.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause An internal software failure occurred.

Action Contact your technical support representative.

SNMPD_THROTTLE_QUEUE_DRAINED

System Log Message *function-name*: cleared all throttled traps

Description The queue of throttled traps was cleared.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

SNMPD_TRAP_COLD_START

System Log Message *function-name*: SNMP trap: cold start

Description The Simple Network Management Protocol (SNMP) agent process (snmpd) generated a cold-start trap when the entire Routing Engine (including the snmpd process) initialized.

Type	Event: This message reports an event, not an error
Severity	critical
Facility	LOG_DAEMON

SNMPD_TRAP_GEN_FAILURE

System Log Message	<i>function-name</i> : SNMP trap error: <i>trap-message</i> (<i>error-message</i>)
Description	The Simple Network Management Protocol (SNMP) agent process (snmpd) could not generate a trap.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

SNMPD_TRAP_INVALID_DATA

System Log Message	<i>function-name</i> : SNMP trap error: invalid <i>message</i> (<i>value</i>) received
Description	The Simple Network Management Protocol (SNMP) agent process (snmpd) received a trap message from a subagent that contained an invalid variable binding (varbind) type.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

SNMPD_TRAP_QUEUED

System Log Message	Adding trap to <i>trap-destination</i> to <i>queue-name</i> queue, size traps in queue
Description	A trap was queued for later transmission.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON
Cause	Possible causes include the following: (a) the system is not completely initialized, (b) a route does not exist, or (c) traps are being throttled.

SNMPD_TRAP_QUEUE_DRAINED

System Log Message	<i>function-name</i> : traps queued to <i>trap-destination</i> sent successfully
Description	The queued traps for the indicated destination were successfully sent.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

SNMPD_TRAP_QUEUE_MAX_ATTEMPTS

System Log Message	<i>function-name</i> : after <i>count</i> attempts, deleting <i>trap-count</i> traps queued to <i>trap-destination</i>
Description	The number of attempts to send traps to the indicated destination exceeded the configured maximum. The traps still waiting to be sent were discarded.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

SNMPD_TRAP_QUEUE_MAX_SIZE

System Log Message	<i>function-name</i> : maximum queue size exceeded (<i>size</i>), discarding trap to <i>trap-destination</i> from <i>queue-name</i> queue
Description	The number of traps in the trap queue exceeded the configured maximum. The traps still waiting to be sent were discarded.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

SNMPD_TRAP_TARGET_ADD_NOTICE

System Log Message	trap target is added, address : <i>target-info</i>
Description	The given trap target is added
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

SNMPD_TRAP_TARGET_DELETE_NOTICE

System Log Message	trap target is removed, henceforth agent will not send any trap to this target : <i>target-info</i>
---------------------------	---

Description	The given trap target is deleted
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

SNMPD_TRAP_THROTTLED

System Log Message	<i>function-name</i> : traps throttled after <i>count</i> traps
Description	The number of traps waiting for transmission exceeded the configured maximum, so the remaining traps were throttled.
Type	Event: This message reports an event, not an error
Severity	info
Facility	LOG_DAEMON

SNMPD_TRAP_WARM_START

System Log Message	<i>function-name</i> : SNMP trap: warm start
Description	The Simple Network Management Protocol (SNMP) agent process (snmpd) generated a warm-start trap when it initialized (other Routing Engine processes were already active).
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

SNMPD_USER_ERROR

System Log Message	<i>function-name</i> : error in <i>action</i> user ' <i>username</i> ' auth ' <i>authentication-type</i> ' priv ' <i>privilege-type</i> '
Description	The indicated operation (creation, installation, or deletion) failed during configuration of the indicated user.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

CHAPTER 110

SPD System Log Messages

This chapter describes messages with the **SPD** prefix. They are generated by the adaptive services process (spd), which provides the user interface for management and configuration of Adaptive Services PICs.

SPD_CONFIGURATION_COMPILE

System Log Message	Compilation of configuration rule <i>rule-name</i> term <i>index</i> failed: <i>reason</i>
Description	The adaptive services process (spd) could not compile a configured object, such as a rule or rule term.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

SPD_CONN_FAILURE

System Log Message	Connection did not succeed (Pic is down or busy) error: <i>error-message</i>
Description	The adaptive services process (spd) attempted to open a connection to an Adaptive Services Physical Interface Card (PIC), to gather information requested in a Simple Network Management Protocol (SNMP) query. The attempt failed with the indicated fatal error.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

SPD_CONN_NO_REPLY

System Log Message	<i>function-name</i> : no reply from <i>interface-name</i> (<i>error-message</i>)
Description	The adaptive services process (spd) did not receive a reply from the indicated interface on an Adaptive Services Physical Interface Card (PIC) for information requested in a Simple Network Management Protocol (SNMP) query.
Type	Error: An error occurred

Severity error
Facility LOG_DAEMON

SPD_CONN_OPEN_FAILURE

System Log Message *function-name: unable to open connection to interface-name (error-message)*

Description The adaptive services process (spd) attempted to open a connection to the indicated interface on an Adaptive Services PIC, to gather information requested in a Simple Network Management Protocol (SNMP) query. The attempt failed for the indicated reason.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

SPD_CONN_SEND_FAILURE

System Log Message *function-name: unable to send query to interface-name (error-message)*

Description The adaptive services process (spd) attempted to send a request for information, needed for a Simple Network Management Protocol (SNMP) query, to the indicated interface on an Adaptive Services Physical Interface Card (PIC). The attempt failed for the indicated reason.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

SPD_CONN_UNEXPECTED_MSG

System Log Message *function-name: unexpected response received from interface-name (error-message)*

Description The adaptive services process (spd) sent a request for information, needed for a Simple Network Management Protocol (SNMP) query, to the indicated interface on an Adaptive Services Physical Interface Card (PIC). It received an unexpected response.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

SPD_DAEMONIZE_FAILED

System Log Message Aborting, unable to run in the background as a daemon: *error-message*

Description The adaptive services process (spd) could not create a version of itself to run in the background as a daemon.

Type Error: An error occurred

Severity	emergency
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB19113 .

SPD_DB_IF_ADD_FAILURE

System Log Message	Unable to add database entry for <i>interface-name: error-message</i>
Description	The adaptive services process (spd) uses an internal database to store information needed to reply to Simple Network Management Protocol (SNMP) queries. It could not add an entry to the database for the indicated interface on an Adaptive Services Physical Interface Card (PIC).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

SPD_DB_IF_ALLOC_FAILURE

System Log Message	Unable to allocate database entry for <i>interface-name: error-message</i>
Description	The adaptive services process (spd) uses an internal database to store information needed to reply to Simple Network Management Protocol (SNMP) queries. It could not allocate an entry in the database for the indicated interface on an Adaptive Services Physical Interface Card (PIC).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

SPD_DB_SVC_SET_ADD_FAILURE

System Log Message	Unable to add database entry for <i>service-set: error-message</i>
Description	The adaptive services process (spd) uses an internal database to store information needed to reply to Simple Network Management Protocol (SNMP) queries. It could not add an entry to the database for the indicated service set.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

SPD_DB_SVC_SET_ALLOC_FAILURE

System Log Message	Unable to allocate database entry for <i>service-set: error-message</i>
---------------------------	---

Description The adaptive services process (spd) uses an internal database to store information needed to reply to Simple Network Management Protocol (SNMP) queries. It could not allocate an entry in the database for the indicated service set.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

SPD_DUPLICATE

System Log Message Another copy of this program is running

Description An attempt to start the adaptive services process (spd) failed because an instance of the process is already running.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

SPD_EVLIB_CREATE_FAILURE

System Log Message evCreate failed with: *error-message*

Description The adaptive services process (spd) could not create a context used for handling all asynchronous events (such as timers and message availability).

Type Error: An error occurred

Severity emergency

Facility LOG_DAEMON

Action For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB19114>.

SPD_EVLIB_EXIT_FAILURE

System Log Message evMainLoop return value: *return-value*, error: *error-message*

Description The adaptive services process (spd) returned from an event loop, which it should never do.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

SPD_GEN_NUM_FAIL

System Log Message Initialization of generation number failed, *error-message*

Description The adaptive services process (spd) attempted to initialize the generation-number for the service sets. However, the memory allocation failed.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Action For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB19115>.

SPD_NOT_ROOT

System Log Message Must be run as root

Description The user who attempted to start the adaptive services process (spd) was not the root user.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

SPD_OUT_OF_MEMORY

System Log Message Insufficient memory for operation *operation*

Description The adaptive services process (spd) attempted to allocate memory for an internal object. The attempt failed.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

SPD_PID_FILE_LOCK

System Log Message Unable to lock PID file: *error-message*

Description The adaptive services process (spd) attempted to lock the file that records its process ID (PID), which serves to prevent multiple instances of spd from running simultaneously. The attempt failed.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

SPD_PID_FILE_UPDATE

System Log Message Unable to update process PID file: *error-message*

Description The adaptive services process (spd) attempted to update the file that records its process ID (PID), which serves to prevent multiple instances of spd from running simultaneously. The attempt failed.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

SPD_SERVICE_NEXT_HOP_ADD_FAILED

System Log Message Unable to add service next hop: *error-message (error-code)*

Description The adaptive services process (spd) could not add a service next hop for the indicated reason.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

SPD_SERVICE_NEXT_HOP_DEL_FAILED

System Log Message Unable to delete service next hop: *error-message (error-code)*

Description The adaptive services process (spd) could not delete a service next hop for the indicated reason.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

SPD_TRAP_OID_GEN_FAILED

System Log Message Unable to generate OID for *identifier (error-message)*

Description The adaptive services process (spd) could not generate the indicated object identifier (OID) for a Simple Network Management Protocol (SNMP) trap notification.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

SPD_TRAP_REQUEST_FAILURE

System Log Message *function-name: type* request failed: *error-message*

Description The adaptive services process (spd) made the indicated type of request to the application programming interface (API) for generating Simple Network Management Protocol (SNMP) traps, but did not receive the expected result.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

SPD_USAGE

System Log Message Usage: spd [-N] [-v] [-d debug-level]

Description The adaptive services process (spd) displayed the syntax statement for the 'spd' command because the command was invoked incorrectly.

Type Event: This message reports an event, not an error
Severity error
Facility LOG_DAEMON

SSH System Log Messages

This chapter describes messages with the **SSH** prefix. They are generated by the ssh-relay process (ssh).

SSH_MSG_REPLAY_DETECT

System Log Message	Potential replay attack detected on SSH connection initiated from <i>source-address:source-port</i>
Description	Potential ssh replay attack detected on the indicated connection.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY

SSH_MSG_REPLAY_LIMIT

System Log Message	Specified number of replay attacks (<i>limit</i>) detected on SSH connection initiated from <i>source-address:source-port</i>
Description	Several potential ssh replay attacks detected on the indicated connection
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY

SSH_RELAY_CONNECT_ERROR

System Log Message	Unable to connect to <i>service-name</i> server: <i>error-message</i>
Description	The 'ssh-relay' program could not connect to the server process for the indicated service.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	The server process is not running or has not enabled the service.

SSH_RELAY_SERVER_ERROR

System Log Message	SSH relay error for <i>service-name</i> service: <i>error-message</i>
Description	The indicated error occurred when a Junos process tried to establish secure shell (SSH) relay during initialization of the indicated service.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative. For more information, see KB18954.

SSH_RELAY_USAGE

System Log Message	Usage: ssh-relay -s <i>service-name</i>
Description	The syntax statement for the 'ssh-relay' command was displayed because the command was invoked with one or more incorrect options, or without necessary options.
Type	Error: An error occurred
Severity	error
Facility	ANY

SSHD System Log Messages

This chapter describes messages with the SSHD prefix. They are generated by the secure shell process (sshd) which grants you access to specified shell accounts.

SSHD_LOGIN_ATTEMPTS_THRESHOLD

System Log Message	Threshold for unsuccessful authentication attempts (<i>limit</i>) reached by user ' <i>username</i> '
Description	The user made too many failed login attempts.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY

SSHD_LOGIN_FAILED

System Log Message	Login failed for user ' <i>username</i> ' from host ' <i>source-address</i> '
Description	A login attempt failed for the indicated username.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY

SSHD_LOGIN_FAILED_LIMIT

System Log Message	Specified number of login failures (<i>limit</i>) for user ' <i>username</i> ' reached from ' <i>remote-address</i> '
Description	Several login attempts failed for the indicated username.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY

SSL System Log Messages

This chapter describes messages with the **SSL** prefix. They are generated by the Secure Sockets Layer (protocol) (SSL) services. These logs contain information about logical system names, SSL proxy whitelists, policy information, and SSL proxy information.

SSL is an application-level protocol that provides encryption technology for the Internet. SSL, also called Transport Layer Security (TLS), ensures the secure transmission of data between a client and a server through a combination of privacy, authentication, confidentiality, and data integrity. SSL relies upon certificates and private-public key exchange pairs for this level of security.

SSL_PROXY_ERROR

System Log Message	<i>lsys:logical-system-name session-id</i> <i><source-address/source-port->destination-address/destination-port></i> <i>NAT:<nat-source-address/nat-source-port->nat-destination-address/nat-destination-port></i> <i>profile-name</i> <i><source-zone-name:source-interface-name->destination-zone-name:destination-interface-name></i> <i>message: message</i>
Description	ssl proxy error log
Type	Error: An error occurred
Severity	error
Facility	LOG_PFE

SSL_PROXY_INFO

System Log Message	<i>lsys:logical-system-name session-id</i> <i><source-address/source-port->destination-address/destination-port></i> <i>NAT:<nat-source-address/nat-source-port->nat-destination-address/nat-destination-port></i> <i>profile-name</i> <i><source-zone-name:source-interface-name->destination-zone-name:destination-interface-name></i> <i>message: message</i>
Description	ssl proxy info log
Type	Event: This message reports an event, not an error
Severity	info

Facility LOG_PFE

SSL_PROXY_SESSION_IGNORE

System Log Message *lsys:logical-system-name session-id*
<source-address/source-port->destination-address/destination-port>
NAT:<nat-source-address/nat-source-port->nat-destination-address/nat-destination-port>
profile-name
<source-zone-name:source-interface-name->destination-zone-name:destination-interface-name>
message: message

Description This log is generated when a non-ssl session is allowed to pass through ssl-proxy. This will happen when initially a session is marked for proxy processing and at some later point it turns out to be a non-ssl session.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

SSL_PROXY_SESSION_WHITELIST

System Log Message *lsys:logical-system-name session-id host:url*
<source-address/source-port->destination-address/destination-port>
NAT:<nat-source-address/nat-source-port->nat-destination-address/nat-destination-port>
profile-name
<source-zone-name:source-interface-name->destination-zone-name:destination-interface-name>
message: message

Description This log is generated when an session is whitelisted.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

SSL_PROXY_SSL_SESSION_ALLOW

System Log Message *lsys:logical-system-name session-id*
<source-address/source-port->destination-address/destination-port>
NAT:<nat-source-address/nat-source-port->nat-destination-address/nat-destination-port>
profile-name
<source-zone-name:source-interface-name->destination-zone-name:destination-interface-name>
message: message

Description This log is generated when an ssl session is allowed to pass through ssl-proxy after some error is detected

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

SSL_PROXY_SSL_SESSION_DROP

System Log Message *lsys:logical-system-name session-id*
<source-address/source-port->destination-address/destination-port>
NAT:<nat-source-address/nat-source-port->nat-destination-address/nat-destination-port>
profile-name
<source-zone-name:source-interface-name->destination-zone-name:destination-interface-name>
message: message

Description This log is generated when an ssl proxy session is dropped by ssl-proxy

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

SSL_PROXY_WARNING

System Log Message *lsys:logical-system-name session-id*
<source-address/source-port->destination-address/destination-port>
NAT:<nat-source-address/nat-source-port->nat-destination-address/nat-destination-port>
profile-name
<source-zone-name:source-interface-name->destination-zone-name:destination-interface-name>
message: message

Description ssl proxy warning log

Type Event: This message reports an event, not an error

Severity info

Facility LOG_PFE

SYSTEM System Log Messages

This chapter describes messages with the **SYSTEM** prefix. Messages without an event ID are grouped under this set of system log messages. For example, messages generated by the kernel, Packet Forwarding Engine, PIC, line-card chassis (LCC), switch-card chassis (SCC), etc. are grouped under the **SYSTEM** messages.

SYSTEM_ABNORMAL_SHUTDOWN

System Log Message	System abnormally shut down
Description	The system shut down abnormally. This can be caused by any number of factors such as pulling the power plug, a kernel panic, a thermal shutdown, and so forth.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

SYSTEM_OPERATIONAL

System Log Message	System is operational
Description	The system has entered operational status, and security logging has been started.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

SYSTEM_SHUTDOWN

System Log Message	<i>System type by username at time: message</i>
Description	An administrator requested that the system be shut down or rebooted.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

TFTPD System Log Messages

This chapter describes messages with the **TFTPD** prefix. They are generated by the Trivial FTP (TFTP) process (tnp.tftpd), which services requests from hardware components for the configuration files that they use during initialization.

TFTPD_AF_ERR

System Log Message	Unexpected address family <i>address-family-type</i>
Description	As each hardware component on the routing platform initializes, it requests its configuration file from the TFTP process (tnp.tftpd). The tnp.tftpd process exited because an incoming packet had the indicated, unexpected value in its address family (sockaddr) field.
Type	Error: An error occurred
Severity	error
Facility	ANY

TFTPD_BIND_ERR

System Log Message	bind: <i>error-message</i>
Description	Binding of a socket to an address failed due to a system error.
Type	Error: An error occurred
Severity	error
Facility	ANY

TFTPD_CONNECT_ERR

System Log Message	connect: <i>error-message</i>
Description	Connection of a socket to an address failed due to a system error.
Type	Error: An error occurred
Severity	error
Facility	ANY

TFTPD_CONNECT_INFO

System Log Message	TFTP operation from address <i>address</i> port <i>port</i> file <i>filename</i>
Description	As each hardware component on the routing platform initializes, it requests its configuration file from the TFTP process (tnp.tftpd). The process established a connection with the indicated characteristics: kind of operation (read or write), address and port connected to, and name of file transferred.
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

TFTPD_CREATE_ERR

System Log Message	check_space <i>error-message</i>
Description	The TFTP process (tnp.tftpd) could not create a core dump file.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	There is probably not enough free space in the file system where tnp.tftpd tried to create the file.

TFTPD_FIO_ERR

System Log Message	ioctl(FIONBIO): <i>error-message</i>
Description	The TFTP process (tnp.tftpd) could not set the standard input to be nonblocking.
Type	Error: An error occurred
Severity	error
Facility	ANY

TFTPD_FORK_ERR

System Log Message	fork: <i>error-message</i>
Description	As each hardware component on the routing platform initializes, it requests its configuration file from the TFTP process (tnp.tftpd). To service multiple clients simultaneously, tnp.tftpd calls the fork() system call to make a copy of itself for each request. The system call returned the indicated error.
Type	Error: An error occurred
Severity	error
Facility	ANY

TFTPD_NAK_ERR

System Log Message	<code>nak error error-code, error-message</code>
Description	The TFTP process (tnp.tftpd) sent a negative acknowledgment to a client because of the indicated error condition.
Type	Error: An error occurred
Severity	warning
Facility	ANY

TFTPD_OPEN_ERR

System Log Message	Unable to open file ' <i>filename</i> ', error: <i>error-message</i>
Description	The TFTP process (tnp.tftpd) could not open the indicated file because of the indicated error.
Type	Error: An error occurred
Severity	warning
Facility	ANY

TFTPD_RECVCOMPLETE_INFO

System Log Message	Received <i>count</i> blocks of <i>block-size</i> size for file ' <i>filename</i> '
Description	The TFTP process (tnp.tftpd) received the last portion of a transmitted file. This message records the number of blocks received, the block size used, and the name of the file to which the data was written.
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

TFTPD_RECVFROM_ERR

System Log Message	<code>recvfrom: error-message</code>
Description	The TFTP process (tnp.tftpd) issued the <code>recvfrom()</code> system call when attempting to receive data from the network. The system call failed.
Type	Error: An error occurred
Severity	error
Facility	ANY

TFTPD_RECV_ERR

System Log Message	<code>recv: error-message</code>
Description	The TFTP process (tnp.tftpd) could not receive data from the network.

Type	Error: An error occurred
Severity	error
Facility	ANY

TFTPD_SENDCOMPLETE_INFO

System Log Message	Sent <i>count</i> blocks of <i>block-size</i> and 1 block of <i>size</i> for file ' <i>filename</i> '
Description	The TFTP process (tnp.tftpd) successfully sent a file. This message records the number of blocks sent, the block size used, the size of the last block, and the name of the source file.
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

TFTPD_SEND_ERR

System Log Message	send: <i>error-message</i>
Description	The TFTP process (tnp.tftpd) could not send data.
Type	Error: An error occurred
Severity	error
Facility	ANY

TFTPD_SOCKET_ERR

System Log Message	socket: <i>error-message</i>
Description	The TFTP process (tnp.tftpd) could not open a socket for data transmission or reception.
Type	Error: An error occurred
Severity	error
Facility	ANY

TFTPD_STATFS_ERR

System Log Message	statfs <i>filename</i> , error: <i>error-message</i>
Description	The TFTP process (tnp.tftpd) issued the statfs() system call to obtain the status of the file system into which it needed to write a crash file. The system call failed with the indicated error.
Type	Error: An error occurred
Severity	error
Facility	ANY

TRANSPORTD System Log Messages

This chapter describes messages with the **TRANSPORTD** prefix.

TRANSPORTD_IPC_MSG_ERROR

System Log Message	<i>function-name</i> : error code <i>error-code</i> , type <i>message-type</i> , subtype <i>message-subtype</i> , opcode <i>message-opcode</i>
Description	The transport process (transportd) detected an error in an interprocess communication (IPC) message with the indicated characteristics.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

TRANSPORTD_IPC_MSG_UNHANDLED

System Log Message	<i>function-name</i> : unable to handle message with type <i>message-type</i> , subtype <i>message-subtype</i> , length <i>length</i> , opcode <i>message-opcode</i> , error <i>error-code</i>
Description	The transport process (transportd) received an interprocess communication (IPC) message about the indicated FRU. The message had the indicated characteristics. The transportd process could not handle the message.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

TRANSPORTD_IPC_UNEXPECTED_MSG

System Log Message	<i>function-name</i> : invalid message received: <i>message</i> (message type <i>message-type</i> , subtype <i>message-subtype</i>)
Description	The transport process (transportd) received a unexpected message with the indicated characteristics.
Type	Error: An error occurred
Severity	error

Facility LOG_DAEMON

TRANSPORTD_IPC_WRITE_ERROR

System Log Message *function-name: errno error-code, error-message*

Description transport process's (transportd) attempt to write to a pipe (to another component) failed.

Type Error: An error occurred

Severity warning

Facility LOG_DAEMON

TRANSPORTD_IPC_WRITE_ERR_NO_PIPE

System Log Message *function-name* pipe is NULL

Description The transport process (transportd) could not send a message to the indicated component because the interprocess communication (IPC) pipe to that component no longer existed.

Type Error: An error occurred

Severity warning

Facility LOG_DAEMON

TRANSPORTD_MGR_CONNECT

System Log Message *function-name* evSelectFD: initial pipe create aborted (errno error-code)

Description The transport process (transportd) could not open a pipe for interprocess communication (IPC) to another component.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

TRANSPORTD_PIPE_WRITE_ERROR

System Log Message Pipe write error: *error-message*

Description The transport process (transportd) experienced a fatal error while writing to a pipe.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

TRANSPORTD_SYSCALL_ERROR

System Log Message *function-name: error from sysctl-function-name: error-message (errno error-code)*

Description The transport process (transportd) received the indicated error from the indicated syscall() operation.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

CHAPTER 117

UFDD System Log Messages

This chapter describes messages with the **UFDD** prefix. They are generated by the Junos OS command-line interface (CLI) and management process (mgd), which together form the Junos user interface that accepts and processes input from users and client applications.

UFDD_GROUP_ACTION_COMPLETE

System Log Message	UFD action complete for group <i>error-message</i>
Description	Downlink ports configured under group was disabled through UFD action.
Type	Event: This message reports an event, not an error
Severity	alert
Facility	LOG_DAEMON

UFDD_LINK_CHANGE

System Log Message	UFD Grp <i>group-name</i> : Downlink <i>interface-name</i> is <i>state</i>
Description	Status of downlink in link-to-disable changed.
Type	Error: An error occurred
Severity	alert
Facility	LOG_DAEMON
Cause	Status change of Uplinks in link-to-monitor list.

CHAPTER 118

UI System Log Messages

This chapter describes messages with the **UI** prefix. They are generated by the Junos OS command-line interface (CLI) and management process (mgd), which together form the Junos user interface that accepts and processes input from users and client applications.

UI_AUTH_BAD_LOCATION

System Log Message	User ' <i>username</i> ' not allowed to log in from host <i>client-name</i> (<i>client-address</i>)
Description	The indicated user was denied login based on the location from which the user was logging in.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_AUTH

UI_AUTH_EVENT

System Log Message	Authenticated user ' <i>username</i> ' at permission level ' <i>authentication-level</i> '
Description	The management process (mgd) authenticated the indicated user.
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

UI_AUTH_INVALID_CHALLENGE

System Log Message	Received invalid authentication challenge for user ' <i>username</i> ': <i>response</i>
Description	When a user logs onto the routing platform and attempts to authenticate, the CLI and management process (mgd) use a challenge-and-response system to limit the exposure of sensitive information such as passwords and keys. The format of the challenge generated by mgd was incorrect.
Type	Error: An error occurred
Severity	error

Facility	LOG_USER
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

UI_BOOTTIME_FAILED

System Log Message	Unable to fetch boot time: <i>error-message</i>
Description	The management process (mgd) could not retrieve the system boot time from the kernel.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

UI_CFG_AUDIT_NEW

System Log Message	User ' <i>username</i> ' action: <i>pathname new-name</i>
Description	The indicated user created a new configuration object by copying or renaming an existing object as indicated.
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

UI_CFG_AUDIT_OTHER

System Log Message	User ' <i>username</i> ' action: <i>pathname delimitervalue</i>
Description	The indicated user deleted, activated, or deactivated a configuration object, as indicated. The Junos configuration log facility logged the change.
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

UI_CFG_AUDIT_SET

System Log Message	User ' <i>username</i> ' action: <i>pathname delimiterdata -> "value"</i>
Description	The indicated user set a value for a configuration object, as indicated.
Type	Event: This message reports an event, not an error

Severity info

Facility ANY

UI_CFG_AUDIT_SET_SECRET

System Log Message User '*username*' action: *pathname*

Description The indicated user set a value for a configuration object, as indicated. For security, the actual value (which might be an authentication key or password, for example) is not recorded.

Type Event: This message reports an event, not an error

Severity info

Facility ANY

UI_CHILD_ARGS_EXCEEDED

System Log Message Too many arguments for child process '*command*'

Description The management process (mgd) invokes some commands on behalf of users. It supplied more arguments than the command's syntax statement specifies.

Type Error: An error occurred

Severity error

Facility ANY

Cause An internal software failure occurred.

Action Contact your technical support representative.

UI_CHILD_CHANGE_USER

System Log Message Unable to switch to local user: *username*

Description The management process (mgd) invokes some commands on behalf of users. Its attempt to adopt the UID of the indicated user failed.

Type Error: An error occurred

Severity error

Facility ANY

Cause An internal software failure occurred.

Action Contact your technical support representative.

UI_CHILD_EXEC

System Log Message Child exec failed for command '*command*': *error-message*

Description	The management process (mgd) invoked the <code>exec()</code> system call while creating a child processes to execute the indicated command on its behalf. The system call failed.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

UI_CHILD_EXITED

System Log Message	Child exited: PID <i>pid</i> , status <i>return-value</i> <i>core-dump-status</i> , command ' <i>command</i> '
Description	The management process (mgd) created a child process to execute the indicated command for it. The child process exited unexpectedly with the indicated status code.
Type	Error: An error occurred
Severity	notice
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

UI_CHILD_FOPEN

System Log Message	Unable to append to log ' <i>filename</i> ': <i>error-message</i>
Description	The management process (mgd) attempted to save the output from a command in the indicated log file, but could not open the file.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

UI_CHILD_OUTPUT

System Log Message	Child output: <i>message</i>
Description	The management process (mgd) spawned a child process that output some messages which were requested to be hidden but need to be logged for informational purposes.

Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

UI_CHILD_PIPE_FAILED

System Log Message	Unable to create pipe for command ' <i>command</i> ': <i>error-message</i>
Description	The management process (mgd) created a child process to execute the indicated command for it. Its attempt to create pipes for communication with the child process failed.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative. For more information, see KB19125.

UI_CHILD_STOPPED

System Log Message	Child stopped: PID <i>pid</i> , signal= <i>signal-name</i> core-dump-status, command=' <i>command</i> ')
Description	The management process (mgd) created a child process to execute the indicated command for it. The child process received the indicated signal and stopped.
Type	Error: An error occurred
Severity	notice
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

UI_CHILD_WAITPID

System Log Message	waitpid failed: PID <i>pid</i> , rc <i>return-value</i> , status <i>status-code</i> : <i>error-message</i>
Description	The management process (mgd) created a child process to execute a command for it. It could not wait for the child process to finish.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	An internal software failure occurred.

Action Contact your technical support representative.

UI_CLASS_MODIFIED_USERS

System Log Message Class '*class-name*' modified, affects users: *username*

Description The indicated class was modified, affecting the indicated users, who are assigned to that class

Type Event: This message reports an event, not an error

Severity info

Facility ANY

UI_CLI_IDLE_TIMEOUT

System Log Message Idle timeout for user '*username*' exceeded and session terminated

Description The indicated user's session was ended after a period of prolonged inactivity.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_USER

UI_CMDLINE_READ_LINE

System Log Message User '*username*', command '*command*'

Description The indicated user typed the indicated command at the CLI prompt and pressed the Enter key, sending the command string to the management process (mgd).

Type Event: This message reports an event, not an error

Severity info

Facility LOG_AUTH

UI_CMD_AUTH_REGEX_INVALID

System Log Message Invalid '*allow-deny*' command authorization regular expression '*regular-expression*': *error-message*

Description An operation that attempted to set command or configuration authorization included the indicated regular expression. The operation failed because the expression syntax was invalid.

Type Error: An error occurred

Severity error

Facility ANY

Action Correct any errors in the regular expression.

UI_COMMIT

System Log Message	User ' <i>username</i> ' requested ' <i>command</i> ' operation (comment: <i>message</i>)
Description	The indicated user requested the indicated type of commit operation on the candidate configuration and added the indicated comment. The 'commit' operation applies to the local Routing Engine and the 'commit synchronize' operation to both Routing Engines.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY

UI_COMMIT_AT_ABORT

System Log Message	<i>reason</i> , will try again
Description	An attempt to complete a pending commit operation was cancelled for the indicated reason.
Type	Error: An error occurred
Severity	error
Facility	ANY

UI_COMMIT_AT_COMPLETED

System Log Message	'commit at' was successful
Description	Changes to the candidate configuration were activated at the time scheduled by a 'commit at' operation.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY

UI_COMMIT_AT_FAILED

System Log Message	<i>reason</i> , scheduled commit cleared
Description	A 'commit at' operation did not complete, for the indicated reason.
Type	Error: An error occurred
Severity	error
Facility	ANY

UI_COMMIT_COMPLETED

System Log Message	commit complete
Description	Changes to the candidate configuration were committed successfully.

Type	Event: This message reports an event, not an error
Severity	warning
Facility	ANY

UI_COMMIT_COMPRESS_FAILED

System Log Message Unable to compress file '*filename*'

Description As part of committing a new configuration, the management process (mgd) compresses and saves a copy of the configuration. mgd saved the configuration file in regular format because it could not compress it.

Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	The Routing Engine is low on resources.
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

UI_COMMIT_CONFIRMED_REMINDER

System Log Message 'commit confirmed' must be confirmed within *duration* minutes

Description A 'commit confirmed' operation has activated the candidate configuration temporarily. If the commit is not confirmed within the indicated number of minutes (for example, by the command-line interface (CLI) 'commit' command), the management process (mgd) will roll back to the previous configuration.

Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY

UI_COMMIT_EMPTY_CONTAINER

System Log Message Skipped empty object '*node-name*'

Description Some container objects are marked for automatic removal from the configuration hierarchy if they are empty when the user who created them changes to the top ([edit]) level of the hierarchy or exits configuration mode. While committing the candidate configuration, the management process (mgd) encountered such an object that was empty but not removed.

Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

- Cause** When the commit operation began, the user who created the new container object had not populated it and was in configuration mode but not at the top level of the hierarchy.
- Action** Populate or remove the empty object before committing the configuration. The user who created the object can remove it by exiting configuration mode or issuing the 'top' command to move to the top level of the hierarchy.

UI_COMMIT_NOT_CONFIRMED

- System Log Message** Commit was not confirmed; *message*
- Description** The 'commit confirmed' operation commits a configuration but requires confirmation within a defined number of minutes for the commit to become permanent. If the commit is not confirmed (by the 'commit' command, for example), the management process (mgd) automatically rolls back to the previously committed configuration. The automatic rollback restores management access to the routing platform in case an error in the configuration blocks access.
- Type** Event: This message reports an event, not an error
- Severity** notice
- Facility** LOG_AUTH

UI_COMMIT_PREV_CNF_SAVED

- System Log Message** Previously committed configuration saved to *filename*
- Description** In case automatic rollback of unconfirmed commit fails, previously committed configuration is saved up for further inspection.
- Type** Event: This message reports an event, not an error
- Severity** notice
- Facility** LOG_AUTH
- Cause** The cause of the problem might be recorded in messages that precede this message in the system log.

UI_COMMIT_PROGRESS

- System Log Message** Commit operation in progress: *message*
- Description** As it performed a commit operation, the management process (mgd) recorded its execution of the indicated step.
- Type** Event: This message reports an event, not an error
- Severity** info
- Facility** ANY

UI_COMMIT_ROLLBACK_FAILED

System Log Message	Automatic rollback failed
Description	The 'commit confirmed' operation commits a configuration but requires confirmation within a defined number of minutes for the commit to become permanent. If the commit is not confirmed (by the 'commit' command, for example), the management process (mgd) automatically rolls back to the previously committed configuration. The 'commit confirmed' operation was not confirmed, but mgd could not roll back the configuration. The configuration might be in an indeterminate state.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH
Cause	The cause of the problem might be recorded in messages that precede this message in the system log.

UI_COMMIT_SYNC_FORCE

System Log Message	All logins to local configuration database were terminated because forced 'commit synchronize' operation was invoked on other Routing Engine
Description	The 'commit synchronize force' command was issued on the other Routing Engine on the router. All login sessions in the local configuration database were terminated and the configuration from the other Routing Engine was committed on the local Routing Engine.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY

UI_COND_GROUPS

System Log Message	<i>message 'group-name' is reason</i>
Description	Conditional groups may get internally effective or revoked as per specified condition
Type	Event: This message reports an event, not an error
Severity	info
Facility	ANY

UI_COND_GROUPS_COMMIT

System Log Message	Cond-Groups: <i>message</i>
Description	Info about an attempt to complete a pending commit operation as by indicated reason.
Type	Event: This message reports an event, not an error

Severity info

Facility ANY

UI_COND_GROUPS_COMMIT_ABORT

System Log Message Cond-Groups: *reason*

Description An attempt to complete a pending commit operation was cancelled for the indicated reason.

Type Error: An error occurred

Severity error

Facility ANY

UI_CONFIGURATION_ERROR

System Log Message Process: *process-name*, path: *pathname*, statement: *configuration-statement*, *error-message*

Description The indicated process found a problem in its configuration.

Type Error: An error occurred

Severity error

Facility ANY

UI_CONFIGURATION_WARNING

System Log Message Process: *process-name*, path: *pathname*, statement: *configuration-statement*, *warning-message*

Description The indicated process found a problem in its configuration.

Type Error: An error occurred

Severity warning

Facility ANY

UI_CONNECT_COMMITD_FAILED

System Log Message *process-name error-message*

Description Commitd is not up to provide access to ephemeral db

Type Error: An error occurred

Severity error

Facility ANY

UI_DAEMON_ACCEPT_FAILED

System Log Message *connection-type* socket connection accept failed: *error-message*

Description The management process (mgd) did not accept an incoming connection request.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

Cause An internal software failure occurred.

Action Contact your technical support representative.

UI_DAEMON_FORK_FAILED

System Log Message Unable to create session child: *error-message*

Description The management process (mgd) invokes the fork() system call to create a copy of itself for each CLI session. The system call failed.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

Cause An internal software failure occurred.

Action Contact your technical support representative.

UI_DAEMON_SELECT_FAILED

System Log Message select failed: *error-message*

Description The management process (mgd) uses the select() system call to listen for incoming connection requests on a socket. The system call failed.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

Cause An internal software failure occurred.

Action Contact your technical support representative.

UI_DAEMON_SOCKET_FAILED

System Log Message *connection-type* socket create failed: *error-message*

Description The management process (mgd) uses sockets to communicate with other JUNOS software processes running on the routing platform. It could not allocate a socket.

Type Error: An error occurred

Severity	error
Facility	LOG_AUTH
Cause	System resources are exhausted.
Action	Contact your technical support representative.

UI_DBASE_ACCESS_FAILED

System Log Message	Unable to reaccess configuration database file ' <i>filename</i> ', address <i>address</i> , size <i>size</i> : <i>reason</i>
Description	To increase the size of the configuration database, the management process (mgd) must unmap the database from its address space, change the database size, and remap the database. The remapping operation failed.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

UI_DBASE_CHECKOUT_FAILED

System Log Message	Database ' <i>filename</i> ' is out of data and needs to be rebuilt
Description	When the routing platform boots, the management process (mgd) checks the configuration database for internal consistency. It found one or more inconsistencies.
Type	Event: This message reports an event, not an error
Severity	alert
Facility	ANY
Cause	mgd restarted after new Junos OS was installed.
Action	None; mgd will rebuild the database.

UI_DBASE_EXTEND_FAILED

System Log Message	Unable to extend configuration database file ' <i>filename</i> ' to size <i>requested-size</i> : <i>reason</i>
Description	The management process (mgd) could not increase the configuration database to the indicated size.
Type	Error: An error occurred
Severity	error

Facility	ANY
Cause	The hard disk is defective or is not installed in the routing platform.
Action	Repair or replace the hard disk.
Cause	There is insufficient disk space on the /var partition on the hard disk.
Action	Delete user files from the /var/homes directory to increase the available disk space.

UI_DBASE_LOGIN_EVENT

System Log Message	User ' <i>username</i> ' entering configuration mode
Description	The indicated user entered configuration mode (logged into the configuration database).
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY

UI_DBASE_LOGOUT_EVENT

System Log Message	User ' <i>username</i> ' exiting configuration mode
Description	The indicated user exited configuration mode (logged out of the configuration database).
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY

UI_DBASE_MISMATCH_EXTENT

System Log Message	Database header extent mismatch for file ' <i>filename</i> ': expecting <i>expected-value</i> , got <i>received-value</i>
Description	The header in the configuration database records the highest address allocated in the database. The management process (mgd) discovered that the highest address actually allocated in the database does not match the header value.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	The database file is corrupted.
Action	Contact your technical support representative.

UI_DBASE_MISMATCH_MAJOR

System Log Message	Database header major version number mismatch for file ' <i>filename</i> ': expecting <i>expected-value</i> , got <i>received-value</i>
Description	For compatibility, the version number recorded in the header of the configuration database must match the version of Junos OS running on the routing platform. The management process (mgd) discovered that the major parts (for example, '5' in '5.x') of the version numbers do not match.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	A recent software upgrade did not complete successfully.
Action	Issue the 'show version' command to check the JUNOS version. If necessary, issue the 'request system reboot' command to reboot the routing platform and complete the software installation.
Cause	The database file is corrupted.
Action	Contact your technical support representative.

UI_DBASE_MISMATCH_MINOR

System Log Message	Database header minor version number mismatch for file ' <i>filename</i> ': expecting <i>expected-value</i> , got <i>received-value</i>
Description	For compatibility, the version number recorded in the header of the configuration database must match the version of Junos OS running on the routing platform. The management process (mgd) discovered that the minor parts (for example, '2' in 'x.2') of the version numbers do not match.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	A recent software upgrade did not complete successfully.
Action	Issue the 'show version' command to check the Junos version. If necessary, issue the 'request system reboot' command to reboot the routing platform and complete the software installation.
Cause	The database file is corrupted.
Action	Contact your technical support representative.

UI_DBASE_MISMATCH_SEQUENCE

System Log Message	Database header sequence numbers mismatch for file ' <i>filename</i> '. If a package has just been added or deleted, please verify and commit the configuration.
Description	The header of the configuration database records the version number of the configuration schema (possible set of statements) used when the database was created. To prevent corruption, all Junos processes that access the database must use the same schema. The management process (mgd) discovered that the version number for the Junos OS installed on the routing platform does not match the header value.
Type	Error: An error occurred
Severity	warning
Facility	ANY
Cause	A recent software upgrade did not complete successfully.
Action	Issue the 'show version' command to check the Junos version. If necessary, issue the 'request system reboot' command to reboot the routing platform and complete the software installation.
Cause	The database file is corrupted.
Action	Contact your technical support representative.

UI_DBASE_MISMATCH_SIZE

System Log Message	Database header size mismatch for file ' <i>filename</i> ': expecting <i>expected-value</i> x, got <i>received-value</i>
Description	The header of the configuration database records the database size. The management process (mgd) discovered that the size of the actual database file does not match the header value.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	The database file is corrupted.
Action	Contact your technical support representative.

UI_DBASE_OPEN_FAILED

System Log Message	Database open failed for file ' <i>filename</i> ': <i>reason</i>
Description	The management process (mgd) could not open the indicated configuration database file.

Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	The database file does not exist.
Action	Select a different filename or create a new configuration.
Cause	The /config directory does not have sufficient space for a new database.
Action	Remove files from the /config directory to make more space available.

UI_DBASE_REBUILD_FAILED

System Log Message	<i>modeusername</i> rebuild of the database ' <i>filename</i> ' failed
Description	The management process (mgd) could not rebuild the configuration database file.
Type	Error: An error occurred
Severity	alert
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB19123 .

UI_DBASE_REBUILD_SCHEMA_FAILED

System Log Message	Automatic rebuild of the database failed
Description	The management process (mgd) could not rebuild the schema for the configuration database.
Type	Error: An error occurred
Severity	alert
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB19124 .

UI_DBASE_REBUILD_STARTED

System Log Message	<i>modeusername</i> rebuild/rollback of the database ' <i>filename</i> ' started
---------------------------	--

Description The management process (mgd) began to rebuild the configuration database file or its schema because that object was not current. The operation will complete shortly.

Type Event: This message reports an event, not an error

Severity alert

Facility ANY

UI_DBASE_RECREATE

System Log Message User '*username*' attempting database re-creation

Description The management process (mgd) discovered that the version of Junos OS running on the routing platform does not match the version of the current configuration database. In response to a prompt from mgd, the indicated user initiated a rebuilding of the database.

Type Event: This message reports an event, not an error

Severity notice

Facility ANY

UI_DBASE_REOPEN_FAILED

System Log Message Reopen of the database failed

Description After rebuilding the schema file for the configuration database, the management process (mgd) closes the file and reopens it in read-only mode to prevent corruption. It could not reopen the file.

Type Error: An error occurred

Severity alert

Facility ANY

Cause An internal software failure occurred.

Action Contact your technical support representative. For more information, see <http://kb.juniper.net/InfoCenter/index?page=content&id=KB19125>.

UI_DELTA_CONSTRAINT_CHECK_FAILED

System Log Message Delta constraint check process failed

Description Delta constraint check process failed to build constraint dependency graph database. Subsequent commits will not be able to use delta constraint check feature. Next reboot will recreate constraint dependency graph database.

Type Error: An error occurred

Severity error

Facility ANY

UI_DELTA_CONSTRAINT_CHECK_FORK_FAILED

System Log Message	Management process can not fork delta constraint check process
Description	Management process can not fork delta constraint check process. Management process would fall back to existing mechanism of constraint checks.
Type	Error: An error occurred
Severity	info
Facility	ANY

UI_DELTA_CONSTRAINT_CHECK_NOT_RUNNING

System Log Message	delta constraint check process can not run because persist groups is not configured
Description	Delta constraint check process can not run because persist groups feature is not configured. To configure persist groups feature 'system commit persist-groups-inheritance' knob is required.
Type	Error: An error occurred
Severity	info
Facility	ANY

UI_DELTA_CONSTRAINT_CHECK_VERSION_MISMATCH

System Log Message	constraint dependency graph database version mismatch
Description	Constraint dependency graph database version mismatch. Delta constraint check process can not make use of this database.
Type	Error: An error occurred
Severity	info
Facility	ANY

UI_DELTA_EXPORTER_FAILURE

System Log Message	delta exporter process failed to export juniper.conf
Description	Delta exporter process failed to export juniper.conf due to some error. Subsequent commits will not use delta-export feature. Please try to reinitialize the delta exporter process using request system commit delta-exporter initialize to use this feature in subsequent commits also.
Type	Error: An error occurred
Severity	error
Facility	ANY

UI_DELTA_EXPORTER_INIT_FAIL

System Log Message	Delta exporter db initialization failed
Description	Delta exporter process failed to initialize it's internal data base. The delta-export feature will not be used for subsequent commits
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH

UI_DUPLICATE_UID

System Log Message	Users <i>username1</i> and <i>username2</i> have the same UID <i>uid</i>
Description	The Junos OS allows multiple user login accounts to share the same UID. This message was logged in case site policy dictates that users should not share UIDs.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY
Action	Assign different UIDs to the affected users.

UI_EPHEMERAL_COMMIT

System Log Message	User ' <i>username</i> ' has requested commit on ' <i>instance</i> ' ephemeral database
Description	The indicated user requested the commit operation on the indicated ephemeral instance
Type	Event: This message reports an event, not an error
Severity	warning
Facility	ANY

UI_EPHEMERAL_COMMIT_COMPLETED

System Log Message	commit complete on ' <i>instance</i> ' ephemeral database
Description	Changes to the indicated ephemeral instance were committed successfully
Type	Event: This message reports an event, not an error
Severity	warning
Facility	ANY

UI_EPHEMERAL_DB_EVENT

System Log Message	User ' <i>username</i> ' is changing configuration into ephemeral db: ' <i>operation</i> '
Description	The indicated user is changing ephemeral db configuration

Type Event: This message reports an event, not an error
Severity info
Facility ANY

UI_FACTORY_OPERATION

System Log Message Committing factory default configuration because CONFIG button was pressed and held
Description The management process (mgd) began a commit operation to activate the factory default configuration, because the CONFIG button on the chassis was pressed and held for 15 seconds or more.

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_AUTH

UI_INITIALSETUP_OPERATION

System Log Message Committing EZsetup configuration as EZsetup option is chosen
Description The management process (mgd) began a commit operation to activate the pre initial setup configuration, because the initial-setup option was selected from the LCD Menu.

Type Event: This message reports an event, not an error
Severity notice
Facility LOG_AUTH

UI_INVALID_REMOTE_PERMISSION

System Log Message invalid permissions from authorization server: *permission-name*
Description RADIUS and TACACS+ authorization servers use Juniper Networks vendor-specific attributes (VSAs) to specify user permissions. A VSA included the indicated permission name, which is invalid.

Type Error: An error occurred
Severity error
Facility ANY

UI_JUNOSCRIP_COMMAND

System Log Message User '*username*' used JUNOScript client to run command '*command*'
Description The indicated user ran the indicated command using the JUNOS XML management protocol.

Type Event: This message reports an event, not an error
Severity info

Facility LOG_AUTH

UI_JUNOSCRIPT_ERROR

System Log Message JUNOScript error: *error-message*

Description The management process (mgd) normally sends an error message to the Junos OS CLI or JUNOScript API client in an <xnm:error> tag. It could not send the tag, so it sent the indicated error message in an XML comment instead.

Type Error: An error occurred

Severity warning

Facility ANY

UI_LCC_NO_MASTER

System Log Message No master Routing Engine defined for LCC/cc

Description By default, the JUNOS software installed on the TX Matrix platform in a routing matrix is automatically copied to and installed on all T640 routing nodes in the routing matrix. The software was not installed on the indicated T640 routing node (line-card chassis, or LCC), because the management process (mgd) on the TX Matrix platform could not determine which Routing Engine on the LCC was the master.

Type Error: An error occurred

Severity error

Facility ANY

Action Resolve the mastership situation on the T640 routing node and install the software on its Routing Engines.

UI_LOAD_EVENT

System Log Message User '*username*' is performing a '*operation*'

Description The indicated user requested the indicated operation ('rollback, ' or 'load' or one of its variants) on the configuration database. The existing configuration database was deleted and a new database was created based on a text file.

Type Event: This message reports an event, not an error

Severity notice

Facility ANY

UI_LOAD_JUNOS_DEFAULT_FILE_EVENT

System Log Message Loading the default config from *pathname*

Description The system is loading junos default configuration from file.

Type Event: This message reports an event, not an error

Severity info
Facility ANY

UI_LOCK_AUTHENTICATION_FAILED

System Log Message *username* failed authentication when unprotecting *pathname*

Description Given hierarchy is locked using apply-lock statement and the user can only unprotect the hierarchy by meeting the required criteria set in apply-lock statement. User doesn't belong to users/classes list configured in apply-lock statement or he has failed to provide correct protect password.

Type Event: This message reports an event, not an error

Severity info

Facility ANY

UI_LOCK_AUTHENTICATION_SUCCESS

System Log Message *username* authenticated to unprotect *pathname*

Description Given hierarchy is locked using apply-lock statement and the user can only unprotect the hierarchy by meeting the required criteria set in apply-lock statement. User authenticated himself successfully.

Type Event: This message reports an event, not an error

Severity info

Facility ANY

UI_LOGIN_EVENT

System Log Message User '*username*' login, class '*class-name*' local-peer[*pid*], ssh-connection '*ssh-connection*', client-mode '*client-mode*'

Description The indicated user started a Junos OS CLI session.

Type Event: This message reports an event, not an error

Severity info

Facility ANY

UI_LOGOUT_EVENT

System Log Message User '*username*' logout

Description The indicated user exited from a Junos OS CLI session.

Type Event: This message reports an event, not an error

Severity info

Facility ANY

UI_LOST_CONN

System Log Message	Lost connection to daemon ' <i>process-name</i> '
Description	The management process (mgd) uses sockets to communicate with other Junos OS processes. The socket it was using for the indicated process closed prematurely.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

UI_MASTERSHIP_EVENT

System Log Message	<i>mastership-event card-name</i> mastership by ' <i>username</i> '
Description	Some redundant routing platform components use a master/standby system in which the master component is active and the standby is inactive but ready to assume mastership. The indicated user performed the indicated operation to modify component mastership.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	ANY

UI_MOTD_PROPAGATE_ERROR

System Log Message	Unable to propagate login announcement (motd) to <i>pathname</i>
Description	The management process (mgd) could not create or write to the indicated file, which was the intended location for the message of the day (MOTD) configured at the [edit system login announcement] hierarchy level.
Type	Error: An error occurred
Severity	error
Facility	ANY

UI_NETCONF_CMD

System Log Message	User ' <i>username</i> ' used NETCONF client to run command ' <i>command</i> '
Description	The indicated user ran the indicated command using the NETCONF application programming interface (API).
Type	Event: This message reports an event, not an error

Severity info
Facility LOG_AUTH

UI_NETCONF_ERROR

System Log Message NETCONF error: *error-message*

Description The management process (mgd) normally sends error messages to the NETCONF client in the <rpc-error> tag element. It could not send that tag element, and instead sent the indicated error message in an XML comment.

Type Error: An error occurred

Severity warning

Facility ANY

UI_PARSE_JUNOSCRIPT_ATTRIBUTES

System Log Message Error parsing attributes in client *junoscript* tag

Description The management process (mgd) encountered an error and exited while attempting to parse the XML attributes in the <junoscript> tag submitted by a client application.

Type Error: An error occurred

Severity error

Facility LOG_AUTH

UI_READ_FAILED

System Log Message read failed for peer *peer-name*: *error-message*

Description The management process (mgd) uses the read() system call to access data sent by other Junos processes running on the routing platform (referred to as its peers). The system call failed for the indicated process.

Type Error: An error occurred

Severity error

Facility ANY

Cause An internal software failure occurred.

Action Contact your technical support representative. For more information, see KB19126.

UI_READ_TIMEOUT

System Log Message Timeout on read of peer '*peer-name*'

Description When communicating with other Junos processes running on the routing platform (referred to as peers), the management process (mgd) waits only a defined period for responses to arrive. The timeout period passed for the indicated process.

Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY

UI_REBOOT_EVENT

System Log Message	System <i>halt-reboot</i> by ' <i>username</i> '
Description	The indicated software process restarted as requested by the indicated user.

Type	Event: This message reports an event, not an error
Severity	warning
Facility	ANY

UI_RESCUE_OPERATION

System Log Message	Committing rescue configuration because CONFIG button was pressed
Description	The management process (mgd) began a commit operation to activate the rescue configuration, because the CONFIG button on the chassis was pressed.

Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_AUTH

UI_RESTART_EVENT

System Log Message	User ' <i>username</i> ' restarting daemon ' <i>process-name</i> ' <i>description</i>
Description	The indicated software process restarted as requested by the indicated user.

Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_AUTH

UI_RESTART_FAILED_EVENT

System Log Message	Failed to restart ' <i>process-name</i> '
Description	Failed to restart the indicated software process as requested by the user.

Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_AUTH

UI_SCHEMA_CHECKOUT_FAILED

System Log Message	Schema is out of date and needs to be rebuilt
---------------------------	---

Description	The Junos user interface schema file records all CLI commands and configuration statements available in the Junos OS. While initializing, the new management process (mgd) determined that the schema's sequence number means that the schema is incompatible with the Junos OS installed on the routing platform.
Type	Error: An error occurred
Severity	alert
Facility	ANY
Cause	The schema is out of date.
Action	None; mgd will rebuild the schema based on the current Junos version.

UI_SCHEMA_MISMATCH_MAJOR

System Log Message	Schema major version mismatch for package <i>package-name</i> (<i>expected-value</i> vs. <i>received-value</i>)
Description	The Junos user interface schema file records all CLI commands and configuration statements available in the Junos OS. While initializing, the management process (mgd) discovered that the major part (for example, '5' in '5.x') of the schema version number does not match the major version number of the Junos OS installed on the routing platform. The mismatch could lead to corruption of the configuration database.
Type	Error: An error occurred
Severity	error
Facility	ANY
Cause	The schema is incompatible with the installed Junos OS.
Action	None; mgd will rebuild the schema based on the current Junos version.
Cause	An internal software failure occurred.
Action	Contact your technical support representative.

UI_SCHEMA_MISMATCH_SEQUENCE

System Log Message	Schema header sequence numbers mismatch for package <i>package-name</i>
Description	The Junos user interface schema file records all CLI commands and configuration statements available in the Junos OS. Schema sequence numbers serve as a checksum of the configuration data schema and ensure that the software used to access the database understands the data. The value in the database file did not match the expected value.
Type	Error: An error occurred

Severity	error
Facility	ANY
Cause	The Junos OS installation did not succeed, possibly because of an internal software error.
Action	Contact your technical support representative.

UI_SCHEMA_SEQUENCE_ERROR

System Log Message	Schema sequence number mismatch
Description	The Junos user interface schema file records all CLI commands and configuration statements available in the Junos OS. The management process (mgd) rebuilds the schema as necessary to be compatible with the Junos OS installed on the routing platform. A sequence number in the schema acts as a checksum that represents its content and format. A Junos process attempted to access the schema but determined that the schema's sequence number means that it is incompatible with the process.
Type	Error: An error occurred
Severity	alert
Facility	ANY
Cause	An internal software failure occurred.
Action	Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB19126 .

UI_SCRIPTS_COPY_FAILED

System Log Message	Unable to copy scripts to re: <i>peer-name</i>
Description	This message is an error.
Type	Error: An error occurred
Severity	error
Facility	ANY

UI_SOCK_WARNING

System Log Message	<i>process-name warning-message</i>
Description	Default socket buffer size retained, could not resize
Type	Error: An error occurred
Severity	error
Facility	ANY

UI_VERSION_FAILED

System Log Message	Unable to fetch system version: <i>error-message</i>
Description	The management process (mgd) could not retrieve version information from the kernel.
Type	Error: An error occurred
Severity	error
Facility	ANY
Action	Contact your technical support representative.

UI_WRITE_RECONNECT

System Log Message	Re-establishing connection to peer ' <i>peer-name</i> '
Description	The management process (mgd) reconnected to the indicated Junos process running on the routing platform.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	ANY

UI_XPATH_CONSTRAINT_CHECK_FAILED

System Log Message	XPath Constraint check failed
Description	Xpath constraint check failed. Cannot proceed with the commit process
Type	Error: An error occurred
Severity	error
Facility	ANY

UI_XPATH_CONSTRAINT_DA_INIT_FAILED

System Log Message	Direct-Access module for Xpath Constraint checkfailed to initialize
Description	Direct-access module failed to initialize, XPath constraint check cannot proceed. Disable the direct access to proceed with commit.
Type	Error: An error occurred
Severity	error
Facility	ANY

UI_XPATH_CONSTRAINT_DOC_FAILED

System Log Message	Failed to create XML Document Object
---------------------------	--------------------------------------

Description Failed to create the XML DOM required for XPath constraint check. Cannot proceed with XPath constraint checks. Commit will fail.

Type Error: An error occurred

Severity error

Facility ANY

UTMD System Log Messages

This chapter describes messages with the **UTMD** prefix. They are generated by the unified threat management process (utmd) which protects the network from all types of attack.

UTMD_MAILNOTIFIER_FAILURE

System Log Message	Error: <i>error-message</i>
Description	The connection could have failed during memory allocation or socket creation
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON

UTMD_MALLOC_FAILURE

System Log Message	Out of memory. Unable to malloc <i>error-message</i> bytes
Description	The example process (utmd) could not allocate memory for a resource possibly due to lack of memory
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB19127 .

UTMD_SSAMLIB_FAILURE

System Log Message	ssamlib call returned error : <i>error-message</i>
Description	The example process (utmd) encountered an error while calling a function or from a callback of the ssamlib library.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

Action For more information, see
<http://kb.juniper.net/InfoCenter/index?page=content&id=KB19128>.

CHAPTER 120

VCCPD System Log Messages

This chapter describes messages with the **VCCPD** prefix. They are generated by the virtual chassis control protocol (vccpd) process which exchanges link-state advertisement based discovery messages between all the packet forwarding engines (PFE) through the virtual chassis ports (VCP).

VCCPD_FABRIC_LSDB_LOOKUP_FAILED

System Log Message	<i>device-id:error-message: Unable to find function-name for dev line-number.</i>
Description	This LSP is not present in the vccpdf link-state database.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Cause	1. The vccpdf link-state database is full and no additional memory can be allocated for it. 2. LSP already deleted from the database.

VCCPD_FABRIC_MALLOC_FAILURE

System Log Message	<i>function-name:line-number - error-message.</i>
Description	The vccpdf process could not allocate memory. The vccpdf process tried to continue functioning, but the lack of memory usually causes the process to fail. An administrator needs to restart it at some point.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	No additional memory is available. Either system resources are exhausted or a software error occurred (such as a memory leak).
Action	Perform one or more of the following actions: (1) Check for unusually high memory usage by vccpdf, (2) Add more memory to the switch. (3) Contact your technical support representative. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB18830 .

VCCPD_FABRIC_PROCESS_OIR_MSG

System Log Message	<i>argument1: argument2.</i>
Description	OIR is user driven feature. After user initiates OIR using CLI configuration, OIR processing through tlv updates for fabric node info based on the oir_slot received through gencfg messages from chassis.
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Cause	OIR initiation through.

VCCPD_FABRIC_SYSCTL_ERROR

System Log Message	<i>function-name: Read error for error-message: sysctl-error (errno error-code).</i>
Description	The vccpdf process received the indicated error from the indicated sysctl() operation.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.
Cause	It is possible that the kernel lacked the resources to fulfill the request.

VCCPD_FABRIC_SYSTEM

System Log Message	<i>function-name: error-message (errno error-code).</i>
Description	A system call made by vccpdf process failed.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.
Cause	It is possible that the kernel lacked the resources to fulfill the request.

VCCPD_FABRIC_UNSUPPORTED_RE_TYPE

System Log Message	<i>argument1: argument2: argument3.</i>
Description	Vccpdf process detected unsupported RE-type during initialization. The installed software version doesn't support the indicated RE-type.

Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Action	Contact your technical support representative.

VCCPD_FABRIC_UNSUPPORTED_SKU_TYPE

System Log Message *argument1*: Neighbor sku type *argument2* *argument3*.

Description Vccpdf process detected neighbor with unsupported SKU-type while forming adjacency for the given device.

Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON
Cause	Due to miswiring of FTE interfaces.

VCCPD_KNL_VERSION

System Log Message Routing socket version mismatch (kernel *kernel-version* != vccpd *version*) -- kernel upgrade required

Description The virtual chassis control protocol process (VCCPD) discovered that the kernel does not support the version of routing sockets it requires.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	The kernel version is older than the VCCPD version.
Action	Upgrade the kernel package.

VCCPD_KNL_VERSIONNONE

System Log Message Routing socket message type *message-type*'s version is not supported by kernel, expected *version* -- kernel upgrade required

Description The virtual chassis control protocol process (VCCPD) discovered that the kernel does not support the routing socket message types that it requires.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	The kernel version is older than the VCCPD version.

Action Upgrade the kernel package.

VCCPD_KNL_VERSIONOLD

System Log Message Routing socket message type *message-type*'s version is older than expected (*kernel-version* < *version*) -- consider upgrading the kernel

Description The virtual chassis control protocol process (VCCPD) discovered that the kernel uses an older version of routing socket message types than it does.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

Cause The kernel version is older than the VCCPD version.

Action Upgrade the kernel package.

VCCPD_PROTOCOL_ADJDOWN

System Log Message Lost adjacency to *neighbor-system-ids* on *interface-name*,

Description A virtual chassis adjacency with the indicated neighboring switch was terminated. The local switch no longer exchanges information with the neighboring switch.

Type Event: This message reports an event, not an error

Severity notice

Facility LOG_DAEMON

Cause The communication path to the neighboring switch was disrupted, a protocol error occurred, or the neighboring switch was powered down.

VCCPD_PROTOCOL_ADJUP

System Log Message New adjacency to *neighbor-system-ids* on *interface-name*

Description A virtual chassis adjacency was established with the indicated neighboring switch. The local switch can now exchange information with it.

Type Event: This message reports an event, not an error

Severity info

Facility LOG_DAEMON

VCCPD_PROTOCOL_LSPCKSUM

System Log Message LSP checksum error, interface *interface-name*, LSP id *lspl*, sequence *sequence-number*, checksum *checksum*, lifetime *duration*

Description	The indicated vccpd link-state PDU (LSP) failed an internal checksum validity test, implying that it was corrupted.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON
Cause	The packet was corrupted in transit between the neighboring switch and this switch, or memory on one of the switches was corrupted.
Action	None, unless a large number of these messages appear in the system log file. The corrupted LSP is purged from the virtual chassis and sent again by the originator. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB19129 .

VCCPD_PROTOCOL_OVERLOAD

System Log Message vccpd database overload

Description The vccpd link-state database is full and no additional memory can be allocated for it.

Type	Error: An error occurred
Severity	alert
Facility	LOG_DAEMON
Cause	No additional memory is available for storing vccpd link-state information. Either system resources are exhausted or a software error occurred (such as a memory leak).
Action	Perform one or more of the following actions: (1) Check for unusually high memory usage by vccpd, (2) Add more memory to the switch. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB19130 .

VCCPD_SYSTEM

System Log Message *reason: error-message*

Description A system call made by this process failed.

Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	It is possible that the kernel lacked the resources to fulfill the request.

VM System Log Messages

This chapter describes messages with the **VM** prefix.

VM_DCF_PB_COMMUNICATION_FAILED

System Log Message	Network problems encountered during PB API call. <i>uid</i> .
Description	The communication failure happens when pb is unreachable. The pb no-longer able to communicate with the junos on dcf or vdcf
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	Either the pb node is dead or the communication between the pb and junos vms is down
Action	Perform following actions to re-establish the communication: (1) check the link both up/down between pb and junos vms. (2) check whether either of the pb nodes is up and running Once the communication is restored the requests in the queue will be processed normally.

VM_DCF_PB_INVALID_IMAGE

System Log Message	Invalid image <i>tag-name</i> for the vm request <i>device-name</i>
Description	Image requested for the vm creation to the pb is invalid. The corresponding image is not found at pb node
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	The junos image copy is not present at pb node
Action	None

VM_DCF_PB_INVALID_UUID

System Log Message	Delete request to PB failed: invalid uuid <i>uid</i>
Description	The delete request for the vm delete did not get executed as uuid is not found in the PB uuid DB.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	The vm spawned by PB in the past may have went down and this is not communicated to the parent of the node.
Action	None

VM_DCF_PB_RESOURCE_FAILURE

System Log Message	No resource to spawn new vm of the label <i>device-name</i>
Description	The request for the virtual machine (VM) create did not get executed because of the resource failure at the pb node.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	The pb node is running out of resources to spawn new vms. The server may be hosting vms nearing the capacity
Action	Check whether the servers on which the vms are hosted is up and running. If possible provide additional resources to meet the demand

CHAPTER 122

VRRPD System Log Messages

This chapter describes messages with the **VRRPD** prefix. They are generated by the Virtual Router Redundancy Protocol (VRRP) process (vrrpd), which provides the user interface for management of VRRP groups.

VRRPD_ADVERT_TIME_MISMATCH

System Log Message Packet received by *interface-name* for VRRP group *vrrp-group-id* had advertisement time *received-value* ms instead of required *expected-value* ms

Description A Virtual Routing Redundancy Protocol (VRRP) advertisement packet received by the indicated interface for the indicated VRRP group specified an advertisement-timer value different from the value configured for the interface and group. The advertisement interval must be the same on all routing platforms in the VRRP group. For VRRP with IPv4, the value is set by the 'advertise-interval <seconds>' or 'fast-interval <milliseconds>' statement at the [edit interfaces <interface-name> unit <logical-unit-number> family inet address <address> vrrp-group <group-number>] hierarchy level. For VRRP with IPv6, the value is set by the 'inet6-advertise-interval <seconds>' or 'fast-interval <milliseconds>' statement at the [edit interfaces <interface-name> unit <logical-unit-number> family inet6 address <address> vrrp-inet6-group <group-number>] hierarchy level.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

VRRPD_AUTH_INFO_INVALID

System Log Message VRRP ad packet from *ip-address* received by interface *interface-name.interface-unit* for group *vrrp-group-id* was invalid: *error-message*

Description The Virtual Routing Redundancy Protocol (VRRP) advertisement packet sent from the indicated IP address and received by the VRRP process (vrrpd) for the indicated group at the indicated address contained invalid authentication information. The message 'invalid-authentication-type' means that the packet specifies an authentication type that is not defined in RFC 2338, Virtual Router Redundancy Protocol. The message 'authentication-type-mismatch' means that the packet specifies an authentication type different from the type used by the interface that received the packet. The message

'authentication-key-mismatch' means that the authentication key in the packet is incorrect.

Type Error: An error occurred
Severity warning
Facility LOG_DAEMON

VRRPD_GET_TRAP_HEADER_FAILED

System Log Message Request for trap signature header failed

Description The Virtual Routing Redundancy Protocol (VRRP) process requested the signature header for an SNMP trap. The request failed.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON
Cause An internal software failure occurred.

VRRPD_LINK_LOCAL_ADD_MISMATCH

System Log Message Link-Local Address Mismatch: *received-value expected-value*

Description The indicated interface received a Virtual Routing Redundancy protocol (VRRP) packet for the indicated VRRP group in which the link-local address was different from the one configured for the group and interface

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

VRRPD_MISSING_VIP

System Log Message Packet received by *interface-name* for VRRP group *vrrp-group-id* did not include required virtual IP address *ip-address*

Description The indicated interface received a Virtual Routing Redundancy protocol (VRRP) packet for the indicated VRRP group in which the list of virtual IP addresses did not include the indicated address. For VRRP with IPv4, the list is defined by the 'virtual-address [<addresses>]' statement at the [edit interfaces <interface-name> unit <logical-unit-number> family inet address <address> vrrp-group <group-number>] hierarchy level. For VRRP with IPv6, the list is defined by the 'virtual-inet6-address [<addresses>]' statement at the [edit interfaces <interface-name> unit <logical-unit-number> family inet6 address <address> vrrp-inet6-group <group-number>] hierarchy level.

Type Error: An error occurred

Severity	error
Facility	LOG_DAEMON
Action	For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB19131 .

VRRPD_NEW_BACKUP

System Log Message	Interface <i>interface-name.interface-unit</i> (local address <i>interface-address</i>) became VRRP backup for group <i>vrrp-group-id</i>
Description	The indicated interface became the Virtual Routing Redundancy Protocol (VRRP) backup for the indicated VRRP group. The VRRP process (vrrpd) stopped sending VRRP advertisements for the virtual IP address on the interface that corresponds to the group.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

VRRPD_NEW_MASTER

System Log Message	Interface <i>interface-name.interface-unit</i> (local address <i>interface-address</i>) became VRRP master for group <i>vrrp-group-id</i> with master reason <i>reason</i>
Description	The indicated interface became the Virtual Routing Redundancy Protocol (VRRP) master for the indicated VRRP group. The VRRP process (vrrpd) started sending VRRP advertisements for the virtual IP address on the interface that corresponds to the group.
Type	Event: This message reports an event, not an error
Severity	warning
Facility	LOG_DAEMON

VRRPD_V3_PROTO_ERROR

System Log Message	VRRP ad packet from <i>ip-address</i> received by interface <i>interface-name.interface-unit</i> was invalid: <i>reason</i>
Description	The Virtual Routing Redundancy Protocol (VRRP) advertisement packet sent from the indicated IP address and received by the VRRP process (vrrpd) contained protocol error as specified in RFC 6527.
Type	Error: An error occurred
Severity	warning
Facility	LOG_DAEMON

VRRPD_VIP_COUNT_MISMATCH

System Log Message	Packet received by <i>interface-name</i> for VRRP group <i>vrrp-group-id</i> had <i>received-value</i> virtual IP addresses instead of required <i>expected-value</i>
---------------------------	---

Description The indicated interface received a Virtual Routing Redundancy Protocol (VRRP) packet for the indicated VRRP group in which the number of virtual IP addresses was different from the number of addresses configured for the group and interface. The list of addresses must be the same on all routing platforms in a VRRP group. For VRRP with IPv4, the list is defined by the 'virtual-address [<addresses>]' statement at the [edit interfaces <interface-name> unit <logical-unit-number> family inet address <address> vrrp-group <group-number>] hierarchy level. For VRRP with IPv6, the list is defined by the 'virtual-inet6-address [<addresses>]' statement at the [edit interfaces <interface-name> unit <logical-unit-number> family inet6 address <address> vrrp-inet6-group <group-number>] hierarchy level.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

WEB System Log Messages

This chapter describes messages with the **WEB** prefix. They are generated by the Hypertext Transfer Protocol process (httpd), which provides a graphical user interface (GUI) for monitoring and configuring J Series Services Routers.

WEB_AUTH_FAIL

System Log Message	Unable to authenticate httpd client (username <i>username</i>)
Description	The checklogin authentication process could not authenticate the indicated user.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_AUTH

WEB_AUTH_SUCCESS

System Log Message	Authenticated httpd client (username <i>username</i>)
Description	The checklogin authentication process authenticated the indicated user.
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_AUTH

WEB_AUTH_TIME_EXCEEDED

System Log Message	Login attempt exceeded maximum processing time
Description	The checklogin process halted a login attempt because it took longer than the maximum processing time allowed.
Type	Error: An error occurred
Severity	error
Facility	LOG_AUTH

WEB_CERT_FILE_NOT_FOUND

System Log Message	Could not find certificate file ' <i>filename</i> ', disabling HTTPS
---------------------------	--

Description http-gk could not open the configured HTTPS certificate for reading.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

WEB_CERT_FILE_NOT_FOUND_RETRY

System Log Message Could not find certificate file '*filename*', retry after 1 sec

Description http-gk retry to open the configured HTTPS certificate for reading.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

WEB_CHILD_STATE

System Log Message Unable to retrieve child state: *error-message*

Description The Web management process (httpd) could not retrieve state information for a child process that had exited, for the indicated reason.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

WEB_CONFIG_OPEN_ERROR

System Log Message Could not open '*filename*' for writing

Description httpd-gk could not open the web server configuration file for writing.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

WEB_CONFIG_WRITE_ERROR

System Log Message Could not write '*filename*' configuration. Disk full?

Description httpd-gk could not write the web server configuration file to disk.

Type Error: An error occurred

Severity error

Facility LOG_DAEMON

WEB_COULDNT_START_HTTPD

System Log Message	Could not fork httpd process!
Description	The Web management gatekeeper process (httpd-gk) could not start the web management process (httpd).
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

WEB_EVENTLIB_INIT

System Log Message	Unable to initialize event library: <i>error-message</i>
Description	The Web management gatekeeper process (httpd-gk) attempted to initialize the event library during startup. The attempt failed for the indicated reason.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

WEB_KEYPAIR_FILE_NOT_FOUND

System Log Message	Could not find key pair file ' <i>filename</i> ', disabling HTTPS
Description	http-gk could not open the configured HTTPS key pair file for reading.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

WEB_MGD_BIND_ERROR

System Log Message	Could not bind mgd listener socket: <i>error-message</i>
Description	The web management process could not open the MGD listening socket.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

WEB_MGD_CHMOD_ERROR

System Log Message	Could not chmod mgd listener socket
Description	The web management process could not change the MGD listening socket to proper file permissions.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

WEB_MGD_CONNECT_ERROR

System Log Message Could not connect to mgd management socket
Description The web management process could not connect to the MGD management socket.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

WEB_MGD_FCNTL_ERROR

System Log Message Could not set incoming mgd request to nonblocking
Description The web management process could not set the MGD listening socket to nonblocking.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

WEB_MGD_LISTEN_ERROR

System Log Message Could not listen mgd listener socket: *error-message*
Description The web management process could not open the MGD listening socket.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON
Action For more information, see
<http://kb.juniper.net/InfoCenter/index?page=content&id=KB19134>.

WEB_MGD_RECVMSG_PEEK_ERROR

System Log Message Could not peek recvmsg() mgd connection
Description The web management process could not peek the incoming MGD request.

Type Error: An error occurred
Severity error
Facility LOG_DAEMON

WEB_MGD_SOCKET_ERROR

System Log Message	Could not create mgd listener socket
Description	The web management process could not open the MGD listening socket.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

WEB_PIDFILE_LOCK

System Log Message	Unable to lock PID file <i>pathname: error-message</i>
Description	The Web management gatekeeper process (httpd-gk) attempted to lock the indicated file, which records its process ID (PID). The file serves to prevent multiple instances of httpd-gk from running simultaneously. The attempt failed for the indicated reason.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

WEB_PIDFILE_UPDATE

System Log Message	Unable to update PID file <i>pathname: error-message</i>
Description	The Web management gatekeeper process (httpd-gk) attempted to update the indicated file, which records the process ID (PID) of the running httpd-gk process. The file serves to prevent multiple instances of httpd-gk from running simultaneously. The attempt failed for the indicated reason.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON
Cause	The most common reason is that another httpd-gk process was already running.

WEB_UNAME_FAILED

System Log Message	Unable to retrieve system hostname: <i>error-message</i>
Description	The Web management gatekeeper process (httpd-gk) attempted to retrieve and store the local hostname, which it shares with its remote clients. The attempt failed for the indicated reason.
Type	Error: An error occurred
Severity	error
Facility	LOG_DAEMON

WEB_WEBAUTH_AUTH_FAIL

System Log Message	Web-authentication of user <i>username</i> with fwauthd failed
Description	The web-authentication authentication process was unable to authenticate the indicated user
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

WEB_WEBAUTH_AUTH_OK

System Log Message	Web-authentication of user <i>username</i> with fwauthd successful
Description	The web-authentication authentication process was able to authenticate the indicated user successfully
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_DAEMON

WEB_WEBAUTH_CONNECT_FAIL

System Log Message	Unable to connect to fwauthd on socket <i>file-descriptor: error-message</i>
Description	The web-authentication authentication process could not connect to fwauthd daemon on the indicated socket
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_DAEMON

CHAPTER 124

WEBFILTER System Log Messages

This chapter describes messages with the **WEBFILTER** prefix. They are generated by the web filtering process (webfilter) which allows you to manage Internet usage by preventing access to inappropriate web content.

WEBFILTER_CACHE_NOT_ENABLED

System Log Message	Failed to enable the web-filtering category cache
Description	Failed to enable the category cache for web-filtering
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_FIREWALL
Cause	Temporarily out of system memory
Action	No recommended action. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB19136 .

WEBFILTER_INTERNAL_ERROR

System Log Message	Error encountered: <i>error-message</i>
Description	An error is encountered in a periodical task or during a server update
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_FIREWALL
Cause	An error is encountered in a periodical task or during a server update
Action	No recommended action

WEBFILTER_REQUEST_NOT_CHECKED

System Log Message	Error encountered: server down, failed to check request <i>error-message</i>
---------------------------	--

Description	Web-filtering failed to check a web request,
Type	Event: This message reports an event, not an error
Severity	error
Facility	LOG_FIREWALL
Cause	Failed to talk to web server, temporary out of system memory or internal error
Action	No recommended action. For more information, see http://kb.juniper.net/InfoCenter/index?page=content&id=KB19137 .

WEBFILTER_SERVER_CONNECTED

System Log Message	Successfully connected to webfilter server <i>name</i>
Description	Client successfully connected to web server
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_FIREWALL
Cause	Successfully connected to web server
Action	No recommended action

WEBFILTER_SERVER_DISCONNECTED

System Log Message	Webfilter: server <i>name</i> disconnected
Description	A socket error is encountered upon connecting to a web server
Type	Event: This message reports an event, not an error
Severity	notice
Facility	LOG_FIREWALL
Cause	A socket error is encountered upon connecting to a web server
Action	No recommended action

WEBFILTER_SERVER_ERROR

System Log Message	WebFilter: An error is received from server <i>name</i> (<i>0xstatus-code</i>): <i>error-message</i>
Description	An error status is received from web server
Type	Event: This message reports an event, not an error
Severity	notice

Facility LOG_FIREWALL

Cause An error status is received from web server

PART 3

Index

- [Index on page 881](#)

Index

Symbols

!	regular expression operator system logging.....	26, 28
#	comments in configuration statements.....	lxx
\$	regular expression operator system logging.....	26, 28
()	regular expression operator system logging.....	26, 28
{ },	in syntax descriptions.....	lxx
*	regular expression operator system logging.....	26, 27
+	regular expression operator system logging.....	26, 28
.	regular expression operator system logging.....	26, 27
< > ,	in syntax descriptions.....	lxx
?	regular expression operator system logging.....	26, 28
[]	regular expression operator system logging.....	26, 28
[],	in configuration statements.....	lxx
^	regular expression operator system logging.....	26, 28
{ }	in configuration statements.....	lxx
	regular expression operator system logging.....	26, 28
(pipe),	in syntax descriptions.....	lxx

A

AAA system log messages.....	69
ACCT system log messages.....	71

ALARM system log messages.....	75
alert (system logging severity level 1).....	24
AMS System Log Messages.....	81
ANALYZER System Log Messages.....	83
ANTISPAM system log messages.....	85
any (system logging facility).....	10
any (system logging severity level).....	10
APPID system log messages.....	87
APPIDD system log messages.....	89
APPPXY system log messages.....	91
APTRACK system log messages.....	93
archive statement usage guidelines.....	20
archive-sites statement system logging usage guidelines.....	20
ASP system log messages.....	97
AUDITD system log messages.....	129
AUTHD system log messages.....	133
authorization (system logging facility).....	10
option to facility-override statement.....	17
AUTOCONFD system log messages.....	137
AV system log messages.....	141

B

BBE system log messages.....	145
BFDD system log messages.....	147
BGP system log messages.....	151
BOOTPD system log messages.....	165
braces, in configuration statements.....	lxx
brackets angle, in syntax descriptions.....	lxx
square, in configuration statements.....	lxx
brief statement system logging usage guidelines.....	12

C

CFMD system log messages.....	171
change-log (system logging facility).....	10
CHASSISD system log messages.....	175
CHASSISM system log messages.....	275
CLKSYNCD system log messages.....	277
comments, in configuration statements.....	lxx
Common Criteria system logging.....	7
conflict-log (system logging facility).....	10

console statement	
system logging	
usage guidelines.....	13
conventions	
text and syntax.....	lxix
COSD system log messages.....	287
critical (system logging severity level 2).....	24
curly braces, in configuration statements.....	lxx
customer support.....	lxxi
contacting JTAC.....	lxxi

D

daemon (system logging facility).....	10
option to facility-override statement.....	17
DCBX system log messages.....	303
DCD system log messages.....	305
DDOS system log messages.....	313
debug (system logging severity level 7).....	24
dfc (system logging facility).....	10
DFCD system log messages.....	317
DFWD system log messages.....	321
DHCPD system log messages.....	323
DIAM system log messages.....	329
documentation	
comments on.....	lxx
DOTIXD system log messages.....	331
DYNAMIC system log messages.....	335

E

emergency (system logging severity level 0).....	24
error (system logging severity level 3).....	24
ESWD system log messages.....	341
EVENTD system log messages.....	351
explicit-priority statement	
usage guidelines	
routing matrix.....	36, 45
single-chassis system.....	22

F

FABOAMD System Log Messages.....	361
facilities (system logging)	
alternate for remote machine.....	17
default for remote machine.....	17
for local machine.....	10
mapping of codes to names.....	23
facility-override statement	
system logging	
usage guidelines.....	15
FC system log messages.....	363

FCOE system log messages.....	369
file statement	
system logging	
usage guidelines.....	11
files	
system log messages, archiving.....	20
files statement	
system logging	
usage guidelines.....	20
FIP system log messages.....	371
FIPS system log messages.....	375
firewall (system logging facility).....	10
FLOW system log messages.....	377
font conventions.....	lxix
FPCLOGIN system log messages.....	381
FSAD system log messages.....	383
ftp (system logging facility).....	10
option to facility-override statement.....	17
FUD system log messages.....	393
FWAUTH system log messages.....	399

G

GPRSD system log messages.....	405
--------------------------------	-----

H

help syslog command	
usage guidelines.....	60
HNCACHED system log messages.....	407
host statement	
system logging	
usage guidelines for routing	
matrix.....	37, 46
usage guidelines for single-chassis	
system.....	13

I

ICCPD system log messages.....	409
icons defined, notice.....	lxviii
IDP system log messages.....	411
info (system logging severity level 6).....	24
interactive-commands (system logging	
facility).....	10

J

JADE system log messages.....	419
JCS system log messages.....	423
JDIAMETERD system log messages.....	429
JIVED system log messages.....	431
JNUD system log messages.....	435

JPTSPD system log messages.....	437
JSERVICES system log messages.....	441
JSRPD system log messages.....	445
JTASK system log messages.....	455
Junos-FIPS	
system logging.....	7

K

kernel (system logging facility).....	10
option to facility-override statement.....	18

L

L2ALD system log messages.....	487
L2CPD system log messages.....	503
L2TPD system log messages.....	507
LACP system log messages.....	537
LACPD system log messages.....	539
LFMD system log messages.....	541
LIBJNX system log messages.....	543
LIBJSNMP system log messages.....	553
LIBMSRPC system log messages.....	559
LICENSE system log messages.....	563
LLDP system log messages.....	571
local0 - local7 (options to facility-override statement).....	18
log files	
specifying properties.....	20
log-prefix statement	
system logging	
usage guidelines.....	19
LOGIN system log messages.....	573
LPDFD system log messages.....	579
LRMUX system log messages.....	581
LSYSD system log messages.....	583

M

manuals	
comments on.....	lxx
match statement	
usage guidelines.....	25
MBG system log messages.....	585
MCSN system log messages.....	601
MIB2D system log messages.....	603
MPLS_OAM system log messages.....	611

N

NEXTHOP system log messages.....	615
----------------------------------	-----

no-world-readable statement	
system logging	
usage guidelines.....	20
notice (system logging severity level 5).....	24
notice icons defined.....	lxviii
NSD system log messages.....	617
NSTRACED system log messages.....	619
NTPD system log messages.....	623

O

operators, regular expression	
system logging.....	26, 27
other-routing-engine option to host statement	
usage guidelines	
routing matrix.....	37, 46
single-chassis system.....	13

P

parentheses, in syntax descriptions.....	lxx
pfe (system logging facility).....	10
PFE system log messages.....	621, 627
PFED system log messages.....	635
PGCPD system log messages.....	637
PING system log messages.....	639
PKID system log messages.....	643
PPMD system log messages.....	653
PPPD system log messages.....	655
priorities	
system logging, including in log message	
for routing matrix.....	36, 45
for single-chassis system.....	22
PROFILER system log messages.....	663

R

RDD system log messages.....	665
regular expression operators	
system logging.....	27
RMOPD system log messages.....	669
routing matrix	
system logging.....	31
RPD system log messages.....	673
RT system log messages.....	747
RTLOG system log messages.....	761
RTLOGD system log messages.....	763

S

SAVAL system log messages.....	767
scc-master option to host statement	
usage guidelines.....	33

SDK system log messages.....	769	regular expression filtering.....	25
SDXD system log messages.....	771	regular expression operators.....	27
severity levels for system logging.....	24	routing matrix.....	31
size statement		severity levels.....	24
system logging		single-chassis system.....	7
usage guidelines.....	20	timestamp, modifying.....	25
SMTPD system log messages.....	777	SYSTEM system log messages.....	813
SNMP system log messages.....	779		
SNMPD system log messages.....	783	T	
source-address statement		technical support	
system logging		contacting JTAC.....	lxxi
usage guidelines for routing		TFTPD system log messages.....	815
matrix.....	37, 46	time-format statement	
usage guidelines for single-chassis		usage guidelines.....	25
system.....	15	transfer-interval statement	
SPD system log messages.....	797	system logging	
SSH system log messages.....	805	usage guidelines.....	20
SSHD system log messages.....	807, 809	TRANSPORTD system log messages.....	819
start-time statement		TX Matrix platform	
system logging		system logging.....	31
usage guidelines.....	20		
structured-data statement		U	
usage guidelines.....	12	UFDD system log messages.....	823
support, technical See technical support		UI system log messages.....	825
syntax conventions.....	lxix	user (system logging facility).....	10
syslog statement		option to facility-override statement.....	18
system processes		user statement	
usage guidelines.....	3	system logging	
system logging		usage guidelines.....	13
Common Criteria.....	7	UTMD system log messages.....	855
defaults.....	4		
different on each node in routing matrix.....	38	V	
disabling.....	28	VCCPD system log messages.....	857
examples.....	29	VM system log messages.....	863
facilities		VRRPD system log messages.....	865
alternate for remote machine.....	17		
default for remote machine.....	17	W	
for local machine.....	10	warning (system logging severity level 4).....	24
mapping of codes to names.....	23	WEB system log messages.....	869
files, archiving.....	20	WEBFILTER system log messages.....	875
forwarding messages in routing matrix.....	33	world-readable statement	
Junos-FIPS.....	7	system logging	
message descriptions		usage guidelines.....	20
displaying.....	60		
fields in.....	60		
messages, displaying			
generated by Junos process.....	55		
generated by service on PIC.....	56		
structured-data format.....	51		