

## mirror disable

---

<b>Syntax</b>	mirror disable <i>triggerType triggerValue</i>
<b>Release Information</b>	Command introduced before JUNOS Release 7.1.0. <b>nas-port-id</b> added in JUNOS Release 7.1.0.
<b>Description</b>	Disables a packet mirroring session that was dynamically configured for a subscriber; uses the trigger information to identify the subscriber's session. There is no <b>no</b> version.
<b>Options</b>	<ul style="list-style-type: none"><li>■ <i>triggerType</i>—One of the following RADIUS attributes that was used as the trigger to start the packet mirroring session<ul style="list-style-type: none"><li>■ acct-session-id—Acct-Session-Id, RADIUS attribute [44]</li><li>■ calling-station-id—Calling-Station-Id, RADIUS attribute [31]</li><li>■ ip-address—Framed-IP-Address, RADIUS attribute [8]; associated with the virtual router where the command is issued, RADIUS VSA [26-1]</li><li>■ nas-port-id—NAS-Port-Id, RADIUS attribute [87]</li><li>■ username—User-Name, RADIUS attribute [1]; associated with the virtual router where the command is issued, RADIUS VSA [26-1]</li></ul></li><li>■ <i>triggerValue</i>—Value of the <i>triggerType</i> (the specified RADIUS attribute) that identifies the subscriber</li></ul>
<b>Mode</b>	Privileged Exec
<b>Related Topics</b>	<ul style="list-style-type: none"><li>■ Configuring CLI-Based Mirroring</li><li>■ Configuring RADIUS-Based Mirroring</li></ul>

