

virtual-router

Syntax `virtual-router vrName | :vrfName | vrName:vrfName`
`no virtual-router vrName [wait-for-completion [waitSeconds]]`

Release Information Command introduced before JUNOS Release 7.1.0.

Description Creates a virtual router or accesses the context of a previously created virtual router or a VRF. The **no** version deletes the virtual router, and the router defaults to the default virtual router. Issuing a **no** version that specifies an existing VRF only displays the error message: “ Cannot delete a VRF with this command.” You must use the **no ip vrf** command to remove a VRF.



NOTE: In Domain Map Configuration mode, the **virtual-router** command has been replaced by the `router-name` command and may be removed completely from Domain Map Configuration mode in a future release.

- Options**
- `vrName`—Name of the virtual router; a string of 1–32 alphanumeric characters
 - `:vrfName`—Name of a VRF in the current VR context; a string of 1–32 alphanumeric characters
 - `vrName:vrfName`—Name of a VRF in the context of a VR other than the current VR
 - `wait-for-completion`—Specifies (in the absence of `waitSeconds`) that the CLI waits for completion of the **no** version operation before it returns a prompt, regardless of how long that takes
 - `waitSeconds`—Number of seconds, in the range 1–64000, that the CLI waits before it returns a prompt, regardless of whether the **no** version operation has been completed

Mode Global Configuration, Privileged Exec

