

## node

---

|                            |  |
|----------------------------|--|
| <b>Syntax</b>              | [ no ] { <i>typeOfInterface</i>   set   superset } node [ group <i>trafficClassGroup</i>   scheduler-profile <i>schedulerProfileName</i> ]*  |
| <b>Release Information</b> | Command introduced before JUNOS Release 7.1.0.<br><b>svlan</b> keyword added in JUNOS Release 7.1.0.<br><b>set</b> and <b>superset</b> keywords added in JUNOS Release 9.2.0.  |
| <b>Description</b>         | Specifies that a scheduler node be configured for each interface of the given interface type. The <b>no</b> version removes this rule from the QoS profile.  |
| <b>Options</b>             | <ul style="list-style-type: none"><li>■ <i>typeOfInterface</i>—Interface types for scheduler nodes to be configured: atm, atm-vc, atm-vp, bridge, ethernet, fr-vc, ip, ip-tunnel, ipv6, l2tp-session, l2tp-tunnel, lsp, serial, server-port, svlan, vlan</li><li>■ set—Configures the node for an interface set</li><li>■ superset—Configures the node for an interface superset</li><li>■ <i>trafficClassGroup</i>—Name of the traffic class group</li><li>■ <i>schedulerProfileName</i>—Name of the scheduler profile</li><li>■ *—Indicates that one or more parameters can be repeated multiple times in a list in the command line</li></ul> |
| <b>Mode</b>                | QoS Profile Configuration  |
| <b>Related Topics</b>      | <ul style="list-style-type: none"><li>■ Configuring a QoS Profile</li><li>■ Configuring Shadow Nodes</li><li>■ Configuring a Basic Parameter Definition for QoS Administrators</li><li>■ Attaching a QoS Profile to an Interface Superset or an Interface Set</li></ul>  |

---

Published: 2009-10-08