

Directory Configuration Properties for the Threat Mitigation Application

The LDAP tab in the local configuration tool for the Threat Mitigation Application contains the following fields.

Configuration Directory URL

- URL of the primary directory.
- Value—URL in the format `ldap://<host>:<port>/`
 - <host> —IP address or name of directory host
 - <port> —Port of directory host
- Default—`ldap://127.0.0.1:389/`
- Property name—`Config.java.naming.provider.url`

Backup Configuration Directory URLs

- List of redundant directories.
- Value—Space-separated list of URLs; URLs have the format `ldap://<host>:<port>/`
 - <host> —IP address or name of directory host
 - <port> —Port of directory host
- Default—Unspecified
- Example—`ldap://192.0.2.1:389/ ldap://192.0.2.3:389/`
- Property name—`Config.net.juniper.smgmt.des.backup_provider_urls`

Configuration Directory Authentication DN

- DN of the directory entry that defines the username with which the SRC component accesses the directory.
- Value—<DN>
- Default—`cn = nic, ou = Components, o = Operators, o = umc`
- Example—`cn = conf, o = Operators, o = umc`
- Property name—`Config.java.naming.security.principal`

Configuration Directory Password

- Password with which the Threat Mitigation Application accesses the directory.
- Value—Text string
- Default—`nic`
- Example—`secret`

- Property name—Config.java.naming.security.credentials

Connect Timeouts [s]

- Maximum time that the directory eventing system (DES) waits for the directory to respond.
- Value—Number of seconds in the range 1–2147483647
- Default—10
- Example—5
- Property name—Config.net.juniper.smgmt.des.connect.timeout