

General Configuration Properties for the Threat Mitigation Application

The Other tab in the local configuration tool for the Threat Mitigation Application contains the following fields.

Service Activation Interface

- Type of interface on which the service would be activated.
- Value
 - Provider Edge Interface (JUNOS subscriber-facing interface)
 - Forwarding Interface (JUNOS forwarding interface)
 - Subscriber Interface (JUNOS subscriber interface)
- Guidelines—If you change this property, you must reconfigure your NIC host. For more information, see Overview of Configuring and Deploying the SRC-TMP.
- Default—Provider Edge Interface

Retailer Domain

- Retailer domain for the SRC-TMP.
- Value—Text string
- Guidelines—This property must match one of the retailer domain names defined for the retailer in the target of the subscriber classification rules used for the interfaces managed by the Threat Mitigation Application. For more information about adding retailers, see Adding Retailers (SRC CLI).
- Default—thma

Path

- Pathname for the SRC-TMP and record servlet.
- Value— < pathname >
- Default—/thmp/record

Retry Period

- Time to wait between two consecutive retries of all pending service activation or deactivation tasks that were executed unsuccessfully.
- Value—Number of milliseconds in the range 0–9223372036854775807
- Guidelines—Do not specify too small a value, because the number of attempts could cause network overload.
- Default—60000

Retry Delay

- Time to wait before retrying all pending service activation or deactivation tasks that were executed unsuccessfully.
- Value—Number of milliseconds in the range 0–9223372036854775807
- Default—10000