

## Specifying Tracking Plug-Ins for Enterprise Subscribers on JUNOS Routing Platforms

When user-tracking plug-ins are attached to the retailer on JUNOS routing platforms, login names are needed to trigger the user-tracking plug-in and generate user-tracking events. Because enterprise subscribers do not have a login name, the SRC-VTA cannot get the required user-tracking events.

To allow enterprise subscribers on JUNOS routing platforms to use retailer-attached user-tracking plug-ins, configure the EJB adapter plug-in to filter SAE plug-in events for the SRC-VTA and send SAE tracking events to the SRC-VTA.

To use the EJB adapter plug-in to send events for a specific retailer:

1. Configure the event admitter of the EJB adapter plug-in (see Configuring the SAE to Send Tracking Events to the SRC-VTA).

Specify the PA\_USER\_DN event attribute with the retailer's relative distinguished name (RDN). For example, the following event admitter matches events from subscribers in the SP-Quota retailer:

```
PA_USER_DN=*SP-Quota*
```

2. Configure the EJB adapter plug-in as the global subscriber-tracking plug-in for the SAE. See Configuring Tracking Plug-Ins.

In the sample procedure, the EJB adapter plug-in called QuotaVTA is configured as the subscriber-tracking plug-in in the nw-area SAE group.

```
[edit shared sae group nw-area configuration plug-ins event-publishers]  
user@host# set subscriber-tracking QuotaVTA
```

