

## Configuring the SRC-VTA to Send E-Mail Notifications

You can configure actions for the mailer processor that cause the SRC-VTA to send e-mail notifications. To configure actions to the mailer processor:

1. In the VTA Configuration Manager navigation pane, select **Edit**.
2. Under Current Configuration, select **Actions**.

A list of actions appears. For example:

The screenshot displays the Juniper VTA Configuration Manager web interface. The top header features the Juniper Networks logo and the text 'VTA Configuration Manager' with a link to 'Edit Configuration'. A left-hand navigation pane lists options: Home, Dir Connection, Configuration (expanded), Create, Edit (selected), Load, Commit, Import, and Export. The main content area is titled 'Current Configuration' and contains three tabs: Event Handlers, Actions (selected), and Processors. Under the 'Actions' tab, a section titled 'Quota VTA Actions' lists ten actions, each with a 'Delete' button: GetAccountBalances, CalcUsage, DebitAccounts, CalculateInterim, SetInterim, StopQuotaService, StartQuotaLocalService, StartQuotaInternetService, and TerminateSession. At the bottom of this section, there is a 'New Quota VTA Actions' label, an input field, and a 'Create' button. The footer of the interface includes the 'Juniper yourNet' logo.


Quota VTA Actions	
<a href="#">GetAccountBalances</a>	Delete
<a href="#">CalcUsage</a>	Delete
<a href="#">DebitAccounts</a>	Delete
<a href="#">CalculateInterim</a>	Delete
<a href="#">SetInterim</a>	Delete
<a href="#">StopQuotaService</a>	Delete
<a href="#">StartQuotaLocalService</a>	Delete
<a href="#">StartQuotaInternetService</a>	Delete
<a href="#">TerminateSession</a>	Delete

New Quota VTA Actions

Create


3. To add an action, enter a name for the action in the New Quota VTA Actions field, and click **Create**.

The action configuration screen appears.

EmailNotification					
Name	Value				
Processor	Mailer <input type="button" value="v"/>				
Function	<input type="text"/>				
Parameter 	<table border="1"> <thead> <tr> <th>Parameter Name</th> <th>Parameter Content</th> </tr> </thead> <tbody> <tr> <td colspan="2"><input type="button" value="Add Parameter"/></td> </tr> </tbody> </table>	Parameter Name	Parameter Content	<input type="button" value="Add Parameter"/>	
Parameter Name	Parameter Content				
<input type="button" value="Add Parameter"/>					
Abort On Error	<input type="text"/> <input type="button" value="v"/> <input type="button" value="Disable"/>				
<input type="button" value="Save"/>					

4. Select **Mailer** in the Processor field, and click **Save**. (If Mailer does not appear in the drop-down list, enable the mailer processor.)

An expanded configuration area for the action appears.

EmailNotification									
Name	Value								
Processor	Mailer <input type="button" value="v"/>								
Function	<input type="text" value="SendEmail"/>								
Parameter 	<table border="1"> <thead> <tr> <th>Parameter Name</th> <th>Parameter Content</th> </tr> </thead> <tbody> <tr> <td><input type="text"/></td> <td><input type="text"/></td> </tr> <tr> <td colspan="2"><input type="button" value="Add Parameter"/></td> </tr> </tbody> </table>	Parameter Name	Parameter Content	<input type="text"/>	<input type="text"/>	<input type="button" value="Add Parameter"/>		<input type="button" value="Delete"/> <input type="button" value="Disable"/>	
Parameter Name	Parameter Content								
<input type="text"/>	<input type="text"/>								
<input type="button" value="Add Parameter"/>									
Abort On Error	<input type="text"/> <input type="button" value="v"/> <input type="button" value="Disable"/>								
<input type="button" value="Save"/>									

5. Edit the action fields.

## E-Mail Notification Fields

### Processor

- Processor for which you are configuring the action.
- Value—Mailer (If Mailer does not appear in the drop-down list, enable the mailer processor.)
- Default—No value

### ***Function***

- Function calls that the mail processor invokes.
- Value
  - SendEmail—Sends e-mail messages. It provides no output.
- Default—No value

### ***Parameter Name***

- Parameters to pass to the processor.
- Value
  - “Recipient” —Address of the e-mail recipient
  - “From” —Address of the e-mail sender
  - “Subject” —Subject of the e-mail
  - “Text” —Text of the e-mail
- Default—No value

### ***Parameter Content***

- Values for the parameters.
- Value
  - Recipient—Address of the e-mail recipient
  - From—Address of the e-mail sender
  - Subject—Subject of the e-mail
  - Text—Text of the e-mail
- Default—No value

### ***Abort On Error***

- Disables or enables and sets the processing in response to an error.
- Value
  - Break—Stop processing the current event.
  - Continue—Continue with the next action, if any, in the same event handler.

- Next Event Handler—Continue with the next event handler (if any).
- Default—No value