

## **Configuring Local Properties for Dynamic Service Activator (C-Web Interface)**

---

Configure basic and initial properties, including directory connection and directory eventing properties. Tasks to configure the local properties for Dynamic Service Activator are:

- Configuring Basic Local Properties for Dynamic Service Activator on page 1
- Configuring Initial Properties for Dynamic Service Activator on page 1
- Configuring Initial Directory Connection Properties for Dynamic Service Activator on page 1
- Configuring Initial Directory Eventing Properties for Dynamic Service Activator on page 1

### ***Configuring Basic Local Properties for Dynamic Service Activator***

To configure basic local properties:

1. Click **Configure > Slot > Slot:0 > DSA**.
2. Enter information as described in the Help text in the main pane, and click **Apply**.

### ***Configuring Initial Properties for Dynamic Service Activator***

To configure initial local properties:

1. Click **Configure > Slot > Slot:0 > DSA > Initial**.
2. Enter information as described in the Help text in the main pane, and click **Apply**.

### ***Configuring Initial Directory Connection Properties for Dynamic Service Activator***

To configure directory connection properties:

1. Click **Configure > Slot > Slot:0 > DSA > Initial > Directory Connection**.

The Directory Connection pane appears.

2. Enter information as described in the Help text in the main pane, and click **Apply**.

### ***Configuring Initial Directory Eventing Properties for Dynamic Service Activator***

To configure initial directory eventing properties:

1. Click **Configure > Slot > Slot:0 > DSA > Initial > Directory Eventing**.

The Directory Eventing pane appears.

2. Enter information as described in the Help text in the main pane, and click **Apply**.

