

Adding Devices as Subscribers (SRC CLI)

Configure a device subscriber for subscriber sessions that manage the forwarding interface on JUNOS routing platforms and the router pseudo-subscriber on JUNOSe routers.

You can add devices as subscribers to subscriber folders, enterprises, and sites. Use the following configuration statements to add a device as a subscriber:

```
subscribers retailer name subscriber-folder folder-name device device-name {
  display-name display-name ;
  maximum-login maximum-login ;
  accounting-user-id accounting-user-id ;
  substitution [ substitution... ];
}
subscribers retailer name subscriber-folder folder-name enterprise name device
device-name {
  display-name display-name ;
  maximum-login maximum-login ;
  accounting-user-id accounting-user-id ;
  substitution [ substitution.. .];
}
subscribers retailer name subscriber-folder folder-name enterprise name site
name device device-name {
  display-name display-name ;
  maximum-login maximum-login ;
  accounting-user-id accounting-user-id ;
  substitution [ substitution... ];
}
```

To add a device as a subscriber:

1. From configuration mode, enter the device subscriber configuration. In this procedure, default@TMJunosA is the name of the device.

```
user@host# edit subscribers retailer SP-TM subscriber-folder devices device
default@TMJunosA
```

2. (Optional) Configure the name of the device as you want it to appear in SRC applications, such as portals.

```
[edit subscribers retailer SP-TM subscriber-folder devices device
default@TMJunosA]
user@host# set display-name display-name
```

3. (Optional) Configure the maximum number of concurrent logins for subscribers associated with this device.

```
[edit subscribers retailer SP-TM subscriber-folder devices device
default@TMJunosA]
user@host# set maximum-login maximum-login
```

4. (Optional) Configure the name that identifies the device in accounting records.

```
[edit subscribers retailer SP-TM subscriber-folder devices device
default@TMJunosA]
user@host# set accounting-user-id accounting-user-id
```

5. (Optional) Configure the actual values for parameters associated with this device.

```
[edit subscribers retailer SP-TM subscriber-folder devices device
default@TMJunosA]
user@host# set substitution [ substitution... ]
```

6. (Optional) Verify your configuration.

```
[edit subscribers retailer SP-TM subscriber-folder devices device
default@TMJunosA]
user@host# show
display-name "Profile for JUNOS router";
accounting-user-id JunosRouter
```