

## Adding Sites (SRC CLI)

---

Use the following configuration statements to add a site:

```
subscribers retailer name subscriber-folder folder-name enterprise name site
name {
  network [ network... ];
  display-name display-name ;
  accounting-user-id accounting-user-id ;
  description description ;
}
```

To add a site:

1. From configuration mode, enter the site configuration. In this procedure, ABCInc is the name of the enterprise, and Montreal is the name of the site.

```
user@host# edit subscribers retailer default subscriber-folder local enterprise
ABCInc site Montreal
```

2. (Optional) Record networks used at the site. If you build a custom enterprise manager application, you can access this information through the enterprise portal APIs.

```
[edit subscribers retailer default subscriber-folder local enterprise ABCInc site
Montreal]
user@host# set network [ network... ]
```

3. (Optional) Configure the name that is displayed in enterprise management portals, if different from the site name.

```
[edit subscribers retailer default subscriber-folder local enterprise ABCInc site
Montreal]
user@host# set display-name display-name
```

4. (Optional) Configure the name that identifies the site in accounting records.

```
[edit subscribers retailer default subscriber-folder local enterprise ABCInc site
Montreal]
user@host# set accounting-user-id accounting-user-id
```

5. (Optional) Enter a description of the site.

```
[edit subscribers retailer default subscriber-folder local enterprise ABCInc site
Montreal]
user@host# set description description
```

6. (Optional) Verify your configuration.

```
[edit subscribers retailer default subscriber-folder local enterprise
ABCInc site Montreal]
user@host# show
display-name "Montreal Office of ABC, Inc.";
```

```
accounting-user-id abcInc;  
description "This enterprise is sample data for use with JUNOS routers.";
```

7. Configure an access for the site. (See Configuring Accesses with the SRC CLI.)