

Configuring Subscriptions (SRC CLI)

After you add subscribers, you configure subscriptions for the subscribers. Residential or enterprise subscribers may also be able to configure subscriptions through the portal, and managers assigned to a subscriber object may be able to configure subscriptions for that object.

You must add a service to the directory before you can specify that service for subscribers. See Overview of Services for the SRC Software.

After you configure a subscription to a service, the service is available to the subscriber through the portal. Depending on the configuration, the subscriber may need to activate the service. You can configure schedules to define when services are available to subscribers. See Overview of Service Schedules.

To allow a subscriber to have a number of subscriptions to a service at the same time, each subscription:

- Must have its own parameter substitutions.
- Can be activated or deactivated independently.

An object for each subscription is created in the directory. The name of the object has the following format:

<ServiceName>%<SubscriptionId>

- <ServiceName> —Name of the service
- <SubscriptionId> —Name of the subscription

Other than the naming convention, multiple subscriptions are identical to regular subscriptions.

```
subscribers retailer name subscription subscription-name {
    status (active | suspended | hidden);
    activation (manual | automatically-on-login);
    activation-order activation-order ;
    substitution [ substitution... ];
}
subscribers retailer name subscriber-folder folder-name subscription
subscription-name {
    status (active | suspended | hidden);
    activation (manual | automatically-on-login);
    activation-order activation-order ;
    substitution [ substitution... ];
}
subscribers retailer name subscriber-folder folder-name subscriber name
subscription subscription-name {
    status (active | suspended | hidden);
    activation (manual | automatically-on-login);
    activation-order activation-order ;
    substitution [ substitution... ];
```

```

}
subscribers retailer name subscriber-folder folder-name enterprise name
  subscription subscription-name {
    status (active | suspended | hidden);
    activation (manual | automatically-on-login);
    activation-order activation-order ;
    substitution [ substitution... ];
  }
subscribers retailer name subscriber-folder folder-name enterprise name site
  name subscription subscription-name {
    status (active | suspended | hidden);
    activation (manual | automatically-on-login);
    activation-order activation-order ;
    substitution [ substitution... ];
  }
subscribers retailer name subscriber-folder folder-name enterprise name access
  name subscription subscription-name {
    status (active | suspended | hidden);
    activation (manual | automatically-on-login);
    activation-order activation-order ;
    substitution [ substitution... ];
  }
subscribers retailer name subscriber-folder folder-name device device-name
  subscription subscription-name {
    status (active | suspended | hidden);
    activation (manual | automatically-on-login);
    activation-order activation-order ;
    substitution [ substitution... ];
  }
subscribers retailer name subscriber-folder folder-name enterprise name device
  device-name subscription subscription-name {
    status (active | suspended | hidden);
    activation (manual | automatically-on-login);
    activation-order activation-order ;
    substitution [ substitution... ];
  }
subscribers retailer name subscriber-folder folder-name enterprise name site
  name device device-name subscription subscription-name {
    status (active | suspended | hidden);
    activation (manual | automatically-on-login);
    activation-order activation-order ;
    substitution [ substitution... ];
  }
}

```

To configure a subscription to a service:

1. From configuration mode, enter the subscription configuration. In this procedure, peter is the name of the subscriber and Video-Gold is the name of the subscription.

```

user@host# edit subscribers retailer default subscriber-folder local subscriber
peter subscription Video-Gold

```

2. (Optional) Configure the status of the service subscription.

```
[edit subscribers retailer default subscriber-folder local subscriber peter
subscription Video-Gold]
user@host# set status (active | suspended | hidden)
```

3. (Optional) Specify how the service is activated.

```
[edit subscribers retailer default subscriber-folder local subscriber peter
subscription Video-Gold]
user@host# set activation (manual | automatically-on-login)
```

4. (Optional) Specify when the SAE should activate this subscription relative to the subscriber's other subscriptions that are configured to activate on login.

```
[edit subscribers retailer default subscriber-folder local subscriber peter
subscription Video-Gold]
user@host# set activation-order activation-order
```

5. (Optional) Configure the actual values for parameters associated with this subscription.

```
[edit subscribers retailer default subscriber-folder local subscriber peter
subscription Video-Gold]
user@host# set substitution [ substitution... ]
```

6. (Optional) Verify your configuration.

```
[edit subscribers retailer default subscriber-folder local subscriber
peter subscription Video-Gold]
user@host# show
status active;
activation manual;
```

