

Viewing Information about Action Congestion Points in a Backbone Network by Service

Purpose View information about action congestion points in a backbone network by service.

Action To view information about action congestion points in a backbone network by service:

- 1. Click **ACP > Backbone > Service**.

The Backbone/Service pane appears.

Monitor

Configure

Diagnose

Manage

Logged in as: admin

Refresh

Preferences

About

Logout

ACP

CLI

Component

Date

Disk

Interfaces...

Iptables...

JPS

NIC

NTP

Redirect Server

Route...

SAE

Security

System

ACP

Backbone / Service

Interface Alias	<input type="text"/>	Interface alias used by backbone service to generate congestion points. Value: Interface alias Default: No value
Interface Description	<input type="text"/>	Description of interface used by backbone service to generate congestion points. Value: Interface description Default: No value
Interface Name	<input type="text"/>	Name of interface related to congestion points. Value: Interface name Default: No value
Nas Port Id	<input type="text"/>	Interface NAS port ID used by backbone service to generate congestion points. Value: NAS port ID Default: No value
Service Name	<input type="text"/>	Name of service used by backbone service to generate congestion points. Value: Service name Default: No value
Slot	<input type="text"/>	Number of the slot for which you want to configure values. Value: Currently, the chassis has only one slot. The valid value is 0. Default value: 0
Style	<div><div></div></div>	Output style. Choices: brief: Display backbone service attributes Default value: detail
Virtual Router Name	<input type="text"/>	Name of virtual router from which to list backbone services. Value: Virtual router name Default: No value

OK

Reset

- 2. In the Interface Alias box, enter the interface alias used by the backbone service to generate congestion points, or leave the box empty to display information about all interfaces.
- 3. In the Interface Description box, enter the interface description used by the backbone service to generate congestion points, or leave the box empty to display information about all interfaces.
- 4. In the Interface Name box, enter the name of an interface to display information about one interface related to congestion points, or leave the box empty to display information about all interfaces.
- 5. In the NAS Port ID box, enter the NAS port ID used by the backbone service to generate congestion points, or leave the box empty to display information about all interfaces.
- 6. In the Service Name box, enter the name of a service to display information about one service, or leave the box empty to display information about all services.
- 7. In the Slot box, enter the number of the slot for which you want to display congestion point information.
- 8. Select an output style from the Style list.

9. In the Virtual Router Name box, enter a virtual router name to display information about a specific virtual router, or leave the box empty to display information about all virtual routers.
10. Click **OK**.

The Backbone/Service pane displays a list of congestion points.