

## Example: SRC User Accounts

---

The following example shows the configuration for user accounts for three system users and the template user “remote.” All users use one of the default system login classes.

```
system login user philip {
    class super-user;
    full-name " Philip of Macedonia" ;
    uid 1001;
    authentication {
    }
    ssh-authorized-keys [ "ssh-rsa AAAAB3NzaC1yc2EAAAABIwAA
        IEAvSqAWNMTQJS9eqG1eq
        RANI3ML4hH+u7WX/HPOW82gDSPpjghnt1e5de3D8UkulIEUB
        f1obgy/7AKc98FqAlvVp5onCiMg8ELD6
        RYkgOgo7U6zERB25qy3sK1Rn9NzrB20qLzbvAcZW1NlePmf
        1R99d/Rge7kB/5k6fq3NOG0fc= id@server" "ssh-rsa AAAAB3NzaC1yc2EA
        AAABlwAAAIEAxIwe9HfZ78vdbfq1+AY0uCF79yGPxgGuw
        GZd9QVdT+dnwGh/4HwLITvKd8SYrhMJsyz5dWuZm94JSwQ
        osm9BVhJwREt39NYIkLWOjGIMkk8Cw4
        TkPfflz1cSbeFxtFBFVaBbo4YkEv5ItbuxwvTWURkvsQa2VJXA
        qls7z8= id2@server2
        erian" "ssh-rsa AAAAB3NzaC1yc2EAAAABIwAAAIEAwOoUD4
        m+SazgzF2kRlq5Y2+lx2zQbCqxBS
        D1rmW92eLPOQIBv/sEy2d8UNeHpoKot9Px8q9ABriOyONc7v
        qNsSVnAMyicQB786uHoabSERVIYscapT
        YvIGg+olbdhKySbSxOoXMehhgoQSOJZxHCbxsQJip7/7vJPCjRG
        U8Xq0= id@server3" ];
    user alexander {
        full-name " Alexander the Great" ;
        uid 1002;
        class view;
        authentication {
        }
        ssh-authorized-keys [ "ssh-rsa
            AAAAB3NzaC1yc2EAAAABIwAAAIEAvSqAWNMTQJS9eqG1eq
            RANI3ML4hH+u7WX/HPOW82gDSPpjghnt1e5de3D8UkulIEUBf1obgy
            /7AKc98FqAlvVp5onCiMg8ELD6
            RYkgOgo7U6zERB25qy3sK1Rn9NzrB20qLzbvAcZW1NlePmf1R99d
            /Rge7kB/5k6fq3NOG0fc= id@server" "ssh-rsa
            AAAAB3NzaC1yc2EAAAABIwAAAIEAxIwe9HfZ78vdbfq1+AY0uCF79y
            GPxgGuw
            GZd9QVdT+dnwGh/4HwLITvKd8SYrhMJsyz5dWuZm94JSwQosm9
            BVhJwREt39NYIkLWOjGIMkk8Cw4
            TkPfflz1cSbeFxtFBFVaBbo4YkEv5ItbuxwvTWURkvsQa2VJXA
            qls7z8= id2@server2
            erian" "ssh-rsa AAAAB3NzaC1yc2EAAAABIwAAAIEAwOoUD4m+Sazgz
            F2kRlq5Y2+lx2zQbCqxBS
            D1rmW92eLPOQIBv/sEy2d8UNeHpoKot9Px8q9ABriOyONc7vqNsS
            VnAMyicQB786uHoabSERVIYscapT
            YvIGg+olbdhKySbSxOoXMehhgoQSOJZxHCbxsQJip7/7vJPCjRGU
            8Xq0= id@server3" ];
        user darius {
            full-name " Darius King of Persia" ;
```

```
uid 1003;
class operator;
authentication {
    ssh " 1024 37 12341234@ecbatana.per" ;
}
}
user remote {
    full-name " All remote users" ;
    uid 9999;
    class read-only;
}
```

- Related Topics**
- Overview of SRC User Accounts
  - Login Classes for SRC User Accounts
  - Types of Authentication for SRC User Accounts
  - Configuring Authentication for SRC User Accounts
  - Viewing Information About the Users on the System