

Configuring Local Properties for SRC-ACP (C-Web Interface)

To configure the local properties for SRC-ACP:

1. Configuring Basic Local Properties for SRC-ACP on page 1
2. Configuring Initial Properties for SRC-ACP on page 1
3. Configuring Directory Connection Properties for SRC-ACP on page 1
4. Configuring Initial Directory Eventing Properties for SRC-ACP on page 1

Configuring Basic Local Properties for SRC-ACP

To configure basic local properties:

1. Click **Configure > Slot > Slot:0 > ACP**.
2. Enter information as described in the Help text in the main pane, and click **Apply**.

Configuring Initial Properties for SRC-ACP

To configure initial properties for SRC-ACP:

1. Click **Configure > Slot > Slot:0 > ACP > Initial**.
2. If desired, specify the properties for ACP as described in the Help text in the main pane, and click **Apply**.

Configuring Directory Connection Properties for SRC-ACP

To configure directory connection properties:

1. Click **Configure > Slot > Slot:0 > ACP > Initial > Directory Connection**.

The Directory Connection pane appears.

2. Enter information as described in the Help text in the main pane, and click **Apply**.

Configuring Initial Directory Eventing Properties for SRC-ACP

To configure initial directory eventing properties:

1. Click **Configure > Slot > Slot:0 > ACP > Initial > Directory Eventing**.

The Directory Eventing pane appears.

2. Enter information as described in the Help text in the main pane, and click **Apply**.

