

Loading Sample Data in to a Juniper Networks Database with the C-Web Interface

The SRC software provides sample data that you can load into the Juniper Networks database. Typically, this data is used for testing or for demonstration purposes. You can load sample data for:

- Enterprise service portals
- SNMP traps for the SNMP agent
- Sample applications:
 - Dynamic Service Activator application (in the SRC Application Library)
 - Intrusion Detection and Prevention (IDP) integration application (unsupported sample application in the SRC Application Library)
 - Instant Virtual Extremity (IVE) Host Checker integration application (unsupported sample application in the SRC Application Library)
 - Traffic-Mirroring Application (unsupported sample application in the SRC Application Library)
 - Sample residential portal (unsupported sample application in the SRC Application Library)
 - Equipment registration mode
 - Internet service provider (ISP) mode

Loading sample data is not required to run the SRC software.

To load sample data from the C-Web interface:

1. Click **Manage > Request > System > LDAP > Load**.

The Load page appears.

2. In the Data box, select the component for which to load sample data, and click **OK**.

Related Topics

- Loading Sample Data in to a Juniper Networks Database (SRC CLI)
- Updating Data on a Juniper Networks Database with the C-Web Interface
- Synchronizing Data on a Juniper Networks Database with the C-Web Interface
- Securing the Juniper Networks Database with the C-Web Interface

