

Configuring QoS Profile-Tracking Plug-Ins with the SRC CLI

Use the following configuration statements to configure the QoS profile tracking plug-in with the SRC CLI:

```
shared sae configuration plug-ins name name qos-profile-tracking {  
    threads threads ;  
    default-qos-profile default-qos-profile ;  
    separator separator ;  
    qos-profile-prefix qos-profile-prefix ;  
    service-selection-attribute service-selection-attribute ;  
    search-filter search-filter ;  
    invisible-qos-service invisible-qos-service ;  
    qos-profile-parameter-name qos-profile-parameter-name ;  
}
```

1. From configuration mode for the QoS profile tracking plug-in.

```
user@host# edit shared sae configuration plug-ins name QosTracking  
qos-profile-tracking
```

2. Configure the number of working threads that all QTP instances share when they process QTP events.

```
[edit shared sae configuration plug-ins name QosTracking qos-profile-tracking]  
user@host# set threads threads
```

3. Configure the name of the QoS profile that is attached to the interface when QoS services have been deactivated.

See Dynamically Managing QoS Profiles .

```
[edit shared sae configuration plug-ins name QosTracking qos-profile-tracking]  
user@host# set default-qos-profile default-qos-profile
```

4. Configure the character that is placed between QoS profile input values when the system concatenates the values during the process of creating QoS profile names.

```
[edit shared sae configuration plug-ins name QosTracking qos-profile-tracking]  
user@host# set separator separator
```

5. Configure the prefix added to the QoS service name as part of the process to determine the name of the QoS profile that needs to be attached to an interface for a particular service.

```
[edit shared sae configuration plug-ins name QosTracking qos-profile-tracking]  
user@host# set qos-profile-prefix qos-profile-prefix
```

6. Configure the name of the attribute in the service definition that you want the QTP to use as QoS profile input values.

```
[edit shared sae configuration plug-ins name QosTracking qos-profile-tracking]
```

```
user@host# set service-selection-attribute service-selection-attribute
```

7. Configure the search filter that the SAE uses to search service objects in the directory to find QoS services.

See Configuring Search Filters for QoS Profile-Tracking Plug-Ins

```
[edit shared sae configuration plug-ins name QosTracking qos-profile-tracking]  
user@host# set search-filter search-filter
```

8. Configure the name of the hidden QoS profile attachment service that the QTP uses to attach QoS profiles to and remove QoS profiles from a router interface.

```
[edit shared sae configuration plug-ins name QosTracking qos-profile-tracking]  
user@host# set invisible-qos-service invisible-qos-service
```

9. Configure the name of the variable parameter used in the QoS profile name field in the QoS profile attachment action of the policy group that is assigned to the hidden QoS service.

```
[edit shared sae configuration plug-ins name QosTracking qos-profile-tracking]  
user@host# set qos-profile-parameter-name qos-profile-parameter-name
```

10. Verify your configuration.

```
[edit shared sae configuration plug-ins name QosTracking  
qos-profile-tracking]  
user@host# show  
threads 1;  
default-qos-profile ;  
separator -;  
qos-profile-prefix qos-profile;  
service-selection-attribute serviceName;  
search-filter (attribute.trackPlug=);  
invisible-qos-service svc-qos-attach;  
qos-profile-parameter-name qpName;
```

- Related Topics**
- Updating QoS Profile Data in the Directory
 - Query Fields
 - Examples: Searching for QoS Information
 - Overview of QoS on JUNOSe Routers